

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent
Kind Code
Date of Patent
Inventor(s)

12404732
B2
September 02, 2025
Kibbe; Charles G. et al.

Trapdoor-style drilling mud screen system and methods thereof

Abstract

A trapdoor-style drilling mud screen system, comprising a first body having a first portion, a second portion and a third portion, a first drilling mud inlet at a first end of the first portion of the first body, a first drilling mud outlet at a second end of the third portion of the first body, a rotating trapdoor subassembly, wherein the rotating trapdoor subassembly is disposed within the second portion of the first body, wherein the first portion of the first body is fluidly connected to a first end of the rotating subassembly, and wherein a second end of the rotating subassembly is fluidly connected to the third portion of the first body, a pivot subassembly, wherein the pivot subassembly is disposed through the rotating trapdoor subassembly and through the second portion of the first body; and a drilling mud screen, wherein the drilling mud screen is disposed within the rotating trapdoor subassembly between the first drilling mud inlet and the first drilling mud outlet. Methods of installing and using the drilling mud screen system are also disclosed.

Inventors: Kibbe; Charles G. (New Iberia, LA), Robin; Ross J. (New Iberia, LA)

Applicant: Black Diamond Oilfield Rentals LLC (Houston, TX)

Family ID: 85286606

Assignee: Black Diamond Oilfield Rentals LLC (Houston, TX)

Appl. No.: 17/984193

Filed: November 09, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230063617 A1	Mar. 02, 2023

Related U.S. Application Data

continuation-in-part parent-doc US 17126415 20201218 US 11802453 child-doc US 17984193
continuation-in-part parent-doc US 15959070 20180420 US 11028656 child-doc US 17126415

Publication Classification

Int. Cl.: E21B21/06 (20060101); E21B19/16 (20060101); E21B21/08 (20060101); E21B21/10 (20060101)

U.S. Cl.:

CPC E21B21/065 (20130101); E21B19/16 (20130101); E21B21/08 (20130101); E21B21/106 (20130101);

Field of Classification Search

CPC: E21B (21/08); E21B (19/16); E21B (21/065); E21B (21/10); E21B (21/12); E21B (21/106)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4226726	12/1979	Rehm	N/A	N/A
4421170	12/1982	Swift et al.	N/A	N/A
6263969	12/2000	Stoesz et al.	N/A	N/A
6517125	12/2002	Brisco	N/A	N/A
6598685	12/2002	Mashburn	N/A	N/A
6782952	12/2003	Garay et al.	N/A	N/A
6976546	12/2004	Herst	N/A	N/A
7243740	12/2006	Frith	N/A	N/A
7913760	12/2010	Robichaux et al.	N/A	N/A
8127867	12/2011	Droke	N/A	N/A
8381808	12/2012	Rogers et al.	N/A	N/A
8695715	12/2013	Rogers et al.	N/A	N/A
9151124	12/2014	Iblings et al.	N/A	N/A
9353605	12/2015	Hailey et al.	N/A	N/A
9598919	12/2016	Cantrell et al.	N/A	N/A
9624727	12/2016	Hutton	N/A	N/A
9677361	12/2016	Patterson	N/A	N/A
10280719	12/2018	O'Neal	N/A	N/A
10323484	12/2018	Liess	N/A	N/A
10415352	12/2018	Thomas et al.	N/A	N/A
10557323	12/2019	Pope	N/A	N/A
11802453	12/2022	Comeaux	N/A	E21B 21/10
2003/0136584	12/2002	Risher et al.	N/A	N/A
2003/0150616	12/2002	Mashburn	N/A	N/A
2004/0079551	12/2003	Herst	N/A	N/A
2006/0065443	12/2005	Hall et al.	N/A	N/A
2008/0087433	12/2007	Mashburn et al.	N/A	N/A

2013/0306304	12/2012	Cherewyk et al.	N/A	N/A
2015/0101804	12/2014	Vu	N/A	N/A
2015/0198016	12/2014	Langlais	N/A	N/A
2015/0267511	12/2014	Patterson	N/A	N/A
2016/0327191	12/2015	Walker et al.	N/A	N/A
2017/0058644	12/2016	Andreychuk et al.	N/A	N/A
2018/0128067	12/2017	Gao et al.	N/A	N/A
2018/0135371	12/2017	Cherewyk	N/A	N/A
2018/0258721	12/2017	Pawar et al.	N/A	N/A
2018/0306000	12/2017	Deboer	N/A	N/A
2018/0313178	12/2017	Biggerstaff et al.	N/A	N/A
2019/0085663	12/2018	Thomas et al.	N/A	N/A
2019/0106954	12/2018	Brown-Kerr et al.	N/A	N/A
2019/0112884	12/2018	Biggerstaff et al.	N/A	N/A
2019/0128454	12/2018	Chirko et al.	N/A	N/A
2019/0264546	12/2018	O'Neal	N/A	N/A

OTHER PUBLICATIONS

Final Office Action on U.S. Appl. No. 15/959,070 dated Aug. 26, 2020, 14 pages. cited by applicant

Final Office Action on U.S. Appl. No. 16/230,597 dated Jun. 2, 2020, 8 pages. cited by applicant
International Search Report and Written Opinion corresponding to PCT/US2018/029620, dated Aug. 30, 2018, 13 pages. cited by applicant

International Search Report and Written Opinion corresponding to PCT/US2020/059416, dated Feb. 4, 2021, 12 pages. cited by applicant

International Search Report and Written Opinion of PCT/US2020/059134, dated Mar. 10, 2021, 24 pages. cited by applicant

International Search Report and Written Opinion on PCT/US2020/058868 dated Mar. 10, 2021, 19 pages. cited by applicant

Non-Final Office Action on U.S. Appl. No. 15/959,070 dated Jun. 23, 2020, 18 pages. cited by applicant

Non-Final Office Action on U.S. Appl. No. 16/230,597 dated Nov. 17, 2020, 8 pages. cited by applicant

Non-Final Office Action on U.S. Appl. No. 17/010,678 dated Apr. 4, 2022, 13 pages. cited by applicant

Non-Final Office Action on U.S. Appl. No. 17/083,201 dated Jul. 28, 2022, 16 pages. cited by applicant

Non-Final Office Action on U.S. Appl. No. 17/123,401 dated Aug. 12, 2022, 25 pages. cited by applicant

Non-Final Office Action on U.S. Appl. No. 15/959,070 dated Apr. 20, 2020 (16 pages). cited by applicant

Non-Final Office Action on U.S. Appl. No. 16/230,597 dated Apr. 28, 2020 (7 pages). cited by applicant

Notice of Allowance on U.S. Appl. No. 15/959,070 dated Jan. 6, 2021, 6 pages. cited by applicant

Notice of Allowance on U.S. Appl. No. 16/230,597 dated Mar. 9, 2021, 5 pages. cited by applicant

US Office Action on U.S. Appl. No. 16/677,084 dated Mar. 23, 2021, 14 pages. cited by applicant

Background/Summary

PRIOR RELATED APPLICATIONS (1) This application is a continuation-in-part of U.S. Nonprovisional patent application Ser. No. 17/126,415 entitled “Valve-Style Drilling Mud Screen System and Methods Thereof,” filed on Dec. 18, 2020, which is a continuation-in-part of U.S. Nonprovisional patent application Ser. No. 15/959,070 entitled “Drilling Mud Screen System and Methods Thereof,” filed on Apr. 20, 2018, which claims the benefit of U.S. Provisional Patent Application Ser. No. 62/598,521 entitled “Improved Drilling Mud Screen System and Methods Thereof,” filed on Dec. 14, 2017, and U.S. Provisional Patent Application Ser. No. 62/491,700 entitled “Drilling Mud Screen System and Methods Thereof,” filed on Apr. 28, 2017. All of said priority applications are incorporated by references in their entirety.

FEDERALLY SPONSORED RESEARCH STATEMENT

(1) Not Applicable (N/A)

REFERENCE TO MICROFICHE APPENDIX

(2) N/A

FIELD OF INVENTION

(3) The present invention relates generally to an improved drilling mud screen system and methods thereof and, more particularly, to an improved drilling mud screen system with a drilling mud screen puller/installer tool and methods thereof.

BACKGROUND OF THE INVENTION

(4) Many drilling rigs use drill pipe mud screens that are in-line with the drilling assembly. Typically, drilling mud screens, commonly Type 3 drilling mud screens, are installed on the drill floor or at the bottom of the drill string. If the drilling mud screen is installed on the drill floor, the drilling mud screen must be reinstalled or replaced every time a section of stand pipe is added to the drill string. In other words, the drilling mud screens must be installed at the top of each 90-foot stand of pipe above the rig crew. As each stand of drill pipe is drilled down to the derrick floor, the top drive sub-connection is separated from the drill pipe stand connection and the drilling mud screen is installed to the top of the next stand of pipe going in the hole. This is a dangerous practice that can result in accidents to the crew below.

(5) Although the Type 3 drilling mud screen appears to work for single-shoulder API rotary shouldered connection types, it does not work for proprietary double-shoulder high-strength connection types that eliminate the space where the drilling mud screen is typically located inside the pipe. Instead, the nose of the double-shoulder pin connection on the top of the drive sub-connection is decreased to the exact width of the drilling mud screen flange, so that “theoretically” the nose of the double-shoulder pin connection may have the same contact inside the mating drill pipe box and same shoulder bearing stress at optimal connection make-up torque as it would in an unmodified assembly. Further, the dimensions of the shortened nose of the double-shoulder pin may not be adequate for the selected drilling mud screen flange. When the dimensions of the shortened nose of the double-shoulder pin are outside the acceptable connection tolerances of about ± 0.000 -inch to about ± 0.0010 -inch, the mating pin and/or box is damaged. Further, rig crews often forget to install the drilling mud screen. This oversight frequently results in damage as the shortened nose of the double-shoulder pin continuously tries to make-up inside the box but fails. These are dangerous practices that can result in drilling mud leaking onto the drilling rig floor creating a slip hazard and/or in a double-shoulder connection failure. Further, this is an expensive practice that rapidly consumes drilling mud screens long before they need to be replaced.

(6) If the drilling mud screen is installed at the bottom of the drill string, the drilling mud screen

must be brought to the surface to be replaced. This is an inefficient practice that can result in lost drilling time.

(7) Thus, an improved drilling mud screen system with a drilling mud screen puller/installer tool is needed to eliminate these problems.

SUMMARY OF THE INVENTION

(8) In an embodiment, a drilling mud screen system comprises a first body having a first drilling mud inlet, an optional first drilling mud inlet, a first drilling mud outlet and a drilling mud screen access port, an optional drilling mud screen insert, a drilling mud screen, and a first end cap.

(9) In an embodiment, the first body has a first end, a second end and a first centerline from the first end to the second end.

(10) In an embodiment, the first drilling mud inlet has a second centerline forming a first angle with the first centerline and extending to the first centerline, wherein the first drilling mud inlet is offset from the first end of the first body. In an embodiment, the first angle is from about 20-degrees to about 120-degrees.

(11) In an embodiment, the optional first drilling mud inlet has an optional second centerline forming an optional first angle with the first centerline and extending to the first centerline and forming an optional second angle with the second centerline, wherein the optional first drilling mud inlet is offset from the first end of the first body and wherein the optional first drilling mud inlet is offset from the second centerline radially about the first centerline. In an embodiment, the optional first angle is from about 20-degrees to about 120-degrees.

(12) In an embodiment, the first drilling mud outlet is at the second end of the first body.

(13) In an embodiment, the drilling mud screen access port is at the first end of the first body. In an embodiment, the first end cap is disposed within the drilling mud access port to close and seal the drilling mud access port.

(14) In an embodiment, the drilling mud screen is disposed within the first body between the first drilling mud inlet and the first drilling mud outlet.

(15) In an embodiment, the drilling mud screen comprises a second body having a second drilling mud inlet, a second drilling mud outlet, a second end cap and a filter.

(16) In an embodiment, the drilling mud screen is constructed from AISI 4145 or equivalent, stainless steel or combinations thereof. In an embodiment, the filter has a hardened coating.

(17) In an embodiment, the optional drilling mud screen insert is disposed within the first body between the first drilling mud inlet and the drilling mud screen.

(18) In an embodiment, the second body has a first end and a second end, wherein the first end and/or the second end of the body has a means to engage a drilling mud screen puller/installer tool.

(19) In an embodiment, the second drilling mud inlet is at the first end of the second body.

(20) In an embodiment, the filter has a first end, a second end, and openings, wherein the filter is fluidly connected to the second end of the second body via a first connection and/or an optional first end retaining ring. In an embodiment, the filter is straight or tapered from the first end to the second end of the filter. In an embodiment, the filter is tapered from the first end to the second end of the filter.

(21) In an embodiment, the filter comprises a plurality of rods having a first end and a second end, wherein the rods are spaced a distance apart to form the openings in the filter. In an embodiment, the rods are tapered from the first end to the second end of the filter.

(22) In an embodiment, the filter comprises a formed sheet having drilled holes or slots spaced a distance apart to form the openings in the filter. In an embodiment, the drilled holes or slots are drilled in any configuration and orientation from the first end to the second end of the filter. In an embodiment, the drilled holes or slots are drilled in offset rows or straight rows from the first end to the second end of the filter.

(23) In an embodiment, the second drilling mud outlet is at the openings of the filter.

(24) In an embodiment, the second end cap is fluidly connected at the second end of the filter via a

second connection. In an embodiment, the filter has an optional retaining ring disposed between the first connection and the second connection.

(25) In an embodiment, the first body comprises a third body and a fourth body, and wherein the third body is fluidly connected to the fourth body via a union.

(26) In an embodiment, one or more of the first body, the second body, the third body and the fourth body are constructed from AISI 4130/75k or equivalent material, AISI 4145 or equivalent, or combinations thereof.

(27) In an embodiment, the first body has a first portion and a second portion surrounding the filter, and wherein a second inner diameter of the second portion is larger than a first inner diameter of the first portion to provide a high flow rate of drilling mud through the filter.

(28) In an embodiment, the second end cap is a flat plate or a flat plate with holes or slots. In an embodiment, the second end cap is an inverted cone or an inverted cone with holes or slots.

(29) In an embodiment, the first centerline of the first body and an inner surface of the second end cap form a cap angle, wherein the cap angle is from about 30-degrees to about 60-degrees. In an embodiment, the first centerline of the first body and an inner surface of the second end cap form a cap angle, wherein the cap angle is from about 35-degrees to about 45-degrees.

(30) In an embodiment, a drilling mud screen system, comprises a first body having a first drilling mud inlet, a first drilling mud outlet and a drilling mud screen access port, a drilling mud screen, a plug and a first end cap.

(31) In an embodiment, the first body has a first end, a second end and a first centerline from the first end to the second end.

(32) In an embodiment, the first drilling mud inlet has a second centerline forming a first angle with the first centerline and extending to the first centerline, wherein the first drilling mud inlet is offset from the first end of the first body.

(33) In an embodiment, the first drilling mud outlet is at the second end of the first body.

(34) In an embodiment, the drilling mud screen access port is at the first end of the first body. In an embodiment, the first end cap is disposed within the drilling mud access port to close and seal the drilling mud access port.

(35) In an embodiment, the first end cap is disposed within the drilling mud access port to close and seal the drilling mud access port.

(36) In an embodiment, the plug is disposed within the first body between the drilling mud access port and the first drilling mud inlet.

(37) In an embodiment, the drilling mud screen is disposed within the first body between the first drilling mud inlet and the first drilling mud outlet.

(38) In an embodiment, the drilling mud screen comprises a second body having a second drilling mud inlet, a second drilling mud outlet, a second end cap and a filter.

(39) In an embodiment, the drilling mud screen is constructed from AISI 4145 or equivalent, stainless steel or combinations thereof. In an embodiment, the optional drilling mud screen insert, the optional first end retaining ring and/or the optional retaining ring is constructed from AISI 4145 or equivalent, stainless steel or combinations thereof and/or has a hardened coating. In an embodiment, the filter has a hardened coating.

(40) In an embodiment, the second body has a first end and a second end, wherein the first end and/or the second end of the body has a means to engage a drilling mud screen puller/installer tool.

(41) In an embodiment, the second drilling mud inlet is at the first end of the second body.

(42) In an embodiment, the filter has a first end, a second end, and openings, wherein the filter is fluidly connected to the second end of the second body. In an embodiment, the filter is straight or tapered from the first end to the second end of the filter. In an embodiment, the filter is tapered from the first end to the second end of the filter.

(43) In an embodiment, the filter comprises a plurality of rods having a first end and a second end, wherein the rods are spaced a distance apart to form the openings in the filter. In an embodiment,

the rods are tapered from the first end to the second end of the filter.

(44) In an embodiment, the filter comprises a formed sheet having drilled holes or slots spaced a distance apart to form the openings in the filter. In an embodiment, the drilled holes or slots are drilled in any configuration and orientation from the first end to the second end of the filter. In an embodiment, the drilled holes or slots are drilled in offset rows or straight rows from the first end to the second end of the filter.

(45) In an embodiment, the second drilling mud outlet is at the openings of the filter.

(46) In an embodiment, the end cap is fluidly connected at the second end of the filter.

(47) In an embodiment, the plug comprises a third body having a first end and a second end, wherein the first end of the third body has a means to engage a drilling mud screen puller/installer tool.

(48) In an embodiment, the first end of the third body has an optional cavity extending towards but not through the flow surface of the plug.

(49) In an embodiment, the third body has an optional port extending from an outer surface of the plug into the optional cavity.

(50) In an embodiment, the second end of the third body has a flow surface to direct the drilling mud from the first drilling mud inlet to the second drilling mud inlet. In an embodiment, the flow surface may be selected from the group consisting of a backwards “J” shape, a curved shape, an “L” shape and combinations and variations thereof.

(51) In an embodiment, one or more of the first body, the second body and the third body are constructed from AISI 4130/75k or equivalent material, AISI 4145 or equivalent, or combinations thereof.

(52) In an embodiment, the first body has a first portion and a second portion surrounding the filter, and wherein a second inner diameter of the second portion is larger than a first inner diameter of the first portion to provide a high flow rate of drilling mud through the filter.

(53) In an embodiment, the second end cap is a flat plate or a flat plate with holes or slots. In an embodiment, the second end cap is an inverted cone or an inverted cone with holes or slots.

(54) In an embodiment, the first centerline of the first body and an inner surface of the second end cap form a cap angle, wherein the cap angle is from about 30-degrees to about 60-degrees. In an embodiment, the first centerline of the first body and an inner surface of the second end cap form a cap angle, wherein the cap angle is from about 35-degrees to about 45-degrees.

(55) In an embodiment, the drilling mud screen system further comprises a transducer subassembly. In an embodiment, the transducer subassembly comprises a transducer body having a drilling mud inlet, a drilling mud outlet and a transducer access port, and a transducer.

(56) In an embodiment, the transducer body has a first end, a second end and a first centerline from the first end to the second end.

(57) In an embodiment, the drilling mud inlet is at the first end of the transducer body.

(58) In an embodiment, the first drilling mud outlet is at the second end of the transducer body.

(59) In an embodiment, the transducer access port has a second centerline forming a transducer angle with the first centerline and extending to the first centerline, wherein the transducer access port is offset from the first end of the transducer body. In an embodiment, the transducer angle is from about 20-degrees to about 120-degrees.

(60) In an embodiment, the transducer is disposed within the transducer access port to close and seal the transducer access port.

(61) In an embodiment, the drilling mud outlet of the transducer subassembly is fluidly connected to the first drilling mud inlet of the drilling mud screen system.

(62) In an embodiment, a drilling mud screen puller/installer tool comprises a hollow body, a striker plate, a shaft having a puller/installer plate and an optional stop plate, groove or painted line, a movable sleeve disposed around a portion of the shaft, and a handle.

(63) In an embodiment, the hollow body has a first end, a second end and a first length.

- (64) In an embodiment, the striker plate has a first end and a second end, wherein the first end of the striker plate is connected to the second end of the body via a first connection.
- (65) In an embodiment, the shaft has a first end, a second end and a second length, wherein the second end of the striker plate is connected to the first end of the shaft via a second connection.
- (66) In an embodiment, the puller/installer plate has a first end and a second end, wherein the second end of the shaft is connected to the first end of the puller/installer plate via a fourth connection. In an embodiment, the puller/installer plate has a means to engage a drilling mud screen. In an embodiment, the puller/installer plate has one or more extensions to fit an outlet of a first portion and/or an inlet of a second portion of the body of the drilling mud screen and to rotationally engage a shoulder inside the inlet of the second portion of the body of the drilling mud screen.
- (67) In an embodiment, the optional stop plate, groove or painted line on the shaft is offset from the first end of the body or the second end of the body. In an embodiment, the stop plate is connected to the shaft via a fifth connection.
- (68) In an embodiment, the movable sleeve has a first end, a second end and a third length, wherein the movable sleeve is disposed around a portion of the shaft.
- (69) In an embodiment, the handle is connected to the movable sleeve via a third connection.
- (70) In an embodiment, one or more of the first, second, third, fourth and fifth connections are welds.
- (71) In an embodiment, one or more of the body and the movable sleeve are constructed from AISI 4140 or equivalent, stainless steel or combinations thereof.
- (72) In an embodiment, one or more of the handle and the shaft are constructed from AISI 1018 or equivalent.
- (73) In an embodiment, one or more of the rounded end, the striker plate and the puller/installer plate are constructed from stainless steel.
- (74) In an embodiment, a method of installing a drilling mud screen system comprises a) providing a drilling mud screen system, b) stopping a drilling mud pump to fluidly connect the drilling mud screen to the drilling mud pump, c) fluidly connecting the drilling mud screen system in line with and immediately upstream or downstream of the drilling mud pump; and d) operating the drilling mud pump to produce flow of drilling mud through the drilling mud screen system.
- (75) In an embodiment, step c) comprises fluidly connecting a drilling mud inlet of the drilling mud screen system to a high-pressure outlet of the drilling mud pump and fluidly connecting a drilling mud outlet of the drilling mud screen system to a vibrator hose or a standpipe.
- (76) In an embodiment, step c) comprises fluidly connecting a drilling mud inlet of the drilling mud screen system to a high-pressure inlet of the drilling mud pump and fluidly connecting a drilling mud outlet of the drilling mud screen system to an inlet of a vibrator hose.
- (77) In an embodiment, step c) comprises fluidly connecting a drilling mud inlet of the drilling mud screen system to an outlet of a vibrator hose and a drilling mud outlet to an inlet of a standpipe.
- (78) In an embodiment, step c) comprises fluidly connecting a drilling mud inlet of the drilling mud screen system to an outlet of a first portion of a standpipe and a drilling mud outlet to an inlet of a second portion of the standpipe.
- (79) In an embodiment, step e) comprises filtering or screening debris from drilling mud.
- (80) In an embodiment, a method of installing and using a drilling mud screen system comprises a) providing the drilling mud screen system; b) stopping a drilling mud pump; c) fluidly connecting a first transducer subassembly, having a transducer, in line with and downstream of the drilling mud pump and fluidly connecting the drilling mud screen system in line with and immediately downstream of the first transducer subassembly; and d) operating the drilling mud pump to produce flow of drilling mud through the first transducer subassembly and the drilling mud screen system.
- (81) In an embodiment, the method further comprises step (f) monitoring the transducer of the first transducer subassembly for property information immediately upstream of the drilling mud screen

system and step (g) using the property information to determine a status of the drilling mud screen system.

(82) In an embodiment, step (c) comprises fluidly connecting a first transducer subassembly, having a transducer, in line with and downstream of the drilling mud pump and fluidly connecting the drilling mud screen system in line with and immediately downstream of the first transducer subassembly, and fluidly connecting a gate valve in line with and immediately downstream of the drilling mud screen system, fluidly connecting a second transducer subassembly, having a low torque plug valve, in line with and immediately downstream of the gate valve and wherein step (d) comprises operating the drilling mud pump to produce flow of drilling mud through the first transducer subassembly, the drilling mud screen system, the gate valve and the second transducer subassembly.

(83) In an embodiment, the method further comprises step (e) stopping the drilling mud pump, step (f) closing the gate valve to isolate the drilling mud screen system, and step (g) pumping cement through the low torque plug valve of the second transducer subassembly, a vibrator hose, a stand pipe, a top drive and a case running tool (CRT).

(84) In an embodiment, a method of removing and replacing a drilling mud screen comprises a) providing the drilling mud screen system; b) stopping a drilling mud pump connected to the drilling mud screen system; c) opening a drilling mud screen access port in the drilling mud screen system to remove and replace a drilling mud screen; d) accessing the interior of the drilling mud screen system to pull the plug from the drilling mud screen system; e) accessing the interior of the drilling mud screen system to pull the drilling mud screen from the drilling mud screen system and to install a replacement drilling mud screen into the drilling mud screen system; f) accessing the interior of the drilling mud screen system to reinstall the plug into the drilling mud screen system; g) closing the drilling mud screen access port in the drilling mud screen system; and h) operating the drilling mud pump to produce flow of drilling mud through the drilling mud screen system.

(85) In an embodiment, step d) comprises using a puller/installer plate and/or a rounded end of a puller/installer tool to engage and pull the plug from the drilling mud screen system. In an embodiment, step d) comprises using a puller/installer plate and/or a rounded end of a puller/installer tool to engage and pull the plug from the drilling mud screen system and, optionally using a stop plate, groove or painted line of the puller/installer tool to determine when the replacement drilling mud screen is installed into the drilling mud screen system.

(86) In an embodiment, step e) comprises using a puller/installer plate of a puller/installer tool to engage and pull the drilling mud screen from the drilling mud screen system. In an embodiment, step e) comprises using a puller/installer plate and/or a rounded end of a puller/installer tool to install the replacement drilling mud screen into the drilling mud screen system.

(87) In an embodiment, step f) comprises using a puller/installer plate and/or a rounded end of a puller/installer tool to reinstall the plug into the drilling mud screen system.

(88) In an embodiment, a valve-style drilling mud screen system comprises a first body, a first drilling mud inlet, a first drilling mud outlet, a rotating subassembly, a pivot subassembly and a drilling mud screen. In an embodiment, the first body has a first portion, a second portion and a third portion. In an embodiment, the first drilling mud inlet is at a first end of the first portion of the body. In an embodiment, the first drilling mud outlet is at a second end of the third portion of the body.

(89) In an embodiment, the rotating subassembly is disposed within the second portion of the first body. In an embodiment, the rotating subassembly has a first end and a second end. In an embodiment, the first portion of the first body is fluidly connected to the first end of the rotating subassembly. In an embodiment, the second end of the rotating subassembly is fluidly connected to the third portion of the first body.

(90) In an embodiment, the pivot subassembly is attached to the rotating subassembly through the second portion of the first body.

(91) In an embodiment, the drilling mud screen is disposed within the rotating subassembly between the first drilling mud inlet and the first drilling mud outlet.

(92) In an embodiment, the rotating subassembly comprises a second body, a third body and a fourth body. In an embodiment, the second body has a first end and a second end. In an embodiment, the third body has a first end and a second end. In an embodiment, the fourth body has a first end and a second end. In an embodiment, the first end of the second body is fluidly connected the second end of the first portion of the first body. In an embodiment, the second end of the second body is rotatably sealable against the first end of the third body. In an embodiment, the second end of the third body is rotatably sealable against the first end of the fourth body. In an embodiment, the second end of the fourth body is fluidly connected to a first end of the third portion of the first body.

(93) In an embodiment, the pivot subassembly comprises a first shaft stud, a second shaft stud and a pivot shaft. In an embodiment, the first shaft stud and/or the second shaft stud are attached to the rotating subassembly through the second portion of the first body. In an embodiment, the pivot shaft is attached to first shaft stud or the second shaft stud.

(94) In an embodiment, the pivot subassembly further comprises a pivot drive. In an embodiment, the pivot drive is attached to the pivot shaft.

(95) In an embodiment, the drilling mud screen system further comprises a camming seal separator capable of separating a first seal and/or a second seal. In an embodiment, the camming seal separator comprises a face-roller camming mechanism or a push-rod camming mechanism.

(96) In an embodiment, the camming seal separator comprises a first cam roller, a first cam bracket and a first cam track.

(97) In an embodiment, the first roller bracket is attached to a first end of a second body of the rotating subassembly. In an embodiment, the first cam roller is attached to the first roller bracket.

(98) In an embodiment, the first cam track is attached to a first end of a third body of the rotating subassembly. In an embodiment, the first cam track has a first recess portion to allow the second end of the second body of the rotating subassembly to close against the first end of the third body of the rotating subassembly.

(99) In an embodiment, the camming seal separator further comprises a second cam roller, a second roller bracket and a second cam track.

(100) In an embodiment, the second roller bracket is attached to the first end of a fourth body of the rotating subassembly. In an embodiment, the second cam roller is attached to the second roller bracket.

(101) In an embodiment, the second cam track is attached to the second end of the third body of the rotating subassembly. In an embodiment, the second cam track has a second recessed portion to allow the second end of the third body of the rotating subassembly to close against the first end of the fourth body of the rotating subassembly.

(102) In an embodiment, the camming seal separator comprises a first pivot pin, a first push rod, a first cam roller and a cam.

(103) In an embodiment, the first pivot pin has a first end and a second end. In an embodiment, the first end of the first pivot pin is attached to the second body of the rotating subassembly through the first portion of the first body.

(104) In an embodiment, the first push rod has a first end and a second end. In an embodiment, the first end of the first push rod is attached to the second end of the first pivot pin.

(105) In an embodiment, the first cam roller is attached to the second end of the first push rod.

(106) In an embodiment, the cam is attached to the pivot shaft. In an embodiment, the cam is sized and shaped such that the second end of the second body of the rotating subassembly closes against the first end of the third body of the rotating subassembly to form the first seal. In an embodiment, the cam is be sized and shaped such that the second end of the third body of the rotating subassembly closes against the first end of the fourth body of the rotating subassembly to form the

second seal.

(107) In an embodiment, the camming seal separator further comprises a second pivot pin, a second push rod, and a second cam roller.

(108) In an embodiment, the second pivot pin has a first end and a second end. In an embodiment, the first end of the second pivot pin is attached to the third body of the rotating subassembly through the third portion of the first body.

(109) In an embodiment, the second push rod has a first end and a second end. In an embodiment, the first end of the second push rod is attached to the second end of the second pivot pin.

(110) In an embodiment, the second cam roller is attached to the second end of the second push rod.

(111) In an embodiment, the camming seal separator further comprises a first guide block and a first spring.

(112) In an embodiment, the first push rod is disposed through the first guide block.

(113) In an embodiment, the first spring is disposed between the first push rod and the first guide block.

(114) In an embodiment, the camming seal separator further comprises a second guide block and a second spring.

(115) In an embodiment, the second push rod is disposed through the second guide block.

(116) In an embodiment, the second spring is disposed between the second push rod and the second guide block.

(117) In an embodiment, the first guide block and/or the second guide block are attached to the second portion of the first body.

(118) In an embodiment, the drilling mud screen comprises a second body, a filter, a first end cap, a second drilling mud inlet and a second drilling mud outlet.

(119) In an embodiment, the second body has a first end and a second end and a first centerline from the first end to the second end.

(120) In an embodiment, the filter has a first end, a second end, and openings. In an embodiment, the first end of the filter is fluidly connected to the first end of the second body via a first connection and/or an optional first end retaining ring.

(121) In an embodiment, the first end cap is fluidly connected at the second end of the filter via a second connection. In an embodiment, the filter has an optional retaining ring disposed between the first connection and the second connection.

(122) In an embodiment, the second drilling mud inlet is at the first end of the second body.

(123) In an embodiment, the second drilling mud outlet is at the openings of the filter.

(124) In an embodiment, one or more of the first body and the second body are constructed from AISI 4130/75k or equivalent material, AISI 4145 or equivalent, or combinations thereof. In an embodiment, one or more of the first body, and the second body are constructed from AISI 4130/75k or equivalent material, AISI 4145 or equivalent, or combinations thereof.

(125) In an embodiment, the filter comprises a plurality of rods having a first end and a second end. In an embodiment, the rods are spaced a distance apart to form the openings in the filter. In an embodiment, the rods are tapered from the first end to the second end.

(126) In an embodiment, the filter comprises a formed sheet having drilled holes or slots spaced a distance apart to form the openings in the filter. In an embodiment, the drilled holes or slots are drilled in offset rows or straight rows from the first end to the second end. In an embodiment, the filter is tapered from the second end to the first end.

(127) In an embodiment, the first end cap is a flat plate or a flat plate with holes or slots.

(128) In an embodiment, the first end cap is an inverted cone or an inverted cone with holes or slots.

(129) In an embodiment, the first centerline of the second body and an outer surface of the first end cap forms a cap angle. In an embodiment, the cap angle is from about 30-degrees to about 90-

degrees. In an embodiment, the cap angle is from about 35-degrees to about 45-degrees.

(130) In an embodiment, the filter, the first end retaining ring and/or the retaining ring are constructed from AISI 4145 or equivalent, stainless steel or combinations thereof.

(131) In an embodiment, the filter, the first end retaining ring and/or the retaining ring has a hardened coating. In an embodiment, one or more of the filter, the first end retaining ring and/or the retaining ring has a Carbide coating with about 6% Cobalt binder.

(132) In an embodiment, the drilling mud screen system further comprises a transducer subassembly. In an embodiment, the transducer subassembly comprises a transducer body having a drilling mud inlet, a drilling mud outlet and a transducer access port, and a transducer.

(133) In an embodiment, the transducer body has a first end, a second end and a first centerline from the first end to the second end.

(134) In an embodiment, the drilling mud inlet is at the first end of the transducer body.

(135) In an embodiment, the first drilling mud outlet is at the second end of the transducer body.

(136) In an embodiment, the transducer access port has a second centerline forming a transducer angle with the first centerline and extending to the first centerline, wherein the transducer access port is offset from the first end of the transducer body. In an embodiment, the transducer angle is from about 20-degrees to about 120-degrees.

(137) In an embodiment, the transducer is disposed within the transducer access port to close and seal the transducer access port.

(138) In an embodiment, the drilling mud outlet of the transducer subassembly is fluidly connected to the first drilling mud inlet of the drilling mud screen system.

(139) In an embodiment, the drilling mud outlet of the transducer subassembly is fluidly connected to the first drilling mud inlet of the drilling mud screen system via a cross-over connection.

(140) In an embodiment, a trapdoor-style drilling mud screen system, comprises a first body having a first portion, a second portion and a third portion, a first drilling mud inlet at a first end of the first portion of the first body, a first drilling mud outlet at a second end of the third portion of the first body, a rotating trapdoor subassembly, wherein the rotating trapdoor subassembly is disposed within the second portion of the first body, wherein the first portion of the first body is fluidly connected to a first end of the rotating subassembly, and wherein a second end of the rotating subassembly is fluidly connected to the third portion of the first body, a pivot subassembly, wherein the pivot subassembly is disposed through the rotating trapdoor subassembly and through the second portion of the first body, and a drilling mud screen, wherein the drilling mud screen is disposed within the rotating trapdoor subassembly between the first drilling mud inlet and the first drilling mud outlet.

(141) In an embodiment, the rotating trapdoor subassembly comprises a second body, wherein a first end of the second body is fluidly connected to a second end of the first portion of the first body and wherein a second end of the second body is fluidly connected to a first end of the third portion of the first body.

(142) In an embodiment, the pivot subassembly comprises a pivot shaft, and a retaining ring, wherein the retaining ring retains the pivot shaft through the second portion of the first body.

(143) In an embodiment, the first portion of the first body comprises a first piston.

(144) In an embodiment, the drilling mud screen system further comprises a piston guide bar disposed through the first portion of the first body and into a portion of the first piston, wherein the piston guide bar guides a second end of the first piston to engage a first end of the rotating trapdoor subassembly when the rotating trapdoor subassembly is in a closed position.

(145) In an embodiment, the drilling mud screen system further comprises a piston guide bar disposed through a first slot in the first portion of the first body or the second portion of the body, and into a second slot in the first piston, wherein the piston guide bar guides a second end of the first piston to engage a first end of the rotating trapdoor subassembly when the rotating trapdoor subassembly is in a closed position.

(146) In an embodiment, the drilling mud screen system further comprises a piston guide bar disposed through the first portion of the first body of the second portion of the body, and into a portion of the first piston, wherein the piston guide bar locks a second end of the first piston to contact and seal a first end of the rotating trapdoor subassembly when the rotating trapdoor subassembly is in a closed position.

(147) In an embodiment, the drilling mud screen system further comprises a piston guide bar disposed through a first slot in the first portion of the first body and into a second slot of the first piston, wherein the piston guide bar locks a second end of the first piston to contact and seal a first end of the rotating trapdoor subassembly when the rotating trapdoor subassembly is in a closed position.

(148) In an embodiment, the drilling mud screen system further comprises a piston guide bar disposed through the first portion of the first body and into a portion of the first piston, wherein the piston guide bar guides a second end of the first piston to disengage from a first end of the rotating trapdoor subassembly when the rotating trapdoor subassembly is in an open position.

(149) In an embodiment, the drilling mud screen system further comprises a piston guide bar disposed through the first portion of the first body and into a portion of the first piston, wherein the piston guide bar separates a second end of the first piston to disengage and create a gap from a first end of the rotating trapdoor subassembly when the rotating trapdoor subassembly is in the open position to avoid damage to a first seal face at the second end of the first piston and/or the second seal face at the first end of the rotating trapdoor subassembly

(150) In an embodiment, the piston guide bar further comprises a ball bearing for smooth operation.

(151) In an embodiment, the drilling mud screen system further comprises a first spring, wherein the first spring is disposed between the first piston and a first subassembly, wherein the first subassembly comprises a second body having a first end and a second end, a second drilling mud inlet at the first end of the second body, and a second drilling mud outlet at the second end of the second body, wherein the second end of the second body is fluidly connected to the first end of the first portion of the first body.

(152) In an embodiment, the second end of the first piston has a first seal face and wherein the first end of the rotating trapdoor subassembly has a second seal face.

(153) In an embodiment, the third portion of the first body comprises a second piston.

(154) In an embodiment, the drilling mud screen system of further comprises a second spring, wherein the second spring is disposed between the second piston and a second subassembly, wherein the second subassembly comprises a third body having a first end and a second end, a third drilling mud inlet at the first end of the third body, a third drilling mud outlet at the second end of the third body, wherein the second end of the third portion of the first body is fluidly connected to the first end of the third body.

(155) In an embodiment, the second end of the rotating trapdoor subassembly has a third seal face and wherein the first end of the second piston has a fourth seal face.

(156) In an embodiment, the drilling mud screen system further comprises a threaded lock ring, wherein the threaded lock ring is disposed around the first portion of the first body and the first end of the trapdoor subassembly.

(157) In an embodiment, the drilling mud screen system further comprises a threaded lock ring, wherein the threaded lock ring is disposed around a first portion of the body and a first end of the rotating trapdoor subassembly to lock the trapdoor subassembly in a closed position.

(158) In an embodiment, the threaded lock ring further comprises a handle.

(159) In an embodiment, the drilling mud screen comprises a third body having a first end and a second end and a first centerline, a filter having a first end, a second end, and openings, wherein the first end of the filter is fluidly connected to the first end of the second body via a first connection and/or an optional first end retaining ring, an end cap fluidly connected at the second end of the

filter via a second connection, wherein the filter has an optional retaining ring disposed between the first connection and the second connection, a second drilling mud inlet at the first end of the second body, and a second drilling mud outlet at the openings of the filter.

(160) In an embodiment, the filter comprises a plurality of rods having a first end and a second end, wherein each of the plurality of rods are spaced a distance apart to form the openings in the filter. In an embodiment, each of the plurality of rods are tapered from the first end to the second end.

(161) In an embodiment, the filter comprises a formed sheet having drilled holes or slots spaced a distance apart to form the openings in the filter. In an embodiment, the drilled holes or slots are drilled in offset rows or straight rows from the first end to the second end.

(162) In an embodiment, the filter is tapered from the first end to the second end.

(163) In an embodiment, the end cap is a flat plate or a flat plate with holes or slots.

(164) In an embodiment, the end cap is an inverted cone or an inverted cone with holes or slots. In an embodiment, the first centerline of the second body and an outer surface of the end cap forms a cap angle, wherein the cap angle is from about 30-degrees to about 90-degrees. In an embodiment, the first centerline of the second body and an outer surface of the end cap forms a cap angle, wherein the cap angle is from about 35-degrees to about 45-degrees.

(165) In an embodiment, the filter, the first end retaining ring and/or the retaining ring are constructed from AISI 4145 or equivalent, stainless steel or combinations thereof.

(166) In an embodiment, the filter, the first end retaining ring and/or the retaining ring has a hardened coating. In an embodiment, one or more of the filter, the first end retaining ring and/or the retaining ring has a Carbide coating with about 6% Cobalt binder.

(167) In an embodiment, one or more of the first body, the second body and the third body are constructed from AISI 4130/75k or equivalent material, AISI 4145 or equivalent, or combinations thereof.

(168) In an embodiment, the drilling mud screen comprises a third body having a first end and a second end and a first centerline, a filter having a first end and a second end, and openings, wherein the second end of the filter is fluidly connected to the first end of the second body via a first connection and/or an optional second end retaining ring, an end cap fluidly connected at the first end of the filter via a second connection, wherein the filter has an optional retaining ring disposed between the first connection and the second connection, a second drilling mud inlet at the openings of the filter, and a second drilling mud outlet at the second end of the second body.

(169) In an embodiment, the filter comprises a plurality of rods having a first end and a second end, wherein each of the plurality of rods are spaced a distance apart to form the openings in the filter. In an embodiment, each of the plurality of rods are tapered from the first end to the second end.

(170) In an embodiment, the filter comprises a formed sheet having drilled holes or slots spaced a distance apart to form the openings in the filter. In an embodiment, the drilled holes or slots are drilled in offset rows or straight rows from the first end to the second end.

(171) In an embodiment, the filter is tapered from the second end to the first end.

(172) In an embodiment, the end cap is a flat plate or a flat plate with holes or slots.

(173) In an embodiment, the end cap is a cone or a cone with holes or slots. In an embodiment, the first centerline of the second body and an outer surface of the end cap forms a cap angle, wherein the cap angle is from about 30-degrees to about 90-degrees. In an embodiment, the first centerline of the second body and an outer surface of the end cap forms a cap angle, wherein the cap angle is from about 35-degrees to about 45-degrees.

(174) In an embodiment, the filter, the first end retaining ring and/or the retaining ring are constructed from AISI 4145 or equivalent, stainless steel or combinations thereof.

(175) In an embodiment, the filter, the first end retaining ring and/or the retaining ring has a hardened coating. In an embodiment, one or more of the filter, the first end retaining ring and/or the retaining ring has a Carbide coating with about 6% Cobalt binder.

(176) In an embodiment, one or more of the first body, the second body and the third body are

constructed from AISI 4130/75k or equivalent material, AISI 4145 or equivalent, or combinations thereof.

(177) In an embodiment, a method of installing a drilling mud screen system comprises (a) stopping a drilling mud pump to fluidly connect the valve-style drilling mud screen system as disclosed herein to the drilling mud pump, (b) fluidly connecting the drilling mud screen system in line with and immediately upstream or downstream of the drilling mud pump, and (c) operating the drilling mud pump to produce flow of drilling mud through the drilling mud screen system.

(178) In an embodiment, step b) comprises fluidly connecting a drilling mud inlet of the drilling mud screen system to a high-pressure outlet of the drilling mud pump and fluidly connecting a drilling mud outlet of the drilling mud screen system to a vibrator hose or a standpipe.

(179) In an embodiment, step b) comprises fluidly connecting a drilling mud inlet of the drilling mud screen system to a high-pressure inlet of the drilling mud pump and fluidly connecting a drilling mud outlet of the drilling mud screen system to an inlet of a vibrator hose.

(180) In an embodiment, step b) comprises fluidly connecting a drilling mud inlet of the drilling mud screen system to an outlet of a vibrator hose and a drilling mud outlet to an inlet of a standpipe.

(181) In an embodiment, step b) comprises fluidly connecting a drilling mud inlet of the drilling mud screen system to an outlet of a first portion of a standpipe and a drilling mud outlet of the drilling mud screen system to an inlet of a second portion of the standpipe.

(182) In an embodiment, the method further comprises step d) filtering or screening debris from drilling mud.

(183) In an embodiment, a method of removing and replacing a drilling mud screen comprises (a) stopping a drilling mud pump connected to the valve-style drilling mud screen system as disclosed herein, (b) rotating a rotating subassembly to open the drilling mud screen system, (c) installing a replacement drilling mud screen, (d) rotating the rotating subassembly to close and seal the drilling mud screen system, and (e) operating the drilling mud pump to produce flow of drilling mud through the drilling mud screen system.

(184) In an embodiment, a method of installing a drilling mud screen system comprises (a) stopping a drilling mud pump, (b) fluidly connecting a first transducer subassembly, having a first transducer, in line with and downstream of the drilling mud pump and fluidly connecting the valve-style drilling mud screen system as disclosed herein in line with and immediately downstream of the first transducer subassembly and (c) operating the drilling mud pump to produce flow of drilling mud through the first transducer subassembly and the drilling mud screen system.

(185) In an embodiment, the method further comprises step (d) monitoring the first transducer of the first transducer subassembly for property information immediately upstream of the drilling mud screen system. In an embodiment, the method further comprises step (e) using the property information to determine a status of the drilling mud screen system.

(186) In an embodiment, step (b) comprises (b-1) fluidly connecting the first transducer subassembly, having the first transducer, in line with and downstream of the drilling mud pump and fluidly connecting the valve-style drilling mud screen system as disclosed herein in line with and immediately downstream of the first transducer subassembly, (b-2) fluidly connecting a gate valve in line with and immediately downstream of the drilling mud screen system, and (b-3) fluidly connecting a second transducer subassembly, having a low torque plug valve, in line with and immediately downstream of the gate valve.

(187) In an embodiment, step (c) comprises operating the drilling mud pump to produce flow of drilling mud through the first transducer subassembly, the drilling mud screen system, the gate valve and the second transducer subassembly.

(188) In an embodiment, the method further comprises step (d) stopping the drilling mud pump, step (e) closing the gate valve to isolate the drilling mud screen system, and step (f) pumping cement through the low torque plug valve of the second transducer subassembly, a vibrator hose, a

stand pipe, a top drive and a case running tool (CRT).

(189) In an embodiment, a method of installing a trapdoor-style drilling mud screen system comprises a) stopping a drilling mud pump to fluidly connect the drilling mud screen system as disclosed herein to the drilling mud pump, b) fluidly connecting the drilling mud screen system in line with and immediately upstream or downstream of the drilling mud pump; and c) operating the drilling mud pump to produce flow of drilling mud through the drilling mud screen system.

(190) In an embodiment, step b) comprises fluidly connecting a drilling mud inlet of the drilling mud screen system to a high-pressure outlet of the drilling mud pump and fluidly connecting a drilling mud outlet of the drilling mud screen system to a vibrator hose or a standpipe.

(191) In an embodiment, step b) comprises fluidly connecting a drilling mud inlet of the drilling mud screen system to a high-pressure inlet of the drilling mud pump and fluidly connecting a drilling mud outlet of the drilling mud screen system to an inlet of a vibrator hose.

(192) In an embodiment, step b) comprises fluidly connecting a drilling mud inlet of the drilling mud screen system to an outlet of a vibrator hose and a drilling mud outlet to an inlet of a standpipe.

(193) In an embodiment, step b) comprises fluidly connecting a drilling mud inlet of the drilling mud screen system to an outlet of a first portion of a standpipe and a drilling mud outlet of the drilling mud screen system to an inlet of a second portion of the standpipe.

(194) In an embodiment, the method further comprises step d) filtering or screening debris from drilling mud.

(195) In an embodiment, a method of removing and replacing a drilling mud screen comprises a) stopping a drilling mud pump connected to the drilling mud screen system as disclosed herein, b) rotating a rotating trapdoor subassembly to open the drilling mud screen system, c) installing a replacement drilling mud screen, d) rotating the rotating trapdoor subassembly to close and seal the drilling mud screen system; and e) operating the drilling mud pump to produce flow of drilling mud through the drilling mud screen system.

(196) In an embodiment, step b) comprises step b-1) removing a piston guide bar and/or a threaded lock ring and step b-2) rotating the rotating trapdoor subassembly to open the drilling mud screen system.

(197) In an embodiment, step d) comprises step d-1) rotating the trapdoor subassembly to close the drilling mud screen system and step d-2) installing a piston guide bar and/or a threaded lock ring to seal the drilling mud screen system.

(198) In an embodiment, step b) comprises step b-1) removing a piston guide bar and/or a threaded lock ring and step b-2) rotating the rotating trapdoor subassembly to open the drilling mud screen system, and step d) comprises step d-1) rotating the trapdoor subassembly to close the drilling mud screen system and step d-2) installing a piston guide bar and/or a threaded lock ring to seal the drilling mud screen system.

(199) These and other objects, features and advantages will become apparent as reference is made to the following detailed description, preferred embodiments, and examples, given for the purpose of disclosure, and taken in conjunction with the accompanying drawings and appended claims.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) For a further understanding of the nature and objects of the present invention, reference should be made to the following detailed disclosure, taken in conjunction with the accompanying drawings, in which like parts are given like reference numerals, and wherein:

(2) FIG. 1 illustrates a photograph of an exemplary drilling mud screen system according to an embodiment of the present invention, showing the system installed at an outlet of a drilling mud

pump upstream of a drilling rig standpipe assembly;

(3) FIG. 2 illustrates a photograph of a single-piece body for the exemplary drilling mud screen system of FIG. 1, showing an unassembled view of a drilling mud inlet, a drilling mud outlet and a drilling mud screen access port;

(4) FIG. 3A illustrates a photograph of a single-piece body for the exemplary drilling mud screen system of FIG. 2, showing a detailed view of a drilling mud inlet and a drilling mud screen access port;

(5) FIG. 3B illustrates a photograph of a single-piece body for the exemplary drilling mud screen system of FIG. 3A, showing a detailed view of the drilling mud screen access port;

(6) FIG. 3C illustrates a photograph of the single-piece body for the exemplary drilling mud screen system of FIG. 3A, showing an end cap installed in the drilling mud screen access port;

(7) FIG. 3D illustrates a photograph of a single-piece body for the exemplary drilling mud screen system of FIGS. 3A-3C, showing a detailed view of the drilling mud inlet;

(8) FIG. 3E illustrates a photograph of a single piece body of the exemplary drilling mud screen system of FIGS. 3A-3C, showing a detailed view of the drilling mud outlet;

(9) FIG. 4A illustrates an upper, cross-sectional view of an exemplary drilling mud screen system according to an embodiment of the present invention, showing a drilling mud screen;

(10) FIG. 4B illustrates a detailed view of A-A of FIG. 4A, showing an end cap installed;

(11) FIG. 4C illustrates a detailed view of A-A of FIGS. 4A-4B, showing the end cap removed;

(12) FIG. 5A illustrates an upper, cross-sectional view of a drilling mud screen according to an embodiment of the present invention, showing a filter and an end cap;

(13) FIG. 5B illustrates a detailed view of A-A of FIG. 5A, showing an inlet of a second portion of a body and an outlet of the first portion of the body;

(14) FIG. 5C illustrates a detailed view of B of FIG. 5A, showing a detailed view of a groove for an O-ring;

(15) FIG. 5D illustrates a detailed view of C of FIG. 5A, showing an enlarged detailed view of the groove for an O-ring;

(16) FIG. 5E illustrates an upper, right perspective view of the drilling mud screen of FIG. 5A;

(17) FIG. 6A illustrates a photograph of a mud screen system according to an embodiment of the present invention, showing a two-piece body for the system;

(18) FIG. 6B illustrates a photograph of the exemplary drilling mud screen system of FIG. 6A, showing a drilling mud outlet;

(19) FIG. 6C illustrates a photograph of the exemplary drilling mud screen system of FIGS. 6A-6B;

(20) FIG. 6D illustrates a photograph of the exemplary drilling mud screen system of FIGS. 6A-6C, showing a drilling mud inlet and a drilling mud screen access port;

(21) FIG. 7A illustrates an upper, cross-sectional view of a drilling mud screen system according to an embodiment of the present invention, showing a single-inlet drilling mud system;

(22) FIG. 7B illustrates an upper, cross-sectional view of a drilling mud screen system according to an embodiment of the present invention, showing a double-inlet drilling mud system;

(23) FIG. 8A illustrates an upper cross-sectional view of an exemplary drilling mud screen puller/installer tool for the exemplary drilling mud screen system of FIGS. 4A-4C;

(24) FIG. 8B illustrates a detailed view of A-A of FIG. 8A, showing a means to engage a drilling mud screen according to an embodiment of the present invention;

(25) FIG. 9A illustrates an upper cross-sectional view of an exemplary drilling mud screen puller/installer tool for the exemplary drilling mud screen system of FIG. 7A;

(26) FIG. 9B illustrates a detailed view of A-A of FIG. 9A, showing a means to engage a drilling mud screen according to an embodiment of the present invention;

(27) FIG. 10 illustrates a flow diagram for a method of using a drilling mud screen system;

(28) FIG. 11 illustrates a flow diagram for a method of using a drilling mud screen puller/installer;

(29) FIG. 12A illustrates a cross-sectional view of the exemplary drilling mud tool of FIG. 8A

pulling the drilling mud screen of FIG. 5 from the exemplary drilling mud screen system of FIG. 4;

(30) FIG. 12B illustrates a cross-sectional view of the exemplary drilling mud tool of FIG. 8A installing the drilling mud screen of FIG. 5 into the exemplary drilling mud screen system of FIG. 4;

(31) FIG. 13A illustrates a cross-sectional view of the exemplary drilling mud tool of FIG. 9A pulling the drilling mud screen of FIG. 5 from the exemplary drilling mud screen system of FIG. 7A;

(32) FIG. 13B illustrates a cross-sectional view of the exemplary drilling mud tool of FIG. 9A installing the drilling mud screen of FIG. 5 into the exemplary drilling mud screen system of FIG. 7A;

(33) FIG. 14 illustrates a cross-sectional view of the exemplary drilling mud screen of FIG. 4, showing an optional plug installed in the drilling mud screen system;

(34) FIG. 15A illustrates an upper, right perspective view of an optional plug with a backward “J” shaped flow surface according to an embodiment of the present invention;

(35) FIG. 15B illustrates a cross-sectional view of the optional plug with the backward “J” shaped flow surface of FIG. 15A;

(36) FIG. 16A illustrates an upper, right perspective view of an optional plug with a curved shaped flow surface according to an embodiment of the present invention;

(37) FIG. 16B illustrates a cross-sectional view of the optional plug with the curved shaped flow surface of FIG. 16A;

(38) FIG. 17A illustrates an upper, right side perspective view of an optional plug with an “L” shaped flow surface according to an embodiment of the present invention;

(39) FIG. 17B illustrates a cross-sectional view of an optional plug with an “L” shaped flow surface of FIG. 17A;

(40) FIG. 18A illustrates an upper cross-sectional view of the exemplary drilling mud tool of FIG. 8A for the exemplary drilling mud system of FIGS. 4A-4C and 14;

(41) FIG. 18B illustrates another upper cross-sectional view of the exemplary drilling mud tool of FIG. 8A for the exemplary drilling mud system of FIGS. 4A-4C and 14;

(42) FIG. 19 illustrates a cross-sectional view of the drilling mud screen system in a monitoring configuration according to an embodiment of the present invention, showing an optional transducer subassembly;

(43) FIG. 20A illustrates an upper, right side perspective view of an optional transducer subassembly according to an embodiment of the present invention;

(44) FIG. 20B illustrates a side perspective view of the optional transducer subassembly of FIG. 20A;

(45) FIG. 21A illustrates an upper view of a mud screen system according to an embodiment of the present invention, showing an optional two-piece body for the system;

(46) FIG. 21B illustrates a detailed, cross-sectional view of A-A of FIG. 21A, showing an entry angle of about 30 degrees;

(47) FIG. 22A illustrates an end view of an optional drilling mud screen according to an embodiment of the present invention;

(48) FIG. 22B illustrates a detailed, cross-sectional view of A-A of FIG. 22A, showing an optional drilling mud screen insert, and optional first end retaining ring, an optional filter length, and an optional filter retaining ring;

(49) FIG. 22C illustrates a detailed view of B of FIG. 22B;

(50) FIG. 22D illustrates a detailed, cross-sectional view of C-C of FIG. 22C;

(51) FIG. 22E illustrates an upper, right perspective view of the drilling mud screen of FIGS. 22A-22B;

(52) FIG. 23 illustrates a cross-sectional view of a mud screen system according to an embodiment of the present invention, showing an optional drilling mud screen insert inserted into a drilling mud

screen;

(53) FIG. 24A illustrates an end view of an optional drilling mud screen insert according to an embodiment of the present invention;

(54) FIG. 24B illustrates a detailed, cross-sectional view of A-A of FIG. 24A, showing an inlet of the drilling mud screen insert and an outlet of the drilling mud screen insert;

(55) FIG. 24C illustrates an upper, right perspective view of the optional drilling mud screen insert of FIGS. 24A-24B;

(56) FIG. 25 illustrates a detailed, cross-sectional view of the optional drilling mud screen, showing an optional first end retaining ring;

(57) FIG. 26A illustrates a side view of an optional drilling mud screen according to an embodiment of the present invention, showing an optional filter length, and an optional filter retaining ring;

(58) FIG. 26B illustrates a detailed, cross-sectional view of the optional drilling mud screen of FIG. 26A, showing an optional drilling mud screen insert, an optional filter length, and an optional filter retaining ring;

(59) FIG. 27A illustrates an end view of an optional filter retaining ring according to an embodiment of the present invention;

(60) FIG. 27B illustrates a detailed, cross-sectional view of A-A of FIG. 27A;

(61) FIG. 27C illustrates a detailed, cross-sectional view of B of FIG. 27B;

(62) FIG. 28 illustrates a cross-sectional view of a drilling mud screen system in a cementing configuration according to an embodiment of the present invention, showing an optional first transducer subassembly having an optional transducer, a drilling mud screen system, an optional gate valve and an optional second transducer subassembly having an optional low torque plug valve;

(63) FIG. 29 illustrates a cross-sectional view of the exemplary drilling mud tool of FIG. 9A inserting the drilling mud screen of FIG. 5 or 22 into the exemplary drilling mud screen system of FIG. 7A or 21B, showing an optional stop plate.

(64) FIG. 30A illustrates an upper, left perspective view of an exemplary drilling mud screen system with a camming seal separator having a face-roller cam mechanism according to an embodiment of the present invention, showing a rotating subassembly in a closed position;

(65) FIG. 30B illustrates the upper, left perspective view of the drilling mud screen system of FIG. 30A, showing an optional first transducer subassembly and an optional second transducer subassembly;

(66) FIG. 30C illustrates an upper, left perspective view of the drilling mud screen system of FIG. 30A, showing a rotating subassembly in the open position;

(67) FIG. 30D illustrates a detail view of a rotating subassembly of FIGS. 30A-30C;

(68) FIG. 30E illustrates a cross-sectional view of the drilling mud screen system of FIG. 30A, showing the rotating subassembly in a closed position;

(69) FIG. 31A illustrates left perspective view of an exemplary drilling mud screen system with a camming seal separator having a face-roller cam mechanism according to an embodiment of the present invention, showing a rotating subassembly in a closed position;

(70) FIG. 31B illustrates the left perspective view of the drilling mud screen system of FIG. 31A, showing an optional first transducer subassembly and an optional second transducer subassembly;

(71) FIG. 31C illustrates a left perspective view of the drilling mud screen system of FIG. 30A, showing a rotating subassembly in the open position;

(72) FIG. 31D illustrates a partial cross-sectional view of the drilling mud screen system of FIG. 31A, showing the rotating subassembly in the closed position;

(73) FIG. 31E illustrates a partial cross-sectional view of the drilling mud screen system of FIGS. 31A and 31C-31D, showing the rotating subassembly in the open position;

(74) FIG. 32A illustrates an upper, left perspective view of an exemplary drilling mud screen

system with a camming seal separator having a push-rod cam mechanism according to an embodiment of the present invention, showing a rotating subassembly in a closed position;

(75) FIG. 32B illustrates the upper, left perspective view of the drilling mud screen system of FIG. 32A, showing the rotating subassembly in an open position;

(76) FIG. 32C illustrates a cross-sectional view of the drilling mud screen system of FIG. 32A, showing the rotating subassembly in a closed position;

(77) FIG. 33A illustrates a left perspective view of an exemplary drilling mud screen system with a camming seal separator having a push-rod cam mechanism according to an embodiment of the present invention, showing a rotating subassembly in a closed position;

(78) FIG. 33B illustrates a left perspective view of the drilling mud screen system of FIG. 33A, showing the rotating subassembly in an open position;

(79) FIG. 33C illustrates a detail view of the push-rod cam mechanism of FIG. 33A, showing the rotating subassembly in a closed position;

(80) FIG. 33D illustrates a detail view of the push-rod cam mechanism of FIGS. 33A and 33C, showing the rotating subassembly in the open position;

(81) FIG. 33E illustrates a partial cross-sectional view of the drilling mud screen system of FIG. 33A, showing the rotating subassembly in the closed position;

(82) FIG. 33F illustrates a detail view of the push-rod cam mechanism of FIG. 33A, showing the rotating subassembly in the closed position;

(83) FIG. 34 illustrates a flow chart for a method of using a drilling mud screen system;

(84) FIG. 35A illustrates a flow chart for a method of using a drilling mud screen system;

(85) FIG. 35B illustrates a flow chart of optional steps for the method in FIG. 35A;

(86) FIG. 36 illustrates a flow chart for a method of removing and replacing a drilling mud screen;

(87) FIG. 37A illustrates an end view of an exemplary trapdoor-style drilling mud screen system according to an embodiment of the present invention;

(88) FIG. 37B illustrates a detailed, cross-sectional view A-A of FIG. 37A;

(89) FIG. 37C illustrates a detailed, cross-sectional view B-B of FIG. 37A;

(90) FIG. 37D illustrates a detailed view C of FIG. 37C;

(91) FIG. 37E illustrates an end view of the exemplary trapdoor-style drilling mud screen system of FIGS. 37A-37D;

(92) FIG. 37F illustrates a detailed, cross-sectional view G-G of FIG. 37E;

(93) FIG. 37G illustrates an end view of the exemplary trapdoor-style drilling mud screen system of FIGS. 37A-37F;

(94) FIG. 37H illustrates a detailed, cross-sectional view J-J of FIG. 37G;

(95) FIG. 37I illustrates an end view of the exemplary trapdoor-style drilling mud screen system of FIGS. 37A-37H;

(96) FIG. 37J illustrates a detailed cross-sectional view H-H of FIG. 37I;

(97) FIG. 37K illustrates an upper, right perspective view of the exemplary trapdoor-style drilling mud screen system of FIGS. 37A-37J, showing the trapdoor-style drilling mud screen system in a closed position;

(98) FIG. 37L illustrates an upper, right perspective view of the exemplary trapdoor-style drilling mud screen system of FIGS. 37A-37K, showing the trapdoor-style drilling mud screen system in an open position;

(99) FIG. 37M illustrates an exploded view of the exemplary trapdoor-style drilling mud screen system of FIGS. 37A-37L;

(100) FIG. 38A illustrates a cross-sectional view of an exemplary trapdoor-style drilling mud screen system having a reversed drilling mud screen, showing the trapdoor-style drilling mud screen system in a closed position;

(101) FIG. 38B illustrates a cross-sectional view of the exemplary trapdoor-style drilling mud screen system of FIG. 38A, showing the trapdoor-style drilling mud screen system in an open

position and

(102) FIG. **39** illustrates a flow diagram for a method of installing and removing a drilling mud screen for the exemplary trapdoor-style drilling mud screen system of FIGS. **39A-39M** and **38A-38B**.

DETAILED DESCRIPTION OF EMBODIMENTS OF THE INVENTION

(103) The following detailed description of various embodiments of the present invention references the accompanying drawings, which illustrate specific embodiments in which the invention can be practiced. While the illustrative embodiments of the invention have been described with particularity, it will be understood that various other modifications will be apparent to and can be readily made by those skilled in the art without departing from the spirit and scope of the invention. Accordingly, it is not intended that the scope of the claims appended hereto be limited to the examples and descriptions set forth herein but rather that the claims be construed as encompassing all the features of patentable novelty which reside in the present invention, including all features which would be treated as equivalents thereof by those skilled in the art to which the invention pertains. Therefore, the scope of the present invention is defined only by the appended claims, along with the full scope of equivalents to which such claims are entitled.

(104) Exemplary Drilling Mud Screen System

(105) FIG. **1** illustrates a photograph of an exemplary drilling mud screen system according to an embodiment of the present invention, showing the system installed at an outlet of a drilling mud pump upstream of a drilling rig standpipe assembly. As shown in FIG. **1**, the drilling mud screen system **100** has a body **105** having a first end **110** and a second end **115**, a drilling mud inlet **120** and a drilling mud outlet **125**, and a drilling mud screen access port **130**. In an embodiment, the drilling mud screen access port **130** may be closed with an end cap **135**.

(106) In an embodiment, a drilling mud inlet **120** of the drilling mud screen system **100** may be fluidly connected to a high-pressure outlet of a drilling mud pump via a connection. In an embodiment, a drilling mud outlet **125** of the drilling mud screen system **100** may be fluidly connected to an inlet of a vibrator hose to a standpipe via a connection.

(107) Alternatively, the drilling mud screen system **100** may be installed between an outlet of the vibrator hose and an inlet of the standpipe, or at any point in the standpipe via a connection.

(108) In an embodiment, the drilling mud inlet **120** may be fluidly connected to, for example, an outlet to a drilling mud pump via a connection; and the drilling mud outlet **125** may be fluidly connected to, for example, an inlet to a vibrator hose via a connection. Any suitable connection may be used for the drilling mud inlet and the drilling mud outlet. For example, suitable connections include, but are not limited to, pipe fittings and welds. Connections are well known in the art. In an embodiment, the drilling mud inlet **120** may be fluidly connected to, for example, an outlet to a drilling mud pump via a weld; and the drilling mud outlet **125** may be fluidly connected to, for example, an inlet to a vibrator hose via a weld.

(109) Single-Piece Body

(110) FIG. **2** illustrates a photograph of a single-piece body for the exemplary drilling mud screen system of FIG. **1**, showing an unassembled view of a drilling mud inlet **220**, a drilling mud outlet **225**, and a drilling mud screen access port **230**. As shown in FIG. **2**, the drilling mud screen system **200** has a body **205** having a first end **210** and a second end **215**, an inlet **220** and an outlet **225**, and a mud screen access port **230**.

(111) In an embodiment, the drilling mud inlet **220** may be fluidly connected to, for example, an outlet of a drilling mud pump via a connection; and the drilling mud outlet **225** may be fluidly connected to, for example, an inlet of a vibrator hose via a connection. Any suitable connection may be used for the drilling mud inlet **220** and the drilling mud outlet **225**. For example, suitable connections include, but are not limited to, pipe fittings and welds. Connections are well known in the art. In an embodiment, the drilling mud inlet **220** may be fluidly connected to, for example, an outlet of a drilling mud pump via a weld; and the drilling mud outlet **225** may be fluidly connected

to, for example, an inlet of a vibrator hose via a weld.

(112) FIG. 3A illustrates a photograph of a single-piece body for the exemplary drilling mud screen system of FIG. 2, showing a detailed view of a drilling mud inlet **320** and a drilling mud screen access port **330**. As shown in FIG. 3A, the drilling mud screen system **300** has a body **305** having a first end **310**, an inlet **320**, a drilling mud screen access port **330**, and an end cap **335**.

(113) FIG. 3B illustrates a photograph of the single-piece body of FIG. 3A, showing a detailed view of the drilling mud screen access port **330**. As shown in FIG. 3B, the drilling mud screen system **300** has a body **305** having a first end **310**, an inlet **320**, and a drilling mud screen access port **330**.

(114) FIG. 3C illustrates a photograph of the single-piece body of FIG. 3A, showing an end cap **335** installed in a drilling mud screen access port **330**. As shown in FIG. 3C, the drilling mud screen access port **330** of the drilling mud screen system **300** may be closed with an end cap **335** via a fitting. Any suitable fitting may be used. For example, suitable fittings include, but are not limited to, pipe fittings. Fittings are well known in the art.

(115) In an embodiment, the drilling mud screen access port **330** of the drilling mud screen system **300** may be sealed with an end cap **335** via an O-ring. Any suitable O-ring may be used. For example, suitable O-rings include, but are not limited to, 300 Series O-rings. O-rings are well known in the art.

(116) In an embodiment, the end cap **335** of the drilling mud screen system **300** may comprise a cap, an O-ring and a pipe collar. In an embodiment, the end cap **335** may be a five-inch 1002 WECO cap with an O-ring.

(117) FIG. 3D illustrates a photograph of a single-piece body of the exemplary drilling mud screen system of FIGS. 3A-3C, showing a detailed view of the drilling mud inlet **320**; and FIG. 3E illustrates a photograph of a single-piece body of the exemplary drilling mud screen system of FIGS. 3A-3C, showing a detailed view of the drilling mud outlet **325**.

(118) In an embodiment, the drilling mud inlet **320** may be fluidly connected to, for example, an outlet of a drilling mud pump via a connection; and the drilling mud outlet **325** may be fluidly connected to an inlet of a vibrator hose via a connection. Any suitable connection may be used for the drilling mud inlet **320** and the drilling mud outlet **325**. For example, suitable connections include, but are not limited to, pipe fittings and welds. Connections are well known in the art. In an embodiment, the drilling mud inlet **320** may be fluidly connected to, for example, an outlet of a drilling mud pump via a weld; and the drilling mud outlet **325** may be fluidly connected to an inlet of a vibrator hose via a weld.

(119) FIG. 4A illustrates an upper, cross-sectional view of an exemplary drilling mud screen system according to an embodiment of the present invention, showing a drilling mud screen. As shown in FIG. 4A, the drilling mud screen system **400** has a body **405** having a first end **410** and a second end **415**, a drilling mud inlet **420** and a drilling mud outlet **425**, a drilling mud screen access port **430**, an end cap **435** and a drilling mud screen **440**.

(120) Any suitable connection may be used for the drilling mud inlet **420** and the drilling mud outlet **425**. For example, suitable connections include, but are not limited to, pipe fittings and welds. Connections are well known in the art.

(121) In an embodiment, the body **405** of the drilling mud screen system **400** may be constructed of any suitable material. For example, suitable materials include, but are not limited to, any alloy steel suitable for a drilling mud application. In an embodiment, the body **405** may be constructed of an American Iron and Steel Industry (AISI) **4130/75k** yield or equivalent material. See e.g., FIG. 2. In an embodiment, the inner surface of the body **405** may be unpainted. See e.g., FIGS. 1 & 3A-3E. In an embodiment, the outer surface of the body **405** may be painted. Id.

(122) In an embodiment, the body **405** has a first centerline **445** and a length **450**. In an embodiment, the first centerline **445** extends through the center of the drilling mud screen access port **430** to the drilling mud outlet **425**. The length **450** of the body **405** may be any suitable length.

In an embodiment, the length **450** of the body **405** may be from about 30-inches to about 50-inches, and any range or value there between. In an embodiment, the length **450** may be about 40-inches.

(123) In an embodiment, the body **405** has a second centerline **455**. In an embodiment, the second centerline **455** extends through the center of the drilling mud inlet **420** to the first centerline **445**.

(124) In an embodiment, the first centerline **445** and the second centerline **455** form a first angle **460**. In an embodiment, the first angle **460** may be from about 30-degrees to about 120-degrees, and any range or value there between. In an embodiment, the first angle **460** may be about 45-degrees. In an embodiment, the first angle **460** may be about 90-degrees.

(125) In an embodiment, the first drilling mud inlet **420** may be offset from a first end **410** of the body **405**. The first drilling mud inlet **420** may be offset from a first end **410** of the body **405** at any suitable distance. In an embodiment, the second centerline **455** may be offset from the first end **410** of the body **405** from about 9-inches to about 13-inches, and any range or value there between. In an embodiment, the second centerline **455** may be offset from the first end **410** of the body **405** about 11-inches.

(126) In an embodiment, the drilling mud inlet **420** may have any suitable inner diameter **465**; and the drilling mud inlet **420** may have any suitable outer diameter **470**. In an embodiment, the inner diameter **465** of the drilling mud inlet **420** may be from about 3-inches to about 5-inches, and any range or value there between. In an embodiment, the inner diameter **465** of the drilling mud inlet **420** may be about 4-inches.

(127) In an embodiment, the outer diameter **470** of the drilling mud inlet **420** may be from about 4.5-inches to about 6.5-inches, and any range or value there between. In an embodiment, the outer diameter **470** of the drilling mud inlet **420** may be about 5.5-inches.

(128) In an embodiment, the body **405** has a first portion **475** and a second portion **480**. In an embodiment, the first portion **475** of the body **405** may have a first inner diameter **485** and an outer diameter **495**; and the second portion **480** of the body **405** may have a second inner diameter **490** and an outer diameter **495**.

(129) In an embodiment, the first inner diameter **485** of the body **405** may be from about 3-inches to about 5-inches, and any range or value there between. In an embodiment, the first inner diameter **485** of the body **405** may be about 4-inches.

(130) In an embodiment, the second inner diameter **490** of the body **405** may be from about 3-inches to about 5-inches, and any range or value there between. In an embodiment, the second inner diameter **490** of the body **405** may be about 4-inches.

(131) In an embodiment, a second portion **480** of the body **405** may have a second inner diameter **490** to provide a high flow rate of drilling mud through the drilling mud screen **440**. In an embodiment, the second inner diameter **490** of the body **405** may be from about 3.5-inches to about 5.5-inches, and any range or value there between. In an embodiment, the second inner diameter **490** of the body **405** may be from about 4.5-inches to about 5.5-inches, and any range or value there between.

(132) In an embodiment, the outer diameter **495** of the first portion **475** and/or the second portion **480** of the body **405** may be from about 5.5-inches to about 7.5-inches, and any range or value there between. In an embodiment, the outer diameter **495** of the first portion **475** and/or the second portion **480** of the body **405** may be about 6.5-inches.

(133) In an embodiment, the drilling mud outlet **425** may have any suitable inner diameter **465**; and the drilling mud outlet **425** may have any suitable outer diameter **470**. In an embodiment, the inner diameter **465** of the drilling mud outlet **425** may be from about 3-inches to about 5-inches, and any range or value there between. In an embodiment, the inner diameter **465** of the drilling mud outlet **425** may be about 4-inches.

(134) In an embodiment, the outer diameter **470** of the drilling mud outlet **425** may be from about 4.5-inches to about 6.5-inches, and any range or value there between. In an embodiment, the outer diameter **470** of the drilling mud outlet **425** may be about 5.5-inches.

(135) FIG. 4B illustrates a detailed view of A-A of FIG. 4A, showing an end cap **435** installed; and FIG. 4C illustrates a detailed view of A-A of FIGS. 4A-4B, showing the end cap **435** removed.

(136) Drilling Mud Screen

(137) The drilling mud screen **500** may be any suitable filter or screen capable of filtering or screening debris from drilling muds. For example, suitable drilling mud screens include, but are not limited to, drill screens and rod screens.

(138) FIG. 5A illustrates an upper, cross-sectional view of a drilling mud screen **500** according to an embodiment of the present invention, showing a filter **530** and an end cap **535**. As shown in FIG. 5A, the drilling mud screen **500** has a body **505** having a first end **510** and a second end **515**, a drilling mud inlet **520**, a drilling mud outlet **525**, a filter **530** and an end cap **535**.

(139) In an embodiment, the drilling mud inlet **520** may be fluidly connected to, for example, an outlet of a drilling mud pump via a connection; and the drilling mud outlet **525** may be fluidly connected to an inlet of a vibrator hose via a connection. Any suitable connection may be used for the drilling mud inlet **520** and the drilling mud outlet **525**. For example, suitable connections include, but are not limited to, pipe fittings and welds. Connections are well known in the art. In an embodiment, the drilling mud inlet **520** may be fluidly connected to, for example, an outlet of a drilling mud pump via a weld; and the drilling mud outlet **525** may be fluidly connected to an inlet of a vibrator hose via a weld.

(140) In an embodiment, the body **505** of the drilling mud screen **500** may be constructed of any suitable material. For example, suitable materials include, but are not limited to, any alloy steel or tool steel. In an embodiment, the body **505** may be constructed of an AISI 4145 or equivalent material. See e.g., FIGS. 5A-5E. In an embodiment, the body **505** may be constructed of tool steel or equivalent material.

(141) In an embodiment, the body **505** of the drilling mud screen **500** may have a hardened coating to reduce washing (i.e., erosion) of the screen **500**. For example, suitable hardened coatings include, but are not limited to, any Carbide coating or equivalent. In an embodiment, the body **505** may have a Carbide coating with about 6% Cobalt binder or equivalent material.

(142) In an embodiment, the body **505** of the drilling mud screen **500** has a centerline **545** and a length **550**. In an embodiment, the centerline **545** extends through the center of the drilling mud screen inlet **520** to the end cap **535**. The length **550** of the body **505** may be any suitable length. In an embodiment, the length **550** of the body **505** may be from about 20-inches to about 30-inches, and any range or value there between. In an embodiment, the length **550** may be about 25-inches.

(143) In an embodiment, the drilling mud inlet **520** of the drilling mud screen **500** may have any suitable inner diameter **565**; and the drilling mud inlet **520** may have any suitable outer diameter **570**. In an embodiment, the inner diameter **565** of the drilling mud inlet **520** may be from about 3-inches to about 5-inches, and any range or value there between. In an embodiment, the inner diameter **565** of the drilling mud inlet **520** may be about 3.9-inches.

(144) In an embodiment, the outer diameter **570** of the drilling mud inlet **520** may be from about 4-inches to about 6-inches, and any range or value there between. In an embodiment, the outer diameter **570** of the drilling mud inlet **520** may be about 4-inches.

(145) In an embodiment, the body **505** of the drilling mud screen **500** has a first portion **575** and a second portion **580**. In an embodiment, the first portion **575** of the body **505** has a first length; and the second portion **580** of the body **505** has a second length. The first portion **575** and the second portion **580** may be any suitable length. In an embodiment, the first portion **575** may have a first length from about 6-inches to about 10-inches; and the second portion **580** may have a second length from about 14-inches to about 20-inches, and any range or value there between. In an embodiment, the first portion **575** may have a first length of about 7.5-inches; and the second portion **580** may have a second length of about 17.5-inches.

(146) In an embodiment, a second portion **580** of the body **505** of the drilling mud screen **500** may have a filter **530**. In an embodiment, the filter **530** may comprise a plurality of rods spaced a

distance apart to form a filter. In an embodiment, the distance may be less than a particle size (e.g., diameter) desired to be filtered from the drilling mud. Particle filtration is well known in the art.

(147) In an embodiment, the filter **530** may comprise a formed sheet having drilled holes spaced a distance apart to form a filter. In an embodiment, the size of the holes (e.g., diameter) may be less than a particle size (e.g., diameter) desired to be filtered. Particle filtration is well known in the art.

(148) In an embodiment, a second portion **580** of the body **505** of the drilling mud screen **500** may have a drilling mud outlet **525**. In an embodiment, the drilling mud outlet **525** may comprise a plurality of spaces (i.e., flow passages) between a plurality of rods. In an embodiment, the drilling mud outlet **525** may comprise a plurality of holes (i.e., flow passages) drilled in a formed sheet.

(149) In an embodiment, a first end **510** of a first portion **575** of the body **505** of the drilling mud screen **500** may have a first inner diameter **585**; and a second end **515** of a second portion **580** of the body **505** may have a second inner diameter **590**.

(150) In an embodiment, the first end **510** of the first portion **575** may be shaped to accept a puller/installer plate **975** of a drilling mud screen puller/installer tool **800, 900**, as discussed below. See e.g., FIGS. **5A, 8A & 9A**.

(151) In an embodiment, the body **505** and/or a filter **530** of the drilling mud screen **500** may have a tapered drilling mud flow path from a larger inner diameter (ID) to a smaller ID to reduce washing (i.e., erosion) of the screen **500**.

(152) In an embodiment, the first inner diameter **585** of the first end **510** of the body **505** of the drilling mud screen **500** may be from about 3-inches to about 5-inches, and any range or value there between. In an embodiment, the first inner diameter **585** of the first end **510** of the body **505** may be about 3.9-inches.

(153) FIG. **5B** illustrates a detailed view of A-A of FIG. **5A**, showing an outlet of a first portion **575** of the body **505** and an inlet of the second portion **580** of the body **505**. In an embodiment, an inner diameter of an outlet of the first portion **575** and an inlet of the second portion **590** of the body **505** may be from about 2-inches to about 3-inches, and any range or value there between. In an embodiment, the inner diameter of the outlet of the first portion **575** of the body **505** and the inlet of the second portion **590** of the body **505** may be about 2.5-inches.

(154) In an embodiment, the outlet of the first portion **575** and/or the inlet of the second portion **590** of the body **505** may be shaped to accept a rounded end **875, 975** of a drilling mud screen puller/installer tool **800, 900**. See e.g., FIGS. **5B, 8B & 9B**. See also FIGS. **12B & 13B**. In an embodiment, the inlet of the second portion **590** of the body **505** may have an inner shoulder to provide a pushing surface for the rounded end **875, 975** of the drilling mud screen puller/installer tool **800, 900**. Id.

(155) In an embodiment, the outlet of the first portion **575** and/or the inlet of the second portion **580** of the body **505** may have a means to engage **540** a drilling mud screen puller/installer tool **800, 900**, as discussed below. See e.g., FIGS. **5A, 8A & 9A**. The means to engage **540** may be any suitable means to accept, and provide a pulling surface for, the drilling mud screen puller/installer tool **800, 900**. For example, a suitable means to engage **540** includes, but is not limited to, a “key” opening to rotationally engage an inner shoulder. In an embodiment, the outlet of the first portion **575** and/or the inlet of the second portion **590** of the body **505** may be shaped to accept a puller/installer plate **870, 970** of a drilling mud screen puller/installer tool **800, 900**. See e.g., FIGS. **5B, 8B & 9B**. See also FIGS. **12A, 13A & 29**. In an embodiment, the inlet of the second portion **590** of the body **505** may have an inner shoulder to provide a pulling surface for the puller/installer plate **870, 970** of the drilling mud screen puller/installer tool **800, 900**. Id.

(156) In an embodiment, the second inner diameter **590** of the second end **515** of the body **505** of the drilling mud screen **500** may be from about 2-inches to about 3-inches, and any range or value there between. In an embodiment, the second inner diameter **590** of the second end **515** of the body **505** may be about 2.3-inches.

(157) In an embodiment, the outer surface **595** of the first portion **575** of the body **505** of the

drilling mud screen **500** may be adapted to engage one or more shoulders in an inner surface of the body **505**. In an embodiment, a first shoulder and a second shoulder of the body **505** may be offset from a first end **510** of the body **505**. Cf. FIGS. **4A** & **5A**. The first and second shoulders may be offset from the first end **510** of the body **505** at any suitable distance. In an embodiment, the first shoulder may be offset from the first end **510** of the body **505** from about 4-inches to about 8-inches; and the second shoulder may be offset from the first end **510** of the body **505** from about 5-inches to about 9-inches, and any range or value there between. In an embodiment, the first shoulder may be offset from the first end **510** of the body **505** about 4.8-inches; and the second shoulder may be offset from the first end **510** of the body **505** about 6.8-inches.

(158) In an embodiment, the outer surface **595** of the body **505** of the drilling mud screen **500** may be sealed against an inner surface of the body **505** via an O-ring. Cf. FIGS. **4A** & **5A**. Any suitable O-ring may be used. For example, suitable O-rings include, but are not limited to, 300 Series O-rings. O-rings are well known in the art.

(159) FIG. **5C** illustrates a detailed view of B of FIG. **5A**; and FIG. **5D** illustrates a detailed view of C of FIG. **5A**, both showing detailed views of a groove for an O-ring. In an embodiment, a groove for an O-ring may be offset from a first end **510** of the body **505** of the drilling mud screen **500**. The groove for the O-ring may be offset from the first end **510** of the body **505** at any suitable distance. In an embodiment, the groove for the O-ring may be offset from the first end **510** of the body **505** from about 4-inches to about 8-inches, and any range or value there between. In an embodiment, the groove for the O-ring may be offset from the first end **510** of the body **505** about 5.7-inches.

(160) In an embodiment, the filter **530** may have a plurality of rods spaced a distance apart to form a filter, or, alternatively, a formed sheet having drilled holes spaced a distance apart to form a filter. In an embodiment, the plurality of rods may be tapered from a larger outer diameter (OD) to a smaller OD to encourage drilling mud flow to exit in straight lines through the drilling mud outlet **525** (i.e., through flow passages between the plurality rods) to reduce washing (i.e., erosion) of the screen **500**. In an embodiment, the filter **530** may have a plurality of straight rows of holes drilled in a formed sheet to encourage drilling mud flow to exit in straight rows of strings through the drilling mud outlet **525** (i.e., through straight flow passages of the drilled holes) to reduce washing (i.e., erosion) of the screen **500**.

(161) In an embodiment, a first end of a filter **530** may be connected to a second end **515** of the body **505** via a connection; and a second end of a filter **530** may be connected to a first end of the end cap **535** via a connection. Any suitable connection may be used for the drilling mud inlet **530**. For example, suitable connections include, but are not limited to, welds. Connections are well known in the art. In an embodiment, the first end of the filter **530** may be connected to the second end **515** of the body **505** via a weld; and the second end of the filter **530** may be connected to the first end of the end cap **535** via a weld.

(162) In an embodiment, the first end of the filter **530** may fit into a first recess in the second end **515** of the body **505**; and the second end of the filter may fit into a second recess in the first end of the end cap **535**. In an embodiment, the first recess and the second recess may be a plurality of recessed holes or a recessed groove. In an embodiment, the first recess and the second recess may be a plurality of recessed holes.

(163) In an embodiment, the filter **530** may be held together with a retaining ring. In an embodiment, the retaining ring may have a plurality of holes to hold the plurality of rods to form the filter **530**. In an embodiment, the plurality of rods may be connected to the plurality of holes in the retainer ring via a connection. Any suitable connection may be used for the drilling mud inlet **530**. For example, suitable connections include, but are not limited to, welds. Connections are well known in the art. In an embodiment, the plurality of rods may be connected to the plurality of holes in the retainer ring via a weld.

(164) In an embodiment, the filter **530**, including any retaining rings, of the drilling mud screen

500 may be constructed of any suitable material. For example, suitable materials include, but are not limited to, any alloy steel. In an embodiment, the filter **530** may be constructed of 304 stainless steel material. See e.g., FIGS. **5A** & **5E**. In an embodiment, the filter **530** may have a hardened coating to reduce washing (i.e., erosion) of the screen **500**.

(165) In an embodiment, the end cap **535** of the drilling mud screen **500** has an inner surface **555**. In an embodiment, the inner surface **555** of the end cap **535** of the drilling mud screen **500** may redirect the flow to reduce washing (i.e., erosion) of the screen **500**. In an embodiment, the inner surface **555** of the end cap **535** of the drilling mud screen **500** forms an inverted cone relative to the second end **515** of the body **505** of the drilling mud screen **500** to redirect the flow. In an embodiment, the tip of the inverted cone may have a rounded or squared shape.

(166) In an embodiment, the body **505** of the drilling mud screen **500** has a centerline **545** and a length **550**. In an embodiment, the centerline **545** extends through the center of the drilling mud screen inlet **520** to the end cap **535**. In an embodiment, the centerline **545** of the body **505** of the drilling mud screen **500** and the inner surface **555** of the end cap **535** form an angle **560**. In an embodiment, the angle **560** may be from about 30-degrees to about 60-degrees, and any range or value there between. In an embodiment, the first angle **560** may be from about 35-degrees to about 45-degrees, and any range or value there between.

(167) In an embodiment, the end cap **535** of the drilling mud screen **500** may be constructed of any suitable material. For example, suitable materials include, but are not limited to, any alloy steel. In an embodiment, the end cap **535** may be constructed of 304 stainless steel material. See e.g., FIGS. **5A** & **5E**. In an embodiment, the end cap **535** of the drilling mud screen **500** may have a hardened coating to reduce washing (i.e., erosion) of the screen **500**. For example, suitable hardened coatings include, but are not limited to, any Carbide coating or equivalent. In an embodiment, the end cap **535** may have a Carbide coating with about 6% Cobalt binder or equivalent material.

(168) FIG. **5E** illustrates an upper, right side perspective view of the drilling mud screen **500** of FIG. **5A**. As shown in FIG. **5E**, the drilling mud screen **500** has a body **505** having a first end **510** and a second end **515**, a drilling mud inlet **520**, a drilling mud outlet **525**, a filter **530** and an end cap **535**. In an embodiment, the body **505** of the drilling mud screen **500** has a first portion **575** and a second portion **580**.

(169) Optional Plug for One-Piece Body

(170) As discussed above, the one-piece body **405** for the exemplary drilling mud screen system of FIGS. **1-4** has a drilling mud flow passage from the drilling mud inlet **420** (through the drilling mud inlet **520** of the drilling mud screen **440**, through the drilling mud outlet **525** of the drilling mud screen **440**) and to the drilling mud outlet **425**. See FIGS. **4A** & **5**.

(171) The one-piece body **405**, however, also has a drilling mud flow passage into a void between the drilling mud inlet **420** the mud screen access port **430**. Id.

(172) FIG. **14** illustrates a cross-sectional view of the exemplary drilling mud screen of FIG. **4**, showing an optional plug installed in the drilling mud screen system. As shown in FIGS. **4** and **14**, the drilling mud screen system **400**, **1400** has a body **405**, **1405** having a first end **410**, **1410** and a second end **415**, **1415**, a drilling mud inlet **420**, **1420** and a drilling mud outlet **425**, **1425**, a drilling mud screen access port **430**, **1430**, an end cap **435**, **1435**, a drilling mud screen **440**, **1440** and a plug **14100**. In an embodiment, the optional plug **14100** has a flow surface **14105**.

(173) In an embodiment, the optional plug **14100** fills the void between the drilling mud inlet **420**, **1420** and the mud screen access port **430**, **1430**; and the flow surface **14105** of the optional plug **14000** directs the drilling mud from the drilling mud inlet **420**, **1420** of the drilling mud screen system **400**, **1400** to the drilling mud inlet **520** of the drilling mud screen **440**, **1440**, resulting in increased flow efficiency and decreased erosion.

(174) In an embodiment, the plug **14100** may be constructed of any suitable material. For example, suitable materials include, but are not limited to, any alloy steel suitable for a drilling mud application. In an embodiment, the plug **14100** may be constructed of an American Iron and Steel

Industry (AISI) **4130/75k** yield or equivalent material.

(175) In an embodiment, the plug **14100** may have any suitable outer diameter to fit within the body **405**, **1405**. In an embodiment, the outer diameter of the plug **14100** may be from about 3-inches to about 5-inches, and any range or value there between. In an embodiment, the outer diameter of the plug **14100** may be about 3.9-inches.

(176) In an embodiment, the optional plug **14100** has a flow surface **14105** to direct the drilling mud from the drilling mud inlet **420**, **1420** of the drilling mud screen system **400**, **1400** to the drilling mud inlet **520** of the drilling mud screen **440**, **1440**. See e.g., FIGS. **4A** & **5**. In an embodiment, the flow surface **14105** may have any suitable shape to direct the drilling mud from the drilling mud inlet of the drilling mud screen system to the drilling mud inlet of the drilling mud screen. Suitable shapes include, but are not limited to, a backward “J” shape, a curved shape, an “L” shape and any combination or variation thereof, as discussed further below.

(177) FIG. **15A** illustrates an upper, right perspective view of an optional plug with a backward “J” shaped flow surface according to an embodiment of the present invention; and FIG. **15B** illustrates a cross-sectional view of the optional plug with the backward “J” shaped flow surface of FIG. **15A**. As shown in FIGS. **15A** and **15B**, the optional plug **1500** has a body **1505** having a first end **1510** and a second end **1515**, a flow surface **1520**, an optional cavity **1530** and an optional port **1560**.

(178) In an embodiment, the first end **1510** of the body **1505** may have a means to engage **1525** a drilling mud screen puller/installer tool **800**. See e.g., FIGS. **8A**, **15A-15B** & **18A-18B**. The means to engage **1525** may be any suitable means to accept, and provide a pulling surface for, the drilling mud screen puller/installer tool **800**. For example, a suitable means to engage **1525** includes, but is not limited to, a “key” opening to rotationally engage an inner shoulder.

(179) In an embodiment, the first end **1510** of the plug **1500** may have an optional cavity **1530** extending towards, but not through, the flow surface **1520** of the plug **1500**.

(180) In an embodiment, the first end **1510** of the plug **1500** may have an optional port **1560** extending from an outer surface of the plug **1500** into the optional cavity **1530**.

(181) In an embodiment, the first end **1510** of the plug **1500** may have any suitable inner diameter **1535** of the optional cavity **1530**. In an embodiment, the inner diameter **1535** of the optional cavity **1530** may be from about 1-inch to about 3-inches, and any range or value there between. In an embodiment, the inner diameter **1535** of the optional cavity **1530** may be about 2-inches.

(182) In an embodiment, the plug **1500** may have any suitable outer diameter **1540**. In an embodiment, the outer diameter **1540** of the plug **1500** may be from about 3-inches to about 5-inches, and any range or value there between. In an embodiment, the outer diameter **1540** of the plug **1500** may be about 3.9-inches.

(183) In an embodiment, the body **1505** has a centerline **1545**, a first length **1550** and a second length **1555**. In an embodiment, the first length **1550** of the body **1505** may be any suitable length. In an embodiment, the first length **1550** of the body **1505** may be from about 6-inches to about 10-inches, and any range or value there between. In an embodiment, the length **1550** may be about 8-inches.

(184) In an embodiment, the second length **1555** of the body **1505** may be any suitable length. In an embodiment, the second length **1555** may be from about 8-inches to about 14-inches, and any range or value there between. In an embodiment, the second length **1555** may be about 11.5-inches.

(185) In an embodiment, the second end **1515** of the plug **1500** may have a flow surface **1520**. In an embodiment, the flow surface **1520** may have any suitable shape to direct the drilling mud from the drilling mud inlet of the drilling mud screen system to the drilling mud inlet of the drilling mud screen. Suitable shapes include, but are not limited to, a backward “J” shape, a curved shape, an “L” shape and any combination or variation thereof, as discussed further below. In an embodiment, the flow surface **1520** may have a backward “J” shape. See FIG. **15B**.

(186) FIG. **16A** illustrates an upper, right perspective view of an optional plug with a curved flow surface according to an embodiment of the present invention; and FIG. **16B** illustrates a cross-

sectional view of the optional plug with the curved flow surface of FIG. 16A. As shown in in FIGS. 16A and 16B, the optional plug 1600 has a body 1605 having a first end 1610 and a second end 1615, a flow surface 1620, an optional cavity 1630 and an optional port 1660.

(187) In an embodiment, the first end 1610 of the body 1605 may have a means to engage 1625 a drilling mud screen puller/installer tool 800. See e.g., FIGS. 8A, 16A-16B, 18A-18B & 29. The means to engage 1625 may be any suitable means to accept, and provide a pulling surface for, the drilling mud screen puller/installer tool 800. For example, a suitable means to engage 1625 includes, but is not limited to, a “key” opening to rotationally engage an inner shoulder.

(188) In an embodiment, the first end 1610 of the plug 1600 may have an optional cavity 1630 extending towards, but not through, the flow surface 1620 of the plug 1600.

(189) In an embodiment, the first end 1610 of the plug 1600 may have an optional port 1660 extending from an outer surface of the plug 1600 into the optional cavity 1630.

(190) In an embodiment, the first end 1610 of the plug 1600 may have any suitable inner diameter 1635 of the optional cavity 1630. In an embodiment, the inner diameter 1635 of the optional cavity 1630 may be from about 1-inch to about 3-inches, and any range or value there between. In an embodiment, the inner diameter 1635 of the optional cavity 1630 may be about 2-inches.

(191) In an embodiment, the plug 1600 may have any suitable outer diameter 1640. In an embodiment, the outer diameter 1640 of the plug 1600 may be from about 3-inches to about 5-inches, and any range or value there between. In an embodiment, the outer diameter 1640 of the plug 1600 may be about 3.9-inches.

(192) In an embodiment, the body 1605 has a centerline 1645, a first length 1650 and a second length 1655. In an embodiment, the first length 1650 of the body 1605 may be any suitable length. In an embodiment, the first length 1650 of the body 1605 may be from about 6-inches to about 10-inches, and any range or value there between. In an embodiment, the length 1650 may be about 8-inches.

(193) In an embodiment, the second length 1655 of the body 1605 may be any suitable length. In an embodiment, the second length 1655 may be from about 8-inches to about 15-inches, and any range or value there between. In an embodiment, the second length 1655 may be about 12-inches.

(194) In an embodiment, the second end 1615 of the plug 1600 may have a flow surface 1620. In an embodiment, the flow surface 1620 may have any suitable shape to direct the drilling mud from the drilling mud inlet of the drilling mud screen system to the drilling mud inlet of the drilling mud screen. Suitable shapes include, but are not limited to, a backward “J” shape, a curved shape, an “L” shape and any combination or variation thereof, as discussed further below. In an embodiment, the flow surface 1620 may have a curved shape. See FIG. 16B.

(195) FIG. 17A illustrates an upper, right perspective view of an optional plug with an “L” flow surface according to an embodiment of the present invention; and FIG. 17B illustrates a cross-sectional view of an optional plug with an “L” flow surface of FIG. 17A. As shown in FIGS. 17A and 17B, the optional plug 1700 has a body 1705 having a first end 1710 and a second end 1715, a flow surface 1720, an optional cavity 1730 and an optional port 1760.

(196) In an embodiment, the first end 1710 of the body 1705 may have a means to engage 1725 a drilling mud screen puller/installer tool 800. See e.g., FIGS. 8A, 17A-17B, 18A-18B & 29. The means to engage 1725 may be any suitable means to accept, and provide a pulling surface for, the drilling mud screen puller/installer tool 800. For example, a suitable means to engage 1725 includes, but is not limited to, a “key” opening to rotationally engage an inner shoulder.

(197) In an embodiment, the first end 1710 of the plug 1700 may have an optional cavity 1730 extending towards, but not through, the flow surface 1720 of the plug 1700.

(198) In an embodiment, the first end 1710 of the plug 1700 may have an optional port 1760 extending from an outer surface of the plug 1700 into the optional cavity 1730.

(199) In an embodiment, the first end 1710 of the plug 1700 may have any suitable inner diameter 1735 of the optional cavity 1730. In an embodiment, the inner diameter 1735 of the optional cavity

1730 may be from about 1-inch to about 3-inches, and any range or value there between. In an embodiment, the inner diameter **1735** of the optional cavity **1730** may be about 2-inches.

(200) In an embodiment, the plug **1700** may have any suitable outer diameter **1740**. In an embodiment, the outer diameter **1740** of the plug **1700** may be from about 3-inches to about 5-inches, and any range or value there between. In an embodiment, the outer diameter **1740** of the plug **1700** may be about 3.9-inches.

(201) In an embodiment, the body **1705** has a centerline **1745**, a first length **1750** and a second length **1755**. In an embodiment, the first length **1750** of the body **1705** may be any suitable length. In an embodiment, the first length **1750** of the body **1705** may be from about 6-inches to about 10-inches, and any range or value there between. In an embodiment, the length **1750** may be about 8-inches.

(202) In an embodiment, the second length **1755** of the body **1705** may be any suitable length. In an embodiment, the second length **1755** may be from about 8-inches to about 15-inches, and any range or value there between. In an embodiment, the second length **1755** may be about 12-inches.

(203) In an embodiment, the second end **1715** of the plug **1700** may have a flow surface **1720**. In an embodiment, the flow surface **1720** may have any suitable shape to direct the drilling mud from the drilling mud inlet of the drilling mud screen system to the drilling mud inlet of the drilling mud screen. Suitable shapes include, but are not limited to, a backward “J” shape, a curved shape, an “L” shape and any combination or variation thereof, as discussed further below. In an embodiment, the flow surface **1720** may have an “L” shape. See FIG. **17B**.

(204) Two-Piece Body

(205) FIG. **6A** illustrates a photograph of a drilling mud screen system according to an embodiment of the present invention, showing a two-piece body for the system. As shown in FIG. **6A**, the drilling mud screen system **600** has a first body **605a** having a first end **610a** and a second end **615a**, a first drilling mud inlet **620a**, a first drilling mud outlet **625a**, a first drilling mud screen access port **630a**, and an end cap **635**. The drilling mud screen system **600** has a second body **605b** having a first end **610b** and a second end **615b**, a second drilling mud inlet **620b** and a second drilling mud outlet **625b**, and a second drilling mud screen access port **630b**.

(206) In an embodiment, the first drilling mud inlet **620a** may be fluidly connected to, for example, an outlet of a drilling mud pump via a connection; and the second drilling mud outlet **625b** may be fluidly connected to an inlet of a vibrator hose via a connection. Any suitable connection may be used for the first drilling mud inlet **620a** and second drilling mud outlet **625b**. For example, suitable connections include, but are not limited to, pipe fittings and welds. Connections are well known in the art. In an embodiment, the first drilling mud inlet **620a** may be fluidly connected to, for example, an outlet of a drilling mud pump via a weld; and the second drilling mud outlet **625b** may be fluidly connected to an inlet of a vibrator hose via a weld.

(207) As shown in FIG. **6A**, the drilling mud screen access port **630** of the drilling mud screen system **600** may be closed with an end cap **635** via a connection. Any suitable connection may be used. For example, suitable connections include, but are not limited to, pipe fittings. Connections are well known in the art.

(208) In an embodiment, the drilling mud screen access port **630** of the drilling mud screen system **600** may be sealed with an end cap **635** via an O-ring. Any suitable O-ring may be used. For example, suitable O-rings include, but are not limited to, 300 Series O-rings. O-rings are well known in the art.

(209) In an embodiment, the end cap **635** of the drilling mud screen system **600** may comprise a cap, an O-ring and a pipe collar. In an embodiment, the end cap may be a five-inch 1002 WECO cap with an O-ring.

(210) FIG. **6B** illustrates a photograph of the exemplary drilling mud screen system of FIG. **6A**, showing a second drilling mud outlet **625b**.

(211) FIG. **6C** illustrates a photograph of the exemplary drilling mud screen system of FIGS. **6A-**

6B.

(212) FIG. 6D illustrates a photograph of the exemplary drilling mud screen system of FIGS. 6A-6C, showing a detailed view of a first body **605a** of the drilling mud screen system **600**. In an embodiment, the first body **605a** may be a five-inch 1002 WECO Y-housing.

(213) Standard Single Inlet and Optional Reduced Angle Inlet Version

(214) FIG. 7A illustrates an upper, cross-sectional view of a drilling mud screen system **700** according to an embodiment of the present invention, showing a standard single-inlet drilling mud system.

(215) FIG. 19 illustrates a cross-sectional view of the drilling mud screen system in a monitoring configuration **1900** according to an embodiment of the present invention, showing an optional transducer subassembly **19100**.

(216) FIG. 21A illustrates an upper view of a mud screen system **2100** according to an embodiment of the present invention, showing an optional two-piece body for the system; and FIG. 21B illustrates a detailed, cross-sectional view of A-A of FIG. 21A, showing an entry angle of about 30 degrees.

(217) FIG. 23 illustrates a cross-sectional view of a mud screen system **2300** according to an embodiment of the present invention, showing an optional drilling mud screen insert **23105** inserted into a drilling mud screen **2340**.

(218) As shown in FIGS. 7A, 19 and 23, the drilling mud screen system **700**, **1900**, **2100**, **2300** has a first body **705a**, **1905a**, **2105a**, **2305a** having a first end **710a**, **1910a**, **2110a**, **2310a** and a second end **715a**, **1915a**, **2115a**, **2315a**, a first drilling mud inlet **720a**, **1920a**, **2120a**, **2320a** and a first drilling mud outlet **725a**, **1925a**, **2125a**, **2325a**, an end cap **735**, **1935**, **2135**, **2335**, and a first drilling mud screen access port **730a**, **1930a**, **2130a**, **2330a**. The drilling mud screen system **700**, **1900**, **2100**, **2300** has a second body **705b**, **1905b**, **2105b**, **2305b** having a first end **710b**, **1910b**, **2110b**, **2310b** and a second end **715b**, **1915b**, **2115b**, **2315b**, a second drilling mud inlet **720b**, **1920b**, **2120b**, **2320b**, a second drilling mud outlet **725b**, **1925b**, **2125b**, **2325b**, and a second drilling mud screen access port **730b**, **1930b**, **2130b**, **2330b**.

(219) In an embodiment, the first drilling mud inlet **720a**, **1930a**, **2130a**, **2330a** may be fluidly connected to, for example, an outlet of a drilling mud pump via a connection; and the second drilling mud outlet **725b**, **1925b**, **2125b**, **2325b** may be fluidly connected to an inlet of a vibrator hose via a connection. Any suitable connection may be used for the first drilling mud inlet **720a**, **1920a**, **2130a**, **2320a** and second drilling mud outlet **725b**, **1925b**, **2125b**, **2325b**. For example, suitable connections include, but are not limited to, pipe fittings and welds. Connections are well known in the art. In an embodiment, the first drilling mud inlet **720a**, **1920a**, **2120a**, **2320a** may be fluidly connected to, for example, an outlet of a drilling mud pump via a weld; and the second drilling mud outlet **725b**, **1925b**, **2125b**, **2325b** may be fluidly connected to an inlet of a vibrator hose via a weld.

(220) In an embodiment, the first body **705a**, **1905a**, **2105a**, **2305a** and the second body **705b**, **1905b**, **2105b**, **2305b** may be fluidly connected by a connection. Any suitable connection may be used for the first body **705a**, **1905a**, **2105a**, **2305a** and the second body **705b**, **1905b**, **2105b**, **2305b**. For example, suitable connections include, but are not limited to, pipe fittings. Connections are well known in the art. In an embodiment, the first body **705a**, **1905a**, **2105a**, **2305a** and the second body **705b**, **1905b**, **2105b**, **2305b** may be fluidly connected by a union. In an embodiment, the union may be a five-inch 1002 WECO union.

(221) In an embodiment, the first body **705a**, **1905a**, **2105a**, **2305a** and the second body **705b**, **1905b**, **2105b**, **2305b** of the drilling mud screen system **700**, **1900**, **2100**, **2300** may be constructed of any suitable material. For example, suitable materials include, but are not limited to, any alloy steel suitable for a drilling mud application. In an embodiment, the first body **705a**, **1905a**, **2105a**, **2305a** and the second body **705b**, **1905b**, **2105b**, **2305b** may be constructed of an AISI 4130/75k yield or equivalent material. See e.g., FIGS. 6A-6D. In an embodiment, the inner surface of the

first body **705a, 1905a, 2105a, 2305a** and the second body **705b, 1905b, 2105b, 2305b** may be unpainted. See e.g., FIG. 6D. In an embodiment, the outer surface of the first body **705a, 1905a, 2105a, 2305a** and the second body **705b, 1905b, 2105b, 2305b** may be painted. See e.g., FIGS. 6A-6D.

(222) In an embodiment, the drilling mud screen system has a length **750, 1950, 2150, 2350**. The length **750, 1950, 2150, 2350** may be any suitable length. In an embodiment, the length **750, 1950, 2150, 2350** may be from about 40-inches to about 80-inches, and any range or value there between. In an embodiment, the length **750, 1950, 2150, 2350** may be about 56-inches.

(223) In an embodiment, the first body **705a, 1905a, 2105a, 2305a** has a first centerline **745a, 1945a, 2145a, 2345a** and a first length **750a, 1950a, 2150a, 2350a**. In an embodiment, the first centerline **745a, 1945a, 2145a, 2345a** extends through the center of the first drilling mud screen access port **730a, 1930a, 2130a, 2330a** to the first drilling mud outlet **725a, 1925a, 2125a, 2325a**. The first length **750a, 1950a, 2150a, 2350a** of the first body **705a, 1905a, 2105a, 2305a** may be any suitable length. In an embodiment, the first length **750a, 1950a, 2150a, 2350a** of the first body **705a, 1905a, 2105a, 2305a** may be from about 20-inches to about 40-inches, and any range or value there between. In an embodiment, the first length **750a, 1950a, 2150a, 2350a** may be about 27-inches or 30-inches.

(224) In an embodiment, the first body **705a, 1905a, 2105a, 2305a** has a second centerline **755, 1955, 2155, 2355** and a third length **750c, 1950c, 2150c, 2350c**. In an embodiment, the second centerline **755, 1955, 2155, 2355** extends through the center of the first drilling mud inlet **720a, 1920a, 2120a, 2320a** to the first centerline **745a, 1945a, 2145a, 2345a** of the first body **705a, 1905a, 2105a, 2305a**. The third length **750c, 1950c, 2150c, 2350c** of the first body **705a, 1905a, 2105a, 2305a** may be any suitable length.

(225) In an embodiment, the third length **750c, 1950c, 2350c** of the first body **705a, 1905a, 2305a** may be from about 10-inches to about 20-inches, and any range or value there between. In an embodiment, the third length **750c, 1950c, 2350c** may be about 14-inches or 16-inches.

(226) In an embodiment, the third length **2150c** of the first body **2105a** may be from about 20-inches to about 40-inches, and any range or value there between. In an embodiment, the third length **2150c** may be about 25-inches or 30-inches.

(227) In an embodiment, the first centerline **745a, 1945a, 2145a, 2345a** and the second centerline **755, 1955, 2155, 2355** of the first body **705a, 1905a, 2105a, 2305a** form a first angle **760, 1960, 2160, 2360**.

(228) In an embodiment, the first angle **760, 1960, 2360** may be from about 30-degrees to about 120-degrees, and any range or value there between. In an embodiment, the first angle **760, 1960, 2360** may be from about 45-degrees to about 60-degrees. In an embodiment, the first angle **760, 1960, 2360** may be about 90-degrees.

(229) In an embodiment, the first body **2105a** may be modified to reduce the entry angle **2160** of the first drilling mud inlet **2120**, resulting in increased flow efficiency and decreased erosion. In an embodiment, the first angle **2160** may be from about 20-degrees to about 120-degrees, and any range or value there between. In an embodiment, the first angle **2160** may be about 30-degrees.

(230) In an embodiment, the first drilling mud inlet **720a, 1920a, 2120a, 2320a** may be offset from a first end **710a, 1910a, 2110a, 2310a** of the first body **705a, 1905a, 2105a, 2305a**. The first drilling mud inlet **720a, 1920a, 2120a, 2320a** may be offset from a first end **710a, 1910a, 2110a, 2310a** of the first body **705a, 1905a, 2105a, 2305a** at any suitable distance. In an embodiment, the second centerline **755, 1955, 2155, 2355** may be offset from the first end **710a, 1910a, 2310a** of the first body **705a, 1905a, 2105a, 2305a** from about 15-inches to about 20-inches, and any range or value there between. In an embodiment, the second centerline **755, 1955, 2155, 2355** may be offset from the first end **710a, 1910a, 2110a, 2310a** of the first body **705a, 1905a, 2105a, 2305a** about 18-inches.

(231) In an embodiment, the first drilling mud inlet **720a, 1920a, 2120a, 2320a** may have any

suitable first inner diameter **765a, 1965a, 2165a, 2365a**; and the first drilling mud inlet **720a, 1920a, 2120a, 2320a** may have any suitable first outer diameter **770a, 1970a, 2170a, 2370a**. In an embodiment, the first inner diameter **765a, 1965a, 2165a, 2365a** of the first drilling mud inlet **720a, 1920a, 2120a, 2320a** may be from about 3-inches to about 5-inches, and any range or value there between. In an embodiment, the first inner diameter **765a, 1965a, 2165a, 2365a** of the first drilling mud inlet **720a, 1920a, 2120a, 2320a** may be about 4-inches.

(232) In an embodiment, the first outer diameter **770a, 1970a, 2170a, 2370a** of the first drilling mud inlet **720a, 1920a, 2120a, 2320a** may be from about 4.5-inches to about 6.5-inches, and any range or value there between. In an embodiment, the first outer diameter **770a, 1970a, 2170a, 2370a** of the first drilling mud inlet **720a, 1920a, 2120a, 2320a** may be about 5.5-inches.

(233) In an embodiment, the second body **705b, 1905b, 2105b, 2305b** has a second centerline **745b, 1945b, 2135b, 2345b** and a second length **750b, 1950b, 2150b, 2350b**. In an embodiment, the second centerline **745b, 1945b, 2145b, 2345b** extends through the center of the second drilling mud screen access port **730b, 1930b, 2130b, 2330b** (and the second drilling mud inlet **720b, 1920b, 2120b, 2320b**) to the second drilling mud outlet **725b, 1925b, 2125b, 2325b**. The second length **750b, 1950b, 2150b, 2350b** of the second body **705b, 1905b, 2105b, 2305b** may be any suitable length. In an embodiment, the second length **750b, 1950b, 2150b, 2350b** of the second body **705b, 1905b, 2105b, 2305b** may be from about 20-inches to about 40-inches, and any range or value there between. In an embodiment, the second length **750b, 1950b, 2150b, 2350b** may be about 25-inches.

(234) In an embodiment, the second drilling mud inlet **720b, 1920b, 2120b, 2320b** may have any suitable second inner diameter **765b, 1965b, 2165b, 2365b**; and the second drilling mud inlet **720b, 1920b, 2120b, 2320b** may have any suitable second outer diameter **770b, 1970b, 2170b, 2370b**. In an embodiment, the second inner diameter **765b, 1965b, 2165b, 2365b** of the second drilling mud inlet **720b, 1920b, 2120b, 2320b** may be from about 3-inches to about 5-inches, and any range or value there between. In an embodiment, the second inner diameter **765b, 1965b, 2165b, 2365b** of the second drilling mud inlet **720b, 1920b, 2120b, 2320b** may be about 4-inches.

(235) In an embodiment, the second outer diameter **770b, 1970b, 2170b, 2370b** of the second drilling mud inlet **720b, 1920b, 2120b, 2320b** may be from about 4.5-inches to about 6.5-inches, and any range or value there between. In an embodiment, the second outer diameter **770b, 1970b, 2170b, 2370b** of the second drilling mud inlet **720b, 1920b, 2120b, 2320b** may be about 5.5-inches.

(236) In an embodiment, the first body **705a, 1905a, 2105a, 2305a** has a first portion **775, 1975, 2175, 2375** and the second body **705b, 1905b, 2105b, 2305b** has a second portion **780, 1980, 2180, 2380**. In an embodiment, the first portion **775, 1975, 2175, 2375** of the first body **705a, 1905a, 2105a, 2305a** may have a first inner diameter **785, 1985, 2185, 2385** and an outer diameter **795, 1995, 2195, 2395**; and the second portion **780, 1980, 2180, 2380** of the second body **705b, 1905b, 2105b, 2305b** may have a second inner diameter **790, 1990, 2190, 2390** and an outer diameter **795, 1995, 2195, 2395**.

(237) In an embodiment, the first inner diameter **785, 1985, 2185, 2385** of the first body **705a, 1905a, 2105a, 2305a** may be from about 3-inches to about 5-inches, and any range or value there between. In an embodiment, the first inner diameter **785, 1985, 2185, 2385** of the first body **705a, 1905a, 2105a, 2305a** may be about 4-inches.

(238) In an embodiment, the first drilling mud outlet **725a, 1925a, 2125a, 2325a** may have any suitable first inner diameter **765a, 1965a, 2165a, 2365a**; and the first drilling mud outlet **725a, 1925a, 2125a, 2325a** may have any suitable first outer diameter **770a, 1970a, 2170a, 2370a**. In an embodiment, the first inner diameter **765a, 1965a, 2165a, 2365a** of the first drilling mud outlet **725a, 1925a, 2125a, 2325a** may be from about 3-inches to about 5-inches, and any range or value there between. In an embodiment, the first inner diameter **765a, 1965a, 2165a, 2365a** of the first drilling mud outlet **725a, 1925a, 2125a, 2325a** may be about 4-inches.

(239) In an embodiment, the first outer diameter **770a, 1970a, 2170a, 2370a** of the first drilling

mud outlet **725a**, **1925a**, **2125a**, **2325a** may be from about 4.5-inches to about 6.5-inches, and any range or value there between. In an embodiment, the first outer diameter **770a**, **1970a**, **2170a**, **2370a** of the first drilling mud outlet **725a**, **1925a**, **2125a**, **2325a** may be about 5-inches.

(240) In an embodiment, the second inner diameter **790**, **1990**, **2190**, **2390** of the second body **705b**, **1905b**, **2105b**, **2305b** may be from about 3-inches to about 5-inches, and any range or value there between. In an embodiment, the second inner diameter **790**, **1990**, **2190**, **2390** of the second body **705b**, **1905b**, **2105b**, **2305b** may be about 4-inches.

(241) In an embodiment, a second portion **780**, **1980**, **2180**, **2380** of the second body **705b**, **1905b**, **2105b**, **2305b** may have a second inner diameter **790**, **1990**, **2190**, **2390** to provide a high flow rate of drilling mud through the drilling mud screen **740**, **1940**, **2140**, **2340**. In an embodiment, the second inner diameter **790**, **1990**, **2190**, **2390** of the second body **705b**, **1905b**, **2105b**, **2305b** may be from about 3.5-inches to about 5.5-inches, and any range or value there between. In an embodiment, the second inner diameter **790**, **1990**, **2190**, **2390** of the second body **705b**, **1905b**, **2105b**, **2305b** may be from about 4.5-inches to about 5.5-inches, and any range or value there between.

(242) In an embodiment, the first outer diameter **795**, **1995**, **2195**, **2395** of the first portion **775**, **1975**, **2175**, **2375** of the first body **705a**, **1905a**, **2105a**, **2305a** and/or the second portion **780**, **1980**, **2180**, **2380** of the second body **705b**, **1905b**, **2105b**, **2305b** may be from about 5.5-inches to about 7.5-inches, and any range or value there between. In an embodiment, the first outer diameter **795**, **1995**, **2195**, **2395** of the first portion **775**, **1975**, **2175**, **2375** of the first body **705a**, **1905a**, **2105a**, **2305a** and/or the second portion **780**, **1980**, **2180**, **2380** of the second body **705b**, **1905b**, **2105b**, **2305b** may be about 6.5-inches.

(243) In an embodiment, the second drilling mud outlet **725b**, **1925b**, **2125b**, **2325b** may have any suitable second inner diameter **765b**, **1965b**, **2165b**, **2365b**; and the second drilling mud outlet **725b**, **1925b**, **2125b**, **2325b** may have any suitable second outer diameter **770b**, **1970b**, **2170b**, **2370b**. In an embodiment, the second inner diameter **765b**, **1965b**, **2165b**, **2365b** of the second drilling mud outlet **725b**, **1925b**, **2125b**, **2325b** may be from about 3-inches to about 5-inches, and any range or value there between. In an embodiment, the second inner diameter **765b**, **1965b**, **2165b**, **2365b** of the second drilling mud outlet **725b**, **1925b**, **2125b**, **2325b** may be about 4-inches.

(244) In an embodiment, the second outer diameter **770b**, **1970b**, **2170b**, **2370b** of the second drilling mud outlet **725b**, **1925b**, **2125b**, **2325b** may be from about 4.5-inches to about 6.5-inches, and any range or value there between. In an embodiment, the second outer diameter **770b**, **1970b**, **2170b**, **2370b** of the second drilling mud outlet **725b**, **1925b**, **2125b**, **2325b** may be about 5.5-inches.

(245) Optional Double Inlet

(246) FIG. 7B illustrates an upper, cross-sectional view of a drilling mud screen system according to an embodiment of the present invention, showing an optional double-inlet drilling mud system.

(247) As shown in FIG. 7B, the drilling mud screen system **700** has a first body **705a** having a first end **710a** and a second end **715a**, a first drilling mud inlet **720a**, an optional first drilling mud inlet **720a'** and a first drilling mud outlet **725a**, an end cap **735**, and a first drilling mud screen access port **730a**. The drilling mud screen system **700** has a second body **705b** having a first end **710b** and a second end **715b**, a second drilling mud inlet **720b**, a second drilling mud outlet **725b**, and a second drilling mud screen access port **730b**.

(248) In an embodiment, the first drilling mud inlet **720a** and the optional first drilling mud inlet **720a'** may be fluidly connected to, for example, an outlet of a drilling mud pump via a connection; and the second drilling mud outlet **725b** may be fluidly connected to an inlet of a vibrator hose via a connection. Any suitable connection may be used for the first drilling mud inlet **720a**, the optional first drilling mud inlet **720a'** and the second drilling mud outlet **725b**. For example, suitable connections include, but are not limited to, pipe fittings and welds. Connections are well known in the art. In an embodiment, the first drilling mud inlet **720a** and the optional first drilling

mud inlet **720a'** may be fluidly connected to, for example, an outlet of a drilling mud pump via a weld; and the second drilling mud outlet **725b** may be fluidly connected to an inlet of a vibrator hose via a weld.

(249) In an embodiment, the first body **705a** and the second body **705b** may be fluidly connected by a connection. Any suitable connection may be used for the first body **705a** and the second body **705b**. For example, suitable connections include, but are not limited to, pipe fittings. Connections are well known in the art. In an embodiment, the first body **705a** and the second body **705b** may be fluidly connected by a union. In an embodiment, the union may be a five-inch 1002 WECO union.

(250) In an embodiment, the first body **705a** and the second body **705b** of the drilling mud screen system **700** may be constructed of any suitable material. For example, suitable materials include, but are not limited to, any alloy steel suitable for a drilling mud application. In an embodiment, the first body **705a** and the second body **705b** may be constructed of an AISI 4130/75k yield or equivalent material. See e.g., FIGS. **6A-6D**. In an embodiment, the inner surface of the first body **705a** and the second body **705b** may be unpainted. See e.g., FIG. **6D**. In an embodiment, the outer surface of the first body **705a** and the second body **705b** may be painted. See e.g., FIGS. **6A-6D**.

(251) In an embodiment, the drilling mud screen system has a length **750**. The length **750** may be any suitable length. In an embodiment, the length **750** may be from about 40-inches to about 80-inches, and any range or value there between. In an embodiment, the length **750** may be about 56-inches.

(252) In an embodiment, the first body **705a** has a first centerline **745a** and a first length **750a**. In an embodiment, the first centerline **745a** extends through the center of the first drilling mud screen access port **730a** to the first drilling mud outlet **725a**. The first length **750a** of the first body **705a** may be any suitable length. In an embodiment, the first length **750a** of the first body **705a** may be from about 20-inches to about 40-inches, and any range or value there between. In an embodiment, the first length **750a** may be about 30-inches.

(253) In an embodiment, the first body **705a** has a second centerline **755** and a third length **750c**. In an embodiment, the second centerline **755** extends through the center of the first drilling mud inlet **720a** to the first centerline **745a** of the first body **705a**. The third length **750c** of the first body **705a** may be any suitable length. In an embodiment, the third length **750c** of the first body **705a** may be from about 10-inches to about 20-inches, and any range or value there between. In an embodiment, the third length **750c** may be about 14-inches or 16-inches.

(254) In an embodiment, the first body **705a** has a second centerline **755** and a third length **750c**, and an optional second centerline **755'** and an optional third length **750c'**. In an embodiment, the second centerline **755** extends through the center of the first drilling mud inlet **720a** to the first centerline **745a** of the first body **705a**. In an embodiment, the optional second centerline **755'** extends through the center of the optional first drilling mud inlet **720a'** to the first centerline **745a** of the first body **705a**. The third length **750c** of the first body **705a** may be any suitable length; and the optional third length **750c'** of the first body **705a** may be any suitable length.

(255) In an embodiment, the third length **750c** of the first body **705a** may be from about 10-inches to about 20-inches, and any range or value there between. In an embodiment, the third length **750c** may be about 14-inches or 16-inches.

(256) In an embodiment, the optional third length **750c'** of the first body **705a** may be from about 10-inches to about 20-inches, and any range or value there between. In an embodiment, the optional third length **750c'** may be about 14-inches or 16-inches.

(257) In an embodiment, the third length **750c** may be the same as the optional third length **750c'**. In an embodiment, the third length **750c** may be different from the optional third length **750c'**.

(258) In an embodiment, the first centerline **745a** and the second centerline **755** of the first body **705a** form a first angle **760**. In an embodiment, the first angle **760** may be from about 30-degrees to about 120-degrees, and any range or value there between. In an embodiment, the first angle **760** may be from about 45-degrees to about 60-degrees. In an embodiment, the first angle **760** may be

about 90-degrees.

(259) In an embodiment, the first drilling mud inlet **720a** may be offset from a first end **710a** of the first body **705a**. The first drilling mud inlet **720a** may be offset from a first end **710a** of the first body **705a** at any suitable distance. In an embodiment, the second centerline **755** may be offset from the first end **710a** of the first body **705a** from about 15-inches to about 20-inches, and any range or value there between. In an embodiment, the second centerline **755** may be offset from the first end **710a** of the first body **705a** about 18-inches.

(260) In an embodiment, the first drilling mud inlet **720a** may have any suitable first inner diameter **765a**; and the first drilling mud inlet **720a** may have any suitable first outer diameter **770a**. In an embodiment, the first inner diameter **765a** of the first drilling mud inlet **720a'** may be from about 3-inches to about 5-inches, and any range or value there between. In an embodiment, the first inner diameter **765a** of the first drilling mud inlet **720a** may be about 4-inches.

(261) In an embodiment, the first centerline **745a** and the optional second centerline **755'** of the first body **705a** form an optional first angle **760'**. In an embodiment, the optional first angle **760'** may be from about 30-degrees to about 120-degrees, and any range or value there between. In an embodiment, the optional first angle **760'** may be from about 45-degrees to about 60-degrees. In an embodiment, the optional first angle **760'** may be about 90-degrees.

(262) In an embodiment, the first angle **760** may be the same as the optional first angle **760'**. In an embodiment, the first angle **760** may be different from the optional first angle **760'**.

(263) In an embodiment, the optional first drilling mud inlet **720a'** may be offset from a first end **710a** of the first body **705a**. The optional first drilling mud inlet **720a'** may be offset from a first end **710a** of the first body **705a** at any suitable distance. In an embodiment, the optional first centerline **755'** may be offset from the first end **710a** of the first body **705a** from about 15-inches to about 20-inches, and any range or value there between. In an embodiment, the optional first centerline **755'** may be offset from the first end **710a** of the first body **705a** about 18-inches.

(264) In an embodiment, the optional second centerline **755'** of the optional first drilling mud inlet **720a'** may be offset from the second centerline **755** of the first drilling mud inlet **720a** radially about the first centerline **745a** of the first body **705a** to form an optional second angle **760''**. In an embodiment, the optional second angle **760''** may be from about 30 degrees to about 120 degrees, and any range or value there between. In an embodiment, the optional second angle **760''** may be from about 45-degrees to about 120-degrees. In an embodiment, the optional second angle **760''** may be from about 90-degrees to about 120-degrees. In an embodiment, the optional second angle **760''** may be about 120-degrees. See FIG. 7B.

(265) In an embodiment, the optional first drilling mud inlet **720a'** may have any suitable optional first inner diameter **765a'**; and the optional first drilling mud inlet **720a'** may have any suitable optional first outer diameter **770a'**. In an embodiment, the optional first inner diameter **765a'** of the optional first drilling mud inlet **720a'** may be from about 3-inches to about 5-inches, and any range or value there between. In an embodiment, the optional first inner diameter **765a'** of the optional first drilling mud inlet **720a'** may be about 4-inches.

(266) In an embodiment, the first outer diameter **770a** of the first drilling mud inlet **720a** may be from about 4.5-inches to about 6.5-inches, and any range or value there between. In an embodiment, the first outer diameter **770a** of the first drilling mud inlet **720a** may be about 5.5-inches.

(267) In an embodiment, the optional first outer diameter **770a'** of the optional first drilling mud inlet **720a'** may be from about 4.5-inches to about 6.5-inches, and any range or value there between. In an embodiment, the optional first outer diameter **770a'** of the optional first drilling mud inlet **720a'** may be about 5.5-inches.

(268) In an embodiment, the second body **705b** has a second centerline **745b** and a second length **750b**. In an embodiment, the second centerline **745b** extends through the center of the second drilling mud screen access port **730b** (and the second drilling mud inlet **720b**) to the second drilling

mud outlet **725b**. The second length **750b** of the second body **705b** may be any suitable length. In an embodiment, the second length **750b** of the second body **705b** may be from about 20-inches to about 40-inches, and any range or value there between. In an embodiment, the second length **750b** may be about 25-inches.

(269) In an embodiment, the second drilling mud inlet **720b** may have any suitable second inner diameter **765b**; and the second drilling mud inlet **720b** may have any suitable second outer diameter **770b**. In an embodiment, the second inner diameter **765b** of the second drilling mud inlet **720b** may be from about 3-inches to about 5-inches, and any range or value there between. In an embodiment, the second inner diameter **765b** of the second drilling mud inlet **720b** may be about 4-inches.

(270) In an embodiment, the second outer diameter **770b** of the second drilling mud inlet **720b** may be from about 4.5-inches to about 6.5-inches, and any range or value there between. In an embodiment, the second outer diameter **770b** of the second drilling mud inlet **720b** may be about 5.5-inches.

(271) In an embodiment, the first body **705a** has a first portion **775** and the second body **705b** has a second portion **780**. In an embodiment, the first portion **775** of the first body **705a** may have a first inner diameter **785** and an outer diameter **795**; and the second portion **780** of the second body **705b** may have a second inner diameter **790** and an outer diameter **795**.

(272) In an embodiment, the first inner diameter **785** of the first body **705a** may be from about 3-inches to about 5-inches, and any range or value there between. In an embodiment, the first inner diameter **785** of the first body **705a** may be about 4-inches.

(273) In an embodiment, the first drilling mud outlet **725a** may have any suitable first inner diameter **765a**; and the first drilling mud outlet **725a** may have any suitable first outer diameter **770a**. In an embodiment, the first inner diameter **765a** of the first drilling mud outlet **725a** may be from about 3-inches to about 5-inches, and any range or value there between. In an embodiment, the first inner diameter **765a** of the first drilling mud outlet **725a** may be about 4-inches.

(274) In an embodiment, the first outer diameter **770a** of the first drilling mud outlet **725a** may be from about 4.5-inches to about 6.5-inches, and any range or value there between. In an embodiment, the first outer diameter **770a** of the first drilling mud outlet **725a** may be about 5-inches.

(275) In an embodiment, the second inner diameter **790** of the second body **705b** may be from about 3-inches to about 5-inches, and any range or value there between. In an embodiment, the second inner diameter **790** of the second body **705b** may be about 4-inches.

(276) In an embodiment, a second portion **780** of the second body **705b** may have a second inner diameter **790** to provide a high flow rate of drilling mud through the drilling mud screen **740**. In an embodiment, the second inner diameter **790** of the second body **705b** may be from about 3.5-inches to about 5.5-inches, and any range or value there between. In an embodiment, the second inner diameter **790** of the second body **705b** may be from about 4.5-inches to about 5.5-inches, and any range or value there between.

(277) In an embodiment, the first outer diameter **795** of the first portion **775** of the first body **705a** and/or the second portion **780** of the second body **705b** may be from about 5.5-inches to about 7.5-inches, and any range or value there between. In an embodiment, the first outer diameter **795** of the first portion **775** of the first body **705a** and/or the second portion **780** of the second body **705b** may be about 6.5-inches.

(278) In an embodiment, the second drilling mud outlet **725b** may have any suitable second inner diameter **765b**; and the second drilling mud outlet **725b** may have any suitable second outer diameter **770b**. In an embodiment, the second inner diameter **765b** of the second drilling mud outlet **725b** may be from about 3-inches to about 5-inches, and any range or value there between. In an embodiment, the second inner diameter **765b** of the second drilling mud outlet **725b** may be about 4-inches.

(279) In an embodiment, the second outer diameter **770b** of the second drilling mud outlet **725b** may be from about 4.5-inches to about 6.5-inches, and any range or value there between. In an embodiment, the second outer diameter **770b** of the second drilling mud outlet **725b** may be about 5.5-inches.

(280) Optional Transducer Subassembly for Two-Piece Body

(281) FIG. **19** illustrates a cross-sectional view of the drilling mud screen system in a monitoring configuration **1900** according to an embodiment of the present invention, showing an optional transducer subassembly **19100**. As shown in FIG. **19**, the drilling mud screen system **19200** has a first body **1905a** having a first end **1910a** and a second end **1915a**, a first drilling mud inlet **1920a** and a first drilling mud outlet **1925a**, an end cap **1935**, a first drilling mud screen access port **1930a**, and an optional transducer subassembly **19100**.

(282) As shown in FIGS. **19** and **28**, the drilling mud inlet **1920** of the drilling mud screen system **19200**, **28200** may be fluidly connected to a drilling mud outlet **28125** of the transducer subassembly **19110**, **28100** via a connection. Any suitable connection may be used for the drilling mud inlet **1920** and the drilling mud outlet **28125**. For example, suitable connections include, but are not limited to, pipe fittings and welds. Connections are well known in the art. In an embodiment, the drilling mud inlet **1920** of the drilling mud screen system **19200**, **28200** may be fluidly connected to a drilling mud outlet **28125** of a transducer subassembly **19100** via a weld.

(283) FIG. **20A** illustrates an upper, right side perspective view of an optional transducer subassembly **2000** according to an embodiment of the present invention; and FIG. **20B** illustrates a side perspective view of the optional transducer subassembly of FIG. **20A**. As shown in FIGS. **20A** and **20B**, the optional transducer subassembly **2000** has a body **2005** having a first end **2010** and a second end **2015**, an inlet **2020** and an outlet **2025**, a transducer port **2030**, and a transducer **28105**. See e.g., FIG. **28**.

(284) In an embodiment, the drilling mud inlet **2020** of the optional transducer subassembly **2000** may be fluidly connected to, for example, an outlet of a drilling mud pump via a connection; and the drilling mud outlet **2025** may be fluidly connected to, for example, an inlet of a drilling mud screen system via a connection. Any suitable connection may be used for the drilling mud inlet **2020** and the drilling mud outlet **2025**. For example, suitable connections include, but are not limited to, pipe fittings and welds. Connections are well known in the art. In an embodiment, the drilling mud inlet **2020** of the optional transducer subassembly **2000** may be fluidly connected to, for example, an outlet of a drilling mud pump via a weld; and the drilling mud outlet **2025** of the optional transducer subassembly **2000** may be fluidly connected to, for example, an inlet of a drilling mud screen system via a weld.

(285) In an embodiment, the transducer access port **2030** of the optional transducer subassembly **2000** may be closed with a transducer via a fitting. Any suitable type of transducer may be used. For example, suitable types of transducers include, but are not limited to, displacement transducers, flow rate transducers, pressure transducers, temperature transducers and any combination thereof. Any suitable fitting may be used. For example, suitable fittings include, but are not limited to, pipe fittings. Fittings are well known in the art. In an embodiment, the transducer access port **2030** of the optional transducer subassembly **2000** may be closed with a pressure transducer via a 2-inch 1502 WECO union.

(286) In an embodiment, a computing device (such as a rig computer) may include a bus that directly or indirectly couples the following devices: memory, one or more processors, one or more presentation components, one or more input/output (I/O) ports, I/O components, a user interface and a power supply. The computing device may include a variety of computer-readable media. The memory may include computer-storage media in the form of volatile and/or nonvolatile memory. The presentation component(s) present data indications to a user or other device. The user interface allows the user to input/output information to/from the computing device. The one or more I/O ports may allow the computing device to be logically coupled to other devices including a

transducer **28105**, and other I/O components, some of which may be built in. See e.g., FIG. **28**.

Examples of other I/O components include a printer, scanner, wireless device, and the like.

(287) In an embodiment, the transducer access port **2030** of the optional transducer subassembly **2000** may be sealed with an end cap via an O-ring. Any suitable O-ring may be used. For example, suitable O-rings include, but are not limited to, 300 Series O-rings. O-rings are well known in the art.

(288) In an embodiment, the body **2005** of the optional transducer subassembly **2000** may be constructed of any suitable material. For example, suitable materials include, but are not limited to, any alloy steel suitable for a drilling mud application. In an embodiment, the body **2005** may be constructed of an American Iron and Steel Industry (AISI) **4130/75k** yield or equivalent material. See e.g., FIG. **2**. In an embodiment, the inner surface of the body **2005** may be unpainted. In an embodiment, the outer surface of the body **2005** may be painted.

(289) In an embodiment, the body **2005** has a first centerline **2045** and a length **2050**. In an embodiment, the first centerline **2045** extends through the center of the drilling mud inlet **2020** to the drilling mud outlet **2025**. The length **2050** of the body **2005** may be any suitable length. In an embodiment, the length **2050** of the body **2005** may be from about 10-inches to about 30-inches, and any range or value there between. In an embodiment, the length **2050** may be about 12-inches.

(290) In an embodiment, the body **2005** has a second centerline **2055**. In an embodiment, the second centerline **2055** extends through the center of the transducer access port **2030** to the first centerline **2045**.

(291) In an embodiment, the first centerline **2045** and the second centerline **2055** form a first angle **2060**. In an embodiment, the first angle **2060** may be from about 20-degrees to about 120-degrees, and any range or value there between. In an embodiment, the first angle **2060** may be about 45-degrees. In an embodiment, the first angle **2060** may be about 90-degrees.

(292) In an embodiment, the transducer access port **2030** may be offset from a first end **2010** of the body **2005**. The transducer access port **2030** may be offset from a first end **2010** of the body **2005** at any suitable distance. In an embodiment, the second centerline **2055** may be offset from the first end **2010** of the body **2005** from about 6-inches to about 15-inches, and any range or value there between. In an embodiment, the second centerline **2055** may be offset from the first end **2010** of the body **2005** about 7-inches.

(293) In an embodiment, the transducer access port **2030** may have any suitable inner diameter. In an embodiment, the inner diameter of the transducer access port **2030** may be from about 1-inches to about 3-inches, and any range or value there between. In an embodiment, the inner diameter of the transducer access port **2030** may be about 2-inches.

(294) In an embodiment, the outer diameter of the transducer access port **2030** may be from about 1.5-inches to about 3.5-inches, and any range or value there between. In an embodiment, the outer diameter of the transducer access port **2030** may be about 2.5-inches.

(295) In an embodiment, the drilling mud inlet **2020** may have any suitable inner diameter **2065**; and the drilling mud inlet **2020** may have any suitable outer diameter **2070**. In an embodiment, the inner diameter **2065** of the drilling mud inlet **2020** may be from about 3-inches to about 5-inches, and any range or value there between. In an embodiment, the inner diameter **2065** of the drilling mud inlet **2020** may be about 4-inches.

(296) In an embodiment, the outer diameter **2070** of the drilling mud inlet **2020** may be from about 4.5-inches to about 6.5-inches, and any range or value there between. In an embodiment, the outer diameter **2070** of the drilling mud inlet **2020** may be about 5.5-inches.

(297) In an embodiment, the drilling mud outlet **2025** may have any suitable inner diameter **2065**; and the drilling mud outlet **2025** may have any suitable outer diameter **2070**. In an embodiment, the inner diameter **2065** of the drilling mud outlet **2025** may be from about 3-inches to about 5-inches, and any range or value there between. In an embodiment, the inner diameter **2065** of the drilling mud outlet **2025** may be about 4-inches.

(298) In an embodiment, the outer diameter **2070** of the drilling mud outlet **2025** may be from about 4.5-inches to about 6.5-inches, and any range or value there between. In an embodiment, the outer diameter **2070** of the drilling mud outlet **2025** may be about 5.5-inches.

(299) Drilling Mud Screen

(300) FIG. 5A illustrates an upper, cross-sectional view of a drilling mud screen **500** according to an embodiment of the present invention, as discussed above. FIG. 5B illustrates a detailed view of A-A of FIG. 5A; FIG. 5C illustrates a detailed view of B of FIG. 5A; and FIG. 5D illustrates a detailed view of C of FIG. 5A. FIG. 5E illustrates an upper, right side perspective view of the drilling mud screen **500** of FIG. 5A.

(301) Optional Drilling Mud Screen

(302) FIG. 22A illustrates an end view of an optional drilling mud screen **2200** according to an embodiment of the present invention; FIG. 22B illustrates a detailed, cross-sectional view of A-A of FIG. 22A, showing an optional drilling mud screen insert **22105**, and optional first end retaining ring **22110**, an optional filter length **22115**, and an optional retaining ring **22120**; FIG. 22C illustrates a detailed view of B of FIG. 22B; FIG. 22D illustrates a detailed, cross-sectional view of C-C of FIG. 22C; and FIG. 22E illustrates an upper, right perspective view of the drilling mud screen **2200** of FIGS. 22A-22B.

(303) As shown in FIG. 22B, the drilling mud screen **2200** has a body **2205** having a first end **2210** and a second end **2215**, a drilling mud inlet **2220**, a drilling mud outlet **2225**, a filter **2230** and an end cap **2235**.

(304) In an embodiment, the drilling mud inlet **2220** may be fluidly connected to, for example, an outlet of a drilling mud pump via a connection; and the drilling mud outlet **2225** may be fluidly connected to an inlet of a vibrator hose via a connection. Any suitable connection may be used for the drilling mud inlet **2220** and the drilling mud outlet **2225**. For example, suitable connections include, but are not limited to, pipe fittings and welds. Connections are well known in the art. In an embodiment, the drilling mud inlet **2220** may be fluidly connected to, for example, an outlet of a drilling mud pump via a weld; and the drilling mud outlet **2225** may be fluidly connected to an inlet of a vibrator hose via a weld.

(305) In an embodiment, the body **2205** of the drilling mud screen **2200** may be constructed of any suitable material. For example, suitable materials include, but are not limited to, any alloy steel or tool steel. In an embodiment, the body **2205** may be constructed of an AISI 4145 or equivalent material. See e.g., FIGS. 5A-5E. In an embodiment, the body **2205** may be constructed of tool steel or equivalent material.

(306) In an embodiment, the body **2205** of the drilling mud screen **2200** may have a hardened coating to reduce washing (i.e., erosion) of the screen **2200**. For example, suitable hardened coatings include, but are not limited to, any Carbide coating or equivalent. In an embodiment, the body **2205** may have a Carbide coating with about 6% Cobalt binder or equivalent material.

(307) In an embodiment, the body **2205** of the drilling mud screen **2200** has a centerline **2245** and a length **2250**. In an embodiment, the centerline **2245** extends through the center of the drilling mud screen inlet **2220** to the end cap **2235**. The length **2250** of the body **2205** may be any suitable length. In an embodiment, the length **2250** of the body **2205** may be from about 20-inches to about 30-inches, and any range or value there between. In an embodiment, the length **2250** may be about 25-inches.

(308) In an embodiment, the drilling mud inlet **2220** of the drilling mud screen **2200** may have any suitable inner diameter **2265**; and the drilling mud inlet **2220** may have any suitable outer diameter **2270**. In an embodiment, the inner diameter **2265** of the drilling mud inlet **2220** may be from about 3-inches to about 5-inches, and any range or value there between. In an embodiment, the inner diameter **2265** of the drilling mud inlet **2220** may be about 3.9-inches.

(309) In an embodiment, the outer diameter **2270** of the drilling mud inlet **2220** may be from about 4-inches to about 6-inches, and any range or value there between. In an embodiment, the outer

diameter **2270** of the drilling mud inlet **2220** may be about 4-inches.

(310) In an embodiment, the body **2205** of the drilling mud screen **2200** has a first portion **2275** and a second portion **2280**. In an embodiment, the first portion **2275** of the body **2205** has a first length **22125**; and the second portion **2280** of the body **2205** has a second length **22130**. The first portion **2275** and the second portion **2280** may be any suitable length. In an embodiment, the first portion **2275** may have a first length **22125** from about 6-inches to about 10-inches, and any range or value there between; and the second portion **2280** may have a second length **22130** from about 14-inches to about 20-inches, and any range or value there between. In an embodiment, the first portion **2275** may have a first length **22125** of about 7.5-inches; and the second portion **2280** may have a second length **22130** of about 17.5-inches.

(311) In an embodiment, the second portion **2280** of the body **2205** has a first section **22135**, a second section **22145** and a third section **22155**. In an embodiment, the first section **22135** has a third length **22140**, the second section **22145** has a fourth length **22150** and the third section **22155** has a fifth length **22160**. The first section **22135**, the second section **22145** and the third section **22155** may be any suitable length. In an embodiment, the first section **22135** may be up to about 20-25% longer than the second section **22145** and/or the third section **22155**, resulting in increased flow efficiency and decreased erosion.

(312) In an embodiment, the first section **22135** may have a third length **22140** from about 4-inches to about 8-inches, and any range or value there between. In an embodiment, the first section **22135** may have a third length **22140** of about 6-inches.

(313) In an embodiment, the second section **22145** may have a fourth length **22150** from about 4-inches to about 8-inches, and any range or value there between. In an embodiment, the second section **22145** may have a fourth length **22150** of about 5-inches.

(314) In an embodiment, the third section **22155** may have a fifth length **22160** from about 4-inches to about 8-inches, and any range or value there between. In an embodiment, the third section **22155** may have a fifth length **22160** of about 5-inches.

(315) In an embodiment, a second portion **2280** of the body **2205** of the drilling mud screen **2200** may have a filter **2230**. In an embodiment, the filter **2230** may comprise a plurality of rods spaced a distance apart to form a filter. In an embodiment, the distance may be less than a particle size (e.g., diameter) desired to be filtered from the drilling mud. Particle filtration is well known in the art.

(316) In an embodiment, the filter **2230** may comprise a formed sheet having drilled holes spaced a distance apart to form a filter. In an embodiment, the size of the holes (e.g., diameter) may be less than a particle size (e.g., diameter) desired to be filtered. Particle filtration is well known in the art.

(317) In an embodiment, a second portion **2280** of the body **2205** of the drilling mud screen **2200** may have a drilling mud outlet **2225**. In an embodiment, the drilling mud outlet **2225** may comprise a plurality of spaces (i.e., flow passages) between a plurality of rods. In an embodiment, the drilling mud outlet **2225** may comprise a plurality of holes (i.e., flow passages) drilled in a formed sheet.

(318) In an embodiment, a first end **2210** of a first portion **2275** of the body **2205** of the drilling mud screen **2200** may have a first inner diameter **2285**; and a second end **2215** of a second portion **2280** of the body **2205** may have a second inner diameter **2290**.

(319) In an embodiment, the first end **2210** of the first portion **2275** may be shaped to accept a puller/installer plate **975** of a drilling mud screen puller/installer tool **800, 900**, as discussed below. See e.g., FIGS. 5A, 8A & 9A.

(320) In an embodiment, the body **2205** and/or a filter **2230** of the drilling mud screen **2200** may have a tapered drilling mud flow path from a larger inner diameter (ID) to a smaller ID to reduce washing (i.e., erosion) of the screen **2200**.

(321) In an embodiment, the first inner diameter **2285** of the first end **2210** of the body **2205** of the drilling mud screen **2200** may be from about 3-inches to about 5-inches, and any range or value there between. In an embodiment, the first inner diameter **2285** of the first end **2210** of the body

2205 may be about 3.9-inches.

(322) FIG. 22D illustrates a detailed view of C-C of FIG. 22C, showing an outlet of a first portion **2275** of the body **2205** and an inlet of the second portion **2280** of the body **2205**. In an embodiment, an inner diameter of an outlet of the first portion **2275** and an inlet of the second portion **2290** of the body **2205** may be from about 2-inches to about 3-inches, and any range or value there between. In an embodiment, the inner diameter of the outlet of the first portion **2275** of the body **2205** and the inlet of the second portion **2290** of the body **2205** may be about 2.5-inches.

(323) In an embodiment, the outlet of the first portion **2275** and/or the inlet of the second portion **2290** of the body **2205** may be shaped to accept a rounded end **875, 975** of a drilling mud screen puller/installer tool **800, 900**. See e.g., FIGS. 5B, 8B & 9B. See also FIGS. 12B, 13B & 29. In an embodiment, the inlet of the second portion **2290** of the body **2205** may have an inner shoulder to provide a pushing surface for the rounded end **875, 975** of the drilling mud screen puller/installer tool **800, 900**. Id.

(324) In an embodiment, the outlet of the first portion **2275** and/or the inlet of the second portion **2280** of the body **2205** may have a means to engage **2240** a drilling mud screen puller/installer tool **800, 900**, as discussed below. See e.g., FIGS. 5A, 8A & 9A. The means to engage **2240** may be any suitable means to accept, and provide a pulling surface for, the drilling mud screen puller/installer tool **800, 900**. For example, a suitable means to engage **2240** includes, but is not limited to, a “key” opening to rotationally engage an inner shoulder. In an embodiment, the outlet of the first portion **2275** and/or the inlet of the second portion **2290** of the body **2205** may be shaped to accept a puller/installer plate **870, 970** of a drilling mud screen puller/installer tool **800, 900**. See e.g., FIGS. 5B, 8B & 9B. See also FIGS. 12A, 13A & 29. In an embodiment, the inlet of the second portion **2290** of the body **2205** may have an inner shoulder to provide a pulling surface for the puller/installer plate **870, 970** of the drilling mud screen puller/installer tool **800, 900**. Id.

(325) In an embodiment, the second inner diameter **2290** of the second end **2215** of the body **2205** of the drilling mud screen **2200** may be from about 2-inches to about 3-inches, and any range or value there between. In an embodiment, the second inner diameter **2290** of the second end **2215** of the body **2205** may be about 2.3-inches.

(326) In an embodiment, the outer surface **2295** of the first portion **2275** of the body **2205** of the drilling mud screen **2200** may be adapted to engage one or more shoulders in an inner surface of the body **2205**. In an embodiment, a first shoulder and a second shoulder of the body **2205** may be offset from a first end **2210** of the body **2205**. Cf. FIGS. 4A & 5A. The first and second shoulders may be offset from the first end **2210** of the body **2205** at any suitable distance. In an embodiment, the first shoulder may be offset from the first end **2210** of the body **2205** from about 4-inches to about 8-inches, and any range or value there between; and the second shoulder may be offset from the first end **2210** of the body **2205** from about 5-inches to about 9-inches, and any range or value there between. In an embodiment, the first shoulder may be offset from the first end **2210** of the body **2205** about 4.8-inches; and the second shoulder may be offset from the first end **2210** of the body **2205** about 6.8-inches.

(327) In an embodiment, the outer surface **2295** of the body **2205** of the drilling mud screen **2200** may be sealed against an inner surface of the body **2205** via an O-ring. Cf. FIGS. 4A & 5A. Any suitable O-ring may be used. For example, suitable O-rings include, but are not limited to, 300 Series O-rings. O-rings are well known in the art.

(328) FIG. 22C illustrates a detailed view of B of FIG. 22B, showing a detailed view of a groove for an O-ring. In an embodiment, a groove for an O-ring may be offset from a first end **2210** of the body **2205** of the drilling mud screen **2200**. The groove for the O-ring may be offset from the first end **2210** of the body **2205** at any suitable distance. In an embodiment, the groove for the O-ring may be offset from the first end **2210** of the body **2205** from about 4-inches to about 8-inches, and any range or value there between. In an embodiment, the groove for the O-ring may be offset from the first end **2210** of the body **2205** about 5.7-inches.

(329) In an embodiment, the filter **2230** may have a plurality of rods spaced a distance apart to form a filter, or, alternatively, a formed sheet having drilled holes spaced a distance apart to form a filter. In an embodiment, the plurality of rods may be tapered from a larger outer diameter (OD) to a smaller OD to encourage drilling mud flow to exit in straight lines through the drilling mud outlet **2225** (i.e., through flow passages between the plurality rods) to reduce washing (i.e., erosion) of the screen **2200**. In an embodiment, the filter **2230** may have a plurality of straight rows of holes drilled in a formed sheet to encourage drilling mud flow to exit in straight rows of strings through the drilling mud outlet **2225** (i.e., through straight flow passages of the drilled holes) to reduce washing (i.e., erosion) of the screen **2200**.

(330) In an embodiment, a first end of a filter **2230** may be connected to a second end **2215** of the body **2205** via a connection; and a second end of a filter **2230** may be connected to a first end of the end cap **2235** via a connection. Any suitable connection may be used for the drilling mud inlet **2230**. For example, suitable connections include, but are not limited to, welds. Connections are well known in the art. In an embodiment, the first end of the filter **2230** may be connected to the second end **2215** of the body **2205** via a weld; and the second end of the filter **2230** may be connected to the first end of the end cap **2235** via a weld.

(331) In an embodiment, the first end of the filter **2230** may fit into a first recess in the second end **2215** of the body **2205**; and the second end of the filter may fit into a second recess in the first end of the end cap **2235**. In an embodiment, the first recess and the second recess may be a plurality of recessed holes or a recessed groove. In an embodiment, the first recess and the second recess may be a plurality of recessed holes.

(332) In an embodiment, the filter **2230** may be held together with a retaining ring. In an embodiment, the retaining ring may have a plurality of holes to hold the plurality of rods to form the filter **2230**. In an embodiment, the plurality of rods may be connected to the plurality of holes in the retainer ring via a connection. Any suitable connection may be used for the drilling mud inlet **2230**. For example, suitable connections include, but are not limited to, welds. Connections are well known in the art. In an embodiment, the plurality of rods may be connected to the plurality of holes in the retainer ring via a weld.

(333) In an embodiment, the filter **2230**, including any retaining rings, of the drilling mud screen **2200** may be constructed of any suitable material. For example, suitable materials include, but are not limited to, any alloy steel or tool steel. In an embodiment, the filter **2230** may be constructed of 304 stainless steel material. See e.g., FIGS. 5A & 5E. In an embodiment, the filter **2230** may be constructed of AISI 4145 or equivalent material. In an embodiment, the filter **2230** may be constructed of D2 tool steel or equivalent material.

(334) In an embodiment, the filter **2230** may have a hardened coating to reduce washing (i.e., erosion) of the screen **2200**. For example, suitable hardened coatings include, but are not limited to, any Carbide coating or equivalent. In an embodiment, the filter **2230** may have a Carbide coating with about 6% Cobalt binder or equivalent material.

(335) In an embodiment, the end cap **2235** of the drilling mud screen **2200** has an inner surface **2255**. In an embodiment, the inner surface **2255** of the end cap **2235** of the drilling mud screen **200** may redirect the flow to reduce washing (i.e., erosion) of the screen **2200**. In an embodiment, the inner surface **2255** of the end cap **2235** of the drilling mud screen **2200** forms an inverted cone relative to the second end **2215** of the body **2205** of the drilling mud screen **2200** to redirect the flow. In an embodiment, the tip of the inverted cone may have a rounded or squared shape.

(336) In an embodiment, the body **2205** of the drilling mud screen **2200** has a centerline **2245** and a length **2250**. In an embodiment, the centerline **2245** extends through the center of the drilling mud screen inlet **2220** to the end cap **2235**. In an embodiment, the centerline **2245** of the body **2205** of the drilling mud screen **2200** and the inner surface **2255** of the end cap **2235** form an angle **2260**. In an embodiment, the angle **2260** may be from about 30-degrees to about 60-degrees, and any range or value there between. In an embodiment, the angle **2260** may be from about 35-degrees to about

45-degrees.

(337) In an embodiment, the end cap **2235** of the drilling mud screen **2200** may be constructed of any suitable material. For example, suitable materials include, but are not limited to, any alloy steel or tool steel. In an embodiment, the end cap **2235** may be constructed of 304 stainless steel material or equivalent material. See e.g., FIGS. **5A** & **5E**. In an embodiment, the end cap **2235** may be constructed of AISI 4155 or equivalent material. In an embodiment, the end cap **2235** may be constructed of tool steel or equivalent material.

(338) In an embodiment, the end cap **2235** of the drilling mud screen **2200** may have a hardened coating to reduce washing (i.e., erosion) of the screen **2200**. For example, suitable hardened coatings include, but are not limited to, any Carbide coating or equivalent. In an embodiment, the end cap **2235** may have a Carbide coating with about 6% Cobalt binder or equivalent material.

(339) FIG. **22E** illustrates an upper, right side perspective view of the drilling mud screen **2200** of FIGS. **22A-22B**. As shown in FIG. **33E**, the drilling mud screen **2200** has a body **2205** having a first end **2210** and a second end **2215**, a drilling mud inlet **2220**, a drilling mud outlet **2225**, a filter **2230** and an end cap **2235**. In an embodiment, the body **2205** of the drilling mud screen **2200** has a first portion **2275** and a second portion **2280**.

(340) Optional Drilling Mud Screen Insert

(341) FIG. **23** illustrates a cross-sectional view of a mud screen system according to an embodiment of the present invention, showing an optional drilling mud screen insert **23105** inserted into a drilling mud screen **2340**. As shown in FIG. **23**, the drilling mud screen system **700**, **1900**, **2100** has an optional drilling mud screen insert **23105** inserted into a drilling mud screen **2340** to reduce the washing (i.e., erosion) of the drilling mud screen **2340**. In an embodiment, the optional drilling mud screen insert **23105** may be inserted into a first end **510**, **2210** of the drilling mud screen **2340**. See e.g., FIGS. **5** & **22**. In an embodiment, the optional drilling mud screen insert **23105** may be brazed or welded to the drilling mud screen **2340**.

(342) FIG. **24A** illustrates an end view of an optional drilling mud screen insert according to an embodiment of the present invention; FIG. **24B** illustrates a detailed, cross-sectional view of A-A of FIG. **24A**, showing an inlet of the drilling mud screen insert and an outlet of the drilling mud screen insert; and FIG. **24C** illustrates an upper, right perspective view of the optional drilling mud screen insert of FIGS. **24A-24B**. As shown in FIG. **24B**, the optional drilling mud screen insert **2400** has a body **2405** having a first end **2410** and a second end **2415**, a drilling mud inlet **2420** and a drilling mud outlet **2425**.

(343) In an embodiment, the body **2405** of the optional drilling mud screen insert **2400** may be constructed of any suitable material. For example, suitable materials include, but are not limited to, any alloy steel or tool steel. In an embodiment, the body **2405** may be constructed of an AISI 4145 or equivalent material. See e.g., FIGS. **5A-5E**. In an embodiment, the body **2405** may be constructed of tool steel or equivalent material.

(344) In an embodiment, the body **2405** of the optional drilling mud screen insert **2400** may have a hardened coating to reduce washing (i.e., erosion) of the insert **2400**. For example, suitable hardened coatings include, but are not limited to, any Carbide coating or equivalent. In an embodiment, the body **2405** may have a Carbide coating with about 6% Cobalt binder or equivalent material.

(345) In an embodiment, the body **2405** of the optional drilling mud screen insert **2400** has a centerline **2445** and a length **2450**. In an embodiment, the centerline **2445** extends through the center of the drilling mud inlet **2420** to the drilling mud outlet **2425**. The length **2450** of the body **2405** may be any suitable length. In an embodiment, the length **2450** of the body **2405** may be from about 5-inches to about 10-inches, and any range or value there between. In an embodiment, the length **2450** may be about 6.9-inches.

(346) In an embodiment, the drilling mud inlet **2420** of the optional drilling mud screen insert **2400** may have any suitable inner diameter **2465**; and the drilling mud inlet **2420** may have any suitable

outer diameter **2470**. In an embodiment, the inner diameter **2465** of the drilling mud inlet **2450** may be from about 3-inches to about 5-inches, and any range or value there between. In an embodiment, the inner diameter **2465** of the drilling mud inlet **2420** may be about 3.9-inches.

(347) In an embodiment, the outer diameter **2470** of the drilling mud inlet **2420** may be from about 4-inches to about 6-inches, and any range or value there between. In an embodiment, the outer diameter **2470** of the drilling mud inlet **2420** may be about 4-inches.

(348) In an embodiment, the drilling mud outlet **2425** of the optional drilling mud screen insert **2400** may have any suitable inner diameter **2468**; and the drilling mud outlet **2425** may have any suitable outer diameter **2472**. In an embodiment, the inner diameter **2468** of the drilling mud outlet **2425** may be from about 2-inches to about 5-inches, and any range or value there between. In an embodiment, the inner diameter **2468** of the drilling mud outlet **2425** may be about 3-inches.

(349) In an embodiment, the outer diameter **2472** of the drilling mud outlet **2425** may be from about 3.5-inches to about 6-inches, and any range or value there between. In an embodiment, the outer diameter **2472** of the drilling mud outlet **2425** may be about 3.5-inches.

(350) In an embodiment, the body **2405** of the optional drilling mud screen insert **2400** has a first portion **2475** and a second portion **2480**. In an embodiment, the first portion **2475** of the body **2405** has a first length **2478**; and the second portion **2480** of the body **2405** has a second length **2482**. The first portion **2475** and the second portion **2480** may be any suitable length. In an embodiment, the first portion **2475** may have a first length **2478** from about 1-inch to about 3-inches, and any range or value there between; and the second portion **2480** may have a second length **2482** from about 3-inches to about 7-inches, and any range or value there between. In an embodiment, the first portion **2475** may have a first length **2478** of about 2-inches; and the second portion **2480** may have a second length **2482** of about 4.9-inches.

(351) In an embodiment, the first portion **2475** of the body **2405** may have a first inner diameter **2485** and a second inner diameter **2490**.

(352) In an embodiment, the first inner diameter **2485** of the first portion **2475** may have any suitable diameter. In an embodiment, the first inner diameter **2485** of the first portion **2475** may be from about 3-inches to about 5-inches, and any range or value there between. In an embodiment, the first inner diameter **2485** of the first portion **2475** may be about 3.9-inches.

(353) In an embodiment, the second inner diameter **2490** of the first portion **2475** may have any suitable diameter. In an embodiment, the second inner diameter **2490** of the first portion **2475** may be from about 2-inches to about 5-inches, and any range or value there between. In an embodiment, the second inner diameter **2490** of the first portion **2475** may be about 3-inches.

(354) In an embodiment, an outer surface of the first portion **2475** and an inner surface of the first portion **2475** form an angle **2495** over a third length **24125**. In an embodiment, the angle may be from about 10-degrees to about 20-degrees, and any range or value there between. In an embodiment, the angle **2495** may be about 15-degrees.

(355) In an embodiment, the third length **24125** may be from about 1-inch to about 2-inches, and any range or value there between. In an embodiment, the third length **24125** may be about 1.5-inches.

(356) Optional First End Retaining Ring

(357) FIG. 25 illustrates a detailed, cross-sectional view of the optional drilling mud screen **2500**, showing an optional first end retaining ring **25110**. As shown in FIG. 25, the optional drilling mud screen **2500** has a body **2505**, a drilling mud outlet **2525**, a filter **2530**, an outer surface of body **2595** and an optional first end retaining ring **25110**.

(358) As shown in FIGS. 22B and 25, the filter **2230** may be held together with an optional first end retaining ring **25110**. In an embodiment, the optional filter retaining ring **25110** may have a plurality of holes to hold the plurality of rods to form the filter **2230**. In an embodiment, the plurality of rods may be connected to the plurality of holes in the optional filter retainer ring via a connection. Any suitable connection may be used for the drilling mud inlet **2230**. For example,

suitable connections include, but are not limited to, welds. Connections are well known in the art. In an embodiment, the plurality of rods may be connected to the plurality of holes in the retainer ring via a weld.

(359) In an embodiment, the optional first end retaining ring **25110** of the optional drilling mud screen **2500** may be constructed of any suitable material. For example, suitable materials include, but are not limited to, any alloy steel or tool steel. In an embodiment, the optional first end retaining ring **25110** may be constructed of an AISI 4145 or equivalent material. See e.g., FIGS. 5A-5E. In an embodiment, the optional first end retaining ring **25110** may be constructed of D2 tool steel or equivalent material.

(360) In an embodiment, the optional first end retaining ring **25110** of the optional drilling mud screen **2500** may have a hardened coating to reduce washing (i.e., erosion) of the retaining ring **25110**. For example, suitable hardened coatings include, but are not limited to, any Carbide coating or equivalent. In an embodiment, the optional first end retaining ring **25110** may have a Carbide coating with about 6% Cobalt binder or equivalent material.

(361) In an embodiment, the optional first end retaining ring **25110** may be modified to reduce an inside surface exit angle between the first portion **2575** and the second portion **2580** of the drilling mud screen **2500**, resulting in increased flow efficiency and decreased erosion. In an embodiment, the exit angle may be about 10-degrees to about 90-degrees, and any range or value there between. In an embodiment, the exit angle may be from about 10-degrees to about 50-degrees. In an embodiment, the exit angle may be about 30-degrees.

(362) Optional Filter Retaining Ring

(363) FIG. **26A** illustrates a side view of an optional drilling mud screen system **2600** according to an embodiment of the present invention, showing an optional filter length **26115**, and an optional filter retaining ring **26120**; and FIG. **26B** illustrates a detailed, cross-sectional view of the optional drilling mud screen system **2600** of FIG. **26A**, showing an optional drilling mud screen insert **26105**, an optional filter length **26115**, and an optional filter retaining ring **26120**. As shown in FIGS. **26A** and **26B**, the optional drilling mud screen system **2600** has an optional drilling mud screen insert **26105**, an optional filter length **26115**, and an optional retaining ring **26120**.

(364) In an embodiment, the optional filter retaining ring **26120** of the optional drilling mud screen **2640** may be constructed of any suitable material. For example, suitable materials include, but are not limited to, any alloy steel or tool steel. In an embodiment, the optional filter retaining ring **26120** may be constructed of an AISI 4145 or equivalent material. See e.g., FIGS. 5A-5E. In an embodiment, the optional filter retaining ring **26120** may be constructed of D2 tool steel or equivalent material.

(365) In an embodiment, the optional filter retaining ring **26120** of the optional drilling mud screen **2640** may have a hardened coating to reduce washing (i.e., erosion) of the optional filter retaining ring **26120**. For example, suitable hardened coatings include, but are not limited to, any Carbide coating or equivalent. In an embodiment, the optional filter retaining ring **26120** may have a Carbide coating with about 6% Cobalt binder or equivalent material.

(366) In an embodiment, the optional filter retaining ring **26120** of the optional drilling mud screen **2640** may be modified to reduce inside surface entry and exit angles of the drilling mud screen **2640**, resulting in increased flow efficiency and decreased erosion. In an embodiment, the entry and exit angles may be from about 10-degrees to about 90-degrees, and any range or value there between. In an embodiment, the entry and exit angles may be from about 10-degrees to about 50-degrees. In an embodiment, the entry and exit angles may be about 30-degrees.

(367) FIG. **27A** illustrates an end view of an optional filter retaining ring **2700** according to an embodiment of the present invention; FIG. **27B** illustrates a detailed, cross-sectional view of A-A of FIG. **27A**; and FIG. **27C** illustrates a detailed, cross-sectional view of B of FIG. **27B**.

(368) As shown in FIGS. **22B** and **27A**, the filter **2230** may be held together with an optional filter retaining ring **2700**. In an embodiment, the optional filter retaining ring **2700** may have a plurality

of holes **2705** to hold the plurality of rods to form the filter **2230**. In an embodiment, the plurality of rods may be connected to the plurality of holes in the optional filter retainer ring via a connection. Any suitable connection may be used for the drilling mud inlet **2230**. For example, suitable connections include, but are not limited to, welds. Connections are well known in the art. In an embodiment, the plurality of rods may be connected to the plurality of holes in the retainer ring via a weld.

(369) In an embodiment, the optional filter retaining rings **2700** of the optional drilling mud screen **2200** may be constructed of any suitable material. For example, suitable materials include, but are not limited to, any alloy steel or tool steel. In an embodiment, the optional filter retaining rings **2700** may be constructed of 304 stainless steel material. See e.g., FIGS. 5A & 5E. In an embodiment, the optional filter retaining rings **2700** may be constructed of AISI 4145 or equivalent material. In an embodiment, the optional filter retaining rings **2700** may be constructed of D2 tool steel or equivalent material.

(370) In an embodiment, the optional filter retaining ring **2700** of the optional drilling mud screen **2220** may have a hardened coating to reduce washing (i.e., erosion) of the screen **2200**. For example, suitable hardened coatings include, but are not limited to, any Carbide coating or equivalent. In an embodiment, the optional filter retaining rings **2700** may have a Carbide coating with about 6% Cobalt binder or equivalent material.

(371) In an embodiment, the optional filter retaining ring **2700** of the optional drilling mud screen **2200** may be modified to reduce inside surface entry and exit angles of the drilling mud screen **2200**, resulting in increased flow efficiency and decreased erosion. In an embodiment, the entry and exit angles may be from about 10-degrees to about 50-degrees, and any range or value there between. In an embodiment, the entry and exit angles may be about 25-degrees or about 30-degrees.

(372) Optional Filter Length

(373) FIG. **26A** illustrates a side view of an optional drilling mud screen system **2600** according to an embodiment of the present invention, showing an optional filter length **26115**, and an optional filter retaining ring **26120**; and FIG. **26B** illustrates a detailed, cross-sectional view of the optional drilling mud screen system **2600** of FIG. **26A**, showing an optional drilling mud screen insert **26105**, an optional filter length **26115**, and an optional filter retaining ring **26120**. As shown in FIGS. **26A** and **26B**, the optional drilling mud screen system **2600** has an optional drilling mud screen insert **26105**, an optional filter length **26115**, and an optional retaining ring **26120**.

(374) As shown in FIG. **26B**, the optional drilling mud screen **2640** has a first portion **2675** and a second portion **2680**. In an embodiment, the first portion **2675** of the optional drilling mud screen **2640** has a first length **26125**; and the second portion **2680** of the optional drilling mud screen **2640** has a second length **26130**. The first portion **2675** and the second portion **2680** may be any suitable length. In an embodiment, the first portion **2675** may have a first length **26125** from about 6-inches to about 10-inches, and any range or value there between; and the second portion **2680** may have a second length **26130** from about 14-inches to about 20-inches, and any range or value there between. In an embodiment, the first portion **2675** may have a first length **26125** of about 7.5-inches; and the second portion **2680** may have a second length **26130** of about 17.5-inches.

(375) In an embodiment, the second portion **2680** of the optional drilling mud screen **2640** has a first section **26135**, a second section **26145** and a third section **26155**. In an embodiment, the first section **26135** has a third length **26140**, the second section **26145** has a fourth length **26150** and the third section **26155** has a fifth length **26160**. The first section **26135**, the second section **26145** and the third section **26155** may be any suitable length. In an embodiment, the first section **26135** of the optional drilling mud screen **2640** may be up to about 20-25% longer than the second section **26145** and/or the third section **26155**, resulting in increased flow efficiency and decreased erosion.

(376) In an embodiment, the first section **26135** may have a third length **26140** from about 4-inches to about 8-inches, and any range or value there between. In an embodiment, the first section **26135**

may have a third length **26140** of about 6-inches.

(377) In an embodiment, the second section **26145** may have a fourth length **26150** from about 4-inches to about 8-inches, and any range or value there between. In an embodiment, the second section **26145** may have a fourth length **26150** of about 5-inches.

(378) In an embodiment, the third section **26155** may have a fifth length **26160** from about 4-inches to about 8-inches, and any range or value there between. In an embodiment, the third section **26155** may have a fifth length **26160** of about 5-inches.

(379) Optional Cementing Configuration

(380) FIG. **28** illustrates a cross-sectional view of a drilling mud screen system in a cementing configuration **2800** according to an embodiment of the present invention, showing an optional first transducer subassembly **28100'** having an optional transducer **28105**, an optional gate valve **28205** and an optional second transducer subassembly **28100''** having an optional low torque plug valve **28110**. As shown in FIG. **28**, the drilling mud screen system in a cementing configuration **2800** comprises an optional first transducer subassembly **28100'** having an optional transducer **28105**, a drilling mud screen system **28200**, an optional gate valve **28300** and an optional second transducer subassembly **28100''** having an optional low torque plug valve **28110**.

(381) In an embodiment, a first drilling mud inlet **28120'** of the optional first transducer subassembly **28100'** may be fluidly connected to, for example, an outlet of a drilling mud pump via a connection; and a first drilling mud outlet **28125'** of the optional first transducer subassembly **28100'** may be fluidly connected to, for example, a drilling mud inlet **28120** of a drilling mud screen system **28200** via a connection. Any suitable connection may be used for the first drilling mud inlet **28120'** and the first drilling mud outlet **28125'**. For example, suitable connections include, but are not limited to, pipe fittings and welds. Connections are well known in the art. In an embodiment, the first drilling mud inlet **28120'** of the optional first transducer subassembly **28100'** may be fluidly connected to, for example, an outlet of a drilling mud pump via a weld; and the first drilling mud outlet **28125'** of the optional first transducer subassembly **28100'** may be fluidly connected to a drilling mud inlet **28220** of a drilling mud screen system **28200** via a weld.

(382) The inlet pressure to the first drilling mud inlet **28120'** of the optional first transducer subassembly **28100'** may be any suitable pressure. In an embodiment, the inlet pressure may be from about 7500 psi to about 10,000 psi, and any range or value there between.

(383) In an embodiment, the transducer access port **28130** of the optional first transducer subassembly **28100'** may be closed with an optional transducer **28105** via a fitting. Any suitable type of transducer **28105** may be used. For example, suitable types of transducers include, but are not limited to, displacement transducers, flow rate transducers, pressure transducers, temperature transducers and any combination thereof. Any suitable fitting may be used. For example, suitable fittings include, but are not limited to, pipe fittings. Fittings are well known in the art. In an embodiment, the transducer access port **2030** of the optional transducer subassembly **2000** may be closed with, for example, a pressure transducer **28105** via a 2-inch 1502 WECO union.

(384) In an embodiment, a computing device (such as a rig computer) may include a bus that directly or indirectly couples the following devices: memory, one or more processors, one or more presentation components, one or more input/output (I/O) ports, I/O components, a user interface and a power supply. The computing device may include a variety of computer-readable media. The memory may include computer-storage media in the form of volatile and/or nonvolatile memory. The presentation component(s) present data indications to a user or other device. The user interface allows the user to input/output information to/from the computing device. The one or more I/O ports may allow the computing device to be logically coupled to other devices including a transducer **28105**, and other I/O components, some of which may be built in. See e.g., FIG. **28**. Examples of other I/O components include a printer, scanner, wireless device, and the like.

(385) In an embodiment, pressure information from, for example, a pressure transducer **28105** will allow a driller to know when a drilling mud screen (not shown) in a drilling mud screen system

28200 is “packing off” For example, the pressure information from the pressure transducer **28105** at the drilling mud inlet **28220** of the drilling mud screen system **28200** may be compared to, for example, pressure information from a pressure transducer on a pressure transducer for a stand pipe. If the pressure decreases at the stand pipe and the pressure increases at the drilling mud inlet **28220** of the drilling mud screen system **28200**, the drilling mud screen (not shown) is likely “packing off” If the pressure decreases or increases at both the stand pipe and the drilling mud screen system, then the problem is likely down hole and not at the drilling mud screen system **28200**. If the problem is at the drilling mud screen system **28200**, the drilling mud screen may be cleaned, repaired or replaced.

(386) In an embodiment, a drilling mud inlet **28220** of the drilling mud screen system **28200** may be fluidly connected to, for example, a first drilling mud outlet **28125'** of the optional first transducer subassembly **28100'** via a connection; and a drilling mud outlet **28225** of the drilling mud screen system **28200** may be fluidly connected to, for example, a drilling mud inlet **28320** of an optional gate valve **28300** via a connection. Any suitable connection may be used for the drilling mud inlet **2820** and the drilling mud outlet **2825**. For example, suitable connections include, but are not limited to, pipe fittings and welds. Connections are well known in the art. In an embodiment, the drilling mud inlet **28200** of the drilling mud screen system **28200** may be fluidly connected to, for example, a first drilling mud outlet **28120'** of the optional first transducer subassembly **28100'** via a weld; and the drilling mud outlet **28225** of the drilling mud screen system **28200** may be fluidly connected to, for example, a drilling mud inlet **28320** of the optional gate valve **28300** via a weld.

(387) The inlet pressure to the drilling mud inlet **28220** of the drilling mud screen system **28200** may be any suitable pressure. In an embodiment, the inlet pressure may be from about 7500 psi to about 10,000 psi, and any range or value there between.

(388) In an embodiment, a drilling mud inlet **28320** of the optional gate valve **28300** may be fluidly connected to, for example, a drilling mud outlet **28220** of the drilling mud screen system **28200** via a connection; and a drilling mud outlet **28325** of the optional gate valve **28300** may be fluidly connected to, for example, a second drilling mud inlet **28120"** of the optional second transducer subassembly **28100"** via a connection. Any suitable connection may be used for the drilling mud inlet **28320** and the drilling mud outlet **28325**. For example, suitable connections include, but are not limited to, pipe fittings and welds. Connections are well known in the art. In an embodiment, the drilling mud inlet **28320** of the optional gate valve **28300** may be fluidly connected to, for example, a drilling mud outlet **28220** of a drilling mud screen system **28200** via a weld; and the drilling mud outlet **28225** of the optional gate valve **28300** may be fluidly connected to, for example, a second drilling mud inlet **28125"** of the optional second transducer subassembly **28100"** via a weld.

(389) In an embodiment, a second drilling mud inlet **28120"** of the optional second transducer subassembly **28100"** may be fluidly connected to, for example, a drilling mud outlet **28325** of the optional gate valve **28300** via a connection; and a second drilling mud outlet **28125"** of the optional second transducer subassembly **28100"** may be fluidly connected to, for example, an inlet of a vibrator hose via a connection. Any suitable connection may be used for the second drilling mud inlet **28120"** and the second drilling mud outlet **28125"**. For example, suitable connections include, but are not limited to, pipe fittings and welds. Connections are well known in the art. In an embodiment, a second drilling mud inlet **28120"** of the optional second transducer subassembly **28100"** may be fluidly connected to, for example, a drilling mud outlet **28325** of the optional gate valve **28300** via a weld; and a second drilling mud outlet **28125"** of the optional second transducer subassembly **28100"** may be fluidly connected to, for example, an inlet of a vibrator hose via a weld.

(390) In an embodiment, an operator may close an optional gate valve **28300** to isolate a drilling mud screen system **28200** (and an upstream drilling mud pump) from cement for a cementing

application. The operator may pump cement through an optional low torque plug valve **28110** in an optional second transducer subassembly **28100**", through a vibrator hose, through a stand pipe, through a top drive and through a casing running tool (CRT).

(391) Drilling Mud Screen Puller/Installer Tool

(392) FIGS. **8A-8B** and **9A-9B** illustrate a drilling mud screen puller/installer tool according to an embodiment of the present invention. The tool permits use of a deep bore in a single-piece body of the drilling mud screen system, and removal of the drilling mud screen from the two-piece body without disassembly of the two-piece body. Further, the tool provides additional force to remove "stuck" drilling mud screens from debris entrapment in the system.

(393) Single-Piece Body

(394) FIG. **8A** illustrates an upper cross-sectional view of a drilling mud screen puller/installer tool for the exemplary drilling mud screen system of FIGS. **4A-4C**; and FIGS. **18A-18B** illustrate an upper cross-sectional view of the drilling mud screen puller/installer tool of FIG. **8A** for the exemplary drilling mud system of FIGS. **4A-4C** and **14**.

(395) As shown in FIG. **8A**, the drilling mud screen puller/installer tool **800** has a body **805** having a first end **810** and a second end **815** and a first length **820**, a shaft **825** having a first end **830** and a second end **835** and a second length **840**, a movable sleeve **845** having a first end **850** and a second end **855** and a third length **860**, a handle **865**, and a puller/installer plate **870**.

(396) The first length **820** of the body **805** may be any suitable length. In an embodiment, the first length **820** of the body **805** may be from about 10-inches to about 30-inches, and any range or value there between. In an embodiment, the first length **820** of the body **805** may be from about 18-inches to about 22-inches.

(397) The inner diameter (ID) of the body **805** may be any suitable diameter. In an embodiment, the ID of the body **805** may be from about 1-inch to about 2-inches, and any range or value there between. In an embodiment, the ID of the body **805** may be about 1.5-inches.

(398) The outer diameter (OD) of the body **805** may be any suitable diameter. In an embodiment, the OD of the body **805** may be from about 1.5-inches to about 2.5-inches, and any range or value there between. In an embodiment, the OD of the body **805** may be about 1.9-inches.

(399) In an embodiment, the body **805** of the drilling mud screen puller/installer tool **800** may be constructed of any suitable material. For example, suitable materials include, but are not limited to, any alloy steel. In an embodiment, the body **805** may be constructed of an American Iron and Steel Industry (AISI) **4140** or equivalent material, stainless steel and combinations thereof. See e.g., FIG. **8A**. In an embodiment, the surface of the body **805** may be painted.

(400) In an embodiment, the body **805** may have a first striker plate **8100**.

(401) The striker plate **8100** may be any suitable length. In an embodiment, the length of the striker plate **8100** may be from about 0.3-inches to about 0.6-inches, and any range or value there between. In an embodiment, the length of the striker plate **8100** may be about 0.5-inches.

(402) In an embodiment, the inner diameter (ID) of the striker plate **8100** may be any suitable diameter. In an embodiment, the ID of the striker plate **8100** may be from about 1-inch to about 1.25-inches, and any range or value there between. In an embodiment, the ID of the striker plate **8100** may be about 1.13-inches.

(403) In an embodiment, the outer diameter (OD) of the striker plate **8100** may be any suitable diameter. In an embodiment, the OD of the striker plate **8100** may be from about 2-inches to about 2.25-inches, and any range or value there between. In an embodiment, the OD of the striker plate **8100** may be about 2.130-inches.

(404) In an embodiment, the striker plate **8100** of the drilling mud screen puller/installer tool **800** may be constructed of any suitable material. For example, suitable materials include, but are not limited to, any alloy steel. In an embodiment, the striker plate **8100** may be constructed of stainless steel. See e.g., FIG. **8A**. In an embodiment, the surface of the striker plate **8100** may be painted.

(405) In an embodiment, the striker plate **8100** may be attached to the second end **815** of the body

805 via a connection. Any suitable connection may be used for the striker plate **8100**. For example, suitable connections include, but are not limited to, pipe fittings and welds. Connections are well known in the art. In an embodiment, the striker plate **8100** may be attached to the second end **815** of the body **805** via a weld.

(406) In an embodiment, the second length **840** of the shaft **825** may be any suitable length. In an embodiment, the second length **840** of the shaft **825** may be from about 30-inches to about 50-inches, and any range or value there between. In an embodiment, the second length **840** of the shaft **825** may be from about 40-inches to about 42-inches.

(407) The diameter of the shaft **825** may be any suitable diameter. In an embodiment, the diameter of the shaft **825** may be from about 0.75-inches to about 1.5-inches, and any range or value there between. In an embodiment, the diameter of the shaft **825** may be about 1.1-inches.

(408) In an embodiment, the shaft **825** of the drilling mud screen puller/installer tool **800** may be constructed of any suitable material. For example, suitable materials include, but are not limited to, any alloy steel. In an embodiment, the shaft **825** may be constructed of an American Iron and Steel Industry (AISI) **1018** or equivalent material. See e.g., FIG. **8A**. In an embodiment, the surface of the shaft **825** may be painted.

(409) In an embodiment, the third length **860** of the movable sleeve **845** may be any suitable length. In an embodiment, the third length **860** of the movable sleeve **845** may be from about 10-inches to about 30-inches, and any range or value there between. In an embodiment, the third length **860** of the movable sleeve **845** may be from about 20-inches to about 22-inches.

(410) The inner diameter (ID) of the movable sleeve **845** may be any suitable diameter. In an embodiment, the ID of the movable sleeve **845** may be from about 1-inch to about 2-inches, and any range or value there between. In an embodiment, the ID of the movable sleeve **845** may be about 1.4-inches.

(411) The outer diameter (OD) of the movable sleeve **845** may be any suitable diameter. In an embodiment, the OD of the movable sleeve **845** may be from about 1.5-inches to about 2.5-inches, and any range or value there between. In an embodiment, the OD of the movable sleeve **845** may be about 1.9-inches.

(412) In an embodiment, the movable sleeve **845** of the drilling mud screen puller/installer tool **800** may be constructed of any suitable material. For example, suitable materials include, but are not limited to, any alloy steel. In an embodiment, the movable sleeve **845** may be constructed of an American Iron and Steel Industry (AISI) **4140** or equivalent material. See e.g., FIG. **8A**. In an embodiment, the surface of the movable sleeve **845** may be painted.

(413) In an embodiment, the first end **810** of the body **805** may have a rounded end **875** having a first end and a second end; the second end **815** of the body **805** may have a striker plate **8100**.

(414) The length of the rounded end **875** may be any suitable length. In an embodiment, the length of the rounded end **875** may be from about 1-inch to about 2-inches, and any range or value there between. In an embodiment, the length of the rounded end **875** may be about 1.3-inches.

(415) The inner diameter (ID) of the rounded end **875** may be any suitable diameter. In an embodiment, the ID of the rounded end **875** may be from about 1.5-inches to about 2-inches, and any range or value there between. In an embodiment, the ID of the rounded end **875** may be about 1.7-inches.

(416) The outer diameter (OD) of the rounded end **875** may be any suitable diameter. In an embodiment, the OD of the rounded end **875** may be from about 2.5-inches to about 3.5-inches, and any range or value there between. In an embodiment, the OD of the rounded end **875** may be about 3-inches.

(417) In an embodiment, the first end of the rounded end **875** may have a rounded edge. See e.g., FIG. **8**. The radius of the rounded edge may be any suitable radius. In an embodiment, the radius may be from about 0.35-inches to about 0.4-inches, and any range or value there between. In an embodiment, the radius may be about 0.375-inches.

(418) In an embodiment, the rounded end **875** of the drilling mud screen puller/installer tool **800** may be constructed of any suitable material. For example, suitable materials include, but are not limited to, any alloy steel. In an embodiment, the rounded end **875** may be painted.

(419) In an embodiment, the second end of the rounded end **875** may be attached to the first end **810** of the body **805** via a connection. Any suitable connection may be used for the second end of the rounded end **875**. For example, suitable connections include, but are not limited to, pipe fittings and welds. Connections are well known in the art. In an embodiment, the second end of the rounded end **875** may be attached to the first end **810** of the body **805** via a weld.

(420) In an embodiment, the body **805** may have a sleeve body **880** having a first end **885** and a second end **890** and a fourth length **895**, and a first striker plate **8100**.

(421) The fourth length **895** of the sleeve body **880** may be any suitable length. In an embodiment, the fourth length **895** of the sleeve body **880** may be from about 10-inches to about 40-inches, and any range or value there between. In an embodiment, the fourth length **895** of the sleeve body **880** may be from about 20-inches to about 22-inches.

(422) The inner diameter (ID) of the sleeve body **880** may be any suitable diameter. In an embodiment, the ID of the sleeve body **880** may be from about 1-inch to about 2-inches, and any range or value there between. In an embodiment, the ID of the sleeve body **880** may be about 1.4-inches.

(423) The outer diameter (OD) of the sleeve body **880** may be any suitable diameter. In an embodiment, the OD of the sleeve body **880** may be from about 1.5-inches to about 2.5-inches, and any range or value there between. In an embodiment, the OD of the sleeve body **880** may be about 1.9-inches.

(424) In an embodiment, the sleeve body **880** of the drilling mud screen puller/installer tool **800** may be constructed of any suitable material. For example, suitable materials include, but are not limited to, any alloy steel. In an embodiment, the sleeve body **880** may be constructed of an American Iron and Steel Industry (AISI) **4140** or equivalent material, stainless steel and combinations thereof. See e.g., FIG. **8A**. In an embodiment, the surface of the sleeve body **880** may be painted.

(425) In an embodiment, the rounded end **875** may be attached to the first end **885** of the sleeve body **880** via a connection. Any suitable connection may be used for the rounded end **875**. For example, suitable connections include, but are not limited to, pipe fittings and welds. Connections are well known in the art. In an embodiment, the rounded end **875** may be attached to the first end **885** of the sleeve body **880** via a weld.

(426) In an embodiment, the striker plate **8100** may be attached to the second end **890** of the sleeve body **880** via a connection. Any suitable connection may be used for the striker plate **8100**. For example, suitable connections include, but are not limited to, pipe fittings and welds. Connections are well known in the art. In an embodiment, the striker plate **8100** may be attached to the second end **890** of the sleeve body **880** via a weld.

(427) In an embodiment, the second end **815** of the body **805** may be attached to the first end **830** of the shaft **825** via a connection. Any suitable connection may be used for the second end **815** of the body **805**. For example, suitable connections include, but are not limited to, pipe fittings and welds. Connections are well known in the art. In an embodiment, the second end **815** of the body **805** may be attached to the first end **830** of the shaft **825** via a weld.

(428) In an embodiment, the movable sleeve **845** may be disposed around the shaft **825**.

(429) In an embodiment, a handle **865** may be attached to the movable sleeve **845** via a connection. Any suitable connection may be used for the handle **865**. For example, suitable connections include, but are not limited to, pipe fittings and welds. Connections are well known in the art. In an embodiment, the handle **865** may be attached to the movable sleeve **845** via a weld.

(430) The handle **865** may be any suitable handle to move the moveable sleeve **845** back and forth. Suitable handles **865** include, but are not limited to, one or more hand holds extending from the

movable sleeve **845**, a hand ring or hand wheel surrounding the movable sleeve **845**, and combinations thereof.

(431) The diameter of the one or more hand holds of the handle **865** may be any suitable diameter. In an embodiment, the diameter of the one or more hand holds of the handle **865** may be from 0.3-inch to about 1.0-inch, and any range or value there between. In an embodiment, the diameter of the one or more hand holds of the handle **865** may be about 0.5-inch.

(432) In an embodiment, the handle **865** of the drilling mud screen puller/installer tool **800** may be constructed of any suitable material. For example, suitable materials include, but are not limited to, any alloy steel. In an embodiment, the handle **865** may be constructed of an American Iron and Steel Industry (AISI) **1018** or equivalent material. See e.g., FIG. **8A**. In an embodiment, the surface of the handle **865** may be painted.

(433) In an embodiment, the handle **865** may be attached to the movable sleeve **845** via a connection. Any suitable connection may be used for the handle **865**. For example, suitable connections include, but are not limited to, pipe fittings and welds. Connections are well known in the art. In an embodiment, the handle **865** may be attached to the movable sleeve **845** via a weld.

(434) In an embodiment, the puller/installer plate **870** may be attached to a second end **835** of the shaft **825** via a connection. Any suitable connection may be used for the puller/installer plate **870**. For example, suitable connections include, but are not limited to, pipe fittings and welds. Connections are well known in the art. In an embodiment, the puller/installer plate **870** may be attached to the second end **835** of the shaft **825** via a weld.

(435) The length of the puller/installer plate **870** may be any suitable length. In an embodiment, the length of the puller/installer plate **870** may be from about 0.5-inch to about 1-inch, and any range or value there between. In an embodiment, the length of the puller/installer plate **870** may be about 0.725-inch.

(436) The diameter of the puller/installer plate **870** may be any suitable diameter. In an embodiment, the diameter of the puller/installer plate **870** may be from about 2-inches to about 2.5-inches, and any range or value there between. In an embodiment, the diameter of the puller/installer plate **870** may be about 2.3-inches.

(437) In an embodiment, the puller/installer plate **870** of the drilling mud screen puller/installer tool **800** may be constructed of any suitable material. For example, suitable materials include, but are not limited to, any alloy steel. In an embodiment, the puller/installer plate **870** may be constructed of a stainless steel. See e.g., FIG. **8A**. In an embodiment, the surface of the puller/installer plate **870** may be painted.

(438) In an embodiment, the puller/installer plate **870** may have a means to engage **8105** a drilling mud screen **500** of the drilling mud screen system **400**. The means to engage **875** may be any suitable means to engage **8105** the drilling mud screen **500**. For example, a suitable means to engage **8105** includes, but is not limited to, one or more extensions to fit an outlet of the first portion **575** and/or an inlet of the second portion **580** of the body **505** of the drilling mud screen **500** and to engage a shoulder outside the inlet of the second portion **580** of the body **505** of the drilling mud screen **500** and/or to rotationally engage a shoulder inside the inlet of the second portion **580** of the body **505** of the drilling mud screen **500**. Cf. FIGS. **5B** & **8B**. See also FIGS. **12A-12B**. In an embodiment, the puller/installer plate **870** may have one or more extensions to fit an outlet of the first portion **575** and/or an inlet of the second portion **580** of the body **505** of the drilling mud screen **500** and to engage a shoulder outside the inlet of the second portion **580** of the body **505** of the drilling mud screen **500** and/or to rotationally engage a shoulder inside the inlet of the second portion **580** of the body **505** of the drilling mud screen **500**. Id.

(439) In an embodiment, the means to engage **8105** may be constructed of any suitable material. For example, suitable materials include, but are not limited to, any alloy steel. In an embodiment, the means to engage **8105** may be constructed of a stainless steel or equivalent material. See e.g., FIG. **8A**. In an embodiment, the means to engage **8105** may be painted.

(440) Two-Piece Body

(441) FIG. 9A illustrates an upper cross-sectional view of a drilling mud screen puller/installer tool for the exemplary drilling mud screen system of FIG. 7. As shown in FIG. 9, the drilling mud screen puller/installer tool **900** has a body **905** having a first end **910** and a second end **915** and a first length **920**, a shaft **925** having a first end **930** and a second end **935** and a second length **940**, a movable sleeve **945** having a first end **950** and a second end **955** and a third length **960**, a handle **965**, and a puller/installer plate **970**.

(442) The first length **920** of the body **905** may be any suitable length. In an embodiment, the first length **920** of the body **905** may be from about 10-inches to about 30-inches, and any range or value there between. In an embodiment, the first length **920** of the body **905** may be from about 18-inches to about 22-inches.

(443) The inner diameter (ID) of the body **905** may be any suitable diameter. In an embodiment, the ID of the body **905** may be from about 1-inch to about 2-inches, and any range or value there between. In an embodiment, the ID of the body **905** may be about 1.5-inches.

(444) The outer diameter (OD) of the body **905** may be any suitable diameter. In an embodiment, the OD of the body **905** may be from about 1.5-inches to about 2.5-inches, and any range or value there between. In an embodiment, the OD of the body **905** may be about 1.9-inches.

(445) In an embodiment, the body **905** of the drilling mud screen puller/installer tool **900** may be constructed of any suitable material. For example, suitable materials include, but are not limited to, any alloy steel. In an embodiment, the body **905** may be constructed of an American Iron and Steel Industry (AISI) **4140** or equivalent material, stainless steel and combinations thereof. See e.g., FIG. 9A. In an embodiment, the surface of the body **905** may be painted.

(446) In an embodiment, the body **905** may have a striker plate **9100**.

(447) The striker plate **9100** may be any suitable length. In an embodiment, the length of the striker plate **9100** may be from about 0.3-inch to about 0.6-inch, and any range or value there between. In an embodiment, the length of the striker plate **9100** may be about 0.5-inch.

(448) In an embodiment, the inner diameter (ID) of the striker plate **9100** may be any suitable diameter. In an embodiment, the ID of the striker plate **9100** may be from about 1-inch to about 1.25-inches, and any range or value there between. In an embodiment, the ID of the striker plate **9100** may be about 1.13-inches.

(449) In an embodiment, the outer diameter (OD) of the striker plate **9100** may be any suitable diameter. In an embodiment, the OD of the striker plate **9100** may be from about 2-inches to about 2.25-inches, and any range or value there between. In an embodiment, the OD of the striker plate **9100** may be about 2.130-inches.

(450) In an embodiment, the striker plate **9100** of the drilling mud screen puller/installer tool **900** may be constructed of any suitable material. For example, suitable materials include, but are not limited to, any alloy steel. In an embodiment, the striker plate **9100** may be constructed of stainless steel. See e.g., FIG. 9A. In an embodiment, the surface of the striker plate **9100** may be painted.

(451) In an embodiment, the striker plate **9100** may be attached to the second end **915** of the body **905** via a connection. Any suitable connection may be used for the striker plate **9100**. For example, suitable connections include, but are not limited to, pipe fittings and welds. Connections are well known in the art. In an embodiment, the striker plate **9100** may be attached to the second end **915** of the body **905** via a weld.

(452) In an embodiment, the second length **940** of the shaft **925** may be any suitable length. In an embodiment, the second length **940** of the shaft **925** may be from about 40-inches to about 60-inches, and any range or value there between. In an embodiment, the second length **940** of the shaft **925** may be from about 50-inches to about 52-inches.

(453) The diameter of the shaft **925** may be any suitable diameter. In an embodiment, the diameter of the shaft **925** may be from about 0.75-inch to about 1.5-inches, and any range or value there between. In an embodiment, the diameter of the shaft **925** may be about 1.1-inches.

(454) In an embodiment, the shaft **925** of the drilling mud screen puller/installer tool **900** may be constructed of any suitable material. For example, suitable materials include, but are not limited to, any alloy steel. In an embodiment, the shaft **925** may be constructed of an American Iron and Steel Industry (AISI) **1018** or equivalent material. See e.g., FIG. **9A**. In an embodiment, the surface of the shaft **925** may be painted.

(455) In an embodiment, the third length **960** of the movable sleeve **945** may be any suitable length. In an embodiment, the third length **960** of the movable sleeve **945** may be from about 10-inches to about 30-inches, and any range or value there between. In an embodiment, the third length **960** of the movable sleeve **945** may be from about 20-inches to about 22-inches.

(456) The inner diameter (ID) of the movable sleeve **945** may be any suitable diameter. In an embodiment, the ID of the movable sleeve **945** may be from about 1-inch to about 2-inches, and any range or value there between. In an embodiment, the ID of the movable sleeve **945** may be about 1.4-inches.

(457) The outer diameter (OD) of the movable sleeve **945** may be any suitable diameter. In an embodiment, the OD of the movable sleeve **945** may be from about 1.5-inches to about 2.5-inches, and any range or value there between. In an embodiment, the OD of the movable sleeve **945** may be about 1.9-inches.

(458) In an embodiment, the movable sleeve **945** of the drilling mud screen puller/installer tool **900** may be constructed of any suitable material. For example, suitable materials include, but are not limited to, any alloy steel. In an embodiment, the movable sleeve **945** may be constructed of an American Iron and Steel Industry (AISI) **4140** or equivalent material. See e.g., FIG. **9A**. In an embodiment, the surface of the movable sleeve **945** may be painted.

(459) In an embodiment, the first end **910** of the body **905** may have a rounded end **975** having a first end and a second end; the second end **915** of the body **905** may have a striker plate **9100**.

(460) The length of the rounded end **975** may be any suitable length. In an embodiment, the length of the rounded end **975** may be from about 1-inch to about 2-inches, and any range or value there between. In an embodiment, the length of the rounded end **975** may be about 1.3-inches.

(461) The inner diameter (ID) of the rounded end **975** may be any suitable diameter. In an embodiment, the ID of the rounded end **975** may be from about 1.5-inches to about 2-inches, and any range or value there between. In an embodiment, the ID of the rounded end **975** may be about 1.7-inches.

(462) The outer diameter (OD) of the rounded end **975** may be any suitable diameter. In an embodiment, the OD of the rounded end **975** may be from about 2.5-inches to about 3.5-inches, and any range or value there between. In an embodiment, the OD of the rounded end **975** may be about 3-inches.

(463) In an embodiment, the first end of the rounded end **975** may have a rounded edge. See e.g., FIG. **9A**. The radius of the rounded edge may be any suitable radius. In an embodiment, the radius may be from about 0.35-inch to about 0.4-inch, and any range or value there between. In an embodiment, the radius may be about 0.375-inch.

(464) In an embodiment, the rounded end **975** of the drilling mud screen puller/installer tool **900** may be constructed of any suitable material. For example, suitable materials include, but are not limited to, any alloy steel. In an embodiment, the rounded end **975** may be painted.

(465) In an embodiment, the second end of the rounded end **975** may be attached to the first end **910** of the body **905** via a connection. Any suitable connection may be used for the second end of the rounded end **975**. For example, suitable connections include, but are not limited to, pipe fittings and welds. Connections are well known in the art. In an embodiment, the second end of the rounded end **975** may be attached to the first end **910** of the body **905** via a weld.

(466) In an embodiment, the body **905** may have a sleeve body **980** having a first end **985** and a second end **990** and a fourth length **995**, and a striker plate **9100**.

(467) The fourth length **995** of the sleeve body **980** may be any suitable length. In an embodiment,

the fourth length **995** of the sleeve body **980** may be from about 10-inches to about 40-inches, and any range or value there between. In an embodiment, the fourth length **995** of the sleeve body **980** may be from about 18-inches to about 20-inches.

(468) The inner diameter (ID) of the sleeve body **980** may be any suitable diameter. In an embodiment, the ID of the sleeve body **980** may be from about 1-inch to about 2-inches, and any range or value there between. In an embodiment, the ID of the sleeve body **980** may be about 1.4-inches.

(469) The outer diameter (OD) of the sleeve body **980** may be any suitable diameter. In an embodiment, the OD of the sleeve body **980** may be from about 1.5-inches to about 2.5-inches, and any range or value there between. In an embodiment, the OD of the sleeve body **980** may be about 1.9-inches.

(470) In an embodiment, the sleeve body **980** of the drilling mud screen puller/installer tool **900** may be constructed of any suitable material. For example, suitable materials include, but are not limited to, any alloy steel. In an embodiment, the sleeve body **980** may be constructed of an American Iron and Steel Industry (AISI) **4140** or equivalent material, stainless steel and combinations thereof. See e.g., FIG. **9A**. In an embodiment, the surface of the sleeve body **980** may be painted.

(471) In an embodiment, the rounded end **975** may be attached to the first end **985** of the sleeve body **880** via a connection. Any suitable connection may be used for the rounded end **975**. For example, suitable connections include, but are not limited to, pipe fittings and welds. Connections are well known in the art. In an embodiment, the rounded end **975** may be attached to the first end **985** of the sleeve body **980** via a weld.

(472) In an embodiment, the striker plate **9100** may be attached to the second end **990** of the sleeve body **980** via a connection. Any suitable connection may be used for the striker plate **9100**. For example, suitable connections include, but are not limited to, pipe fittings and welds. Connections are well known in the art. In an embodiment, the striker plate **9100** may be attached to the second end **990** of the sleeve body **980** via a weld.

(473) In an embodiment, the second end **915** of the body **905** may be attached to the first end **930** of the shaft **925** via a connection. Any suitable connection may be used for the second end **915** of the body **905**. For example, suitable connections include, but are not limited to, pipe fittings and welds. Connections are well known in the art. In an embodiment, the second end **915** of the body **905** may be attached to the first end **930** of the shaft **925** via a weld.

(474) In an embodiment, the movable sleeve **945** may be disposed around the shaft **925**.

(475) In an embodiment, a handle **965** may be attached to the movable sleeve **945** via a connection. Any suitable connection may be used for the handle **965**. For example, suitable connections include, but are not limited to, pipe fittings and welds. Connections are well known in the art. In an embodiment, the handle **965** may be attached to the movable sleeve **945** via a weld.

(476) The handle **965** may be any suitable handle to move the moveable sleeve **945** back and forth. For example, suitable handles **965** include, but are not limited to, one or more hand holds extending from the movable sleeve **945**, a hand ring or hand wheel surrounding the movable sleeve **945**, and combinations thereof.

(477) The diameter of the one or more hand holds of the handle **965** may be any suitable diameter. In an embodiment, the diameter of the one or more hand holds of the handle **965** may be from 0.3-inch to about 1.0-inch, and any range or value there between. In an embodiment, the diameter of the one or more hand holds of the handle **965** may be about 0.5-inch.

(478) In an embodiment, the handle **965** of the drilling mud screen puller/installer tool **900** may be constructed of any suitable material. For example, suitable materials include, but are not limited to, any alloy steel. In an embodiment, the handle **965** may be constructed of an American Iron and Steel Industry (AISI) **1018** or equivalent material. See e.g., FIG. **9A**. In an embodiment, the surface of the handle **965** may be painted.

(479) In an embodiment, the handle **965** may be attached to the movable sleeve **945** via a connection. Any suitable connection may be used for the handle **965**. For example, suitable connections include, but are not limited to, pipe fittings and welds. Connections are well known in the art. In an embodiment, the handle **965** may be attached to the movable sleeve **945** via a weld.

(480) In an embodiment, the puller/installer plate **970** may be attached to a second end **935** of the shaft **925** via a connection. Any suitable connection may be used for the puller/installer plate **970**. For example, suitable connections include, but are not limited to, pipe fittings and welds. Connections are well known in the art. In an embodiment, the puller/installer plate **970** may be attached to the second end **935** of the shaft **925** via a weld.

(481) The length of the puller/installer plate **970** may be any suitable length. In an embodiment, the length of the puller/installer plate **970** may be from about 0.5-inch to about 1-inch, and any range or value there between. In an embodiment, the length of the puller/installer plate **970** may be about 0.725-inch.

(482) The diameter of the puller/installer plate **970** may be any suitable diameter. In an embodiment, the diameter of the puller/installer plate **970** may be from about 2-inches to about 2.5-inches, and any range or value there between. In an embodiment, the diameter of the puller/installer plate **970** may be about 2.3-inches.

(483) In an embodiment, the puller/installer plate **970** of the drilling mud screen puller/installer tool **900** may be constructed of any suitable material. For example, suitable materials include, but are not limited to, any alloy steel. In an embodiment, the puller/installer plate **970** may be constructed of a stainless steel. See e.g., FIG. **9A**. In an embodiment, the surface of the puller/installer plate **970** may be painted.

(484) In an embodiment, the puller/installer plate **970** may have a means to engage **9105** a drilling mud screen **500** of the drilling mud screen system **400**. The means to engage **975** may be any suitable means to engage **9105** the drilling mud screen **500**. For example, a suitable means to engage **9105** includes, but is not limited to, one or more extensions to fit an outlet of the first portion **575** and/or an inlet of the second portion **580** of the body **505** of the drilling mud screen **500** and to engage a shoulder outside the inlet of the second portion **580** of the body **505** of the drilling mud screen **500** and/or to rotationally engage a shoulder inside the inlet of the second portion **580** of the body **505** of the drilling mud screen **500**. Cf. FIGS. **5B** & **8B**. See also FIGS. **13A-13B**. In an embodiment, the puller/installer plate **970** may have one or more extensions to fit an outlet of the first portion **575** and/or an inlet of the second portion **580** of the body **505** of the drilling mud screen **500** and to engage a shoulder outside the inlet of the second portion **580** of the body **505** of the drilling mud screen **500** and/or to rotationally engage a shoulder inside the inlet of the second portion **580** of the body **505** of the drilling mud screen **500**. Id.

(485) In an embodiment, the means to engage **9105** may be constructed of any suitable material. For example, suitable materials include, but are not limited to, any alloy steel. In an embodiment, the means to engage **9105** may be constructed of a stainless steel or equivalent material. See e.g., FIG. **9A**. In an embodiment, the means to engage **9105** may be painted.

(486) Optional Drilling Mud Screen Installer/Puller Tool

(487) One-Piece Body

(488) In an embodiment, the drilling mud screen puller/installer tool **800** has a body **805** having a first end **810** and a second end **815** and a first length **820**, a shaft **825** having a first end **830** and a second end **835** and a second length **840**, a movable sleeve **845** having a first end **850** and a second end **855** and a third length **860**, a handle **865**, an optional stop plate (not shown) and a puller/installer plate **870**. Cf. FIG. **29**. In an embodiment, the optional stop plate (not shown) on the shaft **825** of the puller/installer tool **800** indicates that the puller/installer tool **800** (and, therefore, the drilling mud screen **500**) is fully inserted into the drilling mud screen system **800** when the optional stop plate (not shown) contacts the first end **810** of the body **805** of the system **800**.

(489) In an embodiment, an optional groove or painted line may be used instead of the optional

stop plate on the shaft **825** of the puller/installer tool **800**. In an embodiment, the optional groove or painted line (not shown) on the shaft **825** of the puller/installer tool **800** indicates that the puller/installer tool **800** (and, therefore, the drilling mud screen **500**) is fully inserted into the drilling mud screen system **800** when the optional groove or painted line (not shown) lines up with the first end **810** of the body **805** of the system **800**.

(490) Two-Piece Body

(491) FIG. **29** illustrates a cross-sectional view of the exemplary drilling mud tool of FIG. **9A** inserting the drilling mud screen of FIG. **5** or **22** into the exemplary drilling mud screen system of FIG. **7A** or **21B**, showing an optional stop plate. As shown in FIG. **29**, the drilling mud screen puller/installer tool **900** has a body **905** having a first end **910** and a second end **915** and a first length **920**, a shaft **925** having a first end **930** and a second end **935** and a second length **940**, a movable sleeve **945** having a first end **950** and a second end **955** and a third length **960**, a handle **965**, an optional stop plate **29400** and a puller/installer plate **970**. In an embodiment, the optional stop plate **29400** on the shaft **925** of the puller/installer tool **900** indicates that the puller/installer tool **900** (and, therefore, the drilling mud screen **500** or **2200**) is fully inserted into the drilling mud screen system **700** or **2100** when the optional stop plate **29400** contacts the first end **710a** or **2110a** of the first body **705a** or **2105a** of the system **700** or **2100**.

(492) In an embodiment, an optional groove or painted line may be used instead of the optional stop plate **29400** on the shaft **925** of the puller/installer tool **900**. In an embodiment, the optional groove or painted line (not shown) on the shaft **925** of the puller/installer tool **900** indicates that the puller/installer tool **900** (and, therefore, the drilling mud screen **500** or **2200**) is fully inserted into the drilling mud screen system **700** or **2100** when the optional groove or painted line (not shown) lines up with the first end **710a** or **2110a** of the first body **705a** or **2105a** of the system **700** or **2100**.

(493) Method of Using Drilling Mud Screen System

(494) FIG. **10** illustrates a flow diagram for a method of using a drilling mud screen system, as discussed above. As shown in FIG. **10**, the method of using a drilling mud screen system **1000** comprises stopping a drilling mud pump to stop flow of drilling mud **1005**, fluidly connecting a drilling mud inlet of a drilling mud screen system downstream of an outlet to the drilling mud pump **1010**, fluidly connecting a drilling mud outlet of the drilling mud screen system upstream of an outlet of a stand pipe **1015**, and starting the drilling mud pump to flow drilling mud through the drilling mud screen system **1020**.

(495) In an embodiment, the drilling mud inlet **120**, **220**, **320**, **400**, **620**, **720** of the drilling mud screen system **100**, **200**, **300**, **400**, **600**, **700** may be fluidly connected to a high pressure outlet of the drilling mud pump via a connection. See also FIGS. **14**, **19**, **21**, **23** & **26**. The inlet pressure to the drilling mud inlet **120**, **220**, **320**, **400**, **620**, **720** of the drilling mud screen system **100**, **200**, **300**, **400**, **600**, **700** may be any suitable pressure. In an embodiment, the inlet pressure may be from about 7500 psi to about 10,000 psi, and any range or value there between.

(496) In an embodiment, the drilling mud outlet **125**, **225**, **325**, **425**, **625**, **725** of the drilling mud screen system **100**, **200**, **300**, **400**, **600**, **700** may be fluidly connected to an inlet of a vibrator hose to the standpipe via a connection.

(497) In an embodiment, the drilling mud inlet **120**, **220**, **320**, **400**, **620**, **720** of the drilling mud screen system **100**, **200**, **300**, **400**, **600**, **700** may be fluidly connected to an outlet of a vibrator hose to a standpipe via a connection. In an embodiment, the drilling mud outlet **125**, **225**, **325**, **425**, **625**, **725** of the drilling mud screen system **100**, **200**, **300**, **400**, **600**, **700** may be fluidly connected to an inlet of the standpipe via a connection.

(498) In an embodiment, the drilling mud screen system **100**, **200**, **300**, **400**, **600**, **700** may be fluidly connected at any point in the standpipe via a connection.

(499) Optional Monitoring Configuration

(500) FIG. **10** illustrates a flow diagram for a method of using a drilling mud screen system, as discussed above. As shown in FIG. **10**, the method of using a drilling mud screen system **1000**

comprises stopping a drilling mud pump to stop flow of drilling mud **1005**, fluidly connecting a drilling mud inlet of a drilling mud screen system downstream of an outlet to the drilling mud pump **1010**, fluidly connecting a drilling mud outlet of the drilling mud screen system upstream of an outlet of a stand pipe **1015**, and starting the drilling mud pump to flow drilling mud through the drilling mud screen system **1020**.

(501) In an embodiment, step **1010** comprises fluidly connecting a drilling mud inlet of a transducer subassembly downstream of an outlet to the drilling mud pump; and fluidly connecting a drilling mud inlet of a drilling mud screen system downstream of a drilling mud outlet to the transducer subassembly.

(502) As shown in FIGS. **19** and **28**, the drilling mud inlet **1920** of the drilling mud screen system **19200**, **28200** may be fluidly connected to a drilling mud outlet **28125** of the transducer subassembly **19110**, **28100** via a connection. Any suitable connection may be used for the drilling mud inlet **1920** and the drilling mud outlet **28125**. For example, suitable connections include, but are not limited to, pipe fittings and welds. Connections are well known in the art. In an embodiment, the drilling mud inlet **1920** of the drilling mud screen system **19200**, **28200** may be fluidly connected to a drilling mud outlet **28125** of a transducer subassembly **19100** via a weld.

(503) In an embodiment, the method of using a drilling mud screen system **1000** further comprises monitoring a transducer of the transducer subassembly for property information (e.g., displacement, flow rate, pressure, and/or temperature) at the drilling mud screen system.

(504) In an embodiment, a computing device (such as a rig computer) may include a bus that directly or indirectly couples the following devices: memory, one or more processors, one or more presentation components, one or more input/output (I/O) ports, I/O components, a user interface and a power supply. The computing device may include a variety of computer-readable media. The memory may include computer-storage media in the form of volatile and/or nonvolatile memory. The presentation component(s) present data indications to a user or other device. The user interface allows the user to input/output information to/from the computing device. The one or more I/O ports may allow the computing device to be logically coupled to other devices including a transducer **28105**, and other I/O components, some of which may be built in. See e.g., FIG. **28**. Examples of other I/O components include a printer, scanner, wireless device, and the like.

(505) In an embodiment, the method of using a drilling mud screen system **1000** further comprises using the property information (e.g., displacement, flow rate, pressure, and/or temperature) from the transducer of the transducer subassembly to determine a status of the drilling mud screen system. In an embodiment, the method further comprises using the information to determine when to clean, repair or replace the drilling mud screen in the drilling mud screen system.

(506) In an embodiment, pressure information from, for example, a pressure transducer **28105** will allow a driller to know when a drilling mud screen **1940** in a drilling mud screen system **19200**, **28200** is “packing off.” For example, the pressure information from the pressure transducer **28105** at the drilling mud inlet **1920** of the drilling mud screen system **19200**, **28200** may be compared to, for example, pressure information from a pressure transducer on a pressure transducer for a stand pipe. If the pressure decreases at the stand pipe and the pressure increases at the drilling mud inlet **1920** of the drilling mud screen system **19200**, **28200**, the drilling mud screen **1940** is likely “packing off” If the pressure decreases or increases at both the stand pipe and the drilling mud screen system, then the problem is likely down hole and not at the drilling mud screen system **19200**, **28200**. If the problem is at the drilling mud screen system **19200**, **28200**, the drilling mud screen **1940** may be cleaned, repaired or replaced.

(507) Optional Cementing Configuration

(508) FIG. **10** illustrates a flow diagram for a method of using a drilling mud screen system, as discussed above. As shown in FIG. **10**, the method of using a drilling mud screen system **1000** comprises stopping a drilling mud pump to stop flow of drilling mud **1005**, fluidly connecting a drilling mud inlet of a drilling mud screen system downstream of an outlet to the drilling mud

pump **1010**, fluidly connecting a drilling mud outlet of the drilling mud screen system upstream of an outlet of a stand pipe **1015**, and starting the drilling mud pump to flow drilling mud through the drilling mud screen system **1020**.

(509) In an embodiment, step **1010** comprises fluidly connecting a first drilling mud inlet of a first transducer subassembly downstream of an outlet to the drilling mud pump; and fluidly connecting a first drilling mud inlet of a drilling mud screen system downstream of an outlet to the first transducer subassembly.

(510) In an embodiment, step **1015** comprises fluidly connecting a drilling mud outlet of the drilling mud screen system upstream of a drilling mud inlet of a gate valve, fluidly connecting a drilling mud outlet of the gate valve to a second drilling mud inlet to a second transducer subassembly, and fluidly connecting a second drilling mud outlet of the second transducer subassembly upstream of an outlet of a stand pipe.

(511) As shown in FIG. **28**, the first drilling mud inlet **28120'** of the optional first transducer subassembly **28100'** may be fluidly connected to, for example, an outlet of a drilling mud pump via a connection; and the first drilling mud outlet **28125'** of the optional first transducer subassembly **28100'** may be fluidly connected to, for example, the drilling mud inlet **28120** of the drilling mud screen system **28200** via a connection. Any suitable connection may be used for the first drilling mud inlet **28120'** and the first drilling mud outlet **28125'**. For example, suitable connections include, but are not limited to, pipe fittings and welds. Connections are well known in the art. In an embodiment, the first drilling mud inlet **28120'** of the optional first transducer subassembly **28100'** may be fluidly connected to, for example, an outlet of a drilling mud pump via a weld; and the first drilling mud outlet **28125'** of the optional first transducer subassembly **28100'** may be fluidly connected to the drilling mud inlet **28220** of the drilling mud screen system **28200** via a weld.

(512) The inlet pressure to the first drilling mud inlet **28120'** of the optional first transducer subassembly **28100'** may be any suitable pressure. In an embodiment, the inlet pressure may be from about 7500 psi to about 10,000 psi, and any range or value there between.

(513) In an embodiment, a computing device (such as a rig computer) may include a bus that directly or indirectly couples the following devices: memory, one or more processors, one or more presentation components, one or more input/output (I/O) ports, I/O components, a user interface and a power supply. The computing device may include a variety of computer-readable media. The memory may include computer-storage media in the form of volatile and/or nonvolatile memory. The presentation component(s) present data indications to a user or other device. The user interface allows the user to input/output information to/from the computing device. The one or more I/O ports may allow the computing device to be logically coupled to other devices including a transducer **28105**, and other I/O components, some of which may be built in. See e.g., FIG. **28**. Examples of other I/O components include a printer, scanner, wireless device, and the like.

(514) In an embodiment, pressure information from, for example, a pressure transducer **28105** will allow a driller to know when a drilling mud screen **1940** in a drilling mud screen system **28200** is “packing off.” For example, the pressure information from the pressure transducer **28105** at the drilling mud inlet **28220** of the drilling mud screen system **28200** may be compared to, for example, pressure information from a pressure transducer on a stand pipe. If the pressure decreases at the stand pipe and the pressure increases at the drilling mud inlet **28220** of the drilling mud screen system **28200**, the drilling mud screen **1940** is likely “packing off.” If the pressure decreases or increases at both the stand pipe and the drilling mud screen system, then the problem is likely down hole and not at the drilling mud screen system **28200**. If the problem is at the drilling mud screen system **28200**, the drilling mud screen **1940** may be cleaned, repaired or replaced.

(515) In an embodiment, the drilling mud inlet **28220** of the drilling mud screen system **28200** may be fluidly connected to, for example, the first drilling mud outlet **28125'** of the optional first transducer subassembly **28100'** via a connection; and a drilling mud outlet **28225** of the drilling

mud screen system **28200** may be fluidly connected to, for example, the drilling mud inlet **28320** of the optional gate valve **28300** via a connection. Any suitable connection may be used for the drilling mud inlet **2820** and the drilling mud outlet **2825**. For example, suitable connections include, but are not limited to, pipe fittings and welds. Connections are well known in the art. In an embodiment, the drilling mud inlet **28200** of the drilling mud screen system **28200** may be fluidly connected to, for example, the first drilling mud outlet **28120'** of the optional first transducer subassembly **28100'** via a weld; and the drilling mud outlet **28225** of the drilling mud screen system **28200** may be fluidly connected to, for example, the drilling mud inlet **28320** of the optional gate valve **28300** via a weld.

(516) The inlet pressure to the drilling mud inlet **28220** of the drilling mud screen system **28200** may be any suitable pressure. In an embodiment, the inlet pressure may be from about 7500 psi to about 10,000 psi, and any range or value there between.

(517) In an embodiment, the drilling mud inlet **28320** of the optional gate valve **28300** may be fluidly connected to, for example, the drilling mud outlet **28220** of the drilling mud screen system **28200** via a connection; and a drilling mud outlet **28325** of the optional gate valve **28300** may be fluidly connected to, for example, the second drilling mud inlet **28120"** of the optional second transducer subassembly **28100"** via a connection. Any suitable connection may be used for the drilling mud inlet **28320** and the drilling mud outlet **28325**. For example, suitable connections include, but are not limited to, pipe fittings and welds. Connections are well known in the art. In an embodiment, the drilling mud inlet **28320** of the optional gate valve **28300** may be fluidly connected to, for example, the drilling mud outlet **28220** of the drilling mud screen system **28200** via a weld; and the drilling mud outlet **28225** of the optional gate valve **28300** may be fluidly connected to, for example, a second drilling mud inlet **28125"** of the optional second transducer subassembly **28100"** via a weld.

(518) In an embodiment, the second drilling mud inlet **28120"** of the optional second transducer subassembly **28100"** may be fluidly connected to, for example, the drilling mud outlet **28325** of the optional gate valve **28300** via a connection; and the second drilling mud outlet **28125"** of the optional second transducer subassembly **28100"** may be fluidly connected to, for example, an inlet of a vibrator hose via a connection. Any suitable connection may be used for the second drilling mud inlet **28120"** and the second drilling mud outlet **28125"**. For example, suitable connections include, but are not limited to, pipe fittings and welds. Connections are well known in the art. In an embodiment, the second drilling mud inlet **28120"** of the optional second transducer subassembly **28100"** may be fluidly connected to, for example, the drilling mud outlet **28325** of the optional gate valve **28300** via a weld; and a second drilling mud outlet **28125"** of the optional second transducer subassembly **28100"** may be fluidly connected to, for example, an inlet of a vibrator hose via a weld.

(519) In an embodiment, an operator may close an optional gate valve **28300** to isolate a drilling mud screen system **28200** (and an upstream drilling mud pump) from cement for a cementing application. The operator may pump cement through an optional low torque plug valve **28110** in an optional second transducer subassembly **28100"**, through a vibrator hose, through a stand pipe, through a top drive and through a casing running tool (CRT).

(520) Method of Removing and Replacing Drilling Mud Screen

(521) FIG. **11** illustrates a method of removing and replacing a drilling mud screen in a drilling mud screen system, as discussed above. As shown in FIG. **11**, the method of removing and replacing a drilling mud screen **1100** comprises providing a drilling mud screen system **1105**, stopping a drilling mud pump connected to the drilling mud screen system **1110**, opening a drilling mud screen access port and/or a union in the drilling mud screen system to remove and replace a drilling mud screen **1115**, accessing the interior of the drilling mud screen system to pull the drilling mud screen from the drilling mud screen system and to install a replacement drilling mud screen into the drilling mud screen system **1120**, closing the drilling mud screen access port and or

the union in the drilling mud screen system **1125**, and operating the drilling mud pump to produce flow of drilling mud through the drilling mud screen system **1130**.

(522) In an embodiment, step **1115** comprises opening a drilling mud screen access port **130, 230, 330, 430** in the body **105, 205, 305, 405** of the single-piece drilling mud screen system **100, 200, 300, 400**. See also FIG. **14**. In an embodiment, step **1115** comprises opening the drilling mud screen access port **630, 730** of the first body **605a, 705a** and opening a union between the first body **605a, 705a** and the second body **605b, 705b** of the two-piece drilling mud screen system **600, 700** to remove and replace the drilling mud screen **500**. See also FIGS. **19, 21, 23 & 26**.

(523) In an embodiment, step **1125** comprises closing the drilling mud screen access port **130, 230, 330, 430** in the body **105, 205, 305, 405** of the single piece drilling mud screen system **100, 200, 300, 400**. In an embodiment, step **1125** comprises closing the drilling mud screen access port **130, 230, 330, 430** of the first body **605a, 705a** and connecting the union between the first body **605a, 705a** and the second body **650b, 705b** of the two-piece drilling mud screen system **600, 700**.

(524) In an embodiment, step **1115** comprises opening the drilling mud screen access port **130, 230, 330, 430, 630, 730** of the drilling mud screen system **100, 200, 300, 400, 600, 700**, and step **1120** comprises using a puller/installer plate **870, 970** of a puller/installer tool **800, 900** to engage and pull the drilling mud screen **500** from the drilling mud screen system **100, 200, 300, 400, 600, 700**. In an embodiment, step **1115** comprises opening the drilling mud screen access port **130, 230, 330, 430, 630, 730** of the drilling mud screen system **100, 200, 300, 400, 600, 700**, and step **1120** comprises using the puller/installer plate **875, 975** and/or a rounded end **875, 975** of the puller/installer tool **800, 900** to install the replacement drilling mud screen **500** into the drilling mud screen system **100, 200, 300, 400, 600, 700**.

(525) In an embodiment, step **1120** further comprises using a groove, painted line or stop plate **29110** on the shaft **825, 925** of the puller/installer tool **800, 900** to indicate when the puller/installer tool **800, 900** (and therefore, the drilling mud screen **500, 2200**) is fully inserted in the system **100, 200, 300, 400, 600, 700, 2100**.

(526) Improved Exemplary Valve-Style Drilling Mud Screen System

(527) Body with Face-Roller Camming Mechanism

(528) FIG. **30A** illustrates an upper, left perspective view of an exemplary drilling mud screen system **3000** with a camming seal separator **30200** having a face-roller camming mechanism **30200a** according to an embodiment of the present invention, showing a rotating subassembly **30400** in a closed position; FIG. **30C** illustrates an upper, left perspective view of the drilling mud screen system **3000** of FIG. **30A**, showing a rotating subassembly **30400** in the open position; FIG. **30D** illustrates a detail view of a rotating subassembly **30400** of FIGS. **30A-30C**; and FIG. **30E** illustrates a cross-sectional view of the drilling mud screen system **3000** of FIG. **30A**, showing the rotating subassembly **30400** in a closed position.

(529) FIG. **31A** illustrates left perspective view of an exemplary drilling mud screen system **3100** with a camming seal separator **31200** having a face-roller camming mechanism **31200a** according to an embodiment of the present invention, showing a rotating subassembly **31400** in a closed position; FIG. **31C** illustrates a left perspective view of the drilling mud screen system **3100** of FIG. **30A**, showing a rotating subassembly **31400** in the open position; FIG. **31D** illustrates a partial cross-sectional view of the drilling mud screen system **3100** of FIG. **31A**, showing the rotating subassembly **31400** in the closed position; and FIG. **31E** illustrates a partial cross-sectional view of the drilling mud screen system **3100** of FIGS. **31A** and **31C-31D**, showing the rotating subassembly **31400** in the open position.

(530) FIG. **30B** illustrates the upper, left perspective view of the drilling mud screen system **3000** of FIG. **30A**, showing an optional first transducer subassembly **30100a** and an optional second transducer subassembly **30100b**, as discussed below; and FIG. **31B** illustrates the left perspective view of the drilling mud screen system **3100** of FIG. **31A**, showing an optional first transducer subassembly **31100a** and an optional second transducer subassembly **31100b**.

(531) As shown in FIGS. **30A-30E** and **31A-31E**, the drilling mud screen system **3000, 3100** has a body **3005, 3105** having a first end **3010, 3110** and a second end **3015, 3115**, a drilling mud inlet **3020, 3120** and a drilling mud outlet **3025, 3125**, and a drilling mud screen access port **3130**.

(532) In an embodiment, the drilling mud screen system **3000, 3100** has a drilling mud screen **3040, 3140** fluidly connected to and disposed between the first drilling mud inlet **3020, 3120** and the first drilling outlet **3025, 3125**.

(533) In an embodiment, the body **3005, 3105** has a first portion **3005a, 3105a**, a second portion **3005b, 3105b** and a third portion **3005c, 3105c**. In an embodiment, the first portion **3005a, 3105a** of the body **3005, 3105** is an inlet portion. In an embodiment, the second portion **3005b, 3105b** of the body **3005, 3105** is a rotating subassembly/drilling mud screen portion. In an embodiment, the third portion **3005c, 3105c** of the body **3005, 3105** is an outlet portion.

(534) In an embodiment, the first portion **3005a, 3105a** and the third portion **3005c, 3105c** may be any suitable shape. For example, suitable shapes include, but are not limited to, a cone, a cylinder, a rectangular prism (e.g., cubic, cuboid), a pentagonal prism, a sphere, a spheroid, a triangular prism, and combinations and/or portions thereof. In an embodiment, the first portion **3005a, 3105a** and the third portion **3005c, 3105c** may be a cylinder or a combination of cylinders.

(535) In an embodiment, the first portion **3005a, 3105a** and the third portion **3005c, 3105c** may have any suitable inner diameter or dimension. For example, a suitable inner diameter for the first portion **3005a, 3105a** and the third portion **3005c, 3105c** may be from about 2-inches to about 5-inches, and any range or value there between. In an embodiment, the inner diameter of the first portion **3005a, 3105a** and the third portion **3005c, 3105c** may be about 4.06-inches.

(536) In an embodiment, the second portion **3005b, 3105b** may be any suitable shape. For example, suitable shapes include, but are not limited to, a cone, a cylinder, a rectangular prism (e.g., cubic, cuboid), a pentagonal prism, a sphere, a spheroid, a triangular prism, and combinations and/or portions thereof. In an embodiment, the second portion **3005b, 3105b** may be a rectangular prism with open opposing sides. See e.g., FIGS. **30A-30C** & **31A-31C** (open front and rear sides).

(537) In an embodiment, the second portion **3005b, 3105b** may have any suitable inner diameter or dimension. For example, a suitable inner diameter for the second portion **3005b, 3105b** may be from about 6-inches to about 14-inches, and any range or value there between. In an embodiment, the inner diameter for the second portion **3005b, 3105b** may be about 10-inches.

(538) For example, a suitable inner dimension for the second portion **3005b, 3105b** may be from about 6-inches to about 14-inches square, and any range or value there between. In an embodiment, the inner dimension for the second portion **3005b, 3105b** may be about 10-inches square.

(539) In an embodiment, a drilling mud inlet **3020, 3120** of the drilling mud screen system **3000, 3100** may be fluidly connected to a high-pressure outlet of a drilling mud pump via a connection. In an embodiment, a drilling mud outlet **3025, 3125** of the drilling mud screen system **3000, 3100** may be fluidly connected to an inlet of a vibrator hose to a standpipe via a connection.

(540) Alternatively, the drilling mud screen system **3000, 3100** may be installed between an outlet of the vibrator hose and an inlet of the standpipe, or at any point in the standpipe via a connection.

(541) In an embodiment, the drilling mud inlet **3020, 3120** may be fluidly connected to, for example, an outlet to a drilling mud pump via a connection; and the drilling mud outlet **3025, 3125** may be fluidly connected to, for example, an inlet to a vibrator hose via a connection. Any suitable connection may be used for the drilling mud inlet and the drilling mud outlet. For example, suitable connections include, but are not limited to, pipe fittings and welds. Connections are well known in the art. In an embodiment, the drilling mud inlet **3020, 3120** may be fluidly connected to, for example, an outlet to a drilling mud pump via a weld; and the drilling mud outlet **3025, 3125** may be fluidly connected to, for example, an inlet to a vibrator hose via a weld.

(542) In an embodiment, the body **3005, 3105** of the drilling mud screen system **3000, 3100** may be constructed of any suitable material. For example, suitable materials include, but are not limited to, any alloy suitable for a drilling mud application. In an embodiment, the body **3005, 3105** may

be constructed of a low alloy steel (e.g., 4140, 4145, 4330), a stainless steel (e.g., 17-4, 304, 316), a super alloy (e.g., Inconel), a titanium alloy (e.g., Ti-6Al-4V, Ti-6Al-6V-2Sn), a copper alloy (e.g., Beryllium Copper), a Cobalt alloy (e.g., Stellite), an Aluminum alloy (e.g., 2024, 6061, 7075) and combination thereof. In an embodiment, the body **3005**, **3105** may be constructed of an American Iron and Steel Industry (AISI) **4130/75k** yield or equivalent material. In an embodiment, the inner surface of the body **3005**, **3105** may be unpainted. In an embodiment, the outer surface of the body **3005**, **3105** may be painted.

(543) Pivot Subassembly

(544) As shown in FIGS. **30A-30E** and **31A-31E**, the second portion **3005b**, **3105b** of the body **3005**, **3105** and/or the rotating subassembly **30400**, **31400** has a first shaft stud **3075**, **3175**, a second shaft stud **3080**, **3180**, a pivot shaft **3085**, **3185**, and a pivot drive **3090**, **3190**.

(545) In an embodiment, the rotating subassembly **30400**, **31400** may be retained in the second portion **3005b**, **3105b** of the body **3005**, **3105** via the first shaft stud **3075**, **3175** and the second shaft stud **3080**, **3180**. See e.g., FIGS. **30E** & **31D-31E**. In an embodiment, the rotating subassembly **30400**, **31400** may be retained in the second portion **3005b**, **3105b** of the body **3005**, **3105** via the first shaft stud **3075**, **3175** and the second shaft stud **3080**, **3180** such that the rotating subassembly **30400**, **31400** may rotate with respect to the second portion **3005b**, **3105b** of the body **3005**, **3105**.

(546) In an embodiment, the first shaft stud **3075**, **3175** or the second shaft stud **3080**, **3180** may be attached to the pivot drive **3090**, **3190** via the pivot shaft **3085**, **3185**.

(547) In an embodiment, the pivot drive **3090**, **3190** may be any suitable means of leverage to rotate the rotating subassembly. For example, suitable means of leverage include, but are not limited to a handle, a gear box, or other driving means. In an embodiment, the pivot drive **3090**, **3190** has a handle. In an embodiment, the pivot drive **3090**, **3190** has a gear box.

(548) Rotating Subassembly

(549) FIG. **30D** illustrates a detail view of a rotating subassembly **30400** of FIGS. **30A-30C**; and FIG. **30E** illustrates a cross-sectional view of the drilling mud screen system **3000** of FIG. **30A**, showing the rotating subassembly **30400** in a closed position.

(550) FIG. **31D** illustrates a partial cross-sectional view of the drilling mud screen system **3100** of FIG. **31A**, showing the rotating subassembly **31400** in the closed position; and FIG. **31E** illustrates a partial cross-sectional view of the drilling mud screen system **3100** of FIGS. **31A** and **31C-31D**, showing the rotating subassembly **31400** in the open position.

(551) As shown in FIGS. **30D-30E** and **31D-31E**, the rotating subassembly **30400**, **31400** has a first body **30405a**, **31405a** having a first end **30410a**, **31410a**, a second end **30415a**, **31415a**, a first drilling mud inlet **30420a**, **31420a** and a first drilling mud outlet **30425a**, **31425a**, a second body **30405b**, **31405b** having a first end **30410b**, **31410b**, a second end **30415b**, **31415b**, a second drilling mud inlet **30420b**, **31420b** and a second drilling mud outlet **30425b**, **31425b**, and a third body **30405c**, **31405c** having a first end **30410c**, **31410c**, a second end **30415c**, **31415c**, a third drilling mud inlet **30420c**, **31420c** and a third drilling mud outlet **30425c**, **31425c**.

(552) In an embodiment, the rotating subassembly **30400**, **31400** has a drilling mud screen **3040**, **3140** fluidly connected to and disposed between the second drilling mud inlet **30420b**, **31420b** and the second drilling outlet **30425b**, **31425b**.

(553) In an embodiment, the first body **30405a**, **31405a** is an inlet portion. In an embodiment, the second body **30405b**, **31405b** is a rotating subassembly/drilling mud screen portion. In an embodiment, the third body **30405c**, **31405c** is an outlet portion.

(554) In an embodiment, the first body **30405a**, **31405a** and the third body **30405c**, **31405c** may be any suitable shape. For example, suitable shapes include, but are not limited to, a cone, a cylinder, a rectangular prism (e.g., cubic, cuboid), a pentagonal prism, a sphere, a spheroid, a triangular prism, and combinations and/or portions thereof. In an embodiment, the first body **30405a**, **31405a** and the third body **30405c**, **31405c** may be a cylinder or a combination of cylinders.

(555) In an embodiment, the first body **30405a**, **31405a** and the third body **30405c**, **31405c** may have any suitable inner diameter or dimension. For example, a suitable inner diameter for the first body **30405a**, **31405a** and the third body **30405c**, **31405c** may be from about 2-inches to about 5-inches, and any range or value there between. In an embodiment, the inner diameter of the first body **30405a**, **31405a** and the third body **30405c**, **31405c** may be about 4.06-inches.

(556) In an embodiment, the second body **30405b**, **31405b** may be any suitable shape. For example, suitable shapes include, but are not limited to, a cone, a cylinder, a rectangular prism (e.g., cubic, cuboid), a pentagonal prism, a sphere, a spheroid, a triangular prism, and combinations and/or portions thereof. In an embodiment, the second body **30405b**, **31405b** may be a combination of cylinders. See e.g., FIGS. **30D-30E** & **31D-31E**.

(557) In an embodiment, the second body **30405b**, **31405b** may have any suitable inner diameter or dimension. For example, a suitable inner diameter for the second body **30405b**, **31405b** may be from about 4-inches to about 10-inches, and any range or value there between. In an embodiment, the inner diameter for the second body **30405b**, **31405b** may be about 6-inches.

(558) In an embodiment, an internal drilling mud outlet **3025a**, **3125a** of the body **3005**, **3105** of the drilling mud screen system **3000**, **3100** may be fluidly connected to the first drilling mud inlet **30420a**, **31420a** of the first body **30405a**, **31405a** of the rotating subassembly **30400**, **31400**.

(559) In an embodiment, the first drilling mud outlet **30425a**, **31425a** of the first body **30405a**, **31405a** of the rotating subassembly **30400**, **31400** may be fluidly connected to the second drilling mud inlet **30420b**, **31420b** of the second body **30405b**, **31405b** of the rotating subassembly **30400**, **31400**.

(560) In an embodiment, the second drilling mud outlet **30425b**, **31425b** of the second body **30405b**, **31405b** of the rotating subassembly **30400**, **31400** may be fluidly connected to the third drilling mud inlet **30420c**, **31420c** of the third body **30405c**, **31405c** of the rotating subassembly **30400**, **31400**.

(561) In an embodiment, the third drilling mud outlet **30425c**, **31425c** of the third body **30405c**, **31405c** of the rotating subassembly **30400**, **31400** may be fluidly connected to an internal drilling mud inlet **3020a**, **3120a** of the body **3005**, **3105** of the drilling mud screen system **3000**, **3100**.

(562) In an embodiment, a first guard ring **30430a**, **31430a** may be disposed between the body **3005**, **3105** of the drilling mud screen system **3000**, **3100** and the first end **30410a**, **31410a** of the first body **30405a**, **31405a** of the rotating subassembly **30400**, **31400**. See e.g., FIGS. **30E** & **31D-31E**. In an embodiment, a first guard ring **30430a**, **31430a** may be disposed in a first piston cavity **30435a**, **31435a** between the body **3005**, **3105** of the drilling mud screen system **3000**, **3100** and the first end **30410a**, **31410a** of the first body **30405a**, **31405a** of the rotating subassembly **30400**, **31400** to prevent buildup and compaction of debris in the first piston cavity **30435a**, **31435a**.

(563) In an embodiment, a second guard ring **30430b**, **31430b** may be disposed between the second end **30415c**, **31415c** of the third body **30405c**, **31405c** of the rotating subassembly **30400**, **31400** and the body **3005**, **3105** of the drilling mud screen system **3000**, **3100**. See e.g., FIGS. **30E** & **31D-31E**. In an embodiment, a second guard ring **30430b**, **31430b** may be disposed in a second piston cavity **30435b**, **31435b** between the second end **30415c**, **31415c** of the third body **30405c**, **31405c** of the rotating subassembly **30400**, **31400** and the body **3005**, **3105** of the drilling mud screen system **3000**, **3100** to prevent buildup and compaction of debris in the second piston cavity **30435b**, **31435b**.

(564) In an embodiment, the first guard ring **30430a**, **31430a** and the second guard ring **30430b**, **31430b** may be constructed of any suitable compressible material to prevent buildup and compaction of debris in first piston cavity **30435a**, **31435a** and the second piston cavity **30435b**, **31435b**, respectively.

(565) In an embodiment, a first spring **30440a**, **31440a** may be disposed between the body **3005**, **3105** of the drilling mud screen system **3000**, **3100** and the first body **30405a**, **31405a** of the rotating subassembly **30400**, **31400**. See e.g., FIGS. **30E** & **31D-31E**. In an embodiment, a first

spring **30440a**, **31440a** may be disposed in a first seal piston cavity **30445a**, **31445a** between the body **3005**, **3105** of the drilling mud screen system **3000**, **3100** and the first body **30405a**, **31405a** of the rotating subassembly **30400**, **31400** to engage and seal a second end **30415a**, **31415a** of the first body **30405a**, **31405a** with a first end **30410b**, **31410b** of a second body **30405b**, **31405b** of the rotating subassembly **30400**, **31400**.

(566) In an embodiment, a second spring **30440b**, **31440b** may be disposed between the third body **30405c**, **31504c** of the rotating subassembly **30400**, **31400** and the body **3005**, **3105** of the drilling mud screen system **3000**, **3100**. See e.g., FIGS. **30E** & **31D-31E**. In an embodiment, a second spring **30440b**, **31440b** may be disposed in a second seal piston cavity **30445b**, **31445b** between the third body **30405c** of the rotating subassembly **30400**, **31400** and the body **3005**, **3105** of the drilling mud screen system **3000**, **3100** to engage and seal a second end **30415b**, **31415b** of the second body **30405b**, **31405b** with a first end **30410c**, **31410c** of the third body **30405c**, **31405c** of the rotating subassembly **30400**, **31400**.

(567) In an embodiment, the body **3005**, **3105** of the drilling mud screen system **3000**, **3100** and the first body **30405a**, **31405a** of the rotating subassembly **30400**, **31400** may be sealed via an O-ring. See e.g., FIGS. **30E** & **31D-31E**. Any suitable O-ring may be used. For example, suitable O-rings include, but are not limited to, 300 Series O-rings. O-rings are well known in the art.

(568) In an embodiment, the third body **30405c**, **31405c** of the rotating subassembly **30400**, **31400** and the body **3005**, **3105** of the drilling mud screen system **3000**, **3100** may be sealed with via an O-ring. See e.g., FIG. **30E**. Any suitable O-ring may be used. For example, suitable O-rings include, but are not limited to, 300 Series O-rings. O-rings are well known in the art.

(569) In an embodiment, the second end **30415a**, **31415a** of the first body **30405a**, **31405a** of the rotating subassembly **30400**, **31400** has a first seal face **30450a**, **31450a**. See e.g., FIGS. **30E** & **31E**.

(570) In an embodiment, the first end **30410b**, **31410b** of the second body **30405b**, **31405b** of the rotating subassembly **30400**, **31400** has a second seal face **30450b**, **31450b**. See e.g., FIGS. **30E** & **31C-31E**.

(571) In an embodiment, the first seal face **30450a**, **31450a** and the second seal face **30450b**, **31450b** may have any suitable shapes to form a seal. For example, suitable shapes may be mating concave and convex surfaces, mating concave and convex surfaces similar to a ball valve, and combinations and variations thereof. In an embodiment, the first seal face **30450a**, **31450a** may be concave; and the second seal face **30450b**, **31450b** may be convex.

(572) In an embodiment, the second end **30415b**, **31415b** of the second body **30405b**, **31405b** of the rotating subassembly **3000**, **3100** has a third seal face **30450c**, **314050c**. See e.g., FIGS. **30E** & **31D 10077111n** an embodiment, the first end **30410c**, **314010c** of the third body **30405c**, **31405c** of the rotating subassembly **30400**, **31400** has a fourth seal face **30450d**, **31450d**. See e.g., FIGS. **30E** & **31C-31E**.

(573) In an embodiment, the third seal face **30450c**, **31450c** and the fourth seal face **30450d**, **31450d** may have any suitable shapes to form a seal. For example, suitable shapes may be mating concave and convex surfaces, mating concave and convex surfaces similar to a ball valve, and combinations and variations thereof. In an embodiment, the third seal face **30450c**, **31450c** may be convex; and the fourth seal face **30450d**, **31450d** may be concave.

(574) In an embodiment, the first body **30405a**, **31405a**, the second body **30405b**, **31405b** and the third body **30405c**, **31405c** of the rotating subassembly **30400**, **31400** may be constructed of any suitable material. For example, suitable materials include, but are not limited to, any alloy suitable for a drilling mud application. In an embodiment, the first body **30405a**, **31405a**, the second body **30405b**, **31405b** and the third body **30405c**, **31405c** may be constructed of a low alloy steel (e.g., **4140**, **4145**, **4330**), a stainless steel (e.g., 17-4, 304, 316), a super alloy (e.g., Inconel), a titanium alloy (e.g., Ti-6Al-4V, Ti-6Al-6V-2Sn), a copper alloy (e.g., Beryllium Copper), a Cobalt alloy (e.g., Stellite), an Aluminum alloy (e.g., 2024, 6061, 7075) and combination thereof. In an

embodiment, the first body **30405a**, **31405a**, the second body **30405b**, **31405b** and the third body **30405c**, **31405c** may be constructed of an American Iron and Steel Industry (AISI) **4130/75k** yield or equivalent material. In an embodiment, the inner surface of the first body **30405a**, **31405a**, the inner surface of the second body **30405b**, **31405b** and the inner surface of the third body **30405c**, **31405c** may be unpainted. In an embodiment, the outer surface of the first body **30405a**, **31405a**, the outer surface of the second body **30405b**, **31405b** and the outer surface of the third body **30405c**, **31405c** may be painted.

(575) Camming Seal Separator

(576) In an embodiment, a camming seal separator **30200**, **31200** may be used to prevent unnecessary wear to the seal faces **30450a**, **30450b**, **30450c**, **30450d**, **31450a**, **31450b**, **31450c**, **31450d**, as discussed below.

(577) In an embodiment, the camming seal separator **30200**, **31200** may be any suitable seal separator. For example, a suitable camming seal separator includes, but is not limited to, a face-rolling camming mechanism, a push-rod camming mechanism, and combinations and variations thereof. In an embodiment, the camming seal separator **30200**, **31200** has a face-roller camming mechanism. See e.g., FIGS. **30C-30D** & **31C-31E**.

(578) Face-Rolling Camming Mechanism

(579) FIG. **30C** illustrates an upper, left perspective view of the drilling mud screen system **3000** of FIG. **30A**, showing a rotating subassembly **30400** in the open position; and FIG. **30D** illustrates a detail view of a rotating subassembly **30400** of FIGS. **30A-30C**.

(580) FIG. **31C** illustrates a left perspective view of the drilling mud screen system **3100** of FIG. **30A**, showing a rotating subassembly **31400** in the open position; FIG. **31D** illustrates a partial cross-sectional view of the drilling mud screen system **3100** of FIG. **31A**, showing the rotating subassembly **31400** in the closed position; and FIG. **31E** illustrates a partial cross-sectional view of the drilling mud screen system **3100** of FIGS. **31A** and **31C-31D**, showing the rotating subassembly **31400** in the open position.

(581) As shown in FIGS. **30C-30D** and **31C-31E**, the rotating subassembly **30400**, **31400** has a first face-rolling camming mechanism **30200a**, **31200a** and a second face-rolling camming mechanism **30200b**, **31200b**.

(582) In an embodiment, the first face-rolling camming mechanism **30200a**, **31200a** has a first cam roller **30205a**, **31205a**, a first roller bracket **30210a**, **31210a** and a first cam track **30215a**, **31215a**.

(583) In an embodiment, the second face-rolling camming mechanism **30200b**, **31200b** has a second cam roller **30205b**, **31205b**, a second roller bracket **30210b**, **31210b**, and a second cam track **30215b**, **31215b**.

(584) In an embodiment, the first cam roller **30205a**, **31205a** may be attached to a second end **30415a**, **31415a** of the first body **30405a**, **31405a** of the rotating subassembly **30400**, **31400**. In an embodiment, the first cam roller **30205a**, **31205a** may be attached to a second end **30415a**, **31415a** of the first body **30405a**, **31405a** of the rotating subassembly **3040**, **31400** via fasteners. Any suitable fastener may be used for the first cam roller **30205a**, **31205a** and the first body **30405a**, **31405a** of the rotating subassembly **30400**, **31400**. For example, suitable fasteners include, but are not limited to, bolts, screws, pins, rivets, welds, and combinations thereof. Fasteners are well known in the art.

(585) In an embodiment, the first roller bracket **30210a**, **31210a** may be attached to a second end **30415b**, **31415b** of the first body **30405a**, **31405a** of the rotating subassembly **30400**, **31400**. In an embodiment, the first roller bracket **30210a**, **31210a** may be attached to a second end **30415b**, **31415b** of the first body **30405a**, **31405a** of the rotating subassembly **30400**, **31400** via fasteners. Any suitable fastener may be used for the first roller bracket **30210a**, **31210a** and the first body **30405a**, **31405a** of the rotating subassembly **30400**, **31400**. For example, suitable fasteners include, but are not limited to, bolts, screws, pins, rivets, welds, and combinations thereof. Fasteners are well known in the art.

(586) In an embodiment, the first cam roller **30205a, 31205a** may be attached to the first roller bracket **30210a, 31210a**. In an embodiment, the first cam roller **30205a, 31205a** may be attached to the first roller bracket **30210a, 31210a** via fasteners. Any suitable fastener may be used for the first cam roller **30205a, 31205a** and the first roller bracket **30210a, 31210a**. For example, suitable fasteners include, but are not limited to, bolts, screws, pins, rivets, welds, and combinations thereof. Fasteners are well known in the art.

(587) In an embodiment, the first cam track **30215a, 31215a** may be attached to a first end **30410b, 31410b** of the second body **30405b, 31405b** of the rotating subassembly **30400, 31400**. In an embodiment, the first cam track **30215a, 31215a** may be attached to a first end **30410b, 31410b** of the second body **30405b, 31405b** of the rotating subassembly **30400, 31400** via fasteners. Any suitable fasteners may be used for the first cam track **30215a, 31215a** and the second body **30405b, 31405b** of the rotating subassembly **30400, 31400**. For example, suitable fasteners include, but are not limited to, bolts, screws, pins, rivets, welds, and combinations thereof. Fasteners are well known in the art.

(588) In a closed position for the rotating subassembly **30400, 31400**, the first cam roller **30205a, 31205a** may be disposed in a first recessed portion of the first cam track **30215a, 31215a** allowing the second end **30415a, 31415a** of the first body **30405a, 31405a** of the rotating subassembly **30400, 31400** to close against the first end **3010b, 3110b** of the second body **30405b, 31405b** of the rotating subassembly **30400, 31400** and to form a first seal between seal faces **30450a, 30450b, 31450a, 31450b**.

(589) As the rotating subassembly **30400, 31400** rotates, the first cam roller **30205a, 31205a** travels along the first cam track **30215a, 31215a** and collapses the first body **30405a, 31405a** of the rotating subassembly **30400, 31400** into the body **3005, 3105** to prevent unnecessary wear to the seal faces **30450a, 30450b, 31450a, 31450b**.

(590) In an embodiment, the second cam roller **30205b, 31205b** may be attached to a second end **30415b, 31415b** of the second body **30405b, 31405b** of the rotating subassembly **30400, 31400**. In an embodiment, the second cam roller **30205b, 31205b** may be attached to a second end **30415b, 31415b** of the second body **30405b, 31405b** of the rotating subassembly **30400, 31400** via fasteners. Any suitable fastener may be used for the second cam roller **30205b, 31205b** and the second body **30405b, 31405b** of the rotating subassembly **30400, 31400**. For example, suitable fasteners include, but are not limited to, bolts, screws, pins, rivets, welds, and combinations thereof. Fasteners are well known in the art.

(591) In an embodiment, the second roller bracket **30210b, 31210b** may be attached to a first end **30410c, 31410c** of the third body **30405c, 31405c** of the rotating subassembly **30400, 31400**. In an embodiment, the second roller bracket **30210b, 31210b** may be attached to a first end **30410c, 31410c** of the third body **30405c, 31405c** of the rotating subassembly **30400, 31400** via fasteners. Any suitable fastener may be used for the second roller bracket **30210b, 31210b** and the third body **30405c, 31405c** of the rotating subassembly **30400, 31400**. For example, suitable fasteners include, but are not limited to, bolts, screws, pins, rivets, welds, and combinations thereof. Fasteners are well known in the art.

(592) In an embodiment, the second cam roller **30205b, 31205b** may be attached to the second roller bracket **30210b, 31210b**. In an embodiment, the second cam roller **30205b, 31205b** may be attached to the second roller bracket **30210b, 31210b** via fasteners. Any suitable fastener may be used for the second cam roller **30205b, 31205b** and the second roller bracket **30210b, 31210b**. For example, suitable fasteners include, but are not limited to, bolts, screws, pins, rivets, welds, and combinations thereof. Fasteners are well known in the art.

(593) In an embodiment, the second cam track **30215b, 31215b** may be attached to a second end **30415b, 31415b** of the second body **30405b, 31405b** of the rotating subassembly **30400, 31400**. In an embodiment, the second cam track **30215b, 31215b** may be attached to a second end **30415b, 31415b** of the second body **30405b, 31405b** of the rotating subassembly **30400, 31400** via

fasteners. Any suitable fasteners may be used for the second cam track **30215b**, **31215b** and the second body **30405b**, **31405b** of the rotating subassembly **30400**, **31400**. For example, suitable fasteners include, but are not limited to, bolts, screws, pins, rivets, welds, and combinations thereof. Fasteners are well known in the art.

(594) In a closed position for the rotating subassembly **30400**, **31400**, the second cam roller **30205b**, **31205b** may be disposed in a second recessed portion of the second cam track **30215b**, **31215b** allowing the second end **30415b**, **31415b** of the second body **30405b**, **31405b** of the rotating subassembly **30400**, **31400** to close against the first end **30410c**, **31410c** of the third body **30405c**, **31405c** of the rotating subassembly **30400**, **31400** to form a second seal between seal faces **30450c**, **30450d**, **31450c**, **31450d**.

(595) As the rotating subassembly **30400**, **31400** rotates, the second cam roller **30205b**, **31205b** travels along the second cam track **30215b**, **31215b** and collapses the third body **30405c**, **31405c** of the rotating subassembly **30400**, **31400** into the body **3005**, **3105** to prevent unnecessary wear to the seal faces **30450c**, **30450d**, **31450c**, **31450d**.

(596) Body with Push-Rod Camming Mechanism

(597) FIG. **32A** illustrates an upper, left perspective view of an exemplary drilling mud screen system **3200** with a camming seal separator **32300** having a push-rod camming mechanism **32300a** according to an embodiment of the present invention, showing a rotating subassembly **32400** in a closed position; FIG. **32B** illustrates the upper, left perspective view of the drilling mud screen system **3200** of FIG. **32A**, showing the rotating subassembly **32400** in an open position; and FIG. **32C** illustrates a cross-sectional view of the drilling mud screen system **3200** of FIG. **32A**, showing the rotating subassembly **32400** in a closed position.

(598) FIG. **33A** illustrates a left perspective view of an exemplary drilling mud screen system **3300** with camming seal separator **33300** having a push-rod camming mechanism **33300a** according to an embodiment of the present invention, showing a rotating subassembly **33400** in a closed position; FIG. **33B** illustrates a left perspective view of the drilling mud screen system **3300** of FIG. **33A**, showing the rotating subassembly **33400** in an open position; FIG. **33C** illustrates a detail view of the push-rod camming mechanism **33300a** of FIG. **33A**, showing the rotating subassembly **33400** in a closed position; FIG. **33D** illustrates a detail view of the push-rod camming mechanism **33300a** of FIGS. **33A** and **33C**, showing the rotating subassembly **33400** in the open position; and FIG. **33E** illustrates a partial cross-sectional view of the drilling mud screen system **3300** of FIG. **33A**, showing the rotating subassembly **33400** in the closed position.

(599) As shown in FIGS. **32A-32D** and **33A-33E**, the drilling mud screen system **3200**, **3300** has a body **3205**, **3305** having a first end **3210**, **3310** and a second end **3215**, **3315**, an inlet **3220**, **3320** and an outlet **3225**, **3325**, and drilling mud screen access port **3230**, **3330**.

(600) In an embodiment, the drilling mud screen system **3200**, **3300** has a drilling mud screen **3240**, **3340** fluidly connected to and disposed between the drilling mud inlet **3220**, **3320** and the drilling outlet **3225**, **3325**.

(601) In an embodiment, the body **3205**, **3305** has a first portion **3205a**, **3305a**, a second portion **3205b**, **3305b** and a third portion **3205c**, **3305c**. In an embodiment, the first portion **3205a**, **3305a** of the body **3205**, **3305** is an inlet portion. In an embodiment, the second portion **3205b**, **3305b** of the body **3205**, **3305** is a rotating subassembly/drilling mud screen portion. In an embodiment, the third portion **3205c**, **3305c** of the body **3205**, **3305** is an outlet portion.

(602) In an embodiment, the first portion **3205a**, **3305a** and the third portion **3205c**, **3305c** may be any suitable shape. For example, suitable shapes include, but are not limited to, a cone, a cylinder, a rectangular prism (e.g., cubic, cuboid), a pentagonal prism, a sphere, a spheroid, a triangular prism, and combinations and/or portions thereof. In an embodiment, the first portion **3205a**, **3305a** and the third portion **3205c**, **3305c** may be a cylinder or a combination of cylinders.

(603) In an embodiment, the first portion **3205a**, **3305a**, and the third portion **3205c**, **3305c** may have any suitable inner diameter or dimension. For example, a suitable inner diameter for the first

portion **3205a**, **3305a** and the third portion **3205c**, **3305c** may be from about 2-inches to about 5-inches, and any range or value there between. In an embodiment, the inner diameter of the first portion **3205a**, **3305a** and the third portion **3205c**, **3305c** may be about 4.06-inches.

(604) In an embodiment, the second portion **3205b**, **3305b** may be any suitable shape. For example, suitable shapes include, but are not limited to, a cone, a cylinder, a rectangular prism (e.g., cubic, cuboid), a pentagonal prism, a sphere, a spheroid, a triangular prism, and combinations and/or portions thereof. In an embodiment, the second portion **3205b**, **3305b** may be a rectangular prism with open opposing sides. See e.g., FIGS. **30A-30C** & **31A-31C** (open front and rear sides).

(605) In an embodiment, the second portion **3205b**, **3305b** may have any suitable inner diameter or dimension. For example, a suitable inner diameter for the second portion **3205b**, **3305b** may be from about 6-inches to about 14-inches, and any range or value there between. In an embodiment, the inner diameter for the second portion **3205b**, **3305b** may be about 10-inches.

(606) For example, a suitable inner dimension for the second portion **3205b**, **3305b** may be from about 6-inches to about 14-inches square, and any range or value there between. In an embodiment, the inner dimension for the second portion **3205b**, **3305b** may be about 10-inches square.

(607) In an embodiment, a drilling mud inlet **3220**, **3320** of the drilling mud screen system **3200**, **3300** may be fluidly connected to a high-pressure outlet of a drilling mud pump via a connection. In an embodiment, a drilling mud outlet **3225**, **3325** of the drilling mud screen system **3200**, **3300** may be fluidly connected to an inlet of a vibrator hose to a standpipe via a connection.

(608) Alternatively, the drilling mud screen system **3200**, **3300** may be installed between an outlet of the vibrator hose and an inlet of the standpipe, or at any point in the standpipe via a connection.

(609) In an embodiment, the drilling mud inlet **3220**, **3320** may be fluidly connected to, for example, an outlet to a drilling mud pump via a connection; and the drilling mud outlet **3225**, **3325** may be fluidly connected to, for example, an inlet to a vibrator hose via a connection. Any suitable connection may be used for the drilling mud inlet and the drilling mud outlet. For example, suitable connections include, but are not limited to, pipe fittings and welds. Connections are well known in the art. In an embodiment, the drilling mud inlet **3220**, **3320** may be fluidly connected to, for example, an outlet to a drilling mud pump via a weld; and the drilling mud outlet **3225**, **3325** may be fluidly connected to, for example, an inlet to a vibrator hose via a weld.

(610) In an embodiment, the body **3205**, **3305** of the drilling mud screen system **3200**, **3300** may be constructed of any suitable material. For example, suitable materials include, but are not limited to, any alloy suitable for a drilling mud application. In an embodiment, the body **3205**, **3305** may be constructed of a low alloy steel (e.g., **4140**, **4145**, **4330**), a stainless steel (e.g., 17-4, 304, 316), a super alloy (e.g., Inconel), a titanium alloy (e.g., Ti-6Al-4V, Ti-6Al-6V-2Sn), a copper alloy (e.g., Beryllium Copper), a Cobalt alloy (e.g., Stellite), an Aluminum alloy (e.g., 2024, 6061, 7075), and combinations thereof. In an embodiment, the body **3205**, **3305** may be constructed of an American Iron and Steel Industry (AISI) **4130/75k** yield or equivalent material. In an embodiment, the inner surface of the body **3205**, **3305** may be unpainted. In an embodiment, the outer surface of the body **3205**, **3305** may be painted.

(611) Pivot Subassembly

(612) As shown in FIGS. **32A-32D** and **33A-33E**, the second portion **3205b**, **3305b** of the body **3205**, **3305** and/or the rotating subassembly **32400**, **33400** has a first shaft stud **3275**, **3375**, a second shaft stud **3280**, **3380**, a pivot shaft **3285**, **3385**, and a pivot drive **3290**, **3390**.

(613) In an embodiment, the rotating subassembly **32400**, **33400** may be retained in the second portion **3205b**, **3305b** of the body **3205**, **3305** via the first shaft stud **3275**, **3375** and the second shaft stud **3280**, **3380**. See e.g., FIGS. **32D** & **33E**. In an embodiment, the rotating subassembly **32400**, **33400** may be retained in the second portion **3205b**, **3305b** of the body **3205**, **3305** via the first shaft stud **3275**, **3375** and the second shaft stud **3280**, **3380** such that the rotating subassembly **32400**, **33400** may rotate with respect to the second portion **3205b**, **3305b** of the body **3205**, **3305**.

(614) In an embodiment, the first shaft stud **3275**, **3375** or the second shaft stud **3280**, **3380** may be

attached to the pivot drive **3290, 3390** via the pivot shaft **3285, 3385**.

(615) In an embodiment, the pivot drive **3290, 3390** may be any suitable means of leverage to rotate the rotating subassembly. For example suitable means of leverage include, but are not limited to a handle, a gear box, or other driving means. In an embodiment, the pivot drive **3290, 3390** has a handle. In an embodiment, the pivot drive **3290, 3390** has a gear box.

(616) Rotating Subassembly

(617) FIG. **32C** illustrates a cross-sectional view of the drilling mud screen system **3200** of FIG. **32A**, showing the rotating subassembly **32400** in a closed position.

(618) FIG. **33E** illustrates a partial cross-sectional view of the drilling mud screen system **3300** of FIG. **33A**, showing the rotating subassembly **33400** in the closed position.

(619) As shown in FIGS. **32C** and **33E**, the rotating subassembly **32400, 33400** has a first body **32405a, 33405a** having a first end **32410a, 33410a**, a second end **32415a, 33415a**, a first drilling mud inlet **32420a, 33420a** and a first drilling mud outlet **32425a, 33425a**, a second body **32405b, 33405b** having a first end **32410b, 33410b**, a second end **32415b, 33415b**, a second drilling mud inlet **32420b, 33420b** and a second drilling mud outlet **32425b, 33425b**, and a third body **32405c, 33405c** having a first end **32410c, 33410c**, a second end **32415c, 33415c**, a third drilling mud inlet **32420c, 33420c** and a third drilling mud outlet **32425c, 33425c**.

(620) In an embodiment, the rotating subassembly **32400, 33400** has a drilling mud screen **3240, 3340** fluidly connected to and disposed between the second drilling mud inlet **32420b, 33420b** and the second drilling outlet **32425b, 33425b**.

(621) In an embodiment, the first body **32405a, 33405a** is an inlet portion. In an embodiment, the second body **32405b, 33405b** is a rotating subassembly/drilling mud screen portion. In an embodiment, the third body **32405c, 33405c** is an outlet portion.

(622) In an embodiment, the first body **32405a, 33405a** and the third body **32405c, 33405c** may be any suitable shape. For example, suitable shapes include, but are not limited to, a cone, a cylinder, a rectangular prism (e.g., cubic, cuboid), a pentagonal prism, a sphere, a spheroid, a triangular prism, and combinations and/or portions thereof. In an embodiment, the first body **32405a, 33405a** and the third body **32405c, 33405c** may be a cylinder or a combination of cylinders. See e.g., FIGS. **32C & 33E-33F**.

(623) In an embodiment, the first body **32405a, 33405a** and the third body **32405c, 33405c** may have any suitable inner diameter or dimension. For example, a suitable inner diameter for the first body **32405a, 33405a** and the third body **32405c, 33405c** may be from about 2-inches to about 5-inches, and any range or value there between. In an embodiment, the inner diameter of the first body **32405a, 33405a** and the third body **32405c, 33405c** may be about 4.06-inches.

(624) In an embodiment, the second body **32405b, 33405b** may be any suitable shape. For example, suitable shapes include, but are not limited to, a cone, a cylinder, a rectangular prism (e.g., cubic, cuboid), a pentagonal prism, a sphere, a spheroid, a triangular prism, and combinations and/or portions thereof. In an embodiment, the second body **32405b, 33405b** may be a combination of cylinders. See e.g., FIGS. **32C & 33E-33F**.

(625) In an embodiment, the second body **32405b, 33405b** may have any suitable inner diameter or dimension. For example, a suitable inner diameter for the second body **32405b, 33405b** may be from about 4-inches to about 10-inches, and any range or value there between. In an embodiment, the inner diameter for the second body **32405b, 33405b** may be about 6-inches.

(626) In an embodiment, the rotating subassembly **32400, 33400** has a drilling mud screen **3240, 3340** fluidly connected to and disposed between the second drilling mud inlet **32420b, 33420b** and the second drilling outlet **32425b, 33425b**.

(627) In an embodiment, an internal drilling mud outlet **3225a, 3325a** of the body **3205, 3305** of the drilling mud screen system **3200, 3300** may be fluidly connected to the first drilling mud inlet **32420a, 33420a** of the first body **32405a, 33405a** of the rotating subassembly **32400, 33400**.

(628) In an embodiment, the first drilling mud outlet **32425a, 33425a** of the first body **32405a,**

33405a of the rotating subassembly **32400**, **33400** may be fluidly connected to the second drilling mud inlet **32420b**, **33420b** of the second body **32405b**, **33405b** of the rotating subassembly **32400**, **33400**.

(629) In an embodiment, the second drilling mud outlet **32425b**, **33425b** of the second body **32405b**, **33405b** of the rotating subassembly **32400**, **33400** may be fluidly connected to the third drilling mud inlet **32420c**, **33420c** of the third body **32405c**, **33405c** of the rotating subassembly **32400**, **33400**.

(630) In an embodiment, the third drilling mud outlet **32425c**, **33425c** of the third body **32405c**, **33405c** of the rotating subassembly **32400**, **33400** may be fluidly connected to an internal drilling mud inlet **3220a**, **3320a** of the body **3205**, **3305** of the drilling mud screen system **3200**, **3300**.

(631) In an embodiment, a first guard ring **32430a**, **33430a** may be disposed between the body **3205**, **3305** of the drilling mud screen system **3200**, **3300** and the first end **32410a**, **33410a** of the first body **32405a**, **33405a** of the rotating subassembly **32400**, **33400**. See e.g., FIGS. 32D & 33E-33F. In an embodiment, a first guard ring **32430a**, **33430a** may be disposed in a first piston cavity **32435a**, **33435a** between the body **3205**, **3305** of the drilling mud screen system **3200**, **3300** and the first end **32410a**, **33410a** of the first body **32405a**, **33405a** of the rotating subassembly **32400**, **33400** to prevent buildup and compaction of debris in the first piston cavity **32435a**, **33435a**.

(632) In an embodiment, a second guard ring **32430b**, **33430b** may be disposed between the second end **32415c**, **33415c** of the third body **32405c**, **33405c** of the rotating subassembly **32400**, **33400** and the body **3205**, **3305** of the drilling mud screen system **3200**, **3300**. See e.g., FIGS. 32D & 33E-33F. In an embodiment, a second guard ring **32430b**, **33430b** may be disposed in a second piston cavity **32435b**, **33435b** between the second end **32415c**, **33415c** of the third body **32405c**, **33405c** of the rotating subassembly **32400**, **33400** and the body **3205**, **3305** of the drilling mud screen system **3200**, **3300** to prevent buildup and compaction of debris in the second piston cavity **32435b**, **33435b**.

(633) In an embodiment, the first guard ring **32430a**, **33430a** and the second guard ring **32430b**, **33430b** may be constructed of any suitable compressible material to prevent buildup and compaction of debris in first piston cavity **32435a**, **33435a** and the second piston cavity **32435b**, **33435b**, respectively.

(634) In an embodiment, a first spring **32440a**, **33440a** may be disposed between the body **3205**, **3305** of the drilling mud screen system **3200**, **3300** and the first body **32405a**, **33405a** of the rotating subassembly **32400**, **33400**. See e.g., FIGS. 32D & 33E-33F. In an embodiment, a first spring **32440a**, **33440a** may be disposed in a first seal piston cavity **32445a**, **33445a** between the body **3205**, **3305** of the drilling mud screen system **3200**, **3300** and the first body **32405a**, **33405a** of the rotating subassembly **32400**, **33400** to engage and seal a second end **32415a**, **33415a** of the first body **32405a**, **33405a** with a first end **32410b**, **33410b** of a second body **32405b**, **33405b** of the rotating subassembly **32400**, **33400**.

(635) In an embodiment, a second spring **32440b**, **33440b** may be disposed between the third body **32405c**, **33405c** of the rotating subassembly **32400**, **33400** and the body **3205**, **3305** of the drilling mud screen system **3200**, **3300**. See e.g., FIGS. 32D & 33E. In an embodiment, a second spring **32440b**, **33440b** may be disposed in a second seal piston cavity **32445b**, **33445b** between the third body **32405c**, **33405c** of the rotating subassembly **32400**, **33400** and the body **3205**, **3305** of the drilling mud screen system **3200**, **3300** to engage and seal a second end **32415b**, **33415b** of the second body **32405b**, **33405b** with a first end **32410c**, **33410c** of the third body **32405c**, **33405c** of the rotating subassembly **32400**, **33400**.

(636) In an embodiment, the body **3205**, **3305** of the drilling mud screen system **3200**, **3300** and the first body **32405a**, **33405a** of the rotating subassembly **32400**, **33400** may be sealed via an O-ring. See e.g., FIGS. 32D & 33E-33F. Any suitable O-ring may be used. For example, suitable O-rings include, but are not limited to, 300 Series O-rings. O-rings are well known in the art.

(637) In an embodiment, the third body **32405c**, **33405c** of the rotating subassembly **32400**, **33400**

and the body **3205**, **3305** of the drilling mud screen system **3200**, **3300** may be sealed with via an O-ring. See e.g., FIG. **32D**. Any suitable O-ring may be used. For example, suitable O-rings include, but are not limited to, 300 Series O-rings. O-rings are well known in the art.

(638) In an embodiment, the second end **32415a**, **33415a** of the first body **32405a**, **33405a** of the rotating subassembly **32400**, **33400** has a first seal face **32450a**, **33450a**. See e.g., FIGS. **32D** & **33E-33F**.

(639) In an embodiment, the first end **32410b**, **33410b** of the second body **32405b**, **33405b** of the rotating subassembly **32400**, **33400** has a second seal face **32450b**, **33450b**. See e.g., FIGS. **32D** & **33E-33F**.

(640) In an embodiment, the first seal face **32450a**, **33450a** and the second seal face **32450b**, **33450b** may have any suitable shapes to form a seal. For example, suitable shapes may be mating concave and convex surfaces, mating concave and convex surfaces similar to a ball valve, and combinations and variations thereof. In an embodiment, the first seal face **32450a**, **33450a** may be concave; and the second seal face **32450b**, **33450b** may be convex.

(641) In an embodiment, the second end **32415b**, **33415b** of the second body **32405b**, **33405b** of the rotating subassembly **3200**, **3300** has a third seal face **32450c**, **334050c**. See e.g., FIGS. **32D** & **33E**.

(642) In an embodiment, the first end **324010c**, **334010c** of the third body **32405c**, **33405c** of the rotating subassembly **32400**, **33400** has a fourth seal face **32450d**, **33450d**. See e.g., FIGS. **32D** & **33E**.

(643) In an embodiment, the third seal face **32450c**, **33450c** and the fourth seal face **32450d**, **33450d** may have any suitable shapes to form a seal. For example, suitable shapes may be mating concave and convex surfaces, mating concave and convex surfaces similar to a ball valve, and combinations and variations thereof. In an embodiment, the third seal face **32450c**, **33450c** may be convex; and the fourth seal face **32450d**, **33450d** may be concave.

(644) In an embodiment, the first body **32405a**, **33405a**, the second body **32405b**, **33405b** and the third body **32405c**, **33405c** of the rotating subassembly **32400**, **33400** may be constructed of any suitable material. For example, suitable materials include, but are not limited to, any alloy suitable for a drilling mud application. In an embodiment, the first body **32405a**, **33405a**, the second body **32405b**, **33405b** and the third body **32405c**, **33405c** may be constructed of a low alloy steel (e.g., **4140**, **4145**, **4330**), a stainless steel (e.g., 17-4, 304, 316), a super alloy (e.g., Inconel), a titanium alloy (e.g., Ti-6Al-4V, Ti-6Al-6V-2Sn), a copper alloy (e.g., Beryllium Copper), a Cobalt alloy (e.g., Stellite), an Aluminum alloy (e.g., 2024, 6061, 7075) and combination thereof. In an embodiment, the first body **32405a**, **33405a**, the second body **32405b**, **33405b** and the third body **32405c**, **33405c** may be constructed of an American Iron and Steel Industry (AISI) **4130/75k** yield or equivalent material. In an embodiment, the inner surface of the first body **32405a**, **33405a**, the inner surface of the second body **32405b**, **33405b** and the inner surface of the third body **32405c**, **33405c** may be unpainted. In an embodiment, the outer surface of the first body **32405a**, **33405a**, the outer surface of the second body **32405b**, **33405b** and the outer surface of the third body **32405c**, **33405c** may be painted.

(645) Camming Seal Separator

(646) In an embodiment, a camming seal separator **32300**, **33300** may be used to prevent unnecessary wear to the seal faces **32450a**, **32450b**, **32450c**, **32450d**, **33450a**, **33450b**, **33450c**, **33450d**, as discussed below.

(647) In an embodiment, the camming seal separator **32300**, **33300** may be any suitable seal separator. For example, a suitable camming seal separator includes, but is not limited to, a face-rolling camming mechanism, a push-rod camming mechanism, and combinations and variations thereof. In an embodiment, the camming seal separator **32300**, **33300** has a push-rod camming mechanism. See e.g., FIGS. **32A** & **33C-33F**.

(648) Push-Rod Camming Mechanism

(649) FIG. 32A illustrates an upper, left perspective view of an exemplary drilling mud screen system **3200** with a camming seal separator **32300** having a push-rod camming mechanism **32300a** according to an embodiment of the present invention, showing a rotating subassembly **32400** in a closed position; and FIG. 32B illustrates the upper, left perspective view of the drilling mud screen system **3200** of FIG. 32A, showing the rotating subassembly **32400** in an open position.

(650) FIG. 33C illustrates a detail view of the push-rod camming mechanism **33300a** of FIG. 33A, showing the rotating subassembly **33400** in a closed position; FIG. 33D illustrates a detail view of the push-rod camming mechanism **33300a** of FIGS. 33A and 33C, showing the rotating subassembly **33400** in the open position; FIG. 33E illustrates a partial cross-sectional view of the drilling mud screen system **3300** of FIG. 33A, showing the rotating subassembly **33400** in the closed position; and FIG. 33F illustrates a detail view of the push-rod camming mechanism **33300a** of FIG. 33A, showing the rotating subassembly **33400** in the closed position.

(651) As shown in FIGS. 32A-32B and 33C-33F, the body **3205**, **3305** has a first push-rod camming mechanism **32300a**, **33300a** and a second push-rod camming mechanism **32300b**, **33300b**.

(652) In an embodiment, the first push-rod camming mechanism **32300a**, **33300a** has a first pivot pin **32305a**, **33305a**, a first push rod **32310a**, **33310a**, a first guide block **32315a**, **33315a**, a first spring **32320a**, **33320a**, a first cam roller **32325a**, **33325a** and a cam **32330**, **33330**.

(653) In an embodiment, the second push-rod camming mechanism **32300b**, **33300b** has a second pivot pin **32305b**, **33305b**, a second push rod **32310b**, **33310b**, a second guide block **32315b**, **33315b**, a second spring **32320b**, **33320b**, a second cam roller **32325b**, **33325b** and a cam **32330**, **33330**.

(654) In an embodiment, a first end of the first pivot pin **32305a**, **33305a** may be attached to the first body **32405a**, **33405a** of the rotating subassembly **32400**, **33400** through the first portion **3205a**, **3305a** of the body **3205**, **3305**. In an embodiment, a first end of the first pivot pin **32305a**, **33305a** may be attached to the first body **32405a**, **33405a** of the rotating subassembly **32400**, **33400** through the first portion **3205a**, **3305a** of the body **3205**, **3305** via fasteners. Any suitable fasteners may be used for the first pivot pin **32305a**, **33305a** and the first body **32405a**, **33405a** of the rotating subassembly **32400**, **33400**. For example, suitable fasteners include, but are not limited to, bolts, screws, pins, rivets, welds, and combinations thereof. Fasteners are well known in the art.

(655) In an embodiment, a second end of the first pivot pin **32305a**, **33305a** may be attached to a first end of the first push rod **32310a**, **33310a**. In an embodiment, a second end of the first pivot pin **32305a**, **33305a** may be attached to a first end of the first push rod **32310a**, **33310a** via fasteners. Any suitable fasteners may be used for the first pivot pin **32305a**, **33305a** and the first push rod **32310a**, **33310a**. For example, suitable fasteners include, but are not limited to, bolts, screws, pins, rivets, welds, and combinations thereof. Fasteners are well known in the art.

(656) In an embodiment, a second end of the first push rod **32310a**, **33310a** may be attached to a first cam roller **32325a**, **33325a**. In an embodiment, a second end of the first push rod **32310a**, **33310a** may be attached to a first cam roller **32325a**, **33325a** via fasteners. Any suitable fasteners may be used for the first push rod **32310a**, **33310a** and the first cam roller **32325a**, **33325a**. For example, suitable fasteners include, but are not limited to, bolts, screws, pins, rivets, welds, and combinations thereof. Fasteners are well known in the art.

(657) In an embodiment, the first cam roller **32325a**, **33325a** may travel along a surface of the cam **32330**, **33330**.

(658) In an embodiment, the cam **32330**, **33330** may be attached to the pivot drive **3290**, **3390**. In an embodiment, the cam **32330**, **33330** may be attached to the pivot drive **3290**, **3390** via fasteners. Any suitable fasteners may be used for the cam **32330**, **33330** and the pivot drive **3290**, **3390**. For example, suitable fasteners include, but are not limited to, bolts, screws, pins, rivets, welds, and combinations thereof. Fasteners are well known in the art.

(659) In an embodiment, the cam **32330**, **33330** may be any suitable shape. For example, suitable

shapes include, but are not limited to, an “∞” shape, an “8” shape, a “0” shape, an “O” shape, and combinations and/or portions thereof. In an embodiment, the cam **32330**, **33330** may be a double lobed shape. See e.g., FIGS. **33C-33D**.

(660) In an embodiment, the first push rod **32310a**, **33310a** may be any suitable shape. For example, suitable shapes include, but are not limited to, a cross shape, a “T” shape, a “Y” shape, and combinations and/or portions thereof. In an embodiment, the second body **32310b**, **33310b** may be a cross shape. See e.g., FIGS. **32A-32B** & **33A-33D**.

(661) In an embodiment, a first guide block **32315a**, **33315a** may be attached to the second portion **3205b**, **3305b** of the body **3205**, **3305**. In an embodiment, a first guide block **32315a**, **33315a** may be attached to the second portion **3205b**, **3305b** of the body **3205**, **3305** via fasteners. Any suitable fasteners may be used for the first guide block **32315a**, **33315a** and the second portion **3205b**, **3305b** of the body **3205**, **3305**. For example, suitable fasteners include, but are not limited to, bolts, screws, pins, rivets, welds, and combinations thereof. Fasteners are well known in the art.

(662) In an embodiment, the first push rod **32310a**, **33310a** may pass through the first guide block **32315a**, **33315a**.

(663) In an embodiment, a first end of the first spring **32320a**, **33320a** may be attached to the first guide block **32315a**, **33315a**. In an embodiment, a first end of the first spring **32320a**, **33320a** may be attached to the first guide block **32315a**, **33315a** via fasteners. Any suitable fastener may be used for the first spring **32320a**, **33320a** and the first guide block **32315a**, **33315a**. For example, suitable fasteners include, but are not limited to, bolts, screws, pins, rivets, welds, and combinations thereof. Fasteners are well known in the art.

(664) In an embodiment, a second end of the first spring **32320a**, **33320a** may be attached to the first push rod **32310a**, **33310a**. In an embodiment, a second end of the first spring **32320a**, **33320a** may be attached to the first push rod **32310a**, **33310a** via fasteners. Any suitable fastener may be used for the first spring **32320a**, **33320a** and the first push rod **32310a**, **33310a**. For example, suitable fasteners include, but are not limited to, bolts, screws, pins, rivets, welds, and combinations thereof. Fasteners are well known in the art.

(665) In a closed position for the rotating subassembly **32400**, **33400**, the first cam roller **32325a**, **33325a** may be disposed in a most recessed portion of the cam **32330**, **33330** allowing the second end **32415a**, **32415a** of the first body **32405a**, **33405a** of the rotating subassembly **32400**, **33400** to close against the first end **32410b**, **33410b** of the second body **32405b**, **32405b** of the rotating subassembly **32400**, **33400** to form a first seal between seal faces **32450a**, **32450b**, **33450a**, **33450b**.

(666) As the pivot shaft **3285**, **3385** and the cam **32330**, **33330** (and rotating subassembly **32400**, **33400**) rotates, the first cam roller **32325a**, **33325a** travels along the cam **32330**, **33330** and collapses the first body **32405a**, **33405a** of the rotating subassembly **32400**, **33400** into the body **3205**, **3305** to prevent unnecessary wear to the seal faces **32450a**, **32450b**, **33450a**, **33450b**.

(667) In an embodiment, the cam **32330**, **33330** may be sized and shaped such that the timing of allowing the second end **32415a**, **32415a** of the first body **32405a**, **33405a** of the rotating subassembly **32400**, **33400** to close against the first end **32410b**, **33410b** of the second body **32405b**, **32405b** of the rotating subassembly **32400**, **33400** to form the first seal will best protect the seal faces **32450a**, **32450b**, **33450a**, **33450b**.

(668) In an embodiment, a first end of the second pivot pin **32305b**, **33305b** may be attached to third body **32405c**, **33405c** of the rotating subassembly **32400**, **33400** through the third portion **3205c**, **3305c** of the body **3205**, **3305**. In an embodiment, a first end of the second pivot pin **32305b**, **33305b** may be attached to third body **32405c**, **33405c** of the rotating subassembly **32400**, **33400** through the third portion **3205c**, **3305c** of the body **3205**, **3305** via fasteners. Any suitable fasteners may be used for the second pivot pin **32305b**, **33305b** and the third body **32405c**, **33405c** of the rotating subassembly **32400**, **33400**. For example, suitable fasteners include, but are not limited to, bolts, screws, pins, rivets, welds, and combinations thereof. Fasteners are well known in

the art.

(669) In an embodiment, a second end of the second pivot pin **32305b**, **33305b** may be attached to a first end of the second push rod **32310b**, **33310b**. In an embodiment, a second end of the second pivot pin **32305b**, **33305b** may be attached to a first end of the second push rod **32310b**, **33310b** via fasteners. Any suitable fasteners may be used for the second pivot pin **32305b**, **33305b** and the second push rod **32310b**, **33310b**. For example, suitable fasteners include, but are not limited to, bolts, screws, pins, rivets, welds, and combinations thereof. Fasteners are well known in the art.

(670) In an embodiment, a second end of the second push rod **32310b**, **33310b** may be attached to a second cam roller **32325b**, **33325b**. In an embodiment, a second end of the second push rod **32310b**, **33310b** may be attached to a second cam roller **32325b**, **33325b** via fasteners. Any suitable fasteners may be used for the second push rod **32310b**, **33310b** and the second cam roller **32325b**, **33325b**. For example, suitable fasteners include, but are not limited to, bolts, screws, pins, rivets, welds, and combinations thereof. Fasteners are well known in the art.

(671) In an embodiment, the second cam roller **32325b**, **33325b** may travel along a surface of the cam **32330**, **33330**.

(672) In an embodiment, the cam **32330**, **33330** may be attached to the pivot drive **3290**, **3390**. In an embodiment, the cam **32330**, **33330** may be attached to the pivot drive **3290**, **3390** via fasteners. Any suitable fasteners may be used for the cam **32330**, **33330** and the pivot drive **3290**, **3390**. For example, suitable fasteners include, but are not limited to, bolts, screws, pins, rivets, welds, and combinations thereof. Fasteners are well known in the art.

(673) In an embodiment, the cam **32330**, **33330** may be any suitable shape. For example, suitable shapes include, but are not limited to, an “∞” shape, an “8” shape, a “0” shape, an “O” shape, and combinations and/or portions thereof. In an embodiment, the cam **32330**, **33330** may be a double lobed shape. See e.g., FIGS. **33C-33D**.

(674) In an embodiment, the second push rod **32310b**, **33310b** may be any suitable shape. For example, suitable shapes include, but are not limited to, a cross shape, a “T” shape, a “Y” shape, and combinations and/or portions thereof. In an embodiment, the second push rod **32310b**, **33310b** may be a cross shape. See e.g., FIGS. **32A-32B** & **33A-33D**.

(675) In an embodiment, a second guide block **32315b**, **33315b** may be attached to the second portion **3205b**, **3305b** of the body **3205**, **3305**. In an embodiment, a second guide block **32315b**, **33315b** may be attached to the second portion **3205b**, **3305b** of the body **3205**, **3305** via fasteners. Any suitable fasteners may be used for the second guide block **32315b**, **33315b** and the second portion **3205b**, **3305b** of the body **3205**, **3305**. For example, suitable fasteners include, but are not limited to, bolts, screws, pins, rivets, welds, and combinations thereof. Fasteners are well known in the art.

(676) In an embodiment, the second push rod **32310b**, **33310b** may pass through the second guide block **32315b**, **33315b**.

(677) In an embodiment, a second end of the second spring **32320b**, **33320b** may be attached to the second guide block **32315b**, **33315b**. In an embodiment, a second end of the second spring **32320b**, **33320b** may be attached to the second guide block **32315b**, **33315b** via fasteners. Any suitable fastener may be used for the second spring **32320b**, **33320b** and the second guide block **32315b**, **33315b**. For example, suitable fasteners include, but are not limited to, bolts, screws, pins, rivets, welds, and combinations thereof. Fasteners are well known in the art.

(678) In an embodiment, a first end of the second spring **32320b**, **33320b** may be attached to the second push rod **32310b**, **33310b**. In an embodiment, a first end of the second spring **32320b**, **33320b** may be attached to the second push rod **32310b**, **33310b** via fasteners. Any suitable fastener may be used for the second spring **32320b**, **33320b** and the second push rod **32310b**, **33310b**. For example, suitable fasteners include, but are not limited to, bolts, screws, pins, rivets, welds, and combinations thereof. Fasteners are well known in the art.

(679) In a closed position for the rotating subassembly **32400**, **33400**, the second cam roller

32325b, 33325b may be disposed in a most recessed portion of the cam **32330, 33330** allowing the second end **32415b, 33415b** of the second body **32405b, 33405b** of the rotating subassembly **32400, 33400** to close against the first end **32410c, 33410c** of the third body **32405c, 33405c** of the rotating subassembly **32400, 33400** to form a second seal between seal faces **32450c, 32450d, 33450c, 33450d**.

(680) As the pivot shaft **3285, 3385** and the cam **32330, 33330** (and the rotating subassembly **32400, 33400**) rotates, the second cam roller **32325b, 33325b** travels along the cam **32330, 33330** and collapses the third body **32405c, 33405c** of the rotating subassembly **32400, 33400** into the body **3205, 3305** to prevent unnecessary wear to the seal faces **32450c, 32450d, 33450c, 33450d**.

(681) In an embodiment, the cam **32330, 33330** may be sized and shaped such that the timing of allowing the second end **32415b, 33415b** of the second body **32405b, 33405b** of the rotating subassembly **32400, 33400** to close against the first end **32410c, 33410c** of the third body **32405c, 33405c** of the rotating subassembly **32400, 33400** to form the second seal will best protect the seal faces **32450c, 32450d, 33450c, 33450d**.

(682) Optional Transducer Subassemblies

(683) FIG. **19** illustrates a cross-sectional view of the drilling mud screen system **1900** in a monitoring configuration according to an embodiment of the present invention, showing an optional transducer subassembly **19100**, as discussed above.

(684) FIG. **20A** illustrates an upper, right side perspective view of an optional transducer subassembly **2000** according to an embodiment of the present invention; and FIG. **20B** illustrates a side perspective view of the optional transducer subassembly **2000** of FIG. **20A**, as discussed above.

(685) FIG. **30B** illustrates the upper, left perspective view of the drilling mud screen system **3000** of FIG. **30A**, showing an optional first transducer subassembly **30100a** and an optional second transducer subassembly **30100b**; and FIG. **31B** illustrates the left perspective view of the drilling mud screen system **3100** of FIG. **31A**, showing an optional first transducer subassembly **31100a** and an optional second transducer subassembly **31100b**. See also FIGS. **20A & 20B**.

(686) As shown in FIGS. **30A** and **31A**, the drilling mud screen system **3000, 3100** has a body **3005, 3105** having a first end **3010, 3110** and a second end **3015, 3115**, a drilling mud inlet **3020, 3120** and a drilling mud outlet **30, 25, 3125**, an optional first transducer subassembly **30100a, 31100a** and an optional second transducer subassembly **30100b, 31100b**.

(687) In an embodiment, the drilling mud screen system **3000, 3100** has a drilling mud screen **3040, 3140** fluidly connected to and disposed between the drilling mud inlet **3020, 3120** and the drilling outlet **3025, 3125**.

(688) In an embodiment, a drilling mud inlet **3020, 3120** of the drilling mud screen system **3000, 3100** (e.g., via the first transducer subassembly **30100a, 31100a**) may be fluidly connected to a high-pressure outlet of a drilling mud pump via a connection. In an embodiment, a drilling mud outlet **3025, 3125** (e.g., via the second transducer subassembly **30100b, 31100b**) of the drilling mud screen system **3000, 3100** may be fluidly connected to an inlet of a vibrator hose to a standpipe via a connection.

(689) Alternatively, the drilling mud screen system **3000, 3100** (e.g., via the first transducer subassembly **30100a, 31100a**) may be installed between an outlet of the vibrator hose and an inlet of the standpipe, or at any point in the standpipe via a connection.

(690) In an embodiment, the drilling mud inlet **3020, 3120** (e.g., via the first transducer subassembly **30100a, 31100a**) may be fluidly connected to, for example, an outlet of a drilling mud pump via a connection; and the drilling mud outlet **3025, 3125** (e.g., via the second transducer subassembly **30100b, 31100b**) may be fluidly connected to, for example, an inlet of a vibrator hose via a connection. Any suitable connection may be used for the drilling mud inlet **3020, 3120** and the drilling mud outlet **3025, 3125**. For example, suitable connections include, but are not limited to, pipe fittings and welds. Connections are well known in the art. In an embodiment, the drilling

mud inlet **3020**, **3120** (e.g., via the first transducer subassembly **30100a**, **31100a**) may be fluidly connected to, for example, an outlet of a drilling mud pump via a weld; and the drilling mud outlet **3025**, **3125** (e.g., via the second transducer subassembly **30100b**, **31100b**) may be fluidly connected to, for example, an inlet of a vibrator hose via a weld.

(691) In an embodiment, the first transducer access port **3032a**, **3132a** of the first transducer subassembly **30100a**, **31100a** and/or the second transducer access port **3032b**, **3132b** of the second transducer subassembly **30100b**, **31100b** may be closed with a transducer **28105** via a fitting. See e.g., FIG. **28**. Any suitable type of transducer may be used. For example, suitable types of transducers include, but are not limited to, displacement transducers, flow rate transducers, pressure transducers, temperature transducers and any combination thereof. Any suitable fitting may be used. For example, suitable fittings include, but are not limited to, pipe fittings. Fittings are well known in the art. In an embodiment, the first transducer access port **3032a**, **3132a** of the first transducer subassembly **30100a**, **31100a** and/or the second transducer access port **3032b**, **3132b** of the second transducer subassembly **30100b**, **31100b** may be closed with a pressure transducer via a 2-inch 1502 WECO union.

(692) In an embodiment, a computing device (such as a rig computer) may include a bus that directly or indirectly couples the following devices: memory, one or more processors, one or more presentation components, one or more input/output (I/O) ports, I/O components, a user interface and a power supply. The computing device may include a variety of computer-readable media. The memory may include computer-storage media in the form of volatile and/or nonvolatile memory. The presentation component(s) present data indications to a user or other device. The user interface allows the user to input/output information to/from the computing device. The one or more I/O ports may allow the computing device to be logically coupled to other devices including a transducer **28105**, and other I/O components, some of which may be built in. See e.g., FIG. **28**. Examples of other I/O components include a printer, scanner, wireless device, and the like.

(693) In an embodiment, the first transducer access port **3032a**, **3132a** of the first transducer subassembly **30100a**, **31100a** and/or the second transducer access port **3032b**, **3132b** of the second transducer subassembly **30100b**, **31100b** may be sealed with an end cap via an O-ring. Any suitable O-ring may be used. For example, suitable O-rings include, but are not limited to, 300 Series O-rings. O-rings are well known in the art.

(694) In an embodiment, the first transducer subassembly **30100a**, **31100b** and the second transducer subassembly **30100b**, **31100b** may be constructed of any suitable material. For example, suitable materials include, but are not limited to, any alloy steel suitable for a drilling mud application. In an embodiment, the first transducer subassembly **30100a**, **31100a** and/or the second transducer subassembly **30100b**, **31100b** may be constructed of a low alloy steel (e.g., 4140, 4145, 4330), a stainless steel (e.g., 17-4, 304, 316), a super alloy (e.g., Inconel), a titanium alloy (e.g., Ti-6Al-4V, Ti-6Al-6V-2Sn), a copper alloy (e.g., Beryllium Copper), a Cobalt alloy (e.g., Stellite), an Aluminum alloy (e.g., 2024, 6061, 7075), and combinations thereof. In an embodiment, the first transducer subassembly **30100a**, **31100a** and/or the second transducer subassembly **30100b**, **31100b** may be constructed of an American Iron and Steel Industry (AISI) 4130/75k yield or equivalent material. In an embodiment, the inner surface of the first transducer subassembly **30100a**, **31100a** and/or the inner surface of the second transducer subassembly **30100b**, **31100b** may be unpainted. In an embodiment, the outer surface of the first transducer subassembly **30100a**, **31100a** and/or the outer surface of the second transducer subassembly **30100b**, **31100b** may be painted.

(695) Exemplary Drilling Mud Screens

(696) FIG. 5A illustrates an upper, cross-sectional view of a drilling mud screen **500** according to an embodiment of the present invention, as discussed above. FIG. 5B illustrates a detailed view of A-A of FIG. 5A; FIG. 5C illustrates a detailed view of B of FIG. 5A; and FIG. 5D illustrates a detailed view of C of FIG. 5A. FIG. 5E illustrates an upper, right side perspective view of the

drilling mud screen **500** of FIG. 5A.

(697) Optional Drilling Mud Screen

(698) FIG. **22A** illustrates an end view of an optional drilling mud screen **2200** according to an embodiment of the present invention, as discussed above. FIG. **22B** illustrates a detailed, cross-sectional view of A-A of FIG. **22A**, showing an optional drilling mud screen insert **22105**, and optional first end retaining ring **22110**, an optional filter length **22115**, and an optional retaining ring **22120**; FIG. **22C** illustrates a detailed view of B of FIG. **22B**; and FIG. **22D** illustrates a detailed, cross-sectional view of C-C of FIG. **22C**. FIG. **22E** illustrates an upper, right perspective view of the drilling mud screen **2200** of FIGS. **22A-22B**.

(699) Alternative Improved Exemplary Valve-Style Drilling Mud Screen System

(700) Body with Trapdoor Mechanism

(701) FIG. **37A** illustrates an end view of an exemplary trapdoor-style drilling mud screen system **3700**; FIG. **37B** illustrates a detailed, cross-sectional view A-A of FIG. **37A**; FIG. **37C** illustrates a detailed, cross-sectional view B-B of FIG. **37A**; FIG. **37D** illustrates a detailed view C of FIG. **37C**; FIG. **37E** illustrates an end view of the exemplary trapdoor-style drilling mud screen system **3700** of FIGS. **37A-37D**; FIG. **37F** illustrates a detailed, cross-sectional view G-G of FIG. **37E**; FIG. **37G** illustrates an end view of the exemplary trapdoor-style drilling mud screen system **3700** of FIGS. **37A-37F**; FIG. **37H** illustrates a detailed, cross-sectional view J-J of FIG. **37G**; FIG. **37I** illustrates an end view of the exemplary trapdoor-style drilling mud screen system **3700** of FIGS. **37A-37H**; FIG. **37J** illustrates a detailed cross-sectional view H-H of FIG. **37I**; FIG. **37K** illustrates an upper, right perspective view of the exemplary trapdoor-style drilling mud screen system **3700** of FIGS. **37A-37J**, showing the trapdoor-style drilling mud screen system **3700** in a closed position; FIG. **37L** illustrates an upper, right perspective view of the exemplary trapdoor-style drilling mud screen system **3700** of FIGS. **37A-37K**, showing the trapdoor-style drilling mud screen system **3700** in an open position; and FIG. **37M** illustrates an exploded view of the exemplary trapdoor-style drilling mud screen system **3700** of FIGS. **37A-37L**.

(702) FIG. **38A** illustrates a cross-sectional view of an exemplary trapdoor-style drilling mud screen system **3800** having a reversed drilling mud screen **3840**, showing the trapdoor-style drilling mud screen system **3800** in a closed position; and FIG. **38B** illustrates a cross-sectional view of the exemplary trapdoor-style drilling mud screen system **3800** of FIG. **38A**, showing the trapdoor-style drilling mud screen system **3800** in an open position.

(703) As shown in FIGS. **37A-37M** and **38A-38B**, the drilling mud screen system **3700**, **3800** has a body **3705**, **3805** having a first end **3710**, **3810** and a second end **3715**, **3815**, a drilling mud inlet **3720**, **3820** and a drilling mud outlet **3725**, **3825**.

(704) In an embodiment, the drilling mud screen system **3700**, **3800** has a drilling mud screen **3740**, **3840** fluidly connected to and disposed between the first drilling mud inlet **3720**, **3820** and the first drilling outlet **3725**, **3825**.

(705) In an embodiment, the body **3705**, **3805** has a first portion **3705a**, **3805a**, a second portion **3705b**, **3805b** and a third portion **3705c**, **3805c**. In an embodiment, the first portion **3705a**, **3805a** of the body **3705**, **3805** is an inlet portion. In an embodiment, the second portion **3705b**, **3805b** of the body **3705**, **3805** is a rotating trapdoor subassembly/drilling mud screen portion. In an embodiment, the third portion **3705c**, **3805c** of the body **3705**, **3805** is an outlet portion.

(706) In an embodiment, the first portion **3705a**, **3805a** and the third portion **3705c**, **3805c** may be any suitable shape. For example, suitable shapes include, but are not limited to, a cone, a cylinder, a rectangular prism (e.g., cubic, cuboid), a pentagonal prism, a sphere, a spheroid, a triangular prism, and combinations and/or portions thereof. In an embodiment, the first portion **3705a**, **3805a** and the third portion **3705c**, **3805c** may be a cylinder or a combination of cylinders.

(707) In an embodiment, the first portion **3705a**, **3805a** and the third portion **3705c**, **3805c** may have any suitable inner diameter or dimension. For example, a suitable inner diameter for the first portion **3705a**, **3805a** and the third portion **3705c**, **3805c** may be from about 2-inches to about 5-

inches, and any range or value there between. In an embodiment, the inner diameter of the first portion **3705a**, **3805a** and the third portion **3705c**, **3805c** may be about 4.06-inches.

(708) In an embodiment, the second portion **3705b**, **3805b** may be any suitable shape. For example, suitable shapes include, but are not limited to, a cone, a cylinder, a rectangular prism (e.g., cubic, cuboid), a pentagonal prism, a sphere, a spheroid, a triangular prism, and combinations and/or portions thereof. In an embodiment, the second portion **3705b**, **3805b** may be a cylinder with open upper portion. See e.g., FIGS. **37A-37M** & **38A-38B** (open upper portion).

(709) In an embodiment, the second portion **3705b**, **3805b** may have any suitable inner diameter or dimension. For example, a suitable inner diameter for the second portion **3705b**, **3805b** may be from about 4-inches to about 7-inches, and any range or value there between. In an embodiment, the inner diameter for the second portion **3705b**, **3805b** may be about 4.9-inches.

(710) For example, a suitable inner dimension for the second portion **3705b**, **3805b** may be from about 4-inches to about 7-inches across, and any range or value there between. In an embodiment, the inner dimension for the second portion **3705b**, **3805b** may be about 4.9-inches across.

(711) In an embodiment, a drilling mud inlet **3720**, **3820** of the drilling mud screen system **3700**, **3800** may be fluidly connected to a high-pressure outlet of a drilling mud pump via a connection. In an embodiment, a drilling mud outlet **3725**, **3825** of the drilling mud screen system **3700**, **3800** may be fluidly connected to an inlet of a vibrator hose to a standpipe via a connection.

(712) Alternatively, the drilling mud screen system **3700**, **3800** may be installed between an outlet of the vibrator hose and an inlet of the standpipe, or at any point in the standpipe via a connection.

(713) In an embodiment, the drilling mud inlet **3720**, **3820** may be fluidly connected to, for example, an outlet to a drilling mud pump via a connection; and the drilling mud outlet **3725**, **3825** may be fluidly connected to, for example, an inlet to a vibrator hose via a connection. Any suitable connection may be used for the drilling mud inlet and the drilling mud outlet. For example, suitable connections include, but are not limited to, pipe fittings and welds. Connections are well known in the art. In an embodiment, the drilling mud inlet **3720**, **3820** may be fluidly connected to, for example, an outlet to a drilling mud pump via a weld; and the drilling mud outlet **3725**, **3825** may be fluidly connected to, for example, an inlet to a vibrator hose via a weld.

(714) In an embodiment, the body **3705**, **3805** of the drilling mud screen system **3700**, **3800** may be constructed of any suitable material. For example, suitable materials include, but are not limited to, any alloy suitable for a drilling mud application. In an embodiment, the body **3705**, **3805** may be constructed of a low alloy steel (e.g., 4140, 4145, 4330), a stainless steel (e.g., 17-4, 304, 316), a super alloy (e.g., Inconel), a titanium alloy (e.g., Ti-6Al-4V, Ti-6Al-6V-2Sn), a copper alloy (e.g., Beryllium Copper), a Cobalt alloy (e.g., Stellite), an Aluminum alloy (e.g., 2024, 6061, 7075) and combination thereof. In an embodiment, the body **3005**, **3105** may be constructed of an American Iron and Steel Industry (AISI) 4130/75k yield or equivalent material. In an embodiment, the inner surface of the body **3705**, **3805** may be unpainted. In an embodiment, the outer surface of the body **3705**, **3805** may be painted.

(715) Pivot Subassembly

(716) As shown in FIGS. **37A-37M** and **38A-38B**, the second portion **3705b**, **3805b** of the body **3705**, **3805** and/or the rotating trapdoor subassembly **37400**, **38400** has a pivot shaft **3785**, **3885**, a first retaining ring **3785a** and a second retaining ring **3785b**.

(717) In an embodiment, the rotating trapdoor subassembly **37400**, **38400** may be retained in the second portion **3705b**, **3805b** of the body **3705**, **3805** via the pivot shaft **3785**, **3885**. See e.g., FIGS. **37B**, **37F**, **37H**, **37J-37L** & **37M**. In an embodiment, the rotating trapdoor subassembly **37400**, **38400** may be retained in the second portion **3705b**, **3805b** of the body **3705**, **3805** via the pivot shaft **3785**, **3885** such that the rotating trapdoor subassembly **37400**, **38400** may rotate with respect to the second portion **3705b**, **3805b** of the body **3705**, **3805**.

(718) Rotating Trapdoor Subassembly

(719) FIG. **37K** illustrates an upper, right perspective view of the exemplary trapdoor-style drilling

mud screen system **3700** of FIGS. **37A-37J**, showing the trapdoor-style drilling mud screen system **3700** in a closed position; FIG. **37L** illustrates an upper, right perspective view of the exemplary trapdoor-style drilling mud screen system **3700** of FIGS. **37A-37K**, showing the trapdoor-style drilling mud screen system **3700** in an open position; and FIG. **37M** illustrates an exploded view of the exemplary trapdoor-style drilling mud screen system **3700** of FIGS. **37A-37L**.

(720) FIG. **38A** illustrates a cross-sectional view of an exemplary trapdoor-style drilling mud screen system **3800** having a reversed drilling mud screen **3840**, showing the trapdoor-style drilling mud screen system **3800** in a closed position; and FIG. **38B** illustrates a cross-sectional view of the exemplary trapdoor-style drilling mud screen system **3800** of FIG. **38A**, showing the trapdoor-style drilling mud screen system **3800** in an open position.

(721) As shown in FIGS. **37A-37M** and **38A-38B**, the rotating trapdoor subassembly **37400**, **38400** has a trapdoor body **37405**, **38405** having a first end **37410**, a second end **37415**, a first drilling mud inlet **37420**, a first drilling mud outlet **37425**, and an access port **3730**, **3830**.

(722) In an embodiment, the rotating subassembly **37400**, **38400** has a drilling mud screen **3740**, **3840** fluidly connected to and disposed between the first drilling mud inlet **37420** and the first drilling outlet **37425**.

(723) In an embodiment, the trapdoor body **37405**, **38405** may be any suitable shape. For example, suitable shapes include, but are not limited to, a cone, a cylinder, a rectangular prism (e.g., cubic, cuboid), a pentagonal prism, a sphere, a spheroid, a triangular prism, and combinations and/or portions thereof. In an embodiment, the trapdoor body **37405**, **38405** may be a cylinder or a combination of cylinders. In an embodiment, the trapdoor body **37405**, **38405** may be a combination of a cylinders and a rectangular prism.

(724) In an embodiment, the trapdoor body **37405**, **38405** may have any suitable inner diameter or dimension. For example, a suitable inner diameter for the trapdoor body **37405**, **38405** may be from about 2-inches to about 7-inches, and any range or value there between. In an embodiment, the inner diameter of the trapdoor body **37405**, **38405** may be about 4.06-inches and/or 4.9-inches.

(725) For example, a suitable inner dimension for the trapdoor body **37405**, **38405** may be from about 2-inches to about 7-inches across, and any range or value there between. In an embodiment, the inner dimension for the trapdoor body **37405**, **38405** may be about 4.06-inches and/or 4.9-inches across.

(726) In an embodiment, an internal drilling mud outlet **3725a** of the body **3705**, **3805** of the drilling mud screen system **3700**, **3800** may be fluidly connected to the first drilling mud inlet **37420** of the trapdoor body **37405**, **38405** of the rotating trapdoor subassembly **37400**, **38400**.

(727) In an embodiment, the first drilling mud outlet **37425a** of the trapdoor body **37405a**, **38405a** of the rotating trapdoor subassembly **37400**, **38400** may be fluidly connected to an internal drilling mud inlet **3720a**, **3820a** of the body **3705**, **3805** of the drilling mud screen system **3700**, **3800**.

(728) In an embodiment, a first piston ring **37430a** may be disposed between the first end **3710**, **3810** of the body **3705**, **3805** of the drilling mud screen system **3700**, **3800** and the second end **37515a**, **38515a** of the first subassembly **37500**, **38500**. See e.g., FIG. **37M**. In an embodiment, a first piston ring **37430a** may be disposed in a first piston cavity (not shown) between the body **3705**, **3805** of the drilling mud screen system **3700**, **3800** and the second end **37510a**, **38510a** of the first subassembly **37500**, **38500** to prevent buildup and compaction of debris in the first piston cavity (not shown).

(729) In an embodiment, a second piston ring **37430b** may be disposed between the second end **3715**, **3815** of the body **3705**, **3805** of the drilling mud screen system **3700**, **3800** and the first end **37510b**, **38510** of the second subassembly **37500b**, **38500b**. See e.g., FIG. **37M**. In an embodiment, a second piston ring **37430b** may be disposed in a second piston cavity (not shown) between the second end **3715**, **3815** of the body **3705**, **3805** of the drilling mud screen system **3700**, **3800** and the first end **37510b**, **38510b** of the second subassembly **37500b**, **38500b** to prevent buildup and compaction of debris in the second piston cavity (not shown).

(730) In an embodiment, the first piston ring **37430a** and the second piston ring **37430b** may be constructed of any suitable compressible material to prevent buildup and compaction of debris in a first piston cavity (not shown) and/or a second piston cavity (not shown), respectively.

(731) In an embodiment, a first spring **37440a** may be disposed between the first subassembly **37500a**, **38500a** and the body **3705**, **3805** of the drilling mud screen system **3700**, **3800**. See e.g., FIG. 37M. In an embodiment, a first spring **37440a** may be disposed in a first seal piston cavity (not shown) between the first subassembly **37500a**, **38500a** and the body **3705**, **3805** of the drilling mud screen system **3700**, **3800** to engage and seal a second end **37515a**, **38515a** of the first subassembly **37500a**, **38500a** with a first end **3710**, **3810** of the body **3705**, **3805** of the drilling mud screen system **3700**, **3800**.

(732) In an embodiment, a second spring **37440b** may be disposed between the body **3705**, **3805** of the drilling mud screen system **3700**, **3800** and the second subassembly **37500b**, **38500b**. See e.g., FIG. 37M. In an embodiment, a second spring **37440b** may be disposed in a second seal piston cavity (not shown) between the body **3705**, **3805** of the drilling mud screen system **3700**, **3800** and the second subassembly **37500b**, **38500b** to engage and seal a second end **3715**, **3815** of the body **3705**, **3805** of the drilling mud screen system **3700**, **3800** with a first end **37510b**, **38510b** of the second subassembly **37500b**, **38500b**.

(733) In an embodiment, the body **3705**, **3805** of the drilling mud screen system **3700**, **3700** and the trapdoor body **37405**, **38405** of the rotating trapdoor subassembly **37400**, **38400** may be sealed via an O-ring. See e.g., FIG. 37M. Any suitable O-ring may be used. For example, suitable O-rings include, but are not limited to, 300 Series O-rings. O-rings are well known in the art.

(734) In an embodiment, the second end **3715a** of the first portion **3705a**, **3805a** of the body **3705**, **3805** has a first seal face **37450a**. See e.g., FIG. 37M.

(735) In an embodiment, the first end **37410** of the trapdoor body **37405**, **38405** of the rotating trapdoor subassembly **37400**, **38400** has a second seal face **37450b**. See e.g., FIG. 37M.

(736) In an embodiment, the first seal face **37450a** and the second seal face **37450b** may have any suitable shapes to form a seal. For example, suitable shapes may be mating concave and convex surfaces, mating concave and convex surfaces similar to a ball valve, and combinations and variations thereof. In an embodiment, the first seal face **37450a** may be concave; and the second seal face **37450b** may be convex.

(737) In an embodiment, the second end **37415**, **38415** of the trapdoor body **37405**, **38405** of the rotating trapdoor subassembly **3700**, **3800** has a third seal face **37450c**. See e.g., FIG. 37M.

(738) In an embodiment, the first end **3710c** of the third portion **3705c**, **3805c** of the body **3705**, **3805** has a fourth seal face **37450d**. See e.g., FIG. 37M.

(739) In an embodiment, the third seal face **37450c** and the fourth seal face **37450d** may have any suitable shapes to form a seal. For example, suitable shapes may be mating concave and convex surfaces, mating concave and convex surfaces similar to a ball valve, and combinations and variations thereof. In an embodiment, the third seal face **37450c** may be convex; and the fourth seal face **37450d** may be concave.

(740) In an embodiment, the trapdoor body **37405**, **38405** of the rotating trapdoor subassembly **37400**, **38400** may be constructed of any suitable material. For example, suitable materials include, but are not limited to, any alloy suitable for a drilling mud application. In an embodiment, the trapdoor body **37405**, **38405** may be constructed of a low alloy steel (e.g., 4140, 4145, 4330), a stainless steel (e.g., 17-4, 304, 316), a super alloy (e.g., Inconel), a titanium alloy (e.g., Ti-6Al-4V, Ti-6Al-6V-2Sn), a copper alloy (e.g., Beryllium Copper), a Cobalt alloy (e.g., Stellite), an Aluminum alloy (e.g., 2024, 6061, 7075) and combination thereof. In an embodiment, the trapdoor body **37405**, **38405** may be constructed of an American Iron and Steel Industry (AISI) 4130/75k yield or equivalent material. In an embodiment, the inner surface of the trapdoor body **37405**, **38405** may be unpainted. In an embodiment, the outer surface of the trapdoor body **37405**, **38405** may be painted.

(741) Piston Guide Bar

(742) As shown in FIGS. 37A-37M and FIGS. 38A-38B, the drilling mud screen system 3700, 3800 further comprises a first piston guide bar 37315a and a second piston guide bar 37315b for the first piston 37435a.

(743) In an embodiment, the first piston guide bar 37315a and the second piston guide bar 37315b guides the first piston 37435a to engage the first end 37410 of the rotating trapdoor subassembly 37400 when the rotating trapdoor subassembly 37400 is in a closed position.

(744) In an embodiment, the first piston guide bar 37315a and the second piston guide bar 37315b guides the first piston 37435a to engage a first slot 37335a and a second slot (not shown), respectively, in the first portion 3705a, 3805a of the body 3705 or the second portion 3705b, 3805b of the body 3705, and a third slot 37340a and a fourth slot (not shown), respectively, in the first piston 37435a when the rotating trapdoor subassembly 37400 is in a closed position. See e.g., FIG. 37M.

(745) In an embodiment, the first piston guide bar 37315a and the second piston guide bar 37315b guides the first piston 37435a to engage a first slot 37335a and a second slot (not shown), respectively, in first portion 3705a, 3805a of the body 3705 or the second portion 3705b, 3805b of the body 3705, a third slot 37340a and a fourth slot (not shown), respectively, in the first piston 37435a and a fifth slot 37345a and a sixth slot (not shown) in the threaded lock ring 37600 (discussed below) when the rotating trapdoor subassembly 37400 is in a closed position. See e.g., FIG. 37M.

(746) In an embodiment, the first piston guide bar 37315a and the second piston guide bar 37315b locks the first piston 37435a to contact and seal the first end 37410 of the rotating trapdoor subassembly 37400 when the rotating trapdoor subassembly 37400 is in a closed position.

(747) In an embodiment, the first piston guide bar 37315a and the second piston guide bar 37315b guides the first piston 37435a to disengage from the first end 37410 of the rotating trapdoor subassembly 37400 when the rotating trapdoor subassembly 37400 is in an open position.

(748) In an embodiment, the first piston guide bar 37315a and the second piston guide bar 37315b separates the first piston 37435a to disengage and create a gap from the first end 37410 of the rotating trapdoor subassembly 37400 when the rotating trapdoor subassembly 37400 is in the open position to avoid damage to the first seal face 37450a and/or the second seal face 37450b.

(749) In an embodiment, the first piston guide bar 37315a further comprises a ball bearing for smooth action. In an embodiment, the second piston guide bar 37315b further comprises a ball bearing for smooth action. See e.g., FIG. 37M.

(750) In an embodiment, the first piston guide bar 37315a and the second piston guide bar 37315b may be constructed from any suitable material. For example, suitable materials include, but are not limited to, any alloy suitable for a drilling mud application. In an embodiment, the first piston guide bar 37315a and the second piston guide bar 37315b may be constructed of a low alloy steel (e.g., 4140, 4145, 4330), a stainless steel (e.g., 17-4, 304, 316), a super alloy (e.g., Inconel), a titanium alloy (e.g., Ti-6Al-4V, Ti-6Al-6V-2Sn), a copper alloy (e.g., Beryllium Copper), a Cobalt alloy (e.g., Stellite), an Aluminum alloy (e.g., 2024, 6061, 7075) and combination thereof. In an embodiment, the first piston guide bar 37315a and the second piston guide bar 37315b may be constructed of an American Iron and Steel Industry (AISI) 4130/75k yield or equivalent material

(751) Subassemblies

(752) As shown in FIGS. 37A-37M and FIGS. 38A-38B, the drilling mud screen system 3700, 3800 further comprises a first subassembly 37500a, 38500a and a second subassembly 37500b, 38500b. In an embodiment, the drilling mud screen system 3700, 3800 has a first subassembly 37500a, 38500a having a first end 37510a, 38510a and a second end 37515a, 38515a, a first inlet 37520a, 38520a of the first subassembly 37500a, 38500a and a first outlet 37525a, 38525a of the first subassembly 37500a, 38500a.

(753) In an embodiment, the drilling mud screen system 3700, 3800 has a second subassembly

37500b, 38500b having a first end **37510b, 38510b** and a second end **37515b, 38515b**, a second inlet **37520b, 38520b** of the second subassembly **37500b, 38500b** and a second outlet **37525b, 38525b** of the second subassembly **37500b, 37500b**.

(754) In an embodiment, the first drilling mud inlet **37520a, 38520a** of the first subassembly **37500a, 38500a** may be fluidly connected to, for example, an outlet of a drilling mud pump via a connection; and the second drilling mud outlet **37525b, 38525b** of the second subassembly **37500b, 38500b** may be fluidly connected to an inlet of a vibrator hose via a connection. Any suitable connection may be used for the first drilling mud inlet **37520a, 38520a** of the first subassembly **37500a, 38500a** and the second drilling mud outlet **37525b, 38525b** of the second subassembly **37500b, 38500b**. For example, suitable connections include, but are not limited to, pipe fittings and welds. Connections are well known in the art. In an embodiment, the first drilling mud inlet **37520a, 38520a** of the first subassembly **37500a, 38500a** may be fluidly connected to, for example, an outlet of a drilling mud pump via a weld; and the second drilling mud outlet **37525b, 38525b** of the second subassembly **37500b, 38500b** may be fluidly connected to an inlet of a vibrator hose via a weld.

(755) In an embodiment, the drilling mud inlet **3720, 3820** of the body **3705, 3805** may be fluidly connected to the first drilling mud outlet **37525a, 38525a** of the first subassembly **37500a, 38500a** via a connection; and the drilling mud outlet **3725, 3825** of the body **3705, 3805** may be fluidly connected to the second drilling mud inlet **37520b, 38520b** of the second subassembly **37500b, 38500b** via a connection. Any suitable connection may be used for the drilling mud inlet **3720, 3820** of the body **3705, 3805** and the drilling mud outlet **3725, 3825** of the body **3705, 3805**. For example, suitable connections include, but are not limited to, pipe fittings and other connections. In an embodiment, the first drilling mud inlet **3720, 3820** of the body **3705, 3805** may be fluidly connected to, for example, a first drilling mud outlet **37525a, 38525a** of a first subassembly **37500a, 38500a** via a pipe fitting; and the second drilling mud outlet **3725, 3825** of the body **3705, 3805** may be fluidly connected to a second drilling mud inlet **37520b, 38520b** of the second subassembly **37500b, 38500b** via a pipe fitting.

(756) In an embodiment, the drilling mud outlet **3725a, 3825a** of the body **3705, 3805** may be connected to the first drilling mud inlet **37520a, 38520a** of the first subassembly **37500a, 38500a** via a lock ring **37600, 38600**. In an embodiment, the body **3705, 3805** and/or the first subassembly **37500a, 38500a** may be sealed with the lock ring **37600, 38600** via an O-ring. Any suitable O-ring may be used. For example, suitable O-rings include, but are not limited to, 300 Series O-rings. O-rings are well known in the art.

(757) In an embodiment, the first subassembly **37500a, 38500a** and the second subassembly **37500b, 38500b** of the drilling mud screen system **3700, 3800** may be constructed of any suitable material. For example, suitable materials include, but are not limited to, any alloy steel suitable for a drilling mud application. In an embodiment, the first subassembly **37500a, 38500a** and the second subassembly **37500b, 38500b** may be constructed of an AISI 4130/75k yield or equivalent material. In an embodiment, the inner surface of the first subassembly **37500a, 38500a** and the second subassembly **37500b, 38500b** may be unpainted. In an embodiment, the outer surface of the first subassembly **37500a, 38500a** and the second assembly **37500b, 38500b** may be painted.

(758) Threaded Lock Ring

(759) In an embodiment, the drilling mud screen system **3700, 3800** further comprises a threaded lock ring **37600, 38600** having a first end **37610** and a second end **37615**.

(760) In an embodiment, the threaded lock ring **37600, 38600** is disposed around a first portion **3705a, 3805a** of the body **3705, 3805** and a first end **37410** of the trapdoor body **37405** of the rotating trapdoor subassembly **37400, 38400**.

(761) In an embodiment, the threaded lock ring **37600, 38600** is disposed around a first portion **3705a, 3805a** of the body **3705, 3805** and a first end **37410** of the trapdoor body **37405** of the rotating trapdoor subassembly **37400, 38400** to lock the trapdoor subassembly **37400, 38400** in a

closed position.

(762) In an embodiment, the first piston guide bar **37315a** and the second piston guide bar **37315b** is disposed through a first slot **37335a** and a second slot (not shown) in the first portion **3705a**, **3805a** of the body **3705** or the second portion **3705b**, **3805b** of the body **3705**, a third slot **37340a** and a fourth slot (not shown) in the first piston **37435a** and a fifth slot and a sixth slot (not shown) in the threaded lock ring **37600** to lock the first piston **37435a** in an engaged position when the rotating trapdoor subassembly **37400** is in a closed position. See e.g., FIG. 37M.

(763) In an embodiment, the threaded lock ring **37600**, **38600** further comprises one or more handles **37600a**, **38600a**.

(764) In an embodiment, the threaded lock ring **37600**, **38600** may have any suitable inner diameter or dimension. For example, a suitable inner diameter for the threaded lock ring **37600**, **38600** may be from about 8-inches to about 15-inches, and any range or value there between. In an embodiment, the inner diameter of the threaded lock ring **37600**, **38600** may be about 12.4-inches.

(765) For example, a suitable inner dimension for the threaded lock ring **37600**, **38600** may be from about 8-inches to about 15-inches across, and any range or value there between. In an embodiment, the inner dimension for the threaded lock ring **37600**, **38600** may be about 12.4-inches across.

(766) In an embodiment, the threaded lock ring **37600**, **38600** may be constructed of any suitable material. For example, suitable materials include, but are not limited to, any alloy steel suitable for a drilling mud application. In an embodiment, the threaded lock ring **37600**, **38600** may be constructed of an AISI 4130/75k yield or equivalent material. In an embodiment, the inner surface of the threaded lock ring **37600**, **38600** may be unpainted. In an embodiment, the outer surface of the threaded lock ring **37600**, **38600** may be painted.

(767) Exemplary Drilling Mud Screens

(768) FIG. 5A illustrates an upper, cross-sectional view of a drilling mud screen **500** according to an embodiment of the present invention, as discussed above. FIG. 5B illustrates a detailed view of A-A of FIG. 5A; FIG. 5C illustrates a detailed view of B of FIG. 5A; and FIG. 5D illustrates a detailed view of C of FIG. 5A. FIG. 5E illustrates an upper, right side perspective view of the drilling mud screen **500** of FIG. 5A.

(769) Optional Drilling Mud Screen

(770) FIG. 22A illustrates an end view of an optional drilling mud screen **2200** according to an embodiment of the present invention, as discussed above. FIG. 22B illustrates a detailed, cross-sectional view of A-A of FIG. 22A, showing an optional drilling mud screen insert **22105**, and optional first end retaining ring **22110**, an optional filter length **22115**, and an optional retaining ring **22120**; FIG. 22C illustrates a detailed view of B of FIG. 22B; and FIG. 22D illustrates a detailed, cross-sectional view of C-C of FIG. 22C. FIG. 22E illustrates an upper, right perspective view of the drilling mud screen **2200** of FIGS. 22A-22B.

(771) Alternative Reversed Drilling Mud Screen

(772) The drilling mud screen **3840** may be any suitable filter or screen capable of filtering or screening debris from drilling muds and completion fluids. For example, suitable drilling mud screens include, but are not limited to, drill screens and rod screens.

(773) FIGS. 38A-38B illustrates a cross-sectional view of an exemplary drilling mud screen system **3800** according to an embodiment of the invention, showing a reversed drilling mud screen **3840**.

(774) As shown in FIGS. 5A-5E, 22A-22E and 38A-38B, the drilling mud screen **3840** has a body **505**, **2205** having a first end **515**, **2215** and a second end **510**, **2210**, a drilling mud inlet **525**, **2225**, a drilling mud outlet **520**, **2220**, a filter **530**, **2230** and an end cap **535**, **2235**.

(775) In an embodiment, the drilling mud inlet **525**, **2225** may be fluidly connected to, for example, an outlet of a drilling mud pump via a connection; and the drilling mud outlet **520**, **2220** may be fluidly connected to an inlet of a vibrator hose via a connection. Any suitable connection may be used for the drilling mud inlet **525**, **2225** and the drilling mud outlet **520**, **2220**. For example,

suitable connections include, but are not limited to, pipe fittings and welds. Connections are well known in the art. In an embodiment, the drilling mud inlet **525, 2225** may be fluidly connected to, for example, an outlet of a drilling mud pump via a weld; and the drilling mud outlet **520, 2220** may be fluidly connected to an inlet of a vibrator hose via a weld.

(776) In an embodiment, the body **505, 2205** of the drilling mud screen **3840** may be constructed of any suitable material. For example, suitable materials include, but are not limited to, any alloy steel or tool steel. In an embodiment, the body **505, 2205** may be constructed of an AISI 4145 or equivalent material. In an embodiment, the body **505, 2205** may be constructed of tool steel or equivalent material.

(777) In an embodiment, the body **505, 2205** of the drilling mud screen **3840** may have a hardened coating to reduce washing (i.e., erosion) of the screen **3840**. For example, suitable hardened coatings include, but are not limited to, any Carbide coating or equivalent. In an embodiment, the body **505, 2205** may have a Carbide coating with about 6% Cobalt binder or equivalent material.

(778) In an embodiment, the drilling mud outlet **520, 2220** of the drilling mud screen **3840** may have any suitable inner diameter **565, 2265**; and the drilling mud outlet **520, 2220** may have any suitable outer diameter **570, 2270**. In an embodiment, the inner diameter **565, 2265** of the drilling mud outlet **520, 2220** may be from about 3-inches to about 5-inches, and any range or value there between. In an embodiment, the inner diameter **565, 2265** of the drilling mud outlet **520, 2220** may be about 3.9-inches.

(779) In an embodiment, the outer diameter **570, 2270** of the drilling mud outlet **525, 2225** may be from about 4-inches to about 6-inches, and any range or value there between. In an embodiment, the outer diameter **570, 2270** of the drilling mud inlet **525, 2225** may be about 4-inches.

(780) In an embodiment, a first portion **580, 2280** of the body **505, 2205** of the drilling mud screen **3850** may have a filter **535, 2235**. In an embodiment, the filter **535, 2235** may comprise a plurality of rods spaced a distance apart to form a filter. In an embodiment, the distance may be less than a particle size (e.g., diameter) desired to be filtered from the drilling mud. For example, the particle size desired to be filtered from drilling mud may be from about 3/16-inches and larger. For example, the particle size desired to be filtered from the completion fluids may be from about 200 microns to about 2500 microns.

(781) In an embodiment, the filter **535, 2235** may comprise a formed sheet having drilled holes spaced a distance apart to form a filter. In an embodiment, the size of the holes (e.g., diameter) may be less than a particle size (e.g., diameter) desired to be filtered. For example, the particle size desired to be filtered from drilling mud may be from about 3/16-inches and larger. For example, the particle size desired to be filtered from the completion fluids may be from about 200 microns to about 2500 microns.

(782) In an embodiment, a first portion **580, 2280** of the body **505, 2205** of the drilling mud screen **3850** may have a drilling mud inlet **525, 2225**. In an embodiment, the drilling mud inlet **525, 2225** may comprise a plurality of spaces (i.e., flow passages) between a plurality of rods. In an embodiment, the drilling mud inlet **525, 2225** may comprise a plurality of holes (i.e., flow passages) drilled in a formed sheet. For example, the particle size desired to be filtered from drilling mud may be from about 3/16-inches and larger. For example, the particle size desired to be filtered from the completion fluids may be from about 200 microns to about 2500 microns.

(783) In an embodiment, the first portion **580, 2280** of the body **505, 2205** of the drilling mud screen **3850** may have a first inner diameter **590**; and the second portion **575, 2275** of the body **505, 2205** may have a second inner diameter **585, 2285**.

(784) In an embodiment, the body **505, 2205** and/or a filter **535, 2235** of the drilling mud screen **3840** may have a tapered drilling mud flow path from a larger inner diameter to a smaller inner diameter to reduce washing (i.e., erosion) of the screen **3840**.

(785) In an embodiment, the first inner diameter **590, 2290** of a first end of the body **505, 2205** of the drilling mud screen **3840** may be from about 2-inches to about 3-inches, and any range or value

there between. In an embodiment, the first inner diameter **590, 2290** of the first portion **575, 2275** of the body **505, 2205** may be about 2.3-inches.

(786) In an embodiment, an inner diameter of an outlet of the first portion **580, 2280** and an inlet of the second portion **575, 2275** of the body **505, 2205** may be from about 2-inches to about 3-inches, and any range or value there between. In an embodiment, the inner diameter of the outlet of the first portion **580, 2280** of the body **505, 2205** and the inlet of the second portion **575, 2275** of the body **505, 2205** may be about 2.5-inches.

(787) In an embodiment, the second inner diameter **585, 2285** of a second end of the body **505, 2205** of the drilling mud screen **3840** may be from about 2-inches to about 5-inches, and any range or value there between. In an embodiment, the second inner diameter **585, 2285** of the second end of the body **505, 2205** may be about 3.9-inches.

(788) In an embodiment, the outer surface **595, 2295** of the second portion **527, 2275** of the body **505, 2205** of the drilling mud screen **3840** may be adapted to engage one or more shoulders in an inner surface of the trapdoor body **38405**. In an embodiment, a first shoulder and a second shoulder of the trapdoor body **38405** may be offset from a second end **38415** of the body **38405**. The first and second shoulders may be offset from the second end **38415** of the trapdoor body **38405** at any suitable distance. In an embodiment, the first shoulder may be offset from the second end **38415** of the trapdoor body **38405** from about 4-inches to about 8-inches; and the second shoulder may be offset from the second end **38415** of the trapdoor body **38405** from about 5-inches to about 9-inches, and any range or value there between. In an embodiment, the first shoulder may be offset from the second end **38415** of the trapdoor body **38405** about 4.8-inches; and the second shoulder may be offset from the second end **38415** of the trapdoor body **38405** about 6.8-inches.

(789) In an embodiment, the outer surface **595, 2295** of the body **505, 2205** of the drilling mud screen **4140, 4240** may be sealed against an inner surface of the trapdoor body **38405** via an O-ring. Cf. FIGS. 4A & 5A. Any suitable O-ring may be used. For example, suitable O-rings include, but are not limited to, 300 Series O-rings. O-rings are well known in the art.

(790) In an embodiment, a groove for an O-ring may be offset from a second end **515, 2215** of the body **505, 2205** of the drilling mud screen **3840**. The groove for the O-ring may be offset from the second end **515, 2215** of the body **505, 2205** at any suitable distance. In an embodiment, the groove for the O-ring may be offset from the second end **515, 2215** of the body **505, 2205** from about 4-inches to about 8-inches, and any range or value there between. In an embodiment, the groove for the O-ring may be offset from the second end **515, 2215** of the body **505, 2205** about 5.7-inches.

(791) In an embodiment, the filter **530, 2230** may have a plurality of rods spaced a distance apart to form a filter, or, alternatively, a formed sheet having drilled holes spaced a distance apart to form a filter. In an embodiment, the plurality of rods may be tapered from a larger outer diameter to a smaller outer diameter to encourage drilling mud flow to enter in straight lines through the drilling mud inlet **525, 2225** (i.e., through flow passages between the plurality rods) to reduce washing (i.e., erosion) of the screen **3840**. In an embodiment, the filter **530, 2230** may have a plurality of straight rows of holes drilled in a formed sheet to encourage drilling mud flow to enter in straight rows of strings through the drilling mud inlet **525, 2225** (i.e., through straight flow passages of the drilled holes) to reduce washing (i.e., erosion) of the screen **3840**.

(792) In an embodiment, a first end of a filter **530, 2230** may be connected to a second end of the end cap **535, 2235** via a connection; and a second end of a filter **530, 2230** may be connected to a first end **515, 2215** of the body **505, 2205** via a connection. Any suitable connection may be used for the filter **41230, 42230** and end cap **41235, 42235**. For example, suitable connections include, but are not limited to, welds. Connections are well known in the art. In an embodiment, the first end of the filter **530, 2230** may be connected to the second end of the end cap **535, 2235** via a weld; and the second end of the filter **530, 2230** may be connected to the first end **515, 2215** of the body **505, 2205** via a weld.

(793) In an embodiment, the first end of the filter **530, 2230** may fit into a first recess in the second

end of the end cap **535, 2235**; and the second end of the filter **530, 2230** may fit into a second recess in the first end **515, 2215** of the body **505, 2205**. In an embodiment, the first recess and the second recess may be a plurality of recessed holes or a recessed groove. In an embodiment, the first recess and the second recess may be a plurality of recessed holes.

(794) In an embodiment, the filter **530, 2230** may be held together with a retaining ring. In an embodiment, the retaining ring may have a plurality of holes to hold the plurality of rods to form the filter **530, 2230**. In an embodiment, the plurality of rods may be connected to the plurality of holes in the retainer ring via a connection. Any suitable connection may be used for the filter **530, 2230** and retaining ring. For example, suitable connections include, but are not limited to, welds. Connections are well known in the art. In an embodiment, the plurality of rods may be connected to the plurality of holes in the retainer ring via a weld.

(795) In an embodiment, the filter **530, 2230**, including any retaining rings, of the drilling mud screen **3840** may be constructed of any suitable material. For example, suitable materials include, but are not limited to, any alloy steel. In an embodiment, the filter **530, 2230** may be constructed of 304 stainless steel material. In an embodiment, the filter **530, 2230** may have a hardened coating to reduce washing (i.e., erosion) of the screen **3840**.

(796) In an embodiment, the end cap **535, 2235** of the drilling mud screen **3840** has an outer surface. In an embodiment, the outer surface of the end cap **535, 2235** of the drilling mud screen **3840** may redirect the flow to reduce washing (i.e., erosion) of the screen **3840**. In an embodiment, the outer surface of the end cap **535, 2235** of the drilling mud screen **3840** forms an inverted cone relative to the first end **515, 2215** of the body **505, 2205** of the drilling mud screen **3840** (i.e., an upstream pointing cone) to redirect the flow. In an embodiment, the tip of the inverted cone may have a rounded or squared shape.

(797) In an embodiment, the body **505, 2205** of the drilling mud screen **3840** has a centerline **545, 2245**. In an embodiment, the centerline **545, 2245** extends through the center of the drilling mud screen outlet **525, 2225** to the end cap **535, 2235**. In an embodiment, the centerline **545, 2245** of the body **505, 2205** of the drilling mud screen **3840** and the outer surface **555, 2255** of the end cap **535, 2235** form an angle **560, 2260**. In an embodiment, the angle **560, 2260** may be from about 30-degrees to about 90-degrees, and any range or value there between. In an embodiment, the angle **560, 2260** may be from about 35-degrees to about 45-degrees.

(798) In an embodiment, the end cap **535, 2235** of the drilling mud screen **3840** may be constructed of any suitable material. For example, suitable materials include, but are not limited to, any alloy steel. In an embodiment, the end cap **535, 2235** may be constructed of 304 stainless steel material. In an embodiment, the end cap **535, 2235** of the drilling mud screen **3840** may have a hardened coating to reduce washing (i.e., erosion) of the screen **3840**. For example, suitable hardened coatings include, but are not limited to, any Carbide coating or equivalent. In an embodiment, the end cap **535, 2235** may have a Carbide coating with about 6% Cobalt binder or equivalent material.

(799) Method of Using Valve-Style Drilling Mud Screen System

(800) FIG. **34** illustrates a flow diagram for a method of using a drilling mud screen system, as discussed above. As shown in FIG. **34**, the method of using a drilling mud system **3400** comprises stopping a drilling mud pump to stop flow of drilling mud **3405**, fluidly connecting a drilling mud inlet of a drilling mud screen system downstream of an outlet to the drilling mud pump **3410**, fluidly connecting a drilling mud outlet of the drilling mud screen system upstream of an outlet of a stand pipe **3415**, and starting the drilling mud pump to flow drilling mud through the drilling mud screen system **3420**. See also FIG. **10**.

(801) In an embodiment, the drilling mud inlet **3020, 3120, 3220, 3320** of the drilling mud screen system **3000, 3100, 3200, 3300** may be fluidly connected to a high pressure outlet of the drilling mud pump via a connection. See also FIGS. **14, 19, 21, 23 & 26**. The inlet pressure to the drilling mud inlet **3020, 3120, 3220, 3320** of the drilling mud screen system **3000, 3100, 3200, 3300** may be any suitable pressure. In an embodiment, the inlet pressure may be from about 7500 psi to about

10,000 psi, and any range or value there between.

(802) In an embodiment, the drilling mud outlet **3025, 3125, 3225, 3325** of the drilling mud screen system **3000, 3100, 3200, 3300** may be fluidly connected to an inlet of a vibrator hose to the standpipe via a connection.

(803) In an embodiment, the drilling mud inlet **3020, 3120, 3220, 3320** of the drilling mud screen system **3000, 3100, 3200, 3300** may be fluidly connected to an outlet of a vibrator hose to a standpipe via a connection. In an embodiment, the drilling mud outlet **3025, 3125, 3225, 3325** of the drilling mud screen system **3000, 3100, 3200, 3300** may be fluidly connected to an inlet of the standpipe via a connection.

(804) In an embodiment, the drilling mud screen system **3000, 3100, 3200, 3300** may be fluidly connected at any point in the standpipe via a connection.

(805) Optional Monitoring Configuration

(806) FIG. 35A illustrates a flow diagram for a method of using a drilling mud screen system; and FIG. 35B illustrates a flow diagram of optional steps for the method of FIG. 35A, as discussed above.

(807) As shown in FIGS. 35A and 35B, the method of using a drilling mud screen system **3500** comprises stopping a drilling mud pump to stop flow of drilling mud **3505**, fluidly connecting a drilling mud inlet of a drilling mud screen system downstream of an outlet to the drilling mud pump, and, optionally, fluidly connecting a first transducer to a first transducer access port of the drilling mud screen system (e.g., first transducer subassembly) and/or fluidly connecting a second transducer to a second transducer access port of the drilling mud screen system (e.g., second transducer subassembly) **3510**, fluidly connecting a drilling mud outlet of the drilling mud screen system upstream of an outlet of a stand pipe **3515**, and starting the drilling mud pump to flow drilling mud through the drilling mud screen system **3520**, and optionally, monitoring the first transducer and/or the second transducer for property information **3525**.

(808) In an embodiment, step **3510** comprises fluidly connecting a first transducer to a first transducer access port of the drilling mud screen system (e.g., first transducer subassembly); and fluidly connecting a drilling mud inlet of a drilling mud screen system downstream of an outlet to the drilling mud pump.

(809) In an embodiment, step **3510** comprises fluidly connecting a first transducer to a first transducer access port of the drilling mud screen system (e.g., first transducer subassembly); fluidly connecting a second transducer to a second transducer access port of the drilling mud system (e.g., second transducer subassembly); and fluidly connecting a drilling mud inlet of a drilling mud screen system downstream of an outlet to the drilling mud pump.

(810) As shown in FIGS. 30B and 31B, the first transducer (not shown) may be fluidly connected to the first transducer access port **3032a, 3132a** of the drilling mud screen system **3000, 3100** (e.g., first transducer subassembly **30100a, 31100a**) via a connection. Any suitable connection may be used for the first transducer (not shown). For example, suitable connections include, but are not limited to, pipe fittings. Connections are well known in the art. In an embodiment, the first transducer (not shown) may be fluidly connected to a first transducer access port **3032a, 3132a** of the drilling mud screen system **3000, 3100** (e.g., first transducer subassembly **30100a, 31100a**) via a pipe fitting.

(811) As shown in FIGS. 30B and 31B, the second transducer (not shown) may be fluidly connected to the second transducer access port **3032b, 3132b** of the drilling mud screen system **3000, 3100** (e.g., second transducer subassembly **30100b, 31100b**) via a connection. Any suitable connection may be used for the second transducer (not shown). For example, suitable connections include, but are not limited to, pipe fittings. Connections are well known in the art. In an embodiment, the second transducer (not shown) may be fluidly connected to the second transducer access port **3032b, 3132b** of the drilling mud screen system **3000, 3100** (e.g., second transducer subassembly **30100b, 31100b**) via a pipe fitting.

(812) In an embodiment, the method of using a drilling mud screen system **3500** further comprises monitoring the first transducer (not shown) for property information (e.g., displacement, flow rate, pressure, and/or temperature) at the first transducer access port **3032a**, **3132a** of the drilling mud screen system **3000**, **3100** (e.g., first transducer subassembly **30100a**, **31100a**).

(813) In an embodiment, the method of using a drilling mud screen system **3500** further comprises monitoring the first transducer (not shown) for property information (e.g., displacement, flow rate, pressure, and/or temperature) at the first transducer access port **3032a**, **3132a** of the drilling mud screen system **3000**, **3100** (e.g., first transducer subassembly **30100a**, **31100a**). In an embodiment, the first transducer (not shown) may be fluidly connected upstream of the drilling mud screen **3040**, **3140** of the drilling mud screen system **3000**, **3100**.

(814) In an embodiment, the method of using a drilling mud screen system **3500** further comprises monitoring the second transducer (not shown) for property information (e.g., displacement, flow rate, pressure, and/or temperature) at the second transducer access port **3032b**, **3132b** of the drilling mud screen system **3000**, **3100** (e.g., second transducer subassembly **30100b**, **31100b**).

(815) In an embodiment, the method of using a drilling mud screen system **3500** further comprises monitoring the second transducer (not shown) for property information (e.g., displacement, flow rate, pressure, and/or temperature) at the second transducer access port **3032b**, **3132b** of the drilling mud screen system **3000**, **3100** (e.g., second transducer subassembly **30100b**, **31100b**). In an embodiment, the second transducer (not shown) may be fluidly connected downstream of the drilling mud screen **3040**, **3140** of the drilling mud screen system **3000**, **3100**.

(816) In an embodiment, a computing device (such as a rig computer) may include a bus that directly or indirectly couples the following devices: memory, one or more processors, one or more presentation components, one or more input/output (I/O) ports, I/O components, a user interface and a power supply. The computing device may include a variety of computer-readable media. The memory may include computer-storage media in the form of volatile and/or nonvolatile memory. The presentation component(s) present data indications to a user or other device. The user interface allows the user to input/output information to/from the computing device. The one or more I/O ports may allow the computing device to be logically coupled to other devices including a transducer **28105**, and other I/O components, some of which may be built in. See e.g., FIG. 28. Examples of other I/O components include a printer, scanner, wireless device, and the like.

(817) In an embodiment, the method of using a drilling mud screen system **3500** further comprises using the property information (e.g., displacement, flow rate, pressure, and/or temperature) from the first transducer (not shown) and/or the second transducer (not shown) to determine a status of the drilling mud screen system **3000**, **3100**, **3200**, **3300**. In an embodiment, the method further comprises using the information to determine when to clean, repair or replace the drilling mud screen **3040**, **3140**, **3240**, **3340** in the drilling mud screen system **3000**, **3100**, **3200**, **3300**.

(818) In an embodiment, pressure information from, for example, a second pressure transducer (not shown) will allow a driller to know when a drilling mud screen **3040**, **3140**, **3240**, **3340** in a drilling mud screen system **3000**, **3100**, **3200**, **3300** is “packing off” For example, the pressure information from the second pressure transducer (not shown) at the second transducer access port **3032b**, **3132b** of the drilling mud screen system **3000**, **3100** (e.g., second transducer subassembly **30100b**, **31100b**) may be compared to, for example, pressure information from a pressure transducer on a pressure transducer assembly for a stand pipe. If the pressure decreases at the stand pipe and the pressure increases at the second transducer access port **3032b**, **3132b** of the drilling mud screen system **3000**, **3100** (e.g., second transducer subassembly **30100b**, **31100b**), the drilling mud screen **3040**, **3140** is likely “packing off.” If the pressure decreases or increases at both the stand pipe and the drilling mud screen system **3000**, **3100** (e.g., second transducer subassembly **30100b**, **31100b**), then the problem is likely down hole and not at the drilling mud screen system **3000**, **3100**. If the problem is at the drilling mud screen system **3000**, **3100**, the drilling mud screen **3040**, **3140** may be cleaned, repaired or replaced.

(819) Method of Removing and Replacing Drilling Mud Screen for Improved Drilling Mud Screen System

(820) FIG. **36** illustrates a method of removing and replacing a drilling mud screen in a drilling mud screen system, as discussed above. As shown in FIG. **36**, the method of removing and replacing a drilling mud screen **3600** comprises stopping a drilling mud pump connected to a drilling mud screen system **3605**, rotating a rotating subassembly to open the drilling mud screen system **3610**, accessing the interior of the drilling mud screen system to remove a drilling mud screen from the drilling mud screen system and to install a replacement drilling mud screen into the drilling mud screen system **3615**, rotating the rotating subassembly to close and seal the drilling mud screen system **3620**, and operating the drilling mud pump to produce flow of drilling mud through the replacement drilling mud screen of the drilling mud screen system **3525**. See also FIG. **11**.

(821) Method of Removing and Replacing Drilling Mud Screen for Alternative Improved Drilling Mud Screen System

(822) FIG. **39** illustrates a method of removing and replacing a drilling mud screen in a four-piece drilling mud screen system, as discussed above. As shown in FIG. **39**, the method of removing and replacing a drilling mud screen **3900** comprises stopping a drilling mud pump connected to the trapdoor-style drilling mud screen system **3905**, rotating a rotating trapdoor subassembly to open the drilling mud screen system **3910**, accessing the interior of the drilling mud screen system to remove a drilling mud screen from the drilling mud screen system and to install a replacement drilling mud screen into the drilling mud screen system **3915**, rotating the rotating trapdoor subassembly to close and seal the drilling mud screen system **3920**, and operating the drilling mud pump to produce flow of drilling mud through the replacement drilling mud screen of the drilling mud screen system **3925**.

(823) In the foregoing description of certain embodiments, specific terminology has been resorted to for the sake of clarity. However, the disclosure is not intended to be limited to the specific terms so selected, and it is to be understood that each specific term includes other technical equivalents which operate in a similar manner to accomplish a similar technical purpose. Terms (e.g., “outer” and “inner,” “upper” and “lower,” “first” and “second,” “internal” and “external,” “above” and “below” and the like) are used as words of convenience to provide reference points and, as such, are not to be construed as limiting terms.

(824) The embodiments set forth herein are presented to best explain the present invention and its practical application and to thereby enable those skilled in the art to make and utilize the invention. However, those skilled in the art will recognize that the foregoing description has been presented for the purpose of illustration and example only. The description as set forth is not intended to be exhaustive or to limit the invention to the precise form disclosed. Many modifications and variations are possible in light of the above teaching without departing from the spirit and scope of the following claims.

(825) Also, the various embodiments described above may be implemented in conjunction with other embodiments, e.g., aspects of one embodiment may be combined with aspects of another embodiment to realize yet other embodiments. Further, each independent feature or component of any given assembly may constitute an additional embodiment.

Definitions

(826) As used herein, the terms “a,” “an,” “the,” and “said” mean one or more, unless the context dictates otherwise.

(827) As used herein, the term “about” means the stated value plus or minus a margin of error plus or minus 10% if no method of measurement is indicated.

(828) As used herein, the term “or” means “and/or” unless explicitly indicated to refer to alternatives only or if the alternatives are mutually exclusive.

(829) As used herein, the terms “comprising,” “comprises,” and “comprise” are open-ended

transition terms used to transition from a subject recited before the term to one or more elements recited after the term, where the element or elements listed after the transition term are not necessarily the only elements that make up the subject.

(830) As used herein, the terms “containing,” “contains,” and “contain” have the same open-ended meaning as “comprising,” “comprises,” and “comprise,” provided above.

(831) As used herein, the terms “having,” “has,” and “have” have the same open-ended meaning as “comprising,” “comprises,” and “comprise,” provided above.

(832) As used herein, the terms “including,” “includes,” and “include” have the same open-ended meaning as “comprising,” “comprises,” and “comprise,” provided above.

(833) As used herein, the phrase “consisting of” is a closed transition term used to transition from a subject recited before the term to one or more material elements recited after the term, where the material element or elements listed after the transition term are the only material elements that make up the subject.

(834) As used herein, the term “simultaneously” means occurring at the same time or about the same time, including concurrently.

INCORPORATION BY REFERENCE

(835) All patents and patent applications, articles, reports, and other documents cited herein are fully incorporated by reference to the extent they are not inconsistent with this invention.

Claims

1. A trapdoor-style drilling mud screen system, comprising: (a) a first body having a first portion, a second portion and a third portion; (b) a first drilling mud inlet at a first end of the first portion of the first body; (c) a first drilling mud outlet at a second end of the third portion of the first body; (d) a rotating trapdoor subassembly, wherein the rotating trapdoor subassembly is disposed within the second portion of the first body, wherein the first portion of the first body is fluidly connected to a first end of the rotating subassembly, and wherein a second end of the rotating subassembly is fluidly connected to the third portion of the first body; (e) a pivot subassembly, wherein the pivot subassembly is disposed through the rotating trapdoor subassembly and through the second portion of the first body; and (f) a drilling mud screen, wherein the drilling mud screen is disposed within the rotating trapdoor subassembly between the first drilling mud inlet and the first drilling mud outlet.

2. The drilling mud screen system of claim 1, wherein the rotating trapdoor subassembly comprises: (a) a second body, wherein a first end of the second body is fluidly connected to a second end of the first portion of the first body and wherein a second end of the second body is fluidly connected to a first end of the third portion of the first body.

3. The drilling mud screen system of claim 1, wherein the pivot subassembly comprises: (a) a pivot shaft; and (b) a retaining ring, wherein the retaining ring retains the pivot shaft through the second portion of the first body.

4. The drilling mud screen system of claim 1, wherein the first portion of the first body comprises a first piston.

5. The drilling mud screen system of claim 4 further comprising a piston guide bar disposed through the first portion of the first body and into a portion of the first piston, wherein the piston guide bar guides a second end of the first piston to engage a first end of the rotating trapdoor subassembly when the rotating trapdoor subassembly is in a closed position.

6. The drilling mud screen system of claim 4 further comprising a piston guide bar disposed through the first portion of the first body and into a portion of the first piston, wherein the piston guide bar locks a second end of the first piston to contact and seal a first end of the rotating trapdoor subassembly when the rotating trapdoor subassembly is in a closed position.

7. The drilling mud screen system of claim 4 further comprising a piston guide bar disposed

through the first portion of the first body first body and into a portion of the first piston, wherein the piston guide bar guides a second end of the first piston to disengage from a first end of the rotating trapdoor subassembly when the rotating trapdoor subassembly is in an open position.

8. The drilling mud screen system of claim 4 further comprising a piston guide bar disposed through the first portion of the first body and into a portion of the first piston, wherein the piston guide bar separates a second end of the first piston to disengage and create a gap from a first end of the rotating trapdoor subassembly when the rotating trapdoor subassembly is in the open position to avoid damage to a first seal face at the second end of the first piston and/or the second seal face at the first end of the rotating trapdoor subassembly.

9. The drilling mud screen system of claim 4, wherein the piston guide bar further comprises a ball bearing for smooth operation.

10. The drilling mud screen system of claim 4 further comprising: (a) a first spring, wherein the first spring is disposed between the first piston and a first subassembly, wherein the first subassembly comprises: i. a second body having a first end and a second end; ii. a second drilling mud inlet at the first end of the second body; and iii. a second drilling mud outlet at the second end of the second body, wherein the second end of the second body is fluidly connected to the first end of the first portion of the first body.

11. The drilling mud screen system of claim 10, wherein the second end of the first piston has a first seal face and wherein the first end of the rotating trapdoor subassembly has a second seal face.

12. The drilling mud screen system of claim 4, wherein the third portion of the first body comprises a second piston.

13. The drilling mud screen system of claim 12 further comprising: (a) a second spring, wherein the second spring is disposed between the second piston and a second subassembly, wherein the second subassembly comprises: i. a third body having a first end and a second end; ii. a third drilling mud inlet at the first end of the third body; iii. a third drilling mud outlet at the second end of the third body, wherein the second end of the third portion of the first body is fluidly connected to the first end of the third body.

14. The drilling mud screen system of claim 13, wherein the second end of the rotating trapdoor subassembly has a third seal face and wherein the first end of the second piston has a fourth seal face.

15. The drilling mud screen system of claim 4, further comprising a threaded lock ring, wherein the threaded lock ring is disposed around the first portion of the first body and the first end of the trapdoor subassembly.

16. The drilling mud screen system of claim 15, wherein the threaded lock ring further comprises a handle.

17. The drilling mud screen system of claim 4 further comprising a threaded lock ring, wherein the threaded lock ring is disposed around a first portion of the body and a first end of the rotating trapdoor subassembly to lock the trapdoor subassembly in a closed position.

18. The drilling mud screen system of claim 4 further comprising a piston guide bar disposed through a first slot in the first portion of the first body or the second portion of the body, and into a second slot in the first piston, wherein the piston guide bar guides a second end of the first piston to engage a first end of the rotating trapdoor subassembly when the rotating trapdoor subassembly is in a closed position.

19. The drilling mud screen system of claim 4 further comprising a piston guide bar disposed through a first slot in the first portion of the first body or the second portion of the body, and into a second slot of the first piston, wherein the piston guide bar locks a second end of the first piston to contact and seal a first end of the rotating trapdoor subassembly when the rotating trapdoor subassembly is in a closed position.

20. The drilling mud screen system of claim 1, wherein the drilling mud screen comprises: (a) a second body having a first end and a second end and a first centerline; (b) a filter having a first end,

a second end, and openings, wherein the first end of the filter is fluidly connected to the first end of the second body via a first connection and/or a first end retaining ring; (c) an end cap fluidly connected at the second end of the filter via a second connection, wherein the filter has a retaining ring disposed between the first connection and the second connection; (d) a second drilling mud inlet at the first end of the second body; and (e) a second drilling mud outlet at the openings of the filter.

21. The drilling mud screen system of claim 20, wherein the filter comprises a plurality of rods having a first end and a second end, wherein each of the plurality of rods are spaced a distance apart to form the openings in the filter.

22. The drilling mud screen system of claim 21, wherein each of the plurality of rods are tapered from the first end to the second end.

23. The drilling mud screen system of claim 20, wherein the filter comprises a formed sheet having drilled holes or slots spaced a distance apart to form the openings in the filter.

24. The drilling mud screen system of claim 23, wherein the drilled holes or slots are drilled in offset rows or straight rows from the first end to the second end.

25. The drilling mud screen system of claim 20, wherein the filter is tapered from the first end to the second end.

26. The drilling mud screen system of claim 20, wherein the end cap is a flat plate or a flat plate with holes or slots.

27. The drilling mud screen of claim 20, wherein the end cap is an inverted cone or an inverted cone with holes or slots.

28. The drilling mud screen system of claim 20, wherein the first centerline of the second body and an outer surface of the end cap forms a cap angle, wherein the cap angle is from about 30-degrees to about 90-degrees.

29. The drilling mud screen system of claim 20, wherein the first centerline of the second body and an outer surface of the end cap forms a cap angle, wherein the cap angle is from about 35-degrees to about 45-degrees.

30. The drilling mud screen system of claim 20, wherein the filter, the first end retaining ring and/or the retaining ring are constructed from AISI 4145 or equivalent, stainless steel or combinations thereof.

31. The drilling mud screen system of claim 20, wherein the filter, the first end retaining ring and/or the retaining ring has a hardened coating.

32. The drilling mud screen system of claim 20, wherein one or more of the filter, the first end retaining ring and/or the retaining ring has a Carbide coating with about 6% Cobalt binder.

33. The drilling mud screen system of claim 20, wherein one or more of the first body and the second body are constructed from AISI 4130/75k or equivalent material, AISI 4145 or equivalent, or combinations thereof.

34. The drilling mud screen system of claim 1, wherein the drilling mud screen comprises: (a) a second body having a first end and a second end and a first centerline; (b) a filter having a first end and a second end, and openings, wherein the second end of the filter is fluidly connected to the first end of the second body via a first connection and/or a second end retaining ring; (c) an end cap fluidly connected at the first end of the filter via a second connection, wherein the filter has a retaining ring disposed between the first connection and the second connection; (d) a second drilling mud inlet at the openings of the filter; and (e) a second drilling mud outlet at the second end of the second body.

35. The drilling mud screen system of claim 34, wherein the filter comprises a plurality of rods having a first end and a second end, wherein each of the plurality of rods are spaced a distance apart to form the openings in the filter.

36. The drilling mud screen system of claim 35, wherein each of the plurality of rods are tapered from the first end to the second end.

37. The drilling mud screen system of claim 34, wherein the filter comprises a formed sheet having drilled holes or slots spaced a distance apart to form the openings in the filter.
38. The drilling mud screen system of claim 37, wherein the drilled holes or slots are drilled in offset rows or straight rows from the first end to the second end.
39. The drilling mud screen system of claim 34, wherein the filter is tapered from the second end to the first end.
40. The drilling mud screen system of claim 34, wherein the end cap is a flat plate or a flat plate with holes or slots.
41. The drilling mud screen of claim 34, wherein the end cap is a cone or a cone with holes or slots.
42. The drilling mud screen system of claim 34, wherein the first centerline of the second body and an outer surface of the end cap forms a cap angle, wherein the cap angle is from about 30-degrees to about 90-degrees.
43. The drilling mud screen system of claim 34, wherein the first centerline of the second body and an outer surface of the end cap forms a cap angle, wherein the cap angle is from about 35-degrees to about 45-degrees.
44. The drilling mud screen system of claim 34, wherein the filter, the second end retaining ring and/or the retaining ring are constructed from AISI 4145 or equivalent, stainless steel or combinations thereof.
45. The drilling mud screen system of claim 34, wherein the filter, the second end retaining ring and/or the retaining ring has a hardened coating.
46. The drilling mud screen system of claim 34, wherein one or more of the filter, the second end retaining ring and/or the retaining ring has a Carbide coating with about 6% Cobalt binder.
47. The drilling mud screen system of claim 34, wherein one or more of the first body, and the second body are constructed from AISI 4130/75k or equivalent material, AISI 4145 or equivalent, or combinations thereof.
48. A method of installing a trapdoor-style drilling mud screen system comprising: (a) stopping a drilling mud pump to fluidly connect the drilling mud screen system of claim 1 to the drilling mud pump; (b) fluidly connecting the drilling mud screen system in line with and immediately upstream or downstream of the drilling mud pump; and (c) operating the drilling mud pump to produce flow of drilling mud through the drilling mud screen system.
49. The method of claim 48, wherein step b) comprises fluidly connecting a drilling mud inlet of the drilling mud screen system to a high-pressure outlet of the drilling mud pump and fluidly connecting a drilling mud outlet of the drilling mud screen system to a vibrator hose or a standpipe.
50. The method of claim 48, wherein step b) comprises fluidly connecting a drilling mud inlet of the drilling mud screen system to a high-pressure inlet of the drilling mud pump and fluidly connecting a drilling mud outlet of the drilling mud screen system to an inlet of a vibrator hose.
51. The method of claim 48, wherein step b) comprises fluidly connecting a drilling mud inlet of the drilling mud screen system to an outlet of a vibrator hose and a drilling mud outlet to an inlet of a standpipe.
52. The method of claim 48, wherein step b) comprises fluidly connecting a drilling mud inlet of the drilling mud screen system to an outlet of a first portion of a standpipe and a drilling mud outlet of the drilling mud screen system to an inlet of a second portion of the standpipe.
53. The method of claim 48, further comprising step d) filtering or screening debris from drilling mud.
54. A method of removing and replacing a drilling mud screen comprising: (a) stopping a drilling mud pump connected to the drilling mud screen system of claim 1; (b) rotating a rotating trapdoor subassembly to open the drilling mud screen system; (c) removing the drilling mud screen; (d) installing a replacement drilling mud screen; (e) rotating the rotating trapdoor subassembly to close and seal the drilling mud screen system; and (f) operating the drilling mud pump to produce flow of drilling mud through the drilling mud screen system.

55. The method of claim 54, wherein step b) comprises: step b-1) removing a piston guide bar and/or a threaded lock ring and step b-2) rotating the rotating trapdoor subassembly to open the drilling mud screen system.

56. The method of claim 54, wherein step d) comprises: step d-1) rotating the trapdoor subassembly to close the drilling mud screen system and step d-2) installing a piston guide bar and/or a threaded lock ring to seal the drilling mud screen system.

57. The method of claim 54, wherein step b) comprises: step b-1) removing a piston guide bar and/or a threaded lock ring and step b-2) rotating the rotating trapdoor subassembly to open the drilling mud screen system, and wherein step d) comprises: step d-1) rotating the trapdoor subassembly to close the drilling mud screen system and step d-2) installing a piston guide bar and/or a threaded lock ring to seal the drilling mud screen system.
