

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12405636
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Kim; Youngjae et al.

Electronic device comprising hall sensor for identifying folding state

Abstract

An electronic device is disclosed, including: a first housing, a second housing, a folding housing that pivotably connects the first housing and second housing, a flexible display spanning the first, second and folding housings, a printed circuit board (PCB), a first camera module at least partly visible through a surface of the second housing, a first magnet disposed in the first housing, a second magnet disposed in the second housing, and a hall sensor disposed on the PCB, the hall sensor configured to detect magnetic flux caused by motion of the first and/or second magnet in folding and unfolding of the electronic device so as facilitate determination of a configuration state of the electronic device.

Inventors: Kim; Youngjae (Gyeonggi-do, KR), Chun; Woosung (Gyeonggi-do, KR), Yang; Changkwan (Gyeonggi-do, KR), Ryu; Kwanghee (Gyeonggi-do, KR), Hong; Hyunju (Gyeonggi-do, KR)

Applicant: SAMSUNG ELECTRONICS CO., LTD. (Suwon-si, KR)

Family ID: 85177582

Assignee: Samsung Electronics Co., Ltd. (Suwon-si, KR)

Appl. No.: 18/654054

Filed: May 03, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240281039 A1	Aug. 22, 2024

Foreign Application Priority Data

KR	10-2021-0105594	Aug. 10, 2021
----	-----------------	---------------

Related U.S. Application Data

continuation parent-doc US 17837388 20220610 US 11977419 child-doc US 18654054
continuation parent-doc WO PCT/KR2022/007070 20220517 PENDING child-doc US 17837388

Publication Classification

Int. Cl.: G06F1/16 (20060101)

U.S. Cl.:

CPC G06F1/1677 (20130101); G06F1/1616 (20130101); G06F1/1652 (20130101);
G06F1/1681 (20130101); G06F1/1686 (20130101); G06F1/169 (20130101);
G06F1/1698 (20130101);

Field of Classification Search

CPC: G06F (1/1616); G06F (1/1652); G06F (1/1677)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
8243438	12/2011	Wang	N/A	N/A
8295037	12/2011	Buuck	N/A	N/A
8321709	12/2011	Jin	N/A	N/A
8624695	12/2013	Cretella et al.	N/A	N/A
9823093	12/2016	Kauhaniemi et al.	N/A	N/A
10024689	12/2017	Zhu	N/A	N/A
10063677	12/2017	Cavallaro	N/A	N/A
10073668	12/2017	Chun et al.	N/A	N/A
10338642	12/2018	Furlong	N/A	N/A
10338643	12/2018	Wu	N/A	N/A
10580556	12/2019	Lauder	N/A	N/A
11281254	12/2021	Lee et al.	N/A	N/A
11300995	12/2021	Eom et al.	N/A	N/A
11317010	12/2021	Aschwanden et al.	N/A	N/A
11510328	12/2021	Kim	N/A	N/A
11838434	12/2022	Lyu	N/A	N/A
11977419	12/2023	Kim	N/A	G06F 1/1658
2004/0227407	12/2003	Nagai	N/A	N/A
2014/0035872	12/2013	Park	N/A	N/A
2017/0357292	12/2016	Cho	N/A	N/A
2018/0181361	12/2017	Becze	N/A	B29D 11/00673
2020/0267861	12/2019	Kim	N/A	N/A
2021/0116962	12/2020	Lee	N/A	N/A

2021/0409521	12/2020	Shim et al.	N/A	N/A
2021/0409531	12/2020	Shim et al.	N/A	N/A
2021/0409532	12/2020	Lee	N/A	N/A
2022/0086268	12/2021	Lyu	N/A	G06T 7/55

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
110213413	12/2018	CN	N/A
110849257	12/2019	CN	N/A
4304871	12/2008	JP	N/A
10-0442625	12/2003	KR	N/A
20-0367900	12/2003	KR	N/A
10-0628765	12/2005	KR	N/A
10-2008-0025881	12/2007	KR	N/A
10-2018-0118720	12/2017	KR	N/A
10-2020-0101791	12/2019	KR	N/A
10-2020-0126315	12/2019	KR	N/A
10-2021-0045668	12/2020	KR	N/A
WO 2020/238506	12/2019	WO	N/A
WO2020/256168	12/2019	WO	N/A

OTHER PUBLICATIONS

European Search Report dated Oct. 1, 2024 for EP Application No. 22855970.4. cited by applicant
KR Notification of the Reasons for Rejection dated Oct. 16, 2024 for KR Application No. 10-2021-0105594. cited by applicant

U.S. Appl. No. 17/837,388, filed Jun. 10, 2022; KIM et al. cited by applicant

International Search Report dated Aug. 18, 2022. cited by applicant

PCT International Patent Publication dated Dec. 24, 2020. cited by applicant

English Translation of International Search Report dated Aug. 18, 2022. cited by applicant

Primary Examiner: Wilson; Adrian S

Attorney, Agent or Firm: Nixon & Vanderhye P.C.

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION(S)

(1) This application is based on and claims priority under 35 U.S.C. § 120 to PCT International Application No. PCT/KR2022/007070, which was filed on May 17, 2021, and claims priority to Korean Patent Application No. 10-2021-0105594, filed on Aug. 10, 2021, the disclosures of which are incorporated by reference herein their entirety.

BACKGROUND

Technical Field

(2) The following descriptions relate to an electronic device comprising a hall sensor for identifying a folding state.

Description of Related Art

(3) An electronic device including a flexible display panel has been developed. The electronic device may provide a folding state (e.g., completely folding), an unfolding state (e.g., completely

unfolded), an intermediate state between the folding state and the unfolding state through the flexible display panel. The electronic device may provide a wider screen in the unfolding state, provide enhanced portability in the folding state, and provide various user experiences in the intermediate state.

(4) The electronic device may include a flexible display panel, and may provide various states (e.g., a folding state, an unfolding state, or an intermediate state) through the flexible display panel. The electronic device may include a plurality of magnets to maintain the folding state or to identify the folding state. In order to provide different functions according to the various states, the electronic device may include a hall sensor that identifies the various states using a magnetic field from at least some of the plurality of magnets.

(5) Meanwhile, since the magnetic field from the plurality of magnets may affect the performance of components included in the electronic device, it may be required in the electronic device to mount the hall sensor in a position capable of reducing the number of magnets.

(6) The technical problems to be achieved in this document are not limited to those described above, and other technical problems not mentioned herein will be clearly understood by those having ordinary knowledge in the art to which the present disclosure belongs, from the following description.

SUMMARY

(7) According to an embodiment, an electronic device may comprise a first housing comprising a first surface and a second surface faced away the first surface; a second housing comprising a third surface and a fourth surface faced away the third surface; a folding housing pivotably connecting a side surface of the first housing and a side surface of the second housing facing the side surface of the first housing based on a folding axis; a flexible display panel disposed on the first surface and the third surface across the folding housing; a printed circuit board (PCB) in the first housing; a camera module, comprising a magnet, attached to the PCB, the camera module at least partially exposed through a portion of the second surface; a first magnet in the first housing disposed along a periphery of the first surface spaced apart from the folding axis from among peripheries of the first surface parallel to the folding axis; a second magnet in the second housing disposed in a position corresponding to a position of the first magnet; and a hall sensor, disposed between a periphery of the first surface adjacent to the first magnet from among peripheries of the first surface perpendicular to the folding axis and the camera module, mounted on the PCB.

(8) According to an embodiment, an electronic device may comprise a first housing comprising a first surface and a second surface faced away the first surface; a second housing comprising a third surface and a fourth surface faced away the third surface; a folding housing pivotably connecting a side surface of the first housing and a side surface of the second housing facing the side surface of the first housing based on a folding axis; a flexible display panel disposed on the first surface and the third surface across the folding housing; a first magnet in the first housing disposed along a periphery of the first surface spaced apart from the folding axis from among peripheries of the first surface parallel to the folding axis; a second magnet in the second housing disposed in a position corresponding to a position of the first magnet; a plurality of antenna contacts, adjacent to the periphery that is adjacent to the first magnet from among the peripheries of the first surface perpendicular to the folding axis, attached to the PCB along a periphery of the PCB, spaced apart from each other; and a hall sensor, mounted on the PCB, spaced apart from each of the plurality of antenna contacts, spaced apart from the first magnet.

(9) According to an embodiment, an electronic device may comprise a first housing comprising a first surface and a second surface faced away the first surface; a second housing comprising a third surface and a fourth surface faced away the third surface; a folding housing pivotably connecting a side surface of the first housing and a side surface of the second housing facing the side surface of the first housing based on a folding axis; a flexible display panel disposed on the first surface and the third surface across the folding housing; a camera module, comprising a magnet, attached to the

first PCB in the first housing, a second PCB in the second housing, and the first PCB, the camera module at least partially exposed through a portion of the second surface; a first magnet in the first housing disposed along a periphery of the first surface spaced apart from the folding axis from among peripheries of the first surface parallel to the folding axis; a second magnet in the second housing disposed in a position corresponding to a position of the first magnet; a plurality of antenna contacts attached to the second PCB along an periphery of the second PCB, adjacent to an periphery adjacent to the second magnet among periphery of the third surface perpendicular to the folding shaft, spaced apart from each other; and a hall sensor, mounted on the second PCB, spaced apart from each of the plurality of antenna contacts, spaced apart from the second magnet.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a block diagram of an electronic device in a network environment according to certain embodiments.
- (2) FIG. 2A illustrates an example of an unfolding state of an electronic device according to an embodiment.
- (3) FIG. 2B illustrates an example of a completely folding state of an electronic device according to an embodiment.
- (4) FIG. 2C is an expanded view of an electronic device according to an embodiment.
- (5) FIG. 3A illustrates an example of a positional relationship between a first housing and a second housing in an unfolding state of an electronic device according to an embodiment.
- (6) FIG. 3B illustrates an example of positional relationships between the first housing and the second housing in a folding state of the electronic device according to an embodiment.
- (7) FIG. 4 is a simplified block diagram of an electronic device according to an embodiment.
- (8) FIG. 5 is a top view and a bottom view of an electronic device in an unfolding state including a hall sensor in a first housing according to an embodiment.
- (9) FIG. 6A is a top view and a bottom view of an electronic device in a folding state, according to an embodiment.
- (10) FIG. 6B is a top view of the electronic device of FIG. 5 from which a flexible display panel is removed, according to an embodiment.
- (11) FIGS. 6C and 6D are bottom views of the electronic device of FIG. 5 from which the display panel and the rear plate are removed, according to an embodiment.
- (12) FIG. 7A is a top view of an electronic device indicating an area A of FIG. 6B according to an embodiment.
- (13) FIG. 7B is a bottom view of an electronic device indicating area A of FIG. 6B according to an embodiment.
- (14) FIG. 7C illustrates an example of a positional relationship between magnets in an electronic device according to an embodiment.
- (15) FIG. 8 is a section view taken along line A-A' of FIG. 7B.
- (16) FIG. 9 is a section view taken along line B-B' of FIG. 7B.
- (17) FIG. 10 illustrates an example of candidate positions of a hall sensor in an electronic device according to an embodiment.
- (18) FIG. 11 illustrates an example of a layer in a PCB on which a hall sensor in an electronic device is mounted, according to an embodiment.
- (19) FIG. 12 is a bottom view of an electronic device in an unfolding state in which a display panel and a rear plate are removed, including a hall sensor in a second housing according to an embodiment.
- (20) FIG. 13 is a bottom view of an electronic device illustrating area A of FIG. 12, according to an

embodiment.

DETAILED DESCRIPTION

(21) FIG. 1 is a block diagram illustrating an electronic device **101** in a network environment **100** according to certain embodiments. Referring to FIG. 1, the electronic device **101** in the network environment **100** may communicate with an electronic device **102** via a first network **198** (e.g., a short-range wireless communication network), or at least one of an electronic device **104** or a server **108** via a second network **199** (e.g., a long-range wireless communication network). According to an embodiment, the electronic device **101** may communicate with the electronic device **104** via the server **108**. According to an embodiment, the electronic device **101** may include a processor **120**, memory **130**, an input module **150**, a sound output module **155**, a display module **160**, an audio module **170**, a sensor module **176**, an interface **177**, a connecting terminal **178**, a haptic module **179**, a camera module **180**, a power management module **188**, a battery **189**, a communication module **190**, a subscriber identification module (SIM) **196**, or an antenna module **197**. In some embodiments, at least one of the components (e.g., the connecting terminal **178**) may be omitted from the electronic device **101**, or one or more other components may be added in the electronic device **101**. In some embodiments, some of the components (e.g., the sensor module **176**, the camera module **180**, or the antenna module **197**) may be implemented as a single component (e.g., the display module **160**).

(22) The processor **120** may execute, for example, software (e.g., a program **140**) to control at least one other component (e.g., a hardware or software component) of the electronic device **101** coupled with the processor **120**, and may perform various data processing or computation. According to an embodiment, as at least part of the data processing or computation, the processor **120** may store a command or data received from another component (e.g., the sensor module **176** or the communication module **190**) in volatile memory **132**, process the command or the data stored in the volatile memory **132**, and store resulting data in non-volatile memory **134**. According to an embodiment, the processor **120** may include a main processor **121** (e.g., a central processing unit (CPU) or an application processor (AP)), or an auxiliary processor **123** (e.g., a graphics processing unit (GPU), a neural processing unit (NPU), an image signal processor (ISP), a sensor hub processor, or a communication processor (CP)) that is operable independently from, or in conjunction with, the main processor **121**. For example, when the electronic device **101** includes the main processor **121** and the auxiliary processor **123**, the auxiliary processor **123** may be adapted to consume less power than the main processor **121**, or to be specific to a specified function. The auxiliary processor **123** may be implemented as separate from, or as part of the main processor **121**.

(23) The auxiliary processor **123** may control at least some of functions or states related to at least one component (e.g., the display module **160**, the sensor module **176**, or the communication module **190**) among the components of the electronic device **101**, instead of the main processor **121** while the main processor **121** is in an inactive (e.g., sleep) state, or together with the main processor **121** while the main processor **121** is in an active state (e.g., executing an application). According to an embodiment, the auxiliary processor **123** (e.g., an image signal processor or a communication processor) may be implemented as part of another component (e.g., the camera module **180** or the communication module **190**) functionally related to the auxiliary processor **123**. According to an embodiment, the auxiliary processor **123** (e.g., the neural processing unit) may include a hardware structure specified for artificial intelligence model processing. An artificial intelligence model may be generated by machine learning. Such learning may be performed, e.g., by the electronic device **101** where the artificial intelligence is performed or via a separate server (e.g., the server **108**). Learning algorithms may include, but are not limited to, e.g., supervised learning, unsupervised learning, semi-supervised learning, or reinforcement learning. The artificial intelligence model may include a plurality of artificial neural network layers. The artificial neural network may be a deep neural network (DNN), a convolutional neural network (CNN), a recurrent

neural network (RNN), a restricted Boltzmann machine (RBM), a deep belief network (DBN), a bidirectional recurrent deep neural network (BRDNN), deep Q-network or a combination of two or more thereof but is not limited thereto. The artificial intelligence model may, additionally or alternatively, include a software structure other than the hardware structure.

(24) The memory **130** may store various data used by at least one component (e.g., the processor **120** or the sensor module **176**) of the electronic device **101**. The various data may include, for example, software (e.g., the program **140**) and input data or output data for a command related thereto. The memory **130** may include the volatile memory **132** or the non-volatile memory **134**.

(25) The program **140** may be stored in the memory **130** as software, and may include, for example, an operating system (OS) **142**, middleware **144**, or an application **146**.

(26) The input module **150** may receive a command or data to be used by another component (e.g., the processor **120**) of the electronic device **101**, from the outside (e.g., a user) of the electronic device **101**. The input module **150** may include, for example, a microphone, a mouse, a keyboard, a key (e.g., a button), or a digital pen (e.g., a stylus pen).

(27) The sound output module **155** may output sound signals to the outside of the electronic device **101**. The sound output module **155** may include, for example, a speaker or a receiver. The speaker may be used for general purposes, such as playing multimedia or playing record. The receiver may be used for receiving incoming calls. According to an embodiment, the receiver may be implemented as separate from, or as part of the speaker.

(28) The display module **160** may visually provide information to the outside (e.g., a user) of the electronic device **101**. The display module **160** may include, for example, a display, a hologram device, or a projector and control circuitry to control a corresponding one of the display, hologram device, and projector. According to an embodiment, the display module **160** may include a touch sensor adapted to detect a touch, or a pressure sensor adapted to measure the intensity of force incurred by the touch.

(29) The audio module **170** may convert a sound into an electrical signal and vice versa. According to an embodiment, the audio module **170** may obtain the sound via the input module **150**, or output the sound via the sound output module **155** or a headphone of an external electronic device (e.g., an electronic device **102**) directly (e.g., wiredly) or wirelessly coupled with the electronic device **101**.

(30) The sensor module **176** may detect an operational state (e.g., power or temperature) of the electronic device **101** or an environmental state (e.g., a state of a user) external to the electronic device **101**, and then generate an electrical signal or data value corresponding to the detected state. According to an embodiment, the sensor module **176** may include, for example, a gesture sensor, a gyro sensor, an atmospheric pressure sensor, a magnetic sensor, an acceleration sensor, a grip sensor, a proximity sensor, a color sensor, an infrared (IR) sensor, a biometric sensor, a temperature sensor, a humidity sensor, or an illuminance sensor.

(31) The interface **177** may support one or more specified protocols to be used for the electronic device **101** to be coupled with the external electronic device (e.g., the electronic device **102**) directly (e.g., wiredly) or wirelessly. According to an embodiment, the interface **177** may include, for example, a high definition multimedia interface (HDMI), a universal serial bus (USB) interface, a secure digital (SD) card interface, or an audio interface.

(32) A connecting terminal **178** may include a connector via which the electronic device **101** may be physically connected with the external electronic device (e.g., the electronic device **102**). According to an embodiment, the connecting terminal **178** may include, for example, a HDMI connector, a USB connector, a SD card connector, or an audio connector (e.g., a headphone connector).

(33) The haptic module **179** may convert an electrical signal into a mechanical stimulus (e.g., a vibration or a movement) or electrical stimulus which may be recognized by a user via his tactile sensation or kinesthetic sensation. According to an embodiment, the haptic module **179** may include, for example, a motor, a piezoelectric element, or an electric stimulator.

(34) The camera module **180** may capture a still image or moving images. According to an embodiment, the camera module **180** may include one or more lenses, image sensors, image signal processors, or flashes.

(35) The power management module **188** may manage power supplied to the electronic device **101**. According to an embodiment, the power management module **188** may be implemented as at least part of, for example, a power management integrated circuit (PMIC).

(36) The battery **189** may supply power to at least one component of the electronic device **101**. According to an embodiment, the battery **189** may include, for example, a primary cell which is not rechargeable, a secondary cell which is rechargeable, or a fuel cell.

(37) The communication module **190** may support establishing a direct (e.g., wired) communication channel or a wireless communication channel between the electronic device **101** and the external electronic device (e.g., the electronic device **102**, the electronic device **104**, or the server **108**) and performing communication via the established communication channel. The communication module **190** may include one or more communication processors that are operable independently from the processor **120** (e.g., the application processor (AP)) and supports a direct (e.g., wired) communication or a wireless communication. According to an embodiment, the communication module **190** may include a wireless communication module **192** (e.g., a cellular communication module, a short-range wireless communication module, or a global navigation satellite system (GNSS) communication module) or a wired communication module **194** (e.g., a local area network (LAN) communication module or a power line communication (PLC) module). A corresponding one of these communication modules may communicate with the external electronic device via the first network **198** (e.g., a short-range communication network, such as Bluetooth™, wireless-fidelity (Wi-Fi) direct, or infrared data association (IrDA)) or the second network **199** (e.g., a long-range communication network, such as a legacy cellular network, a 5G network, a next-generation communication network, the Internet, or a computer network (e.g., LAN or wide area network (WAN))). These various types of communication modules may be implemented as a single component (e.g., a single chip), or may be implemented as multi components (e.g., multi chips) separate from each other. The wireless communication module **192** may identify and authenticate the electronic device **101** in a communication network, such as the first network **198** or the second network **199**, using subscriber information (e.g., international mobile subscriber identity (IMSI)) stored in the subscriber identification module **196**.

(38) The wireless communication module **192** may support a 5G network, after a 4G network, and next-generation communication technology, e.g., new radio (NR) access technology. The NR access technology may support enhanced mobile broadband (eMBB), massive machine type communications (mMTC), or ultra-reliable and low-latency communications (URLLC). The wireless communication module **192** may support a high-frequency band (e.g., the mmWave band) to achieve, e.g., a high data transmission rate. The wireless communication module **192** may support various technologies for securing performance on a high-frequency band, such as, e.g., beamforming, massive multiple-input and multiple-output (massive MIMO), full dimensional MIMO (FD-MIMO), array antenna, analog beam-forming, or large scale antenna. The wireless communication module **192** may support various requirements specified in the electronic device **101**, an external electronic device (e.g., the electronic device **104**), or a network system (e.g., the second network **199**). According to an embodiment, the wireless communication module **192** may support a peak data rate (e.g., 20 Gbps or more) for implementing eMBB, loss coverage (e.g., 164 dB or less) for implementing mMTC, or U-plane latency (e.g., 0.5 ms or less for each of downlink (DL) and uplink (UL), or a round trip of 1 ms or less) for implementing URLLC.

(39) The antenna module **197** may transmit or receive a signal or power to or from the outside (e.g., the external electronic device) of the electronic device **101**. According to an embodiment, the antenna module **197** may include an antenna including a radiating element composed of a conductive material or a conductive pattern formed in or on a substrate (e.g., a printed circuit board

(PCB)). According to an embodiment, the antenna module **197** may include a plurality of antennas (e.g., array antennas). In such a case, at least one antenna appropriate for a communication scheme used in the communication network, such as the first network **198** or the second network **199**, may be selected, for example, by the communication module **190** (e.g., the wireless communication module **192**) from the plurality of antennas. The signal or the power may then be transmitted or received between the communication module **190** and the external electronic device via the selected at least one antenna. According to an embodiment, another component (e.g., a radio frequency integrated circuit (RFIC)) other than the radiating element may be additionally formed as part of the antenna module **197**.

(40) According to various embodiments, the antenna module **197** may form a mmWave antenna module. According to an embodiment, the mmWave antenna module may include a printed circuit board, a RFIC disposed on a first surface (e.g., the bottom surface) of the printed circuit board, or adjacent to the first surface and capable of supporting a designated high-frequency band (e.g., the mmWave band), and a plurality of antennas (e.g., array antennas) disposed on a second surface (e.g., the top or a side surface) of the printed circuit board, or adjacent to the second surface and capable of transmitting or receiving signals of the designated high-frequency band.

(41) At least some of the above-described components may be coupled mutually and communicate signals (e.g., commands or data) therebetween via an inter-peripheral communication scheme (e.g., a bus, general purpose input and output (GPIO), serial peripheral interface (SPI), or mobile industry processor interface (MIPI)).

(42) According to an embodiment, commands or data may be transmitted or received between the electronic device **101** and the external electronic device **104** via the server **108** coupled with the second network **199**. Each of the electronic devices **102** or **104** may be a device of a same type as, or a different type, from the electronic device **101**. According to an embodiment, all or some of operations to be executed at the electronic device **101** may be executed at one or more of the external electronic devices **102**, **104**, or **108**. For example, if the electronic device **101** should perform a function or a service automatically, or in response to a request from a user or another device, the electronic device **101**, instead of, or in addition to, executing the function or the service, may request the one or more external electronic devices to perform at least part of the function or the service. The one or more external electronic devices receiving the request may perform the at least part of the function or the service requested, or an additional function or an additional service related to the request, and transfer an outcome of the performing to the electronic device **101**. The electronic device **101** may provide the outcome, with or without further processing of the outcome, as at least part of a reply to the request. To that end, a cloud computing, distributed computing, mobile edge computing (MEC), or client-server computing technology may be used, for example. The electronic device **101** may provide ultra low-latency services using, e.g., distributed computing or mobile edge computing. In another embodiment, the external electronic device **104** may include an internet-of-things (IoT) device. The server **108** may be an intelligent server using machine learning and/or a neural network. According to an embodiment, the external electronic device **104** or the server **108** may be included in the second network **199**. The electronic device **101** may be applied to intelligent services (e.g., smart home, smart city, smart car, or healthcare) based on 5G communication technology or IoT-related technology.

(43) FIG. 2A illustrates an example of an unfolding state of an electronic device according to an embodiment.

(44) FIG. 2B illustrates an example of a completely folding state of an electronic device according to an embodiment.

(45) FIG. 2C is an expanded view of an electronic device according to an embodiment.

(46) FIG. 3A illustrates an example of a positional relationship between a first housing and a second housing in an unfolding state of an electronic device according to an embodiment.

(47) FIG. 3B illustrates an example of positional relationships between the first housing and the

second housing in a folding state of the electronic device according to an embodiment.

(48) Referring to FIGS. 2A, 2B, and 2C, the electronic device **101** may include a first housing **210**, a second housing **220**, a flexible display panel **230**, and a folding housing **265** (shown in FIG. 2B).
(49) In an embodiment, the first housing **210** may include a first surface **211**, a second surface **212** faced away the first surface **211**, and a first side surface **213** surrounding at least a portion of the first surface **211** and the second surface **212**. In an embodiment, the second surface **212** may further include at least one camera module **234** exposed through a portion of the second surface **212**. In an embodiment, the first housing **210** may include a first protective member **214** disposed along at least some of the periphery of the first surface **211**. In an embodiment, the first protective member **214** may prevent the inflow of foreign substances (e.g., dust or moisture) through an interval between the flexible display panel **230** and the first housing **210**. In an embodiment, the first protective member **214** may be attached to the first side **213** of the first housing **210**. In an embodiment, the first protective member **214** may be integrally formed with the first side surface **213**. In an embodiment, the first housing **210** may provide a space formed by the first surface **211**, the second surface **212**, and the first side surface **213** as a space for mounting components of the electronic device **101**. In an embodiment, the first side surface **213** may include a plurality of conductive members **226**, a plurality of non-conductive members **227**, or a combination thereof. For example, the plurality of conductive members **226** may include a conductive member **226-1**, a conductive member **226-2**, a conductive member **226-3**, a conductive member **226-4**, a conductive member **226-5**, and a conductive member **226-7**, spaced apart from each other and A plurality of non-conductive members **227** may include a non-conductive member **227-1**, a non-conductive member **227-2**, a non-conductive member **227-3**, a non-conductive member **227-4**, a non-conductive member **227-5**, and a non-conductive member **227-6**, spaced apart from each other. However, it is not limited thereto.

(50) In an embodiment, the second housing **220** may include a third surface **221**, a fourth surface **222** faced away the third surface **221**, and a second side surface **223** surrounding at least a portion of the third surface **221** and the fourth surface **222**. In an embodiment, the fourth surface **222** may further include a display panel **235** disposed on the fourth surface **222**. In an embodiment, the second housing **220** may include a second protective member **224** disposed along at least a portion of edges of the third surface **221**. In an embodiment, the second protective member **224** may prevent the inflow of foreign substances (e.g., dust or moisture) through an interval between the flexible display panel **230** and the second housing **220**. In an embodiment, the second protective member **224** may be attached to the second side **223** of the first housing **220**. In an embodiment, the second protective member **224** may be integrally formed with the second side surface **223**. In an embodiment, the second housing **220** may provide a space formed by the third surface **221**, the fourth surface **222**, and the second side surface **223** as a space for mounting components of the electronic device **101**. In an embodiment, the second side surface **223** may include a plurality of conductive members **228**, a plurality of non-conductive members **229**, or a combination thereof. For example, the plurality of conductive members **228** may include a conductive member **228-1**, a conductive member **228-2**, a conductive member **228-3**, a conductive member **228-4**, a conductive member **228-5**, a conductive member **228-6**, and a conductive member **228-7** spaced apart from each other and a plurality of non-conductive members (**229**) may include a non-conductive member (**229-1**), a non-conductive member (**229-2**), a non-conductive member (**229-3**), a non-conductive member (**229-4**), and a non-conductive member (**229-6**) spaced apart from each other. However, it is not limited thereto.

(51) In an embodiment, at least a portion of a plurality of conductive members **226**, at least a portion of a plurality of conductive members **228**, at least a portion of a plurality of non-conductive members **227**, at least a portion of a plurality of non-conductive members **229**, or a combination thereof may form at least one antenna structure.

(52) In an embodiment, the second side surface **223** may be rotatably connected to the first side

surface **213** through a hinge structure **260** (shown in FIG. 2C) mounted in the folding housing **265**. In an embodiment, the hinge structure **260** may include hinge modules **262**, a first hinge plate **266**, and a second hinge plate **267**. In an embodiment, the first hinge plate **266** may be connected to the first housing **210**, and the second hinge plate **267** may be connected to the second housing **220**.

(53) In an embodiment, the flexible display panel **230** may include a window exposed toward the outside. In an embodiment, the window may be used to protect the flexible display panel **230**. In an embodiment, since the window is implemented using a transparent member, the image displayed on the flexible display panel **230** may be viewable outside the electronic device **101** through the window. In an embodiment, the window may include a glass material such as ultra-thin glass (UTG) or a polymer material such as polyimide (PI). In an embodiment, the flexible display panel **230** may be disposed on the first surface **211** of the first housing **210** and the third surface **221** of the second housing **220** across the folding housing **265** and include a first display area **231** corresponding to the first surface **211**, a second display area **232** corresponding to the third surface **221**, and a third display area **233** between the first display area **231** and the second display area **232** within the front surface of the flexible display panel **230**. In an embodiment, the first display area **231** may be disposed on at least a part of the first surface **211**, and the second display area **232** may be disposed on the third surface **221**.

(54) In one configuration, a part of the display area (e.g., the first display area **231**, the second display area **232**, or the third display area **233**) of the flexible display panel **230** may include at least one recess or at least one opening. In one configuration, the at least one recess or the at least one opening may not be included in the flexible display panel **230**, but may be covered by the flexible display panel **230** and included in a support member (e.g., bracket) supporting the flexible display panel **230**. In an embodiment, the electronic device **101** may include at least one component for obtaining data from the outside of the electronic device **101** through the at least one recess or the at least one opening. For example, the at least one component may include at least one of a camera **236** or a sensor module **238** disposed in the first display area **231**. In an embodiment, at least one of the camera **236** and the sensor module **238** may be disposed below the rear surface of the first display area **231**. In an embodiment, at least one of the camera **236** or the sensor module **238** may be wrapped by the flexible display panel **230**. In one configuration, at least one of the camera **236** or the sensor module **238** wrapped by the flexible display panel **230** may not be exposed to the outside. However, it is not limited thereto.

(55) Meanwhile, although not illustrated in FIGS. 2a and 2b, in an embodiment, the flexible display panel **230** may further include a rear surface opposite to the front surface. In an embodiment, the flexible display panel **230** may be supported by the first support member **270** of the first housing **210** and the second support member **280** of the second housing **220**.

(56) In an embodiment, the folding housing **265** may be configured to form a first housing **210** and form a first support member **270** and a second housing **220** fastened to the first hinge plate **266** and pivotably connect the second support member **280** coupled to the second hinge plate **267**. In an embodiment, the folding housing **265** may be at least partially exposed between the first housing **210** and the second housing **220** while the electronic device **101** is in a folding state defined in the following description. In an embodiment, the folding housing **265** may be covered by the first housing **210** and the second housing **220** while the electronic device **101** is in an unfolding state defined in the following description.

(57) In an embodiment, the electronic device **101** may be folded based on the axis **237** passing through the folding housing **265**. For example, the folding housing **265** may be disposed between the first housing **210** and the second housing **220** of the electronic device **101** to allow the electronic device **101** to be bent, curved, or folded. For example, the first housing **210** may be connected to the second housing **220** through a hinge structure **260** mounted in the folding housing **265** and may rotate about an axis **237**. For example, the hinge structure **260** may include hinge modules **262** disposed at both ends of the first hinge plate **266** and the second hinge plate **267**. In

an embodiment, the hinge modules **262** may include hinge gears interdigitated therein. In an embodiment, the first hinge plate **266** and the second hinge plate **267** may rotate about an axis **237** through the hinge gears. In an embodiment, the electronic device **101** may be folded so that the first housing **210** and the second housing **220** face each other by rotating about the axis **237**. In an embodiment, the electronic device **101** may be folded so that the first housing **210** and the second housing **220** be laid over or overlap each other. The axis **237** may be referred to as a folding axis in terms of a reference for folding the electronic device **101**.

(58) In an embodiment, the electronic device **101** may include a plurality of components in a space formed by the first housing **210**, the second housing **220**, the flexible display panel **230**, and the folding housing **265**. For example, referring to FIG. 2c, the electronic device **101** may include a first support member **270**, a second support member **280**, a hinge structure **260** surrounded by a folding housing **265**, flexible display panel **230**, printed circuit boards (PCB) **250**, batteries **255**, a folding housing **265**, an antenna **285**, display panel **235** and a rear plate **290**. According to embodiments, at least some of the plurality of components may not be included in the electronic device **101**.

(59) In an embodiment, the hinge structure **260** may include hinge modules **262**, a first hinge plate **266**, and a second hinge plate **267**. In an embodiment, the hinge modules **262** may include hinge gears that pivotably connect the first hinge plate **266** and the second hinge plate **267**. The hinge gears are engaged with each other to rotate, thereby rotating the first hinge plate **266** and the second hinge plate **267**.

(60) In an embodiment, the first hinge plate **266** may be coupled to the first support member **270** of the first housing **210**, and the second hinge plate **267** may be coupled to the second support member **280** of the second housing **220**. The first housing **210** and the second housing **220** may be rotated by at least one rotation of the first hinge plate **266** or the second hinge plate **267**.

(61) In an embodiment, the first housing **210** may include a first support member **270**, and the second housing **220** may include a second support member **280**. In an embodiment, at least a portion of the first support member **270** may be surrounded by the first side surface **213**, and at least a portion of the second support member **280** may be surrounded by the second side surface **223**. In an embodiment, the first support member **270** may be integrally formed with the first side surface **213**, and the second support member **280** may be integrally formed with the second side surface **223**. In an embodiment, the first support member **270** may be a separate component distinguished from the first side surface **213**, and the second support member **280** may be a separate component distinguished from the second side surface **223**. In an embodiment, the first side surface **213** and the second side surface **223** may be formed of a metal material, a non-metal material, or a combination thereof. In an embodiment, at least a portion of the first side surface **213** and at least a portion of the second side surface **223** may be used as at least one antenna structure.

(62) The first support member **270** may be coupled to the flexible display panel **230** on at least a portion of one surface of the first support member **270**, and may be coupled to the rear plate **290** on at least a portion of the other surface of the first support member **270**. The second support member **280** may be coupled to the flexible display panel **230** in at least a portion of one surface of the second support member **280** and may be coupled to the display panel **235** on the other surface of the second support member **280**.

(63) In an embodiment, printed circuit boards **250** and a battery **255** may be included between a surface formed by the first support member **270** and the second support member **280** and a surface formed by the display panel **235** and the rear plate **290**. The PCBs **250** may include a first PCB disposed in the first support member **270**, and a second PCB disposed in the second support member **280** and spaced apart from the first PCB. The first PCB and the second PCB may be connected to each other through at least one FPCB **253**. The shape of the first PCB may be distinguished from the shape of the second PCB according to the internal shape of the electronic device **101**. In an embodiment, the PCBs **250** may mount at least a portion of a processor, memory,

or interface.

(64) In an embodiment, the batteries **255** may be used to provide power to at least one component of the electronic device **101**. In an embodiment, the batteries **255** may be rechargeable. In an embodiment, at least some of the batteries **255** may be disposed on substantially the same plane as the plane defined by the PCBs **250**. For example, the PCBs **250** and the batteries **255** may be disposed on the second surface **212** and fourth surface **222**, unlike the flexible display panels **230** disposed on the first surfaces **211** and third surfaces **221**. In an embodiment, the PCBs **250** and the batteries **255** may be supported by at least a portion of the first support member **270** and at least a portion of the second support member **280**.

(65) In an embodiment, the antenna **285** may be disposed between the rear plate **290** and the battery supported by at least a part of the first support member **270** of the batteries **255**. For example, the antenna **285** may include a near field communication (NFC) antenna, a wireless charging antenna, and/or a magnetic secure transmission (MST) antenna. For example, antenna **285** may perform short-range communication with an external device or wirelessly transmit and receive power utilized for charging. However, it is not limited thereto.

(66) In an embodiment, the electronic device **101** may provide an unfolding state in which the first housing **210** and the second housing **220** are fully folded out by the folding housing **265**. For example, referring to FIG. **3A**, the electronic device **101** may be in the unfolding state **300**. In an embodiment, the state **300** may mean a state in which the first direction **301** facing the first surface **211** corresponds to the second direction **302** facing the third surface **221**. For example, in the state **300**, the first direction **301** may be parallel to the second direction **302**. For example, in the state **300**, the first direction **301** may be the same as the second direction **302**. In an embodiment, the first surface **211** may form substantially one plane with the third surface **221** in the state **300**. In an embodiment, an angle **303** between the first surface **211** and the third surface **221** in the state **300** may be 180 degrees. In an embodiment, the state **300** may mean a state in which all of the entire display area of the flexible display panel **230** may be provided on substantially one plane. For example, the state **300** may mean a state in which all of the first display area **231**, the second display area **232**, and the third display area **233** can be provided on one plane. For example, in the state **300**, the third display area **233** may not include a curved surface. In an embodiment, the unfolding state may be referred to as an outspread state or an outspreading state.

(67) In an embodiment, the electronic device **101** may provide a folding state in which the first housing **210** and the second housing **220** are folded in by the folding housing **265**. For example, referring to FIG. **3B**, the electronic device **101** may be in the folding state including a state **310**, a state **320**, and a state **330**. In an embodiment, the folding state including the state **310**, the state **320**, and the state **330** may mean a state in which the first direction **301** facing the first surface **211** is distinguished from the second direction **302** facing the third surface **221**. For example, in state **310**, an angle between the first direction **301** and the second direction **302** may be 45 degrees, and the first direction **301** and the second direction **302** may be distinguished from each other; and in the state **320**, an angle between the first direction **301** and the second direction **302** is 90 degrees, and the first direction **301** and the second direction **302** are distinguished from each other; and in state **330**, an angle between the first direction **301** and the second direction **302** may be substantially 180 degrees, and the first direction **301** and the second direction **302** may be distinguished from each other. In an embodiment, an angle between the first surface **211** and the third surface **221** in the folding state may be greater than or equal to 0 degrees and less than 180 degrees. For example, in state **310**, the angle **313** between the first surface **211** and the third surface **221** may be 135 degrees, and in state **320**, the angle **323** between the first surface **211** and the third surface **221** may be 90 degrees, and in state **330**, the angle **333** between the first surface **211** and the third surface **221** may be substantially 0 degrees. In an embodiment, the folding state may be referred to as a folding state.

(68) In an embodiment, the folding state may include a plurality of sub-folding states, unlike the unfolding state. For example, referring to FIG. **3B**, the folding state may include a fully folding

state **330** in which the first surface **211** substantially overlaps the third surface **221** by rotation provided through the folding housing **265** and the intermediate folding state **310** between the state **330** and the unfolding state (e.g., the state **300** of FIG. **3A**) and the plurality of sub-folding states including the state **320**. For example, the electronic device **101** may provide a state **330** in which the entire area of the first display area **231** substantially completely overlaps the entire area of the second display area **232** as the first surfaces **211** and third surfaces **221** face each other by the folding housing **265**. For example, the electronic device **101** may provide a state **330** in which the first direction **301** is substantially opposite to the second direction **302**. As another example, the state **330** may mean a state in which the flexible display panel **230** is covered in the view of the user who is looking at the electronic device **101**. However, it is not limited thereto.

(69) In an embodiment, the flexible display panel **230** may be bent by rotation provided through the folding housing **265**. For example, in the flexible display panel **230**, unlike the first display area **231** and the second display area **232**, the third display area **233** may be bent according to a folding operation. For example, the third display area **233** may be in a curved state to prevent damage to the flexible display panel **230** within the fully folding state. In the fully folding state, unlike the third display area **233** being curved, the entire first display area **231** may completely overlap the entire second display area **232**.

(70) Meanwhile, FIGS. **2A**, **2B**, **2C**, **3A**, and **3B** illustrate an example in which the flexible display panel **230** of the electronic device **101** includes one folding display area (e.g., the third display area **233**) or the electronic device **101** includes one folding housing (e.g., the folding housing **265**), but this is for convenience of explanation. According to embodiments, the flexible display panel **230** of the electronic device **101** may include a plurality of folding display areas. For example, the flexible display panel **230** of the electronic device **101** may include two or more folding display areas, and the electronic device **101** may include two or more folding housings for providing each of the two or more folding areas.

(71) FIG. **4** is a simplified block diagram of an electronic device according to an embodiment. The block diagram may indicate a functional configuration of the electronic device **101** shown in each of FIGS. **1** and **2A**, **2B**, **2C**, **3A**, and **3B**.

(72) According to an embodiment, FIG. **5** is a top view and a bottom view of an electronic device in an unfolding state including a hall sensor in a first housing.

(73) FIG. **6A** is a top view and a bottom view of an electronic device in a folding state, according to an embodiment.

(74) FIG. **6B** is a top view of the electronic device of FIG. **5** from which a flexible display panel is removed, according to an embodiment.

(75) FIGS. **6C** and **6D** are bottom views of the electronic device of FIG. **5** from which the display panel and the rear plate are removed, according to an embodiment.

(76) FIG. **7A** is a top view of an electronic device indicating an area A of FIG. **6B** according to an embodiment.

(77) FIG. **7B** is a bottom view of an electronic device indicating area A of FIG. **6B** according to an embodiment.

(78) FIG. **7C** illustrates an example of a positional relationship between magnets in an electronic device according to an embodiment.

(79) FIG. **8** is a section view cut along line A-A' of FIG. **7B**.

(80) FIG. **9** is a section view taken along line B-B' of FIG. **7B**.

(81) FIG. **10** illustrates an example of candidate positions of a hall sensor in an electronic device according to an embodiment.

(82) FIG. **11** illustrates an example of a layer in a PCB on which a hall sensor in an electronic device is mounted, according to an embodiment.

(83) FIG. **12** is a bottom view of an electronic device in an unfolding state in which a display panel and a rear plate are removed, including a hall sensor in a second housing according to an

embodiment.

(84) FIG. 13 is a bottom view of an electronic device illustrating area A of FIG. 12, according to an embodiment.

(85) Referring to FIG. 4, the electronic device **101** may include a processor **120**, a flexible display panel **230**, an electromagnetic induction panel **401**, and a hall sensor **455**.

(86) In an embodiment, the processor **120** may include the processor **120** illustrated in FIG. 1. In an embodiment, the processor **120** may be operatively or operably coupled with or connected with the flexible display panel **230**. In an embodiment, the processor **120** may be operatively coupled or connected with the electromagnetic induction panel **401**. In an embodiment, the processor **120** may be operatively coupled or connected with the hall sensor **455**. For example, the processor **120** may include the sensor hub processor operatively coupled with the hall sensor **455** and defined through the description of FIG. 1. For example, the processor **120** may include the application processor operatively coupled with the hall sensor **455** and defined through the description of FIG. 1. However, it is not limited thereto.

(87) In an embodiment, the flexible display panel **230** may include the display module **160** shown in FIG. 1. In an embodiment, flexible display panel **230** may be used to display an image obtained by processor **120** or an image obtained by display driving circuit. For example, the flexible display panel **230** may be used to display the image on at least one of the first display area **231**, the second display area **232**, or the third display area **233** under the control of the display driving circuit. However, it is not limited thereto.

(88) In an embodiment, the flexible display panel **230** may include at least one of a cover panel (C-panel) for protecting the flexible display panel **230**, A base substrate, a thin film transistors (TFT) layer formed on the base substrate, a pixel layer (or an organic light emitting layer) including pixels that emit light based on a voltage applied from the thin film transistor layer, or a polarizing layer disposed on the pixel layer. The flexible display panel **230** may further include any suitable components such as a thin film encapsulation layer (TFE) for encapsulating the pixel layer and a back film for supporting the base substrate. In an embodiment, the base substrate may be formed of a polymer material (e.g., polyimide (PI), etc.) to ensure flexibility of the substrate, but is not limited thereto. In an embodiment, the substrate may include at least one of polyethylene terephthalate, polymethyl methacrylate, polyamide, polyimide, polypropylene, and polyurethane. In an embodiment, the substrate may be formed of a plurality of layers. In an embodiment, the polarizing layer may enhance the clarity of an image displayed through the flexible display panel **230** by imparting directionality to light emitted from the flexible display panel **230** (e.g., pixel layer). In an embodiment, the flexible display panel **230** may further include a window disposed on the polarization layer. In some embodiments, the flexible display panel **230** may not include the polarization layer. For example, when the flexible display panel **230** does not include the polarization layer, the flexible display panel **230** may further include a color filter layer for enhancing the color purity and a black matrix layer (BM) for preventing light reflection on the thin film encapsulation layer to enhance visibility, or may further include the color filter layer and a black pixel define layer (PDL).

(89) In an embodiment, the electromagnetic induction panel **401** (e.g., digitizer) may be used to receive a touch input from the stylus pen through interworking with a stylus pen including a coil. For example, the electromagnetic induction panel **401** may receive a touch input from the stylus pen based on an exchange of an electromagnetic signal with the stylus pen located within a specified distance from the electromagnetic induction panel **401** (or flexible display panel **230**). In an embodiment, the electromagnetic induction panel **401** may be disposed under the flexible display panel **230**. In an embodiment, the electromagnetic induction panel **401** may be spaced apart from the first area and the first area under the first display area **231** and may be formed in a second area under the second display area **232**. For example, a space between the first area of the electromagnetic induction panel **401** and the second area of the electromagnetic induction panel

401 may be defined under at least a part of the third display area **233**. However, it is not limited thereto. According to embodiments, the electromagnetic induction panel **401** may not be included in the electronic device **101**.

(90) In an embodiment, the hall sensor **455** may be used to identify whether the electronic device **101** is in the unfolding state (e.g., state **300**) or in the folding state (e.g., state **330**). For example, the processor **120** may obtain at least one of data on a magnetic field from a first magnet in the first housing **210** or data on a magnetic field from a second magnet in the second housing **220** through the hall sensor **455**. In an embodiment, the first magnet may be disposed along a portion of the periphery of the first housing **210** parallel to the axis **237** spaced apart from the axis **237** and the second magnet may be disposed at a position corresponding to the position of the first magnet. In an embodiment, the first magnet may be disposed along a portion of a periphery spaced from and perpendicular to axis **237** and the second magnet may be disposed at a position corresponding to the position of the first magnet. In an embodiment, the first magnet may be disposed in a corner area spaced apart from the axis **237** among the corner areas of the first surface **211** of the first housing **210**, the second magnet may be disposed at a position corresponding to the position of the first magnet.

(91) For example, referring to FIG. 5, within a state **500** (e.g., the unfolding state) in which the first surface **211** and the third surface **221** form one plane, the magnet **501** which is the first magnet disposed under the first display area **231** may be disposed within the corner area **503** spaced apart from the axis **237** among the corner area **503** of the first surface **211**, the corner area **504**, the corner area **505**, and the corner area **506**; and the magnet **502**, which is the second magnet disposed under the second display area **232**, may be disposed in the corner area **507** of the third surface **221** corresponding to the corner area **503** of the first surface **211**, and corner area **508** of the third surface **221** corresponding to the corner area **504** of the first surface **211**, corner area **509** of the third surface **221** corresponding to the corner area **505** of the first surface **211**, and the corner area **506** of the third surface **221**. For example, within a state **550** (e.g., the unfolding state) in which the second surface **212** and the fourth surface **222** form one plane, the magnet **501** is disposed within the corner area **553** of the second surface **212** among the corner areas **553** of the second surface **212** corresponding to the corner areas **503** of the first surface **211**, the corner area **554** of the second surface **212** corresponding to the corner area **504** of the first surface **211**, the corner area **555** of the second surface **212** corresponding to the corner area **505** of the first surface **211**, and the corner area **556** of the second surface **211** corresponding to the corner area **506** of the first surface **211**; and the magnet **502** may be disposed in the corner region **557** of the fourth surface **222** among the corner region **557** of the fourth surface **222** corresponding to the corner region **553** of the second surface **212**, the corner region **558** of the fourth surface **222** corresponding to the corner region **554** of the second surface **212**, the corner region **559** of the fourth surface **222** corresponding to the corner region **555** of the second surface **212** and the corner region **560** of the fourth surface **222** corresponding to the corner region **556** of the second surface **212**.

(92) For example, referring to FIG. 6A, when looking at the fourth surface **222** in the state **600** (e.g., the fully folding state) in which at least a portion of the third surface **221** substantially overlaps on at least a portion of the first surface **211**, the magnet **501** and the magnet **502** may be disposed within the corner region **557** of the fourth surface **222**; and when looking at the second surface **212** in the state **650** (e.g., the fully folding state) in which at least a portion of the first surface **211** substantially overlaps at least a portion of the third surface **221**, the magnet **501** and the magnet **502** may be disposed in the corner region **553** of the second face **212**.

(93) Although not illustrated in FIGS. 5 and 6A, in an embodiment, the magnet **501** may be disposed along at least a part of an edge **526** spaced apart from the axis **237** among edges of the first surface **211** parallel to the axis **237**, and the magnet **502** may be disposed at a position corresponding to the position of the magnet **501**. For example, the magnet **501** may be disposed along at least a portion of the edge **526** between the magnets **521** and the corner region **503** to be

described later, and the magnet **502** may be disposed along the edge **527** between the magnets **522** and the corner region **507** to be described later and at a position corresponding to the position of the magnet **501**. In an embodiment, the magnet **501** may be disposed in the corner region **505** (or the corner region **555** of the second surface **212**), and the magnet **502** may be disposed in the corner region **509** (or the corner region **559** of the fourth surface **221**) corresponding to the corner region **505** of the first surface **211**.

(94) Referring back to FIG. **4**, the hall sensor **455** may be related to the first magnet and the second magnet among a plurality of magnets included in the electronic device **101**. For example, the electronic device **101** may further include not only the first magnet and the second magnet, but also other magnets distinguished from the first magnet and the second magnet. In an embodiment, positions of the other magnets may be different from positions of the first magnet and positions of the second magnet. For example, referring to FIGS. **5** and **6A**, unlike magnets **501** and **502** disposed in the corner region **503** and the corner region **507** respectively, some of the other magnets **521** may be disposed along edges **526** of the first surface **211** (or edges **528** of the second surface **212**) spaced apart from the axis **237** among edges of the first surface **211** parallel to the axis **237**; and unlike the magnet **501** and the magnet **502**, magnets **522** disposed at positions corresponding to the positions of the magnets **521** may be disposed along edges **527** (or edges **529** of the fourth surface **222**) of the third surface **221** corresponding to edges **526** of the first surface **211**. For example, the magnets **521** may be disposed between the battery in the first housing **210** of the batteries **255** and the edge **526**, the magnets **522** may be disposed between the battery in the second housing **220** of the batteries **255** and the edge **527**. In an embodiment, the magnets **521** may be disposed such that a magnetic field from the magnets **521** does not affect the performance of at least one camera module **234**. For example, the magnets **521** may be spaced apart from at least one camera module **234** so that the magnetic field does not affect the performance of at least one camera module **234**. For example, the magnets **521** spaced apart from at least one camera **234** may be closer to the edge **531** of the second surface **212** than the edge **530** of the second surface **212** adjacent (e.g., or proximate) to the at least one camera module **234**. Meanwhile, the positions of the magnets **522** may correspond to the positions of the magnets **521**. However, it is not limited thereto.

(95) In an embodiment, each of a magnet array including a magnet **501** and a magnet **502** and a magnet array including magnets **521** and **522**, may be included in the electronic device **101** to maintain the fully folding state. For example, in order to maintain the fully folding state through an attractive magnetic force between the magnet **501** and the magnet **502** within the fully folding state, the polarity of the surface of the magnet **501** facing the magnet **502** in the completely folding state may be opposite to the polarity of the surface of the magnet **502** facing the magnet **501**. For example, when the pole of the surface of the magnet **501** facing the magnet **502** in the fully folding state is N pole, the pole of the surface of the magnet **502** facing the magnet **501** in the fully folding state may be S pole. Meanwhile, when the pole of the surface of the magnet **501** facing the magnet **502** in the completely folding state is the N pole, the pole of the other surface of the magnet **501** facing the surface of the magnet **501** may be the S pole, and the other surface of the magnet **502** facing the surface of the magnet **502** may be the N pole. For example, in order to maintain the fully folding state through attractive magnetic force between magnets **521** and **522** in the fully folding state, some polarities of magnets **522** facing parts of magnets **521** in the fully folding state may be opposite to those of magnets **521**. In an embodiment, the attractive force between the magnets **521** and **522** may be greater than the attractive force between the magnets **501** and **502**. However, it is not limited thereto.

(96) In one configuration, when viewed from above with the electronic device **101** in the unfolding state in which the flexible display panel **230** is removed, each of the magnet **501** and the magnets **521** may be exposed, and when the electronic device **101** in the unfolding state in which the display panel **235** and the rear plate **290** are removed is viewed from the top, covered by the first support

member **270**; When the electronic device **101** in the unfolding state from which the flexible display panel **230** is removed is viewed from above, each of the magnets **502** and **522** may be exposed, and when the electronic device **101** in the unfolding state from which the display panel **235** and the rear plate **290** are removed is viewed from the top, each of the same may be covered by the second support member **280**. For example, referring to FIG. **6B**, each of the magnet **501** and the magnets **521** is supported by a recess formed on the first support member **270** and is exposed to an exterior environment when viewed from above; and each of the magnets **502** and **522** may be supported by a recess formed on the second support member **280** and may be exposed to the outside when viewed from above. The polarity (e.g., N pole) of the surface of the magnet **501** facing the magnet **502** in the fully folding state may be opposite to the polarity (e.g., S pole) of the surface of the magnet **502** facing the magnet **501** in the fully folding state. The polarity of some of the magnets **521** facing some parts of the magnets **522** in the fully folding state may be opposite to the polarity of some of the magnets **522** in the fully folding state, the polarity of the other portion of the magnets **521** in contact with the portion of the magnets **521** may be opposite to the polarity of the portion of the magnets **521**, the polarity of the other portion of magnets **522** in contact with the portion of magnets **522** may be opposite to the polarity of the portion of magnets **522**. Meanwhile, the hall sensor **455** may be disposed adjacent (e.g., or proximate) to the magnet **501** of the magnets **502**, the magnets **521**, and the magnets **522** within the unfolding state, and may be covered by the first support member **270**. For example, referring to FIG. **6C**, each of the magnet **501** and the magnets **521** is formed on the first support member **270**, supported by a recess facing the first surface **211**, and covered by a surface of the first support member **270** facing the second surface **212** when viewed from above; and each of the magnets **502** and **522** may be formed on the second support member **280**, supported by a recess facing the third surface **221**, and covered by a surface of the second support member **280** facing the fourth surface **222** when viewed from above. Meanwhile, the hall sensor **455** may be adjacent (e.g., or proximate) to the magnet **501** among the magnet **501**, the magnets **502**, the magnets **521**, and the magnets **522** within the unfolding state; and covered by a surface of the first PCB in the first housing **210** to which at least one camera module **234** is attached.

(97) In an embodiment, each of magnet **501**, magnet **502**, magnets **521**, and the magnets **522** may be disposed so as to be exposed when the electronic device **101** in the unfolding state with the display panel **235** and the rear plate **290** removed is viewed from above. For example, referring to FIG. **6D**, each of the magnet **501** and the magnets **521** may be formed on the first support member **270** and supported by a recess facing the second surface **212** and is exposed to the outside when viewed from above; and each of the magnets **502** and **522** may be formed on the second support member **280** and supported by a recess facing the fourth surface **222** and exposed toward the outside when viewed from above. Meanwhile, the hall sensor **455** may be disposed adjacent (e.g., or proximate) to the magnet **501** of the magnets **502**, the magnets **521**, and the magnets **522** within the unfolding state and covered by a surface of the first PCB in the first housing **210** to which at least one camera module **234** is attached.

(98) Referring back to FIG. **4**, in an embodiment, the hall sensor **455** may be more adjacent (e.g., or proximate) to the first magnet than some of the other magnets in the first housing **210**. For example, since the first PCB on which the hall sensor **455** is mounted includes an area closer to the first magnet than some of the other magnets, the hall sensor **455** may be closer to the first magnet than some of the other magnets. For example, referring to FIGS. **5** and **6**, the hall sensor **455** may be closer to the magnet **501** than the magnets **521**.

(99) Referring back to FIG. **4**, in an embodiment, the hall sensor **455** disposed under the first display area **231** may be spaced apart from at least one camera module **234**. For example, at least one camera module **234** may include a camera module including a magnet causing a magnetic field that changes according to a photographing (or shooting) state (or the state of movement of at least one camera module **234**). For example, the magnet may be included in the camera module, which

is a wide-angle camera module, for optical image stabilization (OIS) function. For example, the magnet may be included in the camera module for enabling an auto focus function. However, it is not limited thereto. In an embodiment, the hall sensor **455** spaced apart from the camera module may be disposed at a position spaced apart from the magnetic field that changes according to the photographing state (or the moving state of the camera module). For example, the hall sensor **455** spaced apart from the camera module may be disposed at a position capable of identifying whether the state of the electronic device **101** is in the unfolding state or the folding state (e.g., the fully folding state) regardless of whether the magnetic field is changed. For example, referring to FIGS. **7A**, **7B**, and **8**, the hall sensor **455** may be mounted on a surface **703** (shown in FIGS. **7A** and **8**) of the first PCB faced away a surface **702** (shown in FIGS. **7B** and **8**) of the first PCB (e.g., the first PCB) in the first housing **210** to which the camera module **701** is attached in order to allow the hall sensor **455** to be spaced apart from the camera module **701** (e.g., a wide-angle camera module) which is the camera module included in at least one camera module **234**. In an embodiment, the hall sensor **455** spaced apart from the camera module **701** may be mounted on the surface **703** of the first PCB between the edge **704** (shown in FIG. **7A**) (or an edge **705** (shown in FIG. **7B**) adjacent (e.g., or proximate) to the magnet **501** among edges of the second surface **212** of the first housing **210** perpendicular to the axis **237**) adjacent (e.g., or proximate) to the magnet **501** and the camera module **701** among edges of the first surface **211** of the first housing **210** perpendicular to the axis **237**. In an embodiment, the hall sensor **455** disposed under the flexible display panel **230** may be disposed on a surface **703** that is disposed under the flexible display panel **230** (shown in FIG. **8**), adjacent (e.g., or proximate) to the magnet **501** supported by the first support member **270** (shown in FIG. **8**) in the first housing **210**, and faced away from the surface **702** on which the camera module **701** is disposed. In an embodiment, the distance **706** (shown in FIGS. **7A** and **7B**) between a part of the camera module **701** and a part of the hall sensor **455** may be set in consideration of a range in which a magnetic field from at least one magnet **801** in the camera module **701** for providing OIS is changed according to the photographing state or the movement state of the camera module **701**. In an embodiment, the distance **706** may be set to identify through the hall sensor **455** whether the state of the electronic device **101** is in the unfolding state or the folding state (e.g., the fully folding state), regardless of whether the magnetic field is changed. For example, the distance **706** may be set to be 20 mm or more. However, it is not limited thereto.

(100) Referring back to FIG. **4**, in an embodiment, at least one camera module **234** may further include another camera module that is distinguished from the camera module. For example, unlike the camera module, the other camera module may not include a magnet (e.g., a magnet for providing OIS) causing a magnetic field that changes according to a photographing state of the other camera (or a moving state of the other camera module). In other words, only the camera module among the camera module and the other camera module may include the magnet causing a magnetic field that changes according to a photographing state (or a movement state of the camera module). Since the other camera module does not include the magnet, the other camera module may not affect the hall sensor **455** used to identify whether the state of the electronic device **101** is in the unfolding state or the folding state (e.g., the fully folding state). As another example, the other camera module may include a magnet causing a magnetic field having a smaller change than a change in the magnetic field caused by the magnet in the camera module. Since the magnet in the other camera module causes a change in a magnetic field relatively smaller than that of the magnet in the camera module, the other camera module may not affect the hall sensor **455** used to identify whether the electronic device **101** is in the unfolding state or the folding state (e.g., the fully folding state). However, it is not limited thereto. In an embodiment, the hall sensor **455** may be disposed closer to the other camera module than the camera module. For example, referring to FIGS. **7A** and **7B**, the hall sensor **455** may be closer to a camera module **707** that is another camera module and is an ultra-wide camera module than the camera module **701**. For example, the camera module **707** may be positioned between the hall sensor **455** and the camera module **701**. For example, the

distance **708** (shown in FIGS. 7A and 7B) between the hall sensor **455** and the camera module **707** may be shorter than the distance **706**. However, it is not limited thereto.

(101) Meanwhile, referring back to FIG. 4, because identifying whether the electronic device **101** is in the unfolding state or in the folding state (e.g., the fully folding state) via the hall sensor **455** utilizes a difference between data on the magnetic field obtained through the hall sensor **455** in the unfolding state and data on the magnetic field obtained through the hall sensor **455** in the folding state, the relative positional relationship between magnets used to identify the state of the electronic device **101** may need to be changed with respect to the hall sensor **455** according to the state of the electronic device **101**. Since the first magnet and the second magnet change depending on whether the state of the electronic device **101** is in the unfolding state or the folding state (e.g., the fully folding state), they may be used to identify the state of the electronic device **101** through the hall sensor **455**. For example, referring to FIG. 7C, since a relative positional relationship between the first magnet **501** and the second magnet **502** in the unfolding state is distinguished from a relative positional relationship between the magnet **501** and the magnet **502** in the folding state, the magnet **501** and the magnet **502** may be used to identify the state of the electronic device **101** through the hall sensor **455**. Meanwhile, since the relative positional relationship between the magnet **501** and the hall sensor **455** is independently maintained from the change in the state of the electronic device **101**, and the relative positional relationship between the magnet **502** and the hall sensor **455** is changed according to the change in the state of the electronic device **101**, the state of the electronic device **101** may be identified based on a change in a relative position between the magnet **501** and the magnet **502** according to the state of the electronic device **101** and based on a change in a magnetic field caused based on a change in a relative position between the hall sensor **455** and the magnet **502** according to a state of the electronic device **101** through the hall sensor **455**.

(102) Referring back to FIG. 4, Identifying a difference between the magnetic field caused by the first magnet and the second magnet in the unfolding state and the magnetic field in the folding state (e.g., the fully folding state) may be utilized to identify whether the electronic device **101** is in the unfolding state or in the folding state (e.g., the fully folding state) using the hall sensor **455**. In an embodiment, the Hall sensor **455** may be spaced more than a certain distance from the first magnet to identify the difference. For example, when the hall sensor **455** is disposed too close to the first magnet, the difference in the magnetic field may not be identified by the hall sensor **455** due to the first magnet, and thus the hall sensor **455** may be spaced apart from the first magnet by a certain distance or more. For example, referring to FIGS. 7A and 7B, the hall sensor **455** may be spaced apart from the magnet **501**. For example, a distance **709** between a portion of the hall sensor **455** and a portion of the magnet **501** may be set to a length capable of identifying a difference in the magnetic field through the hall sensor **455**. For example, the length may be 4 mm (millimeter). However, it is not limited thereto.

(103) Referring back to FIG. 4, in an embodiment, illustrated in FIG. 2, the hall sensor **455**, as shown in FIG. 2, may be spaced apart from at least one component of the electronic device **101** electrically connected to At least a part of a plurality of conductive members **226**, at least a part of a plurality of conductive members **228**, at least a part of a plurality of non-conductive members **227**, and at least a part of a plurality of non-conductive members **229**, at least one antenna structure or formed by a combination thereof. In an embodiment, the at least one component may include a plurality of antenna contacts (or a plurality of antenna connectors) electrically connected to the at least one antenna structure. In an embodiment, at least one electrical path extending from the hall sensor **455** for connection with components (e.g., the processor **120** shown in FIG. 1) of the electronic device **101** may be spaced apart from an electrical path connecting each of the plurality of antenna contacts to a communication module (e.g., communication module **190**) of the electronic device **101**. For example, referring to FIGS. 7A, 7B, and 9, the hall sensor **455** may be spaced apart from each of the antenna contact **711-2** and the antenna contact **711-3** in order to

prevent or reduce malfunction of the hall sensor **455** caused by the antenna structure, which is in contact with the antenna contact **711-2** and the antenna contact **711-3** and is formed by the conductive member **226-3**. The hall sensor **455** may be spaced apart from the antenna contact **711-1** in order to prevent or reduce malfunction of the hall sensor **455** caused by the antenna structure, which is in contact with the antenna contact **711-1** and is formed by the conductive member **226-4** electrically separated from the conductive member **226-3** by the non-conductive member **227-3**. Each of a plurality of antenna contacts **711** including an antenna contact **711-1**, an antenna contact **711-2**, and an antenna contact **711-3** may be disposed on the surface **702** of the first PCB facing the surface **703** of the first PCB in the first housing **210** in which the hall sensor **455** is disposed.

(104) For example, the hall sensor **455** may be spaced apart from the antenna contact **710** to prevent or reduce malfunction of the hall sensor **455** caused by the antenna structure, which is in contact with the antenna contact **710** and formed by the conductive member **226-3**. In an embodiment, the antenna contact **710** may be adjacent (e.g., or proximate) to an edge **526** spaced apart from the axis **237** among edges of the first surface **211** parallel to the axis **237**. In an embodiment, the antenna contact **710** may protrude from the surface **703** of the first PCB. In an embodiment, the antenna contact **710** may be configured with a C-clip protruding from the surface **703** of the first PCB. The antenna contact **710** implemented using the C-clip may be electrically coupled to the conductive member **226-3** physically connected to the upper surface of the C-clip. Since the C-clip is implemented using an elastic body, the electrical coupling between the conductive member **226-3** and the antenna contact **710** may be maintained by the elastic force of the C-clip. The antenna contact **710** implemented using the C-clip may electrically connect the antenna structure to the ground. However, it is not limited thereto.

(105) For example, the hall sensor **455** may be spaced apart from each of the antenna contact **711-2** and the antenna contact **711-3** in order to prevent or reduce interference of signals received through the antenna contact **711-2** and the antenna contact **711-3** connected to the antenna structure formed by the conductive member **226-3** from the external electronic device; and spaced apart from the antenna contact **711-1** in order to prevent or reduce interference of a signal received from an external electronic device through an antenna contact **711-1** connected to an antenna structure formed by the conductive member **226-4** electrically separated from the conductive member **226-3** by the non-conductive member **227-3**. Each of a plurality of antenna contacts **711** including an antenna contact **711-1**, an antenna contact **711-2**, and an antenna contact **711-3** may be disposed on the surface **702** of the first PCB facing the surface **703** of the first PCB in the first housing **210** in which the hall sensor **455** is disposed.

(106) For example, the hall sensor **455** may be spaced apart from the antenna contact **710** to prevent or reduce interference with a signal received through the antenna contact **710** connected to the antenna structure formed by the conductive member **226-3**. The antenna contact **710** may be disposed on the surface **703** of the first PCB in the first housing **210** on which the hall sensor **455** is disposed. In an embodiment, the antenna contact **710** may connect the antenna structure with a communication module of the electronic device **101**.

(107) Although not illustrated in FIGS. 7A, 7B, and 9, the hall sensor **455** may be electrically separated or spaced apart from an electrical path from each of the antenna connectors **710** or a plurality of antenna contacts **711** in order to prevent or reduce interference with a signal provided to the communication module of the electronic device **101** through an electrical path from each of the antenna contacts **710** or a plurality of antenna contacts **711**. For example, the hall sensor **455** may be disposed at a position capable of electrically separating the electrical path extending from the hall sensor **455** from each of the antenna contacts **710** or a plurality of antenna contacts **711**.

(108) Referring back to FIG. 4, at least one component of the electronic device **101** protruding from one surface of the first PCB in the first housing **210** may be pressed by the at least one other component of the electronic device **101** to form an electrical connection (or electrical coupling) with at least one other component of the electronic device **101**. When the hall sensor **455** is

disposed at a position corresponding to a position of the at least one component on the other surface of the first PCB opposite from the one surface of the first PCB on which the at least one component is disposed, the hall sensor **455** may be disposed within a position within the other surface of the first PCB, which is distinguished from a position within the one surface of the first PCB on which the at least one component of the electronic device **101** is disposed, Since the hall sensor **455** may be affected by a force caused by pressing the at least one component of the electronic device **101** by the at least one other component of the electronic device **101**. For example, the hall sensor **455** may be located within a position where the influence from the force is reduced. In an embodiment, the hall sensor **455** disposed on the other surface of the first PCB may be disposed at a position located within an area within the one surface of the first PCB on which the hall sensor **455** is mounted and protruding from the first PCB and distinguished from positions at which a plurality of antenna contacts is disposed. For example, referring to FIGS. **7A**, **7B**, and **9**, the hall sensor **455** may be disposed at a position on the surface **703** of the first PCB, which is distinguished from a position where each of the plurality of antenna contacts **711** coupled on the surface **702** of the first PCB on which the hall sensor **455** is mounted. In an embodiment, each of the plurality of antenna contacts **711** may be contacted to the first PCB along an edge **712** of the first PCB adjacent (e.g., or proximate) to an edge **704** (shown in FIG. **7A**) adjacent (e.g., or proximate) to a magnet **501** among edges of the first surface **211** of the first housing **210** perpendicular to the axis **237** or adjacent (e.g., or proximate) to an edge **705** (shown in FIG. **7B**) adjacent (e.g., or proximate) to the magnet **501** among edges of the second surface **212** of the first housing **210** perpendicular to the axis **237**. In an embodiment, a plurality of antenna contacts **711** may be spaced apart from each other. In an embodiment, each of a plurality of antenna contacts **711** may be a component that electrically connects the at least one antenna structure to the communication module (e.g., the wireless communication module **192** shown in FIG. **1**) of the electronic device **101** by physically contacting at least one the antenna structure formed by at least a portion of a plurality of conductive members **226**, at least a portion of a plurality of non-conductive members **227**, or combinations thereof; and electrically connects the ground to the at least one antenna structure. For example, the antenna contacts **711-1** may electrically connect the antenna structure formed by the conductive member **226-4** to the communication module by physically contacting the antenna structure formed by the conductive member **226-4** and each of the antenna contact **711-2** and the antenna contact **711-3** may electrically connect the antenna structure formed by the conductive member **226-3** to the communication module by physically contacting the antenna structure formed by the conductive member **226-3** electrically separated from the conductive member **226-4** by the non-conductive member **227-3**. In an embodiment, the antenna contact **711-1** may electrically connect the antenna structure formed by the conductive member **226-4** to the ground and each of the antenna contact **711-2** and the antenna contact **711-3** may electrically connect the antenna structure formed by the conductive member **226-3** electrically separated from the conductive member **226-4** by the non-conductive member **227-3** to the ground. In an embodiment, each of a plurality of antenna contacts **711** may protrude from the surface **702** (see FIGS. **7B** and **9**) of the first PCB. In an embodiment, the Hall sensor **455** may be disposed at a location on the surface **703** of the first PCB that is distinct from a location on the surface **702** of the first PCB where each of the plurality of antenna contacts **711** is disposed to prevent force caused by pressing each of a plurality of antenna contacts **711** protruding from the surface **702** of the first PCB from being transmitted to the hall sensor **455**. In an embodiment, the hall sensor **455** may be disposed between an edge of the camera module **701** closest to the edge **712** of the first PCB and parallel to the edge **712** of the first PCB and a plurality of antenna contacts **711**.

(109) Referring back to FIG. **4**, the hall sensor **455** may be disposed at a position where a difference between the first value for indicating the magnitude of the magnetic flux density obtained through the hall sensor **455** within a position that does not cause a decrease in the performance of the at least one component and the unfolding state and the second value for

indicating the magnitude of the magnetic flux density obtained through the hall sensor **455** in the folding state (e.g., the complete folding state) is greater than a reference value, as well as a position on the first PCB in which an impact caused by the pressing of at least one component of the electronic device **101** disposed around the hall sensor **455** is transmitted to be less than a reference size. For example, referring to FIG. **10**, considering the remaining mounting space on the first PCB and the distance between the camera module **701** (not shown in FIG. **10**) and the hall sensor **455** (e.g., distance **706** (shown within FIGS. **7A** and **7B**)), the hall sensor **455** may be disposed at a candidate position **1001** on the surface **703** of the first PCB, a candidate position **1002** on the surface **703** of the first PCB, a candidate position **1003** on the surface **703** of the first PCB, and a candidate position **1004** on the surface **703** of the first PCB, a candidate position **1005** on the surface **702** of the first PCB, or a candidate position **1006** on the surface **702** of the first PCB. (110) For example, when the hall sensor **455** is disposed on the candidate position **1001** on the surface **703** of the first PCB, since the hall sensor **455** is adjacent (e.g., or proximate) to the magnet **501**, a difference between the first value and the second value obtained through the hall sensor **455** may be smaller than the reference value. Since the difference between the first value and the second value is smaller than the reference value, it may be inappropriate to identify whether the electronic device **101** is in the unfolding state or in the folding state (e.g., in the fully folding state) through the hall sensor **455** disposed on the candidate position **1001** on the surface **703** of the first PCB.

(111) For another example, when the hall sensor **455** is disposed on the candidate position **1002** on the surface **703** of the first PCB, since the hall sensor **455** faces at least a portion of the antenna contact **710** protruding from the surface **702** of the first PCB through the first PCB, the hall sensor **455** disposed on the candidate position **1002** on the surface **703** of the first PCB may be affected by a force caused by the antenna contact **710** being pressed to form an electrical coupling with other components of the electronic device **101**. Since the hall sensor **455** may be damaged by force (e.g., an impact), it may be inappropriate to dispose the hall sensor **455** on the candidate position **1002** on the surface **703** of the first PCB.

(112) As another example, since the candidate position **1003** on the surface **703** of the first PCB is a position where an electrical path from the antenna contact **710** passes within the first PCB, when the hall sensor **455** is disposed on the candidate position **1003** on the surface **703** of the first PCB, performance of the antenna structure may be degraded. Due to the potential decrease in performance, it may be inappropriate to arrange the hall sensor **455** on the candidate position **1003** on the surface **703** of the first PCB.

(113) For another example, when the hall sensor **455** is disposed on the candidate position **1004** on the surface **703** of the first PCB, a difference between the first value and the second value obtained through the hall sensor **455** may be smaller than the reference value. Since the difference between the first value and the second value is smaller than the reference value, it may be inappropriate to identify whether the electronic device **101** is in the unfolding state or in the folding state (e.g., in the fully folding state), when the hall sensor **455** disposed on the candidate position **1004** on the surface **703** of the first PCB.

(114) For another example, since the candidate position **1005** on the surface **702** of the first PCB is a position through which an electrical path for the antenna contact **710** passes, at least one wiring in the first PCB connected to the hall sensor **455** disposed on the candidate position **1005** on the surface **702** of the first PCB may degrade performance of the antenna structure. Due to the potential decrease in performance, it may be inappropriate to arrange the hall sensor **455** on the candidate position **1005** on the surface **702** of the first PCB. Meanwhile, the surface **702** of the first PCB may include a connection part **1010-1** and a connection part **1010-2** on the first PCB connecting the antenna contact **711-3**, a connection part **1010-3** and a connection part **1010-4** on the first PCB connecting the antenna contact **711-2**, and a connection portion **1010-5** on the first PCB connecting the antenna contact **711-1**.

(115) As another example, since the candidate position **1006** on the surface **702** of the first PCB is spaced apart from each of a plurality of antenna contacts **711** and from the antenna contact **710** and from an electrical path for a signal provided to the communication module of the electronic device **101** through the antenna contact **710**, and from an electrical path for a signal provided to the communication module of the electronic device **101** through each of a plurality of antenna contacts **711**, the hall sensor **455** disposed on the candidate position **1006** on the surface **702** of the first PCB may not affect the performance of at least one antenna structure connected to each of the plurality of antenna contacts **711** and the antenna contact **710**. For example, the hall sensor **455** disposed on the candidate position **1006** on the surface **702** of the first PCB may prevent or reduce interference with a signal provided to the communication module through the at least one antenna structure connected to each of a plurality of antenna contacts **711** and antenna contacts **710**. Since the difference between the first value obtained through the hole sensor **455** disposed on the candidate position **1006** on the surface **702** of the first PCB in the unfolding state and the second value obtained through the hole sensor **455** disposed on the candidate position **1006** on the surface **702** of the first PCB in the folding state (e.g., the fully folding state) is greater than the reference value, the hall sensor **455** disposed on the candidate position **1006** on the surface **702** of the first PCB may be used to identify whether the state of the electronic device **101** is in the unfolding state or in the folding state (e.g., the fully folding state).

(116) Referring back to FIG. 4, the performance of the hall sensor **455**, as used to identify whether the state of the electronic device **101** is the unfolding state or the folding state (e.g., the fully folding state), may be degraded by one or more components (e.g., wiring for the power signal among power signals and control signals generated in the electronic device **101**) of the electronic device **101** that generate magnetic force drift, are located around the hall sensor **455**, and shield another magnetic body located around the hall sensor **455** and/or a magnetic force (e.g., magnetic force caused by the first magnet and the second magnet) located around the hall sensor **455** and directed toward the hall sensor **455**. In an embodiment, in order to prevent a degradation in performance of the hall sensor **455**, the hall sensor **455** may be spaced apart from components of the electronic device **101** that cause the magnetic force drift, the other magnetic body, and components of the electronic device **101** shielding the magnetic force toward the hall sensor **455**.

(117) In an embodiment, to prevent a degradation in performance of the hall sensor **455** used to identify whether the state of the electronic device **101** is in the unfolding state or the folding state (e.g., the fully folding state), a partial region of the first PCB located around the hall sensor **455** may include at least one layer including a non-electric material. For example, referring to FIG. 11, in an embodiment, at least one layer in a partial region **1101** of the first PCB positioned between the hall sensor **455** mounted on the surface **702** of the first PCB and the antenna contact **710** may include a non-electric material. For example, a partial region **1101** of the first PCB may include a fill cut region (or an ungrounded region). At least one layer in a partial region **1102** of the first PCB positioned between the hall sensor **455** mounted on the surface **702** of the first PCB and a plurality of antenna contacts **711** may include a non-electric material. For example, a partial region **1102** of the first PCB may include a fill cut region (or an ungrounded region). However, it is not limited thereto.

(118) Although not illustrated in FIGS. 5 to 11 (FIG. 5, 6A, 6B, 6C, 6D, 7A, 7B, 7C, 8, 9, 10, 11), in an embodiment, the hall sensor **455** may relate to magnets **521** (shown in FIGS. 5 and 6A to 6D) and magnets **522** (shown in FIGS. 5A to 6D). In an embodiment, when the hall sensor **455** is related to the magnets **521** and **522** and mounted within the first housing **210**, the hall sensor **455** may be spaced apart from the magnets **521** and adjacent (e.g., or proximate) to the magnets **521**. In an embodiment, the hall sensor **455** adjacent (e.g., or proximate) to the magnets **521** may be spaced apart from at least one antenna contact electrically coupled to the antenna structure formed by the conductive member **226-2**. In an embodiment, the hall sensor **455** adjacent (e.g., or proximate) to the magnets **521** may be spaced apart from at least one antenna contact, which is electrically

separated from the antenna structure formed by the conductive member **226-2** by the non-conductive member **227-1** and electrically coupled to the antenna structure formed by the conductive member **226-1**. However, it is not limited thereto.

(119) Referring back to FIG. **4**, in an embodiment, the hall sensor **455** may be included in the second housing **22** including the display panel **235** exposed through a part of the fourth surface **222** instead of the first housing **210** including at least one camera module **234** exposed through a portion of the second surface **212**. In an embodiment, the hall sensor **455** in the second housing **220** may be adjacent (e.g., or proximate) to the second magnet in the second housing **220** and may be spaced apart from the second magnet.

(120) For example, referring to FIG. **12**, the hall sensor **455** may be mounted on the surface **1201** of the second PCB in the second housing **220** facing the fourth surface **222** (shown in FIG. **2A**). In one configuration, the hall sensor **455** mounted on the surface **1201** of the second PCB may be supported by a recess in the second support member **280** and may be adjacent (e.g., or proximate) to the magnet **502** exposed when the electronic device **101** removed the display panel **235** is viewed from the top, and may be spaced apart from the magnet **502**. In an embodiment, the magnet **501** may be disposed at a position corresponding to the position of the magnet **502**, and may be exposed when the electronic device **101** from which the display panel **235** is removed is viewed from above. In an embodiment, the hall sensor **455** mounted on the surface **1201** of the second PCB may be supported by a recess in the second support member **280** and spaced apart from the magnets **522** disposed along the edge of the second housing **220** parallel to the axis **237**. For example, the distance between the hall sensor **455** and the magnet **502** may be shorter than the distance between the hall sensor **455** and the magnets **522**. In one configuration, the magnets **521** may be disposed at positions corresponding to the positions of the magnets **522**, and may be exposed when the electronic device **101** from which the display panel **235** is removed is viewed from above. According to embodiments, the magnet **501**, the magnet **502**, the magnets **521**, and the magnets **522** may be disposed as shown in FIG. **6C**. Meanwhile, although not shown in FIGS. **12** and **13**, according to embodiments, the hall sensor **455** may be mounted on the other surface of the second PCB that is separated while facing the surface **1201** of the second PCB.

(121) In an embodiment, the hall sensor **455** may be disposed between the edge adjacent (e.g., or proximate) to the magnet **502** among edges of the second housing **220** perpendicular to the axis **237** and at least one camera module projected (reflected, or mirrored) onto the second housing **220** when the state of the electronic device **101** is in the fully folding state.

(122) In an embodiment, the Hall sensor **455** may be spaced apart from each of the plurality of antenna contacts **1211** disposed along at least some of the edges of the second PCB. For example, referring to FIG. **13**, The hall sensor **455** may be spaced apart from the antenna contact **1211-1**, which is electrically connected, in contact with the antenna structure formed by the conductive member **228-4**. For example, the hall sensor **455** may be spaced apart from each of the antenna contact **1211-2** and the antenna contact **1211-3**, which may be electrically connected, in contact with an antenna structure formed by the conductive member **228-3** electrically separated from the conductive member **228-4** by a non-conductive member **229-3**. In an embodiment, a plurality of antenna contacts **1211** may have the same or similar functions as the functions of a plurality of antenna contacts **711** described above. In an embodiment, a plurality of antenna contacts **1211** may be disposed along an edge closest to the hall sensor **455** from among edges of the second housing **220** perpendicular to the axis **237**. In an embodiment, a plurality of antenna contacts **1211** may be disposed on the surface **1201** of the second PCB on which the hall sensor **455** is disposed.

Although not shown in FIGS. **12** and **13**, the plurality of antenna contacts **1211** may be disposed on the other surface of the second PCB facing and separated from the surface **1201** of the second PCB on which the Hall sensor **455** is disposed. In other words, the hall sensor **455** may be disposed on a surface of the second PCB that is in contact with a plurality of antenna contacts **1211**, or may be disposed on a surface opposite to a surface of the second PCB in contact with a plurality of antenna

contacts **1211**.

(123) Meanwhile, although not shown in FIGS. **12** and **13**, an antenna contact that is in contact with the antenna structure formed by the conductive member **228-3** and is electrically connected may be disposed along an edge spaced apart from the axis **237** among edges of the second housing **220** parallel to the axis **237**. The hall sensor **455** may be spaced apart from the antenna contact. In an embodiment, the antenna contact may have the same or similar function as the function of the antenna contact **710** described above. In an embodiment, the antenna contact may be disposed on the surface **1201** of the second PCB. In an embodiment, the antenna contact may be disposed on another surface of the second PCB opposite to the surface **1201** of the second PCB. In other words, the hall sensor **455** may be disposed on a surface of the second PCB in contact with the antenna contact, or may be disposed on a surface opposite to a surface of the second PCB in contact with the antenna contact.

(124) Meanwhile, although not illustrated in FIGS. **12** and **13**, a partial region of the second PCB positioned around the hall sensor **455** may include at least one layer including a non-dielectric material to prevent a decrease in performance of the hall sensor **455**. For example, at least one layer in a partial region of the second PCB positioned between the hall sensor **455** mounted on the surface **1201** (or a surface opposite to the surface **1201** of the second PCB) of the second PCB and a plurality of antenna contacts **1211** may include a non-electric material. For example, at least one layer in a partial region of the second PCB positioned between the hall sensor **455** mounted on the surface **1201** (or a surface opposite to the surface **1201** of the second PCB) of the second PCB and the antenna contact may include a non-dielectric material. For example, the partial region of the second PCB may include a fill cut region (or an ungrounded region). However, it is not limited thereto.

(125) Referring back to FIG. **4**, using the hall sensor **455** illustrated through FIGS. **5** to **13** and descriptions thereof, processor **120** may obtain data on magnetic flux density from the first magnet and the second magnet, and based on the data, may identify whether electronic device **101** is in the unfolding state or in the folding state (e.g., the fully folding state).

(126) In an embodiment, processor **120** may identify a change in magnetic flux density in a direction parallel to axis **237** from the data, and may identify whether electronic device **101** is in the unfolding state or in the folding state based on the identified change. In an embodiment, processor **120** may identify a change in magnetic flux density in a direction perpendicular to axis **237** from the data, and may identify whether electronic device **101** is in the unfolding state or in the folding state based on the identified change. In an embodiment, the processor **120** may identify a change in magnetic flux density from the data in a first direction facing the first surface **211** of the first housing **210** or in a second direction opposite to the first direction and may identify whether the electronic device **101** is in the unfolding state or in the folding state based on the identified change. However, it is not limited thereto.

(127) In an embodiment, processor **120** may identify whether the state of electronic device **101** is switched from the unfolding state by comparing the data with the first reference data while the state of the electronic device **101** is in the unfolding state, and may identify whether the state of the electronic device **101** is switched from the complete folding state by comparing the data with the second reference data distinguished from the first reference data while the state of the electronic device **101** is in the folding state. Since a relative positional relationship between the first magnet and the second magnet in the unfolding state is different from a relative positional relationship between the first magnet and the second magnet in the fully folding state, the processor **120** may identify the transition of the state of the electronic device **101** using the first reference data while the electronic device **101** is in the unfolding state and may identify the transition of the state of the electronic device **101** using the second reference data while the electronic device **101** is in the fully folding state. However, it is not limited thereto.

(128) In an embodiment, when an angle between the first surface **211** of the first housing **210** and

the third surface **221** of the second housing **220** may be identified through the hall sensor **455** based on a change in magnetic flux density caused by the first magnet and the second magnet, the processor **120** may identify an angle between the first surface **211** of the first housing **210** and the third surface **221** of the second housing **220** by comparing the data with the third reference data while the state of the electronic device **101** is switched from the unfolding state, and may identify an angle between the first surface **211** of the first housing **210** and the third surface **221** of the second housing **220** by comparing the data with fourth reference data distinguished from the third reference data while the state of the electronic device **101** is switched from the full folding state. For example, since a distribution of a change that changes according to the transition from the unfolding state to the fully folding state in magnetic flux density caused by the first magnet and the second magnet and a distribution of a change that changes according to the transition from the fully folding state to the unfolding state in magnetic flux density may be different from each other, the processor **120** may identify an angle between the first surface **211** of the first housing **210** and the third surface **221** of the second housing **220** using the third reference data while the state of the electronic device **101** is switched from the unfolding state, and may identify an angle between the first surface **211** of the first housing **210** and the third surface **221** of the second housing **220** using the fourth reference data while the state of the electronic device **101** is switched from the fully folding state. However, it is not limited thereto.

(129) In an embodiment, the processor **120** may correct the data obtained through the hall sensor **455** and identify whether the state of the electronic device **101** is the unfolding state or the folding state based on the corrected data. For example, when the magnetic flux density caused by the first magnet and the second magnet changes over time, the data obtained through the hall sensor **455** may reflect the state of the electronic device **101** differently from the actual state. To prevent misidentification caused by a difference between the state of the electronic device **101** indicated by the data and the actual state of the electronic device **101**, the processor **120** may obtain data obtained through the hall sensor **455** as reference data while identifying that the state of the electronic device **101** is within the fully folding state through the illuminance sensor (e.g., an illuminance sensor in the sensor module **176** shown in FIG. 1) of the electronic device **101**. The processor **120** may correct the data based on the reference data and identify the state of the electronic device **101** based on the corrected data, thereby maintaining the performance of the identification through the hall sensor **455** even if the magnetic flux density from the first magnet and the second magnet changes over time. However, it is not limited thereto.

(130) As illustrated through FIGS. 4 to 13, and descriptions thereof, in order to prevent the corner region (e.g., the corner region **507** shown in FIG. 5) of the third surface **221** from being spaced apart from the corner region (e.g., the corner region **503** shown in FIG. 5) of the first surface **211**, the electronic device **101** may identify the state of the electronic device **101** using an array of magnets mounted in the electronic device **101** and a hall sensor **455** used to identify a change in magnetic force caused by the array of magnets. In an embodiment, since the hall sensor **455** is adjacent (e.g., or proximate) to one of the magnets, the hall sensor **455** may maintain a magnetized state even when a situation related to the electronic device **101** is changed. In an embodiment, since the hall sensor **455** is spaced apart from the camera module in the electronic device **101** causing a magnetic field that changes according to the photographing state, hall sensor **455** may be used to identify the state of electronic device **101** within a state in which the influence from the operation of the camera module is reduced. In an embodiment, the hall sensor **455** may be robust from impact because it protrudes from the PCB in the electronic device **101** and is spaced apart from a plurality of antenna contacts pressed by other components of the electronic device **101**. In an embodiment, since the hall sensor **455** is spaced apart from the plurality of antenna contacts, the hall sensor **455** may reduce or prevent degradation of performance of the hall sensor **455** or malfunction of the hall sensor **455** caused by the antenna structure formed by the conductive member in contact with the plurality of antenna contacts. In an embodiment, since the hall sensor **455** is located within another

area on the PCB distinct from the area on the PCB in which the electrical path from the plurality of antenna contacts is formed, the hall sensor **455** may reduce or prevent a decrease in performance of the antenna structure related to the plurality of antenna contacts. In an embodiment, since the hall sensor **455** is spaced apart from the wiring for the power signal, the hall sensor **455** may prevent the magnetic force drift from affecting the hall sensor **455**. In an embodiment, since magnets interlocked with the hall sensor **455** are disposed in a corner area (e.g., a corner area **503**) of the first surface **211** and a corner area (e.g., a corner area **507**) of the third surface **221** respectively, the electronic device **101** may prevent a dead zone in which performance of recognizing a stylus pen is reduced through the electromagnetic induction panel **401** included in the electronic device **101**.

(131) As described above, the electronic device (e.g., the electronic device **101**) according to an embodiment may include a first surface (e.g., a first surface **211**) and a first housing (e.g., first housing **210**) including a first surface and a second surface (e.g., a second surface **212**) opposite from the first surface, a second housing (e.g., the second housing **220**) including a third surface (e.g., the third surface **221**) and a fourth surface (e.g., the fourth surface **222**) opposite from the third surface, a folding housing (e.g., folding housing **265**) rotatably connecting a side surface of the second housing facing a side surface of the first surface and a side surface of the first surface with respect to a folding axis, a flexible display panel (e.g., flexible display **230**) disposed across the folding housing on the first surface and the third surface, a printed circuit board (PCB) in the first housing, A camera module (e.g., a camera module **701**) attached to the PCB, partially exposed through a part of the second surface, and including a magnet, a first magnet (e.g., magnet **501**) in the first housing, disposed along an edge spaced apart from the folding axis among edges of the first surface parallel to the folding axis, the second magnet (e.g., magnet **502**) in the second housing disposed at a position corresponding to the position of the first magnet, a hall sensor mounted on the PCB, spaced apart from the camera module, and disposed between the camera module and an edge of the first side perpendicular to the folding axis adjacent (e.g., or proximate) the first magnet (Example: Hall sensor **455**). In an embodiment, the first magnet may be disposed in one (a) corner area (e.g., a corner area **503**) spaced apart from the folding axis among corner areas of the first surface.

(132) In an embodiment, the electronic device may be disposed under at least a portion of the flexible display panel, and may further include an electromagnetic induction panel, configured to receive input from a stylus pen including a coil.

(133) In an embodiment, the electronic device may further include at least one processor operatively coupled to the Hall sensor and disposed within the first housing or the second housing; wherein the at least one processor is configured to: obtain, through the hall sensor, data regarding change of magnetic flux density from the second magnet; and identify, based on the data, whether the electronic device is in an unfolding state in which a first direction the first surface faces corresponds to a second direction the third surface faces or in a folding state distinct from the unfolding state.

(134) In an embodiment, the electronic device may further include a plurality of antenna contacts (e.g., a plurality of antenna contacts **711**), adjacent (e.g., or proximate) to the periphery that is adjacent (e.g., or proximate) to the first magnet from among the peripheries of the first surface perpendicular to the folding axis, attached to the PCB along a periphery of the PCB, the plurality of antenna contacts spaced apart from each other; wherein the hall sensor may be spaced apart from the plurality of antenna contacts. In an embodiment, the hall sensor may be disposed between the plurality of antenna contacts and the camera module.

(135) In an embodiment, the electronic device may further include an antenna contact (e.g., antenna contact **710**) on the PCB, adjacent (e.g., or proximate) to a periphery of the PCB that is adjacent (e.g., or proximate) to the periphery of the first surface spaced apart from the folding axis from among the peripheries of the first surface parallel to the folding axis, attached to the PCB; wherein the hall sensor may be spaced apart from the antenna contact. In an embodiment, the hall sensor

may be mounted on another area of the PCB, which is distinguished from an area of the PCB in which an electrical path extending from the antenna contact is formed.

(136) In an embodiment, the electronic device may further include another camera module disposed between the camera module and the hall sensor, at least partially exposed through another portion of the second surface, the other camera mounted on the PCB; wherein the camera module from among the camera module and the other camera module may be configured to provide optical image stabilization (OIS) according to a state of a movement of the camera module.

(137) In an embodiment, the hall sensor and the camera module may be disposed at a distance to reduce interference of the hall sensor by magnetism of the magnet in the camera module being moved for an optical image stabilization (OIS) function.

(138) In an embodiment, the electronic device further may include third magnets in the first housing, adjacent (e.g., or proximate) to the periphery of the first surface spaced apart from the folding axis from among the peripheries of the first surface parallel to the folding axis, spaced apart from the first magnet; and fourth magnets in the second housing disposed in positions respectively corresponding to positions of the third magnets and an attractive force between the third magnets and the fourth magnets may be greater than an attractive force between the first magnet and the second magnet.

(139) In an embodiment, the processor may be configured to: identify, while a state of the electronic device is an unfolding state in which a first direction the first surface faces corresponds to a second direction the third surface faces, whether the state of the electronic device is switched from the unfolding state or not, by comparing data regarding change of magnetic flux density from the second magnet with first reference data; and identify, while the state of the electronic device is a fully folding state in which at least portion of the first surface is in contact with at least portion of the third surface, whether the state of the electronic device is switched from the fully folding state or not, by comparing the data with second reference data distinct from the first reference data.

(140) In an embodiment, the processor may be configured to: identify, while a state of the electronic device is switched from an unfolding state in which a first direction the first surface faces corresponds to a second direction the third surface faces, angle between the first surface and the third surface, by comparing data regarding change of magnetic flux density from the second magnet with first reference data; and identify, while the state of the electronic device is switched from a fully folding state in which at least portion of the first surface is in contact with at least portion of the third surface, the angle of the first surface and the third surface by comparing the data with second reference data distinct from the first reference data.

(141) In an embodiment, the processor may be configured to identify a change in magnetic flux density in a direction parallel to the folding axis from the data, based on the identified change, and identify whether the electronic device is in the unfolding state or in the folding state.

(142) In an embodiment, the processor may be configured to identify a change in magnetic flux density in a direction perpendicular to the folding axis from the data and identify whether the electronic device is in the unfolding state or in the folding state, based on the identified change.

(143) In an embodiment, the processor may be configured to identify a change in magnetic flux density in the first direction or the second direction from the data and based on the identified change, identify whether the electronic device is in the unfolding state or in the folding state.

(144) In an embodiment, each of the first magnet, the second magnet, and the hall sensor may be disposed under the flexible display panel.

(145) In an embodiment, the PCB may include a plurality of layers, and the hall sensor may be mounted on a layer closest to the first surface among the plurality of layers.

(146) In an embodiment, the electronic device may include a first housing including a first surface and a second surface faced away the first surface, a second housing including a third surface and a fourth surface faced away the third surface, a folding housing pivotably connecting a side surface of the first housing and a side surface of the second housing facing the side surface of the first

housing based on a folding axis, a flexible display panel disposed on the first surface and the third surface across the folding housing, a printed circuit board (PCB) in the first housing, a plurality of antenna contacts, adjacent (e.g., or proximate) to a periphery of the first surface that is adjacent (e.g., or proximate) to the first magnet from among peripheries of the first surface perpendicular to the folding axis, attached to the PCB, the plurality of antenna contacts spaced apart from each other, a first magnet in the first housing disposed along a periphery of the first surface spaced apart from the folding axis from among peripheries of the first surface parallel to the folding axis, a second magnet in the second housing disposed in a position corresponding to a position of the first magnet and a hall sensor, spaced apart from each of the plurality of antenna contacts, spaced apart from the first magnet, the hall sensor mounted on the PCB. In an embodiment, the first magnet may be disposed in one (a) corner region (e.g., corner region 503) spaced apart from the folding axis among corner regions of the first surface.

(147) In an embodiment, the electronic device further may include an antenna contact on the PCB, mounted on the PCB, adjacent (e.g., or proximate) to a periphery of the PCB that is adjacent (e.g., or proximate) to the periphery of the first surface spaced apart from the folding axis from among the peripheries of the first surface parallel to the folding axis; and the hall sensor may be spaced apart from the antenna contact.

(148) In an embodiment, the electronic device may further include a camera module attached to the PCB, partially exposed through a part of the second surface, and including a magnet and the hall sensor may be spaced apart from the camera module and may be disposed between an edge adjacent (e.g., or proximate) to the first magnet among edges of the first surface perpendicular to the folding axis and the camera module.

(149) In an embodiment, the electronic device may include a first housing including a first surface and a second surface faced away the first surface; a second housing including a third surface and a fourth surface faced away the third surface; a folding housing pivotably connecting a side surface of the first housing and a side surface of the second housing facing the side surface of the first housing based on a folding axis; a flexible display panel disposed on the first surface and the third surface across the folding housing; a first printed circuit board (PCB) in the first housing; a second PCB in the second housing; a camera module, mounted on the first PCB, at least partially exposed through portion of the second surface, the camera module including a magnet; a first magnet in the first housing, disposed along a periphery of the first surface spaced apart from the folding axis from among peripheries of the first surface parallel to the folding axis; a second magnet in the second housing disposed in a position corresponding to a position of the first magnet; a plurality of antenna contacts, adjacent (e.g., or proximate) to a periphery of the third surface that is adjacent (e.g., or proximate) to the second magnet from among peripheries of the third surface perpendicular to the folding axis, spaced apart from each other; and a hall sensor, mounted on the second PCB, spaced apart from each of the plurality of antenna contacts, the hall sensor spaced apart from the second magnet. In an embodiment, the first magnet may be disposed in one (a) corner region (e.g., corner region 503) spaced apart from the folding axis among corner regions of the first surface.

(150) The electronic device according to certain embodiments may be one of various types of electronic devices. The electronic devices may include, for example, a portable communication device (e.g., a smartphone), a computer device, a portable multimedia device, a portable medical device, a camera, a wearable device, or a home appliance. According to an embodiment of the disclosure, the electronic devices are not limited to those described above.

(151) It should be appreciated that certain embodiments of the present disclosure and the terms used therein are not intended to limit the technological features set forth herein to particular embodiments and include various changes, equivalents, or replacements for a corresponding embodiment. With regard to the description of the drawings, similar reference numerals may be used to refer to similar or related elements. It is to be understood that a singular form of a noun corresponding to an item may include one or more of the things, unless the relevant context clearly

indicates otherwise. As used herein, each of such phrases as “A or B,” “at least one of A and B,” “at least one of A or B,” “A, B, or C,” “at least one of A, B, and C,” and “at least one of A, B, or C,” may include any one of, or all possible combinations of the items enumerated together in a corresponding one of the phrases. As used herein, such terms as “1st” and “2nd,” or “first” and “second” may be used to simply distinguish a corresponding component from another, and does not limit the components in other aspect (e.g., importance or order). It is to be understood that if an element (e.g., a first element) is referred to, with or without the term “operatively” or “communicatively”, as “coupled with,” “coupled to,” “connected with,” or “connected to” another element (e.g., a second element), it means that the element may be coupled with the other element directly (e.g., wiredly), wirelessly, or via a third element.

(152) As used in connection with certain embodiments of the disclosure, the term “module” may include a unit implemented in hardware, software, or firmware, and may interchangeably be used with other terms, for example, “logic,” “logic block,” “part,” or “circuitry”. A module may be a single integral component, or a minimum unit or part thereof, adapted to perform one or more functions. For example, according to an embodiment, the module may be implemented in a form of an application-specific integrated circuit (ASIC).

(153) Certain embodiments as set forth herein may be implemented as software (e.g., the program **140**) including one or more instructions that are stored in a storage medium (e.g., internal memory **136** or external memory **138**) that is readable by a machine (e.g., the electronic device **101**). For example, a processor (e.g., the processor **120**) of the machine (e.g., the electronic device **101**) may invoke at least one of the one or more instructions stored in the storage medium, and execute it, with or without using one or more other components under the control of the processor. This allows the machine to be operated to perform at least one function according to the at least one instruction invoked. The one or more instructions may include a code generated by a compiler or a code executable by an interpreter. The machine-readable storage medium may be provided in the form of a non-transitory storage medium. The term “non-transitory” simply means that the storage medium is a tangible device, and does not include a signal (e.g., an electromagnetic wave), but this term does not differentiate between where data is semi-permanently stored in the storage medium and where the data is temporarily stored in the storage medium.

(154) According to an embodiment, a method according to certain embodiments of the disclosure may be included and provided in a computer program product. The computer program product may be traded as a product between a seller and a buyer. The computer program product may be distributed in the form of a machine-readable storage medium (e.g., compact disc read only memory (CD-ROM)), or be distributed (e.g., downloaded or uploaded) online via an application store (e.g., PlayStore™), or between two user devices (e.g., smart phones) directly. If distributed online, at least part of the computer program product may be temporarily generated or at least temporarily stored in the machine-readable storage medium, such as memory of the manufacturer's server, a server of the application store, or a relay server.

(155) According to certain embodiments, each component (e.g., a module or a program) of the above-described components may include a single entity or multiple entities, and some of the multiple entities may be separately disposed in different components. According to certain embodiments, one or more of the above-described components may be omitted, or one or more other components may be added. Alternatively or additionally, a plurality of components (e.g., modules or programs) may be integrated into a single component. In such a case, according to certain embodiments, the integrated component may still perform one or more functions of each of the plurality of components in the same or similar manner as they are performed by a corresponding one of the plurality of components before the integration. According to certain embodiments, operations performed by the module, the program, or another component may be carried out sequentially, in parallel, repeatedly, or heuristically, or one or more of the operations may be executed in a different order or omitted, or one or more other operations may be added.

Claims

1. A foldable electronic device comprising: a housing including: a first housing part, and a second housing part rotatably coupled with the first housing part; a flexible display; a first magnet disposed under a first corner area of the flexible display that is positioned on the first housing part; a second magnet disposed under a second corner area of the flexible display that is positioned on the second housing part and overlaps the first corner area of the flexible display in a folded state of the foldable electronic device, wherein the first magnet and the second magnet are configured to maintain the folded state of the foldable electronic device through an attractive magnetic force between the first magnet and the second magnet; a first camera disposed in the first housing part; a second camera, configured with optical image stabilization (OIS), disposed in the first housing part; and a hall sensor, disposed in the first housing part, configured to generate data for identifying whether a state of the foldable electronic device corresponds to an unfolded state of the foldable electronic device or the folded state of the foldable electronic device based on a magnetic field to be caused by the first magnet and the second magnet, wherein a distance between the first magnet and the hall sensor is smaller than a distance between the first magnet and the first camera, and wherein a distance between the hall sensor and the first camera is smaller than a distance between the hall sensor and the second camera.
2. The foldable electronic device of claim 1, wherein the first housing part includes: a first periphery portion substantially perpendicular to an axis of the second housing part for rotating with respect to the first housing part; and a second periphery portion, substantially perpendicular to the first periphery portion, substantially parallel to the axis, wherein the first periphery portion of the first housing part and the second periphery portion of the first housing part join each other at the first corner area, wherein the hall sensor is disposed between the second camera in the first housing part and the first periphery portion of the first housing part.
3. The foldable electronic device of claim 2, wherein the hall sensor is disposed between the first camera in the first housing part and the first periphery portion of the first housing part.
4. The foldable electronic device of claim 3, wherein the second camera among the first camera and the second camera has an OIS mechanism, wherein the hall sensor is spaced apart from the second camera such that whether the state of the foldable electronic device corresponds to the unfolded state of the foldable electronic device or the folded state of the foldable electronic device is identified independently of changes in a magnetic field caused from the second camera in the first housing part, and wherein the changes in the magnetic field from the second camera are to be caused according to the OIS mechanism of the second camera.
5. The foldable electronic device of claim 3, further comprising: a printed circuit board (PCB) disposed in the first housing part, wherein the first camera and the second camera are attached to the PCB to face in a first direction, and wherein the hall sensor is mounted on a side of the PCB facing in a second direction opposite to the first direction.
6. The foldable electronic device of claim 5, further comprising: antenna contacts, spaced apart from each other, disposed along the first periphery portion of the first housing part, wherein the first periphery portion of the first housing part includes a lateral conductive portion configured to function as an antenna radiator, wherein each of the antenna contacts is contacted on both the PCB and the lateral conductive portion included in the first periphery portion of the first housing part to electrically connect the PCB to the lateral conductive portion included in the first periphery portion of the first housing part, and wherein the hall sensor is spaced apart from each of the antenna contacts.
7. The foldable electronic device of claim 6, wherein the antenna contacts are disposed on another side of the PCB that is opposite to the side of the PCB on which the hall sensor is mounted.
8. The foldable electronic device of claim 6, wherein the hall sensor is disposed between the second

camera and a virtual line connecting the antenna contacts.

9. The foldable electronic device of claim 6, wherein the hall sensor is spaced apart from the antenna contacts to reduce a malfunction of the hall sensor.

10. The foldable electronic device of claim 6, wherein the hall sensor is spaced apart from the antenna contacts to reduce any interference to a signal received through the lateral conductive portion.

11. The foldable electronic device of claim 1, further comprising: third magnets and fourth magnets, configured to maintain the folded state of the foldable electronic device through an attractive magnetic force between the third magnets and the fourth magnets, wherein the first housing part includes: a first periphery portion; and a second periphery portion substantially perpendicular to the first periphery portion, wherein the first periphery portion of the first housing part and the second periphery portion join each other at the first corner area, wherein the second housing part includes: a third periphery portion extending from the first periphery portion of the first housing part; and a fourth periphery portion substantially perpendicular to the third periphery portion of the second housing part, wherein the third periphery portion of the second housing part and the fourth periphery portion of the second housing part join each other at the second corner area, wherein the third magnets are disposed along the second periphery portion of the first housing part, wherein the fourth magnets are disposed along the fourth periphery portion of the second housing part, and wherein the hall sensor is closer to the first magnet than the third magnets.

12. The foldable electronic device of claim 11, wherein the hall sensor is spaced apart from the third magnets such that whether the state of the foldable electronic device corresponds to the unfolded state of the foldable electronic device or the folded state of the foldable electronic device can be identified independently of changes in a magnetic field from the third magnets and the fourth magnets caused according to change from the unfolded state of the foldable electronic device to the folded state of the foldable electronic device.

13. The foldable electronic device of claim 1, further comprising: at least one processor, comprising processing circuitry, configured to identify based on data from the hall sensor the unfolded state of the foldable electronic device and the folded state of the foldable electronic device.

14. A foldable electronic device comprising: a housing including: a first housing part, and a second housing part rotatably coupled with the first housing part; a flexible display; a first magnet disposed under a first corner area of the flexible display that is positioned on the first housing part; a second magnet disposed under a second corner area of the flexible display that is positioned on the second housing part and overlaps the first corner area of the flexible display in a folded state of the foldable electronic device, wherein the first magnet and the second magnet are configured to maintain the folded state of the foldable electronic device based on an attractive magnetic force between the first magnet and the second magnet; a first camera disposed in the first housing part; a second camera, configured for an optical image stabilization (OIS), disposed in the first housing part; and a hall sensor, disposed in the second housing part, configured to obtain data for identifying whether a state of the foldable electronic device corresponds to an unfolded state of the foldable electronic device or the folded state of the foldable electronic device based on a magnetic field to be caused by the first magnet and the second magnet, wherein the hall sensor is closer to the first camera projected onto the second housing part in the folded state of the foldable electronic device than the second camera projected onto the second housing part in the folded state of the foldable electronic device.

15. The foldable electronic device of claim 14, wherein the second housing part includes: a first periphery portion substantially perpendicular to an axis of the second housing part for rotating with respect to the first housing part; and a second periphery portion, substantially perpendicular to the first periphery portion, substantially parallel to the axis, wherein the first periphery portion of the second housing part and the second periphery portion of the second housing part join each other at

the second corner area, wherein the hall sensor is disposed between the first periphery portion of the second housing part and a virtual line extending a periphery portion of the second camera projected onto the second housing part in the folded state of the foldable electronic device, wherein the periphery portion of the second camera projected onto the second housing part in the folded state of the foldable electronic device is: substantially parallel to the first periphery portion of the second housing part; and closer to the first periphery portion of the second housing part than another periphery portion of the second camera projected onto the second housing part in the folded state of the foldable electronic device being substantially parallel to the first periphery portion of the second housing part.

16. The foldable electronic device of claim 15, wherein the hall sensor is disposed between the first periphery portion of the second housing part and a virtual line extending a periphery portion of the first camera projected onto the second housing part in the folded state of the foldable electronic device, wherein the periphery portion of the first camera projected onto the second housing part in the folded state of the foldable electronic device is: substantially parallel to the first periphery portion of the second housing part; and closer to the first periphery portion of the second housing part than another periphery portion of the first camera projected onto the second housing part in the folded state of the foldable electronic device being substantially parallel to the first periphery portion of the second housing part.

17. The foldable electronic device of claim 16, wherein the first camera comprises an ultrawide-angle camera, and wherein the second camera comprises a wide-angle camera.

18. The foldable electronic device of claim 14, further comprising: a first printed circuit board (PCB) disposed in the first housing part; and a second PCB disposed in the second housing part, wherein the first camera and the second camera are attached to the first PCB to face in a first direction, and wherein the hall sensor is mounted on a side of the second PCB facing in a second direction opposite to the first direction.

19. The foldable electronic device of claim 18, wherein the second housing part includes: a first periphery portion substantially perpendicular to an axis of the second housing part rotating with respect to the first housing part; and a second periphery portion, substantially perpendicular to the first periphery portion, substantially parallel to the axis, wherein the first periphery portion of the second housing part and the second periphery portion of the second housing part join each other at the second corner area, wherein the foldable electronic device further comprises antenna contacts, spaced apart from each other, disposed along the first periphery portion of the second housing part, wherein the first periphery portion of the second housing part includes a lateral conductive portion configured to function as an antenna, wherein each of the antenna contacts is contacted on both the second PCB and the lateral conductive portion included in the first periphery portion of the second housing part to connect the second PCB to the lateral conductive portion included in the first periphery portion of the second housing part, and wherein the hall sensor is spaced apart from each of the antenna contacts.

20. The foldable electronic device of claim 19, wherein the antenna contacts are disposed on another side of the second PCB that is opposite to the side of the PCB on which the hall sensor is mounted.
