

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent

12406613

Kind Code

B2

Date of Patent

September 02, 2025

Inventor(s)

Lee; Seungeun et al.

Electronic device including display and camera and method controlling thereof

Abstract

An electronic device and method are disclosed. The electronic device includes a first camera; a first display panel including multiple pixels and disposed to overlap the first camera, in at least a partial region thereof; and a processor. The processor implements the method, including: displaying, on a first display panel, a graphic user interface; activating, via at least one processor, a first camera, wherein the first display panel includes multiple pixels, and is disposed to overlap the first camera in at least a partial region thereof; deactivating, via the at least one processor, at least one pixel disposed within a first region of the first display panel, wherein the first region is included in the partial region; and changing the graphic user interface to be displayed at least in part to a second region of the first display panel, wherein the second region is in contact with the first region.

Inventors: Lee; Seungeun (Gyeonggi-do, KR), Kim; Chakyum (Gyeonggi-do, KR), Kang; Minseok (Gyeonggi-do, KR), Han; Byeungwoong (Gyeonggi-do, KR), Heo; Changryong (Gyeonggi-do, KR)

Applicant: Samsung Electronics Co., Ltd. (Gyeonggi-do, KR)

Family ID: 85200135

Assignee: Samsung Electronics Co., Ltd. (Suwon-si, KR)

Appl. No.: 17/977059

Filed: October 31, 2022

Prior Publication Data

Document Identifier

Publication Date

US 20230054033 A1

Feb. 23, 2023

Foreign Application Priority Data

KR

10-2021-0105186

Aug. 10, 2021

Related U.S. Application Data

continuation parent-doc WO PCT/KR2022/011918 20220810 PENDING child-doc US 17977059

Publication Classification

Int. Cl.: **G06F3/04886** (20220101); **G06F1/18** (20060101); **G06F3/04817** (20220101); **G06F3/04845** (20220101); **G09G3/00** (20060101); **G09G3/20** (20060101); **H04N23/90** (20230101)

U.S. Cl.:

CPC **G09G3/2096** (20130101); **G06F1/181** (20130101); **G06F3/04817** (20130101); **G06F3/04845** (20130101); **G06F3/04886** (20130101); **G09G3/035** (20200801); **H04N23/90** (20230101); G09G2340/0464 (20130101); G09G2340/14 (20130101); G09G2354/00 (20130101)

Field of Classification Search

CPC: G09G (3/2096); G09G (3/035); G09G (2340/0464); G09G (2340/14); G09G (2354/00); G09G (3/2092); G09G (2300/0426); G09G (2300/0439); G09G (2380/02); G06F (1/181); G06F (3/04817); G06F (3/04845); G06F (3/04886); G06F (1/1637); G06F (1/1652); G06F (1/1686); H04N (23/90); H04M (1/0214); H04M (1/0266); H04M (2250/52); H04M (1/0264)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
8723824	12/2013	Myers et al.	N/A	N/A
10019940	12/2017	Rappoport et al.	N/A	N/A
10416843	12/2018	Hong et al.	N/A	N/A
10482309	12/2018	Zhang et al.	N/A	N/A
10733931	12/2019	Jung et al.	N/A	N/A
11158230	12/2020	Lee et al.	N/A	N/A
11233923	12/2021	Nicholson et al.	N/A	N/A
11283971	12/2021	Moon et al.	N/A	N/A
11412146	12/2021	Miao	N/A	N/A
2016/0132192	12/2015	Sutton et al.	N/A	N/A
2019/0130822	12/2018	Jung	N/A	G09G 3/3208
2020/0183450	12/2019	Jang	N/A	H04M 1/0216
2020/0329178	12/2019	Moon et al.	N/A	N/A
2020/0342800	12/2019	Li et al.	N/A	N/A
2022/0182549	12/2021	Zhang	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
------------	------------------	---------	-----

112311998	12/2020	CN	N/A
3859724	12/2020	EP	N/A
2021-508855	12/2020	JP	N/A
10-2016-0062414	12/2015	KR	N/A
10-2017-0113066	12/2016	KR	N/A
10-1800669	12/2016	KR	N/A
10-2019-0101148	12/2018	KR	N/A
10-2020-0119639	12/2019	KR	N/A
10-2397044	12/2021	KR	N/A
2019/154072	12/2018	WO	N/A
2020/209646	12/2019	WO	N/A

OTHER PUBLICATIONS

WO 2019/154072 (Eng Translation) publihsed on Aug. 15, 2019. cited by examiner
International Search Report dated Nov. 22, 2022. cited by applicant
Extended European Search Report dated Sep. 5, 2024. cited by applicant

Primary Examiner: Yi; Rinna

Attorney, Agent or Firm: Cha & Reiter, LLC.

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION(S) (1) This application is a continuation of International Application No. PCT/KR2022/011918, which was filed on Aug. 10, 2022, and claims priority to Korean Patent Application No. 10-2021-0105186, filed on Aug. 10, 2021, and to Korean Patent Application No. 10-2022-0005759, filed on Jan. 14, 2022, in the Korean Intellectual Property Office, the disclosures of which are incorporated by reference herein their entireties.

BACKGROUND

Technical Field

(1) Certain embodiments disclosed herein relate to an electronic device having an under-display camera, and more particular, to altering a user interface according to usage of the under-display camera.

Description of Related Art

(2) Ongoing development continues for under-display cameras (UDC). UDC cameras may include frontal camera disposed in a front-facing display region, and/or disposed on a back surface of the display. The usage of UDC cameras has grown in line with the gradual expansion in the display size of recent electronic devices. Optical transmittance of the display in which a UDC camera is disposed is important, because external light enters to the UDC camera through the display. To better provide a high degree of optical transmittance, attempts have been made to partially remove pixels in the particular display region in which the UDC camera is disposed, and/or to widen intervals of pixel wiring.

(3) An electronic device including a UDC camera may display a user interface, including various objects (e.g., app icons, menus, etc.). Such objects may be utilized to display information, represent selectable elements and icons for executing various functions of the electronic device, and may also include entertainment and other aesthetic elements.

(4) The UDC is advantageous in that more surface area can be allocated to the display, by disposing the display above the camera, rather than allocating non-display space for the camera. However,

when the UDC is operated, at least some of pixels in the peripheral display regions of the camera overlapping the UDC may be deactivated, to increase the quality of image capture. In this case, display objects previously displayed in the corresponding display region are removed, which may result in the convenience and usability of the electronic device to be degraded.

SUMMARY

(5) An electronic device is disclosed according to certain embodiments disclosed herein includes: a first camera; a first display panel including multiple pixels and disposed to overlap the first camera, in at least a partial region thereof; and a processor, wherein the processor is configured to: display a graphic user interface on the first display panel, control activation of the first camera, deactivate at least one pixel disposed within a first region of the first display panel, wherein the first region is included in the partial region, and change the graphic user interface to be displayed at least in part to a second region of the first display panel, wherein the second region is at least partially in contact with the first region

(6) A method is disclosed according to certain embodiments disclosed herein, and includes: displaying, on a first display panel, a graphic user interface; activating, via at least one processor, a first camera, wherein the first display panel includes multiple pixels, and is disposed to overlap the first camera in at least a partial region thereof; deactivating, via the at least one processor, at least one pixel disposed within a first region of the first display panel, wherein the first region is included in the partial region; and changing the graphic user interface to be displayed at least in part to a second region of the first display panel, wherein the second region is at least partially in contact with the first region.

(7) According to certain embodiments, usability of a UDC-equipped electronic device may be improved by altering the user interface displayed on the screen, according to a present photographic mode.

(8) According to certain embodiments, display regions the electronic device may be utilized with greater efficiency when accommodating operations of a UDC.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) In describing the drawings, identical or similar reference numerals are used to designate identical or similar elements.

(2) FIG. 1 is a block diagram of an electronic device in a network environment according to certain embodiments.

(3) FIG. 2A is a perspective view of the front surface of an electronic device according to certain embodiments.

(4) FIG. 2B is a perspective view of the rear surface of the electronic device in FIG. 2A according to certain embodiments.

(5) FIG. 3A is a front perspective view illustrating a flat state or an unfolding state of an electronic device including a second form according to certain embodiments.

(6) FIG. 3B is a plan view illustrating the front surface of an electronic device in the unfolded state in FIG. 3A according to certain embodiments.

(7) FIG. 3C is a plan view illustrating the rear surface of an electronic device in the unfolded state in FIG. 3A according to certain embodiments.

(8) FIG. 4 is an exploded perspective view of a display **400** according to certain embodiments.

(9) FIG. 5A is a partial cross-sectional view of an electronic device, taken along line 5-5 in FIG. 2A according to certain embodiments.

(10) FIG. 5B is an enlarged view of region **6** in FIG. 5A according to certain embodiments.

(11) FIG. 6 illustrates a partial configuration of a display panel when region **7** in FIG. 5B according

to certain embodiments is seen from above.

(12) FIG. 7 is a block diagram of an electronic device according to certain embodiments.

(13) FIG. 8 shows an electronic device according to certain embodiments, which changes a user interface.

(14) FIG. 9 is a flowchart showing operations of changing a user interface by an electronic device according to certain embodiments.

(15) FIG. 10 is a flowchart showing operations of changing a user interface by an electronic device including at least one camera according to certain embodiments.

(16) FIG. 11 shows an electronic device according to certain embodiments, which changes a user interface based on a position in which an object is displayed.

(17) FIG. 12 is a flowchart showing operations in which an electronic device according to certain embodiments changes a user interface, based on a position in which an object is displayed.

(18) FIG. 13 shows an electronic device according to certain embodiments, which changes a user interface based on an executed application.

(19) FIG. 14 is a flowchart of operations in which an electronic device according to certain embodiments changes a user interface, based on an executed application.

(20) FIG. 15 shows changing a user interface by an electronic device displaying multiple user interfaces according to certain embodiments.

(21) FIG. 16 is a flowchart showing operations of changing a user interface by an electronic device displaying multiple user interfaces according to certain embodiments.

(22) FIG. 17A illustrates an unfolded state of an electronic device including a third form according to certain embodiments.

(23) FIG. 17B illustrates a folded state of the electronic device in FIG. 17A according to certain embodiments.

(24) FIG. 18 is a flowchart showing operations of changing a user interface by an electronic device including multiple displays and multiple cameras according to certain embodiments.

DETAILED DESCRIPTION

(25) It should be appreciated that certain embodiments of the present disclosure and the terms used therein are not intended to limit the technological features set forth herein to particular embodiments and include various changes, equivalents, or replacements for a corresponding embodiment.

(26) With regard to the description of the drawings, similar reference numerals may be used to refer to similar or related elements. It is to be understood that a singular form of a noun corresponding to an item may include one or more of the things, unless the relevant context clearly indicates otherwise.

(27) As used herein, each of such phrases as “A or B,” “at least one of A and B,” “at least one of A or B,” “A, B, or C,” “at least one of A, B, and C,” and “at least one of A, B, or C,” may include any one of, or all possible combinations of the items enumerated together in a corresponding one of the phrases. As used herein, such terms as “1st” and “2nd,” or “first” and “second” may be used to simply distinguish a corresponding component from another, and does not limit the components in other aspect (e.g., importance or order). It is to be understood that if an element (e.g., a first element) is referred to, with or without the term “operatively” or “communicatively”, as “coupled with,” “coupled to,” “connected with,” or “connected to” another element (e.g., a second element), it means that the element may be coupled with the other element directly (e.g., wiredly), wirelessly, or via a third element.

(28) FIG. 1 is a block diagram illustrating an electronic device **101** in a network environment **100** according to certain embodiments. Referring to FIG. 1, the electronic device **101** in the network environment **100** may communicate with an electronic device **102** via a first network **198** (e.g., a short-range wireless communication network), or at least one of an electronic device **104** or a server **108** via a second network **199** (e.g., a long-range wireless communication network).

According to an embodiment, the electronic device **101** may communicate with the electronic device **104** via the server **108**. According to an embodiment, the electronic device **101** may include a processor **120**, memory **130**, an input module **150**, a sound output module **155**, a display module **160**, an audio module **170**, a sensor module **176**, an interface **177**, a connecting terminal **178**, a haptic module **179**, a camera module **180**, a power management module **188**, a battery **189**, a communication module **190**, a subscriber identification module (SIM) **196**, or an antenna module **197**. In some embodiments, at least one of the components (e.g., the connecting terminal **178**) may be omitted from the electronic device **101**, or one or more other components may be added in the electronic device **101**. In some embodiments, some of the components (e.g., the sensor module **176**, the camera module **180**, or the antenna module **197**) may be implemented as a single component (e.g., the display module **160**).

(29) The processor **120** may execute, for example, software (e.g., a program **140**) to control at least one other component (e.g., a hardware or software component) of the electronic device **101** coupled with the processor **120**, and may perform various data processing or computation.

According to an embodiment, as at least part of the data processing or computation, the processor **120** may store a command or data received from another component (e.g., the sensor module **176** or the communication module **190**) in volatile memory **132**, process the command or the data stored in the volatile memory **132**, and store resulting data in non-volatile memory **134**. According to an embodiment, the processor **120** may include a main processor **121** (e.g., a central processing unit (CPU) or an application processor (AP)), or an auxiliary processor **123** (e.g., a graphics processing unit (GPU), a neural processing unit (NPU), an image signal processor (ISP), a sensor hub processor, or a communication processor (CP)) that is operable independently from, or in conjunction with, the main processor **121**. For example, when the electronic device **101** includes the main processor **121** and the auxiliary processor **123**, the auxiliary processor **123** may be adapted to consume less power than the main processor **121**, or to be specific to a specified function. The auxiliary processor **123** may be implemented as separate from, or as part of the main processor **121**.

(30) The auxiliary processor **123** may control at least some of functions or states related to at least one component (e.g., the display module **160**, the sensor module **176**, or the communication module **190**) among the components of the electronic device **101**, instead of the main processor **121** while the main processor **121** is in an inactive (e.g., sleep) state, or together with the main processor **121** while the main processor **121** is in an active state (e.g., executing an application). According to an embodiment, the auxiliary processor **123** (e.g., an image signal processor or a communication processor) may be implemented as part of another component (e.g., the camera module **180** or the communication module **190**) functionally related to the auxiliary processor **123**. According to an embodiment, the auxiliary processor **123** (e.g., the neural processing unit) may include a hardware structure specified for artificial intelligence model processing. An artificial intelligence model may be generated by machine learning. Such learning may be performed, e.g., by the electronic device **101** where the artificial intelligence is performed or via a separate server (e.g., the server **108**). Learning algorithms may include, but are not limited to, e.g., supervised learning, unsupervised learning, semi-supervised learning, or reinforcement learning. The artificial intelligence model may include a plurality of artificial neural network layers. The artificial neural network may be a deep neural network (DNN), a convolutional neural network (CNN), a recurrent neural network (RNN), a restricted Boltzmann machine (RBM), a deep belief network (DBN), a bidirectional recurrent deep neural network (BRDNN), deep Q-network or a combination of two or more thereof but is not limited thereto. The artificial intelligence model may, additionally or alternatively, include a software structure other than the hardware structure.

(31) The memory **130** may store various data used by at least one component (e.g., the processor **120** or the sensor module **176**) of the electronic device **101**. The various data may include, for example, software (e.g., the program **140**) and input data or output data for a command related

thereto. The memory **130** may include the volatile memory **132** or the non-volatile memory **134**.

(32) The program **140** may be stored in the memory **130** as software, and may include, for example, an operating system (OS) **142**, middleware **144**, or an application **146**.

(33) The input module **150** may receive a command or data to be used by another component (e.g., the processor **120**) of the electronic device **101**, from the outside (e.g., a user) of the electronic device **101**. The input module **150** may include, for example, a microphone, a mouse, a keyboard, a key (e.g., a button), or a digital pen (e.g., a stylus pen).

(34) The sound output module **155** may output sound signals to the outside of the electronic device **101**. The sound output module **155** may include, for example, a speaker or a receiver. The speaker may be used for general purposes, such as playing multimedia or playing record. The receiver may be used for receiving incoming calls. According to an embodiment, the receiver may be implemented as separate from, or as part of the speaker.

(35) The display module **160** may visually provide information to the outside (e.g., a user) of the electronic device **101**. The display module **160** may include, for example, a display, a hologram device, or a projector and control circuitry to control a corresponding one of the display, hologram device, and projector. According to an embodiment, the display module **160** may include a touch sensor adapted to detect a touch, or a pressure sensor adapted to measure the intensity of force incurred by the touch.

(36) The audio module **170** may convert a sound into an electrical signal and vice versa. According to an embodiment, the audio module **170** may obtain the sound via the input module **150**, or output the sound via the sound output module **155** or a headphone of an external electronic device (e.g., an electronic device **102**) directly (e.g., wiredly) or wirelessly coupled with the electronic device **101**.

(37) The sensor module **176** may detect an operational state (e.g., power or temperature) of the electronic device **101** or an environmental state (e.g., a state of a user) external to the electronic device **101**, and then generate an electrical signal or data value corresponding to the detected state. According to an embodiment, the sensor module **176** may include, for example, a gesture sensor, a gyro sensor, an atmospheric pressure sensor, a magnetic sensor, an acceleration sensor, a grip sensor, a proximity sensor, a color sensor, an infrared (IR) sensor, a biometric sensor, a temperature sensor, a humidity sensor, or an illuminance sensor.

(38) The interface **177** may support one or more specified protocols to be used for the electronic device **101** to be coupled with the external electronic device (e.g., the electronic device **102**) directly (e.g., wiredly) or wirelessly. According to an embodiment, the interface **177** may include, for example, a high definition multimedia interface (HDMI), a universal serial bus (USB) interface, a secure digital (SD) card interface, or an audio interface.

(39) A connecting terminal **178** may include a connector via which the electronic device **101** may be physically connected with the external electronic device (e.g., the electronic device **102**). According to an embodiment, the connecting terminal **178** may include, for example, a HDMI connector, a USB connector, a SD card connector, or an audio connector (e.g., a headphone connector).

(40) The haptic module **179** may convert an electrical signal into a mechanical stimulus (e.g., a vibration or a movement) or electrical stimulus which may be recognized by a user via his tactile sensation or kinesthetic sensation. According to an embodiment, the haptic module **179** may include, for example, a motor, a piezoelectric element, or an electric stimulator.

(41) The camera module **180** may capture a still image or moving images. According to an embodiment, the camera module **180** may include one or more lenses, image sensors, image signal processors, or flashes.

(42) The power management module **188** may manage power supplied to the electronic device **101**. According to an embodiment, the power management module **188** may be implemented as at least part of, for example, a power management integrated circuit (PMIC).

(43) The battery **189** may supply power to at least one component of the electronic device **101**.

According to an embodiment, the battery **189** may include, for example, a primary cell which is not rechargeable, a secondary cell which is rechargeable, or a fuel cell.

(44) The communication module **190** may support establishing a direct (e.g., wired) communication channel or a wireless communication channel between the electronic device **101** and the external electronic device (e.g., the electronic device **102**, the electronic device **104**, or the server **108**) and performing communication via the established communication channel. The communication module **190** may include one or more communication processors that are operable independently from the processor **120** (e.g., the application processor (AP)) and supports a direct (e.g., wired) communication or a wireless communication. According to an embodiment, the communication module **190** may include a wireless communication module **192** (e.g., a cellular communication module, a short-range wireless communication module, or a global navigation satellite system (GNSS) communication module) or a wired communication module **194** (e.g., a local area network (LAN) communication module or a power line communication (PLC) module). A corresponding one of these communication modules may communicate with the external electronic device via the first network **198** (e.g., a short-range communication network, such as Bluetooth™, wireless-fidelity (Wi-Fi) direct, or infrared data association (IrDA)) or the second network **199** (e.g., a long-range communication network, such as a legacy cellular network, a 5G network, a next-generation communication network, the Internet, or a computer network (e.g., LAN or wide area network (WAN))). These various types of communication modules may be implemented as a single component (e.g., a single chip), or may be implemented as multi components (e.g., multi chips) separate from each other. The wireless communication module **192** may identify and authenticate the electronic device **101** in a communication network, such as the first network **198** or the second network **199**, using subscriber information (e.g., international mobile subscriber identity (IMSI)) stored in the subscriber identification module **196**.

(45) The wireless communication module **192** may support a 5G network, after a 4G network, and next-generation communication technology, e.g., new radio (NR) access technology. The NR access technology may support enhanced mobile broadband (eMBB), massive machine type communications (mMTC), or ultra-reliable and low-latency communications (URLLC). The wireless communication module **192** may support a high-frequency band (e.g., the mmWave band) to achieve, e.g., a high data transmission rate. The wireless communication module **192** may support various technologies for securing performance on a high-frequency band, such as, e.g., beamforming, massive multiple-input and multiple-output (massive MIMO), full dimensional MIMO (FD-MIMO), array antenna, analog beam-forming, or large scale antenna. The wireless communication module **192** may support various requirements specified in the electronic device **101**, an external electronic device (e.g., the electronic device **104**), or a network system (e.g., the second network **199**). According to an embodiment, the wireless communication module **192** may support a peak data rate (e.g., 20 Gbps or more) for implementing eMBB, loss coverage (e.g., 164 dB or less) for implementing mMTC, or U-plane latency (e.g., 0.5 ms or less for each of downlink (DL) and uplink (UL), or a round trip of 1 ms or less) for implementing URLLC.

(46) The antenna module **197** may transmit or receive a signal or power to or from the outside (e.g., the external electronic device) of the electronic device **101**. According to an embodiment, the antenna module **197** may include an antenna including a radiating element implemented using a conductive material or a conductive pattern formed in or on a substrate (e.g., a printed circuit board (PCB)). According to an embodiment, the antenna module **197** may include a plurality of antennas (e.g., array antennas). In such a case, at least one antenna appropriate for a communication scheme used in the communication network, such as the first network **198** or the second network **199**, may be selected, for example, by the communication module **190** (e.g., the wireless communication module **192**) from the plurality of antennas. The signal or the power may then be transmitted or received between the communication module **190** and the external electronic device via the selected at least one antenna. According to an embodiment, another component (e.g., a radio

frequency integrated circuit (RFIC)) other than the radiating element may be additionally formed as part of the antenna module **197**.

(47) According to certain embodiments, the antenna module **197** may form a mmWave antenna module. According to an embodiment, the mmWave antenna module may include a printed circuit board, a RFIC disposed on a first surface (e.g., the bottom surface) of the printed circuit board, or adjacent to the first surface and capable of supporting a designated high-frequency band (e.g., the mmWave band), and a plurality of antennas (e.g., array antennas) disposed on a second surface (e.g., the top or a side surface) of the printed circuit board, or adjacent to the second surface and capable of transmitting or receiving signals of the designated high-frequency band.

(48) At least some of the above-described components may be coupled mutually and communicate signals (e.g., commands or data) therebetween via an inter-peripheral communication scheme (e.g., a bus, general purpose input and output (GPIO), serial peripheral interface (SPI), or mobile industry processor interface (MIPI)).

(49) According to an embodiment, commands or data may be transmitted or received between the electronic device **101** and the external electronic device **104** via the server **108** coupled with the second network **199**. Each of the electronic devices **102** or **104** may be a device of a same type as, or a different type, from the electronic device **101**. According to an embodiment, all or some of operations to be executed at the electronic device **101** may be executed at one or more of the external electronic devices **102**, **104**, or **108**. For example, if the electronic device **101** should perform a function or a service automatically, or in response to a request from a user or another device, the electronic device **101**, instead of, or in addition to, executing the function or the service, may request the one or more external electronic devices to perform at least part of the function or the service. The one or more external electronic devices receiving the request may perform the at least part of the function or the service requested, or an additional function or an additional service related to the request, and transfer an outcome of the performing to the electronic device **101**. The electronic device **101** may provide the outcome, with or without further processing of the outcome, as at least part of a reply to the request. To that end, a cloud computing, distributed computing, mobile edge computing (MEC), or client-server computing technology may be used, for example. The electronic device **101** may provide ultra low-latency services using, e.g., distributed computing or mobile edge computing. In another embodiment, the external electronic device **104** may include an internet-of-things (IoT) device. The server **108** may be an intelligent server using machine learning and/or a neural network. According to an embodiment, the external electronic device **104** or the server **108** may be included in the second network **199**. The electronic device **101** may be applied to intelligent services (e.g., smart home, smart city, smart car, or healthcare) based on 5G communication technology or IoT-related technology.

(50) FIG. 2A is a perspective view of the front surface of an electronic device **200** (e.g., a mobile electronic device) according to certain embodiments. FIG. 2B is a perspective view of the rear surface of the electronic device **200** in FIG. 2A according to certain embodiments.

(51) Referring to FIGS. 2A and 2B, the electronic device **200** according to an embodiment may include a housing **210** including a first surface (or a front surface) **210A**, a second surface (or a rear surface) **210B**, and a side surface **210C** surrounding a space between the first surface **210A** and the second surface **210B**. In another embodiment (not shown), a housing may indicate a structure forming some of the first surface **210A**, the second surface **210B**, and the side surface **210C** in FIG. 2A. According to an embodiment, the first surface **210A** may be formed of a front plate **202** (e.g., a polymer plate or a glass plate including various coated layers), at least a part of which is substantially transparent. The second surface **210B** may be formed of a rear plate **211** which is substantially opaque. The rear plate **211** may be formed of, for example, coated or colored glass, ceramic, polymer, metal (e.g., aluminum, stainless steel (STS), or magnesium), or a combination of at least two of the materials. The side surface **210C** may be coupled to the front plate **202** and the rear plate **211**, and may be formed of a side bezel structure **218** (or a “side member”) containing

metal and/or polymer. In an embodiment, the rear plate **211** and the side bezel structure **218** may be integrally formed, and may include an identical material (e.g., a metal material, such as aluminum). (52) In the illustrated embodiment, the front plate **202** may include a first region **210D**, curved and seamlessly extending from the first surface **210A** toward the rear plate, at each of both ends of a long edge of the front plate. In the illustrated embodiment (see FIG. 2B), the rear plate **211** may include a second region **210E**, curved and seamlessly extending from the second surface **210B** toward the front plate, at each of both ends of a long edge thereof. In an embodiment, the front plate **202** or the rear plate **211** may include one of the first region **201D** or the second region **201E**. In an embodiment, the front plate **202** may include a flat surface disposed parallel to the second surface **210B** without including the first region and the second region. In the embodiments, when the electronic device is seen from the side, the side bezel structure **218** may have a first thickness (or width) at a side surface which does not include the first region **210D** or the second region **210E**, as described above, and may have a second thickness less than the first thickness at a side surface which includes the first region **210D** or the second region **210E**.

(53) According to an embodiment, the electronic device **200** may include at least one among a display **400**, an input device **203**, sound output devices **207** and **214**, sensor modules **204** and **219**, camera modules **205** and **212**, key input devices **217**, an indicator (not shown), and a connector **208**. In an embodiment, the electronic device **200** may omit at least one (e.g., the key input devices **217** or the indicator) of the elements, or may additionally include another element.

(54) The display **400**, for example, may be visually exposed through a considerable part of the front plate **202**. In an embodiment, at least a part of the display **400** may be exposed through the front plate **202** which forms the first surface **210A**, and the first region **201D** of the side surface **210C**. The display **400** may be coupled to or disposed adjacent to a touch sensing circuit, a pressure sensor capable of measuring the strength (pressure) of a touch, and/or a digitizer for detecting a magnetic field-type stylus pen. In an embodiment, at least some of the sensor modules **204** and **219** and/or at least some of the key input devices **217** may be disposed in the first region **201D** and/or the second region **201E**.

(55) The input device **203** may include a microphone **203**. In an embodiment, the input device **203** may include multiple microphones **203** disposed so as to sense the direction of a sound. The sound output devices **207** and **214** may include speakers **207** and **214**. The speakers **207** and **214** may include an external speaker **207** and a call receiver **214**. In an embodiment, at least some of the microphone **203**, the speakers **207** and **214**, and the connector **208** may be disposed in the inner space of the electronic device **200**, and may be exposed to an outside environment through at least one hole formed in the housing **210**. In an embodiment, the hole formed in the housing **210** may be commonly used for the microphone **203** and the speakers **207** and **214**. In an embodiment, the sound output devices **207** and **214** may include a speaker (e.g., a piezo speaker) operating without the hole formed in the housing **210**.

(56) The sensor modules **204** and **219** may generate electrical signals or data values corresponding to an operation state inside the electronic device **200** or an environment state outside the electronic device **200**. The sensor modules **204** and **219** may include, for example, a first sensor module **204** (e.g., a proximity sensor) and/or a second sensor module (not shown) (e.g., a fingerprint sensor), disposed in the first surface **210A** of the housing **210**, and/or a third sensor module **219** (e.g., an HRM sensor) disposed in the second surface **210B** of the housing **210**. The fingerprint sensor may be disposed under the first surface **210A** (e.g., a home key button) of the housing **210**, a partial region of the second surface **210B**, and/or the display **400**. The electronic device **200** may further include at least one among unillustrated sensor modules, for example, a gesture sensor, a gyro sensor, a barometric pressure sensor, a magnetic sensor, an acceleration sensor, a grip sensor, a color sensor, an infrared (IR) sensor, a biosensor, a temperature sensor, a humidity sensor, a proximity sensor, or an illumination sensor.

(57) The camera modules **205** and **212** may include a first camera module **205** disposed in the first

surface **210A** of the electronic device **200**, a second camera module **212** disposed in the second surface **210B**, and/or a flash **213**. The camera modules **205** and **212** may include one lens or multiple lenses, an image sensor, and/or an image signal processor. The flash **213** may include, for example, a light-emitting diode or a xenon lamp. In an embodiment, at least two lenses (a wide-angle lens, an ultra-wide-angle lens, or a telephoto lens) and image sensors may be disposed in one surface of the electronic device **200**.

(58) The key input devices **217** may be disposed in the side surface **210C** of the housing **210**. In another embodiment, the electronic device **200** may not include some or all of the above-mentioned key input devices **217**, and key input devices **217**, which are not included, may be implemented in other forms, such as soft keys, on the display **400**. In another embodiment, the key input devices **217** may be implemented by using pressure sensors included in the display **400**.

(59) The indicator may be disposed, for example, in the first surface **210A** of the housing **210**. The indicator may provide, for example, state information of the electronic device **200** in the form of light (e.g., a light-emitting element). In another embodiment, the light-emitting element may provide, for example, a light source operating in conjunction with the operation of the first camera module **205**. The indicator may include, for example, an LED, an IR LED and/or a xenon lamp.

(60) The connector hole **208** may include a first connector hole **208** capable of receiving a connector (e.g., a universal serial bus (USB) connector) for transmitting or receiving power and/or data to or from an external electronic device, and/or a second connector hole (or an earphone hole) (not shown) capable of receiving a connector for transmitting or receiving an audio signal to or from the external electronic device.

(61) Some camera modules **205** of the camera modules **205** and **212**, some sensor modules **204** among the sensor modules **204** and **219**, or the indicator may be disposed to be exposed through the display **400**. For example, the first camera module **205**, the first sensor modules **204**, or the indicator may be disposed in the inner space of the electronic device **200** so as to be exposed to an external environment through an opening bored in the display **400** up to the front plate, or through a transmissive region of the display **400**. According to an embodiment, a region in which the display **400** faces the first camera module **205** is a part of a region in which contents are displayed, and may be formed as a transmissive region having a predetermined transmittance. According to an embodiment, the transmissive region may be formed to have a transmittance ranging from about 5% to about 20%. This transmissive region may include a region overlapping an effective aperture (e.g., a field of view) of the first camera module **205**, through which light that is imaged by an image sensor to produce an image passes. For example, the transmissive region of the display **400** may include a region having a pixel density lower than that therearound. For example, the transmissive region may replace the opening. For example, the first camera module **205** may include an under-display camera (UDC). In another embodiment, some sensor modules **204** may be disposed in the inner space of the electronic device so as to perform functions thereof without being visually exposed through the front plate **202**. For example, in this case, a region of the display **400**, which faces the sensor module, may not utilize a bored opening.

(62) According to certain embodiments, the electronic device **200** has a bar-type or plate-type exterior, but the disclosure is not limited thereto. For example, the illustrated electronic device **200** may be a part of a foldable electronic device, a slidable electronic device, a stretchable electronic device, and/or a rollable electronic device. The “foldable electronic device”, the “slidable electronic device”, the “stretchable electronic device”, and/or the “rollable electronic device” may imply an electronic device in which, because the bending deformation of a display (e.g., the display **400** in FIG. 3A) is possible, at least a part of the display may be folded or may be wound or rolled, or the region of the display may be at least partially enlarged and/or received into a housing (e.g., the housing **210** in FIGS. 2A and 2B). In the foldable electronic device, the slidable electronic device, the stretchable electronic device, and/or the rollable electronic device, a screen display region may be extended and used by unfolding a display or exposing the wider area of the display to the

outside according to a user's need.

(63) FIG. 3A is a front perspective view illustrating a flat state or an unfolding state) of an electronic device including a second form according to certain embodiments.

(64) FIG. 3B is a plan view illustrating the front surface of an electronic device in the unfolded state in FIG. 3A according to certain embodiments.

(65) FIG. 3C is a plan view illustrating the rear surface of an electronic device in the unfolded state in FIG. 3A according to certain embodiments.

(66) Referring to FIGS. 3A to 3C, the electronic device **300** may include a pair of housings **310** and **320** (e.g., foldable housings) rotatably coupled to each other so as to be folded while facing each other with reference to a hinge device (e.g., the hinge device **340** in FIG. 3B). In an embodiment, the hinge device (e.g., the hinge device **340** in FIG. 3B) may be disposed in the X-axis direction or may be disposed in the Y-axis direction. In an embodiment, at least two hinge devices (e.g., the hinge device **340** in FIG. 3B) may also be disposed to be folded in an identical direction or in different directions. According to an embodiment, the electronic device **300** may include a flexible display **400** (e.g., a foldable display) disposed in a region formed by the pair of housings **310** and **320**. According to an embodiment, a first housing **310** and a second housing **320** may be disposed at both sides with reference to a folding axis (axis A), and may have shapes substantially symmetric with respect to the folding axis (axis A). According to an embodiment, the angle or the distance between the first housing **310** and the second housing **320** may vary depending on whether the state of the electronic device **300** is an unfolded state (a flat state or unfolding state), a folded state (a folding state), or an intermediate state.

(67) According to certain embodiments, the pair of housings **310** and **320** may include the first housing **310** (e.g., a first housing structure) coupled to the hinge device (e.g., the hinge device **340** in FIG. 3B) and the second housing **320** (e.g., a second housing structure) coupled to the hinge device (e.g., the hinge device **340** in FIG. 3B). According to an embodiment, in an unfolded state, the first housing **310** may include a first surface **311** facing a first direction (e.g., a forward direction) (the z-axis direction) and a second surface **312** opposite to the first surface **311** and facing a second direction (e.g., a backward direction) (−z-axis direction). According to an embodiment, in the unfolded state, the second housing **320** may include a third surface **321** facing a first direction (the z-axis direction) and a fourth surface **322** facing a second direction (−z-axis direction). According to an embodiment, the electronic device **300** may operate in such a manner that the first surface **311** of the first housing **310** and the third surface **321** of the second housing **320** face a substantially identical first direction (the z-axis direction) in the unfolded state and that the first surface **311** and the third surface **321** face each other in the folded state. According to an embodiment, the electronic device **300** may operate in such a manner that the second surface **312** of the first housing **310** and the fourth surface **322** of the second housing **320** face a substantially identical second direction (the −z-axis direction) in the unfolded state and that the second surface **312** and the fourth surface **322** face directions opposite to each other in the folded state. For example, in the folded state, the second surface **312** may face the first direction (the z-axis direction), and the fourth surface **322** may face the second direction (the −z-axis direction).

(68) According to certain embodiments, the first housing **310** may include a first side member **313** at least partially forming the exterior of the electronic device **300** and a first rear cover **314** coupled to the first side member **313** and forming at least a part of the second surface **312** of the electronic device **300**. According to an embodiment, the first side member **313** may include a first side surface **313a**, a second side surface **313b** extending from one end of the first side surface **313a**, and a third side surface **313c** extending from the other end of the first side surface **313a**. According to an embodiment, the first side member **313** may be formed in a right-angled tetragonal (e.g., square or rectangular) shape through the first side surface **313a**, the second side surface **313b**, and the third side surface **313c**.

(69) According to certain embodiments, the second housing **320** may include a second side member

323 at least partially forming the exterior of the electronic device **300**, and a second rear cover **324** coupled to the second side member **323** and forming at least a part of the fourth surface **322** of the electronic device **300**. According to an embodiment, the second side member **323** may include a fourth side surface **323a**, a fifth side surface **323b** extending from one end of the fourth side surface **323a**, and a sixth side surface **323c** extending from the other end of the fourth side surface **323a**. According to an embodiment, the second side member **323** may be formed in a right-angled tetragonal shape through the fourth side surface **323a**, the fifth side surface **323b**, and the sixth side surface **323c**.

(70) According to certain embodiments, the pair of housings **310** and **320** are not limited to the illustrated form and coupling, and may be implemented by other shapes or a combination and/or coupling of other components. For example, in an embodiment, the first side member **313** may be formed integrally with the first rear cover **314**, and the second side member **323** may be formed integrally with the second rear cover **324**.

(71) According to certain embodiments, when the electronic device **300** is in an unfolded state, the second side surface **313b** of the first side member **313** and the fifth side surface **323b** of the second side member **323** may be connected to each other without any gap therebetween. According to an embodiment, when the electronic device **300** is in an unfolded state, the third side surface **313c** of the first side member **313** and the sixth side surface **323c** of the second side member **323** may be connected to each other without any gap therebetween. According to an embodiment, when the electronic device **300** is in an unfolded state, a length obtained by summing the second side surface **313b** and the fifth side surface **323b** may be configured to be greater than the length of the first side surface **313a** and/or the fourth side surface **323a**. Furthermore, a length obtained by summing the third side surface **313c** and the sixth side surface **323c** may be configured to be greater than the length of the first side surface **313a** and/or the fourth side surface **323a**.

(72) According to certain embodiments, the first rear cover **314** and/or the second rear cover **324** may be formed of at least one or a combination of at least two among, for example, coated or colored glass, ceramic, polymer, or metal (e.g., aluminum, stainless steel (STS), or magnesium).

(73) According to certain embodiments, the flexible display **400** may be disposed to extend from the first surface **311** of the first housing **310** to at least a part of the third surface **321** of the second housing **320** via the hinge device (e.g., the hinge device **340** in FIG. 3B). For example, the flexible display **400** may include a first part **330a** substantially corresponding to the first surface **311**, a second part **330b** corresponding to the third surface **321**, and a third part **330c** (e.g., a bendable region) connecting the first part **330a** to the second part **330b** and corresponding to the hinge device (e.g., the hinge device **340** in FIG. 3B). According to an embodiment, the electronic device **300** may include a first protective cover **315** (e.g., a first protective frame or a first decoration member) coupled along the edge of the first housing **310**. According to an embodiment, the electronic device **300** may include a second protective cover **325** (e.g., a second protective frame or a second decoration member) coupled along the edge of the second housing **320**. According to an embodiment, the first protective cover **315** and/or the second protective cover **325** may be formed of a metal or polymer material. According to an embodiment, the first protective cover **315** and/or the second protective cover **325** may be used as decoration members. According to an embodiment, the flexible display **400** may be positioned such that the edge of the first part **330a** is interposed between the first housing **310** and the first protective cover **315**. According to an embodiment, the flexible display **400** may be positioned such that the edge of the second part **330b** is interposed between the second housing **320** and the second protective cover **325**. According to an embodiment, the flexible display **400** may be positioned such that the edge of the flexible display **400**, corresponding to a protective cap **335** disposed in a region corresponding to the hinge device (e.g., the hinge device **340** in FIG. 3B), is protected through the protective cap. Therefore, the edge of the flexible display **400** may be substantially protected from the outside. According to an embodiment, the electronic device **300** may include a hinge housing **341** (e.g., a hinge cover)

disposed to support the hinge device (e.g., the hinge device **340** in FIG. 3B), be exposed outside when the electronic device **300** is in a folded state, and be moved into a first space (e.g., in the inner space of the first housing **310**) and a second space (e.g., the inner space of the second housing **320**) when the electronic device **300** is in an unfolded state and thus be not viewed from outside. In an embodiment, the flexible display **400** may be disposed to extend from at least a part of the second surface **312** to at least a part of the fourth surface **322**. In this case, the electronic device **300** may be folded such that the flexible display **400** is exposed outside (an out-folding method).

(74) According to certain embodiments, the electronic device **300** may include a sub-display **331** disposed separately from the flexible display **400**. According to an embodiment, the sub-display **331** may be disposed to be at least partially disposed on the second surface **312** of the first housing **310**, and thus, in the folded state, may display state information of the electronic device **300** replacing a display function of the flexible display **400**. According to an embodiment, the sub-display **331** may be disposed so as to be viewed from outside through at least a partial region of the first rear cover **314**. In an embodiment, the sub-display **331** may be disposed on the fourth surface **322** of the second housing **320**. In this case, the sub-display **331** may be disposed so as to be exposed from outside through at least a partial region of the second rear cover **324**.

(75) According to certain embodiments, the electronic device **300** may include at least one among an input device **303** (e.g., a microphone), sound output devices **301** and **302**, sensor modules **304**, camera devices **305** and **308**, key input devices **306**, or a connector port **307**. In the illustrated embodiment, the input device **303** (e.g., the microphone), the sound output devices **301** and **302**, the sensor modules **304**, the camera devices **305** and **308**, the key input devices **306**, or the connector port **307** may indicate a hole or a shape formed in the first housing **310** or the second housing **320**, but may be defined as including a substantial electronic component which is disposed in the electronic device **300** and operates through a hole or a shape (e.g., the input device, the sound output device, the sensor module, or the camera device).

(76) According to certain embodiments, the input device **303** may include at least one microphone **303** disposed in the second housing **320**. In an embodiment, the input device **303** may include multiple microphones **303** disposed to sense the direction of a sound. In an embodiment, the multiple microphones **303** may be disposed in appropriate positions at the first housing **310** and/or the second housing **320**. According to an embodiment, the sound output devices **301** and **302** may include speakers **301** and **302**. According to an embodiment, the speakers **301** and **302** may include a call receiver **301** disposed at the first housing **310** and a speaker **302** disposed at the second housing **320**. In an embodiment, the input device **303**, the sound output devices **301** and **302**, and the connector port **307** may be disposed in a space provided in the first housing **310** and/or the second housing **320** of the electronic device **300**, and may be exposed to an external environment through at least one hole formed in the first housing **310** and/or the second housing **320**. According to an embodiment, at least one connector port **307** may be used to transmit or receive power and/or data to or from an external electronic device. In an embodiment, at least one connector port (e.g., an earphone jack hole) may receive a connector (e.g., an earphone jack) for transmitting or receiving an audio signal to or from an external electronic device. In an embodiment, holes formed in the first housing **310** and/or the second housing **320** may be commonly used for the input device **303** and the sound output devices **301** and **302**. In an embodiment, the sound output devices **301** and **302** may include a speaker (e.g., a piezo speaker) operating without holes formed in the first housing **310** and/or the second housing **320**.

(77) According to certain embodiments, the sensor modules **304** may generate electrical signals or data values corresponding to an operation state inside the electronic device **300** or an environment state outside the electronic device **300**. The sensor modules **304** may detect an external environment through, for example, the first surface **311** of the first housing **310**. In an embodiment, the electronic device **300** may further include at least one sensor module disposed to detect an external environment through the second surface **312** of the first housing **310**. According to an

embodiment, the sensor modules **304** (e.g., an illumination sensor) may be disposed under the flexible display **400** so as to detect an external environment through the flexible display **400**. According to an embodiment, the sensor modules **304** may include at least one among a gesture sensor, a gyro sensor, a barometric pressure sensor, a magnetic sensor, an acceleration sensor, a grip sensor, a color sensor, an infrared (IR) sensor, a biosensor, a temperature sensor, a humidity sensor, an illumination sensor, a proximity sensor, or an ultrasonic sensor.

(78) According to certain embodiments, the camera devices **305** and **308** may include a first camera device **305** (e.g., a front camera device) disposed in the first surface **311** of the first housing **310**, and a second camera device **308** disposed in the second surface **312** of the first housing **310**. The electronic device **300** may further include a flash **309** disposed near the second camera device **308**. According to an embodiment, the camera devices **305** and **308** may include one or multiple lenses, an image sensor, and/or an image signal processor. The flash **309** may include, for example, a light-emitting diode or a xenon lamp. According to an embodiment, the camera devices **305** and **308** may be disposed such that at least two lenses (a wide-angle lens, an ultra-wide-angle lens, or a telephoto lens) and image sensors are positioned in one surface (e.g., the first surface **311**, the second surface **312**, the third surface **321**, or the fourth surface **322**) of the electronic device **300**. In an embodiment, the camera devices **305** and **308** may also include an image sensor and/or lenses for time of flight (TOF).

(79) According to certain embodiments, the key input devices **306** (e.g., a key button) may be disposed in the third side surface **313c** of the first side member **313** of the first housing **310**. In an embodiment, the key input devices **306** may also be disposed in at least one side surface among the other side surfaces **313a** and **313b** of the first housing **310** and/or side surfaces **323a**, **323b**, and **323c** of the second housing **320**. In an embodiment, the electronic device **300** may not include some or all of the key input devices **306**, and key input devices **306**, which are not included, may be implemented in other forms, such as soft keys, on the flexible display **400**. In an embodiment, the key input devices **306** may also be implemented using pressure sensors included in the flexible display **400**.

(80) According to certain embodiments, some camera devices (e.g., the first camera device **305**) of the camera devices **305** and **308** or the sensor modules **304** may be disposed to be exposed through the flexible display **400**. For example, the first camera device **305** or the sensor modules **304** may be disposed in the inner space of the electronic device **300** so as to be exposed to an external environment through an opening (e.g., a through-hole) at least partially formed in the flexible display **400**. In another embodiment, some sensor modules **304** may also be disposed in the inner space of the electronic device **300** so as to perform functions thereof without being visually exposed through the flexible display **400**. For example, in this case, a region of the flexible display **400**, facing the sensor modules, may not utilize an opening.

(81) FIG. **4** is an exploded perspective view of a display **400** according to certain embodiments.

(82) The display **400** in FIG. **4** may be at least partially similar to the display module **160** in FIG. **1**, or may further include another embodiment of a display.

(83) Referring to FIG. **4**, the display **400** may include a polarizer (POL) (**432**) (e.g., a polarizing film or a polarizing layer), a display panel **431**, and at least one subsidiary material layer **440** attached to the rear surface of the display panel **431**, which are sequentially disposed on the rear surface of a front cover **420** (e.g., a front plate, a glass plate, a first cover member, or a cover member) through an adhesive member (e.g., an adhesive member **410** in FIG. **5A**). According to an embodiment, the adhesive member **410** may include an optical clear adhesive (OCA), a pressure sensitive adhesive (PSA), a thermo-responsive adhesive, a normal adhesive, or a double-sided tape. According to an embodiment, the display panel **431** and the POL **432** may be integrally formed.

(84) According to certain embodiments, the display **400** may include a control circuit (not shown). According to an embodiment, the control circuit may include a flexible printed circuit board (FPCB) configured to electrically connect a main printed circuit board of an electronic device (e.g.,

the electronic device **200** in FIG. 2A) to the display panel **431**, and a display driver IC (DDI) mounted on the FPCB. According to an embodiment, the display **400** may additionally include a touch panel **433**. According to an embodiment, when the display **400** operates as an in-cell-type or on-cell-type touch display according to the placement position of the touch panel **433**, the control circuit may include a touch display driver IC (TDDI). In another embodiment, the display **400** may include a fingerprint sensor (not shown) disposed near the control circuit. According to an embodiment, the fingerprint sensor may include an ultrasonic or optical fingerprint sensor capable of recognizing a fingerprint of a finger which touches or approaches the outer surface of the front cover **420** through holes at least partially formed in some of the elements of the display **400**.

(85) According to certain embodiments, the at least one subsidiary material layer **440** may include at least one polymer member **441** or **442** disposed on the rear surface of the display panel **431**, at least one functional member **443** disposed on the rear surface of the at least one polymer member **441** or **442**, and a conductive member **444** disposed on the rear surface of the at least one functional member **443**. According to an embodiment, the at least one polymer member **441** or **442** may include a light-blocking layer **441** (e.g., a black layer including uneven patterns) for removing bubbles generated between the display panel **431** and attachments thereunder and blocking light generated in the display panel **431** or light entering from the outside and/or a buffer layer **442** disposed to moderate an impact. According to an embodiment, the at least one functional member **443** may include a heat dissipation sheet (e.g., a graphite sheet) for heat dissipation, an added display, a force touch FPCB, a fingerprint sensor FPCB, an antenna radiator of communication, a conductive/nonconductive tape, or an open cell sponge. According to an embodiment, the conductive member **444**, which is metal plate, may contribute to reinforcement of the rigidity of an electronic device (e.g., the electronic device **200** in FIG. 2), and may be used to shield ambient noise and dissipate heat emitted from ambient heat-emitting components. According to an embodiment, the conductive member **444** may include Cu, Al, Mg, SUS, or CLAD (e.g., a lamination member in which SUS and Al are alternately disposed). In another embodiment, the display **400** may further include a detection member **445** for detecting an input by an electromagnetic induction type writing member (e.g., an electronic pen). According to an embodiment, the detection member **445** may include a digitizer. According to an embodiment, the detection member **445** may be disposed between the at least one polymer member **442** and the functional member **443**. In another embodiment, the detection member **445** may also be disposed between the display panel **431** and the at least one polymer member **441**. In another embodiment, the detection member **445** may be disposed on the rear surface of the conductive member **444**.

(86) According to certain embodiments, the subsidiary material layer **440** may include openings **4411**, **4421**, **4451**, and **4441** formed in positions corresponding to a camera module (e.g., a camera module **500** in FIG. 5A). According to an embodiment, the camera module **500** may be disposed close to the rear surface of the display panel **431** through openings **4411**, **4421**, **4451**, and **4441**. According to an embodiment, the POL **432** or the touch panel **433** disposed on the display panel **431** may also include an opening **4321** or **4331** formed therethrough at a corresponding position in order to prevent the degradation of performance of the camera module **500** due to a refractive index. In another embodiment, at a position corresponding to the camera module **500**, the POL **432** and/or the touch panel **433** may be transparently processed, or polarization characteristics may be removed. In another embodiment, layers with no opening (e.g., the display panel **431**) and/or the touch panel **433** may include a coated layer capable of performing index matching in order to reduce a refractive index difference. According to an embodiment, the display **400** may include an organic light emitting diode (OLED) display or a liquid crystal display (LCD).

(87) FIG. 5A is a partial cross-sectional view of the electronic device **200**, taken along line 5-5 in FIG. 2A according to certain embodiments.

(88) In describing FIG. 5A, the description is made by using an unbreakable (UB) type OLED display (e.g., a curved display) as an example, but is not limited thereto. For example, the

description may be applied to a flat type display of an on-cell touch active matrix organic light-emitting diode (AMOLED) (OCTA) scheme.

(89) Referring to FIG. 5A, the electronic device **200** may include a front cover **420** (e.g., a cover member, a front plate, a front window, or a first plate) facing a first direction (the z-axis direction), a rear cover **680** (e.g., a rear cover member, a rear plate, a rear window, or a second plate) facing a direction opposite to the direction faced by the front cover **420**, and a side member **610** surrounding a space **2001** between the front cover **420** and the rear cover **680**. According to an embodiment, the electronic device **200** may include a first waterproof member **4201** disposed between a subsidiary material layer **440** of a display **400** and the side member **610**. According to an embodiment, the electronic device **200** may include a second waterproof member **6801** disposed between the side member **610** and the rear cover **680**. The first waterproof member **4201** and the second waterproof member **6801** may prevent outside foreign matter or water from being introduced into the inner space **2001** of the electronic device **200**. In another embodiment, a waterproof member may be disposed in at least a part of a mounting support structure between a camera module **500** and the side member **610**. In another embodiment, the first waterproof member **4201** and/or the second waterproof member **6801** may be replaced with an adhesive member.

(90) According to certain embodiments, the side member **610** may further include a first support member **611** which at least partially extends into the inner space **2001** of the electronic device **200**. According to an embodiment, the first support member **611** may be formed by a structural coupling with the side member **610**. According to an embodiment, the first support member **611** may support the camera module **500** such that the camera module **500** is aligned and disposed near the rear surface of a display panel **431** through an opening (e.g., an opening (OP) in FIG. 5B) of the subsidiary material layer **440** of the display **400**.

(91) According to certain embodiments, the camera module **500** may include a camera housing **510**, a lens housing **520** disposed in an inner space **5101** of the camera housing **510** and at least partially protruding in a display direction (e.g., the z-axis direction), multiple lenses **530** (**531**, **532**, **533**, and **534**) aligned at regular intervals in an inner space **5201** of the lens housing **520**, and at least one image sensor **540** disposed in the inner space **5101** of the camera housing **510** so as to acquire at least a part of light having passed through the multiple lenses **530**. According to an embodiment, when the camera module **500** includes an auto focus (AF) function, the lens housing **520** may move through a predetermined driving unit in the camera housing **510** such that the distance to the display panel **431** varies. According to an embodiment, a separate driving unit may be disposed such that the camera module **500** changes the position of at least one of the multiple lenses **530** in order to perform the AF function. In another embodiment, in the camera module **500**, the camera housing **510** may be omitted, and the lens housing **520** may be directly disposed at the first support member **611** through a predetermined alignment process. According to an embodiment, when the lens housing **520** is directly disposed at the first support member **611**, the camera housing **510** may be omitted in order to reduce a camera arrangement space, and the lens housing **520** may be disposed to be attached to one side surface of the first support member **611**. According to an embodiment, the camera module **500** may be aligned through a through-hole **601** of the first support member **611**, and then may be attached to the rear surface of the first support member **611** by an adhesive member **612** (e.g., a bonding member or a tape member).

(92) According to certain embodiments, the display **400** may include a touch panel (e.g., the touch panel **433** in FIG. 4), a POL **432**, a display panel **431**, a light-blocking layer **441**, a buffer layer (e.g., the buffer layer **442** in FIG. 4), a digitizer (e.g., the detection member **445** in FIG. 4), a functional member (e.g., the functional member **443** in FIG. 4), and/or a conductive member (e.g., the conductive member **444** in FIG. 4). According to an embodiment, the camera module **500** may be supported by a second support member **660** (e.g., a rear case) additionally disposed in the inner space of the electronic device.

(93) FIG. 5B is an enlarged view of region **6** in FIG. 5A according to certain embodiments.

(94) Referring to FIG. 5B, the electronic device **200** may include an adhesive member **410**, the POL **432**, the display panel **431**, and the subsidiary material layer **440**, which are disposed between the rear surface of the front cover **420** and the side member **610**. According to an embodiment, when the front cover **420** is seen from above, the POL **432** may include an opening **4321** formed in order to improve an optical transmittance of the camera module **500**. In another embodiment, in the adhesive member **410** disposed on the POL **432**, a part corresponding to the opening **4321** may be at least partially omitted. In an embodiment, the opening **4321** formed in the POL **432** may be filled with an index material for adjusting the refractive index according to an increase in interfacial reflection. According to an embodiment, the POL **432** may be omitted, and may also be replaced with a color filter layer including a color filter and a black mask in the corresponding position thereof. In this case, the color filter layer may also include an opening in order to improve an optical transmittance of the camera module.

(95) According to an embodiment, a region of the POL **432** corresponding to the multiple lenses **530** may be formed to have a high transmittance without having the opening **4321** formed therethrough. For example, at least a partial region of the POL **432** (e.g., a region corresponding to the multiple lenses **530**) may be formed of a material having a transmittance different from that of the remaining region of the POL **432**, or may be formed of another member capable of increasing a transmittance. According to an embodiment, a member (not shown) for increasing a transmittance may be disposed on at least a part (e.g., an upper side surface or a lower side surface) of the region of the POL **432** corresponding to the multiple lenses **530**. According to an embodiment, when the front cover **420** is seen from above, the subsidiary material layer **440** may include an opening (OP) formed in a region at least partially overlapping the multiple lenses **530**. According to an embodiment, the opening (OP) formed in the subsidiary material layer **440** may be formed as one opening (OP) by overlapping an opening (e.g., the opening **4411** in FIG. 4) formed in a light-blocking layer **441**, an opening (e.g., the opening **4421** in FIG. 4) formed in the buffer layer **442**, an opening (e.g., the opening **4431** in FIG. 4) formed in the functional member **443**, and an opening (e.g., the opening **4441** in FIG. 4) formed in the conductive member **444**. According to an embodiment, the openings may have different sizes so as to correspond to the shape of the camera module **500**.

(96) According to certain embodiments, when the display **400** is seen from above, the display panel **431** may include a first region **A1**, which overlaps an effective aperture of the camera module **500**, and a second region **A2** surrounding the first region **A1**. According to an embodiment, the first region **A1** may be formed to have a light transmittance utilized by the camera module **500** through adjustment of a pixel density and/or a wiring density. According to an embodiment, the second region **A2** may include a normal active region of the display panel **431**. According to an embodiment, the second region **A2** may be a region in which a light transmittance for the camera module **500** has not been taken into account. According to an embodiment, the display panel **431** may include first multiple pixels (e.g., **P** in FIG. 6), arranged to have a first arrangement density in the first region **A1**, and second multiple pixels (e.g., **P** in FIG. 6) having a second arrangement density, higher than the first arrangement density, in the second region **A2**. In an embodiment, the wiring density of the first region **A1** may be formed to be lower than the wiring density of the second region **A2**, thereby contributing to transmittance improvement.

(97) FIG. 6 illustrates a partial configuration of a display panel when region **7** in FIG. 5B according to certain embodiments of the disclosure is seen from above.

(98) Referring to FIG. 6, when the display **400** is seen from above, the display panel may include a first region **A1** overlapping an effective aperture of the camera module **500**, and a second region **A2** surrounding the first region **A1**. According to an embodiment, the display panel **431** may include first multiple pixels **P** arranged to have a first arrangement density in the first region **A1** and second multiple pixels **P** having a second arrangement density higher than the first arrangement density in the second region **A2**. According to an embodiment, when the display panel **431** is seen from

above, the first region A1 of the display panel **431** may include first sub-regions SA1 overlapping spaces between the multiple pixels P and second sub-regions SA2 overlapping the multiple pixels P and light emitters.

(99) According to certain embodiments, a light extractor **4315** may be disposed at a part of a first sub-region SA1 in which pixels P are not arranged. For example, the light extractor **4315** may be disposed to have a designated width along the edge of the first sub-region SA1. This is for the purpose of preventing light emitted from a second sub-region SA2 from being color-mixed with light emitted from an adjacent pixel. According to an embodiment, light injector **4316** may be disposed at a part of a second sub-region SA2. According to an embodiment, the light injector **4316** may be disposed to have a designated width along the edge of the second sub-region SA2. In an embodiment, the light injector **4316** may be disposed at the entirety of the second sub-region SA2. In an embodiment, in order to reduce visibility of the boundary between the first region A1 and the second region A2, a light injector **4316-1** may be further disposed to have a designated width in the second region A2 at a boundary part (B) between the first region A1 and the second region A2.

(100) FIG. 7 is a block diagram of an electronic device **101** according to certain embodiments.

(101) Referring to FIG. 7, the electronic device **101** may include a processor **120** (e.g., the processor **120** in FIG. 1), a first display **161**, a second display **162**, a first camera **181**, and/or a second camera **182**. The electronic device **101** may include at least some among the elements and/or functions of the electronic device **101** in FIG. 1.

(102) According to certain embodiments, the first display **161** may visually display information to the outside (e.g., a user) of the electronic device **101**. The first display **161** may include at least some among the elements and/or functions of the display module **160** in FIG. 1. According to an embodiment, the first display **161** may include a touch sensor or a pressure sensor, which is configured to sense a touch. According to certain embodiments, the first display **161** may include multiple pixels (e.g., the multiple pixels P in FIG. 6) in at least a partial region thereof. According to an embodiment, each of the multiple pixels may be controlled by the processor **120** and/or a driving circuit for controlling the first display **161** to emit light, thereby displaying visual information to the outside of the electronic device **101**. According to an embodiment, the first display **161** may include at least two regions (e.g., the first region A1 and/or the second region A2 in FIG. 6) which are different from each other in the arrangement density of multiple pixels. The first region A1 and the second region A2 on the first display **161** may have different pixel arrangement densities, and thus the respective regions may have different light transmittances. For example, the first region A1 may include multiple pixels with a relatively low arrangement density (e.g., a first arrangement density) compared with the second region A2, and the second region A2 may include multiple pixels with a relatively high arrangement density (e.g., a second arrangement density) compared with the first region A1. In a region (e.g., the first region A1) having a relatively lower arrangement density among the regions of the first display **161**, the light transmittance of a display may be higher than in the other region. According to an embodiment, a partial region (e.g., the first region A1) of the first display **161** may be deactivated. For example, the first region A1, among the regions of the first display **161**, may be deactivated, and the second region A2 may be activated. When a partial region of the first display **161** is deactivated, at least one pixel disposed in the deactivated region may be deactivated. The deactivated or activated state of the partial region of the first display **161** may be controlled and switched by the processor **120** and/or the driving circuit, which are connected to the first display **161**. According to an embodiment, the first region A1 of the first display **161** may be disposed to at least partially overlap a field-of-view region corresponding to the field of view (FOV) of the first camera **181**.

(103) According to certain embodiments, the second display **162** may visually display information to the outside (e.g., a user) of the electronic device **101**. The second display **162** may include at least some among the elements and/or functions of the display module **160** in FIG. 1. According to an embodiment, the second display **162** may include a touch sensor or a pressure sensor, which is

configured to sense a touch. According to certain embodiments, the second display **162** may include multiple pixels (e.g., the multiple pixels P in FIG. **6**) in at least a partial region thereof. According to an embodiment, each of the multiple pixels may be controlled by the processor **120** and/or a driving circuit for controlling the second display **162** to emit light, thereby displaying visual information to the outside of the electronic device **101**. According to an embodiment, the second display **162** may include at least two regions (e.g., a third region and/or a fourth region) (e.g., the first region A1 and/or the second region A2 in FIG. **6**) which are different from each other in the arrangement density of multiple pixels. The third region and the fourth region on the second display **162** may have different pixel arrangement densities, and thus the respective regions may have different light transmittances. For example, the third region may include multiple pixels with a relatively low arrangement density (e.g., a first arrangement density) compared with the fourth region, and the fourth region may include multiple pixels with a relatively high arrangement density (e.g., a second arrangement density) compared with the third region. In a region (e.g., the third region) having a relatively lower arrangement density among the regions of the second display **162**, the light transmittance of a display may be higher than in the other region. According to an embodiment, a partial region (e.g., the third region) of the second display **162** may be deactivated. For example, the third region, among the regions of the second display **162**, may be deactivated, and the fourth region may be activated. When a partial region of the second display **162** is deactivated, at least one pixel disposed in the deactivated region may be deactivated. The deactivated or activated state of the partial region of the second display **162** may be controlled and switched by the processor **120** and/or the driving circuit, which are connected to the second display **162**. According to an embodiment, the third region of the second display **162** may be disposed to at least partially overlap a field-of-view region corresponding to the field of view (FOV) of the second camera **182**.

(104) According to an embodiment, the electronic device **101** may include at least one of the first display **161** and the second display **162**, and may include the first display **161** without including the second display **162**.

(105) According to an embodiment, when one display among the first display **161** and the second display **162** may be driven to display visual information to the outside, the other display may be deactivated, or the first display **161** and the second display **162** may be simultaneously activated.

(106) According to certain embodiments, the first camera **181** may capture a still image or a moving image. The first camera **181** may include at least some of the elements or functions of the camera module **180** in FIG. **1**. According to certain embodiments, the first camera **181** may convert light incident from the outside to an electrical signal to generate image information. According to certain embodiments, the first camera **181** may capture an image of an environment outside the electronic device **101** and may generate image information obtained by capturing an ambient environment. According to an embodiment, the first camera **181** may be disposed such that a region corresponding to the field of view (FOV) thereof overlaps at least a partial region (e.g., the first region A1) of the first display **161**.

(107) According to certain embodiments, the second camera **182** may capture a still image or a moving image. The second camera **182** may include at least some of the elements or functions of the camera module **180** in FIG. **1**. According to certain embodiments, the second camera **182** may convert light incident from the outside to an electrical signal to generate image information. According to certain embodiments, the second camera **182** may capture an image of an environment outside the electronic device **101** and may generate image information obtained by capturing an ambient environment. According to an embodiment, the second camera **182** may be disposed such that a region corresponding to the field of view (FOV) thereof overlaps at least a partial region (e.g., the third region) of the second display **162**.

(108) According to an embodiment, the electronic device **101** may include at least one of the first camera **181** and the second camera **182**, and may include the first camera **181** without including the

second camera **182**.

(109) According to an embodiment, when one camera among the first camera **181** and the second camera **182** may be driven to capture an image outside the electronic device **101**, the other camera may be deactivated, or the first camera **181** and the second camera **182** may be simultaneously activated.

(110) According to certain embodiments, the processor **120** may control each of the elements of the electronic device **101** and/or may process calculation or data regarding communication. The processor **120** may include at least some of the elements and/or functions of the processor **120** in FIG. **1**. The processor **120** may be operatively, electrically, and/or functionally connected to the elements of the electronic device **101**, such as the first display **161**, the second display **162**, the first camera **181** and/or the second camera **182**. Each operation of the processor **120** according to certain embodiments may be performed in real time. For example, multiple operations performed by the processor **120** may be substantially simultaneously performed. Operations, which may be performed by the processor **120**, and the type and/or amount of calculation and data processing will not be limited. However, herein, a description will be made solely of a method for changing a user interface according to certain embodiments, and elements and functions of the processor **120** related to an operation of performing the method.

(111) According to certain embodiments, the processor **120** may control the first display **161** and/or the second display **162** to display a user interface. The user interface may include at least one graphical object which is visually displayed. According to an embodiment, the user interface may include a graphical user interface. At least one object included in the user interface may include an image object which may be visually displayed on a display (e.g., the first display **161** and/or the second display **162**). According to an embodiment, the at least one object included in the user interface may include an image object for displaying a region for reception of a user input, displaying information about the electronic device **101** or an application, or displaying an execution screen or a related object together in a predetermined region. For example, the object may include an icon, an input field, a badge, a button, a display window, a widget, and/or a tool bar. According to an embodiment, the object may include an object, which is visually displayed on the display, such as an image, text, and/or a figure indicating a predetermined region on the display. The object included in the user interface is not limited to the above-mentioned examples.

(112) According to an embodiment, the processor **120** may activate at least one of the first display **161** and the second display **162**, and may display the user interface including the at least one object on the first display **161** and/or the second display **162**. According to an embodiment, the processor **120** may activate one of the first display **161** and the second display **162**, and may switch one of the first display **161** and the second display **162** from the activated state to a deactivated state while switching the other deactivated display to an activated state. According to another embodiment, the processor **120** may simultaneously activate the first display **161** and the second display **162** to display the user interface on each display.

(113) According to certain embodiments, the processor **120** may capture an image. According to an embodiment, the processor **120** may use the first camera **181** and/or the second camera **182** to capture a still image and/or a moving image. The processor **120** may receive an input about capturing of a still image and/or a moving image, and may control, based on the received input, the first camera **181** and/or the second camera **182** to capture the still image and/or the moving image. According to an embodiment, the input about image capturing, received by the processor **120**, may include an input for activating a camera (e.g., the first camera **181** and/or the second camera **182**). The processor **120** may receive the input about image capturing, and may activate one of the first camera **181** and the second camera **182**. According to an embodiment, the input about image capturing may include an input for switching, while one camera of the first camera **181** or the second camera **182** is activated, the other camera to an activated state.

(114) According to certain embodiments, the processor **120** may activate one of cameras (e.g., the

first camera **181** and/or the second camera **182**), and may determine the activated camera. According to an embodiment, the processor **120** may determine whether the activated camera is the first camera **181** or the second camera **182**.

(115) According to certain embodiments, the processor **120** may deactivate at least a partial region of the region of a display (e.g., the first display **161** and/or the second display **162**). According to an embodiment, when a camera (e.g., the first camera **181** and/or the second camera **182**) is activated, the processor **120** may deactivate a pixel included in at least a partial region of the display, which corresponds to the camera or the field of view of the camera. According to an embodiment, the first display **161** may include a first region (e.g., the first region **A1** in FIG. 5B) overlapping an effective aperture or the field of view of the first camera **181** and a second region (e.g., the second region **A2** in FIG. 5B) surrounding the first region **A1**. According to an embodiment, the first region **A1** may be formed to have light transmittance utilized by the first camera **181** by adjusting a pixel density and/or a wiring density to be relatively low. According to an embodiment, the second region **A2** may include a normal active area, that is, a region in which a pixel density and/or a wiring density is high compared with the first region **A1**. According to an embodiment, the second region **A2** may be a region in which the light transmittance for the camera (e.g., the first camera **181**) is not considered. According to an embodiment, when the first camera **181** is activated, the processor **120** may deactivate at least one pixel corresponding to the first region **A1** on the first display **161**. According to an embodiment, the processor **120** may deactivate at least some of multiple pixels corresponding to the first region **A1**. According to an embodiment, the processor **120** may deactivate all pixels corresponding to the first region **A1**. According to an embodiment, the second display **162** may include a third region (e.g., the first region **A1** in FIG. 5B) overlapping the effective aperture or the field of view of the second camera **182** and a fourth region (e.g., the second region **A2** in FIG. 5B) surrounding the third region. According to an embodiment, the third region may be formed to have light transmittance utilized by the second camera **182** by adjusting a pixel density and/or a wiring density to be relatively low. According to an embodiment, the fourth region may include a normal active area, that is, a region in which a pixel density and/or a wiring density is high compared with the third region. According to an embodiment, the fourth region may be a region in which the light transmittance for the camera (e.g., the second camera **182**) is not considered. According to an embodiment, when the second camera **182** is activated, the processor **120** may deactivate at least one pixel corresponding to the third region on the second display **162**. According to an embodiment, the processor **120** may deactivate at least some of multiple pixels corresponding to the third region. According to an embodiment, the processor **120** may deactivate all pixels corresponding to the third region.

(116) According to certain embodiments, the processor **120** may change a user interface so as to correspond to at least a part of the remaining region, which is not deactivated, in the region of the first display **161** and/or the second display **162**. According to an embodiment, the processor **120** may change a user interface so as to correspond to the second region **A2** on the first display **161**. The second region may include at least a partial region of the remaining region of the first display **161**, which surrounds the first region **A1**. The processor **120** may distinguish the first region **A1** and the second region **A2** in the remaining region other than the first region **A1** on the first display **161**. According to an embodiment, the processor **120** may read data designated about the range of the second region **A2** in a memory (e.g., the memory **130** in FIG. 1) to determine the second region **A2**. According to an embodiment, the processor **120** may determine the first region **A1**, and may determine that a region within a designated distance from the first region **A1** in the region of the first display **161** is the second region. According to an embodiment, the processor **120** may determine that a region including a graphical object (e.g., a window or a tool bar), which overlaps the first region **A1** among graphical objects displayed on the first display **161** or is displayed in a region within the designated distance from the first region **A1**, is the second region. In this case, the shape and/or size of the second region may be changed based on a user interface.

(117) According to certain embodiments, the processor **120** may change a user interface. Changing of a user interface may include operations for movement, enlargement, reduction, shape change, addition, and/or removal of at least one graphical object included in the user interface. According to an embodiment, the processor **120** may change, based on the second region **A2**, an object included in a user interface. According to an embodiment, the processor **120** may change a user interface, based on the form (e.g., shape or configuration) of the second region **A2**. The processor **120**, for example, may move, based on the shape of the determined second region **A2**, multiple objects included in a user interface to realign or rearrange the multiple objects. Since the first region **A1** may be in a deactivated state, the second region **A2** may include a region other than the first region **A1**. According to an embodiment, the processor **120** may change a user interface by changing, among objects included in the user interface, an object overlapping the first region **A1**, an object positioned within the designated distance from the first region **A1**, and/or objects adjacent thereto.

(118) According to certain embodiments, the processor **120** may determine information about the position of at least one object included in the user interface. For example, the processor **120** may determine information about a position in which a graphical object is displayed on the first display **161**.

(119) According to certain embodiments, the processor **120** may change a user interface, based on information about a position in which an object included in the user interface is displayed on the first display **161** and information about the position of the first region **A1** on the first display **161**. According to an embodiment, the processor **120** may change the user interface when a position, in which at least one graphical object is displayed on the first display **161**, overlaps the first region **A1**. According to an embodiment, the processor **120** may change the user interface when a position, in which at least one graphical object is displayed on the first display **161**, is within the designated distance from the first region **A1**. According to an embodiment, the processor **120** may change the user interface when a position of at least one graphical object, among graphical objects in the second region **A2**, overlaps the first region **A1** or is within the designated distance from the first region **A1**. For example, the processor **120** may change the position of an object, which overlaps the first region **A1** or is within the designated distance from the first region **A**, or may change, together with the position of the corresponding object, the position of another object adjacent to or positioned within a designated distance from the corresponding object, thereby realigning or rearranging multiple objects included in the user interface.

(120) A description of a series of configurations and/or functions by which the processor **120** changes the user interface has been made with reference to an operation of controlling the first camera **181** and the first display **161**, but may be made with reference to the second camera **182** and the second display **162**. For example, a description of the first display **161** may correspond to the second display **162**, a description of the first region **A1** may correspond to the third region of the second display **162**, a description of the second region **A2** may correspond to the fourth region of the second display **162**, and a description of the first camera **181** may correspond to the second camera **182**.

(121) According to certain embodiments, the processor **120** may execute an application. According to an embodiment, the application may be executed as a program (e.g., the program **140** in FIG. **1**) which is stored as software in a memory (e.g., the memory **130** in FIG. **1**). The application may include, for example, a home, dialer, SMS/MMS, browser, camera, alarm, voice recognition, e-mail, calendar, media player, album, or environment information (e.g., atmospheric pressure, humidity, or temperature information measurement) application. The processor **120** may execute an application stored in the memory **130** to perform a function provided by the application. According to an embodiment, the processor **120** may display an execution screen of the application on the first display **161** and/or the second display **162**. The application may include a user interface including at least one graphical object, and the processor **120** may display the user interface including at least one object as the execution screen of the application on a display (e.g., the first display **161** and/or

the second display **162**). While an application is executed, the user interface may include at least one object which is to be displayed on an execution screen of the executed application.

(122) According to certain embodiments, the processor **120** may determine, based on the executed application, whether to change the user interface. According to an embodiment, the processor **120** may activate a camera (e.g., the first camera **181** and/or the second camera **182**) to deactivate at least a partial region of a display (e.g., the first display **161** and/or the second display **162**). In this case, whether to change the user interface may be determined based on the executed and/or displayed application. According to an embodiment, the processor **120** may determine, based on a function of an application, whether to change the user interface. For example, the processor **120** may not change the user interface when an executed application includes a moving-image playback function.

(123) According to certain embodiments, the processor **120** may simultaneously execute at least two applications (e.g., a first application and a second application). According to an embodiment, the processor **120** may simultaneously execute the first application and the second application, and may simultaneously display an execution screen of the first application and an execution screen of the second application on a display (e.g., the first display **161** and/or the second display **162**). The processor **120** may display execution screens of multiple different applications in segments of the region on a display, respectively, or may display the execution screens such that some of the execution screens of the respective applications overlap each other. According to an embodiment, the processor **120** may display, on the display, a first user interface at least including the execution screen of the first application. For example, the processor **120** may display, on the display, the first user interface including at least one object as the execution screen of the first application. While the first application is executed, the first user interface may include at least one object which is to be displayed on the execution screen of the executed first application. According to an embodiment, the processor **120** may display, on the display, a second user interface at least including the execution screen of the second application. For example, the processor **120** may display, on the display, the second user interface including at least one object as the execution screen of the second application. While the second application is executed, the second user interface may include at least one object which is to be displayed on the execution screen of the executed second application. According to an embodiment, the processor **120** may simultaneously display the first user interface and the second user interface on the display. The processor **120** may divide a display screen into multiple windows and may display different user interfaces in regions corresponding to the windows, respectively.

(124) According to certain embodiments, when a pixel corresponding to the first region (e.g., the first region **A1** in FIG. **6**) is deactivated while multiple user interfaces are displayed on one display (e.g., the first display **161**), the processor **120** may determine a user interface to be changed among the multiple user interfaces. According to an embodiment, the processor **120** may determine a position of a region for displaying the first user interface and a position of a region for displaying the second user interface among regions of the first display **161**. The processor **120** may determine a region overlapping the first region **A1** among at least a partial region on the first display **161**, corresponding to the first user interface, and at least a partial region of the first display **161** corresponding to the second user interface. According to an embodiment, the processor **120** may change a user interface, among the first user interface and the second user interface, in which a displayed region corresponds to a region overlapping the first region **A1**.

(125) FIG. **8** shows an electronic device (e.g., the electronic device **101** in FIG. **7**) according to certain embodiments, which changes a user interface.

(126) Referring to FIG. **8**, the electronic device **101** may control a display **400** (e.g., the display **400** in FIG. **4** or the first display **161** in FIG. **7**) to display a user interface. The user interface may include at least one graphical object which is visually displayed. According to an embodiment, the user interface may include one or more graphics. At least one graphic and/or image object included

in the user interface may be visually displayed on the display **400**. According to an embodiment the user interface may include display of a region for reception of a user input, displaying information about the electronic device **101** or an application executable on the same, or displaying an execution screen of an application, and/or a related object, together in a predetermined region. For example, the object may include an icon, an input field, a badge, a button, a display window, a widget, and/or a tool bar. Referring to FIG. **8**, the electronic device **101** may display, on the display **400**, a user interface including an image object, such as a first icon **811**, a second icon **813**, a third icon **815**, or a fourth icon **817**. According to an embodiment, the object may include an object, visually displayed on the display, such as an image, text, and/or a figure indicating a predetermined region on the display. For example, the user interface may include a section surrounding the first icon **811**, the second icon **813**, the third icon **815**, and the fourth icon **817**, and all graphical objects which include a window for executing an application and are displayed on the display **400**.

(127) Referring to FIG. **8**, the electronic device **101** may deactivate at least a partial region of the region of the display **400**. According to an embodiment, when a camera **205** (e.g., the first camera module **205** in FIG. **2A** or the first camera **181** in FIG. **7**) is activated, the electronic device **101** may deactivate at least one pixel disposed in at least a partial region of the display **400**, which corresponds to the camera **205** or the field of view of the camera **205**. According to an embodiment, the display **400** may include a first region **801** that overlaps with an effective aperture or the field of view of the camera **205**, and a second region **802** surrounding the first region **801**. According to an embodiment, the first region **801** may be formed to include a light transmittance allowing for sufficient operation of the camera **205**, by adjusting a pixel density and/or a wiring density so as to permit the desired transmittance of the first region **801** of the display. According to an embodiment, the second region **802** may include a normal active area, which may indicate a region in which a pixel density and/or a wiring density is higher than that of the first region **801**. According to an embodiment, the second region **802** may be a region in which the light transmittance for the camera **205** is not considered. According to an embodiment, when the camera **205** is activated, the electronic device **101** may deactivate at least one pixel corresponding to the first region **801** on the display **400**. According to an embodiment, the electronic device **101** may deactivate at least some of the pixels corresponding to the first region **801**. According to an embodiment, the electronic device **101** may deactivate all pixels of the first region **801**.

(128) According to certain embodiments, the electronic device **101** may alter a user interface so as to correspond to at least a part of the remaining region, which is not deactivated, in the region of the display **400**. According to an embodiment, the electronic device **101** may change a user interface so as to correspond to the second region **802** on the display **400**. The second region may include at least a partial region of the remaining region of the display **400**, which surrounds the first region **801**. The electronic device **101** may distinguish between the first region **801** and the second region **802**, in that the second region **802** includes a remaining display area of the sub-portion of the display that excludes the first region **801** on the display **400**. According to an embodiment, the electronic device **101** may read data designating the range of the second region **802** in a memory (e.g., the memory **130** in FIG. **1**) to determine the second region **802**. According to an embodiment, the electronic device **101** may determine the first region **801**, and may determine that a region within a designated distance from the first region **801** in the region of the display **400** is the second region **802**. According to an embodiment, the electronic device **101** may identify the second region. For example, the electronic device **101** may determine that a region including a graphical object (e.g., a window or a tool bar) that overlaps the first region **801** is the second region. the electronic device **101** may determine that a region including a graphic disposed within the designated distance from the first region **801** is the second region. In this case, the shape and/or size of the second region **802** may be changed based on the user interface. Referring to FIG. **8**, the second region **802** according to an embodiment may be limited to a region of a graphical object (e.g., a tool bar) which is positioned in a range in which the graphical object overlaps the first region **801**.

Alternatively, the second region **802** may be configured to be a window capable of including all of the third icon **815**, which is a graphical object overlapping the first region **801**, and the first icon **811**, the second icon **813**, and the fourth icon **817**, which are adjacent thereto or parallel objects of an identical class, or the entire region of the display **400** except for the first region **801**.

(129) According to certain embodiments, the electronic device **101** may change a user interface. Changing of a user interface may include operations for movement, enlargement, reduction, shape change, addition, and/or removal of at least one graphical object (e.g., the first icon **811**, the second icon **813**, the third icon **815** and/or the fourth icon **817**) included in the user interface. According to an embodiment, the electronic device **101** may change, based on the second region **802**, an object included in a user interface. According to an embodiment, the electronic device **101** may change a user interface, based on the form of the second region **802**. The electronic device **101**, for example, may move, based on the shape of the determined second region **802**, multiple objects included in a user interface to realign or rearrange the multiple objects. When the electronic device **101** changes a user interface, the first region **801** may be in a deactivated state, and thus the second region **802** may include a region other than the first region **801**. According to an embodiment, the electronic device **101** may change a user interface by changing, among objects included in the user interface, an object overlapping the first region **801**, an object positioned within the designated distance from the first region **801**, and/or objects adjacent thereto. Referring to FIG. **8**, when the camera **205** is activated, the electronic device **101** may move the third icon **815** overlapping the first region **801** to change the user interface. The electronic device **101** may change the user interface by moving, in order to move the third icon **815**, another graphical object included in the user interface including the first icon **811**, the second icon **813**, and the fourth icon **817**, which are objects adjacent to the third icon **815**.

(130) According to certain embodiments, the electronic device **101** may determine information about the position of at least one object included in the user interface. For example, the electronic device **101** may determine information about a position in which a graphical object is displayed on the display **400**. Referring to FIG. **8**, the electronic device **101** may determine each of positions in which graphical objects including the third icon **815** are displayed on the display **400**.

(131) According to certain embodiments, the electronic device **101** may change a user interface, based on information about a position in which an object included in the user interface is displayed on the display **400** and information about the position of the first region **801** on the display **400**. According to an embodiment, the electronic device **101** may change the user interface when a position, in which at least one graphical object is displayed on the display **400**, overlaps the first region **801**. According to an embodiment, the electronic device **101** may change the user interface when a position, in which at least one graphical object is displayed on the display **400**, is within the designated distance from the first region **801**. Referring to FIG. **8**, the third icon **815** is displayed such that the position of the first region **801** overlaps therewith, and the electronic device **101** may determine, based on thereon, to change the user interface. According to an embodiment, the electronic device **101** may change the user interface when a position of at least one graphical object, among graphical objects in the second region **802**, overlaps the first region **801** or is within the designated distance from the first region **801**. For example, the electronic device **101** may change the position of an object, which overlaps the first region **801** or is within the designated distance from the first region **801**, or may change, together with the position of the corresponding object, the position of another object adjacent to or positioned within a designated distance from the corresponding object, thereby realigning or rearranging multiple objects included in the user interface. Referring to FIG. **8**, the electronic device **101** may rearrange multiple graphical objects (e.g., the first icon **811**, the second icon **813**, and the fourth icon **817**) adjacent to or positioned within a designated distance (e.g., within the second region **802**), including the third icon **815**, in a user interface displayed on the display **400**.

(132) FIG. **9** is a flowchart showing operations of changing a user interface by an electronic device

according to certain embodiments.

(133) Referring to FIG. 9, multiple operations of changing a user interface by an electronic device (e.g., the electronic device **101** in FIG. 1 or the electronic device **101** in FIG. 7) may be considered to be operations performed by a processor (e.g., the processor **120** in FIG. 7) of the electronic device **101**. Operations in FIG. 9 may be changed or replaced, and/or the order thereof may be switched, and a new operation may be added.

(134) Referring to operation **901**, the processor **120** may display a user interface on a first display (e.g., the first display **161** in FIG. 7). According to certain embodiments, the processor **120** may control the first display **161** to display a user interface. The user interface may include display of at least one graphical object. According to an embodiment, the user interface may include one or more graphic elements. At least one object included in the user interface may include an image object which may be visually displayed on a display (e.g., the first display **161**). According to an embodiment, the at least one object included in the user interface may include an image object for displaying a region for reception of a user input, displaying information about the processor **120** or an application, or displaying an execution screen or a related object together in a predetermined region. For example, the object may include an icon, an input field, a badge, a button, a display window, a widget, and/or a tool bar. According to an embodiment, the object may include an object, which is visually displayed on the display, such as an image, text, and/or a figure indicating a predetermined region on the display. The object included in the user interface is not limited to the above-mentioned examples.

(135) Referring to operation **902**, the processor **120** may activate a first camera (e.g., the first camera **181** in FIG. 7). According to certain embodiments, the processor **120** may capture an image. According to an embodiment, the processor **120** may activate the first camera **181** to capture a still image and/or a moving image. The processor **120** may receive an input regarding still-image and/or moving-image capturing, and may control, based on the received input, the first camera **181** to capture a still image and/or a moving image. According to an embodiment, the input regarding image capturing, received by the processor **120**, may include an input for activating a camera (e.g., the first camera **181**). The processor **120** may receive the input regarding image capturing to activate the first camera **181**.

(136) Referring to operation **903**, the processor **120** may deactivate at least one pixel of the display disposed within a first region (e.g., the first region **A1** in FIG. 5B or the first region **801** in FIG. 8, which in some embodiments overlaps a field-of-view of the camera). According to certain embodiments, the processor **120** may deactivate at least a partial region (e.g., the first region) of the region of the first display **161**. According to an embodiment, when the camera (e.g., the first camera **181**) is activated, the processor **120** may deactivate a pixel included in at least a partial region of the first display **161** that corresponds to the camera or the field of view of the camera. According to an embodiment, the first display **161** may include a first region (e.g., the first region **A1** in FIG. 5B or the first region **801** in FIG. 8) overlapping an effective aperture or the field of view of the first camera **181** and a second region (e.g., the second region **A2** in FIG. 5B or the second region **802** in FIG. 8) surrounding the first region **801**. According to an embodiment, the first region **801** may be formed to have light transmittance utilized by the first camera **181** by adjusting a pixel density and/or a wiring density to be relatively low. According to an embodiment, the second region **802** may include a normal active area, that is, a region in which a pixel density and/or a wiring density is high compared with the first region **801**. According to an embodiment, the second region **802** may be a region in which the light transmittance for the camera (e.g., the first camera **181**) is not considered. According to an embodiment, when the first camera **181** is activated, the processor **120** may deactivate at least one pixel corresponding to the first region **801** on the first display **161**. According to an embodiment, the processor **120** may deactivate at least some of multiple pixels corresponding to the first region **801**. According to an embodiment, the processor **120** may deactivate all pixels corresponding to the first region **801**.

(137) Referring to operation **904**, the processor **120** may change the user interface so as to correspond to the second region. According to certain embodiments, the processor **120** may change the user interface so as to correspond to at least a part of the remaining region, which is not deactivated, in the region of the first display **161**. According to an embodiment, the processor **120** may change the user interface by moving an element thereof from the first into the second region **802** on the first display **161**. The second region may include at least a partial region of the remaining region of the first display **161**, which surrounds the first region **801**. The processor **120** may distinguish the first region **801** and the second region **802** in the remaining region other than the first region **801** on the first display **161**. According to an embodiment, the processor **120** may read data designated about the range of the second region **802** in a memory (e.g., the memory **130** in FIG. 1) to determine the second region **802**. According to an embodiment, the processor **120** may determine the first region **801**, and may determine that a region within a designated distance from the first region **801** in the region of the first display **161** is the second region **802**. According to an embodiment, the processor **120** may determine that a region including a graphical object (e.g., a window or a tool bar), which overlaps the first region **801** or is displayed in a region within the designated distance from the first region **801**, among graphical objects displayed on the first display **161** is the second region. In this case, the shape and/or size of the second region **802** may be changed based on the user interface.

(138) Referring to operation **905**, the processor **120** may deactivate the first camera **181**. According to certain embodiments, the processor **120** may receive an input regarding still-image and/or moving-image capturing, and may control, based on the received input, the first camera **181** to capture a still image and/or a moving image. According to an embodiment, the input regarding image capturing, received by the processor **120**, may include an input for deactivating a camera (e.g., the first camera **181**). The processor **120** may receive the input regarding image capturing to deactivate the first camera **181**. According to an embodiment, when the electronic device **101** includes multiple cameras (e.g., the first camera **181** and the second camera **182** in FIG. 7), the input regarding image capturing may include an input for switching the cameras. For example, the processor **120** may receive, while activating the first camera **181**, an input for switching an activated camera from the first camera **181** to the second camera **182**. When the processor **120** receives the camera-switching input while activating the first camera **181**, the processor **120** may deactivate the first camera **181** and activate the second camera **182**.

(139) Referring to operation **906**, the processor **120** may return the changed user interface. According to certain embodiments, when the first camera **181** is deactivated, the processor **120** may reactivate the first region **801** that was previously deactivated, in response to a present deactivation of the first camera **181**. In this case, the first display **161** returns to a state in which the entire region thereof is activated, and thus the processor **120** may return the user interface changed in operation **904** to a state before being changed.

(140) FIG. 10 is a flowchart showing operations of changing a user interface by an electronic device including at least one camera according to certain embodiments.

(141) Referring to FIG. 10, multiple operations of changing a user interface by an electronic device (e.g., the electronic device **101** in FIG. 1 or the electronic device **101** in FIG. 7) may be considered to be operations performed by a processor (e.g., the processor **120** in FIG. 7) of the electronic device **101**. Operations in FIG. 10 may be changed, may be replaced, and/or may be switched in the order thereof, and a new operation may be added.

(142) Referring to operation **1001**, the processor **120** may display a user interface on a first display (e.g., the first display **161** in FIG. 7). According to certain embodiments, the processor **120** may control the first display **161** to display a user interface. The user interface may include at least one graphical object which is visually displayed. According to an embodiment, the user interface may include a graphical user interface. At least one object included in the user interface may include an image object which may be visually displayed on a display (e.g., the first display **161**). According

to an embodiment, the at least one object included in the user interface may include an image object for displaying a region for reception of a user input, displaying information about the processor **120** or an application, or displaying an execution screen or a related object together in a predetermined region. For example, the object may include an icon, an input field, a badge, a button, a display window, a widget, and/or a tool bar. According to an embodiment, the object may include an object, which is visually displayed on the display, such as an image, text, and/or a figure indicating a predetermined region on the display. The object included in the user interface is not limited to the above-mentioned examples.

(143) Referring to operation **1002**, the processor **120** may activate a camera (e.g., the first camera **181** and/or the second camera **182** in FIG. 7). According to certain embodiments, the processor **120** may activate a camera to capture an image. According to an embodiment, the processor **120** may use the first camera **181** and/or the second camera **182** to capture a still image and/or a moving image. The processor **120** may receive an input regarding still-image and/or moving-image capturing, and may control, based on the received input, the camera to capture a still image and/or a moving image. According to an embodiment, the input regarding image capturing, received by the processor **120**, may include an input for activating a camera (e.g., the first camera **181** and/or the second camera **182**). The processor **120** may receive the input regarding image capturing to activate the camera.

(144) Referring to operation **1003**, the processor **120** may determine whether the activated camera is a first camera (e.g., the first camera **181** in FIG. 7) or another camera (e.g., a second non-UDC camera). According to certain embodiments, the processor **120** may activate one of cameras (e.g., the first camera **181** and/or the second camera **182**), and may determine the activated camera. When the electronic device **101** includes multiple cameras (e.g., the first camera **181** and the second camera **182**), the processor **120** may determine which camera is a camera activated at the time of camera activation. According to an embodiment, the processor **120** may determine whether the activated camera is the first camera **181** or the second camera **182**. When it is determined that the activated camera is the first camera **181**, the processor **120** moves to operation **1004**.

(145) Referring to operation **1004**, the processor **120** may deactivate at least one pixel corresponding to a first region (e.g., the first region A1 in FIG. 5B or the first region **801** in FIG. 8). According to certain embodiments, the processor **120** may deactivate at least a partial region (e.g., the first region **801**) of a display (e.g., the first display **161**), which is disposed to overlap the activated camera (e.g., the first camera **181**) determined in operation **1003**. According to certain embodiments, the processor **120** may deactivate at least a partial region (e.g., the first region) of the region of the first display **161**. According to an embodiment, when the camera (e.g., the first camera **181**) is activated, the processor **120** may deactivate a pixel included in at least a partial region of the first display **161**, which corresponds to the first camera **181** or the field of view of the first camera **181**. According to an embodiment, the first display **161** may include a first region (e.g., the first region A1 in FIG. 5B or the first region **801** in FIG. 8) overlapping an effective aperture or the field of view of the first camera **181**, and a second region (e.g., the second region A2 in FIG. 5B or the second region **802** in FIG. 8) surrounding the first region **801**. According to an embodiment, the first region **801** may be formed to have light transmittance utilized by the first camera **181** by adjusting a pixel density and/or a wiring density to be relatively low. According to an embodiment, the second region **802** may include a normal active area, that is, a region in which a pixel density and/or a wiring density is high compared with the first region **801**. According to an embodiment, the second region **802** may be a region in which the light transmittance for a camera (e.g., the first camera **181**) is not considered. According to an embodiment, when the first camera **181** is activated, the processor **120** may deactivate at least one pixel corresponding to the first region **801** on the first display **161**. According to an embodiment, the processor **120** may deactivate at least some of multiple pixels corresponding to the first region **801**. According to an embodiment, the processor **120** may deactivate all pixels corresponding to the first region **801**.

(146) Referring to operation **1005**, the processor **120** may change the user interface so as to correspond to the second region **802**. According to certain embodiments, the processor **120** may change the user interface so as to correspond to at least a part of the remaining region, which is not deactivated, in the region of the first display **161**. According to an embodiment, the processor **120** may change the user interface so as to correspond to the second region **802** on the first display **161**. The second region may include at least a partial region of the remaining region of the first display **161**, which surrounds the first region **801**. The processor **120** may distinguish the first region **801** and the second region **802** in the remaining region other than the first region **801** on the first display **161**. According to an embodiment, the processor **120** may read data designated about the range of the second region **802** in a memory (e.g., the memory **130** in FIG. 1) to determine the second region **802**. According to an embodiment, the processor **120** may determine the first region **801**, and may determine that a region within a designated distance from the first region **801** in the region of the first display **161** is the second region **802**. According to an embodiment, the processor **120** may determine that a region including a graphical object (e.g., a window or a tool bar), which overlaps the first region **801** or is displayed in a region within the designated distance from the first region **801**, among graphical objects displayed on the first display **161** is the second region. In this case, the shape and/or size of the second region **802** may be changed based on the user interface.

(147) FIG. 11 shows an electronic device according to certain embodiments, which changes a user interface based on a position in which an object is displayed.

(148) Referring to FIG. 11, the electronic device **101** may control a display **400** (e.g., the display **400** in FIG. 4 or the first display **161** in FIG. 7) to display a user interface. The user interface may include display of at least one graphical object. According to an embodiment, the user interface may be a graphical user interface. At least one object included in the user interface may include an image object that is visually displayed on the display **400**. According to an embodiment, the at least one object included in the user interface may include an image object for indicating a region for reception of a user input, displaying information about the electronic device **101** or an application, or displaying an execution screen or a related object together in a predetermined region. For example, the object may include an icon, an input field, a badge, a button, a display window, a widget, and/or a tool bar. Referring to FIG. 11, the electronic device **101** may display, on the display **400**, a user interface including an image object, such as a first icon **1110** or a second icon **1120**. According to an embodiment, the object may include an object, visually displayed on the display, such as an image, text, and/or a figure indicating a predetermined region on the display. For example, the user interface may include a section surrounding the first icon **1110** and the second icon **1120**, and all graphical objects which include a window for executing an application and are displayed on the display **400**.

(149) Referring to FIG. 11, the electronic device **101** may deactivate at least a partial region of the region of the display **400**. According to an embodiment, when a camera **205** (e.g., the first camera module **205** in FIG. 2A or the first camera **181** in FIG. 7) is activated, the electronic device **101** may deactivate a pixel included in at least a partial region of the display **400**, which is disposed overlaying and proximate to the camera **205** and/or overlaps the field of view of the camera **205**. According to an embodiment, the display **400** may, for example, include a first region **1101** overlapping an effective aperture or the field of view of the camera **205** and a second region **1102** surrounding the first region **1101**. According to an embodiment, the first region **1101** may include light transmittance enabling operation of the camera **205** by selection of a pixel density and/or a wiring density of the first region of the display. According to an embodiment, the second region **1102** may include a normal active area, that is, a region in which a pixel density and/or a wiring density is higher compared with the first region **1101**. According to an embodiment, the second region **1102** may be a region in which the light transmittance for the camera **205** is not considered. According to an embodiment, when the camera **205** is activated, the electronic device **101** may deactivate at least one pixel corresponding to the first region **1101** on the display **400**. According to

an embodiment, the electronic device **101** may deactivate at least some of multiple pixels corresponding to the first region **1101**. According to an embodiment, the electronic device **101** may deactivate all pixels corresponding to the first region **1101**.

(150) According to certain embodiments, the electronic device **101** may change a user interface so as to correspond to at least a part of the remaining region, which is not deactivated, in the region of the display **400**. According to an embodiment, the electronic device **101** may change a user interface so as to correspond to the second region **1102** on the display **400**. The second region may include at least a partial region of the remaining region of the display **400**, which surrounds the first region **1101**. The electronic device **101** may distinguish the first region **1101** and the second region **1102** in the remaining region other than the first region **1101** on the display **400**. According to an embodiment, the electronic device **101** may read data indicating a range of the second region **1102** in a memory (e.g., the memory **130** in FIG. 1), to determine the second region **1102**. According to an embodiment, the electronic device **101** may determine the first region **1101**, and may determine that a region disposed within a designated distance from the first region **1101** in the region of the display **400** is the second region **1102**. According to an embodiment, the electronic device **101** may determine that the second region is a region including a graphical object (e.g., a window or a tool bar) that overlaps the first region **1101** or is displayed in a region within the designated distance from the first region **1101**, from among graphical objects displayed on the display **400** is the second region. In this case, the shape and/or size of the second region **1102** may be changed based on the user interface. Referring to FIG. 11, the second region **1102** according to an embodiment may be limited to a region of a graphical object (e.g., an upper-end bar) positioned in a range in which the graphical object overlaps the first region **1101**. Alternatively, the second region **1102** may be configured to be a window capable of including the first icon **1110**, which is a graphical object overlapping the first region **1101**, or the entire region of the display **400** except for the first region **1101**.

(151) According to certain embodiments, the electronic device **101** may change a user interface. Changing of a user interface may include operations for movement, enlargement, reduction, shape change, addition, and/or removal of at least one graphical object (e.g., the first icon **1110** and/or the second icon **1120**) included in the user interface. According to an embodiment, the electronic device **101** may change a user interface by changing, among objects included in the user interface, an object overlapping the first region **1101**, an object positioned within the designated distance from the first region **1101**, and/or objects adjacent thereto. Referring to FIG. 11, when the camera **205** is activated, the electronic device **101** may change the user interface to accommodate operation of the camera by moving the first icon **1110** away from overlapping the first region **1101**. This operation may be executed in absence of any change to the second icon **1120**, which is already spaced apart from the first region **1101** and positioned in a range in which the second icon **1120** did not overlap the first icon **1110**, even when the first icon **1110** is moved. For example, no changes are made to any graphical object disposed outside a range of a designated distance from the first region **1101**. The electronic device **101** may move the first icon **1110** to change the user interface.

(152) According to certain embodiments, the electronic device **101** may determine information about the position of at least one object included in the user interface. For example, the electronic device **101** may determine information about a position in which a graphical object is displayed on the display **400**. Referring to FIG. 11, the electronic device **101** may determine each of positions in which graphical objects including the first icon **1110** and the second icon **1120** are displayed on the display **400**.

(153) According to certain embodiments, the electronic device **101** may change the user interface, based on information about a position in which an object included in the user interface is displayed on the display **400** and information about the position of the first region **1101** on the display **400**. According to an embodiment, the electronic device **101** may change the user interface when a position, in which at least one graphical object is displayed on the display **400**, overlaps the first

region **1101**. According to an embodiment, the electronic device **101** may change the user interface when a position, in which at least one graphical object is displayed on the display **400**, is within the designated distance from the first region **1101**.

(154) Referring to FIG. **11**, the first icon **1110** is displayed such that the position of the first region **1101** overlaps therewith, and the electronic device **101** may determine, based thereon, to change the user interface. According to an embodiment, the electronic device **101** may change the user interface when a position of at least one graphical object, among graphical objects in the second region **1102**, overlaps the first region **1101** or is within the designated distance from the first region **1101**. For example, the electronic device **101** may change the position of an object, which overlaps the first region **1101** or is within the designated distance from the first region **1101**, or may change, together with the position of the corresponding object, the position of another object adjacent to or positioned within a designated distance from the corresponding object, thereby realigning or rearranging multiple objects included in the user interface.

(155) FIG. **12** is a flowchart showing operations in which an electronic device according to certain embodiments changes a user interface, based on a position in which an object is displayed.

(156) Referring to FIG. **12**, multiple operations of changing a user interface by an electronic device (e.g., the electronic device **101** in FIG. **1** or the electronic device **101** in FIG. **7**) may be considered to be operations performed by a processor (e.g., the processor **120** in FIG. **7**) of the electronic device **101**. Operations in FIG. **12** may be changed, may be replaced, and/or may be switched in the order thereof, and a new operation may be added.

(157) Referring to operation **1201**, the processor **120** may display a user interface on a first display (e.g., the first display **161** in FIG. **7**). According to certain embodiments, the processor **120** may control the first display **161** to display a user interface. The user interface may include at least one graphical object which is visually displayed. According to an embodiment, the user interface may include a graphical user interface. At least one object included in the user interface may include an image object which may be visually displayed on a display (e.g., the first display **161**). According to an embodiment, the at least one object included in the user interface may include an image object for displaying a region for reception of a user input, displaying information about the processor **120** or an application, or displaying an execution screen or a related object together in a predetermined region. For example, the object may include an icon, an input field, a badge, a button, a display window, a widget, and/or a tool bar. According to an embodiment, the object may include an object, which is visually displayed on the display, such as an image, text, and/or a figure indicating a predetermined region on the display. The object included in the user interface is not limited to the above-mentioned examples.

(158) Referring to operation **1202**, the processor **120** may activate a first camera (e.g., the first camera **181** in FIG. **7**). According to certain embodiments, the processor **120** may capture an image. According to an embodiment, the processor **120** may use the first camera **181** to capture a still image and/or a moving image. The processor **120** may receive an input regarding still-image and/or moving-image capturing, and may control, based on the received input, the first camera **181** to capture a still image and/or a moving image. According to an embodiment, the input regarding image capturing, received by the processor **120**, may include an input for activating a camera (e.g., the first camera **181**). The processor **120** may receive the input regarding image capturing to activate the first camera **181**.

(159) Referring to operation **1203**, the processor **120** may deactivate at least one pixel corresponding to a first region (e.g., the first region **A1** in FIG. **5B** or the first region **801** in FIG. **8**). According to certain embodiments, the processor **120** may deactivate at least a partial region (e.g., the first region) of the region of the first display **161**. According to an embodiment, when the camera (e.g., the first camera **181**) is activated, the processor **120** may deactivate a pixel included in at least a partial region of the first display **161** that corresponds to the camera or the field of view of the camera. According to an embodiment, the first display **161** may include a first region (e.g.,

the first region **A1** in FIG. 5B or the first region **801** in FIG. 8) overlapping an effective aperture or the field of view of the first camera **181** and a second region (e.g., the second region **A2** in FIG. 5B or the second region **802** in FIG. 8) surrounding the first region **801**. According to an embodiment, the first region **801** may be formed to have light transmittance utilized by the first camera **181** by adjusting a pixel density and/or a wiring density to be relatively low. According to an embodiment, the second region **802** may include a normal active area, that is, a region in which a pixel density and/or a wiring density is high compared with the first region **801**. According to an embodiment, the second region **802** may be a region in which the light transmittance for the camera (e.g., the first camera **181**) is not considered. According to an embodiment, when the first camera **181** is activated, the processor **120** may deactivate at least one pixel corresponding to the first region **801** on the first display **161**. According to an embodiment, the processor **120** may deactivate at least some of multiple pixels corresponding to the first region **801**. According to an embodiment, the processor **120** may deactivate all pixels corresponding to the first region **801**.

(160) Referring to operation **1204**, the processor **120** may determine information indicative of a position at which a first object (e.g., the third icon **815** in FIG. 8) is displayed. The first object may include at least one graphical object included in the user interface. According to certain embodiments, the processor **120** may determine information about the position of at least one object (e.g., the first object) included in the user interface. For example, the processor **120** may determine information about a position at which a graphical object is displayed on the first display **161**.

(161) Referring to operation **1205**, the processor **120** may change the user interface, based on the information about a position in which the first object is displayed, and information about the first region. According to certain embodiments, the processor **120** may change the user interface, based on information about a position in which an object included in the user interface is displayed on the first display **161** and information about the position of the first region **801** on the first display **161**. According to an embodiment, the processor **120** may change the user interface when a position, in which at least one graphical object is displayed on the first display **161**, overlaps the first region **801**. According to an embodiment, the processor **120** may change the user interface when a position, in which at least one graphical object is displayed on the first display **161**, is disposed within a designated distance from the first region **801**. According to an embodiment, the processor **120** may change the user interface when a position of at least one of graphical objects in the second region **802** overlaps the first region **801** or is within a designated distance from the first region **801**. For example, the processor **120** may change the position of an object which overlaps the first region **801** or is within the designated distance from the first region **801**, or may change, together with the position of the corresponding object, the position of another object adjacent to or positioned within a designated distance from the corresponding object, thereby realigning or rearranging multiple objects included in the user interface.

(162) FIG. 13 shows an electronic device according to certain embodiments, which changes a user interface based on an executed application.

(163) According to certain embodiments, the electronic device **101** may determine whether to change a user interface, based on an executed application. According to an embodiment, the electronic device **101** may activate a camera (e.g., the first camera **181** in FIG. 7) to deactivate at least a partial region of a display **400** (e.g., the first display **161** in FIG. 7). In this case, whether to change the user interface may be determined based on an executed and/or displayed application. According to an embodiment, the electronic device **101** may determine whether to change the user interface, based on a function of an application. For example, the electronic device **101** may not change the user interface when an executed application includes a moving-image playback function.

(164) Referring to FIG. 13, the electronic device **101** may execute a first application (e.g., a media player) including a moving-image (e.g., video, animated image, etc.) playback function. The

electronic device **101** may display a user interface corresponding to the first application on the display **400**. As seen in FIG. **13**, the electronic device **101** may display a moving-image playback window **1312** on the user interface of the first application. Furthermore, a first icon **1311** that corresponds to a video call function may be displayed while the camera is executed. In this case, the playback window **1312** and a first region **1301** (in which the camera is disposed) overlap with each other, and thus, the electronic device **101** may avoid changing or altering the playback window **1312** in order to prioritize a smooth viewing experience of the moving image for the user. When the first application including the moving-image playback function is executed, the electronic device **101** may pause any changes to the user interface.

(165) According to an embodiment, the electronic device **101** may determine whether to change the user interface, based on whether an execution screen (e.g., the playback window **1312**) of the first application including the moving-image playback function overlaps the first region **1301**. As noted above, a smooth viewing experience may be prioritized over the camera operation. Accordingly when the first application is executed, the electronic device **101** may pause changes in the user interface when overlap is detected. Alternatively, the user interface may be changed when the execution screen of the first application is detected as having no overlap with the first region **1301**.

(166) FIG. **14** is a flowchart showing operations in which an electronic device according to certain embodiments changes a user interface, based on an executed application.

(167) Referring to FIG. **14**, multiple operations of changing a user interface by an electronic device (e.g., the electronic device **101** in FIG. **1** or the electronic device **101** in FIG. **7**) may be considered to be operations performed by a processor (e.g., the processor **120** in FIG. **7**) of the electronic device **101**. Operations in FIG. **14** may be changed, may be replaced, and/or may be switched in the order thereof, and a new operation may be added.

(168) Referring to operation **1401**, the processor **120** may execute a first application. According to certain embodiments, the processor **120** may execute various applications. According to an embodiment, the application may be executed as a program (e.g., the program **140** in FIG. **1**) which is stored as software in a memory (e.g., the memory **130** in FIG. **1**). The application may include, for example, a home, dialer, SMS/MMS, browser, camera, alarm, voice recognition, e-mail, calendar, media player, album, or environment information (e.g., atmospheric pressure, humidity, or temperature information measurement) application. The processor **120** may execute an application stored in the memory **130** to perform a function provided by the application.

(169) Referring to operation **1402**, the processor **120** may display a user interface on a first display (e.g., the first display **161** in FIG. **7**). According to certain embodiments, the processor **120** may control the first display **161** to display a user interface. According to an embodiment, the processor **120** may display an execution screen of an application on the first display **161**. The application may include a user interface including at least one graphical object, and the processor **120** may display, on a display (e.g., the first display **161**), a user interface including at least one object as an application execution screen. While an application is executed, the user interface may include at least one object which is to be displayed on an execution screen of the executed application. The user interface may include at least one graphical object which is visually displayed. According to an embodiment, the user interface may include a graphical user interface. At least one object included in the user interface may include an image object which may be visually displayed on a display (e.g., the first display **161**). According to an embodiment, the at least one object included in the user interface may include an image object for displaying a region for reception of a user input, displaying information about the processor **120** or an application, or displaying an execution screen or a related object together in a predetermined region. For example, the object may include an icon, an input field, a badge, a button, a display window, a widget, and/or a tool bar. According to an embodiment, the object may include an object, which is visually displayed on the display, such as an image, text, and/or a figure indicating a predetermined region on the display.

(170) Referring to operation **1403**, the processor **120** may activate a first camera (e.g., the first

camera **181** in FIG. 7). According to certain embodiments, the processor **120** may capture an image. According to an embodiment, the processor **120** may use the first camera **181** to capture a still image and/or a moving image. The processor **120** may receive an input regarding still-image and/or moving-image capturing, and may control, based on the received input, the first camera **181** to capture a still image and/or a moving image. According to an embodiment, the input regarding image capturing, received by the processor **120**, may include an input for activating a camera (e.g., the first camera **181**). The processor **120** may receive the input regarding image capturing to activate the first camera **181**.

(171) Referring to operation **1404**, the processor **120** may deactivate at least one pixel corresponding to a first region (e.g., the first region **A1** in FIG. 5B or the first region **801** in FIG. 8). According to certain embodiments, the processor **120** may deactivate at least a partial region (e.g., the first region) of the region of the first display **161**. According to an embodiment, when the camera (e.g., the first camera **181**) is activated, the processor **120** may deactivate a pixel included in at least a partial region of the first display **161** that corresponds to the camera or the field of view of the camera. According to an embodiment, the first display **161** may include a first region (e.g., the first region **A1** in FIG. 5B or the first region **801** in FIG. 8) overlapping an effective aperture or the field of view of the first camera **181** and a second region (e.g., the second region **A2** in FIG. 5B or the second region **802** in FIG. 8) surrounding the first region **801**. According to an embodiment, the first region **801** may be formed to have light transmittance utilized by the first camera **181** by adjusting a pixel density and/or a wiring density to be relatively low. According to an embodiment, the second region **802** may include a normal active area, that is, a region in which a pixel density and/or a wiring density is high compared with the first region **801**. According to an embodiment, the second region **802** may be a region in which the light transmittance for the camera (e.g., the first camera **181**) is not considered. According to an embodiment, when the first camera **181** is activated, the processor **120** may deactivate at least one pixel corresponding to the first region **801** on the first display **161**. According to an embodiment, the processor **120** may deactivate at least some of multiple pixels corresponding to the first region **801**. According to an embodiment, the processor **120** may deactivate all pixels corresponding to the first region **801**.

(172) Referring to operation **1405**, the processor **120** may determine whether to change a first user interface, based on one or more characteristics, configurations, settings, operations, etc. of the first application. According to certain embodiments, the processor **120** may determine whether to change the user interface, based on the executed application. According to an embodiment, the processor **120** may activate the camera (e.g., the first camera **181** in FIG. 7) to deactivate at least a partial region of the display **400** (e.g., the first display **161** in FIG. 7). In this case, determining whether to change the user interface may be based on the executed and/or displayed application. According to an embodiment, the processor **120** may determine, based on a function of an application, whether to change the user interface. For example, when the executed application includes a moving-image playback function, the processor **120** may pause or preclude any changes to the user interface to prioritize smooth playback of the moving-image. According to an embodiment, the processor **120** may execute the first application (e.g., a media player) including a moving-image playback function. The processor **120** may display a user interface corresponding to the first application on the display **400**. For example, the processor **120** may display a moving-image playback window in the middle of the user interface corresponding to the first application. In this case, when the first application including a moving-image playback function is executed, the processor **120** may not change the user interface in order to allow a user to smoothly watch a moving image. According to an embodiment, the processor **120** may determine whether to change the user interface, based on whether an execution screen of the first application including a moving-image playback function overlaps the first region **1301**. Even while the first application is executed, the processor **120** may change the user interface when the execution screen of the first application does not overlap the first region.

(173) Referring to operation **1406**, the processor **120** may change the first user interface, upon determining that the one or more characteristics, configurations, settings, operations of the first application permit such a change. (Alternatively, if it is determined to pause or preclude any such changes, no change to the first user interface is executed). According to an embodiment, the processor **120** may change a user interface so as to correspond to at least a part of the remaining region, which is not deactivated, in the region of the first display **161**. According to an embodiment, the processor **120** may change the user interface so as to correspond to the second region **802** on the first display **161**. The second region may include at least a partial region of the remaining region of the first display **161**, which surrounds the first region **801**. The processor **120** may distinguish the first region **801** and the second region **802** in the remaining region other than the first region **801** on the first display **161**. According to an embodiment, the processor **120** may read data designated about the range of the second region **802** in a memory (e.g., the memory **130** in FIG. 1) to determine the second region **802**. According to an embodiment, the processor **120** may determine the first region **801**, and may determine that a region within a designated distance from the first region **801** in the region of the first display **161** is the second region **802**. According to an embodiment, the processor **120** may determine that a region including a graphical object (e.g., a window or a tool bar), which overlaps the first region **801** or is displayed in a region within the designated distance from the first region **801**, among graphical objects displayed on the first display **161** is the second region. In this case, the shape and/or size of the second region **802** may be changed based on the user interface.

(174) FIG. 15 shows changing a user interface by an electronic device displaying multiple user interfaces according to certain embodiments.

(175) According to certain embodiments, the electronic device **101** may simultaneously execute at least two applications (e.g., a first application and a second application). According to an embodiment, the electronic device **101** may simultaneously execute the first application and the second application, and may simultaneously display an execution screen **1510** of the first application and an execution screen **1520** of the second application on a display **400**. The electronic device **101** may display execution screens **1510** and **1520** of multiple different applications in segments of the region on the display, respectively, or may display the execution screens such that parts of the execution screens of the respective applications overlap each other. Referring to FIG. 15, the electronic device **101** may display, on the display **400**, a first user interface at least including the execution screen **1510** of the first application. For example, the electronic device **101** may display, on the display **400**, the first user interface including at least one object (e.g., a first icon **1511**, a second icon **1513**, a third icon **1515**, or a fourth icon **1517**) as the execution screen **1510** of the first application. While the first application is executed, the first user interface may include at least one object which is to be displayed on the execution screen of the executed first application.

(176) Referring to FIG. 15, the electronic device **101** may display, on the display, a second user interface at least including the execution screen **1520** of the second application. For example, the electronic device **101** may display, on the display, the second user interface including at least one object as the execution screen of the second application. While the second application is executed, the second user interface may include at least one object which is to be displayed on the execution screen of the executed second application. According to an embodiment, the electronic device **101** may simultaneously display the first user interface and the second user interface on the display. The electronic device **101** may divide a display screen into multiple windows and may display different user interfaces in regions corresponding to the windows, respectively.

(177) According to certain embodiments, when a pixel corresponding to a first region **1501** (e.g., the first region **801** in FIG. 8) is deactivated while multiple user interfaces are displayed on one display **400**, the electronic device **101** may determine a user interface to be changed among the multiple user interfaces. According to an embodiment, the electronic device **101** may determine a

position of a region for displaying the first user interface and a position of a region for displaying the second user interface among regions of the first display **400**. The electronic device **101** may determine a region overlapping the first region **1501** among at least a partial region on the first display **400**, corresponding to the first user interface, and at least a partial region on the first display **400**, corresponding to the second user interface. According to an embodiment, the electronic device **101** may change a user interface, among the first user interface and the second user interface, in which a displayed region corresponds to a region overlapping the first region **1501**. Referring to FIG. **15**, the electronic device **101** may determine that a user interface overlapping the first region **1501** overlaps the position of the execution screen **1510** of the first application, and may change a user interface positioned in the execution screen **1510** of the first application.

(178) FIG. **16** is a flowchart showing operations of changing a user interface by an electronic device displaying multiple user interfaces according to certain embodiments.

(179) Referring to FIG. **16**, multiple operations of changing a user interface by an electronic device (e.g., the electronic device **101** in FIG. **1** or the electronic device **101** in FIG. **7**) may be considered to be operations performed by a processor (e.g., the processor **120** in FIG. **7**) of the electronic device **101**. Operations in FIG. **16** may be changed, may be replaced, and/or may be switched in the order thereof, and a new operation may be added.

(180) Referring to operation **1601**, the processor **120** may display a first user interface and a second user interface on a first display (e.g., the first display **161** in FIG. **7**). According to certain embodiments, the processor **120** may simultaneously execute at least two applications (e.g., a first application and a second application). According to an embodiment, the processor **120** may simultaneously execute the first application and the second application, and may simultaneously display an execution screen of the first application and an execution screen of the second application on a display (e.g., the first display **161**). The processor **120** may display execution screens of multiple different applications in segments of the region on the display, respectively, or may display the execution screens such that parts of the execution screens of the respective applications overlap each other. According to an embodiment, the processor **120** may display, on the display, a first user interface at least including the execution screen of the first application. For example, the processor **120** may display, on the display, the first user interface including at least one object as the execution screen of the first application. While the first application is executed, the first user interface may include at least one object which is to be displayed on the execution screen of the executed first application. According to an embodiment, the processor **120** may display, on the display, a second user interface at least including the execution screen of the second application. For example, the processor **120** may display, on the display, the second user interface including at least one object as the execution screen of the second application. While the second application is executed, the second user interface may include at least one object which is to be displayed on the execution screen of the executed second application. According to an embodiment, the processor **120** may simultaneously display the first user interface and the second user interface on the display. The processor **120** may divide a display screen into multiple windows and may display different user interfaces in regions corresponding to the windows, respectively.

(181) Referring to operation **1602**, the processor **120** may activate a first camera (e.g., the first camera **181** in FIG. **7**). According to certain embodiments, the processor **120** may capture an image. According to an embodiment, the processor **120** may use the first camera **181** to capture a still image and/or a moving image. The processor **120** may receive an input regarding still-image and/or moving-image capturing, and may control, based on the received input, the first camera **181** to capture a still image and/or a moving image. According to an embodiment, the input regarding image capturing, received by the processor **120**, may include an input for activating a camera (e.g., the first camera **181**). The processor **120** may receive the input regarding image capturing to activate the first camera **181**.

(182) Referring to operation **1603**, the processor **120** may deactivate at least one pixel

corresponding to a first region (e.g., the first region A1 in FIG. 5B or the first region 801 in FIG. 8). According to certain embodiments, the processor 120 may deactivate at least a partial region (e.g., the first region) of the region of the first display 161. According to an embodiment, when the camera (e.g., the first camera 181) is activated, the processor 120 may deactivate a pixel included in at least a partial region of the first display 161 that corresponds to the camera or the field of view of the camera. According to an embodiment, the first display 161 may include a first region (e.g., the first region A1 in FIG. 5B or the first region 801 in FIG. 8) overlapping an effective aperture or the field of view of the first camera 181 and a second region (e.g., the second region A2 in FIG. 5B or the second region 802 in FIG. 8) surrounding the first region 801. According to an embodiment, the first region 801 may be formed to have light transmittance utilized by the first camera 181 by adjusting a pixel density and/or a wiring density to be relatively low. According to an embodiment, the second region 802 may include a normal active area, that is, a region in which a pixel density and/or a wiring density is high compared with the first region 801. According to an embodiment, the second region 802 may be a region in which the light transmittance for the camera (e.g., the first camera 181) is not considered. According to an embodiment, when the first camera 181 is activated, the processor 120 may deactivate at least one pixel corresponding to the first region 801 on the first display 161. According to an embodiment, the processor 120 may deactivate at least some of multiple pixels corresponding to the first region 801. According to an embodiment, the processor 120 may deactivate all pixels corresponding to the first region 801.

(183) Referring to operation 1604, the processor 120 may determine a region that overlaps the first region, from among a region corresponding to the first user interface, and a region corresponding to the second user interface. According to certain embodiments, when a pixel corresponding to the first region (e.g., the first region 801 in FIG. 8) is deactivated while multiple user interfaces are displayed on one display (e.g., the first display 161), the processor 120 may determine a user interface to be changed from among the multiple displayed user interfaces. According to an embodiment, the processor 120 may determine positions of a region for displaying the first user interface and a region for displaying the second user interface, among regions of the first display 161. The processor 120 may determine a region overlapping the first region 801, from among at least a partial region on the first display 161, corresponding to the first user interface, and at least a partial region on the first display 161, corresponding to the second user interface.

(184) Referring to operation 1605, the processor 120 may change one of the user interfaces, as selected from among the first user interface and the second user interface, which was identified to be the overlapping region determined in operation 1604. According to an embodiment, the processor 120 may change the user interface of the overlapping region identified from among the first user interface and the second user interface.

(185) FIG. 17A illustrates an unfolded state (e.g., a first state) of an electronic device 1700 according to certain embodiments.

(186) FIG. 17B illustrates a folded state (e.g., a second state) of the electronic device 1700 in FIG. 17A according to certain embodiments.

(187) Referring to FIGS. 17A and 17B, the electronic device 1700 may include a pair of housings 1710 and 1720 (e.g., foldable housings) coupled to be rotatable about a folding axis A through a hinge device so as to be folded with respect to each other, and a first display 1730 (e.g., a flexible display, a foldable display, or a main display) and a second display 1751 (e.g., a sub display), disposed through the pair of housings 1710 and 1720. According to an embodiment, the hinge device may be disposed so as not to be viewed from outside through a first housing 1710 and a second housing 1720 in the folded state, and may be disposed so as not to be viewed, in the unfolded state, from outside through a hinge cover 1765 which protects the hinge device and covers a foldable part. Herein, a surface on which the first display 1730 is disposed may be defined as the front surface of the electronic device 1700, and a surface opposite to the front surface may be defined as the rear surface of the electronic device 1700. Furthermore, a surface surrounding the

space between the front surface and the rear surface may be defined as the side surface of the electronic device **1700**.

(188) According to certain embodiments, the pair of housings **1710** and **1720** may include the first housing **1710** and the second housing **1720** disposed to be foldable with respect to each other through the hinge device. According to an embodiment, the pair of housings **1710** and **1720** are not limited to the forms and coupling illustrated in FIGS. **17A** and **17B**, and may be implemented by other shapes or a combination and/or coupling of other components. According to an embodiment, the first housing **1710** and the second housing **1720** may be disposed at both sides with reference to the folding axis A, and may have shapes which are overall symmetric with respect to the folding axis A. According to an embodiment, the first housing **1710** and the second housing **1720** may be asymmetrically folded with reference to the folding axis A. According to an embodiment, an angle or a distance formed between the first housing **1710** and the second housing **1720** may vary depending on whether the electronic device **1700** is in an unfolded state (e.g., a first state), a folded state (e.g., a second state), or an intermediate state (e.g., a third state).

(189) According to certain embodiments, in the unfolded state of the electronic device **1700**, the first housing **1710** may be connected to the hinge device, and may include a first surface **1711** disposed to face the front surface of the electronic device **1700**, a second surface **1712** facing a direction opposite to the direction faced by the first surface **1711**, and a first side member **1713** surrounding at least a part of a first space between the first surface **1711** and the second surface **1712**. According to an embodiment, in the unfolded state of the electronic device **1700**, the second housing **1720** may be connected to the hinge device, and may include a third surface **1721** disposed to face the front surface of the electronic device **1700**, a fourth surface **1722** facing a direction opposite to the direction faced by the third surface **1721**, and a second side member **1723** surrounding at least a part of a second space between the third surface **1721** and the fourth surface **1722**. According to an embodiment, the first surface **1711** may face, in the unfolded state, the same direction as the third surface **1721**, and may face the third surface **1721** in the folded state. According to an embodiment, the electronic device **1700** may include a recess **1702** which is formed through structural coupling of the first housing **1710** and the second housing **1720** so as to receive the first display **1730**. According to an embodiment, the recess **1702** may have substantially the same size as the first display **1730**.

(190) According to certain embodiments, the hinge cover **1765** may be disposed between the first housing **1710** and the second housing **1720**, and may be disposed to cover the hinge device. According to an embodiment, depending on the unfolded state, the folded state, or the intermediate state of the electronic device **1700**, the hinge cover **1765** may be covered by a part of the first housing **1710** and a part of the second housing **1720** or may be exposed outside. For example, when the electronic device **1700** is in the unfolded state, the hinge cover **1765** may be covered by the first housing **1710** and the second housing **1720**, and thus may not be exposed. According to an embodiment, when the electronic device **1700** is in the folded state, the hinge cover **1765** may be exposed outside between the first housing **1710** and the second housing **1720**. According to an embodiment, in the case of the intermediate state in which the first housing **1710** and the second housing **1720** are folded with a certain angle, the hinge cover **1765** may be at least partially exposed to the outside of the electronic device **1700** between the first housing **1710** and the second housing **1720**. For example, a region of the hinge cover **1765** exposed outside may be smaller than that in a completely folded state. According to an embodiment, the hinge cover **1765** may include a curved surface.

(191) According to certain embodiments, when the electronic device **1700** is in the unfolded state (e.g., the state in FIG. **17A**), the first housing **1710** and the second housing **1720** may form an angle of 180 degrees, and a first region **1730a**, a folding region **1730c**, and a second region **1730b** of the first display **1730** may be disposed to form an identical flat surface and face an identical direction. In another embodiment, when the electronic device **1700** is in the unfolded state, the first housing

1710 may rotate 180 degrees with respect to the second housing **1720** to be reversely folded such that the second surface **1712** and the fourth surface **1722** face each other (an out-folding scheme). (192) According to certain embodiments, when the electronic device **1700** is in the folded state (e.g., the state in FIG. **17B**), the first surface **1711** of the first housing **1710** and the third surface **1721** of the second housing **1720** may be disposed to face each other. In this case, the first region **1730a** and the second region **1730b** of the first display **1730** may be disposed to face each other while forming a narrow angle (e.g., a range of 0 degrees-10 degrees) with each other through the folding region **1730c**. According to an embodiment, at least a part of the folding region **1730c** may be formed as a curved surface having a predetermined curvature radius. According to an embodiment, when the electronic device **1700** is in the intermediate state, the first housing **1710** and the second housing **1720** may be disposed with a certain angle therebetween. In this case, the first region **1730a** and the second region **1730b** of the first display **1730** may form an angle which is larger than that in the folded state and smaller than that in the unfolded state, and the curvature radius of the folding region **1730c** may be longer than that in the folded state. In an embodiment, the first housing **1710** and the second housing **1720** may form, through the hinge device, an angle which may stop at a designated folding angle between the folded state and the unfolded state (a free stop function). In an embodiment, the first housing **1710** and the second housing **1720** may operate, through the hinge device, while receiving pressure applied in a direction in which the same are unfolded or folded with reference to a designated inflection angle.

(193) According to certain embodiments, the electronic device **1700** may include at least one among at least one display **1730** or **1751** disposed in the first housing **1710** and/or the second housing **1720**, an input device **1715**, sound output devices **1727** and **1728**, sensor modules **1717a**, **1717b**, and **1726**, camera modules **1716a**, **1716b**, and **1725**, key input devices **1719**, an indicator (not shown), or a connector port **1729**. In an embodiment, in the electronic device **1700**, at least one of the elements may be omitted, or at least one other element may be additionally included.

(194) According to certain embodiments, the at least one display **1730** or **1751** may include the first display **1730** (e.g., a flexible display) disposed to be supported by the first surface **1711** of the first housing **1710**, the hinge device, and the third surface **1721** of the second housing **1720**, and the second display **1751** disposed in the inner space of the second housing **1720** so as to be viewed from outside through the fourth surface **1722**. According to an embodiment, the first display **1730** may be mainly used in the unfolded state of the electronic device **1700**, and the second display **1751** may be mainly used in the folded state of the electronic device **1700**. According to an embodiment, when the electronic device **1700** is in the intermediate state, the first display **1730** or the second display **1751** may be used based on the folding angle of the first housing **1710** and the second housing **1720**.

(195) According to certain embodiments, the first display **1730** may be disposed in a space formed by the pair of housings **1710** and **1720**. For example, the first display **1730** may be seated in the recess **1702** formed by the pair of housings **1710** and **1720**, and may be disposed to occupy most of the front surface of the electronic device **1700**. According to an embodiment, the first display **1730** may include a flexible display having at least a partial region which may be deformed into a flat surface or a curved surface. According to an embodiment, the first display **1730** may include the first region **1730a** facing the first housing **1710**, the second region **1730b** facing the second housing **1720**, and the folding region **1730c** connecting the first region **1730a** to the second region **1730b** and facing the hinge device.

(196) According to an embodiment, the first region **1730a** of the first display **1730** may substantially form the first surface **1711** of the first housing **1710**. According to an embodiment, the second region **1730b** of the first display **1730** may substantially form the third surface **1721** of the second housing **1720**.

(197) According to an embodiment, division of the region of the first display **1730** may be merely example physical division by the pair of housings **1710** and **1720** and the hinge device.

Substantially, the first display **1730** may be displayed as one seamless entire screen through the pair of housings **1710** and **1720** and the hinge device. According to an embodiment, the first region **1730a** and the second region **1730b** may have shapes which are fully symmetric with reference to the folding region **1730c**, or may have shapes which are partially asymmetric.

(198) According to certain embodiments, the electronic device **1700** may include a first rear cover **1740**, disposed on the second surface **1712** of the first housing **1710**, and a second rear cover **1750**, disposed on the fourth surface **1722** of the second housing **1720**. In an embodiment, at least a part of the first rear cover **1740** may be formed integrally with the first side member **1713**. In an embodiment, at least a part of the second rear cover **1750** may be formed integrally with the second side member **1723**. According to an embodiment, at least one of the first rear cover **1740** and the second rear cover **1750** may be formed of a substantially transparent plate (e.g., a polymer plate or a glass plate including various coated layers) or an opaque plate. According to an embodiment, the first rear cover **1740** may be formed of an opaque plate, which are made of, for example, coated or colored glass, ceramic, polymer, metal (e.g., aluminum, stainless steel (STS), or magnesium), or a combination of at least two of the materials. According to an embodiment, the second rear cover **1750** may be formed of a substantially transparent plate, which is made of, for example, glass or polymer. Therefore, the second display **1751** may be disposed in the inner space of the second housing **1720** so as to be viewed from outside through the second rear cover **1750**.

(199) According to certain embodiments, the input device **1715** may include a microphone **1715**. In an embodiment, the input device **1715** may include multiple microphones **1715** so as to sense the direction of a sound. According to an embodiment, the sound output devices **1727** and **1728** may include speakers **1727** and **1728**. According to an embodiment, the speakers **1727** and **1728** may include a call receiver **1727**, disposed through the fourth surface **1722** of the second housing **1720**, and an external speaker **1728**, disposed through the side member of the second housing **1720**. In an embodiment, the microphone **1715**, the speakers **1727** and **1728**, and the connector port **1729** may be disposed in spaces of the first housing **1710** and/or the second housing **1720**, and may be exposed to an external environment through at least one hole formed in the first housing **1710** and/or the second housing **1720**. In an embodiment, the holes formed in the first housing **1710** and/or the second housing **1720** may be commonly used for the microphone **1715** and the speakers **1727** and **1728**. In an embodiment, the sound output devices **1727** and **1728** may include a speaker (e.g., a piezo speaker) operating without any hole formed in the first housing **1710** and/or the second housing **1720**.

(200) According to certain embodiments, the camera modules **1716a**, **1716b**, and **1725** may include a first camera device **1716a** disposed in the first surface **1711** of the first housing **1710**, a third camera device **1716b** disposed in the second surface **1712** of the first housing **1710**, and/or a second camera device **1725** disposed in the fourth surface **1722** of the second housing **1720**. According to an embodiment, the electronic device **1700** may include a flash **1718** disposed near the third camera device **1716b**. According to an embodiment, the flash **1718** may include, for example, a light-emitting diode or a xenon lamp. According to an embodiment, each of the camera devices **1716a**, **1716b**, and **1725** may include one or multiple lenses, an image sensor, and/or an image signal process. In an embodiment, at least one of the camera devices **1716a**, **1716b**, and **1725** may include two or more lenses (wide-angle and telephoto lenses) and image sensors, and may be disposed together in any one surface of the first housing **1710** and/or the second housing **1720**.

(201) According to certain embodiments, the sensor modules **1717a**, **1717b**, and **1726** may generate an electrical signal or a data value corresponding to an operation state inside the electronic device **1700** or an environment state outside the electronic device **1700**. According to an embodiment, the sensor modules **1717a**, **1717b**, and **1726** may include a first sensor module **1717a** disposed in the first surface **1711** of the first housing **1710**, a second sensor module **1717b** disposed in the second surface **1712** of the first housing **1710**, and/or a third sensor module **1726** disposed in

the fourth surface **1722** of the second housing **1720**. In an embodiment, the sensor modules **1717a**, **1717b**, and **1726** may include at least one among a gesture sensor, a grip sensor, a color sensor, an infrared (IR) sensor, an illumination sensor, an ultrasonic sensor, an iris recognition sensor, or a distance detection sensor (a TOF sensor or a LiDAR scanner).

(202) According to certain embodiments, the electronic device **1700** may further include at least one among unillustrated sensor modules, for example, a barometric pressure sensor, an angle sensor, a gyro sensor, a magnetic sensor, a biosensor, a temperature sensor, a humidity sensor, or a fingerprint recognition sensor. In an embodiment, the fingerprint recognition sensor may be disposed through at least one of the first side member **1713** of the first housing **1710** and/or the second side member **1723** of the second housing **1720**.

(203) According to certain embodiments, the key input devices **1719** may be disposed to be exposed outside through the first side member **1713** of the first housing **1710**. In an embodiment, the key input devices **1719** may also be disposed to be exposed outside through the second side member **1723** of the second housing **1720**. In an embodiment, the electronic device **1700** may not include some or all of the above-mentioned key input devices **1719**, and key input devices **1719**, which are not included, may be implemented in other forms, such as soft keys, on the at least one display **1730** or **1751**. In another embodiment, the key input devices **1719** may be implemented by using pressure sensors included in the at least one display **1730** or **1751**.

(204) According to certain embodiments, the connector port **1729** may receive a connector (e.g., a USB connector or an interface connector port module (IF module)) for transmitting or receiving power and/or data to or from an external electronic device. In an embodiment, the connector port **1729** may perform a function of transmitting and receiving an audio signal to and from the external electronic device, or may further include a separate connector port (e.g., an earphone jack hole) for performing an audio signal transmission/reception function. According to certain embodiments, at least one camera device **1716a** or **1725** among the camera devices **1716a**, **1716b**, and **1725**, at least one sensor module **1717a** or **1726** among the sensor modules **1717a**, **1717b**, and **1726**, and/or the indicator may be disposed to be visually exposed through the at least one display **1730** or **1751**. For example, the at least one camera device **1716a** or **1725**, the at least one sensor module **1717a** or **1726**, and/or the indicator may be disposed under an active region (display area) of the display **1730** or **1751** in the inner space of at least one housing **1710** or **1720**, and may be disposed so as to be exposed to an external environment through an opening bored up to a cover member (e.g., a window layer (not shown) of the first display **1730** and/or the second rear cover **1750**). In another embodiment, some camera devices or sensor module **1704** may be disposed to perform functions thereof without being visually exposed through the display. For example, a region of the display **1751** (e.g., a display panel), facing the camera device and/or the sensor module, may not utilize a bored opening.

(205) According to certain embodiments, the first display **1730** may visually display information to the outside (e.g., a user) of the electronic device **101**. The first display **1730** may include at least some of the elements and/or functions of the display module **160** in FIG. 1. According to an embodiment, the first display **1730** may include a touch sensor or a pressure sensor, which is configured to sense a touch. According to certain embodiments, the first display **1730** may include multiple pixels (e.g., the multiple pixels P in FIG. 6) in at least a partial region thereof. According to an embodiment, each of the multiple pixels may be controlled by the processor **120** and/or a driving circuit for controlling the first display **1730** to emit light, thereby displaying visual information to the outside of the electronic device **101**. According to an embodiment, the first display **1730** may include at least two regions (e.g., the first region A1 and/or the second region A2 in FIG. 6) which are different from each other in the arrangement density of multiple pixels. The first region A1 and the second region A2 on the first display **1730** may have different pixel arrangement densities, and thus the respective regions may have different light transmittances. For example, the first region A1 may include multiple pixels with a relatively low arrangement density

(e.g., a first arrangement density) compared with the second region A2, and the second region A2 may include multiple pixels with a relatively high arrangement density (e.g., a second arrangement density) compared with the first region A1. In a region (e.g., the first region A1) having a relatively lower arrangement density among the regions of the first display **1730**, the light transmittance of a display may be higher than in the other region. According to an embodiment, a partial region (e.g., the first region A1) of the first display **1730** may be deactivated. For example, the first region A1, among the regions of the first display **1730**, may be deactivated, and the second region A2 may be activated. When a partial region of the first display **1730** is deactivated, at least one pixel disposed in the deactivated region may be deactivated. The deactivated or activated state of the partial region of the first display **1730** may be controlled and switched by the processor **120** and/or the driving circuit, which are connected to the first display **1730**. According to an embodiment, the first region A1 of the first display **1730** may be disposed to at least partially overlap a field-of-view region corresponding to the field of view (FOV) of the first camera device **1716a**.

(206) According to certain embodiments, the second display **1751** may visually display information to the outside (e.g., a user) of the electronic device **101**. The second display **1751** may include at least some among the elements and/or functions of the display module **160** in FIG. 1. According to an embodiment, the second display **1751** may include a touch sensor or a pressure sensor, which is configured to sense a touch. According to certain embodiments, the second display **1751** may include multiple pixels (e.g., the multiple pixels P in FIG. 6) in at least a partial region thereof. According to an embodiment, each of the multiple pixels may be controlled by the processor **120** and/or a driving circuit for controlling the second display **1751** to emit light, thereby displaying visual information to the outside of the electronic device **101**. According to an embodiment, the second display **1751** may include at least two regions (e.g., a third region and/or a fourth region) (e.g., the first region A1 and/or the second region A2 in FIG. 6) which are different from each other in the arrangement density of multiple pixels. The third region and the fourth region on the second display **1751** may have different pixel arrangement densities, and thus the respective regions may have different light transmittances. For example, the third region may include multiple pixels with a relatively low arrangement density (e.g., a first arrangement density) compared with the fourth region, and the fourth region may include multiple pixels with a relatively high arrangement density (e.g., a second arrangement density) compared with the third region. In a region (e.g., the third region) having a relatively lower arrangement density among the regions of the second display **1751**, the light transmittance of a display may be higher than in the other region. According to an embodiment, a partial region (e.g., the third region) of the second display **1751** may be deactivated. For example, the third region, among the regions of the second display **1751**, may be deactivated, and the fourth region may be activated. When a partial region of the second display **1751** is deactivated, at least one pixel disposed in the deactivated region may be deactivated. The deactivated or activated state of the partial region of the second display **1751** may be controlled and switched by the processor **120** and/or the driving circuit, which are connected to the second display **1751**. According to an embodiment, the third region of the second display **1751** may be disposed to at least partially overlap a field-of-view region corresponding to the field of view (FOV) of the second camera device **1725**.

(207) FIG. 18 is a flowchart showing operations of changing a user interface by an electronic device (e.g., the electronic device **101** in FIG. 7 or the electronic device **1700** in FIG. 17A) including multiple displays (e.g., the first display **1730** and the second display **1751** in FIG. 17A) (e.g., the first display **161** and the second display **162** in FIG. 7) and multiple cameras (e.g., the first camera device **1716a**, the third camera device **1716b**, and/or the second camera device **1725** in FIG. 17A) (e.g., the first camera **181** and the second camera **182** in FIG. 7) according to certain embodiments.

(208) Referring to FIG. 18, multiple operations of changing a user interface by an electronic device (e.g., the electronic device **101** in FIG. 1, the electronic device **101** in FIG. 7, or the electronic

device **1700** in FIG. **17A**) may be considered to be operations performed by a processor (e.g., the processor **120** in FIG. **7**) of the electronic device (e.g., **101**). Operations in FIG. **18** may be changed, may be replaced, and/or may be switched in the order thereof, and a new operation may be added.

(209) Referring to operation **1801**, the processor **120** may display a user interface on at least one of a first display (e.g., the first display **1730** in FIG. **17A** or the first display **161** in FIG. **7**) and a second display (e.g., the second display **1751** in FIG. **17B** or the second display **162** in FIG. **7**). According to certain embodiments, the processor **120** may control the first display **161** to display a user interface. The user interface may include at least one graphical object which is visually displayed. According to an embodiment, the user interface may include a graphical user interface. At least one object included in the user interface may include an image object which may be visually displayed on a display (e.g., the first display **161**). According to certain embodiments, the processor **120** may control the second display **162** to display a user interface. The user interface may include at least one graphical object which is visually displayed. According to an embodiment, the processor **120** may activate at least one of the first display **161** and the second display **162**, and may display the user interface including the at least one object on the first display **161** and/or the second display **162**. According to an embodiment, the processor **120** may activate one of the first display **161** and the second display **162**, and may switch one of the first display **161** and the second display **162** from the activated state to a deactivated state while switching the other deactivated display to an activated state. According to another embodiment, the processor **120** may simultaneously activate the first display **161** and the second display **162** to display a user interface on each display.

(210) Referring to operation **1802**, the processor **120** may activate a camera (e.g., the first camera **181** and/or the second camera **182** in FIG. **7**). According to certain embodiments, the processor **120** may capture an image. According to an embodiment, the processor **120** may use the first camera **181** and/or the second camera **182** to capture a still image and/or a moving image. The processor **120** may receive an input regarding still-image and/or moving-image capturing, and may control, based on the received input, the camera to capture a still image and/or a moving image. According to an embodiment, the input regarding image capturing, received by the processor **120**, may include an input for activating a camera (e.g., the first camera **181** and/or the second camera **182**). The processor **120** may receive the input regarding image capturing to activate the camera.

(211) Referring to operation **1803**, the processor **120** may determine which camera was activated from among the multiple cameras equipped in the electronic device. For example, the processor **120** may determine which of a first camera (e.g., the first camera **181** in FIG. **7** or the first camera device **1716a** in FIG. **17A**), a second camera (e.g., the second camera **182** in FIG. **7** or the second camera device **1725** in FIG. **17A**) or a third camera (e.g., the third camera device **1716b** in FIG. **17A**) is the activated camera. According to certain embodiments, the processor **120** may activate one of multiple cameras (e.g., the first camera, the second camera, and/or the third camera), and may determine the activated camera. According to an embodiment, the processor **120** may determine whether the activated camera is the first camera, the second camera, or the third camera. The processor **120** may move to operation **1804** when the activated camera is determined to be the first camera, may move to operation **1806** when the activated camera is determined to be the second camera, and may end operations according to FIG. **18** when the activated camera is determined to be the third camera.

(212) Referring to operation **1804** in which the first camera was activated, the processor **120** may deactivate at least one pixel corresponding to a first region (e.g., the first region **A1** in FIG. **5B** or the first region **801** in FIG. **8**). According to certain embodiments, the processor **120** may deactivate at least a partial region (e.g., the first region) of the region of the first display **161**. According to an embodiment, when the camera (e.g., the first camera **181**) is activated, the processor **120** may deactivate a pixel included in at least a partial region of the first display **161** that

corresponds to the camera or the field of view of the camera. According to an embodiment, the first display **161** may include a first region (e.g., the first region **A1** in FIG. 5B or the first region **801** in FIG. 8) overlapping an effective aperture or the field of view of the first camera **181** and a second region (e.g., the second region **A2** in FIG. 5B or the second region **802** in FIG. 8) surrounding the first region **801**. According to an embodiment, the first region **801** may be formed to have light transmittance utilized by the first camera **181** by adjusting a pixel density and/or a wiring density to be relatively low. According to an embodiment, the second region **802** may include a normal active area, that is, a region in which a pixel density and/or a wiring density is high compared with the first region **801**. According to an embodiment, the second region **802** may be a region in which the light transmittance for the camera (e.g., the first camera **181**) is not considered. According to an embodiment, when the first camera **181** is activated, the processor **120** may deactivate at least one pixel corresponding to the first region **801** on the first display **161**. According to an embodiment, the processor **120** may deactivate at least some of multiple pixels corresponding to the first region **801**. According to an embodiment, the processor **120** may deactivate all pixels corresponding to the first region **801**.

(213) Referring to operation **1805**, the processor **120** may change the user interface so at least a portion of the same is moved to the second region **802**. According to certain embodiments, the processor **120** may change the user interface so as to correspond to at least a part of the remaining region, which is not deactivated, in the region of the first display **161**. According to an embodiment, the processor **120** may change the user interface so as to correspond to the second region **802** on the first display **161**. The second region may include at least a partial region of the remaining region of the first display **161**, which surrounds the first region **801**. The processor **120** may distinguish the first region **801** and the second region **802** in the remaining region other than the first region **801** on the first display **161**. According to an embodiment, the processor **120** may read data designated about the range of the second region **802** in a memory (e.g., the memory **130** in FIG. 1) to determine the second region **802**. According to an embodiment, the processor **120** may determine the first region **801**, and may determine that a region within a designated distance from the first region **801** in the region of the first display **161** is the second region. According to an embodiment, the processor **120** may determine that a region including a graphical object (e.g., a window or a tool bar), which overlaps the first region **801** or is displayed in a region within the designated distance from the first region **801**, among graphical objects displayed on the first display **161** is the second region. In this case, the shape and/or size of the second region **802** may be changed based on the user interface.

(214) Referring to operation **1806** in which the second camera is activated, the processor **120** may deactivate at least one pixel corresponding to a third region. According to an embodiment, the second display **162** may include at least two regions (e.g., a third region and/or a fourth region) (e.g., the first region **A1** and/or the second region **A2** in FIG. 6) which are different from each other, in the arrangement density of multiple pixels. The third region and the fourth region on the second display **162** may have different pixel arrangement densities, and thus the respective regions may have different light transmittances. For example, the third region may include multiple pixels with a relatively low arrangement density (e.g., a first arrangement density) compared with the fourth region, and the fourth region may include multiple pixels with a relatively high arrangement density (e.g., a second arrangement density) compared with the third region. In a region (e.g., the third region) having a relatively lower arrangement density among the regions of the second display **162**, the light transmittance of a display may be higher than in the other region. According to an embodiment, a partial region (e.g., the third region) of the second display **162** may be deactivated. For example, the third region, among the regions of the second display **162**, may be deactivated, and the fourth region may be activated. When a partial region of the second display **162** is deactivated, at least one pixel disposed in the deactivated region may be deactivated. The deactivated or activated state of the partial region of the second display **162** may be controlled and

switched by the processor **120** and/or the driving circuit, which are connected to the second display **162**. According to an embodiment, the third region of the second display **162** may be disposed to at least partially overlap a field-of-view region corresponding to the field of view (FOV) of the second camera device **182**. According to certain embodiments, the processor **120** may deactivate at least a partial region (e.g., the third region) in the region of the second display **162**. According to an embodiment, when a camera (e.g., the second camera **182**) is activated, the processor **120** may deactivate a pixel included in at least a partial region of the second display **162**, which corresponds to the camera or the field of view of the camera. According to an embodiment, the second display **162** may include a third region (e.g., the first region **A1** in FIG. 5B or the first region **801** in FIG. 8) overlapping the effective aperture or the field of view of the second camera **182** and a fourth region (e.g., the second region **A2** in FIG. 5B or the second region **802** in FIG. 8) surrounding the third region. According to an embodiment, the third region may be formed to have light transmittance utilized by the second camera **182** by adjusting a pixel density and/or a wiring density to be relatively low. According to an embodiment, the fourth region may include a normal active area, that is, a region in which a pixel density and/or a wiring density is high compared with the third region. According to an embodiment, the fourth region may be a region in which the light transmittance for the camera (e.g., the second camera **182**) is not considered. According to an embodiment, when the second camera **182** is activated, the processor **120** may deactivate at least one pixel corresponding to the third region on the second display **162**. According to an embodiment, the processor **120** may deactivate at least some of multiple pixels corresponding to the third region. According to an embodiment, the processor **120** may deactivate all pixels corresponding to the third region.

(215) Referring to operation **1807**, the processor **120** may change the user interface so at least a portion of the same is moved to the fourth region. According to certain embodiments, the processor **120** may change the user interface so as to correspond to at least a part of the remaining region, which is not deactivated, in the region of the second display **162**. According to an embodiment, the processor **120** may change the user interface so as to correspond to the fourth region on the second display **162**. The fourth region may include at least a partial region of the remaining region of the second display **162**, which surrounds the third region. The processor **120** may distinguish the third region and the fourth region in the remaining region other than the third region on the second display **162**. According to an embodiment, the processor **120** may read data designated about the range of the fourth region in a memory (e.g., the memory **130** in FIG. 1) to determine the fourth region. According to an embodiment, the processor **120** may determine the third region, and may determine that a region within a designated distance from the third region in the region of the second display **162** is the fourth region. According to an embodiment, the processor **120** may determine that a region including a graphical object (e.g., a window or a tool bar), which overlaps the third region or is displayed in a region within the designated distance from the third region, among graphical objects displayed on the second display **162** is the fourth region. In this case, the shape and/or size of the fourth region may be changed based on the user interface.

(216) An electronic device according to certain embodiments disclosed herein may include a first camera, a first display panel including multiple pixels and disposed to overlap, in at least a partial region thereof, a field-of-view region corresponding to the field of view of the first camera, and a processor, in which the processor is configured to display a graphic user interface on the first display panel, sense activation of the first camera, deactivate at least one pixel, among the multiple pixels, corresponding to a first region which is at least a partial region of the first display panel, and change the graphic user interface so as to correspond to a second region on the first display panel, which is at least partially in contact with the first region.

(217) Furthermore, the first region of the first display panel may have a first transmittance, may at least partially overlap the first camera, and may include the field-of-view region, and the second region may have a second transmittance lower than the first transmittance.

(218) Furthermore, the graphic user interface may include at least one object including a first object, and the processor may be configured to determine information about a position in which the first object is displayed on the first display panel, and change the graphic user interface, based on the information about the position in which the first object is displayed on the first display panel and information about a position of the first region.

(219) Furthermore, the at least one object may include at least one among at least a part of an execution screen of an application executed by the processor, an icon, a widget, and a state display window.

(220) Furthermore, the processor may be configured to change the graphic user interface by moving the position of the first object.

(221) Furthermore, the processor may be configured to change the graphic user interface when the position in which the first object is displayed on the first display panel overlaps the position of the first region.

(222) Furthermore, the graphic user interface may include multiple objects including the first object, and the processor may be configured to, when a position in which one of the multiple objects is displayed on the first display panel overlaps the first region, change the graphic user interface by moving a position in which an object, positioned within a designated distance from the first region, among the multiple objects, is displayed on the first display panel.

(223) Furthermore, the processor may be configured to change the graphic user interface, based on the form of the second region.

(224) Furthermore, the processor may be configured to execute a first application and control the first display panel to display a first graphic user interface including an execution screen of the first application, and the graphic user interface may include at least one object displayed by the execution screen of the first application.

(225) Furthermore, the processor may be configured to determine whether to change the first graphic user interface, based on the first application, and change the first graphic user interface, based on the determination.

(226) Furthermore, the processor may be configured not to change the first graphic user interface when the first application includes a moving-image playback function.

(227) Furthermore, the processor may be configured to further execute a second application simultaneously with the first application, control the first display panel to display, simultaneously with the first graphic user interface, a second graphic user interface including an execution screen of the second application, determine a region overlapping the first region among a region of the first display panel corresponding to the first graphic user interface and a region of the first display panel corresponding to the second graphic user interface, and change a graphic user interface corresponding to the overlapping region among the first graphic user interface and the second graphic user interface.

(228) Furthermore, the electronic device may further include a second camera disposed in a partial region of the electronic device which does not overlap the first display panel, in which the processor is configured to sense activation of a camera, determine whether the activated camera is the first camera, deactivate at least one pixel corresponding to the first region when the activated camera is the first camera as a result of the determination, and change the graphic user interface so as to correspond to the second region.

(229) Furthermore, the electronic device may include a housing structure, which includes a hinge, a first housing connected to the hinge and including a first surface and a second surface facing a direction opposite to a direction faced by the first surface, and a second housing connected to the hinge and including a third surface and a fourth surface facing a direction opposite to a direction faced by the third surface, the first housing and the second housing being connected so as to be folded or unfolded with reference to a folding axis through the hinge, the first surface and the third surface facing an identical direction in an unfolded first state, and the first surface facing the third

surface in a folded second state, a second display panel exposed outside through at least a part of the fourth surface, and a second camera disposed in the third surface or the fourth surface, in which the first display panel includes a flexible display disposed across the first surface and the third surface, and the processor is configured to sense activation of a camera, determine whether the activated camera is the first camera, deactivate at least one pixel corresponding to the first region when the activated camera is the first camera as a result of the determination, and change the graphic user interface so as to correspond to the second region.

(230) A method of changing a graphic user interface by an electronic device, according to certain embodiments disclosed herein, including a first camera and a first display panel disposed to overlap, in at least a partial region thereof, a field-of-view region corresponding to the field of view of the first camera, the first display panel including a first region which has a first transmittance, at least partially overlaps the first camera, and includes the field-of-view region, the method including displaying a graphic user interface on the first display panel, sensing activation of the first camera, deactivating at least one pixel of the first display panel, corresponding to a first region, and changing the graphic user interface so as to correspond to a second region on the first display panel, which is at least partially in contact with the first region.

(231) Furthermore, the graphic user interface may include at least one object including a first object, and the method may include changing the graphic user interface, based on information about a position in which the first object is displayed on the first display panel and information about a position of the first region.

(232) Furthermore, the at least one object may include at least one among at least a part of an execution screen of an application executed by the processor, an icon, a widget, and a state display window.

(233) Furthermore, the graphic user interface may include multiple objects including the first object, and the method may include, when a position in which one of the multiple objects is displayed on the first display panel overlaps the first region, changing the graphic user interface by moving a position in which an object, positioned within a designated distance from the first region, among the multiple objects, is displayed on the first display panel.

(234) Furthermore, the method may include changing the graphic user interface, based on the form of the second region.

(235) Furthermore, the method may further include executing a first application, and controlling the first display panel to display a first graphic user interface including an execution screen of the first application, and the graphic user interface may include at least one object displayed by the execution screen of the first application.

(236) Furthermore, the method may include determining whether to change the graphic user interface, based on the first application, and changing the graphic user interface, based on the determination.

(237) Furthermore, the electronic device may further include a second camera disposed in a region of the electronic device which does not overlap the first display panel, and the method may include sensing activation of a camera, determining whether the activated camera is the first camera, deactivating at least one pixel corresponding to the first region when the activated camera is the first camera as a result of the determination, and changing the graphic user interface so as to correspond to the second region.

(238) The electronic device according to certain embodiments disclosed herein may be one of various types of electronic devices. The electronic devices may include, for example, a portable communication device (e.g., a smart phone), a computer device, a portable multimedia device, a portable medical device, a camera, a wearable device, or a home appliance. The electronic device according to embodiments of the disclosure is not limited to those described above.

(239) It should be appreciated that certain embodiments of the disclosure and the terms used therein are not intended to limit the technological features set forth herein to particular

embodiments and include various changes, equivalents, or alternatives for a corresponding embodiment. With regard to the description of the drawings, similar reference numerals may be used to designate similar or relevant elements. A singular form of a noun corresponding to an item may include one or more of the items, unless the relevant context clearly indicates otherwise. As used herein, each of such phrases as “A or B,” “at least one of A and B,” “at least one of A or B,” “A, B, or C,” “at least one of A, B, and C,” and “at least one of A, B, or C,” may include all possible combinations of the items enumerated together in a corresponding one of the phrases. As used herein, such terms as “a first”, “a second”, “the first”, and “the second” may be used to simply distinguish a corresponding element from another, and does not limit the elements in other aspect (e.g., importance or order). It is to be understood that if an element (e.g., a first element) is referred to, with or without the term “operatively” or “communicatively”, as “coupled with/to” or “connected with/to” another element (e.g., a second element), it means that the element may be coupled/connected with/to the other element directly (e.g., wiredly), wirelessly, or via a third element.

(240) As used herein, the term “module” may include a unit implemented in hardware, software, or firmware, and may be interchangeably used with other terms, for example, “logic,” “logic block,” “component,” or “circuit”. The “module” may be a minimum unit of a single integrated component adapted to perform one or more functions, or a part thereof. For example, according to an embodiment, the “module” may be implemented in the form of an application-specific integrated circuit (ASIC).

(241) Certain embodiments as set forth herein may be implemented as software (e.g., the program **140**) including one or more instructions that are stored in a storage medium (e.g., the internal memory **136** or external memory **138**) that is readable by a machine (e.g., the electronic device **101**). For example, a processor (e.g., the processor **120**) of the machine (e.g., the electronic device **101**) may invoke at least one of the one or more instructions stored in the storage medium, and execute it. This allows the machine to be operated to perform at least one function according to the at least one instruction invoked. The one or more instructions may include a code generated by a compiler or a code executable by an interpreter. The machine-readable storage medium may be provided in the form of a non-transitory storage medium. The term “non-transitory” simply means that the storage medium is a tangible device, and does not include a signal (e.g., an electromagnetic wave), but this term does not differentiate between where data is semi-permanently stored in the storage medium and where the data is temporarily stored in the storage medium.

(242) According to an embodiment, a method according to certain embodiments of the disclosure may be included and provided in a computer program product. The computer program product may be traded as a product between a seller and a buyer. The computer program product may be distributed in the form of a machine-readable storage medium (e.g., compact disc read only memory (CD-ROM)), or be distributed (e.g., downloaded or uploaded) online via an application store (e.g., Play Store™), or between two user devices (e.g., smart phones) directly. If distributed online, at least part of the computer program product may be temporarily generated or at least temporarily stored in the machine-readable storage medium, such as memory of the manufacturer's server, a server of the application store, or a relay server.

(243) According to certain embodiments, each element (e.g., a module or a program) of the above-described elements may include a single entity or multiple entities, and some of the multiple entities may be separately disposed in any other element. According to certain embodiments, one or more of the above-described elements may be omitted, or one or more other elements may be added. Alternatively or additionally, a plurality of elements (e.g., modules or programs) may be integrated into a single element. In such a case, according to certain embodiments, the integrated element may still perform one or more functions of each of the plurality of elements in the same or similar manner as they are performed by a corresponding one of the plurality of elements before the integration. According to certain embodiments, operations performed by the module, the program,

or another element may be carried out sequentially, in parallel, repeatedly, or heuristically, or one or more of the operations may be executed in a different order or omitted, or one or more other operations may be added.

Claims

1. An electronic device, comprising: a first camera; a first display panel including multiple pixels and disposed to overlap the first camera, the first display panel including a first region overlapping a field of view of the first camera and a second region which is outside of the first region; and a processor, wherein the processor is configured to: display a graphic user interface comprising at least a partial of a first object overlapping the first region and a second object on the second region of the first display panel, control to activate the first camera in response to an input by a user while displaying the graphic user interface, deactivate at least one pixel, among the multiple pixels, corresponding to the first region, and change the graphic user interface by moving, the first object overlapping the field of view of the first camera in a direction toward the second object into the second region and rearranging with the second object on the first display panel.
2. The electronic device of claim 1, wherein the first region of the first display panel includes a first transmittance, at least partially overlaps the first camera, and is disposed within a field-of-view region corresponding to a field-of-view of the first camera, and wherein the second region includes a second transmittance that is lower than the first transmittance.
3. The electronic device of claim 1, wherein the graphic user interface includes the first object, and wherein the processor is configured to: determine a position at which the first object is displayed on the first display panel, and change the graphic user interface, based on the determined position in which the first object is displayed, and a position of the first region.
4. The electronic device of claim 3, wherein changing the graphic user interface includes moving the position of the first object.
5. The electronic device of claim 3, wherein the graphic user interface is changed when the position at which the first object is displayed overlaps with the position of the first region.
6. The electronic device of claim 3, wherein changing the graphic user interface includes moving a display position of the second object, based on detecting the second object disposed within a predesignated distance of the first region.
7. The electronic device of claim 1, wherein the processor is further configured to change the graphic user interface, based on a configuration of the second region.
8. The electronic device of claim 1, wherein the processor is further configured to: execute a first application, and control the first display panel to display a first graphic user interface of the first application, including at least one object.
9. The electronic device of claim 8, wherein the processor is further configured to: determine whether to change the first graphic user interface, based on a configuration of the first application.
10. The electronic device of claim 9, wherein the processor is further configured to maintain the first graphic user interface in an absence of change, when a configuration of the first application includes a video playback function.
11. The electronic device of claim 8, wherein the processor is further configured to: execute a second application simultaneously with the first application, control the first display panel to display, a second graphic user interface of the second application simultaneously with the first graphic user interface, determine whether any portion of the first graphic user interface or the second graphic user interface overlaps the first region, and change the first graphic user interface and/or the second graphic user interface based on detecting a respective overlap with the first region.
12. The electronic device of claim 1, further comprising a second camera disposed in a non-display region of the electronic device, wherein the processor is further configured to: detect activation of

one of the first camera and the second camera, and determine whether the first camera is activated based on the detected activation, wherein the at least one pixel is deactivated and the graphic user interface is changed based on determining that the first camera is activated.

13. The electronic device of claim 12, further comprising: a housing structure, including a hinge, a first housing connected to the hinge and including a first surface and a second surface facing a direction opposite to a direction faced by the first surface, and a second housing connected to the hinge and including a third surface and a fourth surface facing a direction opposite to a direction faced by the third surface, wherein the first housing and the second housing are foldable along a folding axis defined by the hinge, wherein the first surface and the third surface face a same direction in an unfolded first state, and wherein the first surface faces the third surface in a folded second state, and a second display panel visually exposed to an exterior environment through at least a part of the fourth surface; and a second camera disposed in the third surface or the fourth surface, and wherein the first display panel includes a flexible display spanning across the first surface and the third surface.

14. A method of changing a graphic user interface by an electronic device comprising a first camera and a first display panel disposed to overlap the first camera, the first display panel comprising a first region which has a first transmittance and at least partially overlaps the first camera, and a second region which is outside of the first region, the method comprising: displaying the graphic user interface comprising at least a partial of a first object overlapping the first region and a second object on the second region of the first display panel; controlling to activate the first camera in response to an input by a user while displaying the graphic user interface; deactivating at least one pixel, among multiple pixels, corresponding to the first region; and changing the graphic user interface by moving, the first object overlapping a field of view of the first camera in a direction toward the second object into the second region and rearranging with the second object on the first display panel.

15. The method of claim 14, wherein the graphic user interface includes the first object, the method further comprising: determining a position at which the first object is displayed on the first display panel, and changing the graphic user interface, based on the determined position in which the first object is displayed, and a position of the first region.

16. The method of claim 15, wherein changing the graphic user interface includes moving a display position of the second object, based on detecting the second object disposed within a predesignated distance of the first region.

17. The method of claim 14, further comprising changing the graphic user interface, based on a configuration of the second region.

18. The method of claim 14, further comprising: executing a first application; and controlling the first display panel to display a first graphic user interface of the first application, including at least one object.

19. The method of claim 18, comprising: determining whether to change the first graphic user interface, based on a configuration of the first application.

20. The method of claim 14, wherein the electronic device further comprises a second camera disposed in a non-display region of the electronic device, the method further comprising: detecting activation of one of the first camera and the second camera; and determining whether the first camera is activated based on the detected activation, wherein the at least one pixel is deactivated and the graphic user interface is changed based on determining that the first camera is activated.
