

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12408126
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Cheong; Gupil et al.

Electronic device, method, and non-transitory computer readable storage medium for managing transmissions to external electronic devices in wireless environment

Abstract

An electronic device is provided. The electronic device includes a communication circuitry for Bluetooth low energy (BLE), and a processor. The processor is configured to obtain a connected isochronous group (CIG) event including a first connected isochronous stream (CIS) event that includes first sub-events and a second CIS event that includes second sub-events that at least partially overlap at least part of the first sub-events, and transmit, based on receiving an acknowledgement (ACK) signal for first data transmitted to a first external electronic device via a first sub-event among the first sub-events, second data to a second external electronic device via a third sub-event among the second sub-events, wherein the third sub-event overlaps a second sub-event immediately after the first sub-event among the first sub-events.

Inventors: Cheong; Gupil (Suwon-si, KR), Kang; Doosuk (Suwon-si, KR), Yoo; Hyungseoung (Suwon-si, KR), Jin; Juyeon (Suwon-si, KR)

Applicant: Samsung Electronics Co., Ltd. (Suwon-si, KR)

Family ID: 85386559

Assignee: Samsung Electronics Co., Ltd. (Suwon-si, KR)

Appl. No.: 17/896655

Filed: August 26, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230071138 A1	Mar. 09, 2023

Foreign Application Priority Data

KR	10-2021-0120056	Sep. 08, 2021
----	-----------------	---------------

Related U.S. Application Data

continuation parent-doc WO PCT/KR2022/011707 20220805 PENDING child-doc US 17896655

Publication Classification

Int. Cl.: H04W56/00 (20090101); H04L65/1069 (20220101); H04L65/613 (20220101); H04W4/80 (20180101); H04W76/14 (20180101); H04W76/15 (20180101)

U.S. Cl.:

CPC H04W56/001 (20130101); H04L65/1069 (20130101); H04L65/613 (20220501); H04W4/80 (20180201); H04W76/14 (20180201); H04W76/15 (20180201);

Field of Classification Search

CPC: H04W (56/001); H04W (4/80); H04W (76/14); H04W (76/15); H04L (65/1069); H04L (65/613)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6320871	12/2000	Mizuguchi et al.	N/A	N/A
8331312	12/2011	Hart et al.	N/A	N/A
10652659	12/2019	Bhalla et al.	N/A	N/A
10834692	12/2019	Kondareddy	N/A	N/A
10856297	12/2019	Chen	N/A	N/A
10959128	12/2020	Chen	N/A	H04L 1/16
11075968	12/2020	Chen	N/A	H04L 65/80
11240586	12/2021	Yan	N/A	H04W 4/80
2007/0223441	12/2006	Exeler et al.	N/A	N/A
2019/0045304	12/2018	Bhalla	N/A	H04R 3/12
2020/0260322	12/2019	Chen	N/A	N/A
2020/0260448	12/2019	Chen	N/A	H04W 72/0453
2021/0184887	12/2020	Balasubramaniam et al.	N/A	N/A
2021/0376884	12/2020	Linsky	N/A	H04R 3/00
2022/0039041	12/2021	Zhu	N/A	H04L 12/40058
2022/0078541	12/2021	Zhu	N/A	H04W 4/38
2022/0200716	12/2021	Bonde	N/A	H04H 20/89
2022/0240018	12/2021	Hsieh	N/A	H04L 1/189

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
101771460	12/2012	CN	N/A
112188415	12/2020	CN	N/A
112312369	12/2020	CN	N/A
112740728	12/2020	CN	N/A
2020124371	12/2019	WO	N/A

OTHER PUBLICATIONS

European Search Report dated Sep. 25, 2024, issued in European Application No. 22867572.4. cited by applicant

International Search Report dated Nov. 24, 2022, issued in an International Application No. PCT/KR2022/011707. cited by applicant

European Intention to grant dated Jul. 8, 2025, issued in European Application No. 22867572.4. cited by applicant

Primary Examiner: Pasia; Redentor

Attorney, Agent or Firm: Jefferson IP Law, LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION(S) (1) This application is a continuation application, claiming priority under § 365(c), of an International application No.

PCT/KR2022/011707, filed on Aug. 5, 2022, which is based on and claims the benefit of a Korean patent application number 10-2021-0120056, filed on Sep. 8, 2021, in the Korean Intellectual Property Office, of a Korean patent application number 10-2021-0129314, filed on Sep. 29, 2021, in the Korean Intellectual Property Office, and of a Korean patent application number 10-2022-0064536, filed on May 26, 2022, in the Korean Intellectual Property Office, the disclosure of each of which is incorporated by reference herein in its entirety.

BACKGROUND

1. Technical Field

(1) The disclosure relates to an electronic device, a method, and a non-transitory computer readable storage media for managing transmissions to external electronic devices within wireless environments.

2. Description of Related Art

(2) Compared to legacy Bluetooth™ (or classic Bluetooth), Bluetooth™ low energy (BLE) may provide reduced power consumption and provide at least a similar or often greater communication range between connected devices. The BLE may be provided on an industrial, scientific, and medical (ISM) radio band.

SUMMARY

(3) In accordance with an aspect of the disclosure, an electronic device is provided. The electronic device includes a communication circuitry for Bluetooth low energy (BLE), and a processor operatively coupled with the communication circuitry, the processor being configured to obtain a connected isochronous group (CIG) event including a first connected isochronous stream (CIS) event that includes first sub-events, and a second CIS event that includes second sub-events that at least partially overlap at least part of the first sub-events, and transmit, based on receiving an acknowledgement (ACK) signal for first data transmitted to a first external electronic device via a

first sub-event among the first sub-events, second data to a second external electronic device via a third sub-event among the second sub-events, wherein the third sub-event overlaps a second sub-event immediately after the first sub-event among the first sub-events.

(4) In accordance with another aspect of the disclosure, a method for operating an electronic device with a communication circuitry for Bluetooth low energy (BLE) is provided. The method includes obtaining a connected isochronous group (CIG) event including a first connected isochronous stream (CIS) event that includes first sub-events and a second CIS event that includes second sub-events that at least partially overlap at least part of the first sub-events, and transmitting, based on receiving an acknowledgement (ACK) signal for first data transmitted to a first external electronic device via a first sub-event among the first sub-events, second data to a second external electronic device via a third sub-event among the second sub-events, wherein the third sub-event overlaps a second sub-event immediately after the first sub-event among the first sub-events.

(5) In accordance with another aspect of the disclosure, a non-transitory computer-readable storage medium is provided. The non-transitory computer-readable storage medium includes store one or more programs comprising instructions that, when executed by at least one processor of an electronic device with a communication circuitry for a BLE, cause the electronic device to obtain a connected isochronous group (CIG) event that includes a first connected isochronous stream (CIS) event including first sub-events and a second CIS event including second sub-events at least partially overlapping at least part of the first sub-events, based on receiving an acknowledgement (ACK) signal on first data transmitted to a first external electronic device via a first sub-event among the first sub-events, transmit second data to a second external electronic device via a third sub-event among the second sub-events overlapping a second sub-event immediately after the first sub-event among the first sub-events.

(6) In accordance with another aspect of the disclosure, an electronic device is provided. The electronic device includes communication circuitry for Bluetooth low energy (BLE), and a processor operatively coupled with the communication circuitry. The processor is configured to transmit, to a first external electronic device, a first packet that is a last packet from at least one target packet allocated for transmitting to the first external electronic device within a first connected isochronous stream (CIS) event in a connected isochronous group (CIG) event, via a second sub-event before a first sub-event ending the first CIS event, transmit, in response to receiving an acknowledgement (ACK) signal for the first packet via the second sub-event from the first external electronic device, a second packet to a second external electronic device via a sub-event among sub-events in a second CIS event in the CIG event, and re-transmit, in response to receiving a non-acknowledgement (NACK) signal for the first packet via the second sub-event from the first external electronic device, the first packet to the first external electronic device via a sub-event immediately after the second sub-event among remaining sub-events in the first CIS event.

(7) In accordance with another aspect of the disclosure, a method for operating an electronic device with a communication circuitry for Bluetooth low energy (BLE) is provided. The method includes transmitting, to a first external electronic device, a first packet that is a last packet from at least one target packet allocated for transmitting to the first external electronic device within a first connected isochronous stream (CIS) event in a connected isochronous group (CIG) event, via a second sub-event before a first sub-event ending the first CIS event, transmitting, in response to receiving an acknowledgement (ACK) signal for the first packet via the second sub-event from the first external electronic device, a second packet to a second external electronic device via a sub-event among sub-events in a second CIS event in the CIG event, and re-transmitting, in response to receiving a non-acknowledgement (NACK) signal for the first packet via the second sub-event from the first external electronic device, the first packet to the first external electronic device via a sub-event immediately after the second sub-event among remaining sub-events in the first CIS event.

(8) In accordance with another aspect of the disclosure, a non-transitory computer-readable storage medium is provided. The non-transitory computer-readable storage medium stores one or more programs comprising instructions that, when executed by at least one processor of an electronic device with a communication circuitry for a BLE, cause the electronic device to transmit, to a first external electronic device, a first packet that is a last packet from at least one target packet allocated for transmitting to the first external electronic device within a first connected isochronous stream (CIS) event in a connected isochronous group (CIG) event, via a second sub-event before a first sub-event ending the first CIS event, transmit, in response to receiving an acknowledgement (ACK) signal for the first packet via the second sub-event from the first external electronic device, a second packet to a second external electronic device via a sub-event among sub-events in a second CIS event in the CIG event, and re-transmit, in response to receiving a non-acknowledgement (NACK) signal for the first packet via the second sub-event from the first external electronic device, the first packet to the first external electronic device via a sub-event immediately after the second sub-event among remaining sub-events in the first CIS event.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a block diagram of an electronic device in a network environment according to an embodiment of the disclosure;
- (2) FIG. 2 illustrates an example of a wireless environment including an electronic device according to an embodiment of the disclosure;
- (3) FIG. 3 is a simplified block diagram of an electronic device according to an embodiment of the disclosure;
- (4) FIG. 4A is a timing diagram illustrating a connected isochronous group (CIG) event having sequential arrangements;
- (5) FIG. 4B is a timing diagram illustrating a CIG event having an interleaved arrangement;
- (6) FIGS. 5A, 5B, and 5C are timing diagrams illustrating a CIG event having a hybrid arrangement according to various embodiments of the disclosure;
- (7) FIG. 6 is a timing diagram illustrating an anchor point of a CIG event having a hybrid arrangement according to an embodiment of the disclosure;
- (8) FIG. 7A illustrates methods of transmitting data through a CIG event having a hybrid arrangement according to an embodiment of the disclosure;
- (9) FIG. 7B illustrates an example of transmitting data through a CIG event based on identification of a designated event according to an embodiment of the disclosure;
- (10) FIG. 8 is a flowchart illustrating a method of transmitting data via a CIG event including a first CIS event and a second CIS event in a hybrid arrangement according to an embodiment of the disclosure;
- (11) FIG. 9A is a flowchart illustrating a method of obtaining the CIG event including the first CIS event and the second CIS event in a hybrid arrangement, based on synchronization of an anchor point of each of the first sub-events in the first CIS event and an anchor point of each of the second sub-events in the second CIS event, according to an embodiment of the disclosure;
- (12) FIG. 9B is a flowchart illustrating a method of obtaining the CIG event including the first CIS event and the second CIS event in a hybrid arrangement, based on the length of each of the first sub-events in the first CIS event and the length of each of the second sub-events in the second CIS event, according to an embodiment of the disclosure;
- (13) FIG. 10 is a flowchart illustrating a method of transmitting data within a time interval in which at least part of the first CIS event overlaps at least part of the second CIS event, according to an embodiment of the disclosure;

(14) FIG. 11 is a flowchart illustrating a method of obtaining the CIG event including the first CIS event and the second CIS event in a hybrid arrangement based on attributes of data, according to an embodiment of the disclosure;

(15) FIG. 12 is a flowchart illustrating a method of obtaining the CIG event including the first CIS event and the second CIS event in a hybrid arrangement, based on the quality of a link between the first external electronic device and the electronic device, according to an embodiment of the disclosure;

(16) FIG. 13 is a flowchart illustrating a method of allocating an initial CIS event in a CIG event according to an embodiment of the disclosure;

(17) FIG. 14 is a flowchart illustrating a method of allocating an initial CIS event in a CIG event, based on the quality of a first link between a first external electronic device and an electronic device, and the quality of a second link between a second external electronic and an electronic device, according to an embodiment of the disclosure; and

(18) FIG. 15 is a flowchart illustrating a method of transmitting packets via a CIG event with a hybrid arrangement according to an embodiment of the disclosure.

DETAILED DESCRIPTION

(19) The following description with reference to the accompanying drawings is provided to assist in a comprehensive understanding of various embodiments of the disclosure as defined by the claims and their equivalents. It includes various specific details to assist in that understanding, but these are to be regarded as merely exemplary. Accordingly, those of ordinary skill in the art will recognize that various changes and modifications of the various embodiments described herein can be made without departing from the scope and spirit of the disclosure. In addition, descriptions of well-known functions and constructions may be omitted for clarity and conciseness.

(20) The terms and words used in the following description and claims are not limited to the bibliographical meanings, but are merely used by the inventor to enable a clear and consistent understanding of the disclosure. Accordingly, it should be apparent to those skilled in the art that the following description of various embodiments of the disclosure is provided for illustration purposes only and not for the purpose of limiting the disclosure as defined by the appended claims and their equivalents.

(21) It is to be understood that the singular forms “a,” “an,” and “the” include plural referents unless the context clearly dictates otherwise. Thus, for example, reference to “a component surface” includes reference to one or more of such surfaces.

(22) FIG. 1 is a block diagram of an electronic device in a network environment according to an embodiment of the disclosure.

(23) Referring to FIG. 1, an electronic device **101** in a network environment **100** may communicate with an electronic device **102** via a first network **198** (e.g., a short-range wireless communication network), or at least one of an electronic device **104** or a server **108** via a second network **199** (e.g., a long-range wireless communication network). According to an embodiment of the disclosure, the electronic device **101** may communicate with the electronic device **104** via the server **108**.

According to an embodiment of the disclosure, the electronic device **101** may include a processor **120**, a memory **130**, an input module **150**, a sound output module **155**, a display module **160**, an audio module **170**, a sensor module **176**, an interface **177**, a connecting terminal **178**, a haptic module **179**, a camera module **180**, a power management module **188**, a battery **189**, a communication module **190**, a subscriber identification module (SIM) **196**, or an antenna module **197**. In some embodiments of the disclosure, at least one of the components (e.g., the connecting terminal **178**) may be omitted from the electronic device **101**, or one or more other components may be added in the electronic device **101**. In some embodiments of the disclosure, some of the components (e.g., the sensor module **176**, the camera module **180**, or the antenna module **197**) may be implemented as a single component (e.g., the display module **160**).

(24) The processor **120** may execute, for example, software (e.g., a program **140**) to control at least

one other component (e.g., a hardware or software component) of the electronic device **101** coupled with the processor **120**, and may perform various data processing or computation. According to one embodiment of the disclosure, as at least part of the data processing or computation, the processor **120** may store a command or data received from another component (e.g., the sensor module **176** or the communication module **190**) in a volatile memory **132**, process the command or the data stored in the volatile memory **132**, and store resulting data in a non-volatile memory **134**. According to an embodiment of the disclosure, the processor **120** may include a main processor **121** (e.g., a central processing unit (CPU) or an application processor (AP)), or an auxiliary processor **123** (e.g., a graphics processing unit (GPU), a neural processing unit (NPU), an image signal processor (ISP), a sensor hub processor, or a communication processor (CP)) that is operable independently from, or in conjunction with, the main processor **121**. For example, when the electronic device **101** includes the main processor **121** and the auxiliary processor **123**, the auxiliary processor **123** may be adapted to consume less power than the main processor **121**, or to be specific to a specified function. The auxiliary processor **123** may be implemented as separate from, or as part of the main processor **121**.

(25) The auxiliary processor **123** may control at least some of functions or states related to at least one component (e.g., the display module **160**, the sensor module **176**, or the communication module **190**) among the components of the electronic device **101**, instead of the main processor **121** while the main processor **121** is in an inactive (e.g., sleep) state, or together with the main processor **121** while the main processor **121** is in an active state (e.g., executing an application). According to an embodiment of the disclosure, the auxiliary processor **123** (e.g., an image signal processor or a communication processor) may be implemented as part of another component (e.g., the camera module **180** or the communication module **190**) functionally related to the auxiliary processor **123**. According to an embodiment of the disclosure, the auxiliary processor **123** (e.g., the neural processing unit) may include a hardware structure specified for artificial intelligence model processing. An artificial intelligence model may be generated by machine learning. Such learning may be performed, e.g., by the electronic device **101** where the artificial intelligence is performed or via a separate server (e.g., the server **108**). Learning algorithms may include, but are not limited to, e.g., supervised learning, unsupervised learning, semi-supervised learning, or reinforcement learning. The artificial intelligence model may include a plurality of artificial neural network layers. The artificial neural network may be a deep neural network (DNN), a convolutional neural network (CNN), a recurrent neural network (RNN), a restricted boltzmann machine (RBM), a deep belief network (DBN), a bidirectional recurrent deep neural network (BRDNN), deep Q-network or a combination of two or more thereof but is not limited thereto. The artificial intelligence model may, additionally or alternatively, include a software structure other than the hardware structure.

(26) The memory **130** may store various data used by at least one component (e.g., the processor **120** or the sensor module **176**) of the electronic device **101**. The various data may include, for example, software (e.g., the program **140**) and input data or output data for a command related thereto. The memory **130** may include the volatile memory **132** or the non-volatile memory **134**.

(27) The program **140** may be stored in the memory **130** as software, and may include, for example, an operating system (OS) **142**, middleware **144**, or an application **146**.

(28) The input module **150** may receive a command or data to be used by another component (e.g., the processor **120**) of the electronic device **101**, from the outside (e.g., a user) of the electronic device **101**. The input module **150** may include, for example, a microphone, a mouse, a keyboard, a key (e.g., a button), or a digital pen (e.g., a stylus pen).

(29) The sound output module **155** may output sound signals to the outside of the electronic device **101**. The sound output module **155** may include, for example, a speaker or a receiver. The speaker may be used for general purposes, such as playing multimedia or playing record. The receiver may be used for receiving incoming calls. According to an embodiment of the disclosure, the receiver may be implemented as separate from, or as part of the speaker.

(30) The display module **160** may visually provide information to the outside (e.g., a user) of the electronic device **101**. The display module **160** may include, for example, a display, a hologram device, or a projector and control circuitry to control a corresponding one of the display, hologram device, and projector. According to an embodiment of the disclosure, the display module **160** may include a touch sensor adapted to detect a touch, or a pressure sensor adapted to measure the intensity of force incurred by the touch.

(31) The audio module **170** may convert a sound into an electrical signal and vice versa. According to an embodiment of the disclosure, the audio module **170** may obtain the sound via the input module **150**, or output the sound via the sound output module **155** or a headphone of an external electronic device (e.g., an electronic device **102**) directly (e.g., wiredly) or wirelessly coupled with the electronic device **101**.

(32) The sensor module **176** may detect an operational state (e.g., power or temperature) of the electronic device **101** or an environmental state (e.g., a state of a user) external to the electronic device **101**, and then generate an electrical signal or data value corresponding to the detected state. According to an embodiment of the disclosure, the sensor module **176** may include, for example, a gesture sensor, a gyro sensor, an atmospheric pressure sensor, a magnetic sensor, an acceleration sensor, a grip sensor, a proximity sensor, a color sensor, an infrared (IR) sensor, a biometric sensor, a temperature sensor, a humidity sensor, or an illuminance sensor.

(33) The interface **177** may support one or more specified protocols to be used for the electronic device **101** to be coupled with the external electronic device (e.g., the electronic device **102**) directly (e.g., wiredly) or wirelessly. According to an embodiment of the disclosure, the interface **177** may include, for example, a high-definition multimedia interface (HDMI), a universal serial bus (USB) interface, a secure digital (SD) card interface, or an audio interface.

(34) A connecting terminal **178** may include a connector via which the electronic device **101** may be physically connected with the external electronic device (e.g., the electronic device **102**). According to an embodiment of the disclosure, the connecting terminal **178** may include, for example, a HDMI connector, a USB connector, a SD card connector, or an audio connector (e.g., a headphone connector).

(35) The haptic module **179** may convert an electrical signal into a mechanical stimulus (e.g., a vibration or a movement) or electrical stimulus which may be recognized by a user via his tactile sensation or kinesthetic sensation. According to an embodiment of the disclosure, the haptic module **179** may include, for example, a motor, a piezoelectric element, or an electric stimulator.

(36) The camera module **180** may capture a still image or moving images. According to an embodiment of the disclosure, the camera module **180** may include one or more lenses, image sensors, image signal processors, or flashes.

(37) The power management module **188** may manage power supplied to the electronic device **101**. According to one embodiment of the disclosure, the power management module **188** may be implemented as at least part of, for example, a power management integrated circuit (PMIC).

(38) The battery **189** may supply power to at least one component of the electronic device **101**. According to an embodiment of the disclosure, the battery **189** may include, for example, a primary cell which is not rechargeable, a secondary cell which is rechargeable, or a fuel cell.

(39) The communication module **190** may support establishing a direct (e.g., wired) communication channel or a wireless communication channel between the electronic device **101** and the external electronic device (e.g., the electronic device **102**, the electronic device **104**, or the server **108**) and performing communication via the established communication channel. The communication module **190** may include one or more communication processors that are operable independently from the processor **120** (e.g., the application processor (AP)) and supports a direct (e.g., wired) communication or a wireless communication. According to an embodiment of the disclosure, the communication module **190** may include a wireless communication module **192** (e.g., a cellular communication module, a short-range wireless communication module, or a global

navigation satellite system (GNSS) communication module) or a wired communication module **194** (e.g., a local area network (LAN) communication module or a power line communication (PLC) module). A corresponding one of these communication modules may communicate with the external electronic device via the first network **198** (e.g., a short-range communication network, such as Bluetooth™, Wi-Fi direct, or infrared data association (IrDA)) or the second network **199** (e.g., a long-range communication network, such as a legacy cellular network, a 5.sup.th generation (5G) network, a next-generation communication network, the Internet, or a computer network (e.g., LAN or wide area network (WAN))). These various types of communication modules may be implemented as a single component (e.g., a single chip), or may be implemented as multi components (e.g., multi chips) separate from each other. The wireless communication module **192** may identify and authenticate the electronic device **101** in a communication network, such as the first network **198** or the second network **199**, using subscriber information (e.g., international mobile subscriber identity (IMSI)) stored in the subscriber identification module **196**.

(40) The wireless communication module **192** may support a 5G network, after a 4.sup.th generation (4G) network, and next-generation communication technology, e.g., new radio (NR) access technology. The NR access technology may support enhanced mobile broadband (eMBB), massive machine type communications (mMTC), or ultra-reliable and low-latency communications (URLLC). The wireless communication module **192** may support a high-frequency band (e.g., the mm Wave band) to address, e.g., a high data transmission rate. The wireless communication module **192** may support various technologies for securing performance on a high-frequency band, such as, e.g., beamforming, massive multiple-input and multiple-output (massive MIMO), full dimensional MIMO (FD-MIMO), array antenna, analog beam-forming, or large-scale antenna. The wireless communication module **192** may support various requirements specified in the electronic device **101**, an external electronic device (e.g., the electronic device **104**), or a network system (e.g., the second network **199**). According to an embodiment of the disclosure, the wireless communication module **192** may support a peak data rate (e.g., 20 Gbps or more) for implementing eMBB, loss coverage (e.g., 164 dB or less) for implementing mMTC, or U-plane latency (e.g., 0.5 ms or less for each of downlink (DL) and uplink (UL), or a round trip of 1 ms or less) for implementing URLLC.

(41) The antenna module **197** may transmit or receive a signal or power to or from the outside (e.g., the external electronic device) of the electronic device **101**. According to an embodiment of the disclosure, the antenna module **197** may include an antenna including a radiating element including a conductive material or a conductive pattern formed in or on a substrate (e.g., a printed circuit board (PCB)). According to an embodiment of the disclosure, the antenna module **197** may include a plurality of antennas (e.g., array antennas). In such a case, at least one antenna appropriate for a communication scheme used in the communication network, such as the first network **198** or the second network **199**, may be selected, for example, by the communication module **190** (e.g., the wireless communication module **192**) from the plurality of antennas. The signal or the power may then be transmitted or received between the communication module **190** and the external electronic device via the selected at least one antenna. According to an embodiment of the disclosure, another component (e.g., a radio frequency integrated circuit (RFIC)) other than the radiating element may be additionally formed as part of the antenna module **197**.

(42) According to various embodiments of the disclosure, the antenna module **197** may form a mmWave antenna module. According to an embodiment of the disclosure, the mmWave antenna module may include a printed circuit board, a RFIC disposed on a first surface (e.g., the bottom surface) of the printed circuit board, or adjacent to the first surface and capable of supporting a designated high-frequency band (e.g., the mmWave band), and a plurality of antennas (e.g., array antennas) disposed on a second surface (e.g., the top or a side surface) of the printed circuit board, or adjacent to the second surface and capable of transmitting or receiving signals of the designated high-frequency band.

(43) At least some of the above-described components may be coupled mutually and communicate signals (e.g., commands or data) therebetween via an inter-peripheral communication scheme (e.g., a bus, general purpose input and output (GPIO), serial peripheral interface (SPI), or mobile industry processor interface (MIPI)).

(44) According to an embodiment of the disclosure, commands or data may be transmitted or received between the electronic device **101** and the external electronic device **104** via the server **108** coupled with the second network **199**. Each of the electronic devices **102** or **104** may be a device of a same type as, or a different type, from the electronic device **101**. According to an embodiment of the disclosure, all or some of operations to be executed at the electronic device **101** may be executed at one or more of the external electronic devices **102**, **104**, or **108**. For example, if the electronic device **101** should perform a function or a service automatically, or in response to a request from a user or another device, the electronic device **101**, instead of, or in addition to, executing the function or the service, may request the one or more external electronic devices to perform at least part of the function or the service. The one or more external electronic devices receiving the request may perform the at least part of the function or the service requested, or an additional function or an additional service related to the request, and transfer an outcome of the performing to the electronic device **101**. The electronic device **101** may provide the outcome, with or without further processing of the outcome, as at least part of a reply to the request. To that end, a cloud computing, distributed computing, mobile edge computing (MEC), or client-server computing technology may be used, for example. The electronic device **101** may provide ultra low-latency services using, e.g., distributed computing or mobile edge computing. In another embodiment of the disclosure, the external electronic device **104** may include an internet-of-things (IoT) device. The server **108** may be an intelligent server using machine learning and/or a neural network. According to an embodiment of the disclosure, the external electronic device **104** or the server **108** may be included in the second network **199**. The electronic device **101** may be applied to intelligent services (e.g., smart home, smart city, smart car, or healthcare) based on 5G communication technology or IoT-related technology.

(45) An electronic device, using an isochronous logical transport referred to as a connected isochronous stream (CIS), may transmit data (or packets) including information on multimedia contents to each of the external electronic devices through an isochronous link between each of the plurality of external electronic devices and the electronic device. For example, the CIS may be configured as a connected isochronous group (CIG) event including a plurality of CIS events.

(46) Meanwhile, the quality of a link (e.g., CIS link) between each of the plurality of external electronic devices and the electronic device may change depending on a change in a wireless environment including the electronic device. For example, when the electronic device communicates with each of the plurality of external electronic devices through the CIG event including the plurality of CIS events by sequential arrangement or interleaved arrangement, the quality of communication with each of the plurality of external electronic devices may be reduced according to a change in the quality of the link according to a change in a wireless environment.

(47) FIG. 2 illustrates an example of a wireless environment including an electronic device according to an embodiment of the disclosure.

(48) Referring to FIG. 2, the wireless environment **200** may include an electronic device **101**, a first external electronic device **201**, and a second external electronic device **202**.

(49) The electronic device **101** in the wireless environment **200** may be an audio source device such as e.g., a smartphone, a laptop computer, or a tablet personal computer (PC). The electronic device **101** may transmit data on audio played in the electronic device **101** to each of the first external electronic device **201** and the second external electronic device **202**. For example, the data may be usable within each of the first external electronic device **201** and the second external electronic device **202** to output audio from each of the first external electronic device **201** and the second external electronic device **202**. The electronic device **101** may be referred to as a master

device.

(50) The first external electronic device **201** and the second external electronic device **202** in the wireless environment **200** may be audio sink devices such as e.g., earbuds or earphones. For example, the first external electronic device **201** and the second external electronic device **202** may be configured as a pair, but it is not limited to thereto. Each of the first external electronic device **201** and the second external electronic device **202** may receive the data from the electronic device **101** and based on the data, output audio through a speaker of each of the first external electronic device **201** and the second external electronic device **202**. Each of the first external electronic device **201** and the second external electronic device **202** may be referred to as a slave device.

(51) The electronic device **101**, the first external electronic device **201**, and the second external electronic device **202** may support multi-stream audio. For example, synchronized and independent multiple audio streams may be transmitted between the electronic device **101** and the first external electronic device **201** and/or between the electronic device **101** and the second external electronic device **202**. For example, in order to support the multi-stream audio, a connected isochronous group (CIG) **203** including connected isochronous streams (CIS) may be used.

(52) The CIG **203** may consist of two or more CISs with the same ISO (isochronous) interval. For example, the CIG **203** may include a first CIS **204** and a second CIS **205**. Each of the first CIS **204** and the second CIS **205** may be a logical transport to cause the electronic device **101**, the first external electronic device **201**, and the second external electronic device **202** to transfer isochronous data unidirectionally or bidirectionally. Each of the first CIS **204** and the second CIS **205** may be associated with an asynchronous connection (ACL). Each of the first CIS **204** and the second CIS **205** may support packets of variable size and support transmitting one or more packets within an isochronous event.

(53) The first CIS **204** may be used to transmit at least one packet from the electronic device **101** to the first external electronic device **201**. For example, the at least one packet may be used to output audio played in the electronic device **101** through a speaker of the first external electronic device **201**. The first CIS **204** may be used to transmit an acknowledgement signal for the at least one packet or a non-acknowledgement signal for the at least one packet, from the first external electronic device **201** to the electronic device **101**. For example, the acknowledgement signal may be transmitted from the first external electronic device **201** to the electronic device **101** through the first CIS **204** to indicate that the first external electronic device **201** successfully receives the at least one packet, and the non-acknowledgement signal may be transmitted from the first external electronic device **201** to the electronic device **101** through the first CIS **204** to indicate that the first external electronic device **201** fails to receive the at least one packet.

(54) The second CIS **205** may be used to transmit at least one packet from the electronic device **101** to the second external electronic device **202**. For example, the at least one packet may be used to output audio played in the electronic device **101** through a speaker of the second external electronic device **202**. The audio output through the speaker of the first external electronic device **201** and the audio output through the speaker of the second external electronic device **202** may provide stereophonic sound, but it is not limited thereto. The second CIS **205** may be used to transmit an acknowledgement signal for the at least one packet or a non-acknowledgement signal for the at least one packet from the second external electronic device **202** to the electronic device **101**.

(55) FIG. 3 is a simplified block diagram of an electronic device according to an embodiment of the disclosure. Components indicated by the block diagram may be included in the electronic device **101** illustrated in FIG. 1 or the electronic device **101** illustrated in FIG. 2.

(56) FIG. 4A is a timing diagram illustrating a connected isochronous group (CIG) event having sequential arrangement according to an embodiment of the disclosure.

(57) FIG. 4B is a timing diagram illustrating a CIG event having an interleaved arrangement according to an embodiment of the disclosure.

(58) FIGS. 5A, 5B, and 5C are timing diagrams illustrating a CIG event having a hybrid

arrangement according to various embodiments of the disclosure.

(59) FIG. 6 is a timing diagram illustrating an anchor point of a CIG event having a hybrid arrangement according to an embodiment of the disclosure.

(60) FIG. 7A illustrates methods of transmitting data through a CIG event having a hybrid arrangement according to an embodiment of the disclosure.

(61) FIG. 7B illustrates an example of transmitting data through a CIG event based on identification of a designated event according to an embodiment of the disclosure.

(62) Referring to FIG. 3, the electronic device **101** may comprise a processor **120**, a memory **130**, and a communication circuitry **190**.

(63) The processor **120** may comprise the processor **120** in FIG. 1. The memory **130** may comprise the memory **130** of FIG. 1. The communication circuitry **190** may include the communication module **190** of FIG. 1 used to communicate with an external electronic device (e.g., the first external electronic device **201** or the second external electronic device **202** shown in FIG. 2) through the first network **198**.

(64) The processor **120** in the electronic device **101** may obtain, configure, or set a CIG event (e.g., the event of the CIG **203** shown in FIG. 2) including a first CIS event (e.g., an event of the first CIS **204** shown in FIG. 2) for the first external electronic device **201** and a second CIS event (e.g., an event of the second CIS **205** shown in FIG. 2) for the second external electronic device **202**, in order to transmit data or at least one packet to each of the first external electronic device **201** and the second external electronic device **202**. For example, the CIG event including the first CIS event and the second CIS event may start at a start timing of an initial sub-event of an initially scheduled CIS and may end at an end timing of the last sub-event within an ISO interval. For example, the anchor point of the CIG event may occur simultaneously with the anchor point of the first CIS event in the CIG event.

(65) Each of the first CIS event and the second CIS event may consist of one or more sub-events. For example, the sub-event in the first CIS event may be used to transmit packets from the electronic device **101** and transmit a response packet from the first external electronic device **201** (e.g., the acknowledgement signal defined through the description of FIG. 2 or the non-acknowledgement signal defined through the description of FIG. 2). A sub-event in the second CIS event may be used for transmitting a packet from the electronic device **101** and transmitting a response packet from the second external electronic device **202**.

(66) Each of the first CIS event and the second CIS event may be scheduled in a sequential arrangement or an interleaved arrangement within the CIG event. For example, referring to FIG. 4A, as shown in the timing diagram **400**, the processor **120** may schedule a first CIS event **402** including a first sub-event **404** and a second sub-event **405**, and a second CIS event **403** including a first sub-event **406** and a second sub-event **407** in a CIG event **401** in the sequential arrangement. As shown in timing diagram **400**, the processor **120** may acquire, configure, or set the CIG event **401** including the first CIS event **402** and the second CIS event **403** in the sequential arrangement by scheduling the second CIS event **403** immediately after the first CIS event **402**. Since the first CIS event **402** and the second CIS event **403** are scheduled back-to-back in the sequential arrangement, the first CIS event **402** and the second CIS event **403** do not overlap each other in the sequential arrangement.

(67) In another example, referring to FIG. 4B, as shown in timing diagram **450**, the processor **120** may schedule a first CIS event **402** including a first sub-event **404** and a second sub-event **405**, and a second CIS event **403** including a first sub-event **406** and a second sub-event **407** in a CIG event **401** in the interleaved arrangement. As shown in the timing diagram **450**, the processor **120** may obtain, configure, or set the CIG event **401** including the first CIS event **402** and the second CIS event **403** in the interleaved arrangement, by scheduling the first sub-event **406** in the second CIS event **403** immediately after the first sub-event **404** in the first CIS event **402**, scheduling the second sub-event **405** in the first CIS event **402** immediately after the first sub-event **406** in the

second CIS event **403**, and scheduling the second sub-event **407** in the second CIS event **403** immediately after the second sub-event **405** in the first CIS event **402**. For example, within the timing diagram **450**, since the first CIS event **402** starts at the start timing of the first sub-event **404** and ends at the end timing of the second sub-event **405**, while not including the first sub-event **406**, and the second CIS event **403** starts at the start timing of the first sub-event **406** and ends at the end timing of the second sub-event **407**, while not including sub-event **405**, the first CIS event **402** and the second CIS event **403** do not overlap each other in the interleaved arrangement. In each of the sequential arrangement and the interleaved arrangement, since the processor **120** may transmit a packet once through each of the first sub-event **404**, the second sub-event **405**, the first sub-event **406**, and the second sub-event **407**, the processor **120** may transmit a packet to the first external electronic device **201** at most twice through the first CIS event **402** and transmit a packet to the second external electronic device **202** at most twice through the second CIS event **403**, in each of the sequential arrangement and the interleaved arrangement. In other words, in each of the sequential arrangement and the interleaved arrangement, the opportunity to transmit a packet through the first CIS event **402** is fixed and the opportunity to transmit a packet through the second CIS event **403** is fixed. For example, in each of the sequential arrangement and the interleaved arrangement, the processor **120** may not adaptively change the number of times of transmitting a packet through the first CIS event **402** and the number of times of transmitting a packet through the second CIS event **403**, according to the quality of the first link between the first external electronic device **201** and the electronic device **101**, and the quality of the second link between the second external electronic device **202** and the electronic device **101**.

(68) Referring back to FIG. **3**, the processor **120** may obtain, configure, or set the CIG event in order to adaptively change the number of times of transmitting a packet through the first CIS event and the number of times of transmitting a packet through the second CIS event, by scheduling the second CIS event at least partially overlapping at least part of the first CIS event. For example, by scheduling the anchor point of the second CIS event within the first CIS event, the processor **120** may obtain the CIG event including the first CIS event and the second CIS event at least partially overlapping at least part of the first CIS event. The processor **120** may obtain the CIG event including the first CIS event and the second CIS event including the sub-event at least partially overlapping at least part of the sub-events in the first CIS event. Overlapping at least a part of the first CIS event and at least a part of the second CIS event may be referred to as a hybrid arrangement in terms of having both the characteristics of the sequential arrangement and the characteristics of the interleaved arrangement.

(69) The processor **120** may schedule the first CIS event and the second CIS event in the CIG event in the hybrid arrangement, based on satisfying a specified condition.

(70) For example, the processor **120** may schedule the first CIS event and the second CIS event in the CIG event in the hybrid arrangement, based on identifying that at least one external electronic device (e.g., the first external electronic device **201** and the second external electronic device **202**) supports the hybrid arrangement. The processor **120** may schedule the first CIS event and the second CIS event in the CIG event in the hybrid arrangement, based on identifying data indicating the support for the hybrid arrangement from capability information of the at least one external electronic device received from the at least one external electronic device. The processor **120** may schedule the first CIS event and the second CIS event in the CIG event in the hybrid arrangement, based on identifying that a modulation scheme of a signal received from the at least one external electronic device indicates supporting the hybrid arrangement.

(71) For example, under the condition that an anchor point of at least some of the sub-events in the first CIS event corresponds to an anchor point of at least some of the sub-events in the second CIS events, the processor **120** may obtain the CIG event including the second CIS event including the sub-events at least partially overlapping at least a part of the sub-events in the first CIS event. Under the condition that a time interval between an anchor point of a first sub-event among the

sub-events in the first CIS event and an anchor point of a second sub-event immediately after the first sub-event among the sub-events in the first CIS event is a multiple of a time interval between an anchor point of a third sub-event among the sub-events in the second CIS event and an anchor point of a fourth sub-event immediately after the third sub-event of the sub-events in the second CIS event, the processor **120** may obtain the CIG event including the second CIS event including the sub-events at least partially overlapping at least a part of the sub-events in the first CIS event. Under the condition that a time interval between an anchor point of the third sub-event among the sub-events in the second CIS event and an anchor point of the fourth sub-event among the sub-events in the second CIS event is a multiple of a time interval between an anchor point of the first sub-event among the sub-events in the first CIS event and an anchor point of the second sub-event among the sub-events in the first CIS event, the processor **120** may obtain the CIG event including the second CIS event including the sub-events at least partially overlapping at least a part of the sub-events in the first CIS event. Under the condition that a length of each of the sub-events in the first CIS event is a multiple of a length of each of the sub-events in the second CIS events or the length of each of the sub-events in the second CIS event is a multiple of the length of each of the sub-events in the first CIS events, the processor **120** may obtain the CIG event including the second CIS event including the sub-events at least partially overlapping at least the part of the sub-events in the first CIS event. For example, under the condition that the length of each of the sub-events in the first CIS event is identical to the length of each of the sub-events in the second CIS events, the processor **120** may obtain the CIG event including the first CIS event and the second CIS event including sub-events at least partially overlapping at least a part of the sub-events in the first CIS event.

(72) Referring to FIG. 5A, as shown in the timing diagram **500**, the processor **120** may set or obtain a CIG event **501** including a first CIS event **502** and a second CIS event **503** partially overlapping part of the first CIS event **502**. For example, the processor **120** may set or obtain the CIG event **501** by scheduling the first CIS event **502** and the second CIS event **503** so that each of the k th sub-event **502- k** (k is a natural number greater than 1 and less than n) to n -th sub-event **502- n** in the first CIS event **502** overlaps each of the first sub-event **503-1** to $(n-k+1)$ th sub-event **503- $(n-k+1)$** in the second CIS event **503**. Since the first CIS event **502** includes k th sub-events **502- k** to n -th sub-events **502- n** each overlapping the first sub-events **503-1** to $(n-k+1)$ th sub-event **503- $(n-k+1)$** and the first sub-events **502-1** to $(k-1)$ th sub-event **502- $(k-1)$** that do not overlap the second CIS event **503**, the number of times of transmitting a packet through the first CIS event **502** may be $(k-1)$ to n times. Within the timing diagram **500**, since the second CIS event **503** includes first sub-event **503-1** to $(n-k+1)$ th sub-event **503- $(n-k+1)$** each overlapping k th sub-event **502- k** to n th sub-event **502- n** and $(n-k+2)$ th sub-event **503- $(n-k+2)$** to n th sub-event **503- n** that do not overlap the first CIS event **502**, the number of times of transmitting a packet through the second CIS event **503** may be $k-1$ times to n times. For example, the processor **120** may transmit a packet **505** for the first external electronic device **201** through at least a part of a time interval (e.g., first sub-event **502-1** to $(k-1)$ th sub-event **502- $(k-1)$**) of the first CIS event **502** that does not overlap the second CIS event **503**; and transmit one of a packet **505** for the first external electronic device **201** and a packet **506** for the second external electronic device **202** through at least a portion of the time interval (e.g., k -th sub-event **502- k** to n -th sub-event **502- n**) of the first CIS event **502** overlapping the second CIS event **503** (or a time interval (e.g., first sub-event **503-1** to $(n-k+1)$ th sub-event **503- $(n-k+1)$**) of the second CIS event **503** overlapping the first CIS event **502**)); and transmit a packet **506** for the second external electronic device **202** through at least a portion of the time interval (e.g., $(n-k+2)$ th sub-event **503- $(n-k+2)$** to n -th sub-event **503- n**) of the second CIS event **503** that does not overlap the first CIS event **502**. For example, based on transmitting the last target packet transmitted to the first external electronic device **201** through the first CIS event **502** to the first external electronic device **201** through the k th sub-event **502- k** and receiving the acknowledgement signal for the last target packet from the first external electronic device **201**

through the k th sub-event **502- k** , the processor **120** may transmit the packet **506** to the second external electronic device **202** through each of the second sub-event **503-2** to $(n-k+1)$ th sub-event **503- $(n-k+1)$** and cease transmitting the packet **505** to the first external electronic device **201** through the sub-event **502- $(k+1)$** to the sub-event **502- n** . In this situation, the last target packet may refer to a packet that is last transmitted among scheduled target packets, which is transmitted to the first external electronic device **201** in the first CIS event **502** based on a burst number (BN) and a flush timeout (FT) of the first CIS event **502**.

(73) The processor **120** may adaptively change the number of times a packet is transmitted to the first external electronic device **201** through the CIG event **501** and the number of times a packet is transmitted to the second external electronic device **202** through the CIG event **501**, by obtaining the CIG event **501** including the first CIS event **502** and the second CIS event **503** partially overlapping a part of the first CIS event **502**. For example, when the quality of the first link between the first external electronic device **201** and the electronic device **101** is much better than the quality of the second link between the second external electronic device **202** and the electronic device **101**, the processor **120** may enhance the quality of multi-stream audio by allocating a time interval of the second CIS event **503** partially overlapped with a part of the first CIS event **502** with a time interval for transmitting packets to the second external electronic device **202**.

(74) FIG. 5A illustrates an example that the length of each of the first sub-event **502-1** to n -th sub-event **502- n** in the first CIS event **502** is the same as the length of the first sub-event **503-1** to n -th sub-events **503- n** in the second CIS event **503**, but this is only for convenience of description. For example, although not shown in FIG. 5A, even when the length of each of the first sub-event **502-1** to n -th sub-events **502- n** in the first CIS event **502** is different from the length of the first sub-events **503-1** to n -th sub-events **503- n** in the second CIS event **503**, the processor **120** may obtain the CIG event **501** including the first CIS event **502** and the second CIS event **503** at least partially overlapping at least a part of the first CIS event **502**, under the condition that each of the anchor points of at least a part of the first sub-event **502-1** to n -th sub-event **502- n** in the first CIS event **502** (e.g., k -th sub-event **502- k** to n -th sub-event **502- n**) corresponds to each of the anchor points of at least a part of the first sub-event **503-1** to n -th sub-event **503- n** in the second CIS event **503** (e.g., the first sub-event **503-1** to $(n-k+1)$ th sub-event **503- $(n-k+1)$**)).

(75) Although not shown in FIG. 5A, under the condition that an interval between the anchor points of the first sub-event **502-1** to n -th sub-event **502- n** in the first CIS event **502** is a multiple of an interval between the anchor points of the first sub-event **503-1** to n -th sub-event **503- n** in the second CIS event **503**, and an offset of the anchor point of each of the first sub-event **502-1** to n -th sub-event **502- n** in the first CIS event **502** corresponds to an offset of the anchor point of each of the first sub-event **503-1** to n -th sub-event **503- n** in the second CIS event **503**, the processor **120** may obtain the CIG event **501** including the first CIS event **502** and the second CIS event **503** at least partially overlapping at least a part of the first CIS event **502**.

(76) Although not shown in FIG. 5A, under the condition that an interval between the anchor points of the first sub-event **503-1** to n -th sub-event **503- n** in the second CIS event **502** is a multiple of an interval between the anchor points of the first sub-event **502-1** to n -th sub-event **502- n** in the first CIS event **502**, and an offset of the anchor point of each of the first sub-event **502-1** to n -th sub-event **502- n** in the first CIS event **502** corresponds to an offset of the anchor point of each of the first sub-event **503-1** to n -th sub-event **503- n** in the second CIS event **503**, the processor **120** may obtain the CIG event **501** including the first CIS event **502** and the second CIS event **503** at least partially overlapping at least a part of the first CIS event **502**.

(77) In another example, referring to FIG. 5B, as shown in the timing diagram **550**, the processor **120** may obtain a CIG event **551** including a first CIS event **552** and a second CIS event **553** completely overlapping the first CIS event **552**. For example, the processor **120** may obtain the CIG event **551** by scheduling the first CIS event **552** and the second CIS event **553** such that each of the first sub-event **552-1** to the fourth sub-event **552-4** in the first CIS event **552** overlaps each

of the first sub-event **553-1** to the fourth sub-event **553-4** in the second CIS event **553**. Since the first CIS event **552** and the second CIS event **553** completely overlap each other within the CIG event **551**, the processor **120** may adaptively change the number of times a packet may be transmitted through the first CIS event **552** and the number of times a packet may be transmitted through the second CIS event **553**. For example, based on transmitting the last target packet transmitted to the first external electronic device **201** through the first CIS event **552** to the first external electronic device **201** through the first sub-event **552-1** and receiving an acknowledgement signal for the last target packet from the first external electronic device **201** through the first sub-event **552-1**, the processor **120** may stop transmitting packets to the first external electronic device **201** through the second sub-event **552-2** to the fourth sub-event **552-4**, which are remaining sub-events of the first CIS event **552**, and transmit the packets to the second external electronic device **202** through at least a part of the second sub-event **553-2** to the fourth sub-event **553-4**. The processor **120** may enhance the quality of multi-stream audio by adaptively changing a time interval for transmitting a packet for the first external electronic device **201** and a time interval for transmitting a packet for the second external electronic device **202** within the CIG event **551**, according to the difference between the quality of the first link and the quality of the second link.

(78) FIG. 5B illustrates an example that the length of each of the first sub-event **552-1** to the fourth sub-event **552-4** in the first CIS event **552** is the same as the length of each of the first sub-event **553-1** to the fourth sub-event **553-4** in the second CIS event **553**, but this is only for convenience of description. For example, although not shown in FIG. 5B, even when the length of each of the first sub-event **552-1** to the fourth sub-event **552-4** in the first CIS event **552** and the length of each of the first sub-event **553-1** to the fourth sub-event **553-4** in the second CIS event **553** are different from each other, the processor **120** may obtain the CIG event **551** including the first CIS event **552** and the second CIS event **553** overlapped with the first CIS event **552**, under the condition that the anchor point of each of the first sub-event **552-1** to the fourth sub-event **552-4** in the first CIS event corresponds to the anchor point of each of the first sub-event **553-1** to the fourth sub-event **553-4** in the second CIS event **553**. For example, although not shown in FIG. 5B, under the condition that the interval between the anchor points of the first sub-event **552-1** to the fourth sub-event **552-4** in the first CIS event **552** is a multiple of the interval between the anchor points of the first sub-event **553-1** to the fourth sub-event **553-4** in the second CIS event **553**, and the offset of each of the anchor points of the first sub-event **552-1** to the fourth sub-event **552-4** in the first CIS event **552** corresponds to the offset of each of the anchor points of the first sub-event **553-1** to the fourth sub-event **553-4** in the second CIS event **553**, the processor **120** may obtain the CIG event **551** including the first CIS event **552** and the second CIS event **553** overlapping the first CIS event **552**. Such a CIG event **551** is described below with respect to FIG. 5C.

(79) For example, although not shown in FIG. 5B, under the condition that the interval between the anchor points of the first sub-event **553-1** to the fourth sub-event **553-4** in the second CIS event **553** is a multiple of the interval between the anchor points of the first sub-event **552-1** to the fourth sub-event **552-4** in the first CIS event **552**, and the offset of each of the anchor points of the first sub-event **552-1** to the fourth sub-event **552-4** in the first CIS event **552** corresponds to the offset of each of the anchor points of the first sub-event **553-1** to the fourth sub-event **553-4** in the second CIS event **553**, the processor **120** may obtain the CIG event **551** including the first CIS event **552** and the second CIS event **553** overlapping the first CIS event **552**.

(80) Referring to FIG. 5C, as shown in timing diagram **570**, the processor **120** may obtain a CIG event **571** including a first CIS event **572** and a second CIS event **573** fully overlapped with the first CIS event **572**. For example, the processor **120** may obtain the CIG event **571** by scheduling the first CIS event **572** and the second CIS event **573**, so that the first sub-event **572-1** of the first CIS event **572** overlaps the first sub-event **573-1** and the second sub-event **573-2** of the second CIS event **573**, the second sub-event **572-2** of the first CIS event **572** overlaps the third sub-event **573-3** and the fourth sub-event **573-4** of the second CIS event **573**, the third sub-event **572-3** of the first

CIS event **572** overlaps the fifth sub-event **573-5** and the sixth sub-event **573-6** of the second CIS event, and the fourth sub-event **572-4** of the first CIS event **572** overlaps the seventh sub-event **573-7** and the eighth sub-event **573-8** of the second CIS event **573**. Unlike the CIG event **501** and the CIG event **551** respectively shown in FIGS. 5A and 5B, the number of sub-events of the first CIS event **572** of the CIG event **571** may be different from the number of sub-events of the second CIS event **573** of the CIG event **571**. For example, the interval between the anchor points of the sub-events of the first CIS event **572** of the CIG event **571** may be longer than the interval between the anchor points of the sub-events of the second CIS event **573** of the CIG event **571**, as opposed to the CIG event **501** and the CIG event **551** respectively shown in FIGS. 5A and 5B. Unlike the CIG event **501** and the CIG event **551** respectively shown in FIGS. 5A and 5B, the number of times a packet may be transmitted through the first CIS event **572** may be different from the number of times a packet may be transmitted through the second CIS event **573**. For example, the interval between the anchor points of the sub-events of the first CIS event **572** of the CIG event **571** may be a multiple of the interval between the anchor points of the sub-events of the second CIS event **573** of the CIG event **571**.

(81) The offset of the anchor point of each of the sub-events of the first CIS event **572** of the CIG event **571** may be the same as the offset of the anchor point of each of the sub-events of the second CIS event **573** of the CIG event **571**. For example, the position of the anchor point of the first sub-event **572-1** of the first CIS event **572** may be the same as the position of the anchor point of the first sub-event **573-1** of the second CIS event **573**, the position of the anchor point of the second sub-event **572-2** of the first CIS event **572** may be the same as the position of the anchor point of the third sub-event **573-3** of the second CIS event **573**, the position of the anchor point of the third sub-event **572-3** of the first CIS event **572** may be the same as the position of the anchor point of the fifth sub-event **573-5** of the second CIS event **573**, and the position of the anchor point of the fourth sub-event **572-4** of the first CIS event **572** may be the same as the position of the anchor point of the seventh sub-event **573-7** of the second CIS event **573**. For example, the anchor point of the second sub-event **573-2** of the second CIS event **573** may be within the first sub-event **572-1** of the first CIS event **572**, the anchor point of the fourth sub-event **573-4** of the second CIS event **573** may be within the second sub-event **572-2** of the first CIS event **572**, the anchor point of the sixth sub-event **573-6** of the second CIS event **573** may be within the third sub-event **572-3** of the first CIS event **572**, and the anchor point of the eighth sub-event **573-8** of the second CIS event **573** may be within the fourth sub-event **572-4** of the first CIS event **572**. For example, the sub-events of the first CIS event **572** may be synchronized with the sub-events of the second CIS event **573**.

(82) Since the interval between the anchor points of the sub-events of the first CIS event **572** within a time interval for the CIG event **571** is longer than the interval between the anchor points of the sub-events of the second CIS event **573** within the time interval, the time interval may be a time interval that can adaptively select either one of transmission to the first external electronic device **201** and transmission to the second external electronic device **202**, for each sub-event of the first CIS event **572**.

(83) Referring back to FIG. 3, the processor **120** may adaptively change an initial CIS event (e.g., a CIS event that occurred first between the first CIS event and the second CIS event) in the CIG event including the first CIS event and the second CIS event, in order to uniformly distribute time resources provided for the first CIS event and time resources provided for the second CIS event at least partially overlapping at least part of the first CIS event. For example, the processor **120** may schedule the first CIS event and the second CIS event in the first CIG event so that the anchor point of the first CIS event in the first CIG event occurs simultaneously with an anchor point of the first CIG event and occurs before the anchor point of the second CIS event in the first CIG event, and may schedule the first CIS event and the second CIS event in the second CIG event so that the anchor point of the first CIS event in the second CIG event immediately after the first CIG event occurs simultaneously with the anchor point of the second CIG event and occurs before the anchor

point of the second CIS event in the second CIG event. The processor **120** may uniformly distribute the time resources provided for the first CIS event and the time resources provided for the second CIS event at least partially overlapping at least part of the first CIS event, by allocating the initial CIS event in the $(2k-1)$ th CIG event (here, k is a natural number greater than or equal to 1) to the first CIS event, and allocating the initial CIS event in the $2k$ -th CIG event as the second CIS event. Referring to FIG. 6, as shown in the timing diagram **600**, the processor **120** may schedule a CIS event starting at an anchor point **605** of k -th CIG event **601- k** as a first CIS event **602** between the first CIS event **602** and a second CIS event **603** partially overlapping part of the first CIS event **602**, and schedule a CIS event starting at an anchor point **607** of $(k+1)$ th CIG event **601- $(k+1)$** immediately after the k -th CIG event **601- k** as a second CIS event **603** between the first CIS event **602** and the second CIS event **603** partially overlapping part of the first CIS event **602**.

(84) Referring back to FIG. 3, an attribute of data in the packet that can be transmitted through the first CIS event, which is the first CIS event in the CIG event, may correspond to an attribute of data included in the packet that may be transmitted through the second CIS event at least partially overlapping at least part of the first CIS event. The processor **120** may obtain the first CIS event for the first packets to be transmitted to the first external electronic device **201** and obtain the second CIS event for the second packets, to be transmitted to the second external electronic device **202** associated with the first external electronic device **201**, the second packets corresponding to the first packets, respectively. For example, since the first packets correspond to the second packets, the processor **120** may transmit the first packets and the second packets in various schemes through the first CIS event and the second CIS event at least partially overlapping at least part of the first CIS event.

(85) The processor **120** may transmit the second packets through at least part of the second CIS event, under the condition that the transmission of the first packets is completed through at least part of the first CIS event, which is the first CIS event in the CIG event. Such a scheduling of transmitting the second packets after completing the transmission of the first packets makes it possible to change the number of sub-events in the first CIS event used for transmission of the first packets and change the number of sub-events in the second CIS event used for transmission of the second packets, unlike transmitting the first packets and the second packets using the sequential arrangement, and thus, transmitting the second packets after completing transmission of the first packets in the hybrid arrangement makes it possible to provide more enhanced service than transmitting the first packets and the second packets using the sequential arrangement.

(86) Referring to FIG. 7A, the processor **120** may transmit the second packets to the second external electronic device **202** through at least part of the second CIS event **712** at least partially overlapping at least part of the first CIS event **711**, after completing transmission of the first packet **713-1**, the first packet **713-2** and the first packet **713-3** to the first external electronic device **201** through at least part of the first CIS event **711** in the CIG event **710**. In that case, the number of sub-events in the second CIS event **712** that are available for transmitting the second packets may change depending on when the transmission of the first packets is complete. For example, as shown in the timing diagram **700**, when the first packet **713-3** is re-transmitted as opposed to the first packet **713-1** and the first packet **713-2**, the processor **120** may transmit the second packets to the second external electronic device **202** through a portion **714** of the second CIS event **712** including four sub-events. As shown in the timing diagram **701**, when the transmission of the first packets including the first packet **713-1**, the first packet **713-2** and the first packet **713-3** is completed without retransmission, the processor **120** may transmit the second packets to the second external electronic device **202** through a portion **715** of the second CIS event **712** including five sub-events. The hybrid arrangement can provide more adaptive transmission opportunities than the sequential arrangement because the hybrid arrangement makes it possible to change transmission opportunities, as opposed to the sequential arrangement.

(87) The processor **120** may transmit one of the first packets or the second packets in an alternating

manner, and then continue to transmit the other, under the condition that either one of the transmission of the first packets and the transmission of the second packets is completed. For example, since such a transmission scheduling enables continuous transmission as well as alternating transmission, transmitting the first packets and the second packets in the hybrid arrangement makes it possible to provide more enhance service than transmitting the first packets and the second packets using the interleaved arrangement.

(88) Referring to FIG. 7A, the processor **120** may perform, alternately in units of sub-events, transmission of the first packets (e.g., the first packet **723-1**, the first packet **723-2**, and the first packet **723-3**) to the first external electronic device **201**, and transmission of the second packets (e.g., the second packet **724-1**, the second packet **724-2**, and the second packet **724-3**) to the second external electronic device **202**, using the first CIS event **721** in the CIG event **720** and the second CIS event **722** in the CIG event **720** overlapping the first CIS event **721**. For example, as shown in the timing diagram **702**, the processor **120** may transmit the second packet **724-1** to the second external electronic device **202** through the second CIS event **722** after transmitting the first packet **723-1** to the first external electronic device **201** through the first CIS event **721**, transmit the first packet **723-2** to the first external electronic device **201** through the first CIS event **721** after transmitting the second packet **724-1**, re-transmit the second packet **724-1** to the second external electronic device **202** through the second CIS event **722** after transmitting the first packet **723-2**, and transmit the first packet **723-3** to the first external electronic device **201** after re-transmitting the second packet **724-1**. Under the condition that the transmission of the first packet **723-3** succeeds and the retransmission of the second packet **724-1** succeeds, the processor **120** may transmit the second packet **724-2** and the second packet **724-3** to the second external electronic device **202** through a portion **725** of the second CIS event **722** including three sub-events. As opposed to the interleaved arrangement in which it has to transmit the second packet **724-2** and the second packet **724-3** through two sub-events due to the sub-event in the first CIS event **721** (e.g., a sub-event **726**) even though the transmission of the first packets has been completed, the hybrid arrangement makes it possible to transmit the second packet **724-2** and the second packet **724-3** through the portion **725** of the second CIS event **722** including the three sub-events. For example, the hybrid deployment can provide more adaptive transmission opportunities than the interleaved arrangement.

(89) Referring back to FIG. 3, an attribute of data in the packet that may be transmitted through the first CIS event, which is an initial CIS event in the CIG event, may be distinguished from an attribute of data included in the packet that may be transmitted through the second CIS event at least partially overlapping at least part of the first CIS event. For example, when both the first CIS event and the second CIS event are obtained, set, or scheduled for packets to be transmitted to an external electronic device, the processor **120** may transmit a packet including data obtained in every cycle to the external electronic device through the first CIS event that starts before the second CIS event and transmit a packet including data obtained based on identifying a designated event to the external electronic device through the second CIS event. A size of a buffer for data transmitted through the first CIS event may be larger than a size of a buffer for data transmitted through the second CIS event, but it is not limited thereto. The processor **120** may transmit a packet for audio continuously provided through the first CIS event that starts before the timing of starting the second CIS event and transmit a packet for audio provided on condition of identifying a designated event through the second CIS event.

(90) Referring to FIG. 7B, the processor **120** may display a user interface **730** of a game executed in the electronic device **101** through a display of the electronic device **101** (e.g., the display module **160** shown in FIG. 1). While displaying the user interface **730**, for outputting background music (BGM) of the game and sound effects provided based on a user input received through the user interface **730**, using the external electronic device **735**, the processor **120**, as shown in a timing diagram **740**, may obtain a first CIG event **750** including a first CIS event **751** and a second CIS

event **752** partially overlapping part of the first CIS event **751** and obtain a second CIG event **760** including a first CIS event **761** and a second CIS event **762** partially overlapping part of the first CIS event **761**. For example, the processor **120** may transmit a packet **770** for the BGM continuously outputted while executing the game, to the external electronic device **735** through each of the first CIS event **751** and the first CIS event **761**, which is an initial CIS event of each of the first CIG event **750** and the second CIG event **760**, and transmit a packet **771** for the sound effect provided on condition of receiving the user input, to the external electronic device **735** through each of the second CIS event **752** and the second CIS event **762**. For example, when the user input generating the sound effect is not received for the first CIG event **750**, the processor **120**, as shown in the timing diagram **740**, may transmit a packet **770** to the external electronic device **735** through the first CIS event **751** in the first CIG event **750**, and transmit no packet through the second CIS event **752** in the first CIG event **750** or transmit a dummy packet **772** through the second CIS event **752** in the first CIG event **750**. In another example, when a user input **780** generating the sound effect is received for the second CIG event **760**, as shown in the timing diagram **740**, the processor **120** may transmit a packet **770** to the external electronic device **735** through part of the first CIS event **761** in the second CIG event **760**, and transmit a packet **771** to the external electronic device **735** through part of the second CIS event **762** in the second CIG event **760** overlapping part of the first CIS event **761**. The priority of the packet **771** associated with the user input **780** may be higher than the priority of the packet **770**. For example, even when the transmission of the packet **770** is not completed through the part of the first CIS event **761**, the processor **120** may transmit the packet **771** through the part of the second CIS event **762** overlapping the part of the first CIS event **761**, in response to receiving the user input **780**. In other words, the processor **120** may allocate a plurality of CIS events for respectively transmitting packets having different priorities to a single external electronic device such as the external electronic device **735**, and schedule the plurality of CIS events to be fully or partially overlapped with each other.

(91) FIG. **8** is a flowchart illustrating a method of transmitting data via a CIG event including a first CIS event and a second CIS event in a hybrid arrangement according to an embodiment of the disclosure. This method may be executed by the electronic device **101** illustrated in FIG. **1**, the electronic device **101** illustrated in FIG. **2**, the electronic device **101** illustrated in FIG. **3**, or the processor **120** of the electronic device **101**.

(92) Referring to FIG. **8**, in operation **802**, the processor **120** may obtain a CIG event including a first CIS event and a second CIS event at least partially overlapping at least part of the first CIS event. The CIG event may include the first CIS event and the second CIS event in the hybrid arrangement. The first CIS event may be an event used to transmit data to a first external electronic device (e.g., the first external electronic device **201** shown in FIG. **2**), and the second CIS event may be an event used to transmit data to a second external electronic device (e.g., the second external electronic device **202** shown in FIG. **2**). The first CIS event may include first sub-events, and the second CIS event may include second sub-events at least partially overlapping at least part of the first sub-events. By configuring the anchor point of the second CIS event within the first CIS event initiated from the anchor point of the first CIS event, the processor **120** may obtain the CIG event including the first CIS event including the first sub-events and the second CIS event including the second sub-event at least partially overlapping at least part of the first sub-events, although it is not limited thereto.

(93) According to an embodiment of the disclosure, the processor **120** may perform operation **802** based on identifying that the first external electronic device and the second external electronic device support including the first CIS event and the second CIS event in the CIG event in the hybrid arrangement. For example, based on receiving capability information of the first external electronic device from the first external electronic device and receiving capability information of the second external electronic device from the second external electronic device, the processor **120**

may determine including the first CIS event and the second CIS event in the CIG event in the hybrid arrangement, and execute operation **802** based on the determination. However, it is not limited thereto.

(94) In operation **804**, the processor **120** may transmit first data to the first external electronic device through the first sub-event in the first CIS event. The first sub-event may be one of the first sub-events in the first CIS event. The first sub-event may overlap one of the second sub-events in the second CIS event or may not overlap all the second sub-events. When the first sub-event does not overlap all of the second sub-event, the last sub-event of the second sub-event may not overlap all of the first sub-events.

(95) In operation **806**, the processor **120** may receive an acknowledgement signal from the first external electronic device through the first sub-event in the first CIS event. For example, the first external electronic device may set NESN (nextExpectedSeqNum) in the packet to SN (transmitSeqNum), based on receiving the packet including the first data through the first sub-event, and transmit a response packet including the set SN to the electronic device **101** through the first sub-event as the acknowledgement signal. The processor **120** may identify that the first data is normally received by the first external electronic device through the first sub-event based on receiving the acknowledgement signal.

(96) In operation **808**, the processor **120** may transmit second data to the second external electronic device through a third sub-event in the second CIS event, based on receiving the acknowledgement signal from the first external electronic device through the first sub-event. For example, the third sub-event in the second CIS event may be a sub-event of the second sub-events in the second CIS event overlapping the second sub-event immediately after the first sub-event among the first sub-events. The third sub-event in the second CIS event may be a sub-event initiating the second CIS event, although it is not limited thereto. The processor **120** may transmit, to the second external electronic device, at least one packet including the second data through at least one sub-event including the third sub-event in the second CIS event, although it is not limited thereto.

(97) Although not shown in FIG. **8**, the processor may, based on receiving the acknowledgement signal from the first external electronic device through the first sub-event, cease transmitting data to the first external electronic device through all the remaining sub-events in the first CIS event in the CIG event.

(98) As described above, the electronic device **101** may adaptively distribute the time resources for transmitting data to the first external electronic device and the time resources for transmitting data to the second external electronic device, according to a change in at least one of a state of a first link between the first external electronic device and the electronic device **101** or a state of a second link between the second external electronic device and the electronic device **101**, by configuring the CIG event including the first CIS event and the second CIS event in the hybrid arrangement. For example, the electronic device **101** may configure the CIG event including the first CIS event and the second CIS event in the hybrid arrangement, thereby increasing the amount of time resources that may be allocated to each of the first CIS event and the second CIS event.

(99) FIG. **9A** is a flowchart illustrating a method of obtaining the CIG event including the first CIS event and the second CIS event in the hybrid arrangement, based on synchronization of an anchor point of each of the first sub-events in the first CIS event and an anchor point of each of the second sub-events in the second CIS event, according to an embodiment of the disclosure. This method may be executed by the electronic device **101** shown in FIG. **1**, the electronic device **101** shown in FIG. **2**, the electronic device **101** shown in FIG. **3**, or the processor **120** of the electronic device **101**.

(100) Operations **902** to **904** of FIG. **9A** may be associated with operation **802** of FIG. **8**.

(101) Referring to FIG. **9A**, in operation **902**, the processor **120** may identify whether or not the anchor point of each of the first sub-events in the first CIS event defined through the description of FIG. **8** is synchronized with the anchor point of each of the second sub-events in the second CIS

event defined through the description of FIG. 8. When the anchor point of each of the first sub-events is synchronized with the anchor point of each of the second sub-events, it may mean that an offset of the anchor point of each of the first sub-events coincides with an offset of each of the anchor points in the second sub-events, and that an interval between the anchor points of the first sub-events is a multiple of an interval between anchor points of the second sub-events. When the anchor point of each of the first sub-events is synchronized with the anchor point of each of the second sub-events, it may mean that the offset of the anchor point of each of the first sub-events coincides with the offset of the anchor point of each of the second sub-events, and that the interval between the anchor points of the second sub-events is a multiple of the interval between the anchor points of the first sub-events. When the anchor point of each of the first sub-events is synchronized with the anchor point of each of the second sub-events, it may mean that regardless (or independently) of the length of each of the first sub-events and the length of each of the second sub-events, it is possible to perform scheduling to overlap at least part of the first sub-events and at least part of the second sub-events, so the processor **120** may identify whether the anchor point of each of the first sub-events is synchronized with the anchor point of each of the second sub-events. (102) The processor **120** may execute operation **904** on condition that the anchor point of each of the first sub-events is synchronized with the anchor point of each of the second sub-events, and execute operation **906** on condition that the anchor point of each of the first sub-events is not synchronized with the anchor point of each of the second sub-events.

(103) In operation **904**, the processor **120** may obtain the CIG event including the first CIS event and the second CIS event partially overlapping at least part of the first CIS event, based on identifying that the anchor point of each of the first sub-events is synchronized with the anchor point of each of the second sub-events. For example, the processor **120** may obtain the CIG event including the first CIS event and the second CIS event in the hybrid arrangement.

(104) In operation **906**, the processor **120** may obtain the CIG event including the first CIS event and the second CIS event either in the sequential arrangement or in the interleaved arrangement, based on identifying that the anchor point of each of the first sub-events is not synchronized with the anchor point of each of the second sub-events.

(105) FIG. 9B is a flowchart illustrating a method of obtaining the CIG event including the first CIS event and the second CIS event in the hybrid arrangement, based on the length of each of the first sub-events in the first CIS event and the length of each of the second sub-events in the second CIS event according to an embodiment of the disclosure. This method may be executed by the electronic device **101** illustrated in FIG. 1, the electronic device **101** illustrated in FIG. 2, the electronic device **101** illustrated in FIG. 3, or the processor **120** of the electronic device **101**.

(106) Operations **912** to **914** of FIG. 9B may be associated with operation **802** of FIG. 8.

(107) Referring to FIG. 9B, in operation **912**, the processor **120** may identify whether a length of each of the first sub-events in the first CIS event defined through the description of FIG. 8 is identical to a length of each of the second sub-events in the second CIS event defined through the description of FIG. 8. When the length of each of the first sub-events is identical to the length of each of the second sub-events, it may mean that it is possible to perform scheduling to overlap at least part of the first sub-events and at least part of the second sub-events, so the processor **120** may identify whether the length of each of the first sub-events is identical to the length of each of the second sub-events. The processor **120** may identify whether the length of each of the first sub-events is identical to the length of each of the second sub-events, by identifying a parameter (e.g., SE_length) of the first CIS event indicating the length of each of the first sub-events in the first CIS event and a parameter of the second CIS event indicating the length of each of the second sub-events in the second CIS event.

(108) The processor **120** may execute operation **914** on condition that the length of each of the first sub-events is identical to the length of each of the second sub-events, and processor **120** may execute operation **916** on condition that the length of each of the first sub-events is different from

the length of each of the second sub-events.

(109) In operation **912**, the processor **120** may further identify whether a start timing of each of the first sub-events is synchronized with a start timing of each of the second sub-events. For example, when the length of each of the first sub-events is identical to the length of each of the second sub-events, and the start timing of each of the first sub-events is synchronized with the start timing of each of the second sub-events, it may mean that it possible to perform scheduling to overlap at least part of the first sub-events and at least part of the second sub-events, so the processor **120** may execute a comparison between the length of each of the first sub-events and the length of each of the second sub-events and a comparison between the start timing of each of the first sub-events and the start timing of each of the second sub-events. The processor **120** may execute operation **914** on condition that the length of each of the first sub-events is identical to the length of each of the second sub-events and the start timing of each of the first sub-events is synchronized with the start timing of each of the second sub-events, otherwise execute operation **916**.

(110) In operation **914**, the processor **120** may obtain the CIG event including the first CIS event and the second CIS event at least partially overlapping at least part of the first CIS event, based on identifying that the length of each of the first sub-events is identical to the length of each of the second sub-events. For example, the processor **120** may obtain the CIG event including the first CIS event and the second CIS event in the hybrid arrangement.

(111) In operation **916**, the processor **120** may obtain the CIG event including the first CIS event and the second CIS event either in the sequential arrangement or the interleaved arrangement, based on identifying that the length of each of the first sub-events is different from the length of each of the second sub-events.

(112) FIG. **10** is a flowchart illustrating a method of transmitting data within a time interval in which at least part of the first CIS event overlaps at least part of the second CIS event, according to an embodiment of the disclosure. This method may be executed by the electronic device **101** illustrated in FIG. **1**, the electronic device **101** illustrated in FIG. **2**, the electronic device **101** illustrated in FIG. **3**, or the processor **120** of the electronic device **101**.

(113) Operations **1002** and **1006** of FIG. **10** may be associated with the operation **808** of FIG. **8**.

(114) Referring to FIG. **10**, in operation **1002**, after executing operation **806**, the processor **120** may identify whether the first data transmitted through operation **804** is the last target data transmitted to the first external electronic device through the first CIS event. For example, when it is received the acknowledgement signal for the first data, which is the last target data, in operation **806**, it may mean that transmission of all data scheduled for the first CIS event is completed. When the transmission of all scheduled data for the first CIS event is completed, there is no need to transmit data through the second sub-event in the first CIS event immediately after the first sub-event, so the processor **120** may identify whether the first data is the last target data. On condition that the first data is the last target data, the processor **120** may execute operation **1004**, while on condition that the first data is not the last target data, the processor **120** may execute operation **1006**.

(115) In operation **1004**, based on identifying that the first data is the last target data, the processor **120** may transmit second data through the third sub-event in the second CIS event at least partially overlapping at least part of the first CIS event. For example, operation **1004** may correspond to operation **808** of FIG. **8**.

(116) In operation **1006**, based on identifying that the first data is not the last target data, the processor **120** may transmit another data subsequent to the first data through the second sub-event in the first CIS event.

(117) As described above, when transmission of all data scheduled for the first CIS event has been completed before the end of the first CIS event, the electronic device **101** may transmit data to the second external electronic device through sub-events in the second CIS event overlapping the remaining sub-events instead of the remaining sub-events in the first CIS event. In other words, the electronic device **101** may use the CIG event including the first CIS event and the second CIS

event in the hybrid arrangement to increase the number of transmissions to the second external electronic device through the second CIS event.

(118) FIG. **11** is a flowchart illustrating a method of obtaining the CIG event including the first CIS event and the second CIS event in the hybrid arrangement, based on attributes of data, according to an embodiment of the disclosure. This method may be executed by the electronic device **101** illustrated in FIG. **1**, the electronic device **101** illustrated in FIG. **2**, the electronic device **101** illustrated in FIG. **3**, or the processor **120** of the electronic device **101**.

(119) Operations **1102** to **1104** of FIG. **11** may be associated with operation **802** of FIG. **8**.

(120) Referring to FIG. **11**, in operation **1102**, the processor **120** may identify whether the first data or the second data is associated with a multimedia content. For example, the processor **120** may identify whether the first data or the second data is associated with the multimedia content in order to identify whether a size of the first data to be transmitted through the first CIS event or a size of the second data to be transmitted through the second CIS event requires configuring the CIG event including the first CIS event and the second CIS event in the hybrid arrangement. In another example, the processor **120** may identify whether the first data or the second data is associated with the multimedia content in order to identify whether the load of the first external electronic device for processing the first data to be transmitted through the first CIS event or the load of the second external electronic device for processing the second data to be transmitted through the second CIS event requires configuring the CIG event including the first CIS event and the second CIS event in the hybrid arrangement. In another example, the processor **120** may identify whether the first data or the second data is associated with the multimedia content in order to identify whether the quality of service (QoS) of the first data to be transmitted through the first CIS event or the quality of service (QoS) of the second data to be transmitted through the second CIS event requires configuring the CIG event including the first CIS event and the second CIS event in the hybrid arrangement. In another example, the processor **120** may identify whether the first data or the second data is associated with the multimedia content in order to identify whether multi-stream audio is provided through the first external electronic device and the second external electronic device. However, it is not limited thereto.

(121) The processor **120** may execute operation **1104** on condition that the first data or the second data is associated with the multimedia content, and may execute operation **1106** on condition that the first data and the second data are not associated with the multimedia content.

(122) In operation **1104**, the processor **120** may obtain the CIG event including the first CIS event and the second CIS event at least partially overlapping at least part of the first CIS event, based on identifying that the first data or the second data is associated with the multimedia content. For example, the processor **120** may obtain the CIG event including the first CIS event and the second CIS event in the hybrid arrangement.

(123) In operation **1106**, the processor **120** may obtain the CIG event including the first CIS event and the second CIS event either in the sequential arrangement or in the interleaved arrangement, based on identifying that the first data and the second data are not associated with the multimedia content. For example, when the sizes of the first data and the second data are relatively small, the processor **120** may obtain the CIG event in the sequential arrangement or in the interleaved arrangement.

(124) FIG. **12** is a flowchart illustrating a method of obtaining the CIG event including the first CIS event and the second CIS event in the hybrid arrangement, based on the quality of a link between the first external electronic device and the electronic device, according to an embodiment of the disclosure. This method may be executed by the electronic device **101** illustrated in FIG. **1**, the electronic device **101** illustrated in FIG. **2**, the electronic device **101** illustrated in FIG. **3**, or the processor **120** of the electronic device **101**.

(125) Operations **1202** to **1204** of FIG. **12** may be associated with operation **802** of FIG. **8**.

(126) Referring to FIG. **12**, in operation **1202**, the processor **120** may identify whether the quality

of the link between the first external electronic device and the electronic device **101** (or the quality of the link between the second external electronic device and the electronic device **101**) is equal to or greater than a reference quality. For example, when the quality of the link between the first external electronic device and the electronic device **101** is below the reference quality, it may mean that the number of times of transmitting data through the second CIS event overlapping at least part of the first CIS event is limited, so the processor **120** may identify whether the quality of the link between the first external electronic device and the electronic device **101** is equal to or greater than the reference quality. The processor **120** may execute operation **1204** on condition that the quality of the link between the first external electronic device and the electronic device **101** is equal to or higher than the reference quality, and may execute operation **1206** on condition that the quality of the link between the first external electronic device **101** and the electronic device **101** is below the reference quality.

(127) In operation **1204**, the processor **120** may obtain the CIG event including the first CIS event and the second CIS event at least partially overlapping at least part of the first CIS event, based on identifying that the quality of the link between the first external electronic device and the electronic device **101** is equal to or greater than the reference quality. For example, the processor **120** may obtain the CIG event including the first CIS event and the second CIS event in the hybrid arrangement.

(128) In operation **1206**, the processor **120** may obtain the CIG event including the first CIS event and the second CIS event in the sequential arrangement or in the interleaved arrangement, based on identifying that the quality of the link between the first external electronic device and electronic device **101** is below the reference quality.

(129) As described above, the electronic device **101** may obtain the CIG event including the first CIS event and the second CIS event in the hybrid arrangement, based on identifying that the quality of the link between the first external electronic device and the electronic device **101** is equal to or greater than the reference quality, in order to uniformly distribute the time resources used for transmission from the electronic device **101** to the first external electronic device and the time resources used for transmission from the electronic device **101** to the second external electronic device.

(130) FIG. **13** is a flowchart illustrating a method of allocating an initial CIS event in the CIG event according to an embodiment of the disclosure. This method may be executed by the electronic device **101** illustrated in FIG. **1**, the electronic device **101** illustrated in FIG. **2**, the electronic device **101** illustrated in FIG. **3**, or the processor **120** of the electronic device **101**.

(131) Referring to FIG. **13**, in operation **1302**, the processor **120** may obtain the CIG event including the first CIS event and the second CIS event partially overlapping part of the first CIS event. For example, the first CIS event may be a CIS event that occurs before the second CIS event in the CIG event.

(132) In operation **1304**, the processor **120** may obtain a next CIG event immediately after the CIG event, in which the second CIS event partially overlapping part of the first CIS event occurs before the first CIS event. For example, when an anchor point of the CIG event obtained in operation **1302** is an anchor point of the first CIS event, the processor **120** may schedule the anchor point of the next CIG event obtained in operation **1304** as an anchor point of the second CIS event, in order to uniformly distribute the time resources allocated for the first CIS event and the time resources allocated for the second CIS event. When the initial CIS event of the CIG event is the first CIS event, the processor **120** may set the initial CIS event of the next CIG event as the second CIS event.

(133) As described above, the electronic device **101** can make a uniform distribution of different CIS events by scheduling the initial CIS event of k-th CIG event and the initial CIS event of (k+1)th CIG event immediately after the k-th CIG event, as the different CIS events.

(134) FIG. **14** is a flowchart illustrating a method of allocating the initial CIS event in the CIG

event based on the quality of the first link between the first external electronic device and the electronic device and the quality of the second link between the second external electronic device and the electronic device according to an embodiment of the disclosure. This method may be executed by the electronic device **101** illustrated in FIG. **1**, the electronic device **101** illustrated in FIG. **2**, the electronic device **101** illustrated in FIG. **3**, or the processor **120** of the electronic device **101**.

(135) Referring to FIG. **14**, in operation **1402**, the processor **120** may identify whether a value indicating the quality of the first link between the first external electronic device and the electronic device **101** is equal to or greater than a value indicating the quality of the second link between the second external electronic device and the electronic device **101**. For example, the processor **120** may identify whether the value indicating the quality of the first link is equal to or greater than the value indicating the quality of the second link, in order to further secure the time resources for transmission through the second link when the quality of the first link is better than the quality of the second link, and further secure the time resources for transmission through the first link when the quality of the second link is better than the quality of the first link. The processor **120** may execute operation **1404** on condition that the value indicating the quality of the first link is equal to or greater than the value indicating the quality of the second link, and execute operation **1406** on condition that the value indicating the quality of the first link is less than the value indicating the quality of the second link.

(136) In operation **1404**, the processor **120** may set an anchor point of the CIS event (e.g., the first CIS event) for the first external electronic device as an anchor point of the next CIG event, based on identifying that the value indicating the quality of the first link is equal to or greater than the value indicating the quality of the second link. For example, in order to further secure the time resources for transmission through the second link (e.g., transmission through the second CIS event), the processor **120** may set the initial CIS event of the next CIG event as the first CIS event.

(137) In operation **1406**, the processor **120** may set an anchor point of the CIS event (e.g., the second CIS event) for the second external electronic device as an anchor point of the next CIG event, based on identifying that the value indicating the quality of the first link is less than the value indicating the quality of the second link. For example, in order to further secure time resources for transmission through the first link (e.g., transmission through the first CIS event), the processor **120** may set the initial CIS event of the next CIG event as the second CIS event.

(138) As described above, by identifying the CIS event having a better link quality from the first CIS event and the second CIS event, and setting the identified CIS event as an initial event of the CIG event, the electronic device **101** may complete transmission of data through the identified CIS event before the end of the CIS event and transmit data through another CIS event. In other words, the electronic device **101** may control transmissions via the CIG event including the first CIS event and the second CIS event in the hybrid deployment depending on the state of the links, thereby distributing the time resources for data transmission according to the quality of each of the links.

(139) According to various embodiments of the disclosure, as opposed to the illustration of FIG. **14**, the processor **120** may execute operation **1406** on condition that in operation **1402**, the value indicating the quality of the first link is equal to or greater than the value indicating the quality of the second link, and execute operation **1404** on condition that the value indicating the quality of the first link is less than the value indicating the quality of the second link.

(140) FIG. **15** is a flowchart illustrating a method of transmitting packets through the CIG event having the hybrid arrangement according to an embodiment of the disclosure. This method may be executed by the electronic device **101** illustrated in FIG. **1**, the electronic device **101** illustrated in FIG. **2**, the electronic device **101** illustrated in FIG. **3**, or the processor **120** of the electronic device **101**.

(141) Referring to FIG. **15**, in operation **1502**, the processor **120** may transmit a first packet, which is the last packet of at least one target packet allocated to transmit to the first external electronic

device in the first CIS event in the CIG event in hybrid arrangement, to the first external electronic device, through the second sub-event before the first sub-event, the second sub-event ending the first CIS event. For example, the second sub-event may be a sub-event overlapping one of sub-events in the second CIS event in the CIG event.

(142) In operation **1504**, the processor **120** may receive a signal from the first external electronic device through the second sub-event in the first CIS event. For example, the signal may be a response packet to the first packet. For example, the signal may be an acknowledgement signal or a non-acknowledgement signal.

(143) In operation **1506**, the processor **120** may identify whether the signal is the acknowledgement signal. For example, the processor **120** may identify whether the signal is the acknowledgement signal or the non-acknowledgement signal through an SN in the response packet. The processor **120** may execute operation **1508** on condition that the signal is the acknowledgement signal, and execute operation **1510** on condition that the signal is the non-acknowledgement signal.

(144) In operation **1508**, the processor **120** may transmit a second packet to the second external electronic device through one of the sub-events in the second CIS event, in response to identifying that the signal is the acknowledgement signal. For example, when the signal is the acknowledgement signal, it may mean that the transmission scheduled for the first CIS event is completed before the end of the first CIS event, so the processor **120** may transmit the second packet to the second external electronic device through the sub-event.

(145) In operation **1510**, in response to identifying that the signal is the non-acknowledgement signal, the processor **120** may re-transmit the first packet to the first external electronic device through the first sub-event after the second sub-event or a third sub-event immediately after the second sub-event. For example, when the signal is the non-acknowledgement signal, the processor **120** may re-transmit the first packet to complete the transmission scheduled for the first CIS event.

(146) According to an embodiment of the disclosure, the electronic device, method, and computer-readable storage medium can provide a robust service against the change in quality of at least one of a link between the electronic device and the first external electronic device or a link between the electronic device and the second external electronic device, by communicating with each of the first external electronic device and the second external electronic device via a connected isochronous group (CIG) event that includes a first connected isochronous stream (CIS) event including first sub-events and a second CIS event including second sub-events at least partially overlapping at least part of the first sub-events.

(147) As described above, according to an embodiment of the disclosure, an electronic device (e.g., an electronic device **101**) may comprise communication circuitry (e.g., a communication circuitry **190**) for Bluetooth low energy (BLE); at least one memory (e.g., a memory **130**) configured to store instructions; and at least one processor (e.g., a processor **120**) operably coupled with the communication circuitry and the at least one memory, the at least one processor being configured, when executing the instructions, to obtain a connected isochronous group (CIG) event including a first connected isochronous stream (CIS) event including first sub-events and a second CIS event including second sub-events that are at least partially overlapped with at least part of the first sub-events; and based on receiving an acknowledgement (ACK) signal on first data transmitted to a first external electronic device via a first sub-event among the first sub-events, transmit second data to a second external electronic device via a third sub-event among the second sub-events overlapping a second sub-event immediately after the first sub-event among the first sub-events.

(148) The at least one processor, when executing the instructions, may be configured to obtain, based on identifying that an anchor point of each of the first sub events is synchronized with an anchor point of each of the second sub events, the CIG event including the first CIS event including the first sub-events and the second CIS event including the second sub-events at least partially overlapping at least part of the first sub-events. The at least one processor, when executing the instructions, may be further configured to obtain, based on identifying that the anchor point of

each of the first sub events is not synchronized with the anchor point of each of the second sub events, the CIG event including the first CIS event and the second CIS event in the sequential arrangement or the CIG event including the first CIS event and the second CIS event in the interleaved arrangement.

(149) The at least one processor, when executing the instructions, may be further configured to obtain, based on identifying that a length of each of the first sub events is identical to a length of each of the second sub events, the CIG event including the first CIS event including the first sub-events and the second CIS event including the second sub-events at least partially overlapping at least part of the first sub-events. The at least one processor, when executing the instructions, may be further configured to obtain, based on identifying that the length of each of the first sub-events is different from the length of each of the second sub-events, the CIG event including the first CIS event and the second CIS event in the sequential arrangement or the CIG event including the first CIS event and the second CIS event in the interleaved arrangement.

(150) The at least one processor, when executing the instructions, may be configured to obtain the CIG event, by configuring an anchor point of the second CIS event within the first CIS event initiated from an anchor point of the first CIS event, the CIG event including the first CIS event including the first sub-events and the second CIS event including the second sub-events at least partially overlapping at least part of the first sub-events.

(151) The at least one processor, when executing the instructions, may be configured to transmit, based on receiving from the first external electronic device via the first sub-event the acknowledgement signal on the first data that is the last target data transmitted to the first external electronic device via the first CIS event, the second data to the second external electronic device via the third sub-event among the second sub-events.

(152) The third sub-event overlapping the second sub-event may be a sub-event that initiates the second CIS event. A part of the second sub-events may not overlap all of the first sub-events.

(153) The at least one processor, when executing the instructions, may be configured to obtain, based on receiving capability information of the first external electronic device from the first external electronic device and receiving capability information of the second external electronic device from the second external electronic device, the CIG event including the first CIS event including the first sub-events and the second CIS event including the second sub-events at least partially overlapping the at least part of the first sub-events.

(154) The at least one processor, when executing the instructions, may be configured to obtain, based on identifying that the first data or the second data is associated with a multimedia content, the CIG event including the first CIS event including the first sub-events and the second CIS event including the second sub-events at least partially overlapping the at least part of the first sub-events.

(155) The at least one processor, when executing the instructions, may be configured to obtain, based on identifying that the quality of a link between the first external electronic device and the electronic device is equal to or more than a reference quality, the CIG event including the first CIS event including the first sub-events and the second CIS event including the second sub-events at least partially overlapping the at least part of the first sub-events.

(156) The first CIS event may be allocated for the first external electronic device, the second CIS event may be allocated for the second external electronic device, an anchor point of the first CIS event among the anchor point of the first CIS event and the anchor point of the second CIS event may be an anchor point of the CIG event, and the at least one processor, when executing the instructions, may be further configured to obtain another CIG event next to the CIG event, wherein the other CIG event may include a third CIS event and a fourth CIS event, the third CIS event including third sub events and being allocated for the first external electronic device, the fourth CIS event including fourth sub events at least partially overlapped with at least part of the third sub events and being allocated for the second external electronic device, and wherein an anchor point

of the fourth CIS event among an anchor point of the third CIS event and the anchor point of the fourth CIS event is an anchor point of the other CIG event.

(157) The at least one processor, when executing the instructions, may be configured to, based on receiving the acknowledgement signal via the first sub-event, cease transmitting data to the first external electronic device via all of the remaining sub-events in the first CIS event.

(158) The first sub-event may be a sub-event not overlapping with the second sub-events, and a priority of a first service provided through the first data may be higher than a priority of second service provided with the second data.

(159) As described above, a method for operating an electronic device with a communication circuitry for Bluetooth low energy (BLE) according to an embodiment of the disclosure may comprise obtaining a connected isochronous group (CIG) event including a first connected isochronous stream (CIS) event that includes first sub events and a second CIS event that includes second sub events that are at least partially overlapped with at least part of the first sub events; and transmitting, based on receiving an acknowledgement (ACK) signal for first data transmitted to a first external electronic device via a first sub event among the first sub events, second data to a second external electronic device via a third sub event among the second sub events, the third sub event being overlapped with a second sub event immediately after the first sub event among the first sub events.

(160) non-transitory computer-readable storage medium according to an embodiment of the disclosure, may store one or more programs including instructions that, when executed by at least one processor of an electronic device with a communication circuitry for Bluetooth low energy, cause the electronic device to obtain a connected isochronous group (CIG) event including a first connected isochronous stream (CIS) event that includes first sub events and a second CIS event that includes second sub events that are at least partially overlapped with at least part of the first sub events; and transmit, based on receiving an acknowledgement (ACK) signal for first data transmitted to a first external electronic device via a first sub event among the first sub events, second data to a second external electronic device via a third sub event among the second sub events, the third sub event being overlapped with a second sub event immediately after the first sub event among the first sub events.

(161) An electronic device according to an embodiment of the disclosure may comprise a communication circuit for Bluetooth low energy (BLE), and a processor, wherein the processor is configured to transmit, to a first external electronic device, a first packet that is the last packet from at least one target packet allocated for transmitting to the first external electronic device within a first connected isochronous stream (CIS) event in a connected isochronous group (CIG) event, via a second sub event before a first sub event ending the first CIS event; transmit, in response to receiving an acknowledgement (ACK) signal for the first packet via the second sub event from the first external electronic device, a second packet to a second external electronic device via a sub event among sub events in a second CIS event in the CIG event; and re-transmit, in response to a non-acknowledgement (NACK) signal for the first packet via the second sub event from the first external electronic device, the first packet to the first external electronic device via a sub event immediately after the second sub event among the remaining sub events in the first CIS event.

(162) According to an embodiment of the disclosure, a method for operating an electronic device with a communication circuitry for Bluetooth low energy (BLE) may comprise transmitting, to a first external electronic device, a first packet that is the last packet from at least one target packet allocated for transmitting to the first external electronic device within a first connected isochronous stream (CIS) event in a connected isochronous group (CIG) event, via a second sub event before a first sub event ending the first CIS event; transmitting, in response to receiving an acknowledgement (ACK) signal for the first packet via the second sub event from the first external electronic device, a second packet to a second external electronic device via a sub event among sub events in a second CIS event in the CIG event; and re-transmitting, in response to a non-

acknowledgement (NACK) signal for the first packet via the second sub event from the first external electronic device, the first packet to the first external electronic device via a sub event immediately after the second sub event among the remaining sub events in the first CIS event.

(163) According to an embodiment of the disclosure, a non-transitory computer-readable storage medium may store one or more programs including instructions that, when executed by at least one processor of an electronic device with a communication circuitry for a BLE, cause the electronic device to transmit, to a first external electronic device, a first packet that is the last packet from at least one target packet allocated for transmitting to the first external electronic device within a first connected isochronous stream (CIS) event in a connected isochronous group (CIG) event, via a second sub event before a first sub event ending the first CIS event; transmit, in response to receiving an acknowledgement (ACK) signal for the first packet via the second sub event from the first external electronic device, a second packet to a second external electronic device via a sub event among sub events in a second CIS event in the CIG event; and re-transmit, in response to a non-acknowledgement (NACK) signal for the first packet via the second sub event from the first external electronic device, the first packet to the first external electronic device via a sub event immediately after the second sub event among the remaining sub events in the first CIS event.

(164) The electronic device according to various embodiments disclosed herein may be one of various types of electronic devices. The electronic devices may include, for example, a portable communication device (e.g., a smartphone), a computer device, a portable multimedia device, a portable medical device, a camera, a wearable device, or a home appliance. The electronic devices are not limited to those described above.

(165) It should be appreciated that various embodiments of the disclosure and the terms used therein are not intended to limit the technological features set forth herein to particular embodiments and include various changes, equivalents, or replacements for a corresponding embodiment. With regard to the description of the drawings, similar reference numerals may be used to refer to similar or related elements. As used herein, each of such phrases as “A or B,” “at least one of A and B,” “at least one of A or B,” “A, B, or C,” “at least one of A, B, and C,” and “at least one of A, B, or C,” may include any one of, or all possible combinations of the items enumerated together in a corresponding one of the phrases. As used herein, such terms as “1st” and “2nd,” or “first” and “second” may be used to simply distinguish a corresponding component from another, and does not limit the components in other aspect (e.g., importance or order). It is to be understood that if an element (e.g., a first element) is referred to, with or without the term “operatively” or “communicatively,” as “coupled with,” “coupled to,” “connected with,” or “connected to” another element (e.g., a second element), it means that the element may be coupled with the other element directly (e.g., wiredly), wirelessly, or via a third element.

(166) As used in connection with various embodiments of the disclosure, the term “module” may include a unit implemented in hardware, software, or firmware, and may be interchangeably used with other terms, for example, “logic,” “logic block,” “part,” or “circuitry.” A module may be a single integral component, or a minimum unit or part thereof, adapted to perform one or more functions. For example, according to an embodiment of the disclosure, the module may be implemented in a form of an application-specific integrated circuit (ASIC).

(167) Various embodiments as set forth herein may be implemented as software (e.g., the program **140**) including one or more instructions that are stored in a storage medium (e.g., an internal memory **136** or an external memory **138**) that is readable by a machine (e.g., the electronic device **101**). For example, a processor (e.g., the processor **120**) of the machine (e.g., the electronic device **101**) may invoke at least one of the one or more instructions stored in the storage medium, and execute it, with or without using one or more other components under the control of the processor. This allows the machine to be operated to perform at least one function according to the at least one instruction invoked. The one or more instructions may include a code generated by a compiler or a code executable by an interpreter. The machine-readable storage medium may be provided in the

form of a non-transitory storage medium. The term “non-transitory” simply means that the storage medium is a tangible device, and does not include a signal (e.g., an electromagnetic wave), but this term does not differentiate between where data is semi-permanently stored in the storage medium and where the data is temporarily stored in the storage medium.

(168) According to an embodiment of the disclosure, a method according to various embodiments of the disclosure may be included and provided in a computer program product. The computer program product may be traded as a product between a seller and a buyer. The computer program product may be distributed in the form of a machine-readable storage medium (e.g., a compact disc read only memory (CD-ROM)), or be distributed (e.g., downloaded or uploaded) online via an application store (e.g., PlayStore™), or between two user devices (e.g., smart phones) directly. If distributed online, at least part of the computer program product may be temporarily generated or at least temporarily stored in the machine-readable storage medium, such as memory of the manufacturer's server, a server of the application store, or a relay server.

(169) According to various embodiments of the disclosure, each component (e.g., a module or a program) of the above-described components may include a single entity or multiple entities, and some of the multiple entities may be separately disposed in different components. According to various embodiments of the disclosure, one or more of the above-described components may be omitted, or one or more other components may be added. Alternatively or additionally, a plurality of components (e.g., modules or programs) may be integrated into a single component. In such a case, according to various embodiments of the disclosure, the integrated component may still perform one or more functions of each of the plurality of components in the same or similar manner as they are performed by a corresponding one of the plurality of components before the integration. According to various embodiments of the disclosure, operations performed by the module, the program, or another component may be carried out sequentially, in parallel, repeatedly, or heuristically, or one or more of the operations may be executed in a different order or omitted, or one or more other operations may be added.

(170) While the disclosure has been shown and described with reference to various embodiments thereof, it will be understood by those skilled in the art that various changes in form and details may be made therein without departing from the spirit and scope of the disclosure as defined by the appended claims and their equivalents.

Claims

1. An electronic device comprising: communication circuitry for Bluetooth low energy (BLE); at least one processor comprising processing circuitry; and memory comprising one or more storage media storing instructions, when executed by the at least one processor, to cause the electronic device to: obtain a connected isochronous group (CIG) event including a first connected isochronous stream (CIS) event that includes first sub-events and a second CIS event that includes second sub-events that at least partially overlap at least part of the first sub-events, and transmit, based on receiving an acknowledgement (ACK) signal for first data transmitted to a first external electronic device via a first sub-event among the first sub-events, second data to a second external electronic device via a third sub-event among the second sub-events, wherein the third sub-event overlaps a second sub-event immediately after the first sub-event among the first sub-events.
2. The electronic device of claim 1, wherein the instructions, when executed by the at least one processor, cause the electronic device to obtain the CIG event based on identifying that an anchor point of each of the first sub-events is synchronized with an anchor point of each of the second sub-events.
3. The electronic device of claim 2, wherein the instructions, when executed by the at least one processor, cause the electronic device to obtain, based on identifying that the anchor point of each of the first sub-events is not synchronized with the anchor point of each of the second sub-events,

the CIG event including the first CIS event and the second CIS event in sequential arrangement or the CIG event including the first CIS event and the second CIS event in interleaved arrangement.

4. The electronic device of claim 1, wherein the instructions, when executed by the at least one processor, cause the electronic device to obtain the CIG event by configuring an anchor point of the second CIS event within the first CIS event initiated from an anchor point of the first CIS event.
5. The electronic device of claim 1, wherein the instructions, when executed by the at least one processor, cause the electronic device to transmit, based on receiving from the first external electronic device via the first sub-event, the ACK signal for the first data that is a last target data transmitted to the first external electronic device via the first CIS event, the second data to the second external electronic device via the third sub-event among the second sub-events.
6. The electronic device of claim 1, wherein the third sub-event that overlaps the second sub-event is a sub-event initiating the second CIS event.
7. The electronic device of claim 6, wherein at least a portion of the second sub-events does not overlap any of the first sub-events.
8. The electronic device of claim 1, wherein the instructions, when executed by the at least one processor, cause the electronic device to obtain the CIG event based on receiving capability information of the first external electronic device from the first external electronic device and receiving capability information of the second external electronic device from the second external electronic device.
9. The electronic device of claim 1, wherein the instructions, when executed by the at least one processor, cause the electronic device to obtain the CIG event based on identifying that the first data or the second data is associated with a multimedia content.
10. The electronic device of claim 1, wherein the instructions, when executed by the at least one processor, cause the electronic device to obtain the CIG event based on identifying that quality of a link between the first external electronic device and the electronic device is above reference quality.
11. The electronic device of claim 1, wherein the first CIS event is allocated for the first external electronic device, wherein the second CIS event is allocated for the second external electronic device, wherein an anchor point of the first CIS event among the anchor point of the first CIS event and an anchor point of the second CIS event is an anchor point of the CIG event, wherein the instructions, when executed by the at least one processor, cause the electronic device to obtain another CIG event next to the CIG event, wherein the other CIG event includes a third CIS event and a fourth CIS event, wherein the third CIS event includes third sub-events and is allocated for the first external electronic device, wherein the fourth CIS event includes fourth sub-events at least partially overlapped with at least part of the third sub-events and is allocated for the second external electronic device, and wherein an anchor point of the fourth CIS event among an anchor point of the third CIS event and the anchor point of the fourth CIS event is an anchor point of the other CIG event.
12. The electronic device of claim 1, wherein the instructions, when executed by the at least one processor, cause the electronic device to cease, based on receiving the ACK signal via the first sub-event, to transmit data to the first external electronic device via all of remaining sub-events in the first CIS event.
13. The electronic device of claim 1, wherein the first sub-event is a sub-event not overlapped with the second sub-events, and wherein priority of a first service provided through the first data is higher than priority of a second service provided through the second data.
14. A method for operating an electronic device with a communication circuitry for Bluetooth low energy (BLE), the method comprising: obtaining a connected isochronous group (CIG) event including a first connected isochronous stream (CIS) event that includes first sub-events and a second CIS event that includes second sub-events that at least partially overlap at least part of the first sub-events; and transmitting, based on receiving an acknowledgement (ACK) signal for first

data transmitted to a first external electronic device via a first sub-event among the first sub-events, second data to a second external electronic device via a third sub-event among the second sub-events, wherein the third sub-event overlaps a second sub-event immediately after the first sub-event among the first sub-events.

15. The method of claim 14, wherein the obtaining of the CIG event comprises obtaining the CIG event based on identifying that an anchor point of each of the first sub-events is synchronized with an anchor point of each of the second sub-events.

16. The method of claim 15, further comprising: obtaining, based on identifying that the anchor point of each of the first sub-events is not synchronized with the anchor point of each of the second sub-events, the CIG event including the first CIS event and the second CIS event in sequential arrangement or the CIG event including the first CIS event and the second CIS event in interleaved arrangement.

17. The method of claim 14, wherein the obtaining of the CIG event comprises obtaining, by configuring an anchor point of the second CIS event within the first CIS event initiated from an anchor point of the first CIS event, the CIG event.

18. The method of claim 14, wherein the transmitting of the second data comprises transmitting, based on receiving from the first external electronic device via the first sub-event, the ACK signal for the first data that is a last target data transmitted to the first external electronic device via the first CIS event, the second data to the second external electronic device via the third sub-event among the second sub-events.

19. The method of claim 14, wherein the third sub-event that overlaps the second sub-event is a sub-event initiating the second CIS event.

20. An electronic device comprising: communication circuitry for Bluetooth low energy (BLE); at least one processor comprising processing circuitry; and memory comprising one or more storage media storing instructions, when executed by the at least one processor, to cause the electronic device to: transmit, to a first external electronic device, a first packet that is a last packet from at least one target packet allocated for transmitting to a first external electronic device within a first connected isochronous stream (CIS) event in a connected isochronous group (CIG) event, via a first sub-event included in the first CIS event; in response to receiving, via the first sub-event, from the first external electronic device, an acknowledgement (ACK) signal for the first packet transmit, via a second sub-event included in a second CIS event in the CIG event, to a second external electronic device, a second packet, the second sub-event overlapping a third sub-event, included in the first CIS event, subsequent to the first sub-event; and in response to receiving, via the first sub-event, from the first external electronic device, a non-acknowledgement (NACK) signal for the first packet, re-transmit, via the third sub-event, to the first external electronic device, the first packet.
