

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12408312
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Brown; Mike

Display assemblies with vents

Abstract

An electronic display assembly with ventilation, and systems and methods related to the same are provided. The electronic display assembly includes an electronic display layer, a closed loop airflow pathway, and one or more vents fluidly interposed between the closed loop airflow pathway and an ambient environment. A controller may control the vents selectively and individually between an open state and a closed state.

Inventors:	Brown; Mike (Cumming, GA)
Applicant:	Manufacturing Resources International, Inc. (Alpharetta, GA)
Family ID:	85039496
Assignee:	Manufacturing Resources International, Inc. (Alpharetta, GA)
Appl. No.:	17/872441
Filed:	July 25, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230032626 A1	Feb. 02, 2023

Related U.S. Application Data

us-provisional-application US 63226314 20210728

Publication Classification

Int. Cl.: G06F1/16 (20060101); H05K5/00 (20250101); H05K5/02 (20060101); H05K7/00 (20060101); H05K7/20 (20060101); G06F1/20 (20060101)

U.S. Cl.:

CPC **H05K7/20972** (20130101); **H05K5/0214** (20220801); **H05K7/20145** (20130101);
G06F1/203 (20130101)

Field of Classification Search

CPC: G06F (1/1601); G06F (1/1616); G06F (1/1618); G06F (1/162); G06F (1/1622); G06F
(1/1624); G06F (1/1628); G06F (1/163); G06F (1/1633); G06F (1/169); G06F (1/1643);
G06F (1/20); G06F (1/203); G06F (1/206); H05K (7/20972); H05K (5/0214); H05K
(7/20145); G02F (1/133382)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4093355	12/1977	Kaplit et al.	N/A	N/A
4292370	12/1980	Pekko	N/A	N/A
4593978	12/1985	Mourey et al.	N/A	N/A
4634225	12/1986	Haim et al.	N/A	N/A
4748765	12/1987	Martin	N/A	N/A
4763993	12/1987	Vogeley et al.	N/A	N/A
4921041	12/1989	Akachi	N/A	N/A
4952783	12/1989	Aufderheide et al.	N/A	N/A
4952925	12/1989	Haastert	N/A	N/A
4976536	12/1989	Vogeley et al.	N/A	N/A
5029982	12/1990	Nash	N/A	N/A
5088806	12/1991	McCartney et al.	N/A	N/A
5132666	12/1991	Fahs	N/A	N/A
5150231	12/1991	Iwamoto et al.	N/A	N/A
5247374	12/1992	Terada	N/A	N/A
5255029	12/1992	Vogeley et al.	N/A	N/A
5282114	12/1993	Stone	N/A	N/A
5285677	12/1993	Oehler	N/A	N/A
5293930	12/1993	Pitasi	N/A	N/A
5351176	12/1993	Smith Stephen W. et al.	N/A	N/A
5432526	12/1994	Hyatt	N/A	N/A
5535816	12/1995	Ishida	N/A	N/A
5559614	12/1995	Urbish et al.	N/A	N/A
5621614	12/1996	O'Neill	N/A	N/A
5657641	12/1996	Cunningham et al.	N/A	N/A
5748269	12/1997	Harris et al.	N/A	N/A
5765743	12/1997	Sakiura et al.	N/A	N/A
5767489	12/1997	Ferrier	N/A	N/A
5808418	12/1997	Pitman et al.	N/A	N/A
5818010	12/1997	McCann	N/A	N/A
5818694	12/1997	Daikoku et al.	N/A	N/A
5835179	12/1997	Yamanaka	N/A	N/A

5864465	12/1998	Liu	N/A	N/A
5869818	12/1998	Kim	N/A	N/A
5869919	12/1998	Sato et al.	N/A	N/A
5903433	12/1998	Gudmundsson	N/A	N/A
5920367	12/1998	Kajimoto et al.	N/A	N/A
5991153	12/1998	Heady et al.	N/A	N/A
6003015	12/1998	Kang et al.	N/A	N/A
6007205	12/1998	Fujimori	N/A	N/A
6043979	12/1999	Shim	N/A	N/A
6089751	12/1999	Conover et al.	N/A	N/A
6104451	12/1999	Matsuoka et al.	N/A	N/A
6125565	12/1999	Hillstrom	N/A	N/A
6157432	12/1999	Helbing	N/A	N/A
6181070	12/2000	Dunn et al.	N/A	N/A
6191839	12/2000	Briley et al.	N/A	N/A
6198222	12/2000	Chang	N/A	N/A
6211934	12/2000	Habing et al.	N/A	N/A
6215655	12/2000	Heady et al.	N/A	N/A
6351381	12/2001	Bilski et al.	N/A	N/A
6359390	12/2001	Nagai	N/A	N/A
6392727	12/2001	Larson et al.	N/A	N/A
6417900	12/2001	Shin et al.	N/A	N/A
6428198	12/2001	Saccomanno et al.	N/A	N/A
6437673	12/2001	Nishida et al.	N/A	N/A
6473150	12/2001	Takushima et al.	N/A	N/A
6476883	12/2001	Salimes et al.	N/A	N/A
6493440	12/2001	Gromatsky et al.	N/A	N/A
6504713	12/2002	Pandolfi et al.	N/A	N/A
6535266	12/2002	Nemeth et al.	N/A	N/A
6628355	12/2002	Takahara	N/A	N/A
6643130	12/2002	DeMarchis et al.	N/A	N/A
6683639	12/2003	Driessen-Olde Scheper et al.	N/A	N/A
6701143	12/2003	Dukach et al.	N/A	N/A
6714410	12/2003	Wellhofer	N/A	N/A
6727468	12/2003	Nemeth	N/A	N/A
6742583	12/2003	Tikka	N/A	N/A
6812851	12/2003	Dukach et al.	N/A	N/A
6825828	12/2003	Burke et al.	N/A	N/A
6833992	12/2003	Kusaka et al.	N/A	N/A
6839104	12/2004	Taniguchi et al.	N/A	N/A
6850209	12/2004	Mankins et al.	N/A	N/A
6885412	12/2004	Ohnishi et al.	N/A	N/A
6886942	12/2004	Okada et al.	N/A	N/A
6891135	12/2004	Pala et al.	N/A	N/A
6909486	12/2004	Wang et al.	N/A	N/A
6943768	12/2004	Cavanaugh et al.	N/A	N/A
6961108	12/2004	Wang et al.	N/A	N/A
7015470	12/2005	Faytlin et al.	N/A	N/A
7059757	12/2005	Shimizu	N/A	N/A

7083285	12/2005	Hsu et al.	N/A	N/A
7157838	12/2006	Thielemans et al.	N/A	N/A
7161803	12/2006	Heady	N/A	N/A
7164586	12/2006	Lin	N/A	N/A
7190416	12/2006	Paukshto et al.	N/A	N/A
7190587	12/2006	Kim et al.	N/A	N/A
7209349	12/2006	Chien et al.	N/A	N/A
7212403	12/2006	Rockenfell	N/A	N/A
7259964	12/2006	Yamamura et al.	N/A	N/A
7269023	12/2006	Nagano	N/A	N/A
7284874	12/2006	Jeong et al.	N/A	N/A
7342789	12/2007	Hall et al.	N/A	N/A
7396145	12/2007	Wang et al.	N/A	N/A
7447018	12/2007	Lee et al.	N/A	N/A
7452121	12/2007	Cho et al.	N/A	N/A
7457113	12/2007	Kumhyr et al.	N/A	N/A
7466546	12/2007	Park	N/A	N/A
7480140	12/2008	Hara et al.	N/A	N/A
7492589	12/2008	Park	N/A	N/A
7518864	12/2008	Kimura	N/A	N/A
7535543	12/2008	Dewa et al.	N/A	N/A
7591508	12/2008	Chang	N/A	N/A
7602469	12/2008	Shin	N/A	N/A
D608775	12/2009	Leung	N/A	N/A
7667964	12/2009	Kang et al.	N/A	N/A
7682047	12/2009	Hsu et al.	N/A	N/A
7752858	12/2009	Johnson et al.	N/A	N/A
7753567	12/2009	Kang et al.	N/A	N/A
7762707	12/2009	Kim et al.	N/A	N/A
7800706	12/2009	Kim et al.	N/A	N/A
7813124	12/2009	Karppanen	N/A	N/A
7903416	12/2010	Chou	N/A	N/A
7995342	12/2010	Nakamichi et al.	N/A	N/A
8004648	12/2010	Dunn	N/A	N/A
8035968	12/2010	Kwon et al.	N/A	N/A
8081267	12/2010	Moscovitch et al.	N/A	N/A
8081465	12/2010	Nishiura	N/A	N/A
8102173	12/2011	Merrow	N/A	N/A
8102483	12/2011	Perry et al.	N/A	N/A
8142027	12/2011	Sakai	N/A	N/A
8208115	12/2011	Dunn	N/A	N/A
8223311	12/2011	Kim et al.	N/A	N/A
8241573	12/2011	Banerjee et al.	N/A	N/A
8248784	12/2011	Nakamichi et al.	N/A	N/A
8254121	12/2011	Lee et al.	N/A	N/A
8269916	12/2011	Ohkawa	N/A	N/A
8270163	12/2011	Nakamichi et al.	N/A	N/A
8274622	12/2011	Dunn	N/A	N/A
8274789	12/2011	Nakamichi et al.	N/A	N/A
8300203	12/2011	Nakamichi et al.	N/A	N/A

8310824	12/2011	Dunn et al.	N/A	N/A
8320119	12/2011	Isoshima et al.	N/A	N/A
8351014	12/2012	Dunn	N/A	N/A
8358397	12/2012	Dunn	N/A	N/A
8369083	12/2012	Dunn et al.	N/A	N/A
8373841	12/2012	Dunn	N/A	N/A
8379182	12/2012	Dunn	N/A	N/A
8400608	12/2012	Takahashi et al.	N/A	N/A
8472174	12/2012	Idems et al.	N/A	N/A
8472191	12/2012	Yamamoto et al.	N/A	N/A
8482695	12/2012	Dunn	N/A	N/A
8497972	12/2012	Dunn et al.	N/A	N/A
8590602	12/2012	Fernandez	N/A	N/A
8649170	12/2013	Dunn et al.	N/A	N/A
8649176	12/2013	Okada et al.	N/A	N/A
8654302	12/2013	Dunn et al.	N/A	N/A
8678603	12/2013	Zhang	N/A	N/A
8693185	12/2013	Dunn et al.	N/A	N/A
8700226	12/2013	Schuch et al.	N/A	N/A
8711321	12/2013	Dunn et al.	N/A	N/A
8749749	12/2013	Hubbard	N/A	N/A
8755021	12/2013	Hubbard	N/A	N/A
8758144	12/2013	Williams et al.	N/A	N/A
8760613	12/2013	Dunn	N/A	N/A
8767165	12/2013	Dunn	N/A	N/A
8773633	12/2013	Dunn et al.	N/A	N/A
8804091	12/2013	Dunn et al.	N/A	N/A
8823916	12/2013	Hubbard et al.	N/A	N/A
8827472	12/2013	Takada	N/A	N/A
8854572	12/2013	Dunn	N/A	N/A
8854595	12/2013	Dunn	N/A	N/A
8879042	12/2013	Dunn	N/A	N/A
8976313	12/2014	Kim et al.	N/A	N/A
8988647	12/2014	Hubbard	N/A	N/A
9030641	12/2014	Dunn	N/A	N/A
9089079	12/2014	Dunn	N/A	N/A
9119325	12/2014	Dunn et al.	N/A	N/A
9119330	12/2014	Hubbard et al.	N/A	N/A
9173322	12/2014	Dunn	N/A	N/A
9173325	12/2014	Dunn	N/A	N/A
9282676	12/2015	Diaz	N/A	N/A
9285108	12/2015	Dunn et al.	N/A	N/A
9313917	12/2015	Dunn et al.	N/A	N/A
9335579	12/2015	Onoue	N/A	N/A
9338923	12/2015	Lee et al.	N/A	N/A
9357673	12/2015	Chin	N/A	N/A
9370127	12/2015	Dunn	N/A	N/A
9414516	12/2015	Chin et al.	N/A	N/A
9448569	12/2015	Schuch et al.	N/A	N/A
9451060	12/2015	Bowers et al.	N/A	N/A

9451733	12/2015	Dunn et al.	N/A	N/A
9456525	12/2015	Yoon et al.	N/A	N/A
9470924	12/2015	Dunn et al.	N/A	N/A
9500896	12/2015	Dunn et al.	N/A	N/A
9504188	12/2015	Campbell et al.	N/A	N/A
9516485	12/2015	Bowers et al.	N/A	N/A
9549490	12/2016	Hubbard	N/A	N/A
9594271	12/2016	Dunn et al.	N/A	N/A
9600026	12/2016	Birgeoglu et al.	N/A	N/A
9613548	12/2016	DeMars	N/A	N/A
9622392	12/2016	Bowers et al.	N/A	N/A
9629287	12/2016	Dunn	N/A	N/A
9648790	12/2016	Dunn et al.	N/A	N/A
9655289	12/2016	Dunn et al.	N/A	N/A
9703230	12/2016	Bowers et al.	N/A	N/A
9723765	12/2016	DeMars	N/A	N/A
9743553	12/2016	Kim et al.	N/A	N/A
9756739	12/2016	Russell-Clarke et al.	N/A	N/A
9797588	12/2016	Dunn et al.	N/A	N/A
9801305	12/2016	Dunn et al.	N/A	N/A
9823690	12/2016	Bowers et al.	N/A	N/A
9835893	12/2016	Dunn	N/A	N/A
9857618	12/2017	Barnes	N/A	N/A
9861007	12/2017	Yoon et al.	N/A	N/A
9894800	12/2017	Dunn	N/A	N/A
10070540	12/2017	Campagna et al.	N/A	N/A
10080316	12/2017	Dunn et al.	N/A	N/A
10088702	12/2017	Dunn et al.	N/A	N/A
10165712	12/2017	Jang et al.	N/A	N/A
10180591	12/2018	Lee et al.	N/A	N/A
10194564	12/2018	Dunn et al.	N/A	N/A
10212845	12/2018	Dunn et al.	N/A	N/A
10278311	12/2018	DeMars	N/A	N/A
10278312	12/2018	Davis et al.	N/A	N/A
10306781	12/2018	Cho et al.	N/A	N/A
10314212	12/2018	Hubbard	N/A	N/A
10359659	12/2018	Dunn et al.	N/A	N/A
10359817	12/2018	Yun et al.	N/A	N/A
10383238	12/2018	Yun et al.	N/A	N/A
10398066	12/2018	Dunn et al.	N/A	N/A
10405456	12/2018	Jang et al.	N/A	N/A
10409323	12/2018	Birgeoglu et al.	N/A	N/A
10420257	12/2018	Dunn et al.	N/A	N/A
10485113	12/2018	Dunn	N/A	G02F 1/13338
10485147	12/2018	Oh et al.	N/A	N/A
10485148	12/2018	Oh et al.	N/A	N/A
10488896	12/2018	Simpson	N/A	N/A
10499516	12/2018	Dunn et al.	N/A	N/A

10506738	12/2018	Dunn	N/A	N/A
10506740	12/2018	Dunn et al.	N/A	N/A
10524384	12/2018	Dunn et al.	N/A	N/A
10524397	12/2018	Dunn et al.	N/A	N/A
10548247	12/2019	Demars	N/A	N/A
10624218	12/2019	Dunn et al.	N/A	N/A
10660245	12/2019	Dunn et al.	N/A	N/A
10687446	12/2019	Dunn et al.	N/A	N/A
10716224	12/2019	Dunn et al.	N/A	N/A
10721836	12/2019	Dunn et al.	N/A	N/A
10736245	12/2019	Dunn et al.	N/A	N/A
10747261	12/2019	Birgeoglu et al.	N/A	N/A
10754184	12/2019	Wang et al.	N/A	N/A
10757844	12/2019	Dunn et al.	N/A	N/A
10795413	12/2019	Dunn	N/A	N/A
10820445	12/2019	Diaz	N/A	N/A
10827656	12/2019	Hubbard	N/A	N/A
10827657	12/2019	Lee	N/A	N/A
10905035	12/2020	Whitehead et al.	N/A	N/A
10925174	12/2020	Dunn et al.	N/A	N/A
10969615	12/2020	Wang et al.	N/A	N/A
10973156	12/2020	Dunn et al.	N/A	N/A
11013142	12/2020	Dunn et al.	N/A	N/A
11016547	12/2020	Whitehead et al.	N/A	N/A
11019735	12/2020	Dunn	N/A	N/A
11032923	12/2020	Dunn et al.	N/A	N/A
11096317	12/2020	Dunn	N/A	N/A
11191193	12/2020	Hubbard	N/A	N/A
2001/0001459	12/2000	Savant et al.	N/A	N/A
2001/0019454	12/2000	Tadic-Galeb et al.	N/A	N/A
2001/0023914	12/2000	Oddsens, Jr.	N/A	N/A
2001/0032404	12/2000	Hillstrom	N/A	N/A
2002/0009978	12/2001	Dukach et al.	N/A	N/A
2002/0033919	12/2001	Sanelle et al.	N/A	N/A
2002/0050793	12/2001	Cull et al.	N/A	N/A
2002/0065046	12/2001	Mankins et al.	N/A	N/A
2002/0084891	12/2001	Mankins et al.	N/A	N/A
2002/0101553	12/2001	Enomoto et al.	N/A	N/A
2002/0112026	12/2001	Fridman et al.	N/A	N/A
2002/0126248	12/2001	Yoshida	N/A	N/A
2002/0148600	12/2001	Bosch et al.	N/A	N/A
2002/0149714	12/2001	Anderson et al.	N/A	N/A
2002/0154255	12/2001	Gromatzky et al.	N/A	N/A
2002/0164944	12/2001	Haglid	N/A	N/A
2002/0164962	12/2001	Mankins et al.	N/A	N/A
2002/0167637	12/2001	Burke et al.	N/A	N/A
2003/0007109	12/2002	Park	N/A	N/A
2003/0020884	12/2002	Okada et al.	N/A	N/A
2003/0043091	12/2002	Takeuchi et al.	N/A	N/A
2003/0104210	12/2002	Azumi et al.	N/A	N/A

2003/0128511	12/2002	Nagashima et al.	N/A	N/A
2003/0214785	12/2002	Perazzo	N/A	N/A
2004/0012722	12/2003	Alvarez	N/A	N/A
2004/0035032	12/2003	Milliken	N/A	N/A
2004/0035558	12/2003	Todd et al.	N/A	N/A
2004/0036622	12/2003	Dukach et al.	N/A	N/A
2004/0036834	12/2003	Ohnishi et al.	N/A	N/A
2004/0042174	12/2003	Tomioka et al.	N/A	N/A
2004/0103570	12/2003	Ruttenberg	N/A	N/A
2004/0105159	12/2003	Saccomanno et al.	N/A	N/A
2004/0135482	12/2003	Thielemans et al.	N/A	N/A
2004/0165139	12/2003	Anderson et al.	N/A	N/A
2004/0207981	12/2003	Gorenz, Jr. et al.	N/A	N/A
2004/0223299	12/2003	Ghosh	N/A	N/A
2005/0012039	12/2004	Faytlin et al.	N/A	N/A
2005/0012722	12/2004	Chon	N/A	N/A
2005/0062373	12/2004	Kim et al.	N/A	N/A
2005/0073632	12/2004	Dunn et al.	N/A	N/A
2005/0073639	12/2004	Pan	N/A	N/A
2005/0127796	12/2004	Olesen et al.	N/A	N/A
2005/0134525	12/2004	Tanghe et al.	N/A	N/A
2005/0134526	12/2004	Willem et al.	N/A	N/A
2005/0213950	12/2004	Yoshimura	N/A	N/A
2005/0219841	12/2004	Ikeda et al.	N/A	N/A
2005/0229630	12/2004	Richter et al.	N/A	N/A
2005/0237714	12/2004	Ebermann	N/A	N/A
2005/0253699	12/2004	Madonia	N/A	N/A
2005/0276053	12/2004	Nortrup et al.	N/A	N/A
2005/0286131	12/2004	Saxena et al.	N/A	N/A
2006/0012958	12/2005	Tomioka et al.	N/A	N/A
2006/0012985	12/2005	Archie, Jr. et al.	N/A	N/A
2006/0018093	12/2005	Lai et al.	N/A	N/A
2006/0034051	12/2005	Wang et al.	N/A	N/A
2006/0056994	12/2005	Van Lear et al.	N/A	N/A
2006/0077636	12/2005	Kim	N/A	N/A
2006/0082271	12/2005	Lee et al.	N/A	N/A
2006/0092348	12/2005	Park	N/A	N/A
2006/0125998	12/2005	Dewa et al.	N/A	N/A
2006/0132699	12/2005	Cho et al.	N/A	N/A
2006/0177587	12/2005	Ishizuka et al.	N/A	N/A
2006/0199514	12/2005	Kimura	N/A	N/A
2006/0209266	12/2005	Utsunomiya	N/A	N/A
2006/0260790	12/2005	Theno et al.	N/A	N/A
2006/0262079	12/2005	Seong et al.	N/A	N/A
2006/0266499	12/2005	Choi et al.	N/A	N/A
2006/0268194	12/2005	Morimoto et al.	N/A	N/A
2006/0269216	12/2005	Wiemeyer et al.	N/A	N/A
2006/0283579	12/2005	Ghosh et al.	N/A	N/A
2007/0013647	12/2006	Lee et al.	N/A	N/A
2007/0019419	12/2006	Hafuka et al.	N/A	N/A

2007/0030879	12/2006	Hatta	N/A	N/A
2007/0046874	12/2006	Adachi et al.	N/A	N/A
2007/0047239	12/2006	Kang et al.	N/A	N/A
2007/0065091	12/2006	Hinata et al.	N/A	N/A
2007/0076431	12/2006	Atarashi et al.	N/A	N/A
2007/0081344	12/2006	Cappaert et al.	N/A	N/A
2007/0103863	12/2006	Kim	N/A	N/A
2007/0103866	12/2006	Park	N/A	N/A
2007/0115686	12/2006	Tyberghien	N/A	N/A
2007/0139929	12/2006	Yoo et al.	N/A	N/A
2007/0140671	12/2006	Yoshimura	N/A	N/A
2007/0144704	12/2006	Bundza et al.	N/A	N/A
2007/0151274	12/2006	Roche et al.	N/A	N/A
2007/0151664	12/2006	Shin	N/A	N/A
2007/0171353	12/2006	Hong	N/A	N/A
2007/0176885	12/2006	Jun	N/A	N/A
2007/0206158	12/2006	Kinoshita et al.	N/A	N/A
2007/0211205	12/2006	Shibata	N/A	N/A
2007/0212211	12/2006	Chiyoda et al.	N/A	N/A
2007/0217221	12/2006	Lee et al.	N/A	N/A
2007/0237636	12/2006	Hsu	N/A	N/A
2007/0267174	12/2006	Kim	N/A	N/A
2008/0035315	12/2007	Han	N/A	N/A
2008/0054144	12/2007	Wohlford	N/A	N/A
2008/0055534	12/2007	Kawano	N/A	N/A
2008/0076342	12/2007	Bryant et al.	N/A	N/A
2008/0099193	12/2007	Aksamit et al.	N/A	N/A
2008/0148609	12/2007	Ogoreve	N/A	N/A
2008/0165496	12/2007	Kang et al.	N/A	N/A
2008/0209934	12/2007	Richards	N/A	N/A
2008/0218446	12/2007	Yamanaka	N/A	N/A
2008/0236005	12/2007	Isayev et al.	N/A	N/A
2008/0267790	12/2007	Gaudet et al.	N/A	N/A
2008/0283234	12/2007	Sagi et al.	N/A	N/A
2008/0285290	12/2007	Ohashi et al.	N/A	N/A
2008/0296134	12/2007	Hattori et al.	N/A	N/A
2008/0310116	12/2007	O'Connor	N/A	N/A
2008/0310158	12/2007	Harbers et al.	N/A	N/A
2009/0009047	12/2008	Yanagawa et al.	N/A	N/A
2009/0009729	12/2008	Sakai	N/A	N/A
2009/0021461	12/2008	Hu et al.	N/A	N/A
2009/0034188	12/2008	Sween et al.	N/A	N/A
2009/0059518	12/2008	Kakikawa et al.	N/A	N/A
2009/0065007	12/2008	Wilkinson et al.	N/A	N/A
2009/0086430	12/2008	Kang et al.	N/A	N/A
2009/0095819	12/2008	Brown et al.	N/A	N/A
2009/0104989	12/2008	Williams et al.	N/A	N/A
2009/0120629	12/2008	Ashe	N/A	N/A
2009/0122218	12/2008	Oh et al.	N/A	N/A
2009/0126906	12/2008	Dunn	N/A	N/A

2009/0126907	12/2008	Dunn	N/A	N/A
2009/0126914	12/2008	Dunn	N/A	N/A
2009/0129021	12/2008	Dunn	N/A	N/A
2009/0135365	12/2008	Dunn	N/A	N/A
2009/0147170	12/2008	Oh et al.	N/A	N/A
2009/0154096	12/2008	Iyengar et al.	N/A	N/A
2009/0174626	12/2008	Isoshima et al.	N/A	N/A
2009/0231807	12/2008	Bouissier	N/A	N/A
2009/0241437	12/2008	Steinle et al.	N/A	N/A
2009/0244472	12/2008	Dunn	N/A	N/A
2009/0266507	12/2008	Turnbull et al.	N/A	N/A
2009/0279240	12/2008	Karppanen	N/A	N/A
2009/0302727	12/2008	Vincent et al.	N/A	N/A
2009/0306820	12/2008	Simmons et al.	N/A	N/A
2009/0323275	12/2008	Rehmann et al.	N/A	N/A
2010/0060861	12/2009	Medin	N/A	N/A
2010/0079949	12/2009	Nakamichi et al.	N/A	N/A
2010/0079979	12/2009	Nakamichi et al.	N/A	N/A
2010/0162747	12/2009	Hamel et al.	N/A	N/A
2010/0171889	12/2009	Pantel et al.	N/A	N/A
2010/0182562	12/2009	Yoshida et al.	N/A	N/A
2010/0220249	12/2009	Nakamichi et al.	N/A	N/A
2010/0226091	12/2009	Punn	N/A	N/A
2010/0232107	12/2009	Dunn	N/A	N/A
2010/0238394	12/2009	Dunn	N/A	N/A
2010/0321887	12/2009	Kwon et al.	N/A	N/A
2011/0001898	12/2010	Mikubo et al.	N/A	N/A
2011/0013114	12/2010	Dunn et al.	N/A	N/A
2011/0019363	12/2010	Vahlsing et al.	N/A	N/A
2011/0032489	12/2010	Kimoto et al.	N/A	N/A
2011/0051071	12/2010	Nakamichi et al.	N/A	N/A
2011/0051369	12/2010	Takahara	N/A	N/A
2011/0058326	12/2010	Idems et al.	N/A	N/A
2011/0072697	12/2010	Miller	N/A	N/A
2011/0075361	12/2010	Nakamichi et al.	N/A	N/A
2011/0083460	12/2010	Thomas et al.	N/A	N/A
2011/0083824	12/2010	Rogers	N/A	N/A
2011/0085301	12/2010	Dunn	361/695	H05K 7/20972
2011/0085302	12/2010	Nakamichi et al.	N/A	N/A
2011/0114384	12/2010	Sakamoto et al.	N/A	N/A
2011/0116000	12/2010	Dunn et al.	N/A	N/A
2011/0116231	12/2010	Dunn et al.	N/A	N/A
2011/0122162	12/2010	Sato et al.	N/A	N/A
2011/0134356	12/2010	Swatt et al.	N/A	N/A
2011/0141672	12/2010	Farley, Jr. et al.	N/A	N/A
2011/0141724	12/2010	Erion	N/A	N/A
2011/0162831	12/2010	Lee et al.	N/A	N/A
2011/0167845	12/2010	Lee et al.	N/A	N/A
2011/0261523	12/2010	Dunn et al.	N/A	N/A

2011/0297810	12/2010	Tachibana	N/A	N/A
2012/0006523	12/2011	Masahiro et al.	N/A	N/A
2012/0012295	12/2011	Kakiuchi et al.	N/A	N/A
2012/0012300	12/2011	Dunn et al.	N/A	N/A
2012/0014063	12/2011	Weiss	N/A	N/A
2012/0020114	12/2011	Miyamoto et al.	N/A	N/A
2012/0038849	12/2011	Dunn et al.	N/A	N/A
2012/0044217	12/2011	Okada et al.	N/A	N/A
2012/0105790	12/2011	Hubbard	N/A	N/A
2012/0106081	12/2011	Hubbard	361/696	G02F 1/133308
2012/0131936	12/2011	Yoshida et al.	N/A	N/A
2012/0188481	12/2011	Kang et al.	N/A	N/A
2012/0206687	12/2011	Dunn et al.	N/A	N/A
2012/0223877	12/2011	Cho	N/A	N/A
2012/0224116	12/2011	Barnes	N/A	N/A
2012/0236499	12/2011	Murayama et al.	N/A	N/A
2012/0249402	12/2011	Kang	N/A	N/A
2012/0255704	12/2011	Nakamichi	N/A	N/A
2012/0274876	12/2011	Cappaert et al.	N/A	N/A
2012/0284547	12/2011	Culbert et al.	N/A	N/A
2012/0327600	12/2011	Dunn	N/A	N/A
2013/0170140	12/2012	Dunn	N/A	N/A
2013/0173358	12/2012	Pinkus	N/A	N/A
2013/0176517	12/2012	Kim et al.	N/A	N/A
2013/0201685	12/2012	Messmore et al.	N/A	N/A
2013/0258659	12/2012	Erion	N/A	N/A
2013/0279154	12/2012	Dunn	362/97.3	F21V 29/67
2013/0294039	12/2012	Chao	N/A	N/A
2013/0344794	12/2012	Shaw et al.	N/A	N/A
2014/0044147	12/2013	Wyatt et al.	N/A	N/A
2014/0085564	12/2013	Hendren et al.	N/A	N/A
2014/0111758	12/2013	Dunn et al.	N/A	N/A
2014/0113540	12/2013	Dunn et al.	N/A	N/A
2014/0134767	12/2013	Ishida et al.	N/A	N/A
2014/0184980	12/2013	Onoue	N/A	N/A
2014/0190240	12/2013	He et al.	N/A	N/A
2014/0268657	12/2013	Dunn et al.	N/A	N/A
2014/0313452	12/2013	Dunn et al.	N/A	N/A
2014/0313666	12/2013	Chin	N/A	N/A
2014/0313698	12/2013	Dunn et al.	N/A	N/A
2014/0314395	12/2013	Dunn et al.	N/A	N/A
2014/0334100	12/2013	Yoon et al.	N/A	N/A
2014/0361138	12/2013	Ramirez et al.	N/A	N/A
2015/0009625	12/2014	Chin et al.	N/A	N/A
2015/0009627	12/2014	Dunn et al.	N/A	N/A
2015/0087404	12/2014	Lesley et al.	N/A	N/A
2015/0192371	12/2014	Hancock	N/A	N/A
2015/0253611	12/2014	Yang et al.	N/A	N/A
2015/0264826	12/2014	Dunn et al.	N/A	N/A

2015/0319882	12/2014	Dunn et al.	N/A	N/A
2015/0366101	12/2014	Dunn et al.	N/A	N/A
2016/0041423	12/2015	Dunn	N/A	N/A
2016/0044829	12/2015	Dunn	N/A	N/A
2016/0162297	12/2015	Shao	N/A	N/A
2016/0192536	12/2015	Diaz	N/A	N/A
2016/0195254	12/2015	Dunn et al.	N/A	N/A
2016/0198588	12/2015	DeMars	N/A	N/A
2016/0238876	12/2015	Dunn et al.	N/A	N/A
2016/0242329	12/2015	DeMars	N/A	N/A
2016/0242330	12/2015	Dunn	N/A	N/A
2016/0249493	12/2015	Dunn et al.	N/A	N/A
2016/0265759	12/2015	Na et al.	N/A	N/A
2016/0302331	12/2015	Dunn	N/A	N/A
2017/0023823	12/2016	Dunn et al.	N/A	N/A
2017/0068042	12/2016	Dunn et al.	N/A	N/A
2017/0074453	12/2016	Bowers et al.	N/A	N/A
2017/0083043	12/2016	Bowers et al.	N/A	N/A
2017/0083062	12/2016	Bowers et al.	N/A	N/A
2017/0111486	12/2016	Bowers et al.	N/A	N/A
2017/0111520	12/2016	Bowers et al.	N/A	N/A
2017/0111521	12/2016	Bowers et al.	N/A	N/A
2017/0127579	12/2016	Hubbard	N/A	N/A
2017/0140344	12/2016	Bowers et al.	N/A	N/A
2017/0147992	12/2016	Bowers et al.	N/A	N/A
2017/0163519	12/2016	Bowers et al.	N/A	N/A
2017/0172016	12/2016	Kang	N/A	N/A
2017/0175411	12/2016	Bowers et al.	N/A	N/A
2017/0188490	12/2016	Dunn et al.	N/A	N/A
2017/0231112	12/2016	Dunn et al.	N/A	N/A
2017/0245400	12/2016	Dunn et al.	N/A	N/A
2017/0257978	12/2016	Diaz	N/A	N/A
2017/0332523	12/2016	DeMars	N/A	N/A
2017/0345346	12/2016	Hong et al.	N/A	N/A
2018/0020579	12/2017	Chang et al.	N/A	N/A
2018/0042134	12/2017	Dunn et al.	N/A	N/A
2018/0088368	12/2017	Notoshi et al.	N/A	N/A
2018/0088398	12/2017	Lee et al.	N/A	N/A
2018/0116073	12/2017	Dunn	N/A	N/A
2018/0199450	12/2017	Kim et al.	N/A	N/A
2018/0259806	12/2017	Oh et al.	N/A	N/A
2018/0263142	12/2017	Oh	N/A	H05K 7/20972
2018/0314103	12/2017	Dunn et al.	N/A	N/A
2018/0315356	12/2017	Dunn et al.	N/A	N/A
2018/0317330	12/2017	Dunn et al.	N/A	N/A
2018/0317350	12/2017	Dunn et al.	N/A	N/A
2018/0364519	12/2017	Dunn et al.	N/A	N/A
2019/0021189	12/2018	Kim et al.	N/A	N/A
2019/0037738	12/2018	Dunn et al.	N/A	N/A

2019/0089176	12/2018	Dunn et al.	N/A	N/A
2019/0133002	12/2018	Dunn et al.	N/A	N/A
2019/0159363	12/2018	Jang et al.	N/A	N/A
2019/0208674	12/2018	Demars	N/A	N/A
2019/0239365	12/2018	Dunn et al.	N/A	N/A
2019/0289754	12/2018	Hubbard	N/A	N/A
2019/0327865	12/2018	Dunn et al.	N/A	N/A
2020/0154597	12/2019	Dunn et al.	N/A	N/A
2020/0163235	12/2019	Dunn	N/A	N/A
2020/0201402	12/2019	Lee et al.	N/A	N/A
2020/0205303	12/2019	Dunn et al.	N/A	N/A
2020/0253095	12/2019	Dunn et al.	N/A	N/A
2020/0275585	12/2019	Dunn	N/A	N/A
2020/0288585	12/2019	Dunn et al.	N/A	N/A
2020/0319676	12/2019	Dunn	N/A	N/A
2020/0352049	12/2019	Dunn et al.	N/A	N/A
2020/0367391	12/2019	Dunn	N/A	N/A
2020/0387194	12/2019	Dunn	N/A	N/A
2020/0390009	12/2019	Whitehead	N/A	G09F 9/3026
2021/0007241	12/2020	Diaz	N/A	N/A
2021/0022273	12/2020	Hubbard	N/A	N/A
2021/0165472	12/2020	Chin	N/A	N/A
2021/0168949	12/2020	Dunn et al.	N/A	N/A
2021/0231998	12/2020	Noso et al.	N/A	N/A
2021/0243906	12/2020	Dunn	N/A	N/A
2021/0243914	12/2020	Dunn	N/A	N/A
2021/0304644	12/2020	Webster	N/A	N/A
2021/0307214	12/2020	Zhang et al.	N/A	N/A
2021/0345528	12/2020	Dunn	N/A	N/A
2022/0035198	12/2021	Dunn et al.	N/A	N/A
2022/0110227	12/2021	Brown	N/A	N/A
2022/0121255	12/2021	Wang et al.	N/A	N/A
2022/0132707	12/2021	Dunn et al.	N/A	N/A
2022/0287200	12/2021	Dunn et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2011248190	12/2010	AU	N/A
2014287438	12/2017	AU	N/A
2015253128	12/2017	AU	N/A
2017216500	12/2017	AU	N/A
2015229457	12/2018	AU	N/A
2016220308	12/2018	AU	N/A
2017228430	12/2019	AU	N/A
2018258497	12/2020	AU	N/A
2018257648	12/2020	AU	N/A
PI0820231-1	12/2018	BR	N/A
2705814	12/2017	CA	N/A
2947524	12/2017	CA	N/A

2915261	12/2017	CA	N/A
27982777	12/2018	CA	N/A
2809019	12/2018	CA	N/A
2888494	12/2018	CA	N/A
2976116	12/2019	CA	N/A
3015365	12/2020	CA	N/A
3059972	12/2021	CA	N/A
2942321	12/2021	CA	N/A
2702363	12/2004	CN	N/A
201228893	12/2008	CN	N/A
202838830	12/2012	CN	N/A
106304788	12/2016	CN	N/A
107251671	12/2016	CN	N/A
108700739	12/2017	CN	N/A
107251671	12/2018	CN	N/A
1408476	12/2003	EP	N/A
1647766	12/2005	EP	N/A
1722559	12/2005	EP	N/A
1762892	12/2006	EP	N/A
1951020	12/2007	EP	N/A
2225603	12/2009	EP	N/A
2370987	12/2010	EP	N/A
2603831	12/2012	EP	N/A
2801888	12/2013	EP	N/A
2909829	12/2014	EP	N/A
3020260	12/2015	EP	N/A
3040766	12/2015	EP	N/A
3117693	12/2016	EP	N/A
3259968	12/2016	EP	N/A
3423886	12/2018	EP	N/A
3468321	12/2018	EP	N/A
3138372	12/2018	EP	N/A
3117693	12/2018	EP	N/A
2567283	12/2018	EP	N/A
2909829	12/2019	EP	N/A
3615978	12/2019	EP	N/A
3616481	12/2019	EP	N/A
3624574	12/2019	EP	N/A
3468321	12/2020	EP	N/A
3423886	12/2021	EP	N/A
3259968	12/2021	EP	N/A
2402205	12/2003	GB	N/A
402062015	12/1989	JP	N/A
402307080	12/1989	JP	N/A
3153212	12/1990	JP	N/A
H06-2337	12/1993	JP	N/A
6082745	12/1993	JP	N/A
H8-55567	12/1995	JP	N/A
8115788	12/1995	JP	N/A
8194437	12/1995	JP	N/A

H08-305301	12/1995	JP	N/A
8339034	12/1995	JP	N/A
H9-160512	12/1996	JP	N/A
H09246766	12/1996	JP	N/A
11160727	12/1998	JP	N/A
H11296094	12/1998	JP	N/A
2000-10501	12/1999	JP	N/A
2000131682	12/1999	JP	N/A
2001209126	12/2000	JP	N/A
2002-6282	12/2001	JP	N/A
2002158475	12/2001	JP	N/A
2003-76286	12/2002	JP	N/A
2004053749	12/2003	JP	N/A
2004-199675	12/2003	JP	N/A
2004286940	12/2003	JP	N/A
2005017556	12/2004	JP	N/A
2005134849	12/2004	JP	N/A
2005265922	12/2004	JP	N/A
2006-32890	12/2005	JP	N/A
2006513577	12/2005	JP	N/A
2006148047	12/2005	JP	N/A
2006163217	12/2005	JP	N/A
2006-176112	12/2005	JP	N/A
2007003638	12/2006	JP	N/A
2007-293105	12/2006	JP	N/A
09307257	12/2006	JP	N/A
2007322718	12/2006	JP	N/A
2008010361	12/2007	JP	N/A
2008292743	12/2007	JP	N/A
2010024624	12/2009	JP	N/A
2010-102227	12/2009	JP	N/A
2010-282109	12/2009	JP	N/A
2011-14593	12/2010	JP	N/A
2011-503663	12/2010	JP	N/A
2011-75819	12/2010	JP	N/A
2012-118130	12/2011	JP	N/A
2012-133254	12/2011	JP	N/A
2013-537721	12/2012	JP	N/A
2014-225595	12/2013	JP	N/A
2017518526	12/2016	JP	N/A
2018-511838	12/2017	JP	N/A
6305564	12/2017	JP	N/A
2019-512721	12/2018	JP	N/A
6526245	12/2018	JP	N/A
6688402	12/2019	JP	N/A
IP6824440	12/2020	JP	N/A
6858276	12/2020	JP	N/A
20000000118	12/1999	KR	N/A
20000047899	12/1999	KR	N/A
10-2067751	12/2001	KR	N/A

1020040067701	12/2003	KR	N/A
200366674	12/2003	KR	N/A
20050033986	12/2004	KR	N/A
200401354	12/2004	KR	N/A
20060016469	12/2005	KR	N/A
10-0563049	12/2005	KR	N/A
20060054742	12/2005	KR	N/A
10-2006-0070176	12/2005	KR	N/A
100666961	12/2006	KR	N/A
1020070070675	12/2006	KR	N/A
10-2007-0048300	12/2006	KR	N/A
1020070048294	12/2006	KR	N/A
10-2013-0126034	12/2012	KR	N/A
101764381	12/2016	KR	N/A
10-1847151	12/2017	KR	N/A
10-1853885	12/2017	KR	N/A
10-1868077	12/2017	KR	N/A
10-1885884	12/2017	KR	N/A
10-1894027	12/2017	KR	N/A
10-1904363	12/2017	KR	N/A
10-1958375	12/2018	KR	N/A
10-2010515	12/2018	KR	N/A
10-2063885	12/2019	KR	N/A
10-2104342	12/2019	KR	N/A
10-2109072	12/2019	KR	N/A
10-2165778	12/2019	KR	N/A
10-2262912	12/2020	KR	N/A
10-2267374	12/2020	KR	N/A
10-2306650	12/2020	KR	N/A
10-2379046	12/2021	KR	N/A
10-2400990	12/2021	KR	N/A
2513043	12/2013	RU	N/A
WO2005079129	12/2004	WO	N/A
WO2007/116117	12/2006	WO	N/A
WO2007116116	12/2006	WO	N/A
WO2008050660	12/2007	WO	N/A
WO2008/102050	12/2007	WO	N/A
WO2009/047390	12/2008	WO	N/A
WO2009065125	12/2008	WO	N/A
WO2009065125	12/2008	WO	N/A
WO2009135308	12/2008	WO	N/A
WO2010007821	12/2009	WO	N/A
WO2010080624	12/2009	WO	N/A
WO2011069084	12/2010	WO	N/A
WO2011072217	12/2010	WO	N/A
WO2011140179	12/2010	WO	N/A
WO2011150078	12/2010	WO	N/A
WO2012021573	12/2011	WO	N/A
WO2012024426	12/2011	WO	N/A
WO2013/182733	12/2012	WO	N/A

WO2014062815	12/2013	WO	N/A
WO2014149773	12/2013	WO	N/A
WO2014150036	12/2013	WO	N/A
WO2015/138609	12/2014	WO	N/A
WO2015168375	12/2014	WO	N/A
WO2016/102980	12/2015	WO	N/A
WO2016102982	12/2015	WO	N/A
WO2016127613	12/2015	WO	N/A
WO2016133852	12/2015	WO	N/A
WO2017152166	12/2016	WO	N/A
WO2018/200260	12/2017	WO	N/A
WO2018/200905	12/2017	WO	N/A
WO2020/081687	12/2019	WO	N/A
WO2020/205305	12/2019	WO	N/A
WO2022/087488	12/2021	WO	N/A

OTHER PUBLICATIONS

Mentley, David E., State of Flat-Panel Display Technology and Future Trends, Proceedings of the IEEE, Apr. 2002, vol. 90, No. 4, pp. 453-459. cited by applicant

Rohsenow, Warren M., Handbook of Heat Transfer, Third Edition, 1998, select chapters, 112 pages, McGraw-Hill. cited by applicant

The American Heritage College Dictionary, Third Edition, 1993, excerpt, 3 pages, Houghton Mifflin Company. cited by applicant

Civiq Smartscapes LLC. V Manufacturing Resources International, Inc., Petition for Inter Partes Review of U.S. Pat. No. 8,854,572 including Declaration of Greg Blonder in Support of Petition, Curriculum Vitae of Greg Blonder and Prosecution History of U.S. Pat. No. 8,854,572, Petition filed Mar. 14, 2018, 427 pages. cited by applicant

Civiq Smartscapes LLC. V Manufacturing Resources International, Inc., Defendant's Amended Answer and Counterclaims to Plaintiff's First Amended Complaint, Filed Apr. 24, 2018, 240 pages. cited by applicant

Amphenol Corporation, homepage, <https://www.amphenol.com/>, accessed Oct. 12, 2022, 2022, 3 pages. cited by applicant

W. L. Gore & Associates, Inc., Venting, <https://www.gore.com/products/categories/venting>, accessed Oct. 12, 2022, 2022, 13 pages. cited by applicant

Itsenclosures, Product Catalog, 2009, 48 pages. cited by applicant

Itsenclosures, Standard Product Data Sheet, 2011, 18 pages. cited by applicant

Sunbrite tv, All Weather Outdoor LCD Television Model 4610HD, 2008, 1 page. cited by applicant

Sunbrite tv, Introduces Two New All-Weather Outdoor Televisions InfoComm 2008, 7 pages. cited by applicant

Itsenclosures, Viewstation, 2017, 16 pages. cited by applicant

Novitsky, Driving LEDs versus CCFLs for LCD backlighting, Nov. 12, 2007, 6 pages. cited by applicant

Federman, Cooling Flat Panel Displays, 2011, 4 pages. cited by applicant

Zeeff, T.M., EMC analysis of an 18" LCD monitor, 2000, 1 page. cited by applicant

Vertigo Digital Displays, Innovation on Display FlexVu Totem Brochure, 2014, 6 pages. cited by applicant

Vertigo Digital Displays, FlexVu Totem Shelter, 2017, 2 pages. cited by applicant

Vertigo Digital Displays, All Products Catalogue, 2017, 14 pages. cited by applicant

Adnation, Turn Key Advertising Technology Solutions, May 23, 2017, 4 pages. cited by applicant

Civiq Smartscapes, FlexVue Ferro 55P/55L, Mar. 16, 2017, 4 pages. cited by applicant

Wankhede, Evaluation of Cooling Solutions for Outdoor Electronics, Sep. 17-19, 2007, 6 pages. cited by applicant

Bureau of Ships Navy Department, Guide Manual of Cooling methods for Electronic Equipment, Mar. 31, 1955, 212 pages. cited by applicant

Civiq, Invalidity Claim Charts, Appendix A—Appendix D, Jan. 24, 2018, 51 pages. cited by applicant

Civiq, Invalidity Contentions, Jan. 24, 2018, 51 pages. cited by applicant

Scott, Cooling of Electronic Equipment, Apr. 4, 1947, 119 pages. cited by applicant

Sergent, Thermal Management Handbook for Electronic Assemblies, Aug. 14, 1998, 190 pages. cited by applicant

Steinberg, Cooling Techniques for Electronic Equipment First Edition, 1980, 255 pages. cited by applicant

Steinberg, Cooling Techniques for Electronic Equipment Second Edition, 1991, 299 pages. cited by applicant

Yeh, Thermal Management of Microelectronic Equipment, Oct. 15, 2002, 148 pages. cited by applicant

Civiq, Invalidity Claim Chart, Appendix I, Mar. 22, 2018, 4 pages. cited by applicant

Civiq, Invalidity Claim Charts, Appendix F to H, Mar. 22, 2018, 18 pages. cited by applicant

Yung, Using Metal Core Printed Circuit Board as a Solution for Thermal Management article, 2007, 5 pages. cited by applicant

Civiq Smartscapes, LLC V. Manufacturing Resources International, Inc., Memorandum Opinion re claim construction, Sep. 27, 2018, 16 pages. cited by applicant

Civiq Smartscapes, LLC V. Manufacturing Resources International, Inc., Claim Construction Order, Oct. 3, 2018, 2 pages. cited by applicant

Anandan, Munismay, Progress of LED backlights for LCDs, Journal of the SID, 2008, pp. 287-310, 16/2. cited by applicant

Melford Technologies, Part 2, video online at <https://m.youtube.com/watch?v=znlyHWozwDA>, Oct. 21, 2019, 1 page. cited by applicant

Primary Examiner: Haughton; Anthony M

Attorney, Agent or Firm: Standley Law Group LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application claims the benefit of U.S. provisional patent application No. 63/226,314 filed Jul. 28, 2021, the disclosures of which are hereby incorporated by reference as if fully restated herein.

TECHNICAL FIELD

(1) Exemplary embodiments relate generally to display assemblies with vents, such as for humidity and/or pressure control.

BACKGROUND AND SUMMARY OF THE INVENTION

(2) The use of electronic displays, such as for advertising, in the out-of-home market has increased in popularity over recent years. Being located outdoors, such electronic displays are frequently exposed to harsh conditions, including, but not limited to, solar loading, extreme temperatures, precipitation, moisture, contaminants, vandalism, wildlife, and the like. To protect the electronic displays, and associated sensitive components, from such harsh conditions, it is known to place the electronic displays in ruggedized housings. Such housings may fully or partially seal the electronic

displays and other associated sensitive components.

(3) It is known to thermally manage such electronic display assemblies using ambient air and/or circulating gas. Such ambient air may pass through one or more open loop airflow pathways within the assembly, and may thermally interact with circulating gas in one or more closed loop airflow pathways within the assembly where such closed loop pathways are used to remove heat generated by the electronic display assemblies, such as at the backlight.

(4) Such electronic display assemblies, particularly those which incorporate fully or partially sealed areas, sometimes experience moisture, such as in the form of humidity, within the interiors of such units, even within the fully or partially sealed area(s), as such area(s) are generally not 100% sealed in a gas impermeable manner. For example, such areas may be partially or fully sealed against contaminants above a given size (e.g., dust or other particulate) and/or liquids, or in accordance with various standards such as IP65, but may still permit at least some gaseous transfer. Such gaseous transfer may bring moisture with it, such as in the form of humidity, potentially resulting in the formation of condensation on interior surfaces of the assemblies. This may result in undesirable fogging or obfuscation of the displayed images, or water damage to sensitive electronic equipment to name some examples.

(5) Additionally, it may be desirable to control air pressure within such electronic display assemblies for various reasons. This may include controlling bowing of electronic displays, wear and tear on seals, or forces experienced on other various sensitive items within the electronic display assemblies. For example, as electronic displays are increasing in size, the large display layers may be subject to bowing or other distortion based on air pressures encountered. In the case of liquid crystal displays, negative pressure on either side of the layer of liquid crystals may result in cell breach and/or color distortion, such as brown mura. As another example, repeated positive and negative net pressure on gaskets or other seals may result in damage overtime. Therefore, what is needed is a system and method for providing selective venting of an electronic display assembly, such as for humidity and/or pressure control.

(6) Systems and methods are disclosed herein which provide selective venting within an electronic display assembly, such as for humidity and/or pressure control. The electronic display assemblies may include one or more vents. Such vents may be installed within the assemblies in a manner which connects the vents between certain fully or partially sealed areas (hereinafter also the “closed loop areas”) and an ambient environment. The vents may be configured to permit circulating gas within the closed loop areas with which the respective vent is connected to only enter, or only exit, the closed loop areas. This may be by design, or may be selectively controlled to operate in such a manner. In particular, as electronic display assemblies become better sealed, the need for ventilation may be required to prevent large pressure fluctuations or levels which may otherwise cause mechanical damage.

(7) The vents may be positioned relative to one or more fan assemblies or other airflow features such that they are located within one or more areas normally experiencing net positive, or relatively high, air pressure of circulating gas within such closed loop areas, or within one or more areas normally experiencing net negative, or relatively low, air pressure of the circulating gas. In exemplary embodiments, the vents are placed within such high/positive air pressure areas and may be configured to vent circulating gas within the closed loop areas to the ambient environment, such as when experiencing certain net positive pressures and/or pressures above a certain threshold. In this manner, humidity or other moisture within the assemblies may be vented with the expelled circulating gas to reduce or eliminate such humidity or other moisture within the assemblies.

Alternatively, or additionally, the vents placed within such low/negative air pressure areas may be configured to vent ambient air 32 from the ambient environment into the closed loop areas, such as when experiencing certain net negative pressures and/or pressures below a certain threshold. In this manner, air pressure within the closed loop areas may be raised to, or maintained at, net positive pressure and/or above a certain threshold or relative to other portions of the unit, such as to keep

the electronic display layer in compression, to keep humidity and/or other particulate out of the closed loop areas, combinations thereof, or the like. Particularly in the case of liquid crystal displays, compression on the electronic display layer may help to prevent cell breach, brown mura, or other visual distortions. As another example, without limitation, such positive or higher pressures may assist with improving optical performance, such as by preventing distortion by bowing, for example without limitation, of any type or kind of electronic display layer. As yet another example, such positive or higher pressures may assist with driving humidity and other contaminants out of the units.

(8) Opening and closing of the vents may be provided automatically by design of the vents, such as but not limited to, by way of one or more mechanical features of the vents which are designed to operate when experiencing particular absolute or relative pressures. Alternatively, or additionally, opening and closing of the vents may be controlled electronically by one or more controllers. Such opening and closing, by design or electronic operation, may be performed in response to various operating conditions, such as but not limited to, measurements from one or more humidity sensors, temperature sensors, pressure sensors, fan speed sensors, relative pressures experienced at the vents, absolute pressures experienced at the vents, combinations thereof, or the like. In this manner, the vents may be designed and/or controlled to reduce or eliminate condensation, control humidity, and/or maintain positive air pressure within the closed loop areas.

(9) Alternatively, or additionally, the vents may be configured to naturally permit a certain amount of flow from a relatively high-pressure area to a relatively low-pressure area. For example, without limitation, the vents may comprise one or more openings and/or fluid passageways configured to permit various volumetric flow rates at various relative pressures.

(10) Further features and advantages of the systems and methods disclosed herein, as well as the structure and operation of various aspects of the present disclosure, are described in detail below with reference to the accompanying figures.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) In addition to the features mentioned above, other aspects of the present invention will be readily apparent from the following descriptions of the drawings and exemplary embodiments, wherein like reference numerals across the several views refer to identical or equivalent features, and wherein:

(2) FIG. 1 is a perspective view of an exemplary electronic display assembly in accordance with the present invention also illustrating section line A-A;

(3) FIG. 2 is a simplified sectional view of an exemplary embodiment of the electronic display assembly of FIG. 1 taken along section line A-A;

(4) FIG. 3 is a simplified sectional view of another exemplary embodiment of the electronic display assembly of FIG. 1 taken along section line A-A;

(5) FIG. 4 is a simplified sectional view of another exemplary embodiment of the electronic display assembly of FIG. 1 taken along section line A-A;

(6) FIG. 5 is a simplified electrical schematic for use with the electronic display assembly of FIG. 1;

(7) FIG. 6 is a flow chart with exemplary logic for operating the electronic display assembly of FIG. 5;

(8) FIG. 7 is a flow chart with other exemplary logic for operating the electronic display assembly of FIG. 5; and

(9) FIG. 8 is a flow chart with other exemplary logic for operating the electronic display assembly of FIG. 5.

DETAILED DESCRIPTION OF EXEMPLARY EMBODIMENT(S)

(10) Various embodiments of the present invention will now be described in detail with reference to the accompanying drawings. In the following description, specific details such as detailed configuration and components are merely provided to assist the overall understanding of these embodiments of the present invention. Therefore, it should be apparent to those skilled in the art that various changes and modifications of the embodiments described herein can be made without departing from the scope and spirit of the present invention. In addition, descriptions of well-known functions and constructions are omitted for clarity and conciseness.

(11) Embodiments of the invention are described herein with reference to illustrations of idealized embodiments (and intermediate structures) of the invention. As such, variations from the shapes of the illustrations as a result, for example, of manufacturing techniques and/or tolerances, are to be expected. Thus, embodiments of the invention should not be construed as limited to the particular shapes of regions illustrated herein but are to include deviations in shapes that result, for example, from manufacturing.

(12) FIG. 1 is a perspective view of an exemplary electronic display assembly (hereinafter also a “unit”) **10** in accordance with the present invention. The unit **10** may include a structural framework **12**. The structural framework **12** may be configured for mounting to a ground surface, such as a sidewalk or street, mounting to a wall or other surface, incorporation into street furniture (e.g., phone booths, bus shelters, benches, railings, combinations thereof, or the like), combinations thereof, or the like. The structural framework **12** may comprise one or more members, panels, cladding, combinations thereof, or the like and may be configured to form a complete or partial housing. The structural framework **12** may form a full or partial housing for some or all components of the assembly **10**.

(13) The units **10** may comprise one or more electronic display subassemblies **14**. Some or all of the electronic display subassemblies **14** may be attached to the structural framework **12** in a moveable manner, though such is not required. For example, the electronic display subassemblies **14** may be attached to the structural framework **12** in a hinged manner to permit selective movement between a closed position whereby certain parts of the units **10** are fully or partially sealed, and an open position whereby certain parts of the interior of the unit **10** are exposed for access. Full or partial sealing may be provided in accordance with one or more standards, such as but not limited to, ingress protection (IP) ratings provided by the International Electrotechnical Commission (e.g., available at <https://www.iec.ch/ip-ratings>), such as but not limited to, IP 63, 64, 65, 66, 67, and/or 68 by way of non-limiting example.

(14) One or more intakes and exhausts **16** may be provided at the units **10** for ingesting and exhausting ambient air **32**.

(15) FIG. 2 through FIG. 4 illustrate various exemplary embodiments of airflow pathways within the units **10**. FIG. 2 illustrates an exemplary unit **10a** with a single electronic display subassembly **14**. FIGS. 3 and 4 illustrate exemplary units **10b**, **10c** with two electronic display subassemblies **14a**, **14b** placed in a back-to-back arrangement. Any number of electronic display subassemblies **14** may be utilized in any arrangement with the structural framework **12**. Similar or the same components used in conjunction with units **10** having multiple electronic display subassemblies **14** may use the same numbering with the addition of an “a”, “b”, “c”, and/or “1”, “2”, etc. (e.g., **14** to **14a**, **14b**, **30a** to **30a1**, **30a2**).

(16) Each electronic display subassembly **14** may comprise an electronic display layer **20**. In exemplary embodiments, the electronic display layer **20** of each of the electronic display subassemblies **14** may comprise an LCD type display with a layer of liquid crystals, and each of the illumination devices **22** may comprise a direct backlight or edge lighting. However, other types of electronic display technologies may be utilized for such electronic display subassemblies **14** including, but not limited to, plasma displays, LED displays, OLED displays, rear projection, cathode ray tube, combinations thereof, or the like.

(17) Each electronic display subassembly **14** may comprise an illumination device **22**. In exemplary embodiments, the illumination device **22** may comprise a number of lighting elements, such as LEDs, provided at a substrate. In exemplary embodiments, the illumination device **22** may be provided rearward of the electronic display layer **20** to serve as a direct backlight. In other exemplary embodiments, the illumination device **22** may comprise one or more diffusive and/or transmissive layers and the substrate and/or lighting elements may be positioned about the edge of the electronic display layer **20** to provide edge lighting to the same. In certain exemplary embodiments, such as where the electronic display layer **20** is an LED, OLED, or other type of self-illuminating display, the illumination device **22** may not be required.

(18) The electronic display layer **20** and/or illumination device **22** may be positioned rearward of a cover **18**. The cover **18** may comprise one or more layers of a transparent or translucent material. In exemplary embodiments, each cover **18** may comprise two layers bonded with an optically clear adhesive. One or more polarizers, anti-reflective materials, combinations thereof, or the like may be disposed on some or all of the cover **18**. The cover **18** may form part of the electronic display subassembly **14** or may be separate therefrom. The cover **18** and the structural framework **12** may together substantially enclose the units **10**, such as with intakes/exhausts **16** exempted. The cover **18** may be configured to move with the electronic display subassembly **14**, may be configured for independent movement, and/or may be fixed to the structural framework **12**.

(19) A single or multiple such electronic display subassemblies **14** may be provided at a single unit **10**, such as but not limited to, in a back-to-back arrangement. The electronic display subassemblies **14** may be of the same or different type and may comprise the same or different components. The electronic display subassemblies **14** may be provided in any arrangement such as portrait or landscape.

(20) The intakes and/or exhausts **16** may be fluidly connected to one or more open loop airflow pathways **34** within the units **10**. A respective one of the open loop airflow pathways **34a**, **34b** may extend through a respective one of the electronic display subassemblies **14a**, **14b** in exemplary embodiments such that an open loop airflow pathway **34** is provided for each one of the electronic display subassemblies **14**, which may be entirely separate or separated for a distance and rejoined. For example, without limitation, the open loop airflow pathways **34** may extend behind and along at least a portion of the illumination devices **22** for the electronic display layers **20** and/or behind and along at least a portion of the electronic display layers **20** itself, such as in the case of LED, OLED, or other self-illuminating display. The open loop airflow pathways **34** may comprise one or more corrugated layers in exemplary embodiments. However, any type, arrangement, and/or number of airflow pathway(s) may be utilized. One or more filters may be provided at the intakes and/or exhausts **16** and/or along the one or more open loop airflow pathways **34** within the units **10**, though such is not necessarily required.

(21) One or more closed loop airflow pathways may be provided within the units **10**. In exemplary embodiments, such closed loop airflow pathways may comprise at least a front chamber **26**, which may extend between the cover **18** and the electronic display layer **20**, and a rear chamber **28**, which may extend behind the electronic display subassembly **14**, or at least the electronic display layer **20**, but within the structural framework **12**. Where multiple electronic display subassemblies **14a**, **14b** are utilized, the rear chamber **28** may be common to each of the electronic display subassemblies **14a**, **14b**. A heat exchanger **42** may be located within the rear chamber **28**, though such is not required. The heat exchanger **42** may comprise a multilayer heat exchanger configured to accommodate a common flow **30c** of the circulating gas through at least some of the layers as well as one or more flows **32c** of ambient air through at least some other ones of the layers **34c**. However, any type, arrangement, and/or number of airflow pathway(s) may be utilized. One or more filters may be provided at or along the one or more closed loop airflow pathways within the units **10**, though such is not necessarily required. Filters, barriers, walls, gaskets, combinations thereof, or the like may provide separation between open and closed loop airflow pathways.

(22) An illumination device chamber **27** may extend between each of the electronic display layers **20a**, **20b** and the respective illumination devices **22a**, **22b**. A flow of circulating gas **30c** within the rear chamber **28** may be separated such that a first portion **30a** flows through the front chamber **26** and a second portion **30b** flows through the illumination device chamber **27**. The flows **30a**, **30b** may be recombined, such as in the rear chamber **28**.

(23) One or more open loop fans **40** may be provided. The same or different open loop fans **40** may be associated with each of the open loop airflow pathways **34**. The open loop fans **40** may be configured to ingest ambient air **32** into the units **10**, exhaust ambient air **32** from the assembly **10**, and/or move ingested ambient air **32** through the one or more open loop airflow pathways **34** when activated. One or more closed loop fans **38** may be provided. The same or different closed loop fans **38** may be associated with each of the closed loop airflow pathways. The closed loop fans **20** may be configured to move circulating gas through said one or more closed loop airflow pathways when activated. The fans **38**, **40** may comprise axial fans, centrifugal fans, combinations thereof, or the like. Any number or type of fans **38**, **40** may be used at any location in the units **10**, and may be provided in banks or sets. The open loop airflow pathways **34** may be separate from the closed loop airflow pathways, though a complete (e.g., gas impermeable) separation is not necessarily required.

(24) Examples of such airflow configurations and/or operations may include, for example without limitation, those shown and/or described in one or more of U.S. Pat. No. 8,854,595 issued Oct. 7, 2014, U.S. Pat. No. 8,767,165 issued Jul. 1, 2014, U.S. Pat. No. 8,654,302 issued Feb. 18, 2014, U.S. Pat. No. 8,351,014 issued Jan. 8, 2013, U.S. Pat. No. 10,660,245 issued May 19, 2020, U.S. Pat. No. 10,194,564 issued Jan. 29, 2019, and/or U.S. Pat. No. 10,398,066 issued Aug. 27, 2019, the disclosures of each of which are hereby incorporated by reference in their entireties. The structure and/or mechanical operation of the units **10**, and the various components thereof, and/or airflow configurations may include those shown and/or described in U.S. Pat. No. 10,485,113 issued Nov. 19, 2019 (the "133 Patent"), the disclosures of which are hereby incorporated by reference in their entirety. Movement and/or structure for facilitating movement of the electronic display subassemblies **14** may be as shown and/or described in at least the '133 Patent.

(25) The unit **10** may comprise one or more controllers **46**. The controller(s) **46** may comprise one or more programmable logic devices. The unit **10** may comprise one or more sensors **44**. The sensors **44** may comprise, for example without limitation, temperature sensors, fan speed sensors, airflow sensors, humidity sensors, relative humidity sensors, air pressure sensors, differential pressure sensors, location sensors, moisture sensors, combinations thereof, or the like. Any type, kind, or number of sensors **44** may be utilized at any number of locations within the units **10**. The sensor(s) **44** may be in electronic communication with the controller(s) **46**.

(26) Each of the units **10** may comprise one or more vents **36**. The vents **36** may be configured for one way operation, such as but not limited to, to only permit circulating gas to vent from a fluidly connected area of the closed loop airflow pathway(s) to the ambient environment, or only permit ambient air **32** from the ambient environment to vent into the fluidly connected area of the closed loop airflow pathway(s). However, two-way vents (ingestion and exhaustion) may alternatively, or additionally, be utilized. Opening and closing of the vents **36** may be configured to occur under certain conditions, such as but not limited to, at certain air pressures, by design and/or may be electronically controlled. For example, without limitation, the vents **36** may be configured to automatically open or close to permit ingestion of ambient air into the closed loop areas and/or exhaustion of circulating gas from the closed loop areas mechanically when experiencing certain conditions, such as but not limited to, certain relative pressure differences between ambient air and circulating gas and/or certain absolute pressures of ambient air and/or circulating gas, based on physical design and/or structure of the vent **36**. Alternatively, or additionally, the vents **36** may be configured to be operated mechanically based on electronic command, such as but not limited to, by one or more motors.

(27) In exemplary embodiments, each of the vents **36** may be connected to one or more areas of

one or more closed loop airflow pathway(s) within the unit **10**, and the ambient environment directly or to one of more of the open loop airflow pathways **34**. Such connections may be direct, such as where the vent **36** extends between such environments, or indirect, such as by way of tubing or other fluid passageways. The vents **36** may connect to the ambient environment directly and/or by way of the one or more of the open loop airflow pathways **34**.

(28) Some or all of the vents **36** may be passive vents. The vents **36** may be configured to naturally permit flow of air from relatively high-pressure areas to relatively low-pressure areas. Some or all of the vents **36** may comprise fluid passageways such that the vents **36** are capable of selectively releasing circulating gas and/or ingesting ambient air. The size and/or shape of openings in and/or fluid passageways within the vents **36** may be configured to permit various volumetric flow rates at various relative pressures. The size and/or shape of openings in and/or fluid passageways within the vents **36** may be configured to naturally resist particulate and/or water ingestion. The vents **36** may optionally include one or more filters, membranes, or the like configured to resist or prevent particulate and/or water ingestion and/or permit one way flow of air.

(29) Examples of such vents include, for example without limitation, those available from W. L. Gore & Associates, Inc. of Newark, DE (<https://www.gore.com/products/categories/venting>) and/or Amphenol Corp., of Wallingford, Ct. (<https://www.amphenol.com/>), including but not limited to the VEN-PS1NBK-08001 and/or VEN-PS1NBK-08002 products from Amphenol. These are merely exemplary and are not intended to be limiting.

(30) In exemplary embodiments, a first one of the vents **36a** may be placed on a first side of one of the closed loop fans **38** which may be associated with relatively high and/or net positive pressures when the fan **38** is operated. A second one of the vents **36b** may be placed on a second side of one of the same or different ones of the closed loop fans **38**, such as associated with relatively low and/or net negative pressures when the fan **38** is operated. In other exemplary embodiments, a single or multiple vents **36** may be placed exclusively on one side of the closed loop fans **38**. Any number of vents **36** in any number of locations may be utilized. The vents **36** may be configured to ingest ambient air into, and/or exhaust circulating gas from, the associated closed loop areas. In exemplary embodiments, without limitation, one or more passive type vents **63** is placed in close proximity to a negative pressure side of the closed loop fans **38**. In other exemplary embodiments, without limitation, one or more passive type vents **36** is placed in close proximity to a positive pressure side of the closed loop fans **38**.

(31) In exemplary embodiments, one or more of the vents **36** may be positioned on a side of the closed loop fans **38** associated with negative, or relatively low pressure primarily for ingesting ambient air into the associated closed loop area. In this manner, pressures within the closed loop airflow pathways, including the portions of the flow **30a** and **30b** within the front chamber **26** and the illumination devices chamber **27** may be raised to, and/or maintained at, positive pressures to place or keep the electronic display layer **20** in compression. This may prevent cell breach and/or color distortion.

(32) Alternatively, or additionally, one or more of the vents **36** may be positioned on a side of the closed loop fans **38** associated with positive, or relatively high pressure primarily for exhausting circulating gas in the associated closed loop area to the ambient environment. In this manner, circulating gas may be periodically driven out of the closed loop areas. This may reduce or eliminate moisture and other contaminants. This may also maintain the electronic display layer **20** in tension, such as to keep it taught.

(33) In exemplary embodiments, placement of, or at least selective opening of, one or more vents **36** on the side of the closed loop fans **38** associated with relatively high and/or net positive pressures when the fan **38** is operated may result in increasing the average pressure of the circulating gas in the associated closed loop area as compared to without such one or more vents **36** and/or keeping such one or more vents **36** closed. In exemplary embodiments, placement of, or at least selective opening of, one or more vents **36** on the side of the closed loop fans **38** associated

with negative, or relatively low pressure when the fan **38** is operated may result in decreasing the average pressure of the circulating gas in the associated closed loop area as compared to without such one or more vents **36** and/or keeping such one or more vents **36** closed. In this manner, placement and/or operation of the vent(s) **36** may be controlled to control or influence pressures of circulating gas in the closed loop airflow pathway.

(34) Alternatively, or additionally, the vent(s) **36** may be fluidly connected to such areas (e.g., those on the positive or negative side of the closed loop fans **38**). Such fluid connection may be made by way of tubes, for example without limitation. This may permit the vent(s) **36** to be placed in more convenient locations and fluidly connected to the desired region, such as to accomplish the same, or substantially the same, effect while permitting greater design variation and/or where desired placement is impractical or impossible.

(35) FIG. 5 is a simplified electrical schematic for use with the electronic display assembly **10**. The controller **46** may be in electronic communication with some or all components of the assembly **10**. The controller **46** may be in electronic communication with each of the electronic display subassemblies **14**. The controller **46** may be in electronic communication with each of the closed loop fans **38**. The controller **46** may be in electronic communication with each of the open loop fans **40**. The controller **46** may be in electronic communication with each of the sensors **44**. The controller **46** may be in electronic communication with each of the vents **36**. The controller **46** may be configured to receive data from such components and/or send commands to such components by wired or wireless connection. For example, without limitation, the controller **46** may be configured to open or close the vents **36**, control speeds of the fans **38**, **40**, content displayed at the electronic display subassemblies **14**, take measurements from the sensors **44**, combinations thereof, or the like. Such electronic communication is not required between the controller **46** and the aforementioned components. For example, without limitation, the vents **36** may be configured to operate based on experienced conditions (e.g., pressures) and without the need for electronic control.

(36) The controller **46** may be in electronic communication with a network communication device **48**. The network communication device **48** may be configured to receive data from the controller **46** for transmission over one or more networks **50** to one or more electronic devices **52**, such as to permit remote monitoring of the units **10**. The network communication device **48** may be configured to receive commands from the one or more electronic devices **52** for passing to the controller **46**, such as to permit remote control over the units **10**. The networks **50** may comprise cellular networks, wireless networks, wired networks, combinations thereof, or the like. The electronic devices **52** may comprise personal computers, smartphones, tablets, network operation centers, combinations thereof, or the like.

(37) FIG. 6 is a flow chart with exemplary logic for operating the electronic display assembly **10**. Humidity may be measured by way of at least one of the sensors **44**, which may comprise a humidity sensor and/or relative humidity sensor (e.g., psychrometer). The measurement(s) may be reported to, or determined at, the controller **46** from data received from the at least one of the sensors **44**. If the humidity is above a threshold, the controller **46** may be configured to open at least one of the vents **36**. In exemplary embodiments, the controller **46** may be configured to open one or more of the vents **36** on a positive or relatively high-pressure side of one or more of the closed loop fans **38**. The controller **46** may, alternatively or additionally, be configured to close one or more of the vents **36** on a negative or relatively low-pressure side of one or more of the closed loop fans **38**. In other exemplary embodiments, the controller may be configured to open one or more of the vents **36** configured for one-way expulsion of circulating gas and/or close one or more of the vents configured for one-way ingestion of ambient air. Such operations may occur simultaneously or in sequence. This may permit expulsion of moisture from the units **10** with the expelled circulating gas. The threshold may be any amount. In exemplary embodiments, the threshold is set to reflect a point in which condensation is likely to form within the unit **10**, with or

without a margin of safety.

(38) FIG. 7 is a flow chart with other exemplary logic for operating the electronic display assembly 10. Relative humidity may be measured by way of at least one of the sensors 44. Air temperature may be measured by way of the same or different one(s) of the sensors 44. These measurements may be reported to, or determined at, the controller 46 from data received from the sensor(s) 44. Alternatively, or additionally, such measurements may be taken from one or more internet-based sources, such as by way of the network communication device 48. The controller 46 may be configured to determine a dewpoint for the measured air, which may be air within the units 10 or ambient, and calculate a dewpoint spread relative to the air temperature measurements, which may be ambient air within the units 10 or ambient air outside the units 10. In exemplary embodiments, dewpoint is calculated for circulating gas within the unit 10 and dewpoint spread is measured relative to ambient air outside of, or within, the units 10.

(39) Where dewpoint spread reaches one or more thresholds, such as but not limited to within 5° C., the controller 46 may be configured to open one or more of the vents 36 on a positive or relatively high-pressure side of one or more of the closed loop fans 38. The controller 46 may, alternatively or additionally, be configured to close one or more of the vents 36 on a negative or relatively low-pressure side of one or more of the closed loop fans 38. Alternatively, or additionally, the controller 46 may be configured to operate such vents 36 in a manner which only permits circulating gas to be expelled from the unit 10 to ambient. Such operations may occur simultaneously or in sequence. In this manner, moisture may be expelled from the units 10 with the expelled circulating gas. The dewpoint spread threshold may be any amount.

(40) FIG. 8 is a flow chart with other exemplary logic for operating the electronic display assembly 10. Air pressure readings of circulating gas, such as but not limited to, the portion 30a of circulating gas within the front chamber 26 and/or the portion 30b of the circulating gas within the illumination devices chamber 27 may be measured by way of one or more of the sensors 44. The measurements may be reported to, or determined at, the controller 46 from data received from the sensors 44. The controller 46 may be configured to determine if the pressures differential between the first and second portions 30a, 30b is within certain operating conditions. Such operating conditions may be, for example without limitation, both positive. Alternatively, or additionally, such operating conditions may be, without limitation, higher within the front chamber 26 relative within the illumination device chamber 27. These operating conditions may be configured to reduce or eliminate bowing of the electronic display layer 20, and/or maintain compressive forces on the electronic display layer 20. Where such pressure falls outside of desired conditions, the vents 36 may be selectively operated to control the same. For example, without limitation, one or more of the vents 36 associated with negative or relatively low pressure may be opened and/or configured for ingestion of ambient air so as to raise pressures within the closed loop airflow pathway.

(41) While electronic control of the vents 36 is contemplated in at least certain embodiments, such as but not limited to, those shown and/or described with regard to FIGS. 5-8, the vents 36 may be configured to automatically operate by mechanical design in response to various conditions, such as pressures or relative pressures, experienced and thus such electronic control may not be required. The vents 36 may be configured, for example without limitation, to automatically operate mechanically by engineered design and without physical control, in response to the conditions shown and/or described herein and/or achieve the results (e.g., humidity reduction, pressure miniatous) shown and/or described herein.

(42) Any embodiment of the present invention may include any of the features of the other embodiments of the present invention. The exemplary embodiments herein disclosed are not intended to be exhaustive or to unnecessarily limit the scope of the invention. The exemplary embodiments were chosen and described in order to explain the principles of the present invention so that others skilled in the art may practice the invention. Having shown and described exemplary

embodiments of the present invention, those skilled in the art will realize that many variations and modifications may be made to the described invention. Many of those variations and modifications will provide the same result and fall within the spirit of the claimed invention. It is the intention, therefore, to limit the invention only as indicated by the scope of the claims.

(43) Certain operations described herein may be performed by one or more electronic devices. Each electronic device may comprise one or more processors, electronic storage devices, executable software instructions, and the like configured to perform the operations described herein. The electronic devices may be general purpose computers or specialized computing device. The electronic devices may comprise personal computers, smartphone, tablets, databases, servers, or the like. The electronic connections and transmissions described herein may be accomplished by wired or wireless means. The computerized hardware, software, components, systems, steps, methods, and/or processes described herein may serve to improve the speed of the computerized hardware, software, systems, steps, methods, and/or processes described herein.

Claims

1. An electronic display assembly with ventilation comprising: a structural framework; an electronic display subassembly attached to the structural framework and comprising a cover layer forming a forward surface of said electronic display subassembly and an electronic display layer located behind the cover layer; an enclosure for at least the electronic display layer, said enclosure defined, at least in part, by the structural framework and the cover layer; a closed loop airflow pathway extending within the enclosure; and one or more vents fluidly interposed between the closed loop airflow pathway and an ambient environment, wherein said one or more vents are movable between an open state and a closed state.
2. The electronic display assembly of claim 1 wherein: said one or more vents comprise openings and fluid passageways configured to permit gaseous flows at certain volumetric flow rates at certain pressures to the exclusion of gaseous flows at other volumetric flow rates and other pressures.
3. The electronic display assembly of claim 2 wherein: said one or more vents comprise one or more membranes configured to resist ingestion of particulate and water.
4. The electronic display assembly of claim 2 further comprising: at least one fan located along the closed loop airflow pathway, wherein the said one or more vents are located on a negative pressure side of the at least one fan.
5. The electronic display assembly of claim 1 further comprising: a controller in electronic communication with the one or more vents and configured to selectively and individually operate said one or more vents between the open state and the closed state.
6. The electronic display assembly of claim 5 further comprising: at least one fan located along the closed loop airflow pathway; a first one of the one or more vents located on a first side of said at least one fan associated with a positive pressure; and a second one of the one or more vents located on a second side of said at least one fan associated with a negative pressure.
7. The electronic display assembly of claim 5 further comprising: one or more sensors in electronic communication with said controller, wherein said controller is configured to operate said one or more vents between said open state and said closed state at least in part based on data received from said one or more sensors.
8. The electronic display assembly of claim 7 wherein: said one or more sensors comprise a differential pressure sensor fluidly connected to said closed loop airflow pathway and the ambient environment; and said controller is configured to operate the first one of said vents in said closed state and said second one of said vents in said open state after determining, based on data received from said differential pressure sensor, that a measured pressure difference is outside a target range.
9. The electronic display assembly of claim 7 wherein: said one or more sensors comprise a

humidity sensor; and said controller is configured to operate the first one of said vents in said open state and said second one of said vents in said closed state after determining, based on data received from said differential pressure sensor, that a measured humidity is above a predetermined threshold.

10. The electronic display assembly of claim 7 wherein: said one or more sensors comprise a temperature sensor located at the closed loop airflow pathway; and said controller is configured to: measure a temperature of circulating gas within the closed loop airflow pathway by way of the temperature sensor; determine a dewpoint of the ambient environment; determine a dewpoint spread between the temperature and the dewpoint; and where the dewpoint spread is below a predetermined threshold: operate the first one of said vents in said open state; and operate the second one of said vents in said closed state.

11. The electronic display assembly of claim 1 wherein: a first portion of said closed loop airflow pathway extends between said cover and said electronic display layer, a second portion of said closed loop airflow pathway extends rearward of said electronic display layer; said electronic display layer comprises liquid crystals; and said electronic display subassembly comprises a backlight located rearward of the electronic display layer.

12. The electronic display assembly of claim 11 further comprising: a second electronic display subassembly attached to said structural framework, wherein the electronic display subassembly and the second electronic display subassembly are movably attached to opposing sides of said structural framework.

13. The electronic display assembly of claim 1 wherein: each of the one or more vents comprise one-way vents configured to permit exhaust of gas from the electronic display assembly.

14. An electronic display assembly with controllable ventilation, said electronic display assembly comprising: a structural framework; an electronic display subassembly attached to said structural framework and comprising a cover and an electronic display layer; a closed loop airflow pathway for circulating gas extending within one or more of the structural framework and the electronic display subassembly; a fan located along the closed loop airflow pathway; a first controllable vent located on a first side of said fan and fluidly interposed between the closed loop airflow pathway and an ambient environment; a second controllable vent located on a second side of said fan fluidly interposed between the closed loop airflow pathway and the ambient environment, wherein the first and second controllable vents comprise one-way vents configured to permit exhaust of the circulating gas from the closed loop airflow pathway to the ambient environment; one or more sensors, at least one of which is located along the closed loop airflow pathway, wherein said one or more sensors are selected from the group consisting of: temperature sensors, humidity sensors, relatively humidity sensors, and pressure sensors; and a controller in electronic communication with the first and second controllable vents and the one or more sensors, wherein said controller is configured to separately operate said first and second controllable vents between an open state whereby the circulating gas is permitted to exit the closed loop airflow pathway to the ambient environment and a closed state whereby the circulating gas is prevented from exiting the closed loop airflow pathway to the ambient environment based on readings from said one or more sensors.

15. The electronic display assembly of claim 14 further comprising: an open loop airflow pathway for ambient air extending within one or more of the structural framework and the electronic display subassembly, wherein said first and second controllable valves are fluidly connected to the ambient environments by way of the open loop airflow pathway, and wherein at least one of said one or more sensors is located at the open loop airflow pathway.

16. A method for ventilating an electronic display assembly in a controllable fashion, said method comprising: displaying images at an electronic display layer of said electronic display assembly; operating a fan located along a closed loop airflow pathway of the electronic display assembly; receiving data, at a controller, from a sensor located along the closed loop airflow pathway; and operably controlling, by way of the controller, a first vent located at a first side of said fan and a

second vent located at a second side of the fan between an open state and a closed state, wherein each of said first and second vents are fluidly connected to said closed loop airflow pathway and an ambient environment.

17. The method of claim 16: wherein said sensor comprises a differential pressure sensor fluidly connected to said closed loop airflow pathway and the ambient environment; and further comprising: determining, at the controller by way of data received from the differential pressure sensor, that a measured differential pressure is outside a target range; and operating, by way of said controller, the first controllable vent in said closed state and said second controllable vent in said open state.

18. The method of claim 16: wherein said sensor comprises a humidity sensor; and further comprising: determining, at the controller by way of data received from the humidity sensor, that a measured humidity is above a predetermined threshold; and operating, by way of said controller, the first controllable vent in said open state and said second controllable vent in said closed state.

19. The method of claim 16: wherein said sensor comprises a temperature sensor; and further comprising: determining, at the controller, a dewpoint for the ambient environment; determining, at the controller by way of data received from the temperature sensor, a dewpoint spread between the dewpoint and a measured temperature; determining, at the controller, that the dewpoint spread is less than a predetermined threshold; operating the first controllable vent in said open state; and operating the second controllable vent in said closed state.

20. The method of claim 19 wherein: said dewpoint is determined based on data retrieved from one or more internet-based local weather information sources by way of one or more network communication devices in electronic communication with said controller.
