

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12385567
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Ou; Iwa et al.

Sliding component

Abstract

A sliding component having an annular shape is disposed in a place where relative rotation is performed in a rotary machine, in which a plurality of dynamic pressure generating mechanisms are provided in a sliding surface of the sliding component, each including a deep groove portion that communicates with an outer diameter side, and at least one shallow groove portion that communicates with the deep groove portion and extends in a circumferential direction, and the deep groove portion is provided with a trap portion that suppresses a sealed liquid in the deep groove portion from leaking to a leakage side.

Inventors: Ou; Iwa (Tokyo, JP), Imura; Tadatsugu (Tokyo, JP), Suzuki; Hiroshi (Tokyo, JP), Tokunaga; Yuichiro (Tokyo, JP)

Applicant: Eagle Industry Co., Ltd. (Tokyo, JP)

Family ID: 71948294

Assignee: EAGLE INDUSTRY CO., LTD. (Tokyo, JP)

Appl. No.: 18/762527

Filed: July 02, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20250003496 A1	Jan. 02, 2025

Foreign Application Priority Data

JP	2019-017874	Feb. 04, 2019
----	-------------	---------------

Related U.S. Application Data

Publication Classification

Int. Cl.: F16J15/34 (20060101); F16J15/3256 (20160101)

U.S. Cl.:

CPC F16J15/3412 (20130101); F16J15/3256 (20130101);

Field of Classification Search

CPC: F16J (15/3412); F16J (15/3256)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3804424	12/1973	Gerdner	N/A	F16J 15/34
4889348	12/1988	Amundson et al.	N/A	F16J 15/34
5092612	12/1991	Victor et al.	N/A	F16J 15/34
5180173	12/1992	Kimura et al.	N/A	F16J 15/34
5441283	12/1994	Pecht et al.	N/A	F16J 15/34
5492341	12/1995	Pecht et al.	N/A	F16J 15/34
6189896	12/2000	Dickey	N/A	F16C 17/045
7044470	12/2005	Zheng	N/A	F16J 15/342
9039013	12/2014	Artiles	N/A	F16J 15/3412
9151390	12/2014	Hosoe et al.	N/A	N/A
9353867	12/2015	Itadani et al.	N/A	F16J 15/3448
9371912	12/2015	Hosoe et al.	N/A	F16J 15/34
9512923	12/2015	Inoue et al.	N/A	F16J 16/34
9677670	12/2016	Itadani et al.	N/A	F16J 15/3412
9765892	12/2016	Itadani et al.	N/A	F16J 15/34
9772037	12/2016	Itadani et al.	N/A	F16J 15/3412
9822882	12/2016	Kamemura	N/A	F16J 15/3204
9829109	12/2016	Itadani et al.	N/A	F16J 15/40
9841106	12/2016	Itadani et al.	N/A	F16J 15/34
9845886	12/2016	Itadani	N/A	N/A
9850953	12/2016	Tokunaga	N/A	F16J 33/741
10054230	12/2017	Katori	N/A	F16J 15/34
10337560	12/2018	Tokunaga et al.	N/A	F16J 15/40
10473220	12/2018	Tokunaga et al.	N/A	F16J 15/40
10704417	12/2019	Tokunaga et al.	N/A	F01D 25/16
11603934	12/2022	Imura	N/A	F16J 15/34
12049962	12/2023	Ou	N/A	F16J 15/3256
2002/0079648	12/2001	Uth	N/A	F16J 15/34
2010/0038862	12/2009	Young	N/A	B23K 26/352

2012/0018957	12/2011	Watanbe	N/A	F16J 15/34
2012/0280458	12/2011	Artiles et al.	N/A	F16J 15/44
2014/0197600	12/2013	Hosoe et al.	N/A	F16J 16/40
2014/0217676	12/2013	Hosoe et al.	N/A	F16J 15/34
2015/0097341	12/2014	Inoue et al.	N/A	F16J 15/3424
2015/0115537	12/2014	Tokunaga	N/A	F16J 15/34
2015/0123350	12/2014	Itadani et al.	N/A	F16J 15/3412
2015/0184752	12/2014	Itadani	N/A	F16J 15/3412
2015/0226334	12/2014	Itadani	N/A	F16J 15/3412
2015/0260292	12/2014	Inoue	N/A	F16J 15/342
2016/0033045	12/2015	Itadani et al.	N/A	F16J 15/3412
2017/0350407	12/2016	Yamamoto et al.	N/A	F04D 29/046
2018/0073394	12/2017	Tokunaga et al.	N/A	F16D 25/18
2018/0128377	12/2017	Tokunaga et al.	N/A	F16J 15/342
2018/0135699	12/2017	Tokunaga et al.	N/A	F16C 33/80
2018/0172162	12/2017	Tokunaga et al.	N/A	F16J 15/34
2018/0299015	12/2017	Itadani	N/A	F16J 15/3448
2019/0285115	12/2018	Negishi et al.	N/A	F16C 17/04
2019/0301522	12/2018	Negishi et al.	N/A	F16C 17/026
2023/0167905	12/2022	Negishi	N/A	F16J 15/3416

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
677266	12/1986	CH	F16J 15/34
1100503	12/1994	CN	F16J 15/16
1364987	12/2001	CN	F16J 15/40
101469771	12/2008	CN	F16J 15/40
102483162	12/2011	CN	F16J 15/18
103104707	12/2012	CN	F16J 15/16
103122998	12/2012	CN	F16J 15/16
103216626	12/2012	CN	F16J 15/40
103732958	12/2013	CN	F16J 15/34
103765060	12/2013	CN	F16J 15/34
104169622	12/2013	CN	F16J 15/34
104334939	12/2014	CN	F16J 15/34
104919229	12/2014	CN	F16J 15/34
105793628	12/2015	CN	F16J 15/34
106015571	12/2015	CN	F16J 15/16
106104112	12/2015	CN	F16J 15/35
106352093	12/2016	CN	F16J 15/34
106763778	12/2016	CN	F16J 15/16
107407424	12/2016	CN	F16J 15/34
107532725	12/2017	CN	F16J 15/34
107735604	12/2017	CN	F16J 15/34
2444544	12/1973	DE	F16J 15/34
69113539	12/1991	DE	F16J 15/34
102008038396	12/2009	DE	F16J 15/34
2977654	12/2015	EP	F16J 15/34
3091258	12/2015	EP	F16J 15/34
3543569	12/2018	EP	F16J 15/34

2342440	12/1976	FR	F16J 15/34
50-45155	12/1974	JP	F16J 15/34
56-15856	12/1980	JP	F16J 15/34
4-50559	12/1991	JP	F16J 15/34
5-164249	12/1992	JP	F16J 15/34
6-174107	12/1993	JP	F16J 15/34
7-71618	12/1994	JP	F16J 15/34
8-502809	12/1995	JP	F16J 15/34
8-303606	12/1995	JP	F16J 15/34
3079562	12/1999	JP	F16J 15/34
2002-286026	12/2001	JP	F16J 15/34
2011-74931	12/2010	JP	F16J 15/34
2012-2295	12/2011	JP	F16J 15/34
2012-159152	12/2011	JP	F16J 15/34
2017-141962	12/2016	JP	F16J 15/34
2018-200068	12/2017	JP	F16J 15/34
WO9506212	12/1994	WO	F16J 15/34
WO2012046749	12/2011	WO	F16C 17/04
WO2013035502	12/2012	WO	F16J 15/34
WO2013035503	12/2012	WO	F16J 15/34
WO2013176009	12/2012	WO	F16J 15/34
WO2014024742	12/2013	WO	F16J 15/34
WO2014148317	12/2013	WO	F16J 15/34
WO2015199171	12/2014	WO	F16J 15/34
WO2015199172	12/2014	WO	F16J 15/34
WO2016167262	12/2015	WO	F16J 15/34
WO2016186015	12/2015	WO	F16J 15/34
WO2016186019	12/2015	WO	F16J 15/08
WO2016203878	12/2015	WO	F16J 15/34
WO2017061406	12/2016	WO	F16J 15/34
WO2018092742	12/2017	WO	F16J 15/34
WO2018105505	12/2017	WO	F16C 33/12
WO2019139107	12/2018	WO	F16J 15/34

OTHER PUBLICATIONS

U.S. Appl. No. 17/425,679, filed Jul. 23, 2024. cited by applicant

U.S. Appl. No. 16/640,324, filed Feb. 19, 2020, Sasaki et al. cited by applicant

U.S. Appl. No. 17/428,262, filed Aug. 3, 2021, Imura et al. cited by applicant

U.S. Appl. No. 17/428,912, filed Aug. 5, 2021, Ou et al. cited by applicant

U.S. Appl. No. 17/425,679, filed Jul. 23, 2021, Ou et al. cited by applicant

Primary Examiner: Patel; Vishal A

Attorney, Agent or Firm: HAYES SOLOWAY P.C.

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS (1) The present application is a divisional of U.S. patent application Ser. No. 17/425,679, filed Jul. 23, 2021, which is a 371 National Phase

TECHNICAL FIELD

(1) The present invention relates to a sliding component that is subjected to relative rotation, for example, a sliding component used in a seal device that seals a rotating shaft of a rotary machine in an automobile, a general industrial machine, or other sealing fields, or a sliding component used in a bearing of an automobile, a general industrial machine, or a machine in other bearing fields.

BACKGROUND ART

(2) As a seal device that prevents leakage of a sealed liquid, for example, there is a mechanical seal including a pair of sliding components which have an annular shape and rotate relative to each other to cause sliding surfaces to slide against each other. In such a mechanical seal, in recent years, there has been a desire that energy lost by sliding is reduced for environmental measures, and the sliding surface of the sliding component is provided with a positive pressure generating groove communicating with an outer diameter side which is a sealed liquid side of a high pressure, and having a closed one end in the sliding surface. Accordingly, when the sliding components rotate relative to each other, a positive pressure is generated in the positive pressure generating groove to separate the sliding surfaces from each other, and the sealed liquid is introduced into the positive pressure generating groove from the outer diameter side to be held therein. Therefore, the lubricity is improved, and the friction is reduced.

(3) Further, in order to maintain sealability for a long period of time, the mechanical seal is required to satisfy a condition such as “sealing” in addition to “lubrication”. For example, in a mechanical seal described in Patent Citation 1, one sliding component is provided with a Rayleigh step and a reverse Rayleigh step that communicate with a sealed liquid side. Accordingly, when sliding components rotate relative to each other, a positive pressure is generated between sliding surfaces by the Rayleigh step, to separate the sliding surfaces from each other, and the Rayleigh step holds a sealed liquid. Therefore, the lubricity is improved. Meanwhile, since a relatively negative pressure is generated in the reverse Rayleigh step, and the reverse Rayleigh step is disposed closer to a leakage side than the Rayleigh step, the sealed liquid of a high pressure which has flowed out from the Rayleigh step to a gap between the sliding surfaces can be suctioned into the reverse Rayleigh step. In such a manner, the sealed liquid between a pair of the sliding components is prevented from leaking to the leakage side, so that the sealability is improved.

CITATION LIST

Patent Literature

(4) Patent Citation 1: WO 2012/046749 A (pages 14 to 16 and FIG. 1)

SUMMARY OF INVENTION

Technical Problem

(5) However, in Patent Citation 1, since a structure where the reverse Rayleigh step causes the sealed liquid to return to the sealed liquid side is adopted, the sealed liquid is not supplied to the leakage side in the gap between the sliding surfaces, and there is a portion which has no contribution to lubricity, which is a problem. Therefore, sliding components having higher lubricity are required. In addition, the sealed liquid easily leaks from an opening portion of the reverse Rayleigh step, so that the lubricity becomes poorer, which is a problem.

(6) The present invention has been made in view of such a problem, and an object of the present invention is to provide a sliding component that supplies a sealed fluid to a leakage side in a gap between sliding surfaces to exhibit high lubricity and has a small leakage of the sealed fluid.

Solution to Problem

(7) In order to solve the above problem, according to the present invention, there is provided a sliding component that has an annular shape and is disposed in a place where relative rotation is

performed in a rotary machine, including a plurality of dynamic pressure generating mechanisms, in which a plurality of dynamic pressure generating mechanisms are provided in a sliding surface of the sliding component, each of the dynamic pressure generating mechanisms including a deep groove portion that communicates with an outer diameter side or an inner diameter side, and at least one shallow groove portion that communicates with the deep groove portion and extends in a circumferential direction, the shallow groove portion is shallower than the deep groove portion, and the deep groove portion is provided with a trap portion that suppresses leakage of a sealed fluid in the deep groove portion. According to the aforesaid features of the present invention, the deep groove portion has a deep groove depth and a large volume, so that a large amount of the sealed fluid supplied to the leakage side of the sliding surface can be recovered and returned to the shallow groove portion, and the lubricity can be improved by using a wide area extending to the leakage side of the sliding surface. In addition, since the deep groove portion is provided with the trap portion, the sealed fluid can be easily held in the deep groove portion. Therefore, the sealed fluid can be suppressed from leaking from the deep groove portion.

(8) It may be preferable that the deep groove portion communicates with the outer diameter side. According to this preferable configuration, the deep groove portion communicating with the outer diameter side is provided with the trap portion, so that the sealed fluid is held in the deep groove portion against centrifugal force that is generated in the sealed fluid due to relative rotation of the sliding component. Therefore, the sealed fluid can be suppressed from leaking from inside the deep groove portion to the outer diameter side.

(9) It may be preferable that the deep groove portion communicates with a leakage side. According to this preferable configuration, the deep groove portion communicating with the leakage side is provided with the trap portion, so that the sealed fluid can be suppressed from leaking to the leakage side. Further, in a case where the deep groove portion communicates with the outer diameter side, since the sealed fluid is held in the deep groove portion against the centrifugal force, which is generated in the sealed fluid due to relative rotation of the sliding component, and a leakage direction of the sealed fluid, the sealed fluid can be further suppressed from leaking from the deep groove portion to the leakage side located on the outer diameter side.

(10) It may be preferable that the trap portion is a trap piece extending from an inner surface of the deep groove portion. According to this preferable configuration, the trap piece extends from the inner surface of the deep groove portion, so that the trap portion having high rigidity can be easily formed.

(11) It may be preferable that the trap portion includes a guide surface that guides the sealed fluid toward the shallow groove portion. According to this preferable configuration, the sealed fluid held in the deep groove portion by the trap piece can be guided to the shallow groove portion along the guide surface.

(12) It may be preferable that the trap portion is disposed at least in a place near an opening portion of the deep groove portion communicating with the leakage side. According to this preferable configuration, the amount of the sealed fluid held in the deep groove portion can be secured.

(13) It may be preferable that the trap portion is disposed at least in a place where the deep groove portion intersects the shallow groove portion. According to this preferable configuration, the sealed fluid moving from the deep groove portion to the shallow groove portion is held, so that dynamic pressure can be reliably generated.

(14) It may be preferable that the trap portion is axisymmetrically disposed with respect to a center line of the deep groove portion, the center line extending in a radial direction. According to this preferable configuration, the function of holding the sealed fluid can be exhibited to correspond to the sliding component rotating to both sides in the circumferential direction.

(15) It may be preferable that the trap portion is integrally molded with a base material forming the sliding surface. According to this preferable configuration, the trap portion can be easily molded.

(16) It may be preferable that the trap portion defines a meandering groove that meanders in the

deep groove portion. According to this preferable configuration, the function of holding the sealed fluid can be improved by the meandering groove.

(17) Incidentally, the fact that the shallow groove portion of the sliding component according to the present invention extends in the circumferential direction means that the shallow groove portion may extend with at least a component in the circumferential direction, preferably, may extend such that the component along the circumferential direction is larger than the component in the radial direction. In addition, the fact that the deep groove portion extends in the radial direction means that the deep groove portion may extend with at least a component in the radial direction, preferably, may extend such that the component along the radial direction is larger than the component in the circumferential direction.

(18) In addition, the sealed fluid may be a liquid, or have a mist form in which a liquid and a gas are mixed.

Description

BRIEF DESCRIPTION OF DRAWINGS

- (1) FIG. 1 is a longitudinal cross-sectional view illustrating one example of a mechanical seal including a sliding component according to a first embodiment of the present invention.
- (2) FIG. 2 is a view of a sliding surface of a stationary seal ring when seen in an axial direction in the first embodiment.
- (3) FIG. 3 is an A-A cross-sectional view of FIG. 2.
- (4) FIG. 4 is a partial enlarged view of the sliding surface of the stationary seal ring in the first embodiment.
- (5) FIGS. 5A, 5B, and 5C are schematic views describing an operation in which a sealed liquid which is suctioned from an inner diameter side of a liquid guide groove portion at an initial stage of relative rotation flows out to a gap between sliding surfaces in the first embodiment.
- (6) FIG. 6 is a main part enlarged view of the sliding surface of the stationary seal ring in the first embodiment.
- (7) FIG. 7 is a view of a sliding surface of a stationary seal ring as a sliding component according to a second embodiment of the present invention when seen in the axial direction.
- (8) FIG. 8 is a main part enlarged view of the sliding surface of the stationary seal ring in the second embodiment.
- (9) FIG. 9 is a view of a sliding surface of a stationary seal ring as a sliding component according to a third embodiment of the present invention when seen in the axial direction.
- (10) FIG. 10 is a main part enlarged view of a sliding surface of a stationary seal ring as a sliding component according to a fourth embodiment of the present invention.
- (11) FIG. 11 is a main part enlarged view of a sliding surface of a stationary seal ring as a sliding component according to a fifth embodiment of the present invention.
- (12) FIG. 12 is a main part enlarged view of a sliding surface of a stationary seal ring as a sliding component according to a sixth embodiment of the present invention.
- (13) FIG. 13 is a main part enlarged view of a sliding surface of a stationary seal ring as a sliding component according to a seventh embodiment of the present invention.
- (14) FIG. 14 is a main part enlarged view of a sliding surface of a stationary seal ring as a sliding component according to an eighth embodiment of the present invention.
- (15) FIG. 15 is a main part enlarged view of a sliding surface of a stationary seal ring as a sliding component according to a ninth embodiment of the present invention.
- (16) FIG. 16 is a main part enlarged view of a sliding surface of a stationary seal ring as a sliding component according to a tenth embodiment of the present invention.
- (17) FIG. 17 is a main part enlarged view of a sliding surface of a stationary seal ring as a sliding

component according to an eleventh embodiment of the present invention.

DESCRIPTION OF EMBODIMENTS

(18) Modes for implementing a sliding component according to the present invention will be described below based on embodiments.

First Embodiment

(19) A sliding component according to a first embodiment of the present invention will be described with reference to FIGS. **1** to **6**. Incidentally, in the present embodiment, a mode in which the sliding component is a mechanical seal will be described as an example. In addition, a description will be given based on the premise that an inner diameter side of the sliding component forming the mechanical seal is a sealed liquid side (i.e., high-pressure side) as a sealed fluid side and an outer diameter side is an atmosphere side (i.e., low-pressure side) as a leakage side. In addition, for convenience of description, in the drawings, dots may be added to a groove and the like formed in a sliding surface.

(20) A mechanical seal for a general industrial machine illustrated in FIG. **1** is an outside mechanical seal that seals a sealed liquid F which tends to leak from an inner diameter side of sliding surfaces toward an outer diameter side, and mainly includes a rotating seal ring **20** which is a sliding component that has an annular shape and is provided on a rotating shaft **1** with a sleeve **2** interposed therebetween, to be rotatable together with the rotating shaft **1**, and a stationary seal ring **10** that has an annular shape and is a sliding component which is provided on a seal cover **5** fixed to a housing **4** of a mounted apparatus, to not be rotated but be movable in an axial direction. The stationary seal ring **10** is biased in the axial direction by a bellows **7**, so that a sliding surface **11** of the stationary seal ring **10** and a sliding surface **21** of the rotating seal ring **20** slide against each other in close contact with each other. Incidentally, the sliding surface **21** of the rotating seal ring **20** is a flat surface, and a recessed portion is not provided in the flat surface.

(21) The stationary seal ring **10** and the rotating seal ring **20** are representatively made of SiC (as an example of hard material) or a combination of SiC (as the example of hard material) and carbon (as an example of soft material); the sliding material is not limited thereto, and any type of sliding material is applicable as long as the sliding material is used as a sliding material for a mechanical seal. Incidentally, as the SiC, there are materials consisting of different components and compositions of two or more phases including a sintered body in which boron, aluminum, carbon, or the like is used as a sintering additive, for example, reaction-sintered SiC, SiC—TiC, SiC—TiN, and the like consisting of SiC or SiC and Si in which graphite particles are dispersed. As the carbon, resin molded carbon, sintered carbon, and the like carbon including carbon in which a carbonaceous material and a graphite material are mixed can be used. In addition, in addition to the above sliding materials, metallic materials, resin materials, surface modifiers (e.g., coating materials), composite materials, or the like are also applicable.

(22) As illustrated in FIG. **2**, the rotating seal ring **20** slides relative to the stationary seal ring **10** as indicated by an arrow, and a plurality of dynamic pressure generating mechanisms **14** which are integrally molded with a base material forming the sliding surface **11** are evenly provided in the sliding surface **11** of the stationary seal ring **10** in a circumferential direction of the stationary seal ring **10**. A portion of the sliding surface **11** other than the dynamic pressure generating mechanisms **14** is a land **12** forming a flat surface.

(23) Next, an outline of the dynamic pressure generating mechanism **14** will be described based on FIGS. **2** to **4**. Incidentally, hereinafter, a description will be given based on the premise that when the stationary seal ring **10** and the rotating seal ring **20** rotate relative to each other, the left side of the drawing sheet of FIG. **4** is a downstream side of the sealed liquid F flowing in a Rayleigh step **9A** to be described later, and the right side of the drawing sheet of FIG. **4** is an upstream side of the sealed liquid F flowing in the Rayleigh step **9A**.

(24) The dynamic pressure generating mechanism **14** includes a liquid guide groove portion **15** as a deep groove portion that communicates with the atmosphere side and extends in an inner diameter

direction, the Rayleigh step **9A** as a shallow groove portion that extends concentrically with the stationary seal ring **10** from an inner diameter side end portion of the liquid guide groove portion **15** toward the downstream side in the circumferential direction, and a trap portion **13** that gradually narrows the width of a flow path of the liquid guide groove portion **15** as the flow path extends from the outer diameter side toward the inner diameter side. Namely, the dynamic pressure generating mechanism **14** has an inverted L shape formed by the liquid guide groove portion **15** and the Rayleigh step **9A**, when seen in a direction orthogonal to the sliding surface **11**.

Incidentally, the liquid guide groove portion **15** of the first embodiment extends in a radial direction to be orthogonal to an axis of the stationary seal ring **10**. In addition, the liquid guide groove portion **15** and the Rayleigh step **9A** communicate with each other, and a step **18** in a depth direction is formed in a communication portion.

(25) In addition, a wall portion **9a** orthogonal to a rotational direction is formed in an end portion on the downstream side of the Rayleigh step **9A**. Incidentally, the wall portion **9a** is not limited to being orthogonal to the rotational direction, for example, may be inclined with respect to the rotational direction or may be formed in a step shape.

(26) The liquid guide groove portion **15** includes an opening portion **15a** that is open to an outer periphery of the stationary seal ring **10** to communicate with the atmosphere side. In addition, a depth dimension **L10** of the liquid guide groove portion **15** is larger than a depth dimension **L20** of the Rayleigh step **9A** (i.e., $L10 > L20$). Specifically, in the first embodiment, the depth dimension **L10** of the liquid guide groove portion **15** is 100 μm , and the depth dimension **L20** of the Rayleigh step **9A** is 5 μm . Namely, the step **18** in the depth direction is formed between the liquid guide groove portion **15** and the Rayleigh step **9A** by a downstream wall surface **15b** of the liquid guide groove portion **15** and a bottom surface of the Rayleigh step **9A**. Incidentally, as long as the depth dimension of the liquid guide groove portion **15** is larger than the depth dimension of the Rayleigh step **9A**, the depth dimensions of the liquid guide groove portion **15** and the Rayleigh step **9A** can be freely changed, and it is preferable that the dimension **L10** is five times or more the dimension **L20**.

(27) Incidentally, the bottom surface of the Rayleigh step **9A** is a flat surface and is formed in parallel to the land **12**; however, the flat surface is not prevented from being provided with a fine recessed portion or being formed to be inclined with respect to the land **12**. Further, each of two arc-shaped surfaces of the Rayleigh step **9A** is orthogonal to the bottom surface of the Rayleigh step **9A**, the two arc-shaped surfaces extending in the circumferential direction. In addition, a bottom surface **15d** of the liquid guide groove portion **15** is a flat surface and is formed in parallel to the land **12**; however, the flat surface is not prevented from being provided with a fine recessed portion or being formed to be inclined with respect to the land **12**. Further, referring to FIG. 3, the liquid guide groove portion **15** includes the downstream wall surface **15b** and an upstream wall surface **15c** that extend in the radial direction and face each other in the circumferential direction, and the bottom surface **15d** that is orthogonal to the wall surfaces **15b** and **15c**. Namely, the downstream wall surface **15b**, the upstream wall surface **15c**, and the bottom surface **15d** form an inner surface of the liquid guide groove portion **15**.

(28) The trap portion **13** includes a trap piece **13A** that extends to the inner diameter side from the downstream wall surface **15b** of the liquid guide groove portion **15** toward a center side in the circumferential direction of the liquid guide groove portion **15**, the downstream wall surface **15b** being located on the outer diameter side of the Rayleigh step **9A**, and a trap piece **13B** that faces the trap piece **13A** and extends to the inner diameter side from the upstream wall surface **15c** of the liquid guide groove portion **15** toward the center side in the circumferential direction of the liquid guide groove portion **15**. The trap pieces **13A** and **13B** are axisymmetrically disposed with respect to an imaginary center line of the liquid guide groove portion **15**, the imaginary center line extending in the radial direction. Incidentally, in the following description, the trap piece **13A** will be described unless otherwise specified, and the description of the trap piece **13B** will be omitted.

(29) The trap piece **13A** is provided with a low-pressure side wall surface **13a** that extends to the inner diameter side from the downstream wall surface **15b** of the liquid guide groove portion **15** toward the center side in the circumferential direction of the liquid guide groove portion **15**, the downstream wall surface **15b** being located closer to the outer diameter side than a low-pressure side wall surface **9c** extending in the circumferential direction of the Rayleigh step **9A**, and a high-pressure side wall surface **13c** that is continuous with the low-pressure side wall surface **9c** of the Rayleigh step **9A** and extends to the inner diameter side from the downstream wall surface **15b** of the liquid guide groove portion **15** toward the center side in the circumferential direction of the liquid guide groove portion **15**. The low-pressure side wall surface **13a** and the high-pressure side wall surface **13c** of the trap piece **13A** are flat surfaces; however, each of the flat surfaces is not prevented from being provided with a fine recessed portion or an end surface thereof is not prevented from being rounded.

(30) In addition, an end surface of the trap piece **13A** forms the same plane as that of the land **12** and is continuous therewith, the end surface facing the sliding surface **21** of the rotating seal ring **20**. In addition, the trap piece **13A** is continuous from the end surface, which forms the same plane as that of the land **12** and faces the sliding surface **21** of the rotating seal ring **20**, to the bottom surface **15d** of the liquid guide groove portion **15**.

(31) Next, the operation during relative rotation of the stationary seal ring **10** and the rotating seal ring **20** will be described. First, during non-operation of the general industrial machine, namely, when the rotating seal ring **20** does not rotate, a slight amount of the sealed liquid F on the outer diameter side of the sliding surfaces **11** and **21** enters a gap between the sliding surfaces **11** and **21** due to the capillary phenomenon, and in the dynamic pressure generating mechanism **14**, the sealed liquid F which has remained during stop of the general industrial machine and the atmosphere which has entered from the inner diameter side of the sliding surfaces **11** and **21** are mixed. Incidentally, since the sealed liquid F has a higher viscosity than a gas, the amount of leakage from the dynamic pressure generating mechanism **14** to a low-pressure side during stop of the general industrial machine is small.

(32) In a case where almost no sealed liquid F remains in the dynamic pressure generating mechanism **14** during stop of the general industrial machine, when the rotating seal ring **20** rotates relative to the stationary seal ring **10** (refer to the black arrow of FIG. 2), as illustrated in FIG. 4, a low-pressure side fluid A on the atmosphere side is introduced from the liquid guide groove portion **15** as indicated by an arrow L1, and the Rayleigh step **9A** causes the low-pressure side fluid A to move in a following manner in the rotational direction of the rotating seal ring **20** as indicated by an arrow L2, so that dynamic pressure is generated in the Rayleigh step **9A**.

(33) The pressure is the highest in the vicinity of the wall portion **9a** which is the end portion on the downstream side of the Rayleigh step **9A**, so that the low-pressure side fluid A flows out from the vicinity of the wall portion **9a** to the periphery thereof as indicated by an arrow L3. Incidentally, the pressure decreases gradually as the upstream side of the Rayleigh step **9A** is approached.

(34) In addition, when the stationary seal ring **10** and the rotating seal ring **20** rotate relative to each other, the sealed liquid F of a high pressure flows into the gap between the sliding surfaces **11** and **21** from the inner diameter side thereof at all times to perform so-called fluid lubrication. At this time, since the pressure of the sealed liquid F in the vicinity of the Rayleigh step **9A**, as described above, particularly on the downstream side of the Rayleigh step **9A** is high, as indicated by an arrow H1, the sealed liquid F remains located on the land **12** to hardly enter the Rayleigh step **9A**.

(35) On the other hand, since the liquid guide groove portion **15** is a deep groove portion and communicates with the low-pressure side, as indicated by an arrow H2, the sealed liquid F in the vicinity of the liquid guide groove portion **15** easily enters the liquid guide groove portion **15**. In addition, since the sealed liquid F is a liquid and has large surface tension, the sealed liquid F moves along side wall surfaces of the liquid guide groove portion **15** to easily enter the liquid guide groove portion **15**.

(36) Next, an operation in which the sealed liquid F suctioned into the liquid guide groove portion **15** flows out to the gap between the sliding surfaces **11** and **21** will be described.

(37) In a case where almost no sealed liquid F remains in the dynamic pressure generating mechanism **14**, when the rotating seal ring **20** rotates relative to the stationary seal ring **10** (refer to the black arrow of FIG. 2), as illustrated in FIG. 5A, the sealed liquid F which has infiltrated into the liquid guide groove portion **15** becomes an agglomerated droplet as indicated by reference sign H3. Thereafter, as illustrated in FIG. 5B, when the droplet reaches a certain volume, the droplet passes through the trap portion **13** due to a relatively low pressure formed upstream of the Rayleigh step **9A**, as indicated by reference sign H4, to be suctioned into the Rayleigh step **9A**. At the same time, the sealed liquid F newly enters the liquid guide groove portion **15** to become a droplet H3'. At this time, the sealed liquid F of a larger amount than the amount at an initial stage of the relative rotation in FIG. 5A enters the liquid guide groove portion **15**.

(38) Thereafter, as illustrated in FIG. 5C, the sealed liquid F suctioned into the Rayleigh step **9A** receives a large shearing force from the rotating seal ring **20** to move to the downstream side in the Rayleigh step **9A** while the pressure increases, as indicated by an arrow H5, to flow out from the vicinity of the wall portion **9a** to a peripheral portion of the wall portion **9a**. At the same time, a larger amount of the sealed liquid F newly enters the liquid guide groove portion **15** to become a droplet H3'', and as indicated by reference sign H4', the droplet H3' is suctioned into the Rayleigh step **9A**.

(39) Thereafter, the amount of the sealed liquid F entering the liquid guide groove portion **15** is further increased than in the state illustrated in FIG. 5C, and a steady state where the sealed liquid F flows out continuously from the Rayleigh step **9A** to the gap between the sliding surfaces **11** and **21** is reached. In the steady state, the sealed liquid F of a high pressure flows into the gap between the sliding surfaces **11** and **21** from the outer diameter side thereof or the Rayleigh step **9A** at all times to perform fluid lubrication as described above. Incidentally, the time until the steady state is reached via the states of FIGS. 5A to 5C is a transient short time. In addition, when the sealed liquid F remains in the dynamic pressure generating mechanism **14** during stop of the general industrial machine, depending on the amount of the sealed liquid F remaining in the dynamic pressure generating mechanism **14**, the operation starts from any one of the state of FIG. 5A, the state of FIG. 5B, the state of FIG. 5C, and the steady state.

(40) Here, since the liquid guide groove portion **15** is a deep groove portion and communicates with the low-pressure side, the sealed liquid F indicated by the arrow H5 is easily suctioned into the liquid guide groove portion **15** adjacent thereto, so that the amount of the sealed liquid F between the sliding surfaces **11** and **21** is stable and high lubricity can be maintained. In addition, since a liquid has a larger interfacial tension for a solid than a gas, the sealed liquid F is easily held between the sliding surfaces **11** and **21**, and the atmosphere is easily discharged to the outer diameter side of the stationary seal ring **10** and the rotating seal ring **20**.

(41) In addition, referring to FIGS. 5A, 5B and 5C, as illustrated with the droplets H3, H3', and H3'', since in the trap portion **13**, the low-pressure side wall surfaces **13a** and **13a** of the trap pieces **13A** and **13B** which are inclined toward the inner diameter side, which is an inflow direction of the sealed liquid F, from the wall surfaces **15b** and **15c** to the center side in the circumferential direction of the liquid guide groove portion **15** function as guide surfaces that guide the sealed liquid F to a Rayleigh step **9A** side, even when the flow path of the liquid guide groove portion **15** is narrowed by the trap portion **13**, movement of the sealed liquid F is unlikely to be interrupted.

(42) In addition, referring to FIG. 6, as indicated by an arrow H6, since the high-pressure side wall surface **13c** of the trap piece **13A** is continuous with the low-pressure side wall surface **9c** of the Rayleigh step **9A**, the sealed liquid F can be directly guided from the high-pressure side wall surface **13c** to the low-pressure side wall surface **9c** of the Rayleigh step **9A**. For this reason, the efficiency of suction of the sealed liquid F into the Rayleigh step **9A** is good.

(43) In addition, as illustrated in FIG. 6, since the mechanical seal of the present embodiment is an

outside mechanical seal, as indicated by an arrow C, centrifugal force generated by rotation of the rotating seal ring **20** is applied to the sealed liquid F. Therefore, the sealed liquid F in the liquid guide groove portion **15** is biased in a leakage direction toward the atmosphere side which is the outer diameter side. However, since the sealed liquid F is a liquid and has higher viscosity than a gas, and the trap portion **13** counters the centrifugal force which is applied to the sealed liquid F by the high-pressure side wall surfaces **13c** and **13c** of the trap pieces **13A** and **13B** inclined toward the outer diameter side, which is the leakage direction of the sealed liquid F, from a central portion in the circumferential direction of the liquid guide groove portion **15** to the wall surfaces **15b** and **15c**, leakage to the atmosphere side can be suppressed. Further, since the high-pressure side wall surface **13c** of the trap piece **13A** can directly guide the sealed liquid F to the Rayleigh step **9A** as described above, the efficiency of suction of the sealed liquid F from inside the liquid guide groove portion **15** into the Rayleigh step **9A** can be increased by using the centrifugal force.

(44) In addition, in the trap portion **13**, since the width between the trap pieces **13A** and **13B** is narrow, the surface tension applied to the sealed liquid F existing between the trap pieces **13A** and **13B** counters the centrifugal force applied to the sealed liquid F. Accordingly, as illustrated with a halftone dot portion in FIG. **6**, the holding ability to hold the sealed liquid F on the inner diameter side of the trap portion **13** is increased.

(45) As described above, when the stationary seal ring **10** and the rotating seal ring **20** rotate relative to each other, the low-pressure side fluid A on the atmosphere side is suctioned into the Rayleigh step **9A** through the liquid guide groove portion **15**, so that dynamic pressure is generated therein. Since the liquid guide groove portion **15** has a deep groove depth and a large volume, a large amount of the sealed liquid F supplied to the atmosphere side of the sliding surface **11** can be recovered and returned to the Rayleigh step **9A**, and the lubricity can be improved by using a wide area extending to the low-pressure side of the sliding surface **11**. In addition, since the liquid guide groove portion **15** is provided with the trap portion **13**, the sealed liquid F is held in the liquid guide groove portion **15** against the centrifugal force that is generated in the sealed liquid F due to relative rotation of the stationary seal ring **10**. Therefore, the sealed liquid F can be suppressed from leaking to the atmosphere side located on the outer diameter side.

(46) In addition, since a large amount of the sealed liquid F is held in the liquid guide groove portion **15**, the amount of the sealed liquid F suctioned into the Rayleigh step **9A** can be sufficiently secured, and even when the amount of the sealed liquid F held in the liquid guide groove portion **15** increases or decreases in a short time, the amount of the sealed liquid F suctioned into the Rayleigh step **9A** can be substantially constant, and the sliding surfaces **11** and **21** can be avoided from being subjected to poor lubrication. In addition, since the liquid guide groove portion **15** communicates with the low-pressure side, the pressure in the liquid guide groove portion **15** is lower than the pressure of the sealed liquid F between the sliding surfaces **11** and **21**, and the sealed liquid F in the vicinity of the liquid guide groove portion **15** is easily suctioned into the liquid guide groove portion **15**.

(47) In addition, the liquid guide groove portion **15** extends in the radial direction. Specifically, since the liquid guide groove portion **15** extends in a direction orthogonal to a center axis of the stationary seal ring **10**, and the Rayleigh step **9A** is disposed in the circumferential direction from the outer diameter side end portion of the liquid guide groove portion **15** to intersect the liquid guide groove portion **15**, the liquid guide groove portion **15** is unlikely to be affected by the inertia or dynamic pressure of a flow of the sealed liquid F, which is generated in the Rayleigh step **9A**. For this reason, the sealed liquid F or the low-pressure side fluid A adhering to an inside surface of the stationary seal ring **10** is unlikely to be directly suctioned into the Rayleigh step **9A** from the inner diameter side of the liquid guide groove portion **15**. In addition, the sealed liquid F can be held in the liquid guide groove portion **15** without being directly affected by dynamic pressure.

(48) In addition, the trap pieces **13A** and **13B** are continuous from the end surfaces thereof to the bottom surface **15d** of the liquid guide groove portion **15** in the axial direction, the end surfaces

facing the sliding surface **21** of the rotating seal ring **20**, so that the rigidity against external force applied in the axial direction is increased. In addition, since the trap pieces **13A** and **13B** are continuous with the downstream wall surface **15b** and the upstream wall surface **15c** of the liquid guide groove portion **15**, respectively, the rigidity in the circumferential direction is also increased. Namely, since the trap pieces **13A** and **13B** extend from the downstream wall surface **15b**, the upstream wall surface **15c**, and the bottom surface **15d** of the liquid guide groove portion **15**, the trap portion **13** having high rigidity can be easily formed.

(49) In addition, since the trap portion **13** is disposed in a place where the liquid guide groove portion **15** and the Rayleigh step **9A** intersect each other, the sealed liquid F moving from the liquid guide groove portion **15** to the Rayleigh step **9A** is held, so that dynamic pressure can be reliably generated.

(50) In addition, since the trap portion **13** is integrally molded with the base material forming the sliding surface **11**, the trap portion **13** can be easily molded.

(51) In addition, the width in the circumferential direction of the liquid guide groove portion **15** is shortened, so that a large number of the stationary seal rings **10** can be disposed in the circumferential direction. Therefore, the degree of freedom in design is high. Incidentally, the liquid guide groove portion **15** is not limited to extending in the direction orthogonal to the center axis of the stationary seal ring **10**, and may be inclined from a position orthogonal to the center axis of the stationary seal ring **10**. It is preferable that the inclination is less than 45 degrees. Further, the shape of the liquid guide groove portion **15** can be freely changed to an arc shape or the like.

(52) In addition, since the step **18** is formed in the communication portion between the Rayleigh step **9A** and the liquid guide groove portion **15** by a side surface on the downstream side of the liquid guide groove portion **15** and the bottom surface of the Rayleigh step **9A**, the sealed liquid F can be held in the liquid guide groove portion **15** without being directly affected by dynamic pressure.

(53) In addition, since the Rayleigh step **9A** communicates with the liquid guide groove portion **15** over the entire width in the radial direction, an opening region of the Rayleigh step **9A** to the liquid guide groove portion **15** can be secured, and the sealed liquid F held in the liquid guide groove portion **15** can be efficiently suctioned up.

(54) In addition, since the dynamic pressure generating mechanism **14** is provided in the stationary seal ring **10**, when the stationary seal ring **10** and the rotating seal ring **20** rotate relative to each other, the state inside the liquid guide groove portion **15** is easily kept close to atmospheric pressure.

(55) Incidentally, in the first embodiment, a mode in which the liquid guide groove portion **15** and the Rayleigh step **9A** form an inverted L shape when seen in the direction orthogonal to the sliding surface **11** has been provided as an example; however, for example, the liquid guide groove portion **15** and the Rayleigh step **9A** may smoothly communicate with each other without intersecting each other, to form, for example, a linear shape or an arc shape.

(56) In addition, the step **18** may not be provided in the communication portion between the liquid guide groove portion **15** and the Rayleigh step **9A**, for example, the liquid guide groove portion **15** and the Rayleigh step **9A** may communicate with each other through an inclined surface. In this case, for example, a portion having a depth dimension of 5 μm or less can be the Rayleigh step **9A** as a shallow groove portion, and a portion which is deeper than 5 μm can be the liquid guide groove portion **15** as a deep groove portion.

(57) In addition, the shallow groove portion is not limited to extending concentrically with the stationary seal ring in the circumferential direction, for example, may be formed in an arc shape such that the end portion on the downstream side faces the high-pressure side. In addition, the shallow groove portion may extend linearly from the deep groove portion, or may extend in a meandering manner.

(58) In addition, the trap portion **13** may include only the trap piece **13A** disposed on the Rayleigh

step **9A** side which is a dynamic pressure generating groove, the dimension of the trap piece **13A** may be appropriately changed, and the trap piece **13A** may be disposed to be separated from the low-pressure side wall surface **9c** of the Rayleigh step **9A** in the radial direction. Similarly, the trap portion **13** may include only the trap piece **13B** disposed on a side facing the Rayleigh step **9A**. (59) In addition, a mode in which the trap piece **13A** forms the same plane as that of the land **12** has been provided as an example; however, for example, the trap piece **13A** may be recessed from the land **12** in the axial direction. In addition, a mode in which the trap piece **13A** is continuous to the bottom surface **15d** of the liquid guide groove portion **15** in the axial direction has been provided as an example; however, for example, a lower end portion of the trap piece **13A** may be separated from the bottom surface **15d** of the liquid guide groove portion **15**, or a part in the axial direction of the trap piece **13A** may be divided in the middle thereof. Namely, the trap piece **13A** may be configured such that centrifugal force can be suppressed from causing the sealed liquid **F** to leak from inside the liquid guide groove portion **15** to the atmosphere side, and the shape of the trap piece **13A** may be appropriately changed.

(60) In addition, a mode in which the trap piece **13A** is integrally molded with the base material forming the sliding surface **11** has been provided as an example; however, the present invention is not limited to the mode, and a trap piece which is formed separately from the base material forming the sliding surface **11** may be fixed to an inner surface of the liquid guide groove portion **15**.

Second Embodiment

(61) Next, a sliding component according to a second embodiment of the present invention will be described with reference to FIGS. **7** and **8**. Incidentally, the description of configurations which are the same as and duplicated from those in the first embodiment will be omitted.

(62) As illustrated in FIGS. **7** and **8**, a dynamic pressure generating mechanism **141** provided in a stationary seal ring **101** includes the liquid guide groove portion **15**, the Rayleigh step **9A**, a reverse Rayleigh step **9B** as a shallow groove portion that extends concentrically with the stationary seal ring **101** from the inner diameter side end portion of the liquid guide groove portion **15** toward the upstream side in the circumferential direction, and the trap portion **13**. Namely, the dynamic pressure generating mechanism **141** has a T shape when seen in the direction orthogonal to the sliding surface **11**. In addition, the reverse Rayleigh step **9B** is formed with the same depth dimension of $5\ \mu\text{m}$ as that of the Rayleigh step **9A**.

(63) The trap piece **13B** is provided with the low-pressure side wall surface **13a** that extends to the inner diameter side from the upstream wall surface **15c** of the liquid guide groove portion **15** toward the center side in the circumferential direction of the liquid guide groove portion **15**, the upstream wall surface **15c** being located closer to the outer diameter side than the low-pressure side wall surface **9c** extending in the circumferential direction of the reverse Rayleigh step **9B**, and the high-pressure side wall surface **13c** that is continuous with the low-pressure side wall surface **9c** of the reverse Rayleigh step **9B** and extends to the inner diameter side from the upstream wall surface **15c** of the liquid guide groove portion **15** toward the center side in the circumferential direction of the liquid guide groove portion **15**.

(64) When the rotating seal ring **20** rotates counterclockwise on the drawing sheet as indicated by a solid arrow of FIG. **7**, the low-pressure side fluid **A** moves in order of arrows **L1**, **L2**, and **L3**, so that dynamic pressure is generated in the Rayleigh step **9A**. In addition, when the rotating seal ring **20** rotates clockwise on the drawing sheet as indicated by a dotted arrow of FIG. **7**, the low-pressure side fluid **A** moves in order of arrows **L1**, **L2'**, and **L3'**, so that dynamic pressure is generated in the reverse Rayleigh step **9B**. Namely, when the rotating seal ring **20** rotates clockwise on the drawing sheet of FIG. **7**, the reverse Rayleigh step **9B** functions as a Rayleigh step, and the Rayleigh step **9A** functions as a reverse Rayleigh step.

(65) As described above, since the Rayleigh step **9A** and the reverse Rayleigh step **9B** extend from the liquid guide groove portion **15** to both sides in the circumferential direction, and one of the Rayleigh step **9A** and the reverse Rayleigh step **9B** can be used as a shallow groove portion for

generating dynamic pressure, the Rayleigh step **9A** or the reverse Rayleigh step **9B** can be used regardless of the relative rotational direction of the stationary seal ring **101** and the rotating seal ring **20**.

(66) In addition, the Rayleigh step **9A** of the dynamic pressure generating mechanism **141** is adjacent, in the circumferential direction, to the reverse Rayleigh step **9B** of a dynamic pressure generating mechanism **141'** adjacent thereto. Accordingly, the sealed liquid **F** which flows out from the vicinity of the wall portion **9a** of the Rayleigh step **9A** of the dynamic pressure generating mechanism **141** to a peripheral portion thereof to tend to move to the inner diameter side is suctioned from the reverse Rayleigh step **9B** of the dynamic pressure generating mechanism **141'** adjacent thereto. Therefore, a leakage of the sealed liquid **F** to the low-pressure side can be reduced.

(67) In addition, when the rotating seal ring **20** rotates counterclockwise on the drawing sheet as indicated by a solid arrow of FIG. **8**, similar to the first embodiment, the trap portion **13** can suppress the sealed liquid **F** from leaking to the atmosphere side located on the outer diameter side. In addition, when the rotating seal ring **20** rotates clockwise on the drawing sheet as indicated by a dotted arrow of FIG. **8**, the trap portion **13** does not prevent movement of the sealed liquid **F** from the atmosphere side to a sealed liquid **F** side, as indicated by an arrow **H7**, the efficiency of suction of the sealed liquid **F** to the reverse Rayleigh step **9B** by the high-pressure side wall surface **13c** of the trap piece **13B** continuous with the low-pressure side wall surface **9c** is good, and the width between the trap pieces **13A** and **13B** is narrow. Therefore, surface tension is generated in the sealed liquid **F** existing between the trap pieces **13A** and **13B**, the surface tension counters the centrifugal force applied to the sealed liquid **F**, so that the holding ability to hold the sealed liquid **F** on the inner diameter side of the trap portion **13** as illustrated with a halftone dot portion is increased. Namely, the function of holding the sealed liquid **F** can be exhibited to correspond to the stationary seal ring **101** rotating to both sides in the circumferential direction.

(68) Incidentally, in the second embodiment, a case where the Rayleigh step **9A** and the reverse Rayleigh step **9B** have the same depth dimension has been provided as an example; however, the Rayleigh step **9A** and the reverse Rayleigh step **9B** may be formed with different depth dimensions. In addition, both may be the same or different from each other also in length in the circumferential direction and width in the radial direction.

(69) In addition, the Rayleigh step **9A** of the dynamic pressure generating mechanism **141** and the reverse Rayleigh step **9B** of the dynamic pressure generating mechanism **141'** adjacent thereto may be separated from each other by a long distance in the circumferential direction to further increase the pressure which separates the sliding surfaces **11** and **21** from each other.

Third Embodiment

(70) Next, a sliding component according to a third embodiment of the present invention will be described with reference to FIG. **9**. Incidentally, the description of configurations which are the same as and duplicated from those in the second embodiment will be omitted.

(71) As illustrated in FIG. **9**, a plurality of the dynamic pressure generating mechanisms **141** and a plurality of specific dynamic pressure generating mechanisms **16** are formed in a stationary seal ring **102**. The specific dynamic pressure generating mechanism **16** includes a liquid guide groove portion **161** communicating with the high-pressure side, a Rayleigh step **17A** that extends concentrically with the stationary seal ring **102** from an outer diameter side end portion of the liquid guide groove portion **161** toward the downstream side in the circumferential direction, and a reverse Rayleigh step **17B** that extends concentrically with the stationary seal ring **102** from the outer diameter side end portion of the liquid guide groove portion **161** toward the upstream side in the circumferential direction. The liquid guide groove portion **161** and the liquid guide groove portion **15** are formed at positions corresponding to each other in the circumferential direction. In addition, the liquid guide groove portion **161** functions as a deep groove portion of the specific dynamic pressure generating mechanism **16**, and the Rayleigh step **17A** and the reverse Rayleigh

step 17B function as shallow groove portions of the specific dynamic pressure generating mechanism 16.

(72) The Rayleigh step 9A and the reverse Rayleigh step 9B of the dynamic pressure generating mechanism 141 are formed to be longer in the circumferential direction than the Rayleigh step 17A and the reverse Rayleigh step 17B of the specific dynamic pressure generating mechanism 16. In addition, the Rayleigh step 17A and the reverse Rayleigh step 17B are formed with the same depth dimension of 5 μm as that of the Rayleigh step 9A and the reverse Rayleigh step 9B. In addition, the width in the radial direction of the Rayleigh step 17A and the reverse Rayleigh step 17B is smaller than the width in the radial direction of the Rayleigh step 9A and the reverse Rayleigh step 9B. Namely, the volume of the dynamic pressure generating mechanism 141 is larger than the volume of the specific dynamic pressure generating mechanism 16.

(73) When the rotating seal ring 20 rotates counterclockwise on the drawing sheet as indicated by a solid arrow of FIG. 9, the sealed liquid F moves in order of arrows L11, L12, and L13, so that dynamic pressure is generated in the Rayleigh step 17A. In addition, when the rotating seal ring 20 rotates clockwise on the drawing sheet as indicated by a dotted arrow of FIG. 9, the sealed liquid F moves in order of arrows L11, L12', and L13', so that dynamic pressure is generated in the reverse Rayleigh step 17B. In such a manner, regardless of the relative rotational direction of the stationary seal ring 102 and the rotating seal ring 20, dynamic pressure can be generated in the specific dynamic pressure generating mechanism 16.

(74) In addition, while the dynamic pressure generated in the specific dynamic pressure generating mechanism 16 separates the sliding surfaces 11 and 21 from each other to form an appropriate liquid film therebetween, the sealed liquid F which tends to leak from the sliding surface 11 to the low-pressure side can be recovered by the dynamic pressure generating mechanism 141.

(75) In addition, since the volume of the dynamic pressure generating mechanism 141 is larger than the volume of the specific dynamic pressure generating mechanism 16, the suctioning force of the Rayleigh step 9A and the reverse Rayleigh step 9B of the dynamic pressure generating mechanism 141 is increased, so that a balance in dynamic pressure between the dynamic pressure generating mechanism 141 on the low-pressure side and the specific dynamic pressure generating mechanism 16 on the high-pressure side can be adjusted.

(76) In addition, since the wall portion 9a which is an end of the dynamic pressure generating mechanism 141 and a wall portion 17a which is an end of the specific dynamic pressure generating mechanism 16 are shifted from each other in the circumferential direction, the pressure can be distributed with good balance in the circumferential direction of the sliding surfaces 11 and 21.

(77) Incidentally, the length in the circumferential direction of the Rayleigh step 9A and the reverse Rayleigh step 9B may be the same as that of the Rayleigh step 17A and the reverse Rayleigh step 17B, or may be shorter than that of the Rayleigh step 17A and the reverse Rayleigh step 17B. In addition, the Rayleigh step 17A and the reverse Rayleigh step 17B may be formed with a depth dimension different from that of the Rayleigh step 9A and the reverse Rayleigh step 9B. In addition, the width in the radial direction of the Rayleigh step 17A and the reverse Rayleigh step 17B may be larger than the width in the radial direction of the Rayleigh step 9A and the reverse Rayleigh step 9B. Preferably, the volume of the dynamic pressure generating mechanism 141 may be larger than the volume of the specific dynamic pressure generating mechanism 16.

(78) In addition, in the sliding surface 11, the dimension in the radial direction from an outer diameter side end edge of the sliding surface 11 to an outer diameter side end edge of the Rayleigh step 9A of the dynamic pressure generating mechanism 141, the dimension in the radial direction from an inner diameter side end edge of the Rayleigh step 9A of the dynamic pressure generating mechanism 141 to an outer diameter side end edge of the Rayleigh step 17A of the specific dynamic pressure generating mechanism 16, and the dimension in the radial direction from an inner diameter side end edge of the Rayleigh step 17A of the specific dynamic pressure generating mechanism 16 to an inner diameter side end edge of the sliding surface 11 may be appropriately

changed. Accordingly, the amount of the sealed liquid F leaking from between the sliding surfaces **11** and **21** to the atmosphere side and the amount of the sealed liquid F recovered by the dynamic pressure generating mechanism can be more suitably balanced according to the rotational speed of the rotating seal ring **20** and the pressure of the sealed liquid F. Namely, the sealed liquid F can be suppressed from leaking to the atmosphere side.

Fourth Embodiment

(79) Next, a stationary seal ring as a sliding component according to a fourth embodiment of the present invention will be described with reference to FIG. **10**. Incidentally, the description of configurations which are the same as and duplicated from those in the second embodiment will be omitted. In addition, here, only the form of a dynamic pressure generating mechanism **142** will be described.

(80) The dynamic pressure generating mechanism **142** includes the liquid guide groove portion **151**, a Rayleigh step **91A** that extends from the center in the radial direction of the liquid guide groove portion **151** to the downstream side in the circumferential direction (i.e., left side of the figure), a reverse Rayleigh step **91B** that extends from an inner diameter side end portion in the radial direction of the liquid guide groove portion **151** to the upstream side in the circumferential direction (i.e., right side of the figure), the inner diameter side end portion being located closer to the inner diameter side than the Rayleigh step **91A**, and a trap portion **131**. The trap portion **131** includes trap pieces **131A** and **131B** that are alternately disposed in the radial direction.

(81) Accordingly, when the rotating seal ring **20** rotates counterclockwise, in the trap portion **131**, centrifugal force toward the atmosphere side is applied to the sealed liquid F in the liquid guide groove portion **151**, and the sealed liquid F on the inner diameter side of the trap piece **131B** is guided to the downstream side by an inner diameter side wall portion **131c** and is guided to the Rayleigh step **91A** on the further downstream side by the inner diameter side wall portion **131c** of the trap piece **131A**. Therefore, the sealed liquid F is unlikely to move to the atmosphere side of the trap portion **131**. In other words, since the trap portion **131** makes it difficult for the sealed liquid F to linearly move in the radial direction, the function of holding the sealed liquid F in the liquid guide groove portion **151** can be improved.

(82) In addition, in the trap portion **131**, since the width between the trap pieces **131A** and **131B** is narrow, surface tension is generated in the sealed liquid F existing between the trap pieces **131A** and **131B**, and the surface tension counters the centrifugal force applied to the sealed liquid F, so that as illustrated with a halftone dot portion, the holding ability to hold the sealed liquid F on the inner diameter side of the trap portion **131** is increased.

Fifth Embodiment

(83) Next, a stationary seal ring as a sliding component according to a fifth embodiment of the present invention will be described with reference to FIG. **11**. Incidentally, the description of configurations which are the same as and duplicated from those in the second embodiment will be omitted. In addition, here, only the form of a dynamic pressure generating mechanism **143** will be described.

(84) The dynamic pressure generating mechanism **143** includes the Rayleigh step **9A**, the reverse Rayleigh step **9B**, a liquid guide groove portion **152**, and a trap portion **132**. The trap portion **132** includes a plurality of trap pieces **132A** that are disposed at predetermined intervals from the vicinity of an opening portion **152a** of the liquid guide groove portion **152** to the vicinity of an inner diameter side end portion intersecting the Rayleigh step **9A**, a plurality of trap pieces **132B** that are disposed to be axisymmetric with the trap pieces **132A** with respect to an imaginary center line of the liquid guide groove portion **152**, the imaginary center line extending in the radial direction, and a plurality of trap pieces **132C** that are disposed in a central portion in the circumferential direction of the liquid guide groove portion **152** in places where the trap pieces **132C** each are surrounded by four trap pieces **132A**, **132A**, **132B**, and **132B** adjacent to each other.

(85) The trap piece **132A** extends to the outer diameter side from the downstream side of the liquid

guide groove portion **152** toward a center side in the circumferential direction of the liquid guide groove portion **152**. In addition, the trap piece **132A** is provided with a low-pressure side wall surface **132a** that extends to the outer diameter side from the downstream side of the liquid guide groove portion **152** toward the upstream side, a center side wall surface **132b** that is orthogonal to an end portion on the upstream side of the low-pressure side wall surface **132a** and extends to the inner diameter side from the end portion toward the upstream side, and a downstream wall surface **132c** that is orthogonal to an end portion on the inner diameter side of the center side wall surface **132b** and extends to the inner diameter side from the end portion toward the downstream side.

(86) The trap piece **132C** is axisymmetrically formed with respect to the imaginary center line of the liquid guide groove portion **152**, the imaginary center line extending in the radial direction, and extends from the central portion in the circumferential direction of the liquid guide groove portion **152** to the inner diameter side on the downstream side and the inner diameter side on the upstream side. In addition, the trap piece **132C** is provided with low-pressure side wall surfaces **132d** and **132d** that extend from the central portion in the circumferential direction of the liquid guide groove portion **152** to the inner diameter side on the downstream side and the inner diameter side on the upstream side, center side wall surfaces **132e** and **132e** that are orthogonal to an end portion on the downstream side and an end portion on the upstream side of the low-pressure side wall surfaces **132d** and **132d** and extend to the inner diameter side from the end portions toward the upstream side and the downstream side, and inner diameter side wall portions **132f** and **132f** that are orthogonal to end portions on the inner diameter side of the center side wall surfaces **132e** and **132e** and extend to the outer diameter side from the end portions toward the upstream side and the downstream side. An end surface of the trap piece **132C** forms the same plane as that of the land **12**, the end surface facing the sliding surface **21** of the rotating seal ring **20**, and the trap piece **132C** is continuous to a bottom surface **152d** of the liquid guide groove portion **152** in the axial direction.

(87) In addition, an end portion on the downstream side of the trap piece **132C** is disposed to overlap and alternate with an end portion on the upstream side of the trap piece **132A** adjacent thereto in the circumferential direction, and an end portion on the upstream side of the trap piece **132C** is disposed to overlap and alternate with an end portion on the downstream side of the trap piece **132B** adjacent thereto in the circumferential direction.

(88) Accordingly, the center side wall surfaces **132b** and **132b** of the trap pieces **132A** and **132B** inclined to the inner diameter side toward an inflow direction of the sealed liquid F, and the low-pressure side wall surfaces **132d** and **132d** and the center side wall surfaces **132e** and **132e** of the trap piece **132C** function as guide surfaces that guide the sealed liquid F to the Rayleigh step **9A** side, and therefore, even when the flow path is narrowed by the trap portion **132**, the trap portion **132** is unlikely to prevent the sealed liquid F from entering the liquid guide groove portion **152**.

(89) In addition, in the trap portion **132**, since the widths between the trap pieces **132A**, **132B**, and **132C** are narrow, surface tension is generated in the sealed liquid F existing between the trap pieces **132A**, **132B**, and **132C**, and the surface tension counters the centrifugal force applied to the sealed liquid F, so that as illustrated with a halftone dot portion, the holding ability to hold the sealed liquid F on the inner diameter side of the trap portion **132** is increased.

(90) In addition, since the inner diameter side wall portions **132f** and **132f** of the trap piece **132C** can trap the sealed liquid F tending to leak from inside the liquid guide groove portion **152** to the atmosphere side, the sealed liquid F can be suitably suppressed from leaking to the atmosphere side.

(91) In addition, the trap piece **132C** is continuous to the bottom surface **152d** of the liquid guide groove portion **152** in the axial direction, so that the rigidity against external force applied in the axial direction is increased. Namely, since the trap piece **132C** extends from the bottom surface **152d** of the liquid guide groove portion **152**, the trap portion **132** having high rigidity can be easily formed.

Sixth Embodiment

(92) Next, a stationary seal ring as a sliding component according to a sixth embodiment of the present invention will be described with reference to FIG. 12. Incidentally, the description of configurations which are the same as and duplicated from those in the second embodiment will be omitted. In addition, here, only the form of a dynamic pressure generating mechanism **144** will be described.

(93) The dynamic pressure generating mechanism **144** includes the Rayleigh step **9A**, the reverse Rayleigh step **9B**, a liquid guide groove portion **153**, and a trap portion **133**. The trap portion **133** includes a plurality of trap pieces **133A** that are disposed at predetermined intervals from the vicinity of an opening portion **153a** of the liquid guide groove portion **153** to the vicinity of an inner diameter side end portion intersecting the Rayleigh step **9A**, a plurality of trap pieces **133B** that are disposed to be axisymmetric with the trap pieces **133A** with respect to an imaginary center line in the radial direction of the liquid guide groove portion **153**, and a plurality of trap pieces **133C** that are disposed in a central portion in the circumferential direction of the liquid guide groove portion **153** in places where the trap pieces **133C** each are surrounded by four trap pieces **133A**, **133A**, **133B**, and **133B** adjacent to each other.

(94) The trap piece **133A** is orthogonal to a downstream wall surface **153b** of the liquid guide groove portion **153** and extends to a central portion side in the radial direction of the liquid guide groove portion **153**. In addition, the trap piece **133C** extends in parallel to the trap pieces **133A** and **133B**.

(95) In addition, in the trap portion **133**, since the widths between the trap pieces **133A**, **133B**, and **133C** are narrow, surface tension is generated in the sealed liquid F existing between the trap pieces **133A**, **133B**, and **133C**, and the surface tension counters the centrifugal force applied to the sealed liquid F, so that as illustrated with a halftone dot portion, the holding ability to hold the sealed liquid F on the inner diameter side of the trap portion **133** is increased.

Seventh Embodiment

(96) Next, a stationary seal ring as a sliding component according to a seventh embodiment of the present invention will be described with reference to FIG. 13. Incidentally, the description of configurations which are the same as and duplicated from those in the second embodiment will be omitted. In addition, here, only the form of a dynamic pressure generating mechanism **145** will be described.

(97) The dynamic pressure generating mechanism **145** includes the Rayleigh step **9A**, the reverse Rayleigh step **9B**, a liquid guide groove portion **154**, and a trap portion **134**. The trap portion **134** includes a trap piece **134A** that is disposed in an opening portion **154a** of the liquid guide groove portion **154** and extends from a downstream wall surface **154b** of the liquid guide groove portion **154** to a center side in the circumferential direction of the liquid guide groove portion **154**, and a trap piece **134B** that is disposed to be axisymmetric with the trap piece **134A** with respect to an imaginary center line of the liquid guide groove portion **154**, the imaginary center line extending in the radial direction.

(98) Accordingly, in the trap portion **134**, since the width between the trap pieces **134A** and **134B** is narrow, surface tension is generated in the sealed liquid F existing between the trap pieces **134A** and **134B**, and the surface tension counters the centrifugal force applied to the sealed liquid F, so that as illustrated with a halftone dot portion, the holding ability to hold the sealed liquid F on the inner diameter side of the trap portion **134** is increased.

(99) In addition, since the trap portion **134** is disposed in the opening portion **154a** of the liquid guide groove portion **154**, the volume of the liquid guide groove portion **154** on the inner diameter side of the trap portion **134** can be suitably secured. Namely, the amount of the sealed liquid F held in the liquid guide groove portion **154** can be secured. Incidentally, the trap portion is disposed in a place near an opening portion which communicates with the low-pressure side rather than the high-pressure side of the liquid guide groove portion including opening portions, so that the amount of

the sealed liquid F held in the liquid guide groove portion can be secured. Regarding the place near the opening portion referred to here, the trap portion may be disposed within one third of the dimension in the radial direction of the liquid guide groove portion from the opening portion, preferably, may be disposed within one fourth of the dimension in the radial direction of the liquid guide groove portion from the opening portion.

Eighth Embodiment

(100) Next, a stationary seal ring as a sliding component according to an eighth embodiment of the present invention will be described with reference to FIG. 14. Incidentally, the description of configurations which are the same as and duplicated from those in the second embodiment will be omitted. In addition, here, only the form of a dynamic pressure generating mechanism **146** will be described.

(101) The dynamic pressure generating mechanism **146** includes a Rayleigh step **92A**, a reverse Rayleigh step **92B**, a liquid guide groove portion **155** that extends from a central portion in the radial direction between the Rayleigh step **92A** and the reverse Rayleigh step **92B** in an outer diameter direction, and a trap portion **135**. The trap portion **135** is formed in a place where an inner diameter side end portion of the liquid guide groove portion **155** intersects the Rayleigh step **92A** and the reverse Rayleigh step **92B**, and is a shallow groove having the same depth dimension as the depth dimension of the Rayleigh step **92A** and the reverse Rayleigh step **92B**. The trap portion **135** communicates with the Rayleigh step **92A**, the reverse Rayleigh step **92B**, and the liquid guide groove portion **155**.

(102) Accordingly, when the rotating seal ring **20** rotates counterclockwise on the drawing sheet as indicated by a solid arrow, in the trap portion **135**, a majority of the sealed liquid F flowing in from the inner diameter side of the trap portion **135** or the reverse Rayleigh step **92B** as indicated by an arrow H10 is suctioned into the Rayleigh step **92A** as indicated by an arrow H11. Therefore, the inflow amount of the sealed liquid F flowing into the liquid guide groove portion **155** due to centrifugal force as indicated by an arrow H12 is reduced. Accordingly, leakage from the liquid guide groove portion **155** to the atmosphere side can be relatively suppressed. Incidentally, although a direct illustration is omitted, the same also applies to when the rotating seal ring **20** rotates clockwise on the drawing sheet, except that the direction of the arrow H11 is an opposite direction.

Ninth Embodiment

(103) Next, a stationary seal ring as a sliding component according to a ninth embodiment of the present invention will be described with reference to FIG. 15. Incidentally, the description of configurations which are the same as and duplicated from those in the second embodiment will be omitted. In addition, here, only the form of a dynamic pressure generating mechanism **147** will be described.

(104) The dynamic pressure generating mechanism **147** includes a Rayleigh step **93A**, a reverse Rayleigh step **93B**, a liquid guide groove portion **156**, and trap portions **136A** and **136B**. The trap portions **136A** and **136B** are deep grooves having the same depth dimension as the depth dimension of the liquid guide groove portion **156**, and are axisymmetrically disposed with respect to an imaginary center line of the liquid guide groove portion **156**, the imaginary center line extending in the radial direction. The trap portion **136A** includes a peripheral portion **136a** that extends from an inner diameter side end portion of the liquid guide groove portion **156** in the circumferential direction at the same curvature as that of the Rayleigh step **93A**, and a radial portion **136b** that communicates with the peripheral portion **136a** and extends in the radial direction. The peripheral portion **136a** of the trap portion **136A** communicates with the Rayleigh step **93A** and the liquid guide groove portion **156**, and the peripheral portion **136a** of the trap portion **136B** communicates with the liquid guide groove portion **156** and the reverse Rayleigh step **93B**.

(105) Accordingly, when the rotating seal ring **20** rotates counterclockwise on the drawing sheet as indicated by a solid arrow, in the trap portions **136A** and **136B**, the sealed liquid F which has leaked

from the reverse Rayleigh step **93B** to the outer diameter side due to centrifugal force flows into the radial portion **136b** of the trap portion **136B** as indicated by a solid arrow **H22**, and the sealed liquid **F** which has leaked from a downstream wall surface **156b** of the liquid guide groove portion **156** to the downstream side in the circumferential direction (left side of the drawing sheet) flows into the radial portion **136b** of the trap portion **136A** as indicated by a solid arrow **H23**. Therefore, leakage from the dynamic pressure generating mechanism **147** to the atmosphere side can be suppressed.

(106) In addition, when the rotating seal ring **20** rotates clockwise on the drawing sheet as indicated by a dotted arrow, in the trap portions **136A** and **136B**, the sealed liquid **F** which has leaked from the Rayleigh step **93A** to the outer diameter side due to centrifugal force flows into the radial portion **136b** of the trap portion **136A** as indicated by a dotted arrow **H20**, and the sealed liquid **F** which has leaked from an upstream wall surface **156c** of the liquid guide groove portion **156** to the downstream side in the circumferential direction (i.e., right side of the drawing sheet) flows into the radial portion **136b** of the trap portion **136B** as indicated by a dotted arrow **H21**. Therefore, leakage from the dynamic pressure generating mechanism **147** to the atmosphere side can be suppressed.

(107) In addition, in the dynamic pressure generating mechanism **147**, since not only the liquid guide groove portion **156** but also the trap portions **136A** and **136B** can hold the sealed liquid **F**, and the sealed liquid **F** can flow into the Rayleigh step **93A** and the reverse Rayleigh step **93B** through the peripheral portions **136a** and **136a**, a larger amount of the sealed liquid **F** can be held.

Tenth Embodiment

(108) Next, a stationary seal ring as a sliding component according to a tenth embodiment of the present invention will be described with reference to FIG. **16**. Incidentally, the description of configurations which are the same as and duplicated from those in the second embodiment will be omitted. In addition, here, only the form of a dynamic pressure generating mechanism **148** will be described.

(109) The dynamic pressure generating mechanism **148** includes the Rayleigh step **9A**, the reverse Rayleigh step **9B**, a liquid guide groove portion **157**, and a trap portion **137**. The trap portion **137** includes trap wall portions **137A** and **137B** including a plurality of protrusions that protrude from a downstream wall surface **157b** and an upstream wall surface **157c** of the liquid guide groove portion **157** to the upstream side and the downstream side facing each other. Incidentally, broken lines in the drawing illustrate imaginary wall surfaces.

(110) The trap wall portions **137A** and **137B** are disposed to alternate with each other with a predetermined interval therebetween, and a meandering groove **30** which meanders continuously while being bent to a downstream wall surface **157b** side and an upstream wall surface **157c** side is formed between the trap wall portions **137A** and **137B**. The trap wall portions **137A** and **137B** are formed such that end surfaces thereof facing the sliding surface **21** of the rotating seal ring **20** are located at a depth position of 10 μm which is deeper than that of the Rayleigh step **9A** and the reverse Rayleigh step **9B**. The trap wall portions **137A** and **137B** are continuous from the end surfaces thereof to a bottom surface **157d** of the liquid guide groove portion **157** in the axial direction, the end surfaces facing the sliding surface **21** of the rotating seal ring **20**. Incidentally, the depth dimension where the end surfaces of the trap wall portions **137A** and **137B** are located, the end surfaces facing the sliding surface **21** of the rotating seal ring **20**, may be, for example, the same dimension as that of the Rayleigh step **9A** and the reverse Rayleigh step **9B**, a smaller dimension than that of the Rayleigh step **9A** and the reverse Rayleigh step **9B**, or a larger dimension, which is not limited to 10 μm , than that of the Rayleigh step **9A** and the reverse Rayleigh step **9B**.

(111) Accordingly, since the meandering groove **30** of the trap portion **137** makes it difficult for the sealed liquid **F** to linearly move from the sealed liquid **F** side toward the atmosphere side, the function of holding the sealed liquid **F** in the liquid guide groove portion **157** can be improved.

(112) In addition, in the trap portion **137**, since the width of the meandering groove **30** is narrowed

by the trap wall portions **137A** and **137B**, surface tension is generated in the sealed liquid **F** existing in the meandering groove **30**, and the surface tension counters the centrifugal force applied to the sealed liquid **F**, so that as illustrated with a halftone dot portion, the holding ability to hold the sealed liquid **F** on the inner diameter side of the trap portion **137** is increased.

Eleventh Embodiment

(113) Next, a stationary seal ring as a sliding component according to an eleventh embodiment of the present invention will be described with reference to FIG. **17**. Incidentally, the description of configurations which are the same as and duplicated from those in the second embodiment will be omitted. In addition, here, only the form of a dynamic pressure generating mechanism **149** will be described.

(114) The dynamic pressure generating mechanism **149** includes a Rayleigh step **94A**, a reverse Rayleigh step **94B**, a liquid guide groove portion **158**, and a trap portion **138**. The trap portion **138** includes a trap wall portions **138A** and **138B** in which protrusions **19** which have a right-angled triangular shape and are inclined from a downstream wall surface **158b** and an upstream wall surface **158c** to a central portion side in the radial direction of the liquid guide groove portion **158** from the outer diameter side toward the inner diameter side are continuously disposed in the radial direction. Incidentally, in the protrusion **19**, an end surface inclined to the central portion side in the radial direction of the liquid guide groove portion **158** from the outer diameter side toward the inner diameter side is an outer diameter side end surface **19a**, and an end surface extending from an end portion of the outer diameter side end surface **19a** toward the downstream wall surface **158b** or the upstream wall surface **158c** is an inner diameter side end surface **19b**, the end portion being located on the central portion side in the radial direction of the liquid guide groove portion **158**.

(115) The trap wall portions **138A** and **138B** are axisymmetrically disposed with respect to a center line in the radial direction of the liquid guide groove portion **158** with a predetermined interval therebetween. In addition, in the trap wall portion **138A**, an end surface of the trap wall portion **138A** forms the same plane as that of the land **12**, the end surface facing the sliding surface **21** of the rotating seal ring **20**.

(116) Accordingly, when the sealed liquid **F** flows into the liquid guide groove portion **158** from the atmosphere side toward the sealed liquid **F** side, the outer diameter side end surface **19a** of the protrusion **19** functions as a guide surface that guides the sealed liquid **F** to a Rayleigh step **94A** side, and therefore, the trap portion **138** is unlikely to prevent the sealed liquid **F** from being recovered into the Rayleigh step **94A**.

(117) In addition, when the sealed liquid **F** flows into the liquid guide groove portion **158** from the sealed liquid **F** side toward the atmosphere side, as illustrated with a halftone dot portion, in the trap portion **138**, the inner diameter side end surface **19b** of the protrusion **19** can trap the sealed liquid **F**. Therefore, the function of holding the sealed liquid **F** in the liquid guide groove portion **158** can be improved.

(118) The embodiments of the present invention have been described above with reference to the drawings; however, the specific configuration is not limited to the embodiments, and the present invention also includes changes or additions that are made without departing from the concept of the present invention.

(119) For example, in the embodiments, as an example of the sliding component, the mechanical seal for a general industrial machine has been described, but the present invention may be applied to other mechanical seals for an automobile, a water pump, and the like. In addition, the present invention is not limited to the mechanical seal, and may be applied to a sliding component such as a slide bearing other than the mechanical seal.

(120) In addition, in the embodiments, an example where the dynamic pressure generating mechanism is provided only in the stationary seal ring has been described; however, the dynamic pressure generating mechanism may be provided only in the rotating seal ring **20**, or may be provided in both the stationary seal ring and the rotating seal ring.

(121) In addition, in the embodiments, a mode in which the sliding component is provided with the plurality of dynamic pressure generating mechanisms having the same shape has been provided as an example; however, a plurality of dynamic pressure generating mechanisms having different shapes may be provided. In addition, the interval between the dynamic pressure generating mechanism, the number of the dynamic pressure generating mechanisms, or the like can be appropriately changed.

(122) In addition, the trap portion may be configured such that the trap portions of the first embodiment and the fourth to eleventh embodiments are appropriately combined, and the configuration of the trap portion may be appropriately changed as long as the configuration can suppress leakage to the low-pressure side.

(123) In addition, in the embodiments, the outside mechanical seal which seals the sealed liquid F tending to leak from the inner diameter side of the sliding surfaces toward the outer diameter side has been described; however, the present invention may be applied to an inside mechanical seal that seals the sealed liquid F tending to leak from the outer diameter side of the sliding surfaces toward the inner diameter side.

(124) In addition, the description has been given based on the premise that the sealed fluid side is a high-pressure side and the leakage side is a low-pressure side; however, the sealed fluid side may be a low-pressure side and the leakage side may be a high-pressure side, or the sealed fluid side and the leakage side may have substantially the same pressure.

REFERENCE SIGNS LIST

(125) **9A** Rayleigh step (shallow groove portion) **9B** Reverse Rayleigh step (shallow groove portion) **10** Stationary seal ring (sliding component) **11** Sliding surface **13** Trap portion **13A, 13B** Trap piece **13a** Low-pressure side wall surface (guide surface) **14** Dynamic pressure generating mechanism **15** Liquid guide groove portion (Deep groove portion) **15a** Opening portion **15b** Downstream wall surface (inner surface) **15c** Upstream wall surface (inner surface) **15d** Bottom surface (inner surface) **19a** Outer diameter side end surface (guide surface) **20** Rotating seal ring (sliding component) **21** Sliding surface **30** Meandering groove **91A to 94A** Rayleigh step (shallow groove portion) **91B to 94B** Reverse Rayleigh step (shallow groove portion) **131 to 138** Trap portion **141 to 149** Dynamic pressure generating mechanism **151 to 158** Liquid guide groove portion (deep groove portion)

Claims

1. A sliding component that has an annular shape and is disposed in a place where relative rotation is performed in a rotary machine, comprising a plurality of dynamic pressure generating mechanisms, wherein the plurality of dynamic pressure generating mechanisms are provided in a sliding surface of the sliding component, each of the dynamic pressure generating mechanisms including a deep groove portion that communicates with an outer diameter side or an inner diameter side, and at least one shallow groove portion that communicates with the deep groove portion and extends in a circumferential direction, the shallow groove portion is shallower than the deep groove portion, the deep groove portion is provided with a trap portion that suppresses leakage of a sealed fluid in the deep groove portion, the deep groove portion is defined by a pair of side wall surfaces opposed to each other in the circumferential direction, and the trap portion has at least one protruded trap piece which is formed in a quadrilateral shape in a plan view and protruded in a radial direction from one of the side wall surfaces of the deep groove portion.
2. The sliding component according to claim 1, wherein the at least one protruded trap piece includes a pair of side wall surfaces parallel to the circumferential direction.
3. The sliding component according to claim 2, wherein the at least one protruded trap piece further includes an end wall surface which is continuous to and between the side wall surfaces of the protruded trap piece, and the end wall surface of the protruded trap piece is parallel to the radial

direction.

4. The sliding component according to claim 1, wherein the at least one trap portion further has at least one isolated trap piece which is inside the deep groove portion and isolated from the protruded trap piece.

5. The sliding component according to claim 1, wherein the at least one protruded trap pieces are arranged on both sides of the deep groove in the circumferential direction, and the isolated trap pieces are shifted from the protruded trap pieces in the radial direction.

6. The sliding component according to claim 5, wherein the at least one protruded trap pieces and the isolated trap pieces are symmetrically disposed with respect to an imaginary center line of the deep groove portion parallel to the radial direction in a plan view.

7. The sliding component according to claim 1, wherein the deep groove portion communicates with the outer diameter side.

8. The sliding component according to claim 1, wherein the deep groove portion communicates with a leakage side.

9. A sliding component that has an annular shape and is disposed in a place where relative rotation is performed in a rotary machine, comprising a plurality of dynamic pressure generating mechanisms, wherein the plurality of dynamic pressure generating mechanisms are provided in a sliding surface of the sliding component, each of the dynamic pressure generating mechanisms including a deep groove portion and at least one shallow groove portion that extends in a circumferential direction, the shallow groove portion is shallower than the deep groove portion, the deep groove portion is provided with a trap portion that suppresses leakage of a sealed fluid in the deep groove portion, the deep groove portion has a wide groove part and a narrow groove part, the wide groove part of the deep groove portion is wider than the narrow groove part in the circumferential direction, the wide groove part of the deep groove portion communicates with the shallow groove portion, the narrow groove part of the deep groove portion communicates with an outer diameter side or an inner diameter side of the sliding component, the wide groove part of the deep groove portion is defined by a pair of side wall surfaces opposed to each other in the circumferential direction, part of the pair of side wall surfaces extends from a bottom surface of the wide groove part to the sliding surface, and the trap portion is formed by a land portion which defines the narrow groove part of the deep groove portion.

10. The sliding component according to claim 9, wherein the pair of side wall surfaces defining the wide groove part of the deep groove portion is a pair of first side wall surfaces the narrow groove part of the deep groove portion is defined by a pair of second side wall surfaces opposed to each other in the circumferential direction, the deep groove portion is partially defined by a pair of third side wall surfaces connecting the first side wall surfaces to the second side wall surfaces.

11. The sliding component according to claim 10, wherein the first side wall surfaces and the second side wall surfaces are parallel to a radial direction, and the third side wall surfaces are parallel to the circumferential direction.

12. The sliding component according to claim 9, wherein the deep groove portion communicates with the outer diameter side.

13. The sliding component according to claim 9, wherein the deep groove portion communicates with a leakage side.

14. A sliding component that has an annular shape and is disposed in a place where relative rotation is performed in a rotary machine, comprising a plurality of dynamic pressure generating mechanisms, wherein the plurality of dynamic pressure generating mechanisms are provided in a sliding surface of the sliding component, each of the dynamic pressure generating mechanisms including a deep groove portion that communicates with an outer diameter side or an inner diameter side, and at least one shallow groove portion that communicates with the deep groove portion and extends in a circumferential direction, the shallow groove portion is shallower than the deep groove portion, the deep groove portion is provided with a trap portion that suppresses

leakage of a sealed fluid in the deep groove portion, the trap portion has at least four trap pieces which are continuously formed in a radial direction, each of the trap pieces is formed in a triangle shape in a plan view, each of the trap pieces is defined by a first side wall surface which extends from a side wall surface of the deep groove portion toward a center of circumferential width of the deep groove portion, a second side wall surface which is disposed on a leakage side with respect to the first side wall surface, and a connecting surface which extends in parallel to the sliding surface and connects the first side wall surface and the second side wall surface, and at least part of the connecting surface is flush with a bottom surface of the shallow groove portion, wherein at least two of the at least four trap pieces are disposed facing one another, and at least two other of the at least four trap pieces are radially spaced apart from one another.

15. The sliding component according to claim 14, wherein the first side wall surface of each of the trap pieces is parallel to the circumferential direction, the second side wall surface of each of the trap pieces is inclined with respect to the circumferential direction, and the connecting surface partially defining each of the trap pieces is formed in a triangle shape.

16. The sliding component according to claim 14, wherein the trap pieces are arranged throughout from the outer diameter side of the deep groove portion and to the inner diameter side of the deep groove portion.

17. The sliding component according to claim 14, wherein the trap pieces are arranged both sides of the deep groove portion in the circumferential direction.

18. The sliding component according to claim 17, wherein the trap pieces are symmetrically disposed with respect to an imaginary center line of the deep groove portion parallel to the radial direction in a plan view.

19. The sliding component according to claim 14, wherein the deep groove portion communicates with the outer diameter side.

20. The sliding component according to claim 14, wherein the deep groove portion communicates with a leakage side.
