

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12385938
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Zhang; Zhen

Sample dilution method and immunoassay method

Abstract

A sample dilution method. The method comprises the following steps: moving from an initial workstation to a first workstation a ferrying unit bearing a first reactor containing a sample; distributing a diluent into the first reactor located at the first workstation; mixing the diluent and the sample in the first reactor to form a diluted sample; moving to a second workstation the ferrying unit bearing the first reactor containing the diluted sample, and distributing into at least two empty second reactors the diluted sample from the first reactor; moving to the first workstation the ferrying unit bearing all the second reactors containing a diluted sample, and distributing a reagent into the second reactors located at the first workstation; and mixing the reagent and the diluted sample in the second reactor.

Inventors:	Zhang; Zhen (Shenzhen, CN)
Applicant:	SHENZHEN INCRECARE BIOTECH CO. LTD (Shenzhen, CN)
Family ID:	71841147
Assignee:	SHENZHEN INCRECARE BIOTECH CO. LTD (N/A, CN)
Appl. No.:	17/427883
Filed (or PCT Filed):	April 11, 2019
PCT No.:	PCT/CN2019/082178
PCT Pub. No.:	WO2020/155389
PCT Pub. Date:	August 06, 2020

Prior Publication Data

Document Identifier	Publication Date
US 20220120772 A1	Apr. 21, 2022

Foreign Application Priority Data

Publication Classification

Int. Cl.: **G01N35/10** (20060101); **G01N1/38** (20060101); **G01N33/531** (20060101); **G01N35/00** (20060101)

U.S. Cl.:

CPC **G01N35/1002** (20130101); **G01N1/38** (20130101); **G01N33/531** (20130101); **G01N35/0092** (20130101); G01N2035/00465 (20130101)

Field of Classification Search

USPC: None

References Cited**U.S. PATENT DOCUMENTS**

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5882594	12/1998	Kawaguchi	422/65	G01N 35/025
6786235	12/2003	Liang	N/A	N/A
6947126	12/2004	Grant et al.	N/A	N/A
2003/0174306	12/2002	Grant et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
1826218	12/2005	CN	N/A
101675170	12/2009	CN	N/A
201607358	12/2009	CN	N/A
104076160	12/2013	CN	N/A
104730268	12/2014	CN	N/A
106645765	12/2016	CN	N/A
106706942	12/2016	CN	N/A
207816996	12/2017	CN	N/A
207866716	12/2017	CN	N/A
H01257267	12/1988	JP	N/A
H052022	12/1992	JP	N/A
H1062432	12/1997	JP	N/A

OTHER PUBLICATIONS

International Search Report for PCT/CN2019/082178 with English Translation mailed Nov. 1, 2019, 5 pages. cited by applicant

Primary Examiner: Wright; P. Kathryn

Attorney, Agent or Firm: Dickinson Wright PLLC

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION

(1) The present is a national phase application of International Application No. PCT/CN2019/082178, filed on Apr. 11, 2019, which claims the priority of the Chinese patent application filed with the Chinese Patent Office on Feb. 2, 2019, with the filing number of No. 201910107354.9, and the title of “Sample Dilution Method and Immunoassay Method,” the entire contents thereof being incorporated herein by reference.

TECHNICAL FIELD

(2) The present disclosure relates to the technical field of in-vitro diagnostics, in particular to a sample dilution method and an immunoassay method containing respective steps in the sample dilution method.

BACKGROUND ART

(3) The full-automatic immunity analyzer can perform quantitative or qualitative detection on target analyte such as antibody and antigen contained in a sample to be tested such as blood. Generally, an empty reactor is dispensed with the sample to be tested and a reagent (or called as reactant), and after steps such as uniformly mixing, incubating, cleaning and separating (bound-free, i.e. BF separating), a signal reagent is dispensed into the reactor so as to measure an optical signal or an electrical signal, thus realizing measurement and analysis of the target analyte contained in the sample to be tested.

(4) An important parameter for evaluating the operation efficiency of the immunity analyzer is test throughput, where the test throughput may be understood as the number of test results, i.e. the number of measured reactors containing the target analyte, that can be reported by the immunity analyzer in unit time, and the more the total number of reactors measured in unit time is, the higher the test throughput of the immunity analyzer is. As a reaction mode and a test flow of analytical items are usually different, the test throughput of the immunity analyzer is not unchanged, and the maximum test throughput is usually taken as the measurement standard of test speed of the immunity analyzer. In the present disclosure, for convenience of description, unless otherwise specified, the test throughput specifically refers to the maximum test throughput of the analyzer. The treatment of the immunity analyzer on the reactor is regarded as a pipeline, if N reactors containing the target analyte complete the measurement in unit time and leave the pipeline, in order to ensure that the test is performed continuously and reliably according to the maximum throughput, there also must be N empty reactors entering the pipeline within the same period of time, that is, a flow rate (inlet flow rate) of the reactor at an inlet of the pipeline is equal to a flow rate (outlet flow rate) at an outlet. By the same reasoning, in order to ensure seamless and continuous connection of the whole pipeline, the flow rate of the reactor in each stage of the pipeline should be equal to the inlet flow rate and the outlet flow rate, that is, the flow rate of the pipeline is equal everywhere.

(5) Generally, before the sample and the reagent are uniformly mixed, the sample must be diluted first, while the dilution process takes more time, so that the flow rate of the reactor in the dilution stage is relatively low, thereby becoming a bottleneck and a shortcoming that affect the operation efficiency, and causing it difficult for the immunity analyzer to meet the requirements of higher test throughput.

SUMMARY

(6) One technical problem solved by the present disclosure is how to improve the operation efficiency of a sample dilution method.

(7) A sample dilution method, including the following steps: moving a ferrying unit bearing a first reactor already containing a sample from an initial position to a first position; dispensing a diluent

into the first reactor located at the first position; uniformly mixing the sample and the diluent in the first reactor so as to form a diluted sample; moving the ferrying unit bearing the first reactor containing the diluted sample to a second position, and dispensing the diluted sample in the first reactor into at least two empty second reactors; moving the ferrying unit bearing all the second reactors containing the diluted sample to the first position, and dispensing the reagent into the second reactors located at the first position; and uniformly mixing the diluted sample and the reagent in the second reactors.

(8) An immunoassay method, including the steps in the above sample dilution method.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) In order to more clearly illustrate technical solutions in embodiments of the present disclosure or the prior art, accompanying drawings which need to be used in the description of the embodiments or the prior art will be introduced briefly below, and apparently, the accompanying drawings in the description below merely show some embodiments of the present disclosure, and those ordinarily skilled in the art still could obtain other accompanying drawings in light of these accompanying drawings, without using inventive efforts.

(2) FIG. 1 is a plane structural schematic view of a first exemplary immunity analyzer provided in a first embodiment.

(3) FIG. 2 is a partial perspective structural schematic view containing a ferrying unit in FIG. 1.

(4) FIG. 3 is a plane structural schematic view of a second exemplary immunity analyzer provided in the first embodiment.

(5) FIG. 4 is a plane structural schematic view of a third exemplary immunity analyzer provided in the first embodiment.

(6) FIG. 5 is a plane structural schematic view of an immunity analyzer provided in a second embodiment.

(7) FIG. 6 is a schematic diagram of continuously dispensing the same sample into at least two reactors.

(8) FIG. 7 is a timing diagram of dispensing a sample and a reagent into a reactor.

(9) FIG. 8 is a schematic diagram of providing a diluted sample to at least two reactors.

(10) FIG. 9 is a block flowchart of a first liquid dispensing method.

(11) FIG. 10 is a block flowchart of a second liquid dispensing method.

(12) FIG. 11 is a block flowchart of a sample dilution method.

(13) FIG. 12 is a block flowchart of a third liquid dispensing method.

(14) FIG. 13 is a timing diagram of dispensing a sample and a reagent into a reactor in the third liquid dispensing method.

DETAILED DESCRIPTION OF EMBODIMENTS

(15) In order to facilitate understanding the present disclosure, the present disclosure will be described more comprehensively below with reference to relevant accompanying drawings.

Preferred embodiments of the present disclosure are given in the accompanying drawings.

However, the present disclosure may be implemented in many different forms, but not limited to the embodiments described herein. In contrast, these embodiments are provided for the purpose of making the contents disclosed in the present disclosure more thorough and more comprehensive.

(16) It should be noted that when an element is “fixed to” another element, it may be directly on the another element or there may be an intermediate element therebetween. When an element is considered “connected to” another element, it may be directly connected to the another element or there may be an intermediate element therebetween. Terms used herein such as “inner”, “outer”, “left”, “right” and the similar description are merely for illustrative purpose, rather than

representing a unique embodiment.

(17) Referring to FIG. 1 to FIG. 8 together, incubation of sample and reagent (or called as reactant) refers to a process of antigen-antibody binding reaction or biotin-avidin binding reaction of reactants in a reactor **20** in a constant temperature environment before bound-free is started. The reagent and analytical item herein are in a “one-to-one correspondence” relationship, that is, specific reagents corresponding to different analytical items are generally different in terms of formula, reagent volume, component quantity, and the like. Depending on different specific analytical items, the reagent typically includes multiple components, such as the usual 2-5 components, including reagent components such as magnetic particle, marker, diluent, and dissociating agent (respective corresponding reagent components may be represented by R1, R2, R3, and R4, respectively). For example, T4 reagent (thyroxine) includes three components, namely, magnetic particle (R1), marker (R2), and dissociating agent (R4). According to different reaction modes, multiple reagent components of one analytical item may be dispensed at one time or may be dispensed in multiple steps, and when the reagent components are dispensed in multiple steps, a first reagent, a second reagent, a third reagent, and so on are defined according to a dispensing order. After the incubation is completed, bound-free is carried out, where the bound-free refers to a process of capturing bound magnetic particles and labeled complexes with a magnetic field, and meanwhile removing free markers and other unreacted or unbound ingredients (unbound ingredients for short herein for convenience of description). After the bound-free, a signal reagent is dispensed to perform signal incubation (generally for 1-6 minutes), and finally a luminescence amount (reactant signal for short herein for convenience of expression) generated by reaction of a labeled reagent with the signal reagent is measured. The signal reagent is used for measuring the generation of signal (usually the luminescence amount), is usually a kind of common reagent, and has a “one-to-many” correspondence relationship with the analytical item, that is, different analytical items share one signal reagent. Signal incubation refers to a process of reacting in a constant temperature environment for a period of time after the signal reagent is dispensed into the reactor **20** after bound-free, to enhance the signal. It should be noted that, due to different specific components of the signal reagent, some luminous systems do not need signal incubation, and can directly measure in the process of dispensing the signal reagent or after dispensing the signal reagent. The signal reagent may be one or more, for example, some signal reagents include a first signal reagent, a second signal reagent, and so on. In an immunoassay device, the antigens or antibodies contained in the sample bound to the labeled reagent are quantitatively or qualitatively determined through the above process. Besides, an immunity analyzer **10** can perform an analysis corresponding to several different analytical items on a sample.

(18) Operation period or cycle, period for short, is the shortest time window that can be cyclically reproduced in the test process, and it usually has a fixed length of time, and within the time of period, a certain number of process operations, tasks or work packages, and the like, such as operations and tasks of taking liquid, uniformly mixing, incubating, bound-free and measuring, are executed serially or in parallel in a controlled order. The tasks of the same component in one period are usually executed serially, and the tasks of different components in the same period may be executed serially or in parallel depending on whether actions of relevant components have a dependency relationship. All process operations executed in one period are executed only when needed, and not necessarily repeated in another period. In particular, some process operations may appear repeatedly in each period, while other process operations may occur every two or more periods. When multiple tests are performed in succession, since each test is usually at a different stage of the test procedure, among all process operations that occur in a single period, only some process operations are dedicated to executing a test, and other process operations are used for executing other tests. In order to improve the test efficiency and throughput, for components having a speed bottleneck, the number of components may be increased and the period of the components may be prolonged to improve the test efficiency and throughput, so that the operation periods of

different components are not necessarily the same, that is, there may be multiple parallel periods in the same system. Generally, time lengths of multiple parallel periods have a multiple (fold) relationship, with the multiple usually being equal to the number of the same component. When there are two operation periods, they are called as a first period and a second period, respectively, for example, when the number of ferrying units **200** is N ($N \geq 2$, being a natural number), each ferrying unit **200** operates in the first period, the duration of the first period is N times that of the second period, and a sequences of actions of the N ferrying units **200** are continuously “in parallel in a manner of being staggered” by the second period.

(19) It should be noted that not all components or operations run according to the operation period, while some components or operations, of which the operation processes have no effect on the test performance or test result, may not run according to a fixed period, for example, supply of the reactor **20** may not have a fixed operation period.

(20) Referring to FIG. 1 to FIG. 5, the immunity analyzer **10** provided in an embodiment of the present disclosure includes a liquid dispensing device **11** and a reaction device **12**, wherein the liquid dispensing device **11** is located beside the reaction device **12**, and the liquid dispensing device **11** is configured to complete in the reactor **20** the dispensing of a sample and a reagent, and the uniform mixing of the sample and the reagent. The reaction device **12** is configured to perform incubation, bound-free, and measurement for the sample and the reagent (reactants) uniformly mixed in the reactor **20**.

(21) The liquid dispensing device **11** includes a buffer unit **100**, a supply silo **130**, a supply slide **140**, a ferrying unit **200**, a sample adding member **300**, a sample conveying unit **400**, a reagent dispensing member **500**, a storage unit **600**, a transfer unit **700**, a washing tank **800**, and a sorting mechanism. Certainly, the liquid dispensing device **11** may also include a sample adding drive unit **301** and a reagent drive unit **501**, as well as a sample adding power device and a reagent dispensing power device, the sample adding member **300** is installed on the sample adding drive unit **301**, and the sample adding drive unit **301** is configured to drive the sample adding member **300** to move so that the sample adding member **300** draws or discharges the sample under the action of the sample adding power device. The reagent dispensing member **500** is installed on the reagent drive unit **501**, and the reagent drive unit **501** is configured to drive the reagent dispensing member **500** to move so that the reagent dispensing member **500** draws or discharges the reagent under the action of the reagent dispensing power device. The sample adding power device and the reagent dispensing power device may adopt all-purpose fluid quantitative devices such as syringe, plunger pump, and dosing pump.

(22) The sample conveying unit **400** may include a sample rack **410**, a sample tube **430**, and a conveying track **420**. The sample rack **410** may cooperate with the conveying track **420**, the sample tube **430** is placed on the sample rack **410**, and the sample tube **430** is configured to hold the sample, for example, about five to ten sample tubes **430** may be placed on each sample rack **410**. When the sample rack **410** drives the sample tube **430** to move along the conveying track **420** to a designated position, the sample adding member **300** draws the sample in the sample tube **430**, and dispenses the sample into the empty reactor **20**.

(23) The supply silo **130** is configured to store clean and empty reactors **20**. The sorting mechanism may be configured to arrange the reactors **20** placed in disorder from the supply silo **130** so as to sort them in a certain order. The supply slide **140** introduces the sorted reactors **20** into the buffer unit **100** one by one, and the buffer unit **100** is configured to buffer the reactors **20** conveyed by the supply slide **140**.

(24) Referring to FIG. 1, in some embodiments, the whole liquid dispensing device **11** has a receiving position **33**, a sample adding position **34**, and a removing position **35**. The buffer unit **100** includes a turntable **110**. The turntable **110** can rotate around its own central axis. A plurality of buffer positions **101** are provided on the turntable **110**, and the buffer positions **101** are configured to carry the reactors **20**. The buffer positions **101** may be accommodating holes, and certainly, the

accommodating holes may also be replaced by solid structures such as brackets, as long as the reactors **20** can be placed on the turntable **110**. The buffer positions **101** are distributed at intervals along a circumferential direction of the turntable **110**. When the turntable **110** rotates, it can drive the buffer positions **101** to move between the receiving position **33**, the sample adding position **34**, and the removing position **35**, so that the reactor **20** on the turntable **110** moves between the receiving position **33**, the sample adding position **34**, and the removing position **35**. Obviously, the turntable **110** drives the reactor **20** to make circular movement between the receiving position **33**, the sample adding position **34**, and the removing position **35**.

(25) Specifically, the reactor **20** from the supply slide **140** will enter the buffer position **101** on the turntable **110** at the receiving position **33**. When the turntable **110** drives an empty reactor **20** to move to the sample adding position **34**, the sample adding member **300** may draw the sample from the sample tube **430** so as to dispense the sample into the reactor **20**. When the turntable **110** drives the reactor **20** already containing the sample to continue to move to the removing position **35**, the transfer unit **700** will remove the reactor **20** already containing the sample from the turntable **110** at the removing position **35** and transfer the reactor to the ferrying unit **200**.

(26) The buffer positions **101** are arranged at intervals along the circumferential direction of the turntable **110**. The buffer units **100** may only be arranged to form one buffer circle, which is provided close to an edge of the turntable **110**. Certainly, the buffer positions **101** may also be arranged to form a plurality of buffer circles, and the plurality of buffer circles are concentrically arranged around the central axis of the turntable **110**.

(27) Referring to FIG. 3, in some embodiments, the buffer unit **100** includes a sliding block **120**, the sliding block **120** is also provided with the buffer positions **101** for placing the reactor **20**, and the buffer positions **101** on the sliding block **120** may also be accommodating holes. The buffer positions **101** may be only distributed at intervals along a straight line on the sliding block **120** to form a row. Certainly, the buffer positions **101** may be distributed at intervals on the sliding block **120** along a straight line to form multiple rows, in this case, the multiple rows of buffer positions **101** are distributed and arranged on the sliding block **120** in a matrix form. The sliding block **120** makes linear movement between the receiving position **33**, the sample adding position **34**, and the removing position **35**, so as to drive the buffer positions **101** (corresponding to the reactors **20**) thereon to move between the receiving position **33**, the sample adding position **34**, and the removing position **35**. Similarly, referring to the above operation mode of the turntable **110**, the reactor **20** enters the sliding block **120** at the receiving position **33**, the sample adding member **300** dispenses the sample into the reactor **20** located at the sample adding position **34**, and the transfer unit **700** will remove the reactor **20** already containing the sample from the sliding block **120** at the removing position **35** and transfer the reactor to the ferrying unit **200**. In this embodiment, the sliding block **120** and the buffer positions **101** thereon reciprocate linearly between the receiving position **33**, the sample adding position **34**, and the removing position **35** to complete the receipt of the reactor **20**, sample dispensing, and removal of the reactor **20** already containing the sample. The volume of the sliding block **120** itself may be designed to be smaller, meanwhile, an area of a region covered by a linear movement trajectory of the sliding block **120** is small, which is beneficial to optimized space layout of the supply silo **130**, the supply slide **140**, the sample conveying unit **400**, the sample adding member **300**, the transfer unit **700** and so on, can make the liquid dispensing device **11** more compact, and has a lower cost.

(28) Referring to FIG. 4, in some embodiments, the buffer unit **100** includes both the turntable **110** and the sliding block **120** each provided with the buffer positions **101**, the turntable **110** rotates around its own central axis, the turntable **110** can drive the buffer positions **101** thereon to pass through the receiving position **33**, and the reactor **20** on the supply slide **140** will enter the buffer position **101** on the turntable **110** at the receiving position **33**. The sliding block **120** makes linear movement between the sample adding position **34** and the removing position **35**. When the turntable **110** drives the empty reactor **20** to rotate by a set angle from the receiving position **33**, the

transfer unit **700** may remove the empty reactor **20** from the turntable **110** and transfer the empty reactor to the sliding block **120** located at the removing position **35**. When the sliding block **120** drives the reactor **20** to move to the sample adding position **34**, the sample adding member **300** dispenses the sample into the empty reactor **20**, subsequently, after the sliding block **120** drives the reactor **20** containing the sample to move to the removing position **35**, the transfer unit **700** removes the reactor **20** containing the sample from the sliding block **120** at the removing position **35** and transfers the reactor to the ferrying unit **200**.

(29) Referring to FIG. 2, in some embodiments, the liquid dispensing device **11** further includes a frame **210**, a conveyor **220**, a support **230**, and a driver **240**. The conveyor **220** is provided on the frame **210**. The conveyor **220** is configured to drive the support **230** to slide relative to the frame **210**. The conveyor **220** includes a motor **221**, a driving wheel **222**, a driven wheel **223**, and a synchronous belt **224**. The motor **221** is configured to drive the driving wheel **222** to rotate. The synchronous belt **224** is wound on the driving wheel **222** and the driven wheel **223**, and when the motor **221** rotates, the driving wheel **222** and the driven wheel **223** drive the synchronous belt **224** to move. Certainly, in other embodiments, the conveyor **220** may also be replaced by one or several of transmission mechanisms such as screw rod mechanism, and gear-rack.

(30) Specifically, the frame **210** may be provided with a sliding rail **225**, the support **230** cooperates with the sliding rail **225**, the synchronous belt **224** is connected to the support **230** and drives the support **230** to slide along an extending direction of the sliding rail **225**, the driver **240** and the ferrying unit **200** are both provided on the support **230**, the ferrying unit **200** is configured to place the reactor **20**, and the driver **240** can drive the ferrying unit **200** to generate eccentric oscillation, so that the sample and the reagent (reactants) in the reactor **20** are uniformly mixed due to the generation of non-contact eccentric oscillation.

(31) A plurality of receiving holes may be provided on the ferrying unit **200**, and the reactors **20** are inserted into the receiving holes, so as to realize the bearing effect of the ferrying unit **200** on the reactors **20**. Certainly, the receiving holes may also be replaced by solid structures such as brackets, as long as the reactors **20** can be placed on the ferrying unit **200**.

(32) In some embodiments, the whole liquid dispensing device **11** further has an initial position **30** and a first position **31**, and when the motor **221** runs, the ferrying unit **200** can be enabled to make linear reciprocation between the initial position **30** and the first position **31**. When the ferrying unit **200** is located at the initial position **30**, the transfer unit **700** may transfer the reactor **20** containing the sample from the buffer unit **100** to the ferrying unit **200** located at the initial position **30**. Then, the ferrying unit **200** drives the reactor **20** containing the sample to move to the first position **31**, and the reagent dispensing member **500** will draw the reagent from the storage unit **600** for storing the reagent, and dispense the reagent into the reactor **20** located at the first position **31**. Then, in the process of linear movement of the ferrying unit **200**, the driver **240** may drive the ferrying unit **200** to generate eccentric oscillation, so as to uniformly mix the sample and the reagent in the reactor **20**, in this way, the uniform mixing of the reactants and the movement of the ferrying unit **200** may be performed in parallel, that is, the ferrying unit **200** can uniformly mix the reactants in the reactor **20** while moving, thus improving the efficiency and effect of the uniform mixing, thereby increasing the test throughput of the whole device. Certainly, when the ferrying unit **200** is stationary before and after movement, the driver **240** may also drive the ferrying unit **200** to generate eccentric oscillation so as to uniformly mix the sample and the reagent in the reactor **20**. The ferrying unit **200** returns the reactor **20** having been dispensed with the reagent to the initial position **30**, and the transfer unit **700** may remove the reactor **20**, in which the reactants have been uniformly mixed, from the ferrying unit **200** at the initial position **30**, and transfer the reactor to the reaction device **12**, so that the reactor **20** performs incubation, bound-free, and measurement treatments on the reaction device **12**.

(33) It can thus be seen that the driver **240** directly generates eccentric oscillation for the ferrying unit **200**, so that the reactants in the reactor **20** on the ferrying unit **200** are uniformly mixed,

without an additional separate mixing device, the linear movement or stationary state of the ferrying unit **200** does not limit the uniform mixing of the reactants in the reactor **20**, then the problems such as complexity, low mixing efficiency, and poor mixing effect of the prior mixing device are solved. In addition, the ferrying unit **200** makes linear movement between the sample adding member **300**, the transfer unit **700**, and the reagent dispensing member **500**. On one hand, the control difficulty of the linear movement is reduced, so that the ferrying unit **200** moves more accurately and efficiently, the ferrying unit **200** is prevented from deviating from a specified stop position, the ferrying unit **200** can be ensured to be accurately and timely stopped at the initial position **30** or the first position **31**, the reactor **20** containing the sample can be ensured to be smoothly transferred to the ferrying unit **200** at the initial position **30**, and the reagent dispensing member **500** can also be ensured to reliably add the reagent into the reactor **20** at the first position **31**; on the other hand, the reactor **20** containing the sample is carried on the buffer unit **100** so as to wait to be transferred to the ferrying unit **200** and added with the reagent, which is then mixed uniformly, without the need of transferring all the reactors **20** containing the sample to the ferrying unit **200**, thus, the bearing space of the buffer unit **100** is fully utilized, so that the number of reactors **20** simultaneously carried by the ferrying unit **200** is reduced, ensuring the volume of the ferrying unit **200** to be designed smaller, and the structure to be more compact; meanwhile, an area of a region covered by the linear movement trajectory of the ferrying unit **200** is small, which overcomes the limitation that the sample adding member **300**, the transfer unit **700**, and the reagent dispensing member **500** in the prior art must be arranged along a large-radius rotation or rotary disk, optimizes the space layout and the control flow of components or units, can more efficiently connect and coordinate logic actions among the sample adding member **300**, the transfer unit **700**, and the reagent dispensing member **500**, which not only enables the immunity analyzer to be more compact, but also improves the overall operation efficiency.

(34) By dispensing the sample into the reactor **20** on the buffer unit **100**, transferring the reactor **20** having been dispensed with the sample to the ferrying unit **200** to be dispensed with the reagent and uniformly mixing the resultant, the dispensing of the sample and the dispensing of the reagent are realized on different separate units, respectively, and the uniform mixing is directly realized on the ferrying unit, so that the problem that the dispensing of the sample and the dispensing of the reagent are mutually restricted and the problem that the reactants are uniformly mixed separately at a specific position in the prior art are solved, thus improving the efficiency of liquid dispensing and uniform mixing.

(35) In some embodiments, the storage unit **600** is a rotatable disk, the storage unit **600** is provided close to the first position **31**, a plurality of storage portions **610** are provided on the storage unit **600**, the storage portions **610** are configured to place and store a reagent container, the reagent is stored in the reagent container, and the reagent dispensing member **500** is configured to draw the reagent components in the reagent container on the storage portion **610**, and dispense the reagent components into the reactor **20** located at the first position **31**. The number of storage portions **610** may be set according to needs, and the number of storage portions **610** on each storage unit **600** is preferably 15-50 taking use requirements, cost, and layout into consideration, for example, the number of storage portions **610** on each storage unit **600** is 25, in this way, two storage units **600** may store 50 reagent containers in total on line simultaneously. Each storage unit **600** stores all the reagent components required for corresponding analytical item, for example, in one analytical item, three reagent components, i.e. magnetic particle, marker, and dissociating agent, have to be dispensed into the reactor **20**, then the three components, i.e. the magnetic particle, marker, and dissociating agent, are placed on the same storage unit **600**. When a certain analytical item needs to be loaded with a plurality of reagent containers so as to expand a test amount of the item on a machine, the plurality of reagent containers may be stored in each storage unit **600** in any suitable combination. For example, when the number of storage units **600** is two, three TSH (thyroid stimulating hormone) reagent containers each containing 100 tests need to be loaded, and three

TSH reagent containers may be all loaded in the same storage unit **600**, or one TSH reagent container may be loaded in one of the storage units **600**, and the other two TSH reagent containers are loaded in another storage unit **600**. When the storage unit **600** rotates intermittently, the storage portion **610** may be driven to move to a designated liquid-drawing position, so that the reagent dispensing member **500** draws the reagent on the storage portion **610** at the liquid-drawing position and dispenses the reagent into the reactor **20**.

(36) In the process of rotation (revolution) of the storage portions **610** with the storage unit **600**, at least one cavity (such as a magnetic particle cavity holding the magnetic particle reagent components) of the reagent container on the storage portion **610** spins around its own central axis, so that the magnetic particle reagent components existing in a form of solid suspension generate vortex, thereby avoiding precipitation of solid matters (such as magnetic particles) therein. The storage unit **600** may be further provided with a scanner, and the scanner may identify bar code information of the reagent container on the storage portion **610**, so as to distinguish different reagents. The storage unit **600** may further be provided with a refrigerator, and the refrigerator may perform refrigeration processing for the reagent in the storage portion **610**, so as to realize long-term on-line storage of the reagent.

(37) The transfer unit **700** is configured to transfer the reactor **20** between the ferrying unit **200**, the buffer unit **100**, and the reaction device **12**, and the transfer unit **700** may make horizontal movement and vertical movement. Obviously, the removing position **35** and the initial position **30** are both located on the movement trajectory of the transfer unit **700**.

(38) When the liquid dispensing device **11** is adopted to dispense the sample and the reagent into the reactor **20**, and uniformly mix the sample and the reagent, a first liquid dispensing method may be formed, wherein the first liquid dispensing method is mainly characterized in that the sample is dispensed from the buffer unit **100** (not from the ferrying unit **200**) into the reactor **20**. Referring to FIG. **9**, the first liquid dispensing method mainly includes the following steps.

(39) S**510**, providing a buffer unit **100** configured to receive the reactors **20** and drive the reactors **20** to move, and dispensing a sample into an empty reactor **20** located on the buffer unit **100**.

(40) S**520**, making the ferrying unit **200** stop at the initial position **30**, and transferring the reactor **20** having been dispensed with the sample from the buffer unit **100** to the ferrying unit **200** located at the initial position **30**.

(41) S**530**, making the ferrying unit **200** move between the initial position **30** and the first position **31**, and dispensing the reagent into the reactor **20** located at the first position **31**, wherein certainly, the ferrying unit **200** may be enabled to make linear movement between the initial position **30** and the first position **31**, and wherein the sample can be dispensed into the empty reactor **20** on the buffer unit **100** while the ferrying unit **200** carrying the reactor **20** having been dispensed with the sample is moving or stationary.

(42) S**540**, making the ferrying unit **200** uniformly mix the sample and the reagent after the reagent is dispensed into the reactor **20**, wherein the ferrying unit **200** may uniformly mix the reactants in the reactor **20** in a manner of non-contact eccentric oscillation, thereby eliminating carryover contamination of other contact-type stirring on the reactants, and in order to increase the test throughput, the ferrying unit **200** may be enabled to uniformly mix the sample and the reagent in the reactor **20** during movement from the first position **31** to the initial position **30**.

(43) S**550**, making the ferrying unit **200** stop at the initial position **30**, and after uniformly mixing the sample and the reagent, by the transfer unit **700**, removing the reactor **20** from the ferrying unit **200** at the initial position **30**, and transferring the reactor to the reaction device **12**.

(44) In the first liquid dispensing method, a shortest time window, in which a sequence of actions in the above steps S**520**, S**530**, S**540**, and S**550** executed by the ferrying unit **200** can be cyclically reproduced, is recorded as operation period T, and the ferrying unit **200** is allowed to, within one operation period T, receive the reactor **20** having been dispensed with the sample at the initial position **30**, linearly move to the first position **31** to undergo dispensing of the reagent into the

reactor **20**, uniformly mix the reactants in the reactor **20**, and linearly move to the initial position **30** to make the reactor **20** leave.

(45) A time interval between continuously dispensing the sample into at least two empty reactors **20** located on the buffer unit **100** is recorded as a sample dispensing interval t , wherein $t=T$ or there is at least one t , and $t<T$. When $t=T$, in the interval of each operation period T , the sample is dispensed once into the empty reactor **20** located on the buffer unit **100**. In particular, when $t<T$, in the interval of the operation period T , the sample is dispensed more than once into the empty reactor **20** located on the buffer unit **100**. When there is at least one t , and $t<T$, the time for dispensing the sample into the empty reactor **20** located on the buffer unit **100** is not fixed, and may not be limited by the operation period T , and the interval of dispensing the sample is determined according to the needs of test, making the test more flexible and more efficient.

(46) In the first liquid dispensing method, the sample is dispensed only from the buffer unit **100** into the reactor **20**, but not from the ferrying unit **200** into the reactor **20**, in this way, the time for dispensing the sample from the ferrying unit **200** into the reactor **20** can be saved, thus improving the operation efficiency of the liquid dispensing device. In some embodiments, when the buffer unit **100** only includes the turntable **110** making circular movement or only includes the sliding block **120** making linear movement, the step of dispensing the sample into the buffer unit **100** includes the following sub-steps: inputting the reactor **20** from the receiving position **33** to the buffer unit **100**; making the reactor **20** move with the buffer unit **100** from the receiving position **33** to the sample adding position **34**, and dispensing the sample into the reactor **20** located at the sample adding position **34**; and making the reactor **20** move with the buffer unit **100** from the sample adding position **34** to the removing position **35**, wherein the reactor **20** can be transferred from the removing position **35** to the ferrying unit **200**.

(47) In some embodiments, when the buffer unit **100** includes both the turntable **110** making the circular movement and the sliding block **120** making the linear movement, the step of dispensing the sample into the buffer unit **100** includes the following sub-steps: inputting the reactor **20** from the receiving position **33** onto the turntable **110** of the buffer unit **100**; making the turntable **110** move around its own central axis, wherein the reactor **20** rotates by a set angle with the turntable **110**; transferring the reactor **20** from the turntable **110** to the sliding block **120** of the buffer unit **100**, wherein the reactor **20** makes linear movement with the sliding block **120** to the sample adding position **34**, and dispensing the sample into the reactor **20** located at the sample adding position **34**; and making the reactor **20** make linear movement with the sliding block **120** from the sample adding position **34** to the removing position **35**, wherein the reactor **20** can be transferred from the removing position **35** to the ferrying unit **200**.

(48) In order to ensure the maximum test throughput, one reactor **20** in which the reactants have been uniformly mixed must be removed from the ferrying unit **200** within a specified period of time. Thus, the shorter the time from a single reactor **20** entering the ferrying unit **200** to leaving the ferrying unit **200** (i.e., total retention time of the single reactor **20** on the ferrying unit **200**) is, the greater the test throughput is. In the conventional solution of dispensing both the sample and the reagent from the ferrying unit **200** into the reactor **20**, since the sample and the reagent are dispensed both from the ferrying unit **200** to the reactor **20** thereon, the retention time (duration) of the reactor **20** on the ferrying unit **200** will at least include sample dispensing time, reagent dispensing time, moving time of the ferrying unit **200**, and time of uniformly mixing the reactants.

(49) However, for the first liquid dispensing method, the sample is dispensed only from the buffer unit **100** into the reactor **20** (the sample is not dispensed from the ferrying unit **200** into the reactor **20**), that is, the sample is dispensed only into the reactor **20** located at the buffer unit **100**; after the reactor **20** containing the sample is transferred from the buffer unit **100** to the ferrying unit **200**, the reagent will be dispensed into the reactor **20** already containing the sample located on the ferrying unit **200**. Therefore, compared with the conventional solution, on the basis that the operation efficiencies of both the sample adding member **300** and the reagent dispensing member **500** are the

same, and the running speed of the ferrying unit **200** is the same, the retention time of the reactor **20** on the ferrying unit **200** only includes the reagent dispensing time, moving time of the ferrying unit **200**, and the time of uniformly mixing the reactants, thus, the sample dispensing time is saved, and the reactor **20** stays on the ferrying unit **200** for a shorter time, so that the reactor **20** can uniformly mix the reactants in a relatively short period of time and leave the ferrying unit **200**, thus increasing the test throughput of the whole immunity analyzer **10**.

(50) In fact, for the first liquid dispensing method, the dispensing of the sample will not be restricted by a moving speed of the ferrying unit **200** or a position where the ferrying unit is located. When the ferrying unit **200** carrying the reactor **20** having been dispensed with the sample is moving or stationary, the sample adding member **300** may fully utilize the idle waiting time, so as to dispense the sample in advance from the buffer unit **100** into the reactor **20**, then the total retention time of a single reactor **20** on the ferrying unit **200** is reduced, and finally the objective of increasing the maximum test throughput is achieved. Therefore, even when the reagent dispensing member **500** dispenses the reagent from the ferrying unit **200** into the reactor **20** thereon, the sample adding member **300** may dispense the sample from the buffer unit **100** into the reactor **20** thereon, that is, the sample and the reagent may be dispensed synchronously, thereby eliminating the time for dispensing the sample on the ferrying unit **200**. For the conventional solution, the dispensing of the sample cannot get rid of restrictions of the moving speed of the ferrying unit **200** or a position where the ferrying unit is located, and only when the ferrying unit **200** reaches the initial position **30**, the sample adding member **300** can dispense the sample from the ferrying unit into the reactor **20**, then it is impossible to dispense the sample and the reagent into the reactor **20** at the same moment.

(51) Certainly, on the basis of ensuring the same test throughput as the conventional solution, for the first liquid dispensing method, the running speeds (operation efficiencies or operation loads) of the ferrying unit **200**, the sample adding member **300**, and the reagent dispensing member **500** further may be suitably decreased, so as to reduce the difficulty in controlling the movement of the ferrying unit **200**, the sample adding member **300**, and the reagent dispensing member **500**, and vibrations, noises, and failures caused by high-speed operation of various components in the liquid dispensing device **11** are also reduced, thus improving the stability and reliability of the operation of the whole liquid dispensing device **11**.

(52) When the above liquid dispensing device **11** is adopted to dispense the sample and the reagent into the reactor **20**, and uniformly mix the sample and the reagent, a second liquid dispensing method also may be formed, wherein the second liquid dispensing method is mainly characterized in that the same sample is drawn by the sample adding member **300** and dispensed in multiple times into at least two reactors **20**; meanwhile, after the same sample is drawn and continuously dispensed into at least two reactors, the sample adding member **300** is washed or replaced, and in the process of drawing the same sample and continuously dispensing the same sample into at least two reactors, the sample adding member **300** is not washed or replaced. Referring to FIG. **10**, the second liquid dispensing method mainly includes the following steps.

(53) S710, providing the sample adding member **300**, and meanwhile providing the buffer unit **100** and the ferrying unit **200**.

(54) S720, drawing the same sample and continuously dispensing the sample into at least two reactors **20** of the buffer unit **100** by the sample adding member **300**, wherein a time interval between continuously dispensing the sample into at least two empty reactors **20** located on the buffer unit **100** is recorded as a sample dispensing interval t , wherein it could be understood by a person skilled in the art that the same sample herein specifically refers to the same sample to be tested (that is, corresponding to a certain subject, such as a certain patient's sample) that needs to be detected at least twice, and the at least two times of detection may be for at least two different analytical items, and may also be at least two times of detection repeated for the same analytical item; and different samples refer to samples of different subjects.

- (55) **S730**, washing or replacing the sample adding member **300** after drawing the same sample and continuously dispensing the same sample into at least two reactors, wherein in the process of drawing the same sample and continuously dispensing the same sample into at least two reactors, the sample adding member **300** is not washed or replaced, in particular, the sample adding member **300** is washed or replaced between dispensing of different samples.
- (56) **S740**, recording a shortest time window, in which a sequence of actions executed by the ferrying unit **200** can be cyclically reproduced, as operation period T, making the ferrying unit **200** move between the initial position **30** and the first position **31**, and dispensing the reagent by the reagent dispensing member **500** into each reactor **20** already containing the sample at the first position **31**, wherein specifically, the reagent is dispensed by the reagent dispensing member **500** at the first position **31** into each reactor **20** already containing the sample on the ferrying unit **200**. Similar to the ferrying unit **200**, the reagent dispensing member **500** also dispenses the reagent according to the operation period T, i.e. dispenses the reagent into only one reactor **20** already containing the sample within each operation period T. Therefore, for at least two reactors, after the sample is dispensed by the sample adding member **300** according to the sample dispensing interval t, the interval time for dispensing the reagent by the same reagent dispensing member **500** is at least T.
- (57) **S750**, making the ferrying unit **200** uniformly mix the sample and the reagent after the reagent is dispensed into the reactor **20**, wherein the ferrying unit **200** may uniformly mix the reactants in the reactor **20** in a manner of non-contact eccentric oscillation, thereby eliminating carryover contamination of other contact-type stirring on the reactants. In order to increase the test throughput, the ferrying unit **200** may be enabled to uniformly mix the sample and the reagent in the reactor **20** during movement from the first position **31** to the initial position **30**.
- (58) **S760**, after uniformly mixing the sample and the reagent, by the transfer unit **700**, removing the reactor **20** from the ferrying unit **200** at the initial position **30**, and transferring the reactor to the reaction device **12**.
- (59) For other similarities of the second liquid dispensing method, reference may be made to the first liquid dispensing method above, and details are not described herein again.
- (60) In some embodiments, the sample adding member **300** adopts an elongated cylindrical sample needle, and after drawing the same sample and continuously dispensing the same sample into at least two reactors, in particular, between the dispensing of different samples, the sample needle is moved to the washing tank **800**, to wash an inner wall and an outer wall of the sample needle simultaneously, so as to eliminate carryover contamination between different samples. During the washing, a washing liquid is injected into an inner cavity of the sample needle through a hydrodynamic device such as a syringe or a pump, then the washing liquid flowing through the inner cavity of the sample needle at a certain flow speed will flush the inner wall of the sample needle so as to achieve the washing effect, meanwhile, the outer wall of the sample needle is sprayed with or immersed in the washing liquid to wash the outer wall of the sample needle, and the washing liquid flowing out from the inner cavity and the outer wall of the sample needle may be simultaneously discharged into the washing tank **800**. In order to ensure thorough washing of the inner wall and the outer wall of the sample needle so as to eliminate the carryover contamination, and meanwhile ensure the operation efficiency of the sample needle and the test throughput of the immunity analyzer **10**, the duration for washing the sample needle is 2 seconds to 10 seconds.
- (61) In some embodiments, the sample adding member **300** adopts a disposable nozzle, and the disposable nozzle is replaced after the same sample is drawn and continuously dispensed into at least two reactors **20**. In particular, between the dispensing of different samples, the disposable nozzle is replaced. In this way, the washing of the disposable nozzle can be omitted, the washing time is reduced so as to improve the efficiency, and meanwhile, the cost of the disposable nozzle can be compensated by reducing the cost of the washing liquid.

(62) Referring to FIG. 6 and FIG. 7 together, in some embodiments, when a sum of samples required for all analytical items corresponding to the samples to be tested does not exceed a capacity of the sample needle, that is, when the capacity of the sample adding member 300 is greater than a total amount of the same sample required for various reactors 20, the sample adding member 300 draws the same sample only once and continuously dispenses the same sample into different reactors 20 in multiple times. For example, the sample adding member 300 needs to draw a same blood sample (denoted as first S) to detect two items in the five items of thyroid function, i.e. TSH item and T4 item, wherein for the reactor 20 for detecting the TSH item, the reactor 20 (denoted as TSH reactor) needs 100 microliters of blood sample; and for the reactor 20 for detecting the T4 item, the reactor 20 (denoted as T4 reactor) requires 50 microliters of blood sample. In this case, the capacity of the sample adding member 300 is greater than 150 microliters, that is, the capacity of the sample adding member 300 is greater than a sum of the capacity of the blood sample required by the TSH reactor and the blood sample required by the T4 reactor, therefore, the sample adding member 300 draws at least 150 microliters of blood sample (first S) from the sample tube 430 at one time, and when dispensing the blood sample, the buffer unit 100 drives the TSH reactor to move to the sample adding position 34, the sample adding member 300 dispenses 100 microliters of blood sample (first S) into the TSH reactor; then, the buffer unit 100 continues to drive the T4 reactor to move to the sample adding position 34, and after the sample dispensing interval t (there is at least one t , and $t < T$), the sample adding member 300 dispenses 50 microliters of blood sample (first S) into the T4 reactor. Between the dispensing of the blood sample into the TSH reactor and the T4 reactor, as the blood sample is the same, the sample adding member 300 does not need to be washed. Certainly, the sample adding member 300 may be moved to above the washing tank 800 or in the washing tank 800 for hysteresis error calibration, and may also stay at the sample adding position 34. The reagent dispensing member 500 subsequently dispenses the TSH reagent into the TSH reactor, wherein the TSH reagent may include an R1 component and an R2 component, and after at least one operation period T , dispenses the T4 reagent into the T4 reactor, wherein the T4 reagent may also include the R1 component and the R2 component.

(63) In some embodiments, when a sum of samples required for all analytical items corresponding to the samples to be tested exceeds the capacity of the sample needle, i.e., when the capacity of the sample adding member 300 is less than the total amount of the same sample required for various reactors 20, the sample adding member 300 draws the same sample (denoted as second S) in multiple times and dispenses the same sample into different reactors 20 at the sample dispensing interval t (there is at least one t , and $t < T$). For example, the same sample (second S) needs to be dispensed into four reactors 20 so as to detect four different items. Provided that the sample adding member 300 has a capacity of 500 microliters, and the total amount of the same sample required for the four reactors 20 exceeds 500 microliters, in this case, the sample adding member 300 may draw the same sample in two times so as to dispense the same sample (second S) into the four reactors 20. In operation, the sample adding member 300 draws less than 500 microliters of the sample (second S) for the first time, and continuously dispenses the sample into three reactors 20 in a set amount in three times, and then the sample adding member 300 draws less than 500 microliters of the sample for the second time, and dispenses the sample into the last reactor 20 in a set amount. Between the drawing of the same sample (second S) in the first time and in the second time by the sample adding member 300, the sample adding member 300 is run into the washing tank 800 to reset the sample adding power device. Since the reset needs to be performed in the process of washing the sample adding member 300, and there is no problem of carryover contamination for the same sample, the sample adding member 300 only needs to be washed for a short period of time, so that the sample adding member 300 is ready for better completing the second time of sample drawing.

(64) In some embodiments, for the sample dispensing interval t , there is at least one t , and $t < T$, i.e.,

there is at least one interval of operation period T, in which the operation efficiency of the sample adding member **300** is greater than that of the reagent dispensing member **500**. For the same reactor **20** having been dispensed with the sample, the reagent dispensing member **500** can draw different reagent components and dispense the same into the reactor **20** in multiple times in each operation period T. Within the time interval of an operation period T in which the reagent dispensing member **500** dispenses each desired reagent component into a single reactor **20**, the sample adding member **300** can dispense the sample into at least two reactors **20**. In short, each reagent dispensing member **500** can dispense each reagent component into only one reactor **20** within a time interval of the operation period T, while the sample adding member **300** can dispense the sample into at least two reactors **20**. Between the drawing of different reagent components by the reagent dispensing member **500**, the reagent dispensing member **500** is washed so as to prevent carryover contamination of different reagent components; for example, different reagent components include the R1 component and the R2 component, the reagent dispensing member **500** successively draws the R1 component and the R2 component into the same reactor **20**, and before the reagent dispensing member **500** draws the R2 component, the reagent dispensing member **500** that has just drawn the R1 component is washed so as to prevent carryover contamination of the R1 component to the R2 component.

(65) Depending on the needs of the actual situation, the sample quantity each time drawn by the sample adding member **300** can be set to 10 microliters to 500 microliters, and the sample quantity required by each reactor **20** is 5 microliters to 250 microliters.

(66) For the conventional solution, after the sample adding member **300** dispenses the sample into each reactor **20**, the sample adding member **300** needs to be washed, so as to eliminate the carryover contamination caused by extending the sample adding member **300** into the sample tube **430** to draw the sample again and dispensing the sample, in this way, the number of washing times is increased, thereby causing at least the following three defects. First, a lot of time is consumed, which also reduces the operation efficiency of the sample adding member **300**, thereby affecting the test throughput of the whole immunity analyzer **10**. Secondly, a large amount of washing liquid is consumed, thus increasing the test cost of the immunity analyzer **10**. Thirdly, due to more washing times, in order to ensure the operation efficiency of the sample adding member **300** and ensure the test throughput, the washing duration of the sample adding member **300** will be reduced, so that the sample adding member **300** cannot be washed thoroughly, and then the carryover contamination cannot be effectively eliminated.

(67) The second liquid dispensing method has at least the following beneficial effects. Firstly, as the sample adding member **300** draws the same sample and continuously dispenses the same sample into at least two reactors **20**, in the continuous dispensing of the same sample into the two reactors **20**, the sample adding member **300** does not need to extend into the sample tube **430** again to draw the sample, nor the sample adding member **300** needs to be washed, therefore, the sample adding member **300** needs to be washed once at least every two reactors **20**, then the phenomenon that the sample adding member **300** needs to be washed every other reactor **20** in the conventional solution is effectively avoided. This can reduce the number of washing times of the sample adding member **300**, thereby improving the operation efficiency of the sample adding member **300** and the test throughput of the immunity analyzer **10**. Secondly, when the sample adding member **300** is extended into the sample tube **430** multiple times to draw the same sample, the sample adding member **300** only needs to be washed for a short period of time, in this way, the sample adding member **300** can be made to collectively dispense a certain kind of same sample, and then collectively dispense another kind of same sample, thus reducing the switching frequency between different samples, and further functioning to reduce the washing times and the washing duration of the sample adding member **300**. Thirdly, as the washing times of the sample adding member **300** are reduced, on the basis of guaranteeing the operation efficiency and the test throughput, the duration of washing the sample adding member **300** may be suitably prolonged each time, so as to

thoroughly wash the sample adding member **300**, and effectively reduce the risk of carryover contamination between different samples. Obviously, the reduction in washing times also will reduce the consumption of the washing liquid, which can reduce the test cost of the immunity analyzer **10**. Fourthly, on the basis of improving the sample adding efficiency and effectively reducing the carryover contamination between the samples, the ferrying unit **200** and the reagent dispensing member **500** are enabled to efficiently coordinate and move, further improving the efficiency of reagent dispensing and reactant uniform mixing. In an operation period T, the reagent is dispensed by the reagent dispensing member **500** into each reactor **20** already containing the sample at the first position **31**, the sample and the reagent are uniformly mixed by the ferrying unit **200**, the sample dispensing is completed by the buffer unit, and the reagent dispensing and the reactant uniform mixing are completed on the ferrying unit, so that the efficiency of sample and reagent dispensing and reactant uniform mixing is improved, and thus the test efficiency and throughput of the immunity analyzer are improved, for example, the test throughput of the immunity analyzer of the present disclosure can break through the highest level (600 tests per hour) currently reported in the industry, and 720, 800 tests per hour or even higher test throughput can be achieved.

(68) When the above liquid dispensing device **11** is adopted to dispense the sample and the diluent (the diluent may be regarded as a component of a reagent corresponding to an analytical item, as described above) into the reactor **20**, uniformly mix the sample and the diluent to form a diluted sample, then dispense the diluted sample into a plurality of reactors **20**, and finally dispense the reagent into the reactor **20** containing the diluted sample and uniformly mix the resultant, a sample dilution method can be formed. Referring to FIG. **8** and FIG. **11** together, the sample dilution method mainly includes the following steps: **S810**, moving the ferrying unit **200** bearing a first reactor already containing the sample from the initial position **30** to the first position **31**; **S820**, dispensing the diluent into the first reactor located at the first position **31**; **S830**, uniformly mixing the sample and the diluent in the first reactor so as to form a diluted sample; **S840**, moving the ferrying unit **200** bearing the first reactor containing the diluted sample to the second position **32**, dispensing the diluted sample in the first reactor located at the second position into at least two empty second reactors, wherein certainly, the quantity of diluted sample dispensed into each empty second reactor may be different according to different analytical items, for example, the quantity of diluted sample dispensed into one of the second reactors may be greater than that dispensed into another second reactor; **S850**, moving the ferrying unit **200** bearing the second reactors containing the diluted sample to the first position **31**, and dispensing the reagent into the second reactors located at the first position **31**; and **S860**, uniformly mixing the diluted sample and the reagent in the second reactors.

(69) In some embodiments, referring to the relevant introduction in the first liquid dispensing method above, the first reactor is placed on the buffer unit **100**, and after dispensing the sample into the first reactor on the buffer unit **100** by the sample adding member **300**, the first reactor containing the sample is transferred from the buffer unit **100** to the ferrying unit **200** at the initial position **30**. In other words, the sample is dispensed into the reactor **20** only from the buffer unit **100** (not from the ferrying unit **200**), so that the dispensing of the sample is not restricted by the moving speed of the ferrying unit **200** or a position where the ferrying unit is located. When the ferrying unit **200** carrying the reactor **20** is moving or stationary, the sample can be dispensed from the buffer unit **100** (not from the ferrying unit **200**) into the reactor **20**, thus, the test throughput of the immunity analyzer **10** is improved.

(70) In some embodiments, the empty second reactor is placed on the buffer unit **100**, and after the diluted sample is dispensed into the second reactor, the second reactor containing the diluted sample is transferred from the buffer unit **100** to the ferrying unit **200** at the initial position **30**. For the sample and the diluent in the first reactor and the diluted sample and the reagent in the second reactor, they are all uniformly mixed by the ferrying unit **200** itself, and the uniform mixing is

carried out in a manner of non-contact eccentric oscillation. Meanwhile, the initial position **30** is provided between the first position **31** and the second position **32**, and the ferrying unit **200** is enabled to make linear reciprocation between the initial position **30**, the first position **31**, and the second position **32**.

(71) In some embodiments, the buffer unit **100** is enabled to move between the receiving position **33**, the sample adding position **34**, and the removing position **35**. The first reactor and the second reactor both enter the buffer unit **100** from the receiving position **33**, the sample is dispensed from the sample adding position **34** into the first reactor, the diluted sample is also dispensed from the sample adding position **34** into the second reactor, and both the first reactor and the second reactor leave the buffer unit **100** at the removing position **35** and are transferred to the ferrying unit **200**. When the buffer unit **100** is the turntable **110**, the turntable **110** drives the first and second reactors to perform circular movement between the receiving position **33**, the sample adding position **34**, and the removing position **35**. When the buffer unit **100** is the sliding block **120**, the sliding block **120** drives the first and second reactors to make linear movement between the receiving position **33**, the sample adding position **34**, and the removing position **35**.

(72) For the conventional sample dilution method, the diluted sample each time formed from the uniform mixing by the liquid dispensing device **11** can only be used by one reactor **20**, that is, the liquid dispensing device **11** should perform a separate uniform mixing process once for each reactor **20** so as to form the diluted sample, in other words, the diluted sample formed by one uniform mixing process only corresponds to one reactor **20**. In this way, the times of uniform mixing to form the diluted sample are increased, thereby reducing the operation efficiency of dilution of the sample, and further influencing the maximum test throughput of the immunity analyzer **10**.

(73) However, for the sample dilution method above, the liquid dispensing device **11** uniformly mixes the sample and the diluent in the first reactor so as to form the diluted sample, and dispenses the diluted sample in the first reactor into at least two second reactors. Therefore, the diluted sample each time formed from the uniform mixing by the liquid dispensing device **11** can be used by at least two reactors **20**, the liquid dispensing device **11** does not need to perform a separate uniform mixing process for each reactor **20** to form the diluted sample, in other words, the diluted sample formed by one uniform mixing process can correspond to at least two reactors **20**, in this way, the times of uniform mixing to form the diluted sample can be greatly reduced, improving the operation efficiency of the sample dilution method, and thus improving the maximum test throughput of the immunity analyzer **10**. In particular, for an immunoassay item in which the item to be tested needs to be automatically diluted and then tested, such as test item such as autoimmune diseases or allergen detection, sample dilution is often required, and the diluted sample needs to be subjected to a plurality of tests. For such test items, the sample dilution method effectively addresses the maximum test throughput bottleneck of the immunity analyzer **10**.

(74) Referring to FIG. 5 and FIG. 12 together, when the number of ferrying units **200** of the above liquid dispensing device **11** is at least two, a third liquid dispensing method may be formed. Certainly, the third liquid dispensing method is similar to the first liquid dispensing method, that is, the sample is not dispensed from the ferrying unit into the reactor **20**, but is dispensed from the buffer unit **100** into the reactor **20**, and after the sample is dispensed into the reactor **20**, the transfer unit transfers the reactor **20** already containing the sample from the buffer unit **100** to the ferrying unit **200**. The third liquid dispensing method mainly includes the following steps: S910, providing at least two ferrying units **200**, so as to enable each ferrying unit **200** to reciprocate between the initial position **30** and the first position **31**; S920, transferring the reactor **20** already containing the sample to the ferrying unit **200** at the initial position **30**, wherein in fact, the sample is dispensed from the buffer unit **100** into the reactor **20**, and after the sample is dispensed into the reactor **20** on the buffer unit **100**, the reactor **20** already containing the sample is removed from the buffer unit **100** and moved onto the ferrying unit **200** at the initial position **30**; S930, driving, by the ferrying

unit **200**, the reactor **20** input from the buffer unit **100** and containing the sample, to move from the initial position **30** to the first position **31**, dispensing the reagent into the reactor **20** at the first position **31**, and then uniformly mixing the sample and the reagent in the reactor **20**; **S940**, recording a shortest time window, in which a sequence of actions executed by the ferrying unit **200** can be cyclically reproduced, as first period, recording a quotient obtained by dividing the first period by the number of ferrying units **200** as second period, and from the first time of moving the reactor **20** onto one of the ferrying units **200**, moving the reactors **20** successively onto other ferrying units **200** staggered by a time interval of one second period; and **S950**, removing the reactors **20** having completed the uniform mixing from the ferrying units **200** successively staggered by a time interval of one second period, and placing another reactor **20** already containing the sample on the ferrying unit **200** from which the reactor **20** has been removed.

(75) In order for the whole immunity analyzer **10** to have a higher test throughput, the length of the second period may be any suitable value within 4-15 seconds, such as 4 seconds, 4.5 seconds, 5 seconds, 6 seconds, 9 seconds, and the corresponding test throughput is 900-240 tests per hour, that is, the immunity analyzer **10** may continuously report **900-240** results per hour. For convenience of understanding, the following description is made with the second period being 5 seconds as an example.

(76) Assume that the immunity analyzer **10** must complete a measurement for one reactor **20** every 5 seconds, i.e., report a test result every 5 seconds, in this case, the duration of the second period is 5 seconds. Regarding the whole immunity analyzer **10** as a pipeline, it must be ensured that the flow rates at every place of the pipeline are equal, therefore, the ferrying unit **200** also needs to output a reactor **20** having completed the uniform mixing every 5 seconds. If there is only one ferrying unit **200**, since the total time required for the ferrying unit **200** to execute the sequence of actions, such as receiving the reactor **20** already containing the sample, undergoing the reagent dispensing by the reagent dispensing member **500**, performing eccentric oscillation to mix uniformly, and removing the reactor **20** having completed the uniform mixing, in one period is greater than 5 seconds, the ferrying unit **200** cannot output one reactor **20** having completed the uniform mixing every 5 seconds, and the flow rate of the ferrying unit **200** is lower than an outlet flow rate of the pipeline, so that the pipeline cannot continuously operate at the maximum efficiency (test throughput). Therefore, by setting the first period to be twice the second period, i.e., the first period is 10 seconds, and meanwhile by setting the number of ferrying units **200** to be two, the sequence of actions executed by two ferrying units **200** is staggered by the duration of the second period (i.e., 5 seconds), i.e., two ferrying units **200** are operated “in parallel in a manner of being staggered” by one second period.

(77) In operation, according to the existing movement law of the ferrying unit **200**, assume that the reactor **20** already containing the sample is transferred onto a first ferrying unit **200** at 0.sup.th second, then the reactor **20** already containing the sample is transferred onto the second ferrying unit **200** at the 5.sup.th second. Assume that the reactor **20** on the first ferrying unit **200** will be output at the 10.sup.th second, after the reactor **20** is output, the reactor **20** already containing the sample is transferred onto the first ferrying unit. Then, the reactor **20** on the second ferrying unit **200** will be output at the 15.sup.th second, likewise, after the reactor **20** is output, the reactor **20** already containing the sample is transferred onto the second ferrying unit. Cyclically running according to the above operation manner will enable the first ferrying unit **200** to output one reactor **20** at 10.sup.th, 20.sup.th, 30.sup.th . . . 10N.sup.th seconds; meanwhile, the second ferrying unit **200** will output one reactor **20** at 15.sup.th, 25.sup.th, 35.sup.th . . . (5N+10)th seconds. Therefore, on the basis that each ferrying unit **200** outputs one reactor **20** having completed the uniform mixing every 10 seconds, the two ferrying units **200** as a whole will output one reactor **20** having completed the uniform mixing every 5 seconds, so that the purpose of “exchanging quantity for time” is achieved, and the requirement of the highest test throughput of the immunity analyzer **10** is finally met.

(78) Certainly, when the second period is still 5 seconds, the duration of the first period may also be longer, in which case the number of ferrying units **200** is set to be three, four, or even more, and the first period may be set to be three, four, or even more times the second period, that is, the first period is 15 seconds or 20 seconds, and so on. In this way, on the basis of ensuring the test throughput, the moving speed of the ferrying unit **200** can be reduced, the duration for dispensing the reagent and uniformly mixing the sample and the reagent can be prolonged, then the bottleneck of the moving speed of the ferrying unit **200**, the bottleneck of duration of dispensing the reagent and the uniformly mixing the sample and the reagent are effectively solved. In a situation that the moving speed of the ferrying unit **200** and the duration of uniformly mixing the sample and the reagent are fixed, each ferrying unit **200** still outputs one reactor **20** having completed the uniform mixing every 10 seconds, that is, the first period is still 10 seconds.

(79) In the case where the number of storage units **600** of the liquid dispensing device **11** is equal to the number of ferrying units **200**, the third liquid dispensing method further includes the following steps: providing the storage units **600** in the same number as the ferrying units **200**, and storing the reagent in a plurality of storage portions **610** of each storage unit **600**; moving the storage portions **610** with the storage units **600** to liquid drawing positions for drawing the reagent; and making the shortest time window, in which the sequence of actions executed by each storage unit **600** can be cyclically reproduced, equal to the first period, wherein from the first time when one of the storage units **600** drives the storage portions **610** to move towards the liquid drawing position, the other storage units **600** are enabled to drive the storage portions **610** to move towards the corresponding liquid drawing positions successively staggered by a time interval of one second period.

(80) With reference to the above relevant description that at least two ferrying units **200** are operated “in parallel in a manner of being staggered” by one second period, by making the number of storage units **600** equal to that of ferrying units **200**, and meanwhile making the storage units **600** also operated “in parallel in a manner of being staggered” by one second period, when all the storage units **600** are considered as a whole, the storage portion **610** on one of the storage units **600** is moved to the liquid drawing position every second period, so that the reagent dispensing member **500** draws the reagent at the liquid drawing position. Therefore, for a separate storage unit **600**, although the storage portion **610** is driven to move to the liquid drawing position every first period, when all the storage units **600** are considered as a whole, the storage portion **610** arrives at the liquid drawing position every second period, which can also achieve the purpose of “exchanging quantity for time”, and the requirement of the highest test throughput of the immunity analyzer **10** is finally met.

(81) In addition, for the conventional solution, the number of storage unit **600** is usually one, and in order to increase the storage capacity of the reagent used for the analytical items, the number of storage portions **610** must be increased, which thus results in an increased size of the whole storage unit **600**, then the storage unit **600** occupies a large area, which is not beneficial to the layout and manufacturing of the storage unit **600**, and meanwhile, for the storage unit **600** with a large size and weight, the difficulty of controlling the movement thereof is also increased, which results in that the storage portion **610** cannot reach a designated position in a short period of time for the reagent dispensing member **500** to draw the reagent, which becomes a bottleneck in realizing high test throughput. Meanwhile, when the storage unit **600** fails, the whole immunity analyzer **10** cannot operate. By providing at least two storage units **600**, with each storage unit **600** having a relatively small volume, the third liquid dispensing scheme is beneficial for the layout and the movement control of the whole machine, and also can ensure a large reagent storage capacity. Meanwhile, the tolerance of the storage unit **600** to fault can be improved, and when one of the storage units **600** fails and cannot operate, the remaining storage units **600** can continue to operate, which ensures that the reagent can be continuously supplied. Certainly, the failed storage unit **600** may be repaired while other storage units **600** are operating.

(82) In some embodiments, the reagent dispensing members **500** are provided in an equal number

to that of storage units **600** such that each storage unit **600** corresponds to one reagent dispensing member **500**. In this way, the efficiency of dispensing the reagent can be improved, and certainly, the operation efficiency (load) of a single reagent dispensing member **500** can also be reduced on the basis of ensuring the maximum test throughput. The shortest time window, in which the sequence of actions executed by each reagent dispensing member **500** can be cyclically reproduced, is made equal to the first period, and from the time when one of the reagent dispensing members **500** dispenses the reagent, the other reagent dispensing members **500** are made to dispense the reagent successively staggered by the time interval of one second period.

(83) With reference to the above relevant description that at least two ferrying units **200** and at least two storage units **600** are operated “in parallel in a manner of being staggered” by one second period, by making the number of reagent dispensing members **500** equal to that of storage units **600** and that of ferrying units **200**, and meanwhile making the reagent dispensing members **500** also operated “in parallel in a manner of being staggered” by one second period, when all the reagent dispensing members **500** are considered as a whole, one of the reagent dispensing members **500** dispenses the reagent every second period, therefore, for a separate reagent dispensing member **500**, although it dispenses the reagent into one reactor **20** every first period, when all the reagent dispensing members **500** are considered as a whole, there is a reagent dispensing member **500** to dispense the reagent once every second period, which also can achieve the purpose of “exchanging quantity for time”, and the requirement of the highest test throughput of the immunity analyzer **10** is finally met.

(84) When the ferrying unit makes linear movement between the initial position **30** and the first position **31**, the storage units **600** may be divided into two halves equal in number, in which one half of the storage units **600** and the other half of the storage units **600** are symmetrical with respect to the movement trajectory of the ferrying unit **200**, thus facilitating the layout of the whole immunity analyzer **10**.

(85) Therefore, by transferring the reactor **20** already containing the sample to the ferrying unit **200** at the initial position **30**, that is, dispensing the sample from the buffer unit **100** in advance into the reactor **20**, the time for dispensing the sample from the ferrying unit **200** into the reactor **20** is saved, thus the retention time of the reactor **20** on each ferrying unit **200** is reduced, and each ferrying unit **200** is enabled to quickly output one reactor **20**. Meanwhile, at least two ferrying units **200** are provided, and the at least two ferrying units **200** are operated “in parallel in a manner of being staggered” by one second period. Although a single ferrying unit **200** outputs one reactor **20** every first period, all the ferrying units **200**, as a whole, will output one reactor **20** every shorter second period, in this way, the purpose of “exchanging quantity for time” can be achieved, and the requirement of the highest test throughput of the immunity analyzer **10** is finally met.

(86) In some embodiments, the third liquid dispensing method is similar to the second liquid dispensing method, that is, the same sample is drawn by the sample adding member **300** and continuously dispensed into at least two reactors **20** on the buffer unit **100**, meanwhile, after the same sample is drawn and continuously dispensed into at least two reactors, the sample adding member **300** is washed or replaced. For the beneficial effects thereof, reference can be made to the description of the above second liquid dispensing method.

(87) Likewise, in the process of dispensing the sample, the sample adding member **300** adopts a sample needle or a disposable nozzle, and after the same sample is drawn and continuously dispensed into at least two reactors, the inner wall and the outer wall of the sample needle are washed or the disposable nozzle is replaced. For thorough washing, the duration of washing the sample needle is 2 seconds to 10 seconds. When the capacity of the sample adding member **300** is greater than a total amount of the same sample required for various reactors **20**, the sample adding member **300** draws the same sample only once and continuously dispenses the same sample into different reactors **20** in multiple times.

(88) Referring to FIG. 13, testing four analytical items with the same sample (first S) is taken as an

example for illustration. The sample adding member **300** draws the same sample (first S) once and continuously dispenses the first S divided into four parts (denoted as S1, S2, S3, S4, respectively) into four reactors in four times. Since the sample drawn by the sample adding member **300** next time is a different sample, after S1, S2, S3, and S4 are dispensed into the four reactors, the inner wall and the outer wall of the sample needle of the sample adding member **300** are washed or the disposable nozzle is replaced.

(89) For the four reactors into which the sample adding member **300** continuously dispenses the sample with one time of drawing, each reagent dispensing member **500** dispenses the reagent corresponding to the analytical item, according to the first period, into the reactor having been dispensed with the first S on the ferrying unit **200** located at the first position, and the two reagent dispensing members **500** dispense the reagent corresponding to the analytical item, at an interval of N second periods, into the reactors having been dispensed with the first S on the ferrying unit **200** located at the first position **31**. Specifically, a first reagent dispensing member **500** dispenses the reagent into the first reactor **20** containing S1 in the 1.st first period T, and dispenses the reagent into a third reactor **20** containing S3 in the 2.nd first period T, and a second reagent dispensing member **500** dispenses the reagent into the second reactor **20** containing S2 in the 2.nd first period T, and dispenses the reagent into a fourth reactor **20** containing S4 in the 3.rd first period T. It can be seen that the first reagent dispensing member **500** and the second reagent dispensing member **500** dispense the reagent corresponding to the analytical item at an interval of N second periods (T/2). In this way, it can be ensured that there is one reactor **20** in each second period (T/2) to complete the dispensing of the reagent, thereby improving the efficiency of dispensing the reagent. In summary, for at least two reactors dispensed with the same sample, each reagent dispensing member **500** dispenses the reagent of the analytical item at intervals of N (N is an integer, $N \geq 1$) first periods, successively staggered by one second period (T/2).

(90) The third liquid dispensing method of the present disclosure, on the basis of improving the sample dispensing efficiency and effectively reducing the carryover contamination between the samples, enables at least two ferrying units **200**, at least two storage units **600**, and at least two reagent dispensing members **500** to efficiently coordinate and move, further improving the efficiency of reagent dispensing and reactant uniform mixing, thus improving the test efficiency and throughput of the immunity analyzer. For example, the test throughput of the immunity analyzer of the present disclosure can break through the highest level (600 tests per hour) currently reported in the industry, and 720, 800 tests per hour or even higher test throughput can be achieved.

(91) The present disclosure further provides an immunoassay method, wherein the immunoassay method includes the steps of the first liquid dispensing method, the second liquid dispensing method, the third liquid dispensing method, and the sample dilution method in the above.

(92) Various technical features in the above embodiments may be combined arbitrarily, and for the sake of concise description, not all possible combinations of the various technical features in the above embodiments are described, while the combinations of these technical features, without conflict, should be considered as within the scope of the present description.

(93) The above embodiments are merely several embodiments of the present disclosure, of which the description is relatively specific and detailed, but they should not be thus construed as limitation on the patent scope of the present disclosure. It should be indicated that a person ordinarily skilled in the art still could make several modifications and improvements without departing from the concept of the present disclosure, all of which fall within the scope of protection of the present disclosure. Therefore, the scope of protection of the present disclosure should be determined by the attached claims.

Claims

1. A sample dilution method, comprising steps of: moving a ferrying unit bearing a first reactor already containing a sample from an initial position to a first workstation; dispensing a diluent into the first reactor located at the first workstation; uniformly mixing the sample and the diluent in the first reactor so as to form a diluted sample; moving the ferrying unit bearing the first reactor containing the diluted sample to a second position, and dispensing the diluted sample in the first reactor located at the second position into at least two empty second reactors; moving the ferrying unit bearing the second reactors containing the diluted sample to the first workstation, and dispensing a reagent into the second reactors located at the first workstation; and uniformly mixing the diluted sample and the reagent in the second reactors, wherein a buffer unit is provided, the first reactor is placed on the buffer unit, and after dispensing the sample into the first reactor on the buffer unit, the first reactor containing the sample is transferred from the buffer unit to the ferrying unit at the initial position, the ferrying unit is configured to make linear reciprocation between the initial position, the first workstation position and the second position, and wherein the empty second reactors are placed on the buffer unit, and after the diluted sample is dispensed into the second reactors, the second reactors containing the diluted sample are transferred from the buffer unit to the ferrying unit at the initial position.
 2. The sample dilution method according to claim 1, wherein the sample and the diluent in the first reactor and the diluted sample and the reagent in the second reactors are all uniformly mixed by the ferrying unit.
 3. The sample dilution method according to claim 2, wherein the uniform mixing is carried out in a manner of non-contact eccentric oscillation.
 4. The sample dilution method according to claim 1, wherein the buffer unit is configured to move between a receiving workstation, a sample adding position workstation and a removing position, wherein the first reactor and the second reactors enter the buffer unit from the receiving position, the sample and the diluted sample are dispensed into the first reactor and the second reactors at the sample adding workstation, respectively, and the first reactor and the second reactors all leave the buffer unit and are transferred to the ferrying unit at the removing position.
 5. The sample dilution method according to claim 4, wherein the buffer unit is configured to drive the first reactor and the second reactors to make circular movement or linear movement between the receiving position, the sample adding workstation and the removing position.
-