

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12409364
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Son; Taehwan et al.

Electronic device for providing exercise content based on recognition space and operating method thereof

Abstract

An example electronic device may include a plurality of antennas for wireless communication, a processor configured to scan to identify whether there is at least one portable device using the plurality of antennas, define a three-dimensional recognition space based on a first signal for space setting transmitted from a portable device identified by the scan, calculate a position of the identified portable device in the recognition space based on a second signal transmitted from the identified portable device, and generate exercise content based on the position of the identified portable device, and a display module, including a display, configured to display the exercise content.

Inventors: Son; Taehwan (Suwon-si, KR), Park; Jeongmin (Suwon-si, KR), Cho; Daesung (Suwon-si, KR)

Applicant: SAMSUNG ELECTRONICS CO., LTD. (Suwon-si, KR)

Family ID: 87522141

Assignee: SAMSUNG ELECTRONICS CO., LTD. (Suwon-si, KR)

Appl. No.: 18/121656

Filed: March 15, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230249033 A1	Aug. 10, 2023

Foreign Application Priority Data

KR	10-2022-0016364	Feb. 08, 2022
KR	10-2022-0039654	Mar. 30, 2022

Related U.S. Application Data

continuation parent-doc WO PCT/KR2022/018774 20221124 PENDING child-doc US 18121656

Publication Classification

Int. Cl.: **A63B24/00** (20060101); **A63B71/06** (20060101); **G01S5/06** (20060101); **G06F3/01** (20060101)

U.S. Cl.:

CPC **A63B24/0075** (20130101); **A63B24/0062** (20130101); **A63B71/0622** (20130101); **G01S5/06** (20130101); **G06F3/011** (20130101); A63B2220/836 (20130101); A63B2225/54 (20130101)

Field of Classification Search

CPC: A63B (24/0075); A63B (24/0062); A63B (71/0622); A63B (2220/836); A63B (2225/54); A63B (71/06); G01S (5/06); G01S (2205/01); G01S (2205/08); G01S (5/0284); G01S (5/14); G06F (3/011); G06F (3/01); G06Q (50/10); A61B (5/11); A61B (5/681); H04W (4/02); G09B (19/0038)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
7217224	12/2006	Thomas	482/8	H04L 67/12
8419545	12/2012	Yen et al.	N/A	N/A
9108098	12/2014	Galasso	N/A	G06Q 30/0255
9288368	12/2015	O'Sullivan	N/A	H04N 5/04
10024948	12/2017	Ganick et al.	N/A	N/A
11998316	12/2023	Park	N/A	A61B 5/743
12002179	12/2023	Palacios	N/A	A63B 24/0006
2004/0102931	12/2003	Ellis	702/188	A61B 5/0833
2005/0239601	12/2004	Thomas	482/8	A63B 24/00
2007/0061076	12/2006	Shulman	701/500	G06T 7/97
2009/0011907	12/2008	Radow	482/57	B62M 3/00
2009/0098524	12/2008	Walton	434/350	G09B 5/14
2009/0221374	12/2008	Yen et al.	N/A	N/A
2010/0269143	12/2009	Rabowsky	725/63	H04B 7/18591
2014/0049636	12/2013	O'Donnell	348/143	G08B 13/19641
2014/0228982	12/2013	Bharwani	700/56	E02F 9/261
2015/0098021	12/2014	O'Sullivan	348/516	H04N 21/4223
2016/0119590	12/2015	Ganick et al.	N/A	N/A
2016/0271796	12/2015	Babu	N/A	B25J 9/1664
2017/0034430	12/2016	Fu	N/A	H04N 23/70
2018/0255233	12/2017	Shibata	N/A	H04N 23/695

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
4907483	12/2011	JP	N/A
5138833	12/2012	JP	N/A
10-2015-0001433	12/2014	KR	N/A
10-2016-0079664	12/2015	KR	N/A
10-2017-0040039	12/2016	KR	N/A
10-2018-0043866	12/2017	KR	N/A
10-2019-0135870	12/2018	KR	N/A
2010/143359	12/2009	WO	N/A
2020/214758	12/2019	WO	N/A

OTHER PUBLICATIONS

International Search Report for PCT/KR2022/018774, mailed Mar. 7, 2023, 3 pages. cited by applicant

Primary Examiner: Atkinson; Garrett K

Attorney, Agent or Firm: Nixon & Vanderhye, P.C.

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation application of International Application No. PCT/KR2022/018774 designating the United States, filed on Nov. 24, 2022, in the Korean Intellectual Property Receiving Office and claiming priority to Korean Patent Application No. 10-2022-0016364, filed on Feb. 8, 2022, and Korean Patent Application No. 10-2022-0039654, filed on Mar. 30, 2022, in the Korean Intellectual Property Office, the disclosures of which are incorporated by reference herein in their entireties.

BACKGROUND

1. Field

(1) Various embodiments of the following disclosure relate to an electronic device for providing exercise content based on a recognition space and an operating method thereof.

2. Description of Related Art

(2) Portable devices include not only devices carried by a user, for example, smartphones or laptops, but also electronic devices attached to a body of a user for use. A portable device may take the form of, for example, glasses, a watch, or a head-mounted display (HMD), and may be connected to a smartphone or may independently perform various functions. A user may more conveniently perform, through a portable device, various tasks, for example, checking a simple text message or e-mail, health care and fitness management (such as checking a heart rate during exercise and calculating an exercise goal), and scheduling.

SUMMARY

(3) Embodiments of the disclosure provide an electronic device that may set a three-dimensional recognition space based on a signal transmitted from a portable device.

(4) Embodiments of the disclosure provide an electronic device that may calculate a relative position including a distance and an angle between the electronic device and a portable device in a recognition space using a difference in times at which a plurality of antennas receive a signal transmitted from the portable device.

- (5) Embodiments of the disclosure provide an electronic device that may generate exercise content including a character corresponding to a user wearing a portable device based on a relative position with the portable device in a recognition space.
- (6) Embodiments of the disclosure provide an electronic device that may adjust characters, exercise information, and the sizes of the characters displayed on a screen by reflecting movements of users.
- (7) The goals to be achieved are not limited to those described above and may be expanded in various manners within the scope of the disclosure without departing from the spirit and field of the disclosure.
- (8) According to an embodiment, an electronic device includes a plurality of antennas for wireless communication, a processor configured to scan to identify whether there is at least one portable device using the plurality of antennas, define a three-dimensional recognition space based on a first signal for space setting transmitted from a portable device identified by the scan, calculate a position of the identified portable device in the recognition space based on a second signal transmitted from the identified portable device, and generate exercise content based on the position of the identified portable device, and a display module configured to display the exercise content.
- (9) According to an embodiment, an operating method of an electronic device may include scanning to identify whether there is at least one portable device using a plurality of antennas for wireless communication, defining a three-dimensional recognition space based on a first signal for space setting transmitted from the identified portable device, calculating a position of the identified portable device in the recognition space based on a second signal transmitted from the identified portable device, generating exercise content based on the position of the identified portable device, and displaying the exercise content.
- (10) According to embodiments, an electronic device may provide exercise content including a character reflecting a physical action of a user wearing a portable device based on a relative position with the portable device.
- (11) According to embodiments, an electronic device may allow control of exercise content through intuitive motions and also display exercise content based on a relative position between users during a group exercise that the multiple users participate in, thereby increasing the immersion of the users performing an exercise.
- (12) According to embodiments, an electronic device may adjust characters, exercise information, and sizes of the characters displayed on a screen by reflecting movements of users, thereby allowing the users to three-dimensionally experience the movements in a recognition space.
- (13) According to embodiments, an electronic device may set a virtual recognition space, thereby freely setting the activity radius of users without the constraints of space due to the camera angle. In addition, various effects directly or indirectly ascertained through the present disclosure may be provided.
-

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The above and other aspects, features, and advantages of certain embodiments of the present disclosure will be more apparent from the following detailed description, taken in conjunction with the accompanying drawings, in which:
- (2) FIG. 1 is a block diagram illustrating an electronic device in a network environment according to one embodiment;
- (3) FIGS. 2A and 2B are perspective views of an portable device according to one embodiment;
- (4) FIG. 3 is a block diagram illustrating an electronic device according to one embodiment;
- (5) FIG. 4 is a block diagram of an system for providing an exercise content according to one embodiment;

- (6) FIG. 5 is a diagram illustrating an operation of an electronic device according to one embodiment;
- (7) FIG. 6 is a diagram illustrating an example of a range of a recognition space in which an electronic device may recognize a position of a user wearing a portable device according to one embodiment;
- (8) FIG. 7 is a diagram illustrating a method of defining a three-dimensional recognition space by an electronic device according to one embodiment;
- (9) FIG. 8 is a diagram illustrating examples of a recognition space defined by an electronic device based on first signals transmitted from portable devices according to one embodiment;
- (10) FIG. 9 is a diagram illustrating a method of calculating, by an electronic device, positions of portable devices based on second signals transmitted from the portable devices according to one embodiment;
- (11) FIG. 10 is a diagram illustrating transmission and reception sequences between a plurality of antennas of an electronic device and portable devices according to one embodiment;
- (12) FIG. 11 is a flowchart illustrating a method of updating an exercise content by an electronic device according to one embodiment;
- (13) FIG. 12 is a diagram illustrating an operation of an electronic device when another portable device newly enters a recognition space according to one embodiment;
- (14) FIG. 13 is a diagram illustrating an operation of an electronic device when a portable device leaves a recognition space according to one embodiment;
- (15) FIG. 14 is a diagram illustrating a method of reconstructing an exercise content in response to changes in the positions of portable devices positioned in a recognition space according to one embodiment;
- (16) FIG. 15 is a diagram illustrating an example of displaying the positions of a plurality of users in an exercise content when the plurality of users perform a group exercise wearing portable devices according to one embodiment; and
- (17) FIG. 16 is a flowchart illustrating an operating method of an electronic device according to one embodiment.

DETAILED DESCRIPTION

(18) Hereinafter, various embodiments of the disclosure will be described in detail with reference to the accompanying drawings. When describing example embodiments with reference to the accompanying drawings, like reference numerals refer to like components and a description related thereto will not be repeated. However, this is not intended to limit the techniques disclosed herein to specific embodiments, and it should be understood that various modifications, equivalents, and/or alternatives of the embodiments of the disclosure are included. In connection with the description of the drawings, like reference numerals may be used for like components.

(19) FIG. 1 is a block diagram illustrating an electronic device **101** in a network environment **100** according to one embodiment. Referring to FIG. 1, the electronic device **101** in the network environment **100** may communicate with an electronic device **102** via a first network **198** (e.g., a short-range wireless communication network), or communicate with at least one of an electronic device **104** or a server **108** via a second network **199** (e.g., a long-range wireless communication network). According to an embodiment, the electronic device **101** may communicate with the electronic device **104** via the server **108**. According to an embodiment, the electronic device **101** may include a processor **120**, a memory **130**, an input module **150**, a sound output module **155**, a display module **160**, an audio module **170**, and a sensor module **176**, an interface **177**, a connecting terminal **178**, a haptic module **179**, a camera module **180**, a power management module **188**, a battery **189**, a communication module **190**, a subscriber identification module (SIM) **196**, or an antenna module **197**. In some embodiments, at least one of the components (e.g., the connecting terminal **178**) may be omitted from the electronic device **101**, or one or more other components may be added in the electronic device **101**. In some embodiments, some of the components (e.g.,

the sensor module **176**, the camera module **180**, or the antenna module **197**) may be integrated as a single component (e.g., the display module **160**).

(20) The processor **120** may execute, for example, software (e.g., a program **140**) to control at least one other component (e.g., a hardware or software component) of the electronic device **101** connected to the processor **120**, and may perform various data processing or computation.

According to an embodiment, as at least a part of data processing or computation, the processor **120** may store a command or data received from another component (e.g., the sensor module **176** or the communication module **190**) in a volatile memory **132**, process the command or the data stored in the volatile memory **132**, and store resulting data in a non-volatile memory **134**.

According to an embodiment, the processor **120** may include a main processor **121** (e.g., a central processing unit (CPU) or an application processor (AP)), or an auxiliary processor **123** (e.g., a graphics processing unit (GPU), a neural processing unit (NPU), an image signal processor (ISP), a sensor hub processor, or a communication processor (CP)) that is operable independently from, or in conjunction with the main processor **121**. For example, when the electronic device **101** includes the main processor **121** and the auxiliary processor **123**, the auxiliary processor **123** may be adapted to consume less power than the main processor **121** or to be specific to a specified function. The auxiliary processor **123** may be implemented separately from the main processor **121** or as a portion of the main processor **121**.

(21) The auxiliary processor **123** may control at least some of functions or states related to at least one (e.g., the display module **160**, the sensor module **176**, or the communication module **190**) of the components of the electronic device **101**, instead of the main processor **121** while the main processor **121** is in an inactive (e.g., sleep) state or along with the main processor **121** while the main processor **121** is in an active state (e.g., executing an application). According to an embodiment, the auxiliary processor **123** (e.g., an ISP or a CP) may be implemented as a portion of another component (e.g., the camera module **180** or the communication module **190**) that is functionally related to the auxiliary processor **123**. According to an embodiment, the auxiliary processor **123** (e.g., an NPU) may include a hardware structure specified for artificial intelligence model processing. An artificial intelligence model may be generated by machine learning. Such learning may be performed by, for example, the electronic device **101** in which an artificial intelligence model is executed, or performed via a separate server (e.g., the server **108**). Learning algorithms may include, but are not limited to, for example, supervised learning, unsupervised learning, semi-supervised learning, or reinforcement learning. The artificial intelligence model may include a plurality of artificial neural network layers. An artificial neural network may include, for example, a deep neural network (DNN), a convolutional neural network (CNN), a recurrent neural network (RNN), a restricted Boltzmann machine (RBM), a deep belief network (DBN), and a bidirectional recurrent deep neural network (BRDNN), a deep Q-network, or a combination of two or more thereof, but is not limited thereto. The artificial intelligence model may additionally or alternatively, include a software structure other than the hardware structure.

(22) The memory **130** may store various data used by at least one component (e.g., the processor **120** or the sensor module **176**) of the electronic device **101**. The various data may include, for example, software (e.g., the program **140**) and input data or output data for a command related thereto. The memory **130** may include the volatile memory **132** or the non-volatile memory **134**.

(23) The program **140** may be stored as software in the memory **130**, and may include, for example, an operating system (OS) **142**, middleware **144**, or an application **146**.

(24) The input module **150** may receive a command or data to be used by another component (e.g., the processor **120**) of the electronic device **101**, from the outside (e.g., a user) of the electronic device **101**. The input module **150** may include, for example, a microphone, a mouse, a keyboard, a key (e.g., a button), or a digital pen (e.g., a stylus pen).

(25) The sound output module **155** may output a sound signal to the outside of the electronic device **101**. The sound output module **155** may include, for example, a speaker or a receiver. The speaker

may be used for general purposes, such as playing multimedia or playing record. The receiver may be used to receive an incoming call. According to an embodiment, the receiver may be implemented separately from the speaker or as a part of the speaker.

(26) The display module **160** may visually provide information to the outside (e.g., a user) of the electronic device **101**. The display module **160** may include, for example, a control circuit for controlling a display, a hologram device, or a projector and control circuitry to control a corresponding one of the display, the hologram device, and the projector. According to an embodiment, the display module **160** may include a touch sensor adapted to detect a touch, or a pressure sensor adapted to measure the intensity of force incurred by the touch.

(27) The audio module **170** may convert a sound into an electrical signal or vice versa. According to an embodiment, the audio module **170** may obtain the sound via the input module **150** or output the sound via the sound output module **155** or an external electronic device (e.g., the electronic device **102** such as a speaker or a headphone) directly or wirelessly connected to the electronic device **101**.

(28) The sensor module **176** may detect an operational state (e.g., power or temperature) of the electronic device **101** or an environmental state (e.g., a state of a user) external to the electronic device **101**, and generate an electrical signal or data value corresponding to the detected state. According to an embodiment, the sensor module **176** may include, for example, a gesture sensor, a gyro sensor, an atmospheric pressure sensor, a magnetic sensor, an acceleration sensor, a grip sensor, a proximity sensor, a color sensor, an infrared (IR) sensor, a biometric sensor, a temperature sensor, a humidity sensor, or an illuminance sensor.

(29) The interface **177** may support one or more specified protocols to be used for the electronic device **101** to be coupled with the external electronic device (e.g., the electronic device **102**) directly (e.g., wiredly) or wirelessly. According to an embodiment, the interface **177** may include, for example, a high-definition multimedia interface (HDMI), a universal serial bus (USB) interface, a secure digital (SD) card interface, or an audio interface.

(30) The connecting terminal **178** may include a connector via which the electronic device **101** may be physically connected to an external electronic device (e.g., the electronic device **102**). According to an embodiment, the connecting terminal **178** may include, for example, an HDMI connector, a USB connector, an SD card connector, or an audio connector (e.g., a headphone connector).

(31) The haptic module **179** may convert an electrical signal into a mechanical stimulus (e.g., a vibration or a movement) or an electrical stimulus which may be recognized by a user via his or her tactile sensation or kinesthetic sensation. According to an embodiment, the haptic module **179** may include, for example, a motor, a piezoelectric element, or an electric stimulator.

(32) The camera module **180** may capture a still image and moving images. According to an embodiment, the camera module **180** may include one or more lenses, image sensors, image signal processors, or flashes.

(33) The power management module **188** may manage power supplied to the electronic device **101**. According to an embodiment, the power management module **188** may be implemented as, for example, at least a part of a power management integrated circuit (PMIC).

(34) The battery **189** may supply power to at least one component of the electronic device **101**. According to an embodiment, the battery **189** may include, for example, a primary cell which is not rechargeable, a secondary cell which is rechargeable, or a fuel cell.

(35) The communication module **190** may support establishing a direct (e.g., wired) communication channel or a wireless communication channel between the electronic device **101** and the external electronic device (e.g., the electronic device **102**, the electronic device **104**, or the server **108**) and performing communication via the established communication channel. The communication module **190** may include one or more communication processors that are operable independently of the processor **120** (e.g., an AP) and that support a direct (e.g., wired) communication or a wireless communication. According to an embodiment, the communication

module **190** may include a wireless communication module **192** (e.g., a cellular communication module, a short-range wireless communication module, or a global navigation satellite system (GNSS) communication module) or a wired communication module **194** (e.g., a local area network (LAN) communication module, or a power line communication (PLC) module). A corresponding one of these communication modules may communicate with the external electronic device **104** via the first network **198** (e.g., a short-range communication network, such as Bluetooth™, wireless-fidelity (Wi-Fi) direct, or infrared data association (IrDA)) or the second network **199** (e.g., a long-range communication network, such as a legacy cellular network, a 5G network, a next-generation communication network, the Internet, or a computer network (e.g., a LAN or a wide area network (WAN))). These various types of communication modules may be implemented as a single component (e.g., a single chip), or may be implemented as multi components (e.g., multi chips) separate from each other. The wireless communication module **192** may identify and authenticate the electronic device **101** in a communication network, such as the first network **198** or the second network **199**, using subscriber information (e.g., international mobile subscriber identity (IMSI)) stored in the SIM **196**.

(36) The wireless communication module **192** may support a 5G network after a 4G network, and next-generation communication technology, e.g., new radio (NR) access technology. The NR access technology may support enhanced mobile broadband (eMBB), massive machine type communications (mMTC), or ultra-reliable and low-latency communications (URLLC). The wireless communication module **192** may support a high-frequency band (e.g., a mmWave band) to achieve, e.g., a high data transmission rate. The wireless communication module **192** may support various technologies for securing performance on a high-frequency band, such as, e.g., beamforming, massive multiple-input and multiple-output (massive MIMO), full dimensional MIMO (FD-MIMO), an array antenna, analog beam-forming, or a large scale antenna. The wireless communication module **192** may support various requirements specified in the electronic device **101**, an external electronic device (e.g., the electronic device **104**), or a network system (e.g., the second network **199**). According to an embodiment, the wireless communication module **192** may support a peak data rate (e.g., 20 Gbps or more) for implementing eMBB, loss coverage (e.g., 164 dB or less) for implementing mMTC, or U-plane latency (e.g., 0.5 ms or less for each of downlink (DL) and uplink (UL), or a round trip of 1 ms or less) for implementing URLLC.

(37) The antenna module **197** may transmit or receive a signal or power to or from the outside (e.g., the external electronic device) of the electronic device **101**. According to an embodiment, the antenna module **197** may include an antenna including a radiating element including a conductive material or a conductive pattern formed in or on a substrate (e.g., a printed circuit board (PCB)). According to an embodiment, the antenna module **197** may include a plurality of antennas (e.g., array antennas). In such a case, at least one antenna appropriate for a communication scheme used in a communication network, such as the first network **198** or the second network **199**, may be selected by, for example, the communication module **190** from the plurality of antennas. The signal or the power may be transmitted or received between the communication module **190** and the external electronic device via the at least one selected antenna. According to an embodiment, another component (e.g., a radio frequency integrated circuit (RFIC)) other than the radiating element may be additionally formed as a part of the antenna module **197**.

(38) According to various embodiments, the antenna module **197** may form a mmWave antenna module. According to an embodiment, the mmWave antenna module may include a printed circuit board, a RFIC disposed on a first surface (e.g., the bottom surface) of the printed circuit board, or adjacent to the first surface and capable of supporting a designated high-frequency band (e.g., the mmWave band), and a plurality of antennas (e.g., array antennas) disposed on a second surface (e.g., the top or a side surface) of the printed circuit board, or adjacent to the second surface and capable of transmitting or receiving signals of the designated high-frequency band.

(39) At least some of the above-described components may be coupled mutually and communicate

signals (e.g., commands or data) therebetween via an inter-peripheral communication scheme (e.g., a bus, general purpose input and output (GPIO), serial peripheral interface (SPI), or mobile industry processor interface (MIPI)).

(40) According to an embodiment, commands or data may be transmitted or received between the electronic device **101** and the external electronic device **104** via the server **108** coupled with the second network **199**. Each of the external electronic devices **102** and **104** may be a device of the same type as or a different type from the electronic device **101**. According to an embodiment, all or some of operations to be executed by the electronic device **101** may be executed at one or more of the external electronic devices **102** and **104**, and the server **108**. For example, if the electronic device **101** needs to perform a function or a service automatically, or in response to a request from a user or another device, the electronic device **101**, instead of, or in addition to, executing the function or the service, may request one or more external electronic devices to perform at least part of the function or the service. The one or more external electronic devices receiving the request may perform the at least portion of the function or the service requested, or an additional function or an additional service related to the request, and may transfer an outcome of the performing to the electronic device **101**. The electronic device **101** may provide the outcome, with or without further processing of the outcome, as at least portion of a reply to the request. To that end, a cloud computing, distributed computing, mobile edge computing (MEC), or client-server computing technology may be used, for example. The electronic device **101** may provide ultra low-latency services using, e.g., distributed computing or mobile edge computing. In an embodiment, the external electronic device **104** may include an Internet-of-things (IoT) device. The server **108** may be an intelligent server using machine learning and/or a neural network. According to an embodiment, the external electronic device **104** or the server **108** may be included in the second network **199**. The electronic device **101** may be applied to intelligent services (e.g., smart home, smart city, smart car, or healthcare) based on 5G communication technology or IoT-related technology.

(41) FIGS. 2A and 2B are perspective views of an portable device according to one embodiment. Referring to FIGS. 2A and 2B, according to an embodiment, a portable device **200** (e.g., the electronic device **101** of FIG. 1) may include a housing **210** including a first surface (or a front surface) **210A**, a second surface (or a rear surface) **210B**, and a side surface **210C** surrounding a space between the first surface **210A** and the second surface **210B**, and fastening members **250** and **260** connected to at least a portion of the housing **210** and configured to detachably attach the portable device **200** to a body part (e.g., a wrist or an ankle) of a user. In an embodiment (not shown), the housing may also refer to a structure that forms a portion of the first surface **210A**, the second surface **210B**, and the side surface **210C** of FIG. 2A. According to an embodiment, the first surface **210A** may be formed by a front plate **201** (e.g., a glass plate or a polymer plate including various coating layers) of which at least a portion is substantially transparent. The second surface **210B** may be formed by a rear plate **207** that is substantially opaque. The rear plate **207** may be formed of, for example, coated or colored glass, ceramic, polymer, metal (e.g., aluminum, stainless steel (SS), or magnesium), or a combination of at least two thereof. The side surface **210C** may be coupled to the front plate **201** and the rear plate **207** and may be formed by a side bezel structure (or a “side member”) **206** including a metal and/or a polymer. In an embodiment, the rear plate **207** and the side bezel structure **206** may be integrally formed and may include the same material (e.g., a metal material such as aluminum). The fastening members **250** and **260** may be formed of various materials and may have various shapes. For example, the fastening members **250** and **260** may be formed of woven fabric, leather, rubber, urethane, metal, ceramic, or a combination of at least two of the aforementioned materials and may be implemented in an integrated form or with a plurality of unit links that are movable relative to each other.

(42) According to an embodiment, the portable device **200** may include at least one of a display **220** (e.g., the display module **160** of FIG. 1), audio modules **205** and **208** (e.g., the input module

150 or the sound output module **155** of FIG. 1), a sensor module **211** (e.g., the sensor module **176** of FIG. 1), key input devices **202**, **203**, and **204** (e.g., the input module **150** of FIG. 1), or a connector hole **209**. In an embodiment, the portable device **200** may not include at least one (e.g., the key input devices **202**, **203**, and **204**, the connector hole **209**, or the sensor module **211**) of the components, or additionally include other components.

(43) The display **220** may be exposed through, for example, some portions of the front plate **201**. The display **220** may have a shape corresponding to a shape of the front plate **201**, and may have various shapes such as a circle, an oval, or a polygon. The display **220** may be coupled to or disposed adjacent to a touch sensing circuit, a pressure sensor capable of measuring an intensity (or pressure) of a touch, and/or a fingerprint sensor.

(44) The audio modules **205** and **208** may include a microphone hole **205** and a speaker hole **208**. A microphone for acquiring an external sound may be disposed in the microphone hole **205**. In some embodiments, a plurality of microphones may be disposed to detect a direction of a sound. The speaker hole **208** may be used as an external speaker and a call receiver for calls. In an embodiment, the speaker hole **208** and the microphone hole **205** may be implemented as a single hole, or a speaker (e.g., a piezo speaker) may be included without the speaker hole **208**.

(45) The sensor module **211** may generate an electrical signal or a data value corresponding to an internal operating state of the portable device **200** or an external environmental state (e.g., a user state). The sensor module **211** may include, for example, a biometric sensor module **211** (e.g., a heart rate monitor (HRM) sensor) disposed on the second surface **210B** of the housing **210**. The portable device **200** may further include at least one of sensor modules (not shown), for example, a gesture sensor, a gyro sensor, an atmospheric pressure sensor, a magnetic sensor, an acceleration sensor, a grip sensor, a color sensor, an infrared (IR) sensor, a biometric sensor, a temperature sensor, a humidity sensor, or an illuminance sensor.

(46) The sensor module **211** may include electrode areas **213** and **214** that form a portion of the surface of the portable device **200** and a biosignal detection circuit (not shown) electrically connected to the electrode areas **213** and **214**. For example, the electrode areas **213** and **214** may include a first electrode area **213** and a second electrode area **214** disposed on the second surface **210B** of the housing **210**. The sensor module **211** may be configured such that the electrode areas **213** and **214** obtain electrical signals from a part of the user's body and the biosignal detection circuit detects biometric information of the user based on the electrical signals.

(47) The key input devices **202**, **203**, and **204** may include a wheel key **202** disposed on the first surface **210A** of the housing **210** and rotatable in at least one direction, and/or side key buttons **203** and **204** disposed on the side surface **210C** of the housing **210**. The wheel key **202** may have a shape corresponding to the shape of the front plate **201**. In an embodiment, the portable device **200** may not include some or all of the above-described key input devices **202**, **203**, and **204**, and the key input devices **202**, **203**, and **204** that are not included may be implemented in other forms such as soft keys on the display **220**. The connector hole **209** may include another connector hole (not shown) that accommodates a connector (e.g., a universal serial bus (USB) connector) for transmitting and receiving power and/or data to and from an external electronic device and accommodates a connector for transmitting and receiving an audio signal to and from an external electronic device. The portable device **200** may further include, for example, a connector cover (not shown) that covers at least a portion of the connector hole **209** and blocks or reduces the infiltration of external foreign materials into the connector hole **209**.

(48) The fastening members **250** and **260** may be detachably fastened to at least a partial area of the housing **210** using locking members **251** and **261**. The fastening members **250** and **260** may include one or more of a fixing member **252**, a fixing member fastening hole **253**, a band guide member **254**, and a band fixing ring **255**.

(49) The fixing member **252** may be configured to fix the housing **210** and the fastening members **250** and **260** to a part (e.g., a wrist, an ankle, etc.) of the user's body. The fixing member fastening

hole **253** may correspond to the fixing member **252** to fix the housing **210** and the fastening members **250** and **260** to the part of the user's body. The band guide member **254** may be configured to limit a range of a movement of the fixing member **252** when the fixing member **252** is fastened to the fixing member fastening hole **253**, so that the fastening members **250** and **260** may be fastened to the part of the user's body in a state of being brought into close contact with the part of the user's body. The band fixing ring **255** may limit a range of a movement of the fastening member **250**, **260** in a state in which the fixing member **252** and the fixing member fastening hole **253** are fastened with each other.

(50) FIG. **3** is a block diagram illustrating an electronic device according to one embodiment. Referring to FIG. **3**, according to an embodiment, an electronic device **300** (e.g., the electronic device **102** of FIG. **1**) may include a plurality of antennas **310**, a processor **330**, and a display module **350**.

(51) The electronic device **300** may display various images through the display module **350** (e.g., including a display). Here, the images may include still images and moving images, and the electronic device **300** may display various images such as broadcast content and multimedia content through the display module **350**. Further, the electronic device **300** may display a user interface (UI) and an icon. The electronic device **300** may include, for example, a display device such as a smart TV or an Internet TV. However, embodiments are not limited thereto.

(52) The plurality of antennas **310** (e.g., antennas **417** of FIG. **4**) may wirelessly communicate with one or more portable devices (e.g., the electronic device **101** of FIG. **1** or the portable device **200** of FIGS. **2A** and **2B**) adjacent to the electronic device **300**. For example, the plurality of antennas **310** may be disposed at both ends of a display panel (e.g., a display panel **412** of FIG. **4** and/or a display panel **620** of FIG. **6**) of the display module **350** or on a bezel of a display panel **620**. One or more of the plurality of antennas **310** may be disposed at each of two or more symmetrical positions among top, bottom, left, and right of the display module **350**. The plurality of antennas **310** may be disposed, for example, one at each of symmetrical positions on the left and right of the display module **350** or one at each of symmetrical positions on the left, right, top, and bottom of the display module **350**. Alternatively, at least one of the plurality of antennas **310** may be disposed at each of the left, right, top, and bottom of the display module **350**. However, embodiments are not limited thereto.

(53) The processor **330** (e.g., a processor **414** of FIG. **4**) may scan whether there are one or more portable devices **200** using the plurality of antennas **310**. According to an embodiment, the portable device **200** may include, for example, a smart phone, a tag-type device, a dedicated band, a band-type wearable device, a watch-type wearable device, and a glasses-type wearable device. However, embodiments are not limited thereto. Hereinafter, for ease of description, the operation of a watch-type wearable device, which is an example of a portable device, will be mainly described. However, the description may also apply to various other portable devices.

(54) The processor **330** may scan signals received through the plurality of antennas **310**, thereby searching for and/or recognizing one or more portable devices **200** adjacent to the electronic device **300**. A method of searching for and/or recognizing one or more portable devices **200** by the processor **330** will be described further below with reference to FIG. **5**.

(55) The processor **330** may define a three-dimensional recognition space (e.g., a recognition space **630** of FIG. **6**, a recognition space **740** of FIG. **7**, a recognition space **830** of FIG. **8**, a recognition space **850** of FIG. **8**, and/or a recognition space **1340** of FIG. **13**) based on a first signal transmitted from the portable device **200** for space setting. Here, the "recognition space" may refer, for example, to a three-dimensional virtual space representing a range within which the electronic device **300** may recognize the position of a user wearing the portable device **200**. The processor **330** may define the recognition space **630** relative to a front side (e.g., a +z direction of FIG. **6**) of the display module **350** based on the first signal. The front side of the display module **350** may refer, for example, more specifically, to a front side of the display panel (e.g., the display panel **412**

of FIG. 4 and/or the display panel **620** of FIG. 6) included in the display module **350**. In this case, the “front side” of the display panel may, for example, be the front side of a wireless signal space, or the front side of a space where a user consumes exercise content, that is, the front side of the display panel **620** corresponding to a space where a user exercises. According to an embodiment, when trainees view a projection screen that is separately connected to show a screen of a small electronic device that a personal trainer views, the front side of the display panel may be the front side of the projection screen or a space facing the projection screen.

(56) Based on wireless signals, the front side may be recognized, for example, as the front side of the electronic device **300** on which the screen of the display panel **620** is displayed, or as the rear side of the electronic device **300**. Since the front side and the rear side of the electronic device **300** may be recognized as the same by signals, the front side of the wireless signal space may be the front side of the electronic device **300** or the rear side of the electronic device **300**. For example, the electronic device **300** may distinguish the front side of the wireless signal space, for example, by instructing to move left and right in front of the display panel **620**, performing triangulation using the plurality of antennas **310**, or turning on a camera.

(57) In an embodiment, the “front side” of the display panel may be construed as the front side of the display panel **620** corresponding to a space where a user exercises. For example, the electronic device **300** may recognize the front side of the display panel **620** based on whether a user is captured through a camera, or recognize whether the portable device **200** is positioned on the front side of a space where a user consumes an exercise content through ultra-wideband (UWB) wireless signals based on the range of the recognition space **630** which will be described below.

(58) In response to a space setting mode being started in the portable device **200** for setting the recognition space **630**, the processor **330** may provide a user of the portable device **200** with a guide to guide the portable device **200** to be positioned in a boundary area of the recognition space **630** in which the exercise content is to be utilized. The processor **330** may set the plurality of antennas **310** to receive the first signal transmitted from the portable device **200** according to the guide. When each of the plurality of antennas **310** successfully receives the first signal transmitted from the portable device **200** in the boundary area of the recognition space **630** according to the guide, the processor **330** may provide a guide to guide the portable device **200** to move to a boundary area next to the boundary area.

(59) When each of the plurality of antennas **310** successfully receives the first signal, the processor **330** may define the recognition space **630** using the first signal received by each of the plurality of antennas **310**. The recognition space **630** according to an embodiment and a method of defining the recognition space **630** by the processor **330** will be described further below with reference to FIGS. 6, 7, and 8.

(60) The processor **330** may calculate the position of the portable device **200** in the recognition space **630** based on a second signal transmitted from the portable device **200**. In this case, the second signal transmitted from the portable device **200** may be the same as the first signal or different from the first signal. The processor **330** may calculate a first relative position including a distance and an angle between the electronic device **300** and the portable device **200** using a difference in times at which the plurality of antennas **310** receive the second signal. The processor **330** may identify whether the portable device **200** is positioned in the recognition space **630** based on the first relative position. For example, when it is identified that the portable device **200** is not positioned in the recognition space **630**, the processor **330** may reconstruct the exercise content by deleting a character corresponding to the portable device **200** from the exercise content.

Conversely, when it is identified that the portable device **200** is positioned in the recognition space **630**, the processor **330** may determine whether identification information of the portable device **200** is or corresponds to pre-enrolled information, and reconstruct the exercise content with a character corresponding to the portable device **200** according to whether identification information is or corresponds to pre-enrolled information. A method of calculating the position of the portable

device **200** based on the second signal by the processor **330** will be described further below with reference to FIGS. **9** and **10**.

(61) The processor **330** may generate exercise content based on the position of the portable device **200**. The processor **330** may identify whether the portable device **200** leaves the recognition space **630** or newly enters the recognition space **630** while the display module **350** is displaying the exercise content, based on the second signal. For example, when it is identified based on the second signal that the portable device **200** leaves the recognition space **630**, the processor **330** may remove a character corresponding to the leaving portable device **200** from the exercise content. Conversely, when it is identified based on the second signal that the portable device **200** newly enters the recognition space **630**, the processor **330** may add a character corresponding to the newly entering portable device **200** to the exercise content. A method of generating the exercise content by the processor **330** will be described further below with reference to FIGS. **11, 12, 13, 14, 15**, and **16**.

(62) The processor **330** (e.g., including processing circuitry) may control the overall operation of the electronic device **300**. The processor **330** may include one or more processors. The processor **330** may include a plurality of processor modules (e.g., a first processor module and a second processor module), and each of the plurality of processor modules may partially and separately perform any data operation or data processing. Specifically, the processor **330** may perform or control the operation of the electronic device **300** by executing at least one instruction stored in a memory (not shown).

(63) In addition, the processor **330** may perform at least one method that will be described with reference to FIGS. **4** through **17** below or a scheme corresponding to the at least one method. The electronic device **300** may be one in which the processor **330** is implemented as hardware having a circuit that is physically structured to execute desired operations. For example, the desired operations may include code or instructions included in a program. The hardware-implemented processor **330** may include, for example, a microprocessor, a central processing unit (CPU), a graphics processing unit (GPU), a processor core, a multi-core processor, a multiprocessor, an application-specific integrated circuit (ASIC), a field-programmable gate array (FPGA), and/or a neural processing unit (NPU). Alternatively, the processor **330** may be implemented as a digital signal processor (DSP) that processes a digital image signal, an artificial intelligence (AI) processor, or a time controller (TCON). However, embodiments are not limited thereto, and the processor **330** may include one or more of a CPU, a micro controller unit (MCU), a micro processing unit (MPU), a controller, an application processor (AP), a communication processor (CP), or an ARM processor, or may be defined by a corresponding term. Further, the processor **330** may be implemented as a system on chip (SoC) with a processing algorithm embedded or a large scale integration (LSI), or implemented in the form of an ASIC or FPGA.

(64) The processor **330** may drive an operating system or an application program to control hardware or software components connected to the processor **330** and perform various data processing or computation. In addition, the processor **330** may load instructions or data received from at least one of the other components to a memory (not shown) to process the same, and store a variety of data in a non-volatile memory (not shown).

(65) The display module **350** (e.g., including a display) may display exercise content generated by the processor **330**. In this case, the exercise content may include, for example, a dance content and a group exercise content. As shown in FIGS. **14, 15**, and **16**, the exercise content may include, for example, at least one of a character corresponding to a user wearing the portable device **200** or exercise information of the user wearing the portable device **200**. The character corresponding to the user wearing the portable device **200** may be, for example, an avatar of the user or an emoji. However, embodiments are not limited thereto. The character may be selected by the user from among various characters provided by the processor **330** to the user or arbitrarily set by the processor **330**. The exercise information of the user may include, for example, biometric information of the user (e.g., the body temperature, the heart rate, and/or the consumed calories of

the user) sensed through the portable device **200** while the user performs various exercises such as dancing, spinning, yoga, or fitness according to the exercise content displayed through the display module **350** of the electronic device **300**. However, embodiments are not limited thereto.

(66) More specifically, the display module **350** may include an integrated circuit (IC) chip (not shown), and the IC chip may display an image based on an image signal received from the processor **330**. For example, the IC chip may display the image by generating driving signals of a plurality of light sources based on the image signal received from the processor **330** and controlling light emitted from a plurality of pixels (not shown) included in the display module **350** based on the driving signals.

(67) The display module **350** may include a driving circuit that may be implemented in the form of an a-si thin film transistor (TFT), a low temperature poly silicon (LTPS) TFT, or an organic TFT (OTFT), and a backlight unit.

(68) According to an embodiment, the display module **350** may be implemented as various types of displays, such as a liquid crystal display (LCD), a quantum dot (QD) display panel, an organic light-emitting diode (OLED), a liquid crystal on silicon (LCoS), a digital light processing (DLP), a quantum dot light-emitting diode (QLED), a micro light-emitting diode (μ LED), or a mini LED. Meanwhile, the display module **350** may be implemented as a touch screen combined with a touch sensor, a flexible display, a rollable display, a three-dimensional (3D) display, or a display in which a plurality of display modules are physically connected.

(69) FIG. **4** is a block diagram of a system for providing an exercise content according to one embodiment. Referring to FIG. **4**, according to an embodiment, a system **400** may include an electronic device **410** (e.g., the electronic device **102** of FIG. **1**, the electronic device **300** of FIG. **3**, an electronic device **510** of FIG. **5**, an electronic device **710** of FIG. **7**, an electronic device **810** of FIG. **8**, an electronic device **910** of FIG. **9**, an electronic device **1001** of FIG. **10**, an electronic device **1220** of FIG. **12**, an electronic device **1320** of FIG. **13**, an electronic device **1420** of FIG. **14**, and/or an electronic device **1510** of FIG. **15**), and a wearable device **430** (e.g., the electronic device **101** of FIG. **1**, the portable device **200** of FIGS. **2A** and **2B**, a portable device **720** of FIG. **7**, a portable device **820** of FIG. **8**, a portable device **930** of FIG. **9**, a portable device **1003** of FIG. **10**, portable devices **1201**, **1203**, and **1205** of FIG. **12**, portable devices **1301** and **1303** of FIG. **13**, and/or portable devices **1401**, **1403**, and **1405** of FIG. **14**).

(70) The electronic device **410** may include a user input unit **411**, a display panel **412** (e.g., the display panel **620** of FIG. **6**), an interface **413**, a processor **414** (e.g., the processor **330** of FIG. **3**), a fitness service provider **415**, a real time location system (RTLS) **416**, and antennas **417** including antenna 1 through antenna N (e.g., the plurality of antennas **310** of FIG. **3**, and/or a plurality of antennas **911**, **913**, **915**, and **917** of FIG. **9**).

(71) The electronic device **410** may be, for example, a device including the display panel **412** on which the antennas **417** are mounted. However, embodiments are not limited thereto. The antennas **417** may be disposed, for example, one at each of symmetrical positions on the left and right of the display panel **412** or one at each of symmetrical positions on the left, right, top, and bottom of the display panel **412**. In addition, at least one of the antennas **417** may be disposed at each of the left, right, top, and bottom of the display panel **412**. However, embodiments are not limited thereto. The antennas **417** mounted at each position of the display panel **412** may receive a signal transmitted by the wearable device **430**. The position of the wearable device **430** or the position of the user wearing the wearable device **430** may be measured based on a difference between the times at which the antennas **417** receive the signal.

(72) The user input unit **411** (e.g., including circuitry) may receive an input of a user on contents displayed on the display panel **412** of the electronic device **410**. The user input unit **411** may be, for example, a device for receiving various user inputs, such as a voice input, a camera input, a keyboard input, and/or a pen input, a dedicated controller, and/or a remote control. However, embodiments are not limited thereto.

(73) The display panel **412** (e.g., including a display) may display exercise content including fitness content provided through the fitness service provider **415**.

(74) The interface **413** may, for example, including communication circuitry to provide connectivity with devices (e.g., portable devices) connected to the electronic device **410**. The connectivity may be a wireless communication scheme that is the same as a connectivity of the portable device without specifying the specification of the electronic device **410**, and may be, for example, any communication scheme capable of a time difference of arrival (TDoA) method. The connectivity may include, for example, Bluetooth communication, Bluetooth low energy (BLE) communication, Wi-Fi (WiFi) communication, near field communication (NFC), and/or ultra-wideband (UWB) communication. However, embodiments are not necessarily limited thereto.

(75) The electronic device **410** may, for example, include a full-time power supply and have low mobility and thus, may be advantageous in a scanning operation rather than a broadcasting operation. In addition, since the electronic device **410** may be relatively large compared to mobile devices, a large UWB antenna may be disposed thereon. Thus, the electronic device **410** may be advantageous in determining the directional resolution of another device.

(76) The processor **414** (e.g, including processing circuitry) may scan whether there is at least one wearable device **430** using the antennas **417**, and define a three-dimensional recognition space (e.g., the recognition space **630** of FIG. 6, the recognition space **740** of FIG. 7, the recognition space **830** of FIG. 8, the recognition space **850** of FIG. 8, and/or the recognition space **1340** of FIG. 13) based on a first signal transmitted from the wearable device **430** for space setting.

(77) The fitness service provider **415** may generate and/or provide exercise content for a fitness service based on the position of the wearable device **430** calculated by the RTLS **416**. For example, when the calculated position of the wearable device **430** corresponds to the right side of the recognition space **630**, the fitness service provider **415** may generate exercise content displaying a character corresponding to the wearable device **430** on the right side of the scene. As another example, when the calculated position of the wearable device **430** corresponds to the middle of the three-dimensional recognition space **630**, the fitness service provider **415** may generate exercise content displaying a character corresponding to the wearable device **430** in the middle of the scene. As described above, the fitness service provider **415** may provide exercise content displaying a character reflecting the position of the wearable device **430** calculated by the RTLS **416**, thereby providing exercise content reflecting a movement of a user in real time. In addition, the fitness service provider **415** may provide, for example, a service provided by an application executed by the processor **414** and/or a service provided by a server to which the wearable device **430** is connected.

(78) The RTLS **416** may calculate the position of the wearable device **430** in the recognition space **630** by collecting a signal (e.g., a second signal) received by each of the N antennas **417** from the wearable device **430**. The RTLS **416** may include various circuitry such as a clock used by the processor **414** to determine differences in arrival time of signals received by the antennas **417**.

(79) The antennas **417** may be for wireless communication with the wearable device **430**. The antennas **417** may be disposed between the display panel **412** and a support member (not shown). The antennas **417** may include antennas for various wireless communication methods, for example, a Bluetooth antenna, a Wi-Fi antenna, an infrared data association (IrDA) antenna, a legacy cellular antenna, a 5G antenna, a near field communication (NFC) antenna, a wireless charging antenna, and/or a magnetic secure transmission (MST) antenna. However, embodiments are not limited thereto. For example, the antennas **417** may perform short-range communication with an external device, wirelessly transmit and receive power used for charging, or transmit a magnetism-based signal including a short-range communication signal or payment data.

(80) According to an embodiment, when the electronic device **410** performs a predetermined function, multiple wireless connections may be provided in a complex and sequential manner. In this case, for example, according to current consumption and usability, a Bluetooth communication

antenna may be primarily used, and a UWB antenna may be secondarily used.

(81) In an embodiment, an antenna structure may be formed by a portion of a side bezel structure and/or the support member, or a combination thereof.

(82) The wearable device **430** may include a processor **431** (e.g., including processing circuitry), a user input unit **432** (e.g., including circuitry), a battery **433** (e.g., the battery **189** of FIG. 1), an interface **434** (e.g., the communication module **190** of FIG. 1), and an antenna **435** (e.g., the antenna module **197** of FIG. 1).

(83) In response to an input being received through the user input unit **432** (e.g., an input to a “Set” button), the processor **431** may control to transmit a signal including device information of the wearable device **430** and/or information on the position of the wearable device **430** in which the Set button is input to the electronic device **410**.

(84) The user input unit **432** may receive the input on the “Set” button from the user who has moved to the boundary area of the recognition space **630** according to a guide provided through the wearable device **430**, which is set to be in the mode for space setting, and transmit the input to the processor **431**.

(85) The battery **433**, which is a device for supplying power to at least one component of the wearable device **430**, may include, for example, a primary cell that is not rechargeable, a secondary cell that is rechargeable, or a fuel cell. For example, at least a portion of the battery **433** may be disposed on substantially the same plane as a printed circuit board. The battery **433** may be integrally disposed inside the wearable device **430**, or disposed detachably from the wearable device **430**.

(86) The interface **434** may including communication circuitry to provide connectivity with devices (e.g., the electronic device **410**) connected to the wearable device **430**. The connectivity may be a wireless communication scheme that is the same as the connectivity of the electronic device **410** without specifying the specification of the wearable device **430**, and may be, for example, any communication scheme capable of the TDoA method. The connectivity may include, for example, Bluetooth communication, Bluetooth low energy (BLE) communication, Wi-Fi (WiFi) communication, near field communication (NFC), and/or ultra-wideband (UWB) communication. However, embodiments are not necessarily limited thereto.

(87) The antenna **435** may be disposed between a printed circuit board (not shown) and a rear plate (not shown) (e.g., the rear plate **207** of FIG. 2B). However, embodiments are not limited thereto. The antenna **435** may include antennas for various wireless communication methods, for example, a Bluetooth antenna, a Wi-Fi antenna, an infrared data association (IrDA) antenna, a legacy cellular antenna, a 5G antenna, a near field communication (NFC) antenna, a wireless charging antenna, and/or a magnetic secure transmission (MST) antenna. However, embodiments are not limited thereto. For example, the antenna **435** may perform short-range communication with the electronic device **410**, wirelessly transmit and receive power used for charging, or transmit a magnetism-based signal including a short-range communication signal. In an embodiment, an antenna structure may be formed by a portion of a side bezel structure (not shown) (e.g., the side bezel structure **206** of FIG. 2A) and/or the rear plate (not shown) (e.g., the rear plate **207** of FIG. 2B), or a combination thereof.

(88) FIG. 5 is a diagram illustrating an operation of an electronic device according to one embodiment. Referring to FIG. 5, according to an embodiment, a diagram **500** illustrating a situation in which three users **501**, **503**, and **505** wearing portable devices (e.g., the electronic device **101** of FIG. 1, the portable device **200** of FIGS. 2A and 2B, the wearable device **430** of FIG. 4, the portable device **720** of FIG. 7, the portable device **820** of FIG. 8, the portable device **930** of FIG. 9, the portable device **1003** of FIG. 10, the portable devices **1201**, **1203**, and **1205** of FIG. 12, the portable devices **1301** and **1303** of FIG. 13, and/or the portable devices **1401**, **1403**, and **1405** of FIG. 14) are captured through a camera **515** disposed in a front side (e.g., the +z direction of FIG. 6) of a display panel (e.g., the display panel **412** of FIG. 4 and/or the display panel **620** of

FIG. 6) of the electronic device **510** (e.g., the electronic device **102** of FIG. 1, the electronic device **300** of FIG. 3, the electronic device **410** of FIG. 4, the electronic device **710** of FIG. 7, the electronic device **810** of FIG. 8, the electronic device **910** of FIG. 9, the electronic device **1001** of FIG. 10, the electronic device **1220** of FIG. 12, the electronic device **1320** of FIG. 13, the electronic device **1420** of FIG. 14, and/or the electronic device **1510** of FIG. 15) is shown.

(89) For example, the electronic device **510** may perform position recognition between devices of a wireless connection solution through a display module (e.g., the display module **350** of FIG. 3) and a processor (e.g., the processor **330** of FIG. 3) supporting wireless connection such as ultra wideband (UWB), thereby recognizing a plurality of users (e.g., users A, B, and C), tracking the positions of the plurality of users, and/or providing intuitive exercise content **530** according to relative positions between the electronic device **510** and the portable devices (e.g., portable devices **1003**). Here, the “intuitive” exercise content **530** may refer, for example, to exercise content displaying characters respectively corresponding to the plurality of users so that the positions of the plurality of users wearing the portable devices in a recognition space (e.g., the recognition space **630** of FIG. 6, the recognition space **740** of FIG. 7, the recognition space **830** of FIG. 8, the recognition space **850** of FIG. 8, and/or the recognition space **1340** of FIG. 13) in the front side (e.g., the +z direction of FIG. 6) of the display panel **620** of the electronic device **510** may be immediately verified.

(90) When the users approach the electronic device **510** in the front side (e.g., in the +z direction in FIG. 6) of the display panel **620**, the electronic device **510** may recognize the positions of the portable devices (e.g., portable devices **1003**) that the users are wearing and at the same time identify the plurality of users, thereby improving the use accessibility of each user to the exercise content.

(91) The electronic device **510** may track the positions of the plurality of users positioned in the front side (e.g., in the +z direction of FIG. 6) of the display panel **620** and wearing the portable devices (e.g., portable devices **1003**). Hereinafter, the “positions of the plurality of users” refers to the respective positions of the users wearing the portable devices **1003** and may, for example, refer to the positions of the portable devices **1003**.

(92) For example, the electronic device **510** may track an absolute position between the display panel **620** and the portable devices (e.g., portable devices **1003**) and a relative position between the portable devices **1003**. When the portable devices move to new positions as the plurality of users move, the electronic device **510** may reconstruct or update the exercise content to reflect the new positions. In addition, when a user positioned in the front side (e.g., the +z direction) of the display panel **620** moves and leaves the recognition space **630** and/or when a user newly enters the recognition space **630** from the outside, the electronic device **510** may display, in the exercise content, characters moved based on the new positions of the plurality of users to intuitively represent whether the users move, thereby improving the usability and the immersion of the users with respect to the recognition space **630**.

(93) FIG. 6 is a diagram illustrating an example of a range of a recognition space in which an electronic device may recognize a position of a user wearing a portable device according to one embodiment. Referring to FIG. 6, according to an embodiment, a diagram **600** illustrating an example of the recognition space **630** (e.g., the recognition space **740** of FIG. 7, the recognition space **830** of FIG. 8, the recognition space **850** of FIG. 8, and/or the recognition space **1340** of FIG. 13) set based on a front side (e.g., the +z direction of FIG. 6) of an electronic device **610** (e.g., the electronic device **102** of FIG. 1, the electronic device **300** of FIG. 3, the electronic device **410** of FIG. 4, the electronic device **510** of FIG. 5, the electronic device **710** of FIG. 7, the electronic device **810** of FIG. 8, the electronic device **910** of FIG. 9, the electronic device **1001** of FIG. 10, the electronic device **1220** of FIG. 12, the electronic device **1320** of FIG. 13, the electronic device **1420** of FIG. 14, and/or the electronic device **1510** of FIG. 15) is shown.

(94) The recognition space **630** may refer, for example, to a three-dimensional virtual space in

which the electronic device **610** may recognize a user wearing a portable device (e.g., the electronic device **101** of FIG. **1**, the portable device **200** of FIGS. **2A** and **2B**, the wearable device **430** of FIG. **4**, the portable device **720** of FIG. **7**, the portable device **820** of FIG. **8**, the portable device **930** of FIG. **9**, the portable device **1003** of FIG. **10**, the portable devices **1201**, **1203**, and **1205** of FIG. **12**, the portable devices **1301** and **1303** of FIG. **13**, and/or the portable devices **1401**, **1403**, and **1405** of FIG. **14**). The electronic device **610** may define the three-dimensional recognition space **630** having x, y, and z axes based on a space positioned in the front side (e.g., the +z direction of FIG. **6**) of the display panel **620** (e.g., the display panel **412** of FIG. **4**).

(95) The electronic device **610** may set the virtual recognition space **630**, thereby freely setting the activity radius of the users without the constraints of space due to the camera angle.

(96) The electronic device **610** may measure a relative position between the display panel **620** and the wearable device (e.g., wearable device **430**) to distinguish the front, rear, left, right, up, and down directions. The recognition space **630** may vary according to the specification of a connectivity (e.g., via the interface **413** of FIG. **4**) of the electronic device **610**. The electronic device **610** may freely set the range of the recognition space **630** based on the size of a general indoor space.

(97) For example, the recognition space **630** may have a range corresponding to the size of the display panel **620** of the electronic device **610** or the screen of the electronic device **610**.

Alternatively, since transmission of a general wireless signal may appear in a circular or spherical shape, the recognition space **630** may have a range in the form of a semicircle or an arc in front of the electronic device **610**. In addition, the recognition space **630** may be defined by the walls of a room or indoor space in which the electronic device **610** is positioned. However, embodiments are not limited thereto.

(98) For example, when a user executes exercise content through a large-screen display panel **620**, the electronic device **610** may set a space to be utilized for an exercise, that is, the recognition space **630**, through a calibration function before the exercise according to the exercise content being started. For example, the electronic device **610** may receive, through antennas (e.g., the plurality of antennas **310** of FIG. **3**, the antennas **417** of FIG. **4**, and/or the plurality of antennas **911**, **913**, **915**, and **917** of FIG. **9**), a first signal transmitted through the wearable device **430** at the boundary of the recognition space **630**. The electronic device **610** may define the recognition space **630** based on a position determined through the first signal received by each of the antennas **417**. In this case, the first signal transmitted from the wearable device **430** for setting the recognition space **630** may be referred to as a “calibration signal”. An example method of defining the recognition space **630** by the electronic device **610** will be described further below with reference to, for example, FIG. **7**.

(99) FIG. **7** is a diagram illustrating a method of defining a three-dimensional recognition space by an electronic device according to one embodiment. Referring to FIG. **7**, according to an embodiment, diagrams **701**, **703**, **705**, and **707** illustrating processes performed as a user **730** wearing the wearable device **720** (e.g., the electronic device **101** of FIG. **1**, the portable device **200** of FIGS. **2A** and **2B**, the wearable device **430** of FIG. **4**, the portable device **820** of FIG. **8**, the portable device **930** of FIG. **9**, the portable device **1003** of FIG. **10**, the portable devices **1201**, **1203**, and **1205** of FIG. **12**, the portable devices **1301** and **1303** of FIG. **13**, and/or the portable devices **1401**, **1403**, and **1405** of FIG. **14**) starts a space setting mode in the portable device **720** for setting the recognition space **740** (e.g., the recognition space **630** of FIG. **6**, the recognition space **830** of FIG. **8**, the recognition space **850** of FIG. **8**, and/or the recognition space **1340** of FIG. **13**) are shown.

(100) According to an embodiment, the electronic device **710** (e.g., the electronic device **102** of FIG. **1**, the electronic device **300** of FIG. **3**, the electronic device **410** of FIG. **4**, the electronic device **510** of FIG. **5**, the electronic device **610** of FIG. **6**, the electronic device **810** of FIG. **8**, the electronic device **910** of FIG. **9**, the electronic device **1001** of FIG. **10**, the electronic device **1220**

of FIG. 12, the electronic device 1320 of FIG. 13, the electronic device 1420 of FIG. 14, and/or the electronic device 1510 of FIG. 15) and the portable device 720 may each provide a space setting mode for space setting.

(101) As shown in the diagram 701, the user 730 wearing the portable device 720 may start the space setting mode for setting the recognition space 740. For example, an area of the recognition space 740 may be set based on a screen displayed by an image sensor. According to an embodiment, the recognition space 740 may correspond to an exercise space for home training. Since a movement of a user is captured through the image sensor (e.g., a camera sensor or a vision sensor), the area recognized by the image sensor may be displayed on the screen of the electronic device 710. According to an embodiment, the range of the recognition space 740 may be artificially adjusted according to the type of the exercise content.

(102) In addition, since a wireless signal for UWB communication has a wide coverage, the user 730 wearing the portable device 720 may be recognized as being in a space in a front side (e.g., the +z direction of FIG. 6) of the electronic device 710 even when far from the electronic device 710. In an embodiment, the user may artificially set the range of the recognition space 740 through the various methods described above, thereby preventing another user from unnecessarily appearing on the screen even if a wireless signal is detected.

(103) According to an embodiment, an image sensor and/or a camera may be attached to the electronic device 710, or an add-on product may be attached thereto for security issues. In this case, the position at which the image sensor or the camera is mounted or the angle of view of the camera may be different, and accordingly, the range of the recognition space 740 may vary. When the position of the image sensor and/or the camera attached to the electronic device 710 or the angle of view of the camera is different, the range of the recognition space 740 may be artificially corrected by a user.

(104) As the space setting mode is selected in the electronic device 710, a guide for the user 730 of the portable device 720 may be provided through a display panel (e.g., the display panel 412 of FIG. 4 and/or the display panel 620 of FIG. 6) of the electronic device 710. The guide may include a text phrase, a voice, and/or an image (or images) guiding the user 730 of the portable device 720 to be positioned in the boundary area of the recognition space 740 in which the exercise content is utilized. However, embodiments are not limited thereto. The guide may include, for example, a guide phrase of “Move to position A and touch [Set] on your Watch” and an image or a voice indicating the position A may be output together.

(105) At the same time of providing the guide to the user 730 through the screen, the electronic device 710 may set the antennas (e.g., the plurality of antennas 310 of FIG. 3, the antennas 417 of FIG. 4, and/or the antennas 911, 913, 915, and 917 of FIG. 9) to enter a signal receiving mode to receive a signal transmitted from the portable device 720.

(106) When the electronic device 710 provides the guide, the user 730 may move to the position A displayed on the screen of the electronic device 710 and select the “Set” button of the portable device 720 and/or, for example, utter “Set” or “Position set”, as shown in the diagram 703. In this case, the position A may correspond to a relative position between the electronic device 710 and the portable device 720. The position A may correspond to the boundary area of the recognition space 740. When the set button is selected and/or the voice of the user “Set” or “Position set” is detected, the portable device 720 may transmit a first signal for space setting. The plurality of antennas (e.g., the plurality of antennas 310 of FIG. 3, the antennas 417 of FIG. 4, and/or the plurality of antennas 911, 913, 915, and 917 of FIG. 9) respectively disposed at two or more symmetrical positions among the top, bottom, left, and right of the display panel 620 of the electronic device 710 may receive the first signal transmitted by the portable device 720 in the boundary area at the position A at different (first) times T.sub.d1, T.sub.d2, T.sub.d3, and T.sub.d4.

(107) When each of the plurality of antennas (e.g., antennas 911, 913, 915, and 917) successfully receives the first signal transmitted from the portable device 720 in the boundary area at the

position A according to the guide, the electronic device **710** may provide a guide for next position recognition as shown in the diagram **705**. In this case, the guide may be a guide for guiding the user to move to a location B, which is a next boundary area adjacent to the boundary area of the location A. The guide may include, for example, a guide phrase for next position recognition of “Position A recognized. Move to position B and touch [Set] on your Watch” and an image or a voice indicating the position B may be output together.

(108) When the electronic device **710** provides the guide that requests the user to move to the position B, the user **730** may move to the position B displayed on the screen of the electronic device **710** and select the “Set” button of the portable device **720**, as shown in the diagram **707**. As the Set button is selected, the portable device **720** may transmit a first signal for space setting. One or more of the plurality of antennas (e.g., antennas **911**, **913**, **915**, and **917**) respectively disposed at two or more symmetrical positions among the top, bottom, left, and right of the display panel (e.g., display panel **620**) of the electronic device **710** may receive the first signal transmitted by the portable device **720** in the boundary area at the position B at different (second) times T.sub.d1, T.sub.d2, T.sub.d3, and T.sub.d4.

(109) The electronic device **710** may repeat the processes shown in the diagrams **701** through **707**, and thereby complete the settings for four boundary areas (e.g., the boundary area at the position A, the boundary area at the position B, a boundary area at a position C, and/or a boundary area at a position D) of each space. For example, the area corresponding to the upper left corner of the display panel **620** of the electronic device **710** may correspond to the position A, and the area corresponding to the upper right corner of the display panel **620** may correspond to the position B. The area corresponding to the lower left corner of the display panel **620** may correspond to the position C, and the area corresponding to the lower right corner of the display panel **620** may correspond to the position D.

(110) When each of the plurality of antennas (e.g., antennas **911**, **913**, **915**, and **917**) successfully receives the transmitted first signal in the four boundary areas, the electronic device **710** may define the recognition space **740** using the first signal received by each of the plurality of antennas (e.g., antennas **911**, **913**, **915**, and **917**).

(111) FIG. **8** is a diagram illustrating examples of a recognition space defined by an electronic device based on first signals transmitted from portable devices according to one embodiment.

(112) An electronic device **810** may define the recognition space **830** (e.g., the recognition space **630** of FIG. **6**, the recognition space **740** of FIG. **7**, and/or the recognition space **1340** of FIG. **13**) in an area larger than a screen, as shown in a diagram **801**. For example, the electronic device **810** may set an area corresponding to 1.5 times the width of the screen of the electronic device **810** as a horizontal boundary area, and define the recognition space **830** by providing a guide to the user wearing the portable device **820** to move to the four boundary areas (e.g., the boundary area at the position A, the boundary area at the position B, the boundary area at the position C, and/or the boundary area at the position D).

(113) As another example, the electronic device **810** may define an area smaller than the screen as the recognition space **850**, as shown in the diagram **803**. For example, the electronic device **810** may set an area corresponding to 0.8 times the size of the screen of the electronic device **810** as a horizontal and vertical boundary area, and define the recognition space **850** by providing a guide to the user wearing the portable device **820** to move to the four boundary areas (e.g., the boundary area at the position A, the boundary area at the position B, the boundary area at the position C, and/or the boundary area at the position D).

(114) FIG. **9** is a diagram illustrating a method of calculating, by an electronic device, positions of portable devices based on second signals transmitted from the portable devices according to one embodiment. Referring to FIG. **9**, the portable device **930** transmitting a second signal to the plurality of antennas **911**, **913**, **915**, and **917** (e.g., the plurality of antennas **310** of FIG. **3** and/or the antennas **417** of FIG. **4**) disposed at symmetrical positions of top, bottom, left, and right of a

display panel (e.g., the display panel **620** of FIG. **6**) of the electronic device **910** is shown.

(115) The electronic device **910** may calculate a first relative position between the portable device **930** positioned in a front side (e.g., the +z direction of FIG. **6**) of the display module **350** and the electronic device **910**, using differences in the times T.sub.d1, T.sub.d2, T.sub.d3, and T.sub.d4 at which the antennas **911**, **913**, **915**, and **917** disposed at the symmetrical positions receive the second signal. For example, it may take 4 seconds (T.sub.d1) for the first antenna to receive the second signal, and it may take 2.5 seconds (T.sub.d2) for the second antenna to receive the second signal. Further, it may take 3 seconds (T.sub.d3) for the third antenna to receive the second signal, and it may take 1 second (T.sub.d4) for the fourth antenna to receive the second signal. These examples times are provided by way of illustration and explanation and do not necessarily reflect the times that would be involved in an actual implementation.

(116) For example, the electronic device **910** may calculate, by the TDoA method, the first relative position between the portable device **930** and the electronic device **910** based on the differences in the times at which the antennas **911**, **913**, **915**, and **917** receive the second signal. The following various methods may be used to calculate the first relative position between the portable device **930** and the electronic device **910**.

(117) For example, the electronic device **910** may receive a signal unilaterally transmitted by the portable device **930** (e.g., a signal broadcast through Bluetooth or WiFi), and measure a distance based on a signal strength of the received signal. As such, the method of measuring the distance based on the signal strength of the received signal may be referred to as the received signal strength (RSS) method.

(118) In contrast, UWB communication uses the time of flight (ToF) method or the round trip time (RTT) method and thus, may be performed in a manner that the electronic device **910** transmits a first signal to the portable device **930** and the portable device **930** having received the first signal transmits a second signal back to the electronic device **910**. The time-based UWB communication may exhibit relatively high positioning accuracy compared to the RSS method. Further, based on the time difference between the plurality of antennas **911**, **913**, **915**, and **917** of the electronic device **910**, it is possible to determine the direction of the portable device **930** relative to the electronic device **910** as well as the distance between the electronic device **910** and the portable device **930**.

(119) In addition, a method of measuring the distance between the electronic device **910** and the portable device **930** based on time information when the portable device **930** transmits a wireless signal (e.g., a method that uses the global positioning system (GPS)) may be used.

(120) Hereinafter, a method of measuring the distance between the electronic device **910** and the portable device **930** mainly using the ToF method or the RTT method by UWB communication will be described, but the disclosure is not limited in this respect.

(121) As shown in FIG. **9**, the electronic device **910** may include a plurality of UWB antennas **911**, **913**, **915**, and **917** arranged in the form of an array.

(122) For example, when the antenna **911** or **915** disposed on the left side of the display panel and the antenna **913** or **917** disposed on the right side of the display panel exchange signals with the portable device **930** by the RTT method, the distance from the left side and the distance from the right side relative to the portable device **930** in the front side (e.g., the +z direction of FIG. **6**) of the electronic device **910** may be measured (calculated), respectively, based on the position of the user. In this case, if the distance difference between the left side and the right side is close to "0", the electronic device **910** may determine that the portable device **930** is in the center of the front side (e.g., the +z direction of FIG. **6**) of the electronic device **910**. Conversely, if the distance from the left side is relatively short compared to the distance from the right side, the electronic device **910** may determine that the portable device **930** is positioned on the left side relative to the center of the electronic device **910**.

(123) Likewise, the electronic device **910** may estimate the height of the portable device **930** using

the antenna **911** or **913** disposed at the top of the display panel and the antenna **915** or **917** disposed at the bottom of the display panel.

(124) Further, the electronic device **910** may estimate the position of the portable device **930** relative to the electronic device **910** in the recognition space based on the distance obtained through the above process, a horizontal angle obtained using the left-right difference, and a vertical angle obtained using the top-bottom difference. In this case, the estimated distance may have an error within, for example, about 5 cm, and the angle may have an error within, for example, about ± 5 degrees. The estimation errors may vary depending on, for example, the number of antennas or the system accuracy, and embodiments are not limited thereto.

(125) The electronic device **910** may calculate the position and/or the height of the portable device **930** by measuring the signal transmission times between the multiple antennas **911**, **913**, **915**, and **917** whose positions are known and the portable device **930**, which is a signal source, using the various methods described above.

(126) FIG. **10** is a diagram illustrating transmission and reception sequences between a plurality of antennas of an electronic device and portable devices according to one embodiment. Referring to FIG. **10**, according to an embodiment, a diagram **1000** illustrating a situation in which N antennas Antenna 1, Antenna 2, . . . , Antenna N (e.g., the plurality of antennas **310** of FIG. **3**, the antennas **417** of FIG. **4**, and/or the plurality of antennas **911**, **913**, **915**, and **917** of FIG. **9**) disposed in the electronic device **1001** (e.g., the electronic device **102** of FIG. **1**, the electronic device **300** of FIG. **3**, the electronic device **410** of FIG. **4**, the electronic device **510** of FIG. **5**, the electronic device **610** of FIG. **6**, the electronic device **710** of FIG. **7**, the electronic device **810** of FIG. **8**, the electronic device **910** of FIG. **9**, the electronic device **1220** of FIG. **12**, the electronic device **1320** of FIG. **13**, the electronic device **1420** of FIG. **14**, and/or the electronic device **1510** of FIG. **15**) each receive signals transmitted by N portable devices Watch 1, . . . , Watch N (e.g., the electronic device **101** of FIG. **1**, the portable device **200** of FIGS. **2A** and **2B**, the wearable device **430** of FIG. **4**, the portable device **720** of FIG. **7**, the portable device **820** of FIG. **8**, the portable device **930** of FIG. **9**, the portable device **1003** of FIG. **10**, the portable devices **1201**, **1203**, and **1205** of FIG. **12**, the portable devices **1301** and **1303** of FIG. **13**, and/or the portable devices **1401**, **1403**, and **1405** of FIG. **14**) is shown. The N portable devices may be, for example, watch-type portable devices. However, embodiments are not limited thereto.

(127) The distance estimation method performed by the electronic device **1001** using the TDoA of a signal may include at least one of a unidirectional distance estimation method or a bidirectional distance estimation method.

(128) For example, when the unidirectional distance estimation method is used, the electronic device **1001** may estimate the distance based on delay times from the portable device **1003**, which is a transmission signal source, to the antennas Antenna 1, Antenna 2, . . . , Antenna N of the electronic device **1001**, which are reception signal sources, in a passive situation in which only a second signal is received. The electronic device **1001** may estimate the distance by multiplying a delay time (e.g., a time difference) at which the second signal transmitted from the portable device **1003** is received by the speed, thereby calculating a first relative position, in other words, the distance between the portable device **1003** and an antenna having received the second signal.

(129) For example, when the bidirectional distance estimation method is used, the electronic device **1001** may estimate the distance based on a bidirectional signal that the second signal is transmitted by the portable device **1003** back to the transmission direction in response to the reception of the first signal, in an active situation in which the first signal is transmitted to the portable device **1003**. Since the bidirectional signal is used, the electronic device **1001** may estimate the distance by multiplying half the delay time by the speed. The electronic device **1001** may obtain a correlation between a time-delayed waveform of the second signal transmitted from the portable device **1003** and a non-time-delayed waveform of the second signal as a function of the time delay and then, calculate the distance between the portable device **1003** and the antenna having received the second

signal by estimating a time delay having the greatest correlation value as the TDoA.

(130) The portable device **1003** may transmit signals to the electronic device **1001** by dividing time and receive signals sequentially transmitted from the electronic device **1001**, thereby measuring the distances between the portable device **1003** and the antennas having received the signals and/or the directions of the antennas.

(131) The electronic device **1001** may operate based on, for example, the TDoA method. When the signals transmitted from the portable devices **1003** are received by the antennas (e.g., the antennas **911**, **913**, **915**, and **917** of FIG. 9) embedded in the front side (e.g., the +z direction of FIG. 6) of the display module (e.g., the display module **350** of FIG. 3) of the electronic device **1001**, a RTLS (e.g., the RTLS **416** of FIG. 4) of the electronic device **1001** may obtain device information (e.g., device types and/or device identification (ID) information) and T.sub.dx (e.g., T.sub.d1, T.sub.d2, T.sub.d3, and T.sub.d4) information of the portable devices **1003** from the signals received by the respective antennas **911**, **913**, **915**, and **917**. The electronic device **1001** may identify the portable devices **1003** based on the device information of the portable devices **1003**, and calculate relative positions between the front side (e.g., the +z direction of FIG. 6) of the display module (e.g., the display module **350** of FIG. 3) and the portable devices **1003** based on the T.sub.dx information. A time slot may be construed as a time used for each of the antennas **911**, **913**, **915**, and **917** of the electronic device **1001** to receive all signals transmitted by any one portable device. For example, the portable devices may sequentially transmit signals to the electronic device **1001** for each time slot. However, embodiments are not limited thereto.

(132) The number of antennas **911**, **913**, **915**, and **917** disposed in the electronic device **1001** may be increased, and the number of portable devices **1003** may also be increased. According to an embodiment, the minimum number of antennas disposed in the electronic device **1001** may be reduced. For example, two or three antennas may be disposed symmetrically on the left and the right.

(133) FIG. 11 is a flowchart illustrating a method of updating an exercise content by an electronic device according to one embodiment. In the following example embodiments, operations may be performed sequentially, but are not necessarily performed sequentially. For example, the operations may be performed in different orders, and/or at least two of the operations may be performed in parallel.

(134) Referring to FIG. 11, according to an embodiment, an electronic device (e.g., the first electronic device **102** of FIG. 1, the electronic device **300** of FIG. 3, the electronic device **410** of FIG. 4, the electronic device **510** of FIG. 5, the electronic device **610** of FIG. 6, the electronic device **710** of FIG. 7, the electronic device **810** of FIG. 8, the electronic device **910** of FIG. 9, the electronic device **1001** of FIG. 10, the electronic device **1220** of FIG. 12, the electronic device **1320** of FIG. 13, the electronic device **1420** of FIG. 14, and/or the electronic device **1510** of FIG. 15) may provide exercise content through operations **1110** to **1180**.

(135) In operation **1110**, the electronic device **1001** (e.g., the processor **330** of FIG. 3 or the processor **414** of FIG. 4) may scan to identify whether there is a portable device (e.g., the electronic device **101** of FIG. 1, the portable device **200** of FIGS. 2A and 2B, the wearable device **430** of FIG. 4, the portable device **720** of FIG. 7, the portable device **820** of FIG. 8, the portable device **930** of FIG. 9, the portable device **1003** of FIG. 10, the portable devices **1201**, **1203**, and **1205** of FIG. 12, the portable devices **1301** and **1303** of FIG. 13, and/or the portable devices **1401**, **1403**, and **1405** of FIG. 14) in the vicinity thereof, through a plurality of antennas (e.g., the plurality of antennas **310** of FIG. 3, the antennas **417** of FIG. 4, and/or the plurality of antennas **911**, **913**, **915**, and **917** of FIG. 9).

(136) When a portable device **1003** identified by the scanning in operation **1110** responds to a signal transmitted by the electronic device **1001** (e.g., the processor **330** of FIG. 3 or the processor **414** of FIG. 4) in operation **1120**, the electronic device **1001** (e.g., the processor **330** of FIG. 3 or the processor **414** of FIG. 4) may wait for the same signal of the portable device **1003** to be

received through the plurality of antennas **911**, **913**, **915**, and **917** in operation **1130**.

(137) In operation **1140**, the electronic device **1001** (e.g., the processor **330** of FIG. **3** or the processor **414** of FIG. **4**) may determine whether the portable device **1003** is positioned in a front side (e.g., the +z direction of FIG. **6**) of a display module (e.g., the display module **350** of FIG. **3**) of the electronic device **1001**. The electronic device **1001** (e.g., the processor **330** of FIG. **3** or the processor **414** of FIG. **4**) may determine whether the portable device **1003** is positioned in the front side (e.g., the +z direction of FIG. **6**) of the display module of the electronic device **1001** (e.g., the processor **330** of FIG. **3** or the processor **414** of FIG. **4**) by analyzing the angle and/or the distance at which the signal transmitted by the portable device **1003** is received. In this case, the electronic device **1001** (e.g., the processor **330** of FIG. **3** or the processor **414** of FIG. **4**) may determine whether the portable device **1003** is positioned in a recognition space (e.g., the recognition space **630** of FIG. **6**, the recognition space **740** of FIG. **7**, the recognition space **830** of FIG. **8**, the recognition space **850** of FIG. **8**, and/or the recognition space **1340** of FIG. **13**) in the front side (e.g., the +z direction of FIG. **6**) of the display module **350**.

(138) When it is determined in operation **1140** that the portable device **1003** is not positioned in the front side (e.g., the +z direction of FIG. **6**) of the electronic device **1001** (e.g., the processor **330** of FIG. **3** or the processor **414** of FIG. **4**), the electronic device **1001** (e.g., the processor **330** of FIG. **3** or the processor **414** of FIG. **4**) may provide (or reconstruct) exercise content by deleting a content object (e.g., a character, an avatar, an emoji, and/or an emoticon) corresponding to the portable device **1003** from exercise content displayed on the screen in operation **1170**, and then perform operation **1110**.

(139) Conversely, when it is determined in operation **1140** that the portable device **1003** is positioned in the front side (e.g., the +z direction of FIG. **6**) of the electronic device **1001**, the electronic device **1001** (e.g., the processor **330** of FIG. **3** or the processor **414** of FIG. **4**) may determine whether identification information of the portable device **1003** is pre-enrolled information or newly recognized information, in operation **1150**.

(140) When it is determined in operation **1150** that the identification information of the portable device **1003** is pre-enrolled information, the electronic device **1001** (e.g., the processor **330** of FIG. **3** or the processor **414** of FIG. **4**) may update the position of the content object corresponding to the portable device **1003** to the calculated position of the portable device **1003** in operation **1180** and then, perform operation **1110**.

(141) When it is determined in operation **1150** that the identification information of the portable device **1003** is not pre-enrolled information, the electronic device **1001** (e.g., the processor **330** of FIG. **3** or the processor **414** of FIG. **4**) may display a new content object on the screen by adding the position of the newly recognized portable device **1003** to the exercise content, in operation **1160**.

(142) FIG. **12** is a diagram illustrating an operation of an electronic device when a portable device newly enters a recognition space according to one embodiment. Referring to FIG. **12**, according to an embodiment, a diagram **1210** illustrating a situation in which two users, a user A wearing the portable device **1201** (e.g., the electronic device **101** of FIG. **1**, the portable device **200** of FIGS. **2A** and **2B**, the wearable device **430** of FIG. **4**, the portable device **720** of FIG. **7**, the portable device **820** of FIG. **8**, the portable device **930** of FIG. **9**, the portable device **1003** of FIG. **10**, the portable devices **1301** and **1303** of FIG. **13**, and/or the portable devices **1401**, **1403**, and **1405** of FIG. **14**) and a user B wearing the portable device **1203**, are positioned in a recognition space (e.g., the recognition space **630** of FIG. **6**, the recognition space **740** of FIG. **7**, the recognition space **830** of FIG. **8**, the recognition space **850** of FIG. **8**, and/or the recognition space **1340** of FIG. **13**) of the electronic device **1220** (e.g., the electronic device **102** of FIG. **1**, the electronic device **300** of FIG. **3**, the electronic device **410** of FIG. **4**, the electronic device **510** of FIG. **5**, the electronic device **610** of FIG. **6**, the electronic device **710** of FIG. **7**, the electronic device **810** of FIG. **8**, the electronic device **910** of FIG. **9**, the electronic device **1001** of FIG. **10**, the electronic device **1320**

of FIG. 13, the electronic device 1420 of FIG. 14, and/or the electronic device 1510 of FIG. 15), and a diagram 1230 illustrating a situation in which a user C wearing the portable device 1205 newly enters the same recognition space are shown.

(143) The electronic device 1220 may exchange signals (e.g., a first signal and/or a second signal) with the plurality of portable devices 1201, 1203, and 1205 positioned on the front side (e.g., the +z direction of FIG. 6) of the electronic device 1220 in real time through multiple antennas (e.g., the plurality of antennas 310 of FIG. 3, the antennas 417 of FIG. 4, and/or the plurality of antennas 911, 913, 915, and 917 of FIG. 9). In this case, signals transmitted by the portable devices 1201, 1203, and 1205 may be received by the antennas 911, 913, 915, and 917 embedded in the front side (e.g., the +z direction of FIG. 6) of a display module (e.g., the display module 350 of FIG. 3) of the electronic device 1220. A RTLS (e.g., the RTLS 416 of FIG. 4) of the electronic device 1220 may identify the portable devices 1201, 1203, and 1205 by receiving device information of each of the portable devices 1201, 1203, and 1205, and may calculate first relative positions between the front side (e.g., the +z direction of FIG. 6) of the display module 350 and the portable devices 1201, 1203, and 1205 based on Tag information received by each of the antennas 911, 913, 915, and 917.

(144) The electronic device 1220 may identify whether each of the portable devices 1201, 1203, and 1205 is positioned in the recognition space 1340 based on the first relative positions. The electronic device 1220 may also calculate a second relative position between the portable devices 1201, 1203, and 1205, and display a user content object (e.g., a character, an avatar, an emoji, and/or an emoticon) corresponding to each of the portable devices 1201, 1203, and 1205 at a corresponding position in exercise content displayed on the screen. In this case, the electronic device 1220 may detect the positions of all portable devices 1201, 1203, and 1205 detectable on the front side (e.g., the +z direction of FIG. 6), even without the initial settings for recognizing the portable devices 1201, 1203, and 1205.

(145) After the positions of the users are determined in the exercise content according to the relative positions of the portable devices 1201 and 1203 recognized in the front side (e.g., the +z direction of FIG. 6) of the electronic device 1220 as shown in the diagram 1210, a new user C wearing the portable device 1205 may be additionally recognized as shown in the diagram 1230. In this case, the electronic device 1220 may automatically adjust the positions of the user content objects disposed on the screen by calculating the relative position (e.g., the second relative position) between the portable devices 1201, 1203, and 1205 that the users A, B, and C are wearing, irrespective of the order in which the portable devices 1201, 1203, and 1205 that the users are wearing are recognized.

(146) When it is identified that the portable device 1205 that the user C is wearing is positioned in the 3D recognition space as shown in the diagram 1230, the electronic device 1220 may determine whether identification information of the portable device 1205 that the user C is wearing is pre-enrolled information. The electronic device 1220 may provide or reconstruct the exercise content with a character 1235 corresponding to the portable device 1205 according to whether the identification information of the portable device 1205 is pre-enrolled information.

(147) For example, when it is determined that the identification information of the portable device 1205 is pre-enrolled information, the electronic device 1220 may update the position of the character 1235 corresponding to the portable device 1205 displayed in the exercise content, based on the first relative position between the electronic device 1220 and the portable device 1205.

(148) Conversely, when it is determined that the identification information of the portable device 1205 is not pre-enrolled information, the electronic device 1220 may add a new character 1235 corresponding to the portable device 1205 that newly enters the recognition space 1340 to the exercise content. In this case, the new character 1235 may be displayed in the exercise content by reflecting the position of the portable device 1205 that newly enters the recognition space 1340.

(149) FIG. 13 is a diagram illustrating an operation of an electronic device when a portable device leaves a recognition space according to one embodiment. Referring to FIG. 13, according to an

embodiment, a diagram **1310** illustrating a situation in which two users, a user A wearing the portable device **1301** and a user B wearing the portable device **1303** (e.g., the electronic device **101** of FIG. 1, the portable device **200** of FIGS. 2A and 2B, the wearable device **430** of FIG. 4, the portable device **720** of FIG. 7, the portable device **820** of FIG. 8, the portable device **930** of FIG. 9, the portable device **1003** of FIG. 10, the portable devices **1201**, **1203**, and **1205** of FIG. 12, and/or the portable devices **1401**, **1403**, and **1405** of FIG. 14), are positioned in the recognition space **1340** (e.g., the recognition space **630** of FIG. 6, the recognition space **740** of FIG. 7, the recognition space **830** of FIG. 8, and/or the recognition space **850** of FIG. 8) of the electronic device **1320** (e.g., the electronic device **102** of FIG. 1, the electronic device **300** of FIG. 3, the electronic device **410** of FIG. 4, the electronic device **510** of FIG. 5, the electronic device **610** of FIG. 6, the electronic device **710** of FIG. 7, the electronic device **810** of FIG. 8, the electronic device **910** of FIG. 9, the electronic device **1001** of FIG. 10, the electronic device **1220** of FIG. 12, the electronic device **1420** of FIG. 14, and/or the electronic device **1510** of FIG. 15), and a diagram **1330** illustrating a situation in which the user B wearing the portable device **1303** leaves the recognition space **1340** are shown.

(150) While the users A and B are using exercise content provided by the electronic device **1320** as shown in the diagram **1310**, the user B may leave the recognition space **1340** (e.g., the recognition space **630** of FIG. 6, the recognition space **740** of FIG. 7, and/or the recognition space **830** of FIG. 8, and the recognition space **850** of FIG. 8) that is previously defined, as shown in the diagram **1330**. In this case, whether the user B leaves the previously defined recognition space **1340** may be estimated or determined by the following methods.

(151) For example, when the user B included in a field of view (FOV) of the antenna A **1350** of the electronic device **1320** and in a FOV of the antenna B **1352** of the electronic device **1320** in the recognition space **1340** leaves the recognition space **1340**, the portable device **1203** that the user B is wearing may not be detected in the FOV of the antenna B **1352**. Accordingly, the electronic device **1320** may estimate or determine that the user B leaves the recognition space **1340**.

Alternatively, when a time at which a signal transmitted by the portable device **1303** that the user B is wearing is received is beyond a threshold for the difference of (transmission time–reception time), the electronic device **1320** may estimate or determine that the user B leaves the recognition space **1340**.

(152) As described above, the electronic device **1320** may identify whether the portable devices **1301** and **1303** leave the recognition space **1340** or newly enter the recognition space **1340**, based on signals (e.g., second signals) transmitted by the portable devices **1301** and **1303**, while a display module (e.g., the display module **350** of FIG. 3) is displaying the exercise content.

(153) When it is estimated that the portable device **1303** that the user B is wearing is not positioned in the recognition space **1340**, that is, it is estimated that the portable device **1303** leaves the recognition space **1340**, a RTLS (e.g., the RTLS **416** of FIG. 4) of the electronic device **1320** receiving the signal of the portable device **1303** that the user B is wearing may reconstruct or provide the exercise content by deleting a content object (e.g., a character, an avatar, an emoji, and/or an emoticon) corresponding to the leaving portable device **1303** from the exercise content. The RTLS **416** of the electronic device **1320** may remove, from the screen, information about the user B including the content object corresponding to the user B in the exercise content. In this case, the information about the user B may include, for example, the exercise level of the user B, the heart rate of the user B, the consumed calories of the user B according to an exercise, and the body temperature of the user B. However, embodiments are not limited thereto.

(154) FIG. 14 is a diagram illustrating a method of reconstructing an exercise content in response to changes in the positions of portable devices positioned in a recognition space according to one embodiment. Referring to FIG. 14, according to an embodiment, a diagram **1410** illustrating a situation in which a user A wearing the portable device **1401** (e.g., the electronic device **101** of FIG. 1, the portable device **200** of FIGS. 2A and 2B, the wearable device **430** of FIG. 4, the

portable device **720** of FIG. 7, the portable device **820** of FIG. 8, the portable device **930** of FIG. 9, the portable device **1003** of FIG. 10, the portable devices **1201**, **1203**, and **1205** of FIG. 12, and/or the portable devices **1301** and **1303** of FIG. 13), a user B wearing the portable device **1403**, and a user C wearing the portable device **1405** are positioned in a recognition space (e.g., the recognition space **630** of FIG. 6, the recognition space **740** of FIG. 7, the recognition space **830** of FIG. 8, the recognition space **850** of FIG. 8, and/or the recognition space **1340** of FIG. 13) on a front side (e.g., the +z direction of FIG. 6) of the electronic device **1420** (e.g., the electronic device **102** of FIG. 1, the electronic device **300** of FIG. 3, the electronic device **410** of FIG. 4, the electronic device **510** of FIG. 5, the electronic device **610** of FIG. 6, the electronic device **710** of FIG. 7, the electronic device **810** of FIG. 8, the electronic device **910** of FIG. 9, the electronic device **1001** of FIG. 10, the electronic device **1220** of FIG. 12, the electronic device **1320** of FIG. 13, and/or the electronic device **1510** of FIG. 15), and diagrams **1430** and **1450** illustrating situations in which the positions of the users change are shown.

(155) For example, when a plurality of portable devices **1401**, **1403**, and **1405** are positioned in the recognition space, the electronic device **1420** may calculate second relative positions between the plurality of portable devices **1401**, **1403**, and **1405** based on first relative positions between the electronic device **1420** and the plurality of portable devices **1401**, **1403**, and **1405**.

(156) The electronic device **1420** may identify whether there are a plurality of portable devices **1401**, **1403**, and **1405**, based on second signals transmitted by the plurality of portable devices **1401**, **1403**, and **1405**. When it is identified that the plurality of portable devices **1401**, **1403**, and **1405** move to new positions, the electronic device **1420** may track the new positions of the plurality of portable devices **1401**, **1403**, and **1405**. The electronic device **1420** may reconstruct or provide exercise content by adjusting at least one of the positions, exercise information, or sizes of content objects (e.g., characters, avatars, emojis, and or emoticons) corresponding to the plurality of portable devices **1401**, **1403**, and **1405** based on the tracked positions.

(157) The electronic device **1420** may provide exercise content for an exercise that a plurality of users may participate in, such as dancing. In this case, the electronic device **1420** may construct or provide exercise content by reflecting a group choreography among the plurality of users and position change information of the users. The electronic device **1420** may track changes in the positions of the user A, the user B, and the user C who are provided with the exercise content, and display exercise information corresponding to each user on the screen by reflecting the tracked position changes of the users.

(158) For example, when the users arranged as shown in the diagram **1410** move to new positions as shown in the diagram **1430** or **1450**, the electronic device **1420** may detect the movements of the portable devices to the front, rear, left, and right based on signals transmitted by the portable device **1401** that the user A is wearing, the portable device **1403** that the user B is wearing, and the portable device **1405** that the user C is wearing. For example, when the user C positioned at the front and center of the electronic device **1420** in the diagram **1410** moves to the left as shown in the diagram **1430**, the electronic device **1420** may detect the movement of the user C based on the signal transmitted by the portable device **1405** that the user C is wearing. In this case, the electronic device **1420** may reconstruct or provide the exercise content such that the exercise information corresponding to the user C and/or the content object corresponding to the user C displayed on the screen is moved and displayed to the left side in proportion to the distance the user C moves, as shown in the diagram **1430**. In addition, the user A positioned behind the user C on the front side (e.g., the +z direction of FIG. 6) of the electronic device **1420** may move to the center position on the front side (e.g., the +z direction of FIG. 6) of the electronic device **1420**, as shown in the diagram **1450**. In this case, the electronic device **1420** may track the user A who moves to the center based on the signal transmitted by the portable device **1401** that the user A is wearing. The electronic device **1420** may display the content object corresponding to the user A and/or the exercise information of the user A at the center position on the screen on which the exercise content

is displayed, by reflecting the new position of the user A.

(159) When the exercise content provided by the electronic device **1420** is a dance content, the arrangement and/or positions of the users may change according to motions provided by the dance content, and motions of the users may change. For example, according to the exercise content provided by the electronic device **1420**, the user A may perform a sitting motion, and the user B and the user C may perform jumping motions. In this case, the electronic device **1420** may reconstruct or provide the exercise content by adjusting the poses, positions, and sizes of the characters corresponding to the users by reflecting the different motions of the users.

(160) As described above, the electronic device **1420** may adjust the characters, the exercise information, and the sizes of the characters displayed on the screen by reflecting the movements of the users, thereby allowing the users to three-dimensionally experience the movements in the recognition space. Further, the electronic device **1420** may reconstruct the exercise content to interact with the physical actions of the users based on the relative position between the users, thereby improving the immersion of the users.

(161) FIG. **15** is a diagram illustrating an example of displaying the positions of a plurality of users in exercise content when the plurality of users perform a group exercise wearing portable devices according to one embodiment. Referring to FIG. **15**, a diagram **1500** illustrating a situation in which a plurality of users perform a group exercise at fixed positions according to an instruction of an instructor is shown.

(162) The electronic device **1510** (e.g., the electronic device **102** of FIG. **1**, the electronic device **300** of FIG. **3**, the electronic device **410** of FIG. **4**, the electronic device **510** of FIG. **5**, the electronic device **610** of FIG. **6**, the electronic device **710** of FIG. **7**, the electronic device **810** of FIG. **8**, the electronic device **910** of FIG. **9**, the electronic device **1001** of FIG. **10**, the electronic device **1220** of FIG. **12**, the electronic device **1320** of FIG. **13**, and/or the electronic device **1420** of FIG. **14**) may display exercise information (e.g., the consumed calories, the exercise durations, the body temperatures, and/or the heart rates) corresponding to a plurality of users wearing portable devices (e.g., the electronic device **101** of FIG. **1**, the portable device **200** of FIGS. **2A** and **2B**, the wearable device **430** of FIG. **4**, the portable device **720** of FIG. **7**, the portable device **820** of FIG. **8**, the portable device **930** of FIG. **9**, the portable device **1003** of FIG. **10**, the portable devices **1201**, **1203**, and **1205** of FIG. **12**, and/or the portable devices **1301** and **1303** of FIG. **13**) on the screen.

(163) FIG. **16** is a flowchart illustrating an operating method of an electronic device according to one embodiment. In the following embodiments, operations may be performed sequentially, but are not necessarily performed sequentially. For example, the operations may be performed in different orders, and/or at least two of the operations may be performed in parallel.

(164) Referring to FIG. **16**, according to an embodiment, an electronic device (e.g., the electronic device **102** of FIG. **1**, the electronic device **300** of FIG. **3**, the electronic device **410** of FIG. **4**, the electronic device **510** of FIG. **5**, the electronic device **610** of FIG. **6**, the electronic device **710** of FIG. **7**, the electronic device **810** of FIG. **8**, the electronic device **910** of FIG. **9**, the electronic device **1001** of FIG. **10**, the electronic device **1220** of FIG. **12**, the electronic device **1320** of FIG. **13**, the electronic device **1420** of FIG. **14**, and/or the electronic device **1510** of FIG. **15**) may display exercise content through operations **1610** to **1650**.

(165) In operation **1610**, the electronic device (e.g., the processor **330** of FIG. **3** or the processor **414** of FIG. **4**) may scan to identify whether there is at least one portable device (e.g., the electronic device **101** of FIG. **1**, the portable device **200** of FIGS. **2A** and **2B**, the wearable device **430** of FIG. **4**, the portable device **720** of FIG. **7**, the portable device **820** of FIG. **8**, the portable device **930** of FIG. **9**, the portable device **1003** of FIG. **10**, the portable devices **1201**, **1203**, and **1205** of FIG. **12**, the portable devices **1301** and **1303** of FIG. **13**, and/or the portable devices **1401**, **1403**, and **1405** of FIG. **14**), using a plurality of antennas (e.g., the plurality of antennas **310** of FIG. **3**, the antennas **417** of FIG. **4**, and/or the plurality of antennas **911**, **913**, **915**, and **917** of FIG. **9**) for wireless

communication.

(166) In operation **1620**, the electronic device (e.g., the processor **330** of FIG. 3 or the processor **414** of FIG. 4) may define a three-dimensional recognition space (e.g., the recognition space **630** of FIG. 6, the recognition space **740** of FIG. 7, the recognition space **830** of FIG. 8, the recognition space **850** of FIG. 8, and/or the recognition space **1340** of FIG. 13) based on a first signal transmitted from the wearable device **430**, scanned in operation **1610**, for space setting. For example, in response to a space setting mode being started in the wearable device **430** for setting the recognition space **630**, the electronic device (e.g., the processor **330** of FIG. 3 or the processor **414** of FIG. 4) may provide a guide for a user of the wearable device **430**. In this case, the guide may include, for example, a voice and/or an image guiding the wearable device **430** to be positioned in a boundary area of the recognition space **630** in which the exercise content is utilized. However, embodiments are not limited thereto. The electronic device (e.g., the processor **330** of FIG. 3 or the processor **414** of FIG. 4) may receive the first signal transmitted from the wearable device **430** in the boundary area according to the guide. When each of the plurality of antennas (e.g., antennas **911**, **913**, **915**, and **917**) successfully receives the first signal, the electronic device (e.g., the processor **330** of FIG. 3 or the processor **414** of FIG. 4) may define the recognition space **630** using the first signal received by each of the plurality of antennas (e.g., antennas **911**, **913**, **915**, and **917**).

(167) In operation **1630**, the electronic device (e.g., the processor **330** of FIG. 3 or the processor **414** of FIG. 4) may calculate the position of the wearable device **430** in the recognition space **630**, defined in operation **1620**, based on a second signal transmitted from the wearable device **430**. The electronic device (e.g., the processor **330** of FIG. 3 or the processor **414** of FIG. 4) may identify whether the wearable device **430** includes a plurality of wearable devices **430**, based on the second signal. When it is identified that the plurality of wearable devices **430** move to new positions, the electronic device (e.g., the processor **330** of FIG. 3 or the processor **414** of FIG. 4) may track the new positions of the plurality of wearable devices **430**.

(168) In operation **1640**, the electronic device (e.g., the processor **330** of FIG. 3 or the processor **414** of FIG. 4) may generate exercise content based on the position(s) of the wearable device **430** identified in operation **1630**. The electronic device (e.g., the processor **330** of FIG. 3 or the processor **414** of FIG. 4) may reconstruct or provide the exercise content by adjusting at least one of the positions, exercise information, or sizes of content objects (e.g., characters, avatars, emojis, and or emoticons) corresponding to the plurality of wearable devices **430** based on the positions identified or tracked in operation **1630**.

(169) In operation **1650**, the electronic device (e.g., the processor **330** of FIG. 3 or the processor **414** of FIG. 4) may display the exercise content.

(170) According to an embodiment, an electronic device **102**, **300**, **410**, **510**, **610**, **710**, **810**, **910**, **1001**, **1220**, **1320**, **1420**, **1510** may include a plurality of antennas **310**, **417**, **911**, **913**, **915**, **917** for wireless communication, a processor **330**, **414** configured to scan to identify whether there is at least one portable device **101**, **200**, **430**, **720**, **820**, **930**, **1003**, **1201**, **1203**, **1205**, **1301**, **1303**, **1401**, **1403**, **1405** using the plurality of antennas **310**, **417**, **911**, **913**, **915**, **917**, define a three-dimensional recognition space **630**, **740**, **830**, **850**, **1340** based on a first signal transmitted from the portable device **101**, **200**, **430**, **720**, **820**, **930**, **1003**, **1201**, **1203**, **1205**, **1301**, **1303**, **1401**, **1403**, **1405** for space setting, calculate a position of the portable device **101**, **200**, **430**, **720**, **820**, **930**, **1003**, **1201**, **1203**, **1205**, **1301**, **1303**, **1401**, **1403**, **1405** in the recognition space **630**, **740**, **830**, **850**, **1340** based on a second signal transmitted from the portable device **101**, **200**, **430**, **720**, **820**, **930**, **1003**, **1201**, **1203**, **1205**, **1301**, **1303**, **1401**, **1403**, **1405**, and generate exercise content based on the position of the portable device **101**, **200**, **430**, **720**, **820**, **930**, **1003**, **1201**, **1203**, **1205**, **1301**, **1303**, **1401**, **1403**, **1405**, and a display module **350** configured to display the exercise content.

(171) According to an embodiment, the processor **330**, **414** may be configured to define the recognition space **630**, **740**, **830**, **850**, **1340** relative to a front side of the display module **350** based

on the first signal.

(172) According to an embodiment, the processor **330, 414** may be configured to calculate a first relative position including a distance and an angle between the electronic device **102, 300, 410, 510, 610, 710, 810, 910, 1001, 1220, 1320, 1420, 1510** and the portable device **101, 200, 430, 720, 820, 930, 1003, 1201, 1203, 1205, 1301, 1303, 1401, 1403, 1405** in the recognition space **630, 740, 830, 850, 1340** using a difference in times at which the plurality of antennas **310, 417, 911, 913, 915, 917** receive the second signal.

(173) According to an embodiment, the processor **330, 414** may be configured to provide a user of the portable device **101, 200, 430, 720, 820, 930, 1003, 1201, 1203, 1205, 1301, 1303, 1401, 1403, 1405** with a guide to guide the portable device **101, 200, 430, 720, 820, 930, 1003, 1201, 1203, 1205, 1301, 1303, 1401, 1403, 1405** to be positioned in a boundary area of the recognition space **630, 740, 830, 850, 1340** in which the exercise content is to be utilized, in response to a space setting mode being started in the portable device **101, 200, 430, 720, 820, 930, 1003, 1201, 1203, 1205, 1301, 1303, 1401, 1403, 1405** for setting the recognition space **630, 740, 830, 850, 1340**, and set the plurality of antennas **310, 417, 911, 913, 915, 917** to receive the first signal transmitted from the portable device **101, 200, 430, 720, 820, 930, 1003, 1201, 1203, 1205, 1301, 1303, 1401, 1403, 1405** according to the guide.

(174) According to an embodiment, the processor **330, 414** may be configured to provide a guide to guide the portable device **101, 200, 430, 720, 820, 930, 1003, 1201, 1203, 1205, 1301, 1303, 1401, 1403, 1405** to move to a boundary area next to the boundary area, when each of the plurality of antennas **310, 417, 911, 913, 915, 917** successfully receives the first signal transmitted from the portable device **101, 200, 430, 720, 820, 930, 1003, 1201, 1203, 1205, 1301, 1303, 1401, 1403, 1405** in the boundary area according to the guide.

(175) According to an embodiment, the processor **330, 414** may be configured to define the recognition space **630, 740, 830, 850, 1340** using the first signal received by each of the plurality of antennas **310, 417, 911, 913, 915, 917**, when each of the plurality of antennas **310, 417, 911, 913, 915, 917** successfully receives the first signal.

(176) According to an embodiment, one or more of the plurality of antennas **310, 417, 911, 913, 915, 917** may be disposed at each of two or more symmetrical positions among top, bottom, left, and right of the display module **350**, and the processor **330, 414** may be configured to calculate a first relative position between the electronic device **102, 300, 410, 510, 610, 710, 810, 910, 1001, 1220, 1320, 1420, 1510** and the portable device **101, 200, 430, 720, 820, 930, 1003, 1201, 1203, 1205, 1301, 1303, 1401, 1403, 1405** using a difference in times at which the plurality of antennas **310, 417, 911, 913, 915, 917** disposed at the symmetrical positions receive the second signal.

(177) According to an embodiment, the processor **330, 414** may be configured to identify whether the portable device **101, 200, 430, 720, 820, 930, 1003, 1201, 1203, 1205, 1301, 1303, 1401, 1403, 1405** is positioned in the recognition space **630, 740, 830, 850, 1340** based on the first relative position.

(178) According to an embodiment, the processor **330, 414** may be configured to, when it is identified that the portable device **101, 200, 430, 720, 820, 930, 1003, 1201, 1203, 1205, 1301, 1303, 1401, 1403, 1405** is not positioned in the recognition space **630, 740, 830, 850, 1340**, reconstruct the exercise content by deleting a content object corresponding to the portable device **101, 200, 430, 720, 820, 930, 1003, 1201, 1203, 1205, 1301, 1303, 1401, 1403, 1405** from the exercise content.

(179) According to an embodiment, the processor **330, 414** may be configured to, when it is identified that the portable device **101, 200, 430, 720, 820, 930, 1003, 1201, 1203, 1205, 1301, 1303, 1401, 1403, 1405** is positioned in the three-dimensional recognition space **630, 740, 830, 850, 1340**, determine whether identification information of the portable device **101, 200, 430, 720, 820, 930, 1003, 1201, 1203, 1205, 1301, 1303, 1401, 1403, 1405** is pre-enrolled information, and reconstruct the exercise content with a content object corresponding to the portable device **101,**

200, 430, 720, 820, 930, 1003, 1201, 1203, 1205, 1301, 1303, 1401, 1403, 1405 according to whether the identification information is pre-enrolled information.

(180) According to an embodiment, the processor **330, 414** may be configured to, when it is determined that the identification information of the portable device **101, 200, 430, 720, 820, 930, 1003, 1201, 1203, 1205, 1301, 1303, 1401, 1403, 1405** is pre-enrolled information, update a position of the content object corresponding to the portable device **101, 200, 430, 720, 820, 930, 1003, 1201, 1203, 1205, 1301, 1303, 1401, 1403, 1405** displayed in the exercise content, based on the first relative position.

(181) According to an embodiment, the processor **330, 414** may be configured to, when it is determined that the identification information of the portable device **101, 200, 430, 720, 820, 930, 1003, 1201, 1203, 1205, 1301, 1303, 1401, 1403, 1405** is not pre-enrolled information, add a content object corresponding to the position of the portable device **101, 200, 430, 720, 820, 930, 1003, 1201, 1203, 1205, 1301, 1303, 1401, 1403, 1405** to the exercise content.

(182) According to an embodiment, the processors **330** and **414** may be configured to, when the portable device **101, 200, 430, 720, 820, 930, 1003, 1201, 1203, 1205, 1301, 1303, 1401, 1403, 1405** is a plurality of portable devices **101, 200, 430, 720, 820, 930, 1003, 1201, 1203, 1205, 1301, 1303, 1401, 1403, 1405**, calculate second relative positions between the plurality of portable devices **101, 200, 430, 720, 820, 930, 1003, 1201, 1203, 1205, 1301, 1303, 1401, 1403, 1405** based on first relative positions between the electronic device **102, 300, 410, 510, 610, 710, 810, 910, 1001, 1220, 1320, 1420, 1510** and the plurality of portable devices **101, 200, 430, 720, 820, 930, 1003, 1201, 1203, 1205, 1301, 1303, 1401, 1403, 1405**.

(183) According to an embodiment, the processor **330, 414** may be configured to identify whether the portable device **101, 200, 430, 720, 820, 930, 1003, 1201, 1203, 1205, 1301, 1303, 1401, 1403, 1405** leaves the recognition space **630, 740, 830, 850, 1340** or newly enters the recognition space **630, 740, 830, 850, 1340** while the display module **350** is displaying the exercise content, based on the second signal.

(184) According to an embodiment, the processor **330, 414** may be configured to, when it is identified based on the second signal that the portable device **101, 200, 430, 720, 820, 930, 1003, 1201, 1203, 1205, 1301, 1303, 1401, 1403, 1405** leaves the recognition space **630, 740, 830, 850, 1340**, remove a content object corresponding to the leaving portable device **101, 200, 430, 720, 820, 930, 1003, 1201, 1203, 1205, 1301, 1303, 1401, 1403, 1405** from the exercise content, and when it is identified based on the second signal that the portable device **101, 200, 430, 720, 820, 930, 1003, 1201, 1203, 1205, 1301, 1303, 1401, 1403, 1405** newly enters the recognition space **630, 740, 830, 850, 1340**, add a content object corresponding to the newly entering portable device **101, 200, 430, 720, 820, 930, 1003, 1201, 1203, 1205, 1301, 1303, 1401, 1403, 1405** to the exercise content.

(185) According to an embodiment, the processor **330, 414** may be configured to identify whether the portable device **101, 200, 430, 720, 820, 930, 1003, 1201, 1203, 1205, 1301, 1303, 1401, 1403, 1405** is a plurality of portable devices **101, 200, 430, 720, 820, 930, 1003, 1201, 1203, 1205, 1301, 1303, 1401, 1403, 1405**, based on the second signal, when it is identified that the plurality of portable devices **101, 200, 430, 720, 820, 930, 1003, 1201, 1203, 1205, 1301, 1303, 1401, 1403, 1405** move to new positions, track the new positions of the plurality of portable devices **101, 200, 430, 720, 820, 930, 1003, 1201, 1203, 1205, 1301, 1303, 1401, 1403, 1405**, and reconstruct the exercise content by adjusting at least one of positions of content objects corresponding to the plurality of portable devices **101, 200, 430, 720, 820, 930, 1003, 1201, 1203, 1205, 1301, 1303, 1401, 1403, 1405**, exercise information of the content objects, or size of the content objects based on the tracked positions.

(186) According to an embodiment, the exercise content may include at least one of a content object corresponding to a user wearing the portable device **101, 200, 430, 720, 820, 930, 1003, 1201, 1203, 1205, 1301, 1303, 1401, 1403, 1405**, and exercise information of the user wearing the

portable device **101, 200, 430, 720, 820, 930, 1003, 1201, 1203, 1205, 1301, 1303, 1401, 1403, 1405.**

(187) According to an embodiment, an operating method of an electronic device **102, 300, 410, 510, 610, 710, 810, 910, 1001, 1220, 1320, 1420, 1510** may include operation **1610** of scanning to identify whether there is at least one portable device **101, 200, 430, 720, 820, 930, 1003, 1201, 1203, 1205, 1301, 1303, 1401, 1403, 1405** using a plurality of antennas **310, 417, 911, 913, 915, 917** for wireless communication, operation **1620** of defining a three-dimensional recognition space **630, 740, 830, 850, 1340** based on a first signal transmitted from the portable device **101, 200, 430, 720, 820, 930, 1003, 1201, 1203, 1205, 1301, 1303, 1401, 1403, 1405** for space setting, operation **1630** of calculating a position of the portable device **101, 200, 430, 720, 820, 930, 1003, 1201, 1203, 1205, 1301, 1303, 1401, 1403, 1405** in the recognition space **630, 740, 830, 850, 1340** based on a second signal transmitted from the portable device **101, 200, 430, 720, 820, 930, 1003, 1201, 1203, 1205, 1301, 1303, 1401, 1403, 1405**, operation **1640** of generating exercise content based on the position of the portable device **101, 200, 430, 720, 820, 930, 1003, 1201, 1203, 1205, 1301, 1303, 1401, 1403, 1405**, and operation **1650** of displaying the exercise content.

(188) The defining of the recognition space **630, 740, 830, 850, 1340** may include providing a user of the portable device **101, 200, 430, 720, 820, 930, 1003, 1201, 1203, 1205, 1301, 1303, 1401, 1403, 1405** with a guide to guide the portable device **101, 200, 430, 720, 820, 930, 1003, 1201, 1203, 1205, 1301, 1303, 1401, 1403, 1405** to be positioned in a boundary area of the recognition space **630, 740, 830, 850, 1340** in which the exercise content is to be utilized, in response to a space setting mode being started in the portable device **101, 200, 430, 720, 820, 930, 1003, 1201, 1203, 1205, 1301, 1303, 1401, 1403, 1405** for setting the recognition space **630, 740, 830, 850, 1340**, receiving the first signal transmitted from the portable device **101, 200, 430, 720, 820, 930, 1003, 1201, 1203, 1205, 1301, 1303, 1401, 1403, 1405** in the boundary area according to the guide, and defining the recognition space **630, 740, 830, 850, 1340** using the first signal received by each of the plurality of antennas **310, 417, 911, 913, 915, 917**, when each of the plurality of antennas **310, 417, 911, 913, 915, 917** successfully receives the first signal.

(189) The electronic device according to the embodiments disclosed herein may be one of various types of electronic devices. The electronic device may include, for example, a portable communication device (e.g., a smartphone), a computer device, a portable multimedia device, a portable medical device, a camera, a wearable device, a home appliance device, or the like. According to an embodiment of the disclosure, the electronic device is not limited to those electronic devices described above.

(190) It should be appreciated that embodiments of the present disclosure and the terms used therein are not intended to limit the technological features set forth herein to particular embodiments and include various changes, equivalents, or replacements for a corresponding embodiment. In connection with the description of the drawings, like reference numerals may be used for similar or related components. It is to be understood that a singular form of a noun corresponding to an item may include one or more of the things, unless the relevant context clearly indicates otherwise. As used herein, “A or B”, “at least one of A and B”, “at least one of A or B”, “A, B or C”, “at least one of A, B and C”, and “at least one of A, B, or C”, each of which may include any one of the items listed together in the corresponding one of the phrases, or all possible combinations thereof. Terms such as “first”, “second”, or “first” or “second” may simply be used to distinguish the component from other components in question, and do not limit the components in other aspects (e.g., importance or order). It is to be understood that if an element (e.g., a first element) is referred to, with or without the term “operatively” or “communicatively”, as “coupled with”, “coupled to”, “connected with”, or “connected to” another element (e.g., a second element), the element may be coupled with the other element directly (e.g., wiredly), wirelessly, or via a third element.

(191) As used in connection with various embodiments of the disclosure, the term “module” may

include a unit implemented in hardware, software, or firmware, or any combination thereof, and may interchangeably be used with other terms, for example, “logic”, “logic block”, “part”, or “circuitry”. A module may be a single integral component, or a minimum unit or part thereof, adapted to perform one or more functions. For example, according to an embodiment, the module may be implemented in a form of an application-specific integrated circuit (ASIC).

(192) Embodiments as set forth herein may be implemented as software (e.g., the program **140**) including one or more instructions that are stored in a storage medium (e.g., an internal memory **136** or an external memory **138**) that is readable by a machine (e.g., the electronic device **101** of FIG. **1**). For example, a processor (e.g., the processor **120**) of the machine (e.g., the electronic device **101**) may invoke at least one of the one or more instructions stored in the storage medium, and execute it. This allows the machine to be operated to perform at least one function according to the at least one instruction invoked. The one or more instructions may include code generated by a compiler or code executable by an interpreter. The machine-readable storage medium may be provided in the form of a non-transitory storage medium. Here, the term “non-transitory” storage medium may, for example, refer to a tangible device, and does not include a signal (e.g., an electromagnetic wave), but this term does not differentiate between where data is semi-permanently stored in the storage medium and where the data is temporarily stored in the storage medium.

(193) According to an embodiment, a method according to an embodiment of the disclosure may be included and provided in a computer program product. The computer program product may be traded as a product between a seller and a buyer. The computer program product may be distributed in the form of a machine-readable storage medium (e.g., a compact disc read-only memory (CD-ROM)), or be distributed (e.g., downloaded or uploaded) online via an application store (e.g., PlayStore™), or between two user devices (e.g., smartphones) directly. If distributed online, at least part of the computer program product may be temporarily generated or at least temporarily stored in the machine-readable storage medium, such as a memory of the manufacturer's server, a server of the application store, or a relay server.

(194) According to embodiments, each component (e.g., a module or a program) of the above-described components may include a single entity or multiple entities, and some of the multiple entities may be separately disposed in different components. According to various embodiments, one or more of the above-described components or operations may be omitted, or one or more other components or operations may be added. Alternatively or additionally, a plurality of components (e.g., modules or programs) may be integrated into a single component. In such a case, the integrated component may still perform one or more functions of each of the plurality of components in the same or similar manner as they are performed by a corresponding one of the plurality of components before the integration. According to various embodiments, operations performed by the module, the program, or another component may be carried out sequentially, in parallel, repeatedly, or heuristically, or one or more of the operations may be executed in a different order or omitted, or one or more other operations may be added.

(195) While the disclosure has been illustrated and described with reference to various example embodiments, it will be understood that the various example embodiments are intended to be illustrative, not limiting. It will be further understood by those skilled in the art that various changes in form and detail may be made without departing from the true spirit and full scope of the disclosure, including the appended claims and their equivalents. It will also be understood that any of the embodiment(s) described herein may be used in conjunction with any other embodiment(s) described herein.

Claims

1. An electronic device, comprising: a plurality of antennas for wireless communication; a processor configured to scan to identify whether there is at least one portable device using the plurality of antennas, define a three-dimensional recognition space based on a first signal for space setting transmitted from a portable device identified by the scan, calculate a position of the identified portable device in the recognition space based on a second signal transmitted from the portable device, and generate exercise content based on the position of the portable device; and a display module, including a display, configured to display the exercise content.
2. The electronic device of claim 1, wherein the processor is configured to define the recognition space relative to a front side of the display module based on the first signal.
3. The electronic device of claim 2, wherein the processor is configured to calculate a first relative position comprising a distance and an angle between the electronic device and the identified portable device in the recognition space using a difference in times at which the plurality of antennas receive the second signal.
4. The electronic device of claim 2, wherein the processor is configured to identify whether the identified portable device is positioned in the recognition space based on the first relative position.
5. The electronic device of claim 4, wherein the processor is configured to, when it is identified that the identified portable device is not positioned in the recognition space, reconstruct the exercise content by deleting a content object corresponding to the identified portable device from the exercise content.
6. The electronic device of claim 4, wherein the processor is configured to: when it is identified that the identified portable device is positioned in the three-dimensional recognition space, determine whether identification information of the identified portable device is pre-enrolled information, and reconstruct the exercise content with a content object corresponding to the identified portable device according to whether the identification information is pre-enrolled information.
7. The electronic device of claim 6, wherein the processor is configured to, when it is determined that the identification information of the identified portable device is pre-enrolled information, update a position of the content object corresponding to the identified portable device displayed in the exercise content, based on the first relative position.
8. The electronic device of claim 6, wherein the processor is configured to, when it is determined that the identification information of the identified portable device is not pre-enrolled information, add a content object corresponding to the position of the identified portable device to the exercise content.
9. The electronic device of claim 2, wherein the processor is configured to, when the identified portable device includes a plurality of portable devices, calculate second relative positions between the plurality of portable devices based on first relative positions between the electronic device and the plurality of portable devices.
10. The electronic device of claim 2, wherein the processor is configured to identify whether the identified portable device leaves the recognition space or newly enters the recognition space while the display module is displaying the exercise content, based on the second signal.
11. The electronic device of claim 10, wherein the processor is configured to: when it is identified based on the second signal that the identified portable device leaves the recognition space, remove a content object corresponding to the leaving portable device from the exercise content, and when it is identified based on the second signal that the identified portable device newly enters the recognition space, add a content object corresponding to the newly entering portable device to the exercise content.
12. The electronic device of claim 2, wherein the processor is configured to: identify whether the identified portable device includes a plurality of portable devices, based on the second signal, when it is identified that the plurality of portable devices move to new positions, track the new positions

of the plurality of portable devices, and reconstruct the exercise content by adjusting at least one of positions of content objects corresponding to the plurality of portable devices, exercise information of the content objects, or size of the content objects based on the tracked positions.

13. The electronic device of claim 1, wherein the processor is configured to: provide a user of the identified portable device with a guide to guide the identified portable device to be positioned in a boundary area of the recognition space in which the exercise content is to be utilized, in response to a space setting mode for setting the recognition space being started in the identified portable device, and set the plurality of antennas to receive the first signal transmitted from the identified portable device according to the guide.

14. The electronic device of claim 13, wherein the processor is configured to provide a guide to guide the identified portable device to move to another boundary area next to the boundary area, when each of the plurality of antennas successfully receives the first signal transmitted from the identified portable device in the boundary area according to the guide.

15. The electronic device of claim 14, wherein the processor is configured to define the recognition space using the first signal received by each of the plurality of antennas, when each of the plurality of antennas successfully receives the first signal.

16. The electronic device of claim 1, wherein one or more of the plurality of antennas are disposed at each of two or more symmetrical positions among top, bottom, left, and right of the display module, and the processor is configured to calculate a first relative position between the electronic device and the identified portable device using a difference in times at which the plurality of antennas disposed at the symmetrical positions receive the second signal.

17. The electronic device of claim 1, wherein the exercise content comprises at least one of: a content object corresponding to a user wearing the identified portable device; and exercise information of the user wearing the identified portable device.

18. An operating method of an electronic device, the operating method comprising: scanning to identify whether there is at least one portable device using a plurality of antennas for wireless communication; defining a three-dimensional recognition space based on a first signal for space setting transmitted from a portable device identified by the scan; calculating a position of the identified portable device in the recognition space based on a second signal transmitted from the identified portable device; generating exercise content based on the position of the identified portable device; and displaying the exercise content.

19. The operating method of claim 18, wherein the defining of the recognition space comprises: providing a user of the identified portable device with a guide to guide the identified portable device to be positioned in a boundary area of the recognition space in which the exercise content is to be utilized, in response to a space setting mode for setting the recognition space being started in the portable device; receiving the first signal transmitted from the identified portable device in the boundary area according to the guide; and defining the recognition space using the first signal received by each of the plurality of antennas, when each of the plurality of antennas successfully receives the first signal.

20. The operating method of claim 18, wherein the generating of the exercise content comprises: calculating a first relative position comprising a distance and an angle between the electronic device and the identified portable device using a difference in times at which the plurality of antennas receive the second signal; identifying whether the identified portable device is positioned in the recognition space based on the first relative position; reconstructing the exercise content by deleting a content object corresponding to the identified portable device from the exercise content, when it is identified that the identified portable device is not positioned in the recognition space; and reconstructing the exercise content with a content object corresponding to the identified portable device according to whether identification information of the identified portable device is pre-enrolled information, when it is identified that the identified portable device is positioned in the three-dimensional recognition space.

