

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12409809
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Pham; Richard et al.

Remote control of vehicle features based on tactile gestures on electronic device

Abstract

An electronic device and a method for remote control of vehicle features are provided. The electronic device receives a first user input indicative of a selection of a first vehicle from a set of vehicles associated with a user. The electronic device further receives, via a haptic device associated with the electronic device, a second user input including a tactile gesture. The second user input is indicative of an instruction to remotely control a first set of features on the selected first vehicle. The tactile gesture includes a first swipe input along a first direction associated with the haptic device and further includes a second swipe input along a second direction perpendicular to the first direction. The electronic device further controls the first set of features on the selected first vehicle based on the received second user input.

Inventors:	Pham; Richard (Lakewood, CA), Kwon; Do Hyuk (Irvine, CA)
Applicant:	Honda Motor Co., Ltd. (Tokyo, JP)
Family ID:	87762153
Assignee:	Honda Motor Co., Ltd. (Tokyo, JP)
Appl. No.:	17/681604
Filed:	February 25, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230271589 A1	Aug. 31, 2023

Publication Classification

Int. Cl.: B60R25/20 (20130101); B60H1/00 (20060101); E05F15/73 (20150101); G06F3/01 (20060101); G06F3/04817 (20220101); G06F3/0482 (20130101); G06F3/0484

U.S. Cl.:

CPC **B60R25/2045** (20130101); **B60H1/00657** (20130101); **B60R25/209** (20130101); **E05F15/73** (20150115); **G06F3/016** (20130101); **G06F3/017** (20130101); **G06F3/04817** (20130101); **G06F3/0482** (20130101); **G06F3/0484** (20130101); **G06F3/14** (20130101); B60R2325/205 (20130101); E05Y2400/45 (20130101); E05Y2400/85 (20130101); E05Y2400/8515 (20240501); E05Y2900/531 (20130101); E05Y2900/55 (20130101)

Field of Classification Search

CPC: B60R (25/2045); B60R (25/209); B60R (2325/205); E05F (15/73); E05Y (2400/45); E05Y (2400/85); E05Y (2900/531); E05Y (2900/55); G06F (3/016); G06F (3/017); G06F (3/04817); G06F (3/0482); G06F (3/0484); G06F (3/14)

References Cited**U.S. PATENT DOCUMENTS**

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
10166948	12/2018	Kang et al.	N/A	N/A
10564638	12/2019	Lockwood	N/A	G05D 1/0027
10747861	12/2019	Kim et al.	N/A	N/A
10759388	12/2019	Nelson et al.	N/A	N/A
11029840	12/2020	Tamane et al.	N/A	N/A
2011/0282537	12/2010	Yamasaki	701/31.4	G06F 3/0346
2013/0211623	12/2012	Thompson	701/1	H04L 67/12
2014/0005859	12/2013	Baskin	701/2	G07C 9/00309
2014/0095031	12/2013	Boblett	701/49	B60G 17/015
2015/0081169	12/2014	Pisz	701/1	G06F 21/31
2015/0248214	12/2014	Gilger	715/719	G06T 11/206
2017/0308080	12/2016	Brooks	N/A	A61B 5/0077
2017/0320501	12/2016	Li	N/A	G06F 3/04883
2019/0322176	12/2018	Tanaka	N/A	B60K 35/80
2019/0351872	12/2018	Phillips et al.	N/A	N/A
2020/0086829	12/2019	Wall et al.	N/A	N/A
2020/0086830	12/2019	Ichinose	N/A	B60R 25/246
2023/0054373	12/2022	Brooks	N/A	G06Q 10/06311

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
106274807	12/2016	CN	N/A
105607467	12/2017	CN	N/A
107813787	12/2017	CN	N/A
111067202	12/2019	CN	N/A

Primary Examiner: Antonucci; Anne Marie

Assistant Examiner: Del Valle; Luis G

Background/Summary

BACKGROUND

(1) Advancements in the fields of electronics and information technology have led to development of connected vehicles that may communicate with electronic devices that may be located outside the vehicle. For example, an electronic device of a user may be wirelessly connected to the vehicle of the user through a wireless network. Through the electronic device, one or more features of the vehicle may be remotely controlled by the user. Typically, users may operate the electronic device to instruct the vehicles associated with the user to remotely control one or more features of the vehicles. However, some features of the vehicle may be critical to an operation of the vehicle and may need to be controlled carefully. In certain situations, one or more critical features of the vehicle may be accidentally activated or deactivated, via the electronic device, by the user. For example, the electronic device may accidentally control the vehicle to turn on an engine of the vehicle based on an input received from the user. Such erroneous control of the engine of the vehicle may be undesirable for the user as it may lead to pollution, fuel wastage, and also fines in certain cases.

(2) Further limitations and disadvantages of conventional and traditional approaches will become apparent to one of skill in the art, through comparison of described systems with some aspects of the present disclosure, as set forth in the remainder of the present application and with reference to the drawings.

SUMMARY

(3) According to an embodiment of the disclosure, an electronic device is provided. The electronic device may comprise a circuitry. The circuitry may be configured to receive a first user input indicative of a selection of a first vehicle from a set of vehicles associated with a user. The circuitry may be further configured to receive, via a haptic device associated with the electronic device, a second user input including a tactile gesture. For example, the second user input may be indicative of an instruction to remotely control a first set of features on the selected first vehicle. The tactile gesture may include a first swipe input along a first direction associated with the haptic device and may include a second swipe input along a second direction perpendicular to the first direction. The circuitry may be further configured to control the first set of features on the selected first vehicle based on the received second user input.

(4) According to another embodiment of the disclosure, a method in an electronic device is provided. The method may include receiving a first user input indicative of a selection of a first vehicle from a set of vehicles associated with a user. The method may further include receiving, via a haptic device associated with the electronic device, a second user input including a tactile gesture. For example, the second user input may be indicative of an instruction to remotely control a first set of features on the selected first vehicle. The tactile gesture may include a first swipe input along a first direction associated with the haptic device and may include a second swipe input along a second direction perpendicular to the first direction. The method may further include controlling the first set of features on the selected first vehicle based on the received second user input.

(5) According to another embodiment of the disclosure, an electronic device is provided. The electronic device may comprise circuitry. The circuitry may be configured to receive a first user input indicative of a selection of a first vehicle from a set of vehicles associated with a user. The circuitry may be further configured to control a display screen associated with the electronic device to display a first user interface (UI) indicating first information about a first set of features of the selected first vehicle. The circuitry may be further configured to receive a second user input, via the

first UI, to remotely control the first set of features of the selected first vehicle. The circuitry may be further configured to receive a third user input to display second information about the first set of features controlled on a second vehicle of the set of vehicles, wherein the second vehicle is different from the first vehicle. The circuitry may be further configured to control, based on the received third user input, the display screen to display, via a second user interface (UI) different from the first UI, the second information and at least one of an icon or a highlighted portion which notify the user about the first information indicated on the first UI or about the controlled first set of features of the first vehicle.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a block diagram that illustrates an exemplary network environment to remotely control features of a vehicle using an electronic device, in accordance with an embodiment of the disclosure.
- (2) FIG. 2 is a block diagram that illustrates an exemplary electronic device of FIG. 1 to control vehicles, in accordance with an embodiment of the disclosure.
- (3) FIG. 3 is a block diagram that illustrates an exemplary first vehicle of FIG. 1, in accordance with an embodiment of the disclosure.
- (4) FIGS. 4A and 4B is a diagram that collectively illustrate an execution scenario to control a first vehicle by use of the electronic device of FIG. 1, in accordance with an embodiment of the disclosure.
- (5) FIG. 5 is a diagram that illustrates an exemplary scenario of a user interface of the electronic device of FIG. 1 to stop a started engine of a first vehicle, in accordance with an embodiment of the disclosure.
- (6) FIG. 6 is a diagram that illustrates an exemplary scenario of a user interface of the electronic device of FIG. 1 to start a stopped engine of a first vehicle, in accordance with an embodiment of the disclosure.
- (7) FIG. 7 is a diagram that illustrates an exemplary scenario of a user interface of the electronic device of FIG. 1 to start a stopped heating ventilation and air-conditioning (HVAC) system of a first vehicle, in accordance with an embodiment of the disclosure.
- (8) FIG. 8 is a diagram that illustrates an execution scenario to remotely control a second set of features on a first vehicle, in accordance with an embodiment of the disclosure.
- (9) FIG. 9 is a diagram that illustrates an exemplary scenario of a user interface of the electronic device of FIG. 1 to provide health status information and vehicle identification information, in accordance with an embodiment of the disclosure.
- (10) FIG. 10A is a diagram that illustrates an exemplary scenario of a first user interface of the electronic device of FIG. 1 to control features of a selected first vehicle, in accordance with an embodiment of the disclosure.
- (11) FIG. 10B is a diagram that illustrates an exemplary scenario of a second user interface of the electronic device of FIG. 1 to control features of a second vehicle, in accordance with an embodiment of the disclosure.
- (12) FIG. 11 is a flowchart that illustrates exemplary operations to control features of a vehicle, in accordance with an embodiment of the disclosure.
- (13) The foregoing summary, as well as the following detailed description of the present disclosure, is better understood when read in conjunction with the appended drawings. For the purpose of illustrating the present disclosure, exemplary constructions of the preferred embodiment are shown in the drawings. However, the present disclosure is not limited to the specific methods and structures disclosed herein. The description of a method step or a structure referenced by a numeral

in a drawing is applicable to the description of that method step or structure shown by that same numeral in any subsequent drawing herein.

DETAILED DESCRIPTION

(14) The following described implementations may be found in an electronic device and a method for remote control of vehicle features based on tactile gestures on the electronic device. Exemplary aspects of the disclosure provide an electronic device that may comprise circuitry. The circuitry may be configured to receive a first user input indicative of a selection of a first vehicle from a set of vehicles associated with a user. The circuitry may be further configured to receive, via a haptic device associated with the electronic device, a second user input including a tactile gesture. For example, the second user input may be indicative of an instruction to remotely control a first set of features on the selected first vehicle. The first set of features may pertain to one or more critical features (of the selected first vehicle) such as, but are not limited to, an engine control feature, to activate or deactivate the engine of the selected first vehicle remote. The tactile gesture may include a first swipe input along a first direction associated with the haptic device and may include a second swipe input along a second direction, for example, perpendicular to the first direction. For example, a combination of the first swipe and the second swipe of the tactile gesture may correspond to a ‘L-shaped’ gesture’. The circuitry may be further configured to control the first set of features on the selected first vehicle based on the received second user input.

(15) Typically, some critical features of a vehicle may be remotely controlled by use of a vehicle-related device of the user. Examples of such critical features may include, but are not limited to, an engine control feature to activate or deactivate an engine of the vehicle, a door control feature to lock or unlock a door of the vehicle, a window control feature to open or shut a window of the vehicle, and a heating ventilation and air-conditioning (HVAC) control feature to start or stop an HVAC of the vehicle. The critical features may be crucial for the safe operation of the vehicle. Conventional user interfaces of the vehicle-related device for control of such critical features may be difficult to use, as the conventional user interfaces may not be intuitive to a non-technical user. Also, through the conventional user interfaces, users may be prone to accidentally or unintentionally activate or deactivate the critical features of the vehicle.

(16) On the other hand, the electronic device of the present disclosure may receive the second user input (including the tactile gesture) via the haptic device that may be associated with the electronic device. The second user input may enable intuitive remote control of critical features (e.g., the first set of features) of the selected first vehicle. A tactile gesture received through the haptic device may be more user friendly and may correspond to an intuitive mode to capture an input from a user than traditional user interface elements, as the tactile gesture may involve bodily kinesthetic skills that may be known to even non-technical users. Further, the tactile gesture may require the user to provide a predetermined pattern (e.g., an L-shaped pattern) of swipe inputs (as the tactile gesture) through the haptic device to control the critical features of the first vehicle. The use of such predetermined pattern of swipe inputs to control the critical features of the selected first vehicle may prevent accidental or inadvertent activation or deactivation of any critical feature of the selected first vehicle, thereby leading to an enhancement of a user experience of the user to remotely control vehicles.

(17) Reference will now be made in detail to specific aspects or features, examples of which are illustrated in the accompanying drawings. Wherever possible, corresponding or similar reference numbers will be used throughout the drawings to refer to the same or corresponding parts.

(18) FIG. 1 is a block diagram that illustrates an exemplary network environment to remotely control features of a vehicle using an electronic device, in accordance with an embodiment of the disclosure. With reference to FIG. 1, there is shown a network environment diagram **100**. The network environment diagram **100** may include an electronic device **102**, a set of vehicles **104**, a haptic device **106**, a server **108**, and a database **110**. For example, the set of vehicles **104** may include a first vehicle **104A**, a second vehicle **104B**, . . . and an Nth vehicle **104N**. The number of

vehicles shown in FIG. 1 is presented merely as an example. The set of vehicles **104** may include only two vehicles or more vehicles, without deviation from the scope of the disclosure. For the sake of brevity, only three vehicles have been shown in FIG. 1. However, in some embodiments, there may be more than three vehicles, without limiting the scope of the disclosure.

(19) The electronic device **102**, the set of vehicles **104**, and the server **108** may be communicatively coupled to each other via a communication network **114**. Further, the haptic device **106** may be external to the electronic device **102** and may be communicatively coupled to the electronic device **102**. In certain scenarios, the haptic device **106** may be an in-built component of the electronic device **102**. In FIG. 1, there is further shown a user **112** associated with the electronic device **102**. The user **112** may perform a tactile gesture, via the haptic device **106**, in a first direction **116A** and in a second direction **116B** that is different from the first direction **116A**. In an embodiment, the second direction **116B** may be, for example, perpendicular to the first direction **116A**.

(20) The electronic device **102** may include suitable logic, circuitry, interfaces, and/or code that may be configured to receive a first user input to select a first vehicle (e.g., the first vehicle **104A**) from the set of vehicles **104**. The electronic device **102** may be further configured to receive a second user input to remotely control a first set of features on the selected first vehicle **104A**. In an embodiment, the electronic device **102** may receive the second user input, through the haptic device **106**. Based on the received first user input and the second user input, the electronic device **102** may be configured to remotely control the first set of features on the selected first vehicle **104A**. Examples of the electronic device **102** may include, but are not limited to, a computing device, a smartphone, a cellular phone, a mobile phone, a mainframe machine, a server, a computer work-station, a consumer electronic (CE) device, a vehicle remote controller device, a user wearable device, and/or any computing device that may be capable to remotely control one or more vehicles and may be associated with a haptic device.

(21) Each of the set of vehicles **104** may include one or more vehicles that may be owned or used by the user **112**. The term “vehicle” may refer to any moving vehicle that is capable of carrying one or more human occupants powered by any form of energy and may include cars, trucks, vans, minivans, SUVs, motorcycles, scooters, campers, boats, personal watercraft, and aircraft. The vehicle may be a non-autonomous vehicle, a semi-autonomous vehicle, or a fully autonomous vehicle, for example, as defined by National Highway Traffic Safety Administration (NHTSA). Examples of the vehicle may include, but are not limited to, a two-wheeler vehicle, a three-wheeler vehicle, a four-wheeler vehicle, a hybrid vehicle, or a vehicle with autonomous drive capability that uses one or more distinct renewable or non-renewable power sources. A vehicle that uses renewable or non-renewable power sources may include a fossil fuel-based vehicle, an electric propulsion-based vehicle, a hydrogen fuel-based vehicle, a solar-powered vehicle, and/or a vehicle powered by other forms of alternative energy sources. The vehicle may be a system through which the rider (e.g., the user **112**) may travel from a start point to a destination point. Examples of the two-wheeler vehicle may include, but are not limited to, an electric two-wheeler, an internal combustion engine (ICE)-based two-wheeler, or a hybrid two-wheeler. Similarly, examples of the four-wheeler vehicle may include, but are not limited to, an electric car, an internal combustion engine (ICE)-based car, a fuel-cell based car, a solar powered-car, or a hybrid car. The present disclosure may be also applicable to other types of two-wheelers (e.g., a scooter) or four-wheelers. The description of other types of the vehicles has been omitted from the disclosure for the sake of brevity. In an embodiment, the user **112** may own more than one vehicle. Each of the set of vehicles **104** may be registered to the user **112** based on vehicle identification information associated with each vehicle. For example, the vehicle identification information of a vehicle may be transmitted from the vehicle to the electronic device **102** on the registration of the vehicle to the user **112**. The electronic device **102** may store the received vehicle identification information associated with the vehicle in a memory (shown in FIG. 2) of the electronic device **102**.

(22) The haptic device **106** may include suitable logic, circuitry, interfaces, and/or code that may be

configured to receive a gesture input (e.g., a swipe input) from the user **112**. The haptic device **106** may be further configured to provide a haptic feedback to the user **112** on an anatomical portion (e.g., a finger) of a body of the user **112**, which may be in contact with the haptic device **106**. For example, the haptic feedback may be a vibratory haptic feedback on the anatomical portion. In certain cases, the haptic feedback may be provided based on a set of bio-signals associated with the anatomical portion of the body of the user **112**. In an embodiment, the haptic device **106** may be configured to be worn by the user **112** and may be in contact with the anatomical portion (e.g., a finger) of the body of the user **112**. In an embodiment, the wearable haptic device may include sensors, such as tactile sensors that may allow measurement of force of the human touch of the user **112** on a region of the wearable haptic device. Examples of the haptic device **106** may include, but are not limited to, a wearable garment with haptic actuators, a wearable device with haptic actuators, any device in a form of a wearable belt or medical tape/cloth with haptic actuators, a haptic touch screen, a haptic touchpad, a haptic display, or any display device that may be configured to receive a gesture input and provide a haptic feedback to a user. Examples of the wearable haptic device may include, but are not limited to, a haptic glove, a wired glove with haptic actuators, a gaming glove with haptic actuators, a wearable fingertip haptic device (such as a haptic thimble or a touch thimble), a graspable haptic device (which may generate kinesthetic sensations, such as a sensation of movement, position and force in skin, muscles, tendons, and joints of a wearer), or a wearable device (which generates tactile sensations, such as a pressure, friction, or temperature in the skin of a wearer), joysticks with haptic actuators, mouse, finger pad, robotic handle, gripper, and a humanoid robotic hand with haptic actuators. In an embodiment, the haptic device **106** may be implemented as a separate device that may be communicatively coupled to the electronic device **102**, either directly (as shown in FIG. **1**), or via the communication network **114**. In an alternate embodiment, the haptic device **106** may be an in-built component of the electronic device **102** and may be integrated within the electronic device **102**.

(23) The server **108** may include suitable logic, circuitry, and interfaces, and/or code that may be configured to select the first vehicle **104A** from the set of vehicles **104** based on the first user input received from the user **112**. For example, the server **108** may receive the first user input, via the electronic device **102** and select the first vehicle **104A** based on the received first user input. The server **108** may be further configured to remotely control the first set of features on the selected first vehicle **104A** based on the second user input. For example, the server **108** may receive a request to control the first set of features from the electronic device **102**, based on the reception of the second user input, via the electronic device **102**. Based on the received request, the server **108** may transmit instructions to control the first set of features to the selected first vehicle **104A**. In an embodiment, the server **108** may store information about controlled features and timestamp of the control of the set of vehicles **104**. In an embodiment, the server **108** may store information about the first set of features of the set of vehicles **104** and store real-time health status information of the set of vehicles **104**. The server **108** may be implemented as a cloud server and may execute operations through web applications, cloud applications, HTTP requests, repository operations, file transfer, and the like. Other example implementations of the server **108** may include, but are not limited to, a database server, a file server, a web server, a media server, an application server, a mainframe server, or a cloud computing server. In at least one embodiment, the server **108** may be implemented as a plurality of distributed cloud-based resources by use of several technologies that are well known to those ordinarily skilled in the art. A person with ordinary skill in the art will understand that the scope of the disclosure may not be limited to the implementation of the server **108** and the electronic device **102** as two separate entities. In certain embodiments, the functionalities of the server **108** can be incorporated in its entirety or at least partially in the electronic device **102**, without a departure from the scope of the disclosure.

(24) The database **110** may include suitable logic, interfaces, and/or code that may be configured to store information related to the set of vehicles **104** and instructions to control the set of vehicles

104. The database **110** may be derived from data off a relational or non-relational database, or a set of comma-separated values (csv) files in conventional or big-data storage. The database **110** may be stored or cached on a device, such as a server (e.g., the server **108**) or the electronic device **102**. The device storing the database **110** may be configured to receive a query for vehicle identification information or instructions associated with a set of features (e.g., the first set of features) of the set of vehicles **104** from the server **108** and/or the electronic device **102**. In response, the device of the database **110** may be configured to retrieve and provide the queried vehicle identification information or instructions associated with the set of features of set of vehicles **104** to the server **108** and/or the electronic device **102** based on the received query. In some embodiments, the database **110** may be hosted on a plurality of servers stored at same or different locations. The operations of the database **110** may be executed using hardware including a processor, a microprocessor (e.g., to perform or control performance of one or more operations), a field-programmable gate array (FPGA), or an application-specific integrated circuit (ASIC). In some other instances, the database **110** may be implemented using software.

(25) The communication network **114** may include a communication medium through which the electronic device **102**, the set of vehicles **104**, the haptic device **106**, and the server **108** may communicate with each other. The communication network **114** may be one of a wired connection or a wireless connection. Examples of the communication network **114** may include, but are not limited to, the Internet, a cloud network, Cellular or Wireless Mobile Network (such as Long-Term Evolution and 5G New Radio), a Wireless Fidelity (Wi-Fi) network, a Personal Area Network (PAN), a Local Area Network (LAN), or a Metropolitan Area Network (MAN). Various devices in the network environment **100** may be configured to connect to the communication network **114** in accordance with various wired and wireless communication protocols. Examples of such wired and wireless communication protocols may include, but are not limited to, at least one of a Transmission Control Protocol and Internet Protocol (TCP/IP), User Datagram Protocol (UDP), Hypertext Transfer Protocol (HTTP), File Transfer Protocol (FTP), Zig Bee, EDGE, IEEE 802.11, light fidelity (Li-Fi), 802.16, IEEE 802.11s, IEEE 802.11g, multi-hop communication, wireless access point (AP), device to device communication, cellular communication protocols, and Bluetooth (BT) communication protocols.

(26) In operation, the electronic device **102** may be configured to receive a first user input indicative of a selection of a first vehicle (e.g., the first vehicle **104A**) from the set of vehicles **104** associated with the user **112**. In an embodiment, the set of vehicles **104** may be registered with the electronic device **102** and/or the server **108**. For example, a vehicle may be registered at a time of purchase of the vehicle, at a time prior to a use of the vehicle, or at a time prior to the reception of the first user input associated with the vehicle. In an embodiment, each of the set of vehicles **104** may be registered to the user **112** based on vehicle identification information associated with each vehicle. As an example, the vehicle identification information of the vehicle may be transmitted from the vehicle to the electronic device **102** on the registration of the vehicle for the user **112**. The electronic device **102** may store the received vehicle identification information associated with the vehicle in a memory (shown in FIG. 2) of the electronic device **102**. The first user input may indicate a selection of the first vehicle **104A** by the user **112**. In another embodiment, electronic device **102** may select the first vehicle **104A** without the first user input. For example, in such case, the first vehicle **104A** may correspond to a default or primary vehicle of the user **112**. Alternatively, the first vehicle **104A** may be selected based on a past history of selection of vehicles for control by the user **112**. The selection of the first vehicle **104A** from the set of vehicles **104** is described, for example, in FIG. 4A.

(27) The electronic device **102** may be further configured to receive, via the haptic device **106** associated with the electronic device **102**, a second user input including a tactile gesture. The tactile gesture may include a first swipe input along a first direction (e.g., the first direction **116A**) associated with the haptic device **106** and may further include a second swipe input along a second

direction (e.g., the second direction **116B**) that is different from the first direction and, for example, perpendicular to the first direction. For example, the tactile gesture may include the first swipe input and the second swipe input in one of, but not limited to, an L-shape configuration, an inverted L-shape configuration, a T-shape configuration, or an inverted T-shape configuration. In an example, as shown in FIG. 1, the tactile gesture may include swipe inputs in an inverted L-shaped configuration. For instance, the tactile gesture may include the first swipe input in the first direction **116A** (e.g., from a bottom-right end to a top-right end of the electronic device **102**) and the second swipe input in the second direction **116B** (e.g., from a top-right end to a top-left end of the electronic device **102**).

(28) The second user input may be indicative of the instruction to remotely control a first set of features on the selected first vehicle **104A**. For example, the first set of features may include, but are not limited to, an engine control feature, a door control feature, or a window control feature, a luggage compartment control feature, an infotainment control feature, or a heating ventilation and air-conditioning (HVAC) system control feature, associated with the selected first vehicle **104A**. In an embodiment, the first set of features may be critical features of the selected first vehicle **104A**, which may be crucial for the safe operation of the selected first vehicle **104A**. Thus, such features may need to be activated or deactivated with care based on the second user input.

(29) The electronic device **102** may be further configured to control the first set of features on the selected first vehicle **104A** based on the received second user input. For example, the second user input may correspond to an instruction to start an engine of the first vehicle **104A**. Based on the vehicle identification information of the first vehicle **104A** and the received second user input, the electronic device **102** may query the server **108** (or the database **110**) for information related to the instructions to start the engine of the first vehicle **104A**. Based on the query, the electronic device **102** may receive the information related to the instructions to start the engine of the first vehicle **104A** from the server **108** (or the database **110**). The electronic device **102** may transmit the instructions (i.e. to start the engine of the first vehicle **104A**) to the first vehicle **104A**, based on the information received from the server **108** (or the database **110**). In an embodiment, the electronic device **102** may directly store the instructions to control the first set of features, rather than querying from the server **108** (or the database **110**). The first vehicle **104A** may further start the engine of the first vehicle **104A** on receipt of the instructions from the electronic device **102**, and thereby the electronic device **102** may control the first vehicle **104A** to start the engine.

(30) For example, the first set of features may be critical features of the selected first vehicle **104A**, and hence, an accidental activation or deactivation of the first set of features has to be avoided on the first vehicle **104A**. For example, a proper usage of the first set of features may be crucial for the safe operation of the first vehicle **104A**. Conventional user interfaces of a vehicle-related device for control of such critical features may be difficult to use as the conventional user interfaces may not be intuitive to a non-technical user. Some conventional user interfaces may also be prone to accidental or unintentional activation or deactivation of the critical features of the vehicle. To avoid the accidental or unintentional activation or deactivation of the critical features, certain conventional user interfaces may require a user to enter a personal identification number (PIN) or a password to enable the user to control the critical features. In such case, the user may be required to remember the PIN or password and may face an inconvenience to enter the PIN or password every time a feature of the vehicle is to be controlled, which may negatively impact the user experience of the user of the vehicle.

(31) On the other hand, the electronic device **102** of the present disclosure may receive the second user input (including the tactile gesture) via the haptic device **106** that may be associated with the electronic device **102**. The second user input may enable intuitive remote control of critical features (e.g., the first set of features) of the selected first vehicle **104A**. The tactile gesture received through the haptic device **106** may be a more user friendly and may correspond to an intuitive mode to capture an input from the user **112** than traditional user interface elements, as the tactile gesture

indicated by the second user input may involve bodily kinesthetic skills of a person that may be known to even non-technical users. Further, the tactile gesture may correspond to a predetermined pattern (e.g., an L-shaped pattern) of swipe inputs to control the critical features of the first vehicle **104A**. The use of such predetermined pattern of swipe inputs to control the critical features of the selected first vehicle **104A** may prevent accidental or inadvertent activation or deactivation of any critical feature of the selected first vehicle **104A**, thereby leading to an enhancement of a user experience of the user (such as the user **112**).

(32) FIG. 2 is a block diagram that illustrates an exemplary electronic device of FIG. 1 to control vehicles, in accordance with an embodiment of the disclosure. FIG. 2 is explained in conjunction with elements from FIG. 1. With reference to FIG. 2, there is shown a block diagram **200** of the electronic device **102**. The electronic device **102** may include circuitry **202**, a memory **204**, a network interface **206**, and an input/output (I/O) device **208**. The input output device **208** may include the haptic device **106**, and a display device **208A**. Although in FIG. 2, it is shown that the electronic device **102** includes the circuitry **202**, the memory **204**, the network interface **206**, and the input/output (I/O) device **208**; however, the disclosure may not be so limiting, and the electronic device **102** may include less or more components to perform the same or other functions of the electronic device **102**. Details of the other functions or components have been omitted from the disclosure for the sake of brevity.

(33) The circuitry **202** may include suitable logic, circuitry, and interfaces that may be configured to execute program instructions associated with different operations to be executed by the electronic device **102**. For example, some of the operations may include reception of the first user input, reception of the second user input including the tactile gesture, and control of the first set of features on the selected first vehicle **104A**. The circuitry **202** may include one or more specialized processing units, which may be implemented as a separate processor. In an embodiment, the one or more specialized processing units may be implemented as an integrated processor or a cluster of processors that perform the functions of the one or more specialized processing units, collectively. The circuitry **202** may be implemented based on a number of processor technologies known in the art. Examples of implementations of the circuitry **202** may be an X86-based processor, a Graphics Processing Unit (GPU), a Reduced Instruction Set Computing (RISC) processor, an Application-Specific Integrated Circuit (ASIC) processor, a Complex Instruction Set Computing (CISC) processor, a microcontroller, a central processing unit (CPU), and/or other control circuits.

(34) The memory **204** may include suitable logic, circuitry, and interfaces that may be configured to store the one or more instructions to be executed by the circuitry **202**. The memory **204** may be configured to store the vehicle identification information associated with the set of vehicles **104**, information associated with the first set of features of a vehicle, and information associated with a second set of features of a vehicle. The memory **204** may be further configured to store health status information associated with a vehicle. Examples of implementation of the memory **204** may include, but are not limited to, Random Access Memory (RAM), Read Only Memory (ROM), Electrically Erasable Programmable Read-Only Memory (EEPROM), Hard Disk Drive (HDD), a Solid-State Drive (SSD), a CPU cache, and/or a Secure Digital (SD) card.

(35) The network interface **206** may include suitable logic, circuitry, and interfaces that may be configured to facilitate communication between the electronic device **102**, the set of vehicles **104**, and the server **108**, via the communication network **114**. The network interface **206** may be implemented by use of various known technologies to support wired or wireless communication of the electronic device **102** with the communication network **114**. The network interface **206** may include, but is not limited to, an antenna, a radio frequency (RF) transceiver, one or more amplifiers, a tuner, one or more oscillators, a digital signal processor, a coder-decoder (CODEC) chipset, a subscriber identity module (SIM) card, or a local buffer circuitry. The network interface **206** may be configured to communicate via wireless communication with networks, such as the Internet, an Intranet or a wireless network, such as a cellular telephone network, a wireless local

area network (LAN), and a metropolitan area network (MAN). The wireless communication may be configured to use one or more of a plurality of communication standards, protocols and technologies, such as Global System for Mobile Communications (GSM), Enhanced Data GSM Environment (EDGE), wideband code division multiple access (W-CDMA), Long Term Evolution (LTE), 5th Generation New Radio (5G NR), code division multiple access (CDMA), time division multiple access (TDMA), Bluetooth, Wireless Fidelity (Wi-Fi) (such as IEEE 802.11a, IEEE 802.11b, IEEE 802.11g or IEEE 802.11n), voice over Internet Protocol (VoIP), light fidelity (Li-Fi), Worldwide Interoperability for Microwave Access (Wi-MAX), a protocol for email, instant messaging, and a Short Message Service (SMS).

(36) The I/O device **208** may include suitable logic, circuitry, and interfaces that may be configured to receive an input from the user **112** and provide an output based on the received input. For example, the I/O device **208** may receive the first user input and the second user input from the user **112**. Further, the I/O device **208** may provide a first user interface (UI) and a second user interface (as the output shown, for example, in FIGS. **9** and **10A-10B**) for the user **112**. The I/O device **208** which may include various input and output devices, may be configured to communicate with the electronic device **102** or the server **108**. Examples of the I/O device **208** may include, but are not limited to, a touch screen, a keyboard, a mouse, a joystick, a microphone, a display device (e.g., the display device **208A**), a haptic device (e.g., the haptic device **106**), and a speaker.

(37) The display device **208A** may include suitable logic, circuitry, and interfaces that may be configured to display information about the set of vehicles **104**, the first set of features, the second set of features, the health status information, the vehicle identification information, the first UI and the second UI. The display device **208A** may be a touch screen which may enable the user **112** to provide a user-input, (such as the first user input, the second user input, a third user input, and a fourth user input) via the display device **208A**. The touch screen may be at least one of a resistive touch screen, a capacitive touch screen, or a thermal touch screen. The display device **208A** may be realized through several known technologies such as, but not limited to, at least one of a Liquid Crystal Display (LCD) display, a Light Emitting Diode (LED) display, a plasma display, or an Organic LED (OLED) display technology, or other display devices. In accordance with an embodiment, the display device **208A** may refer to a display screen of a head mounted device (HMD), a smart-glass device, a see-through display, a projection-based display, an electro-chromic display, or a transparent display.

(38) The functions or operations executed by the electronic device **102**, as described in FIG. **1**, may be performed by the circuitry **202**. Operations executed by the circuitry **202** are described in detail, for example, in FIGS. **4A** and **4B**.

(39) FIG. **3** is a block diagram that illustrates an exemplary first vehicle of FIG. **1**, in accordance with an embodiment of the disclosure. FIG. **3** is explained in conjunction with elements from FIGS. **1** and **2**. With reference to FIG. **3**, there is shown a block diagram **300** of the first vehicle **104A**. The first vehicle **104A** may include a network interface **302**, an electronic control device **304**, a memory **306**, an engine **308**, a battery **310**, a power system **312**, a steering system **314**, a braking system **316**, and a heating ventilation and air-conditioning (HVAC) system **318**. Although in FIG. **3**, it is shown that the first vehicle **104A** includes the network interface **302**, the electronic control device **304**, the memory **306**, the engine **308**, the battery **310**, the power system **312**, the steering system **314**, the braking system **316**, and the HVAC system **318**; however, the disclosure may not be so limiting, and the first vehicle **104A** may include less or more components to perform the same or other functions of the first vehicle **104A**. Details of the other functions or components have been omitted from the disclosure for the sake of brevity.

(40) The network interface **302** may include suitable logic, circuitry, and interfaces that may be configured to facilitate communication between the first vehicle **104A**, the electronic device **102**, and the server **108**, via the communication network **114**. The network interface **302** may be

implemented by use of various known technologies to support wired or wireless communication of the first vehicle **104A** with the communication network **114**. The network interface **302** may include, but is not limited to, an antenna, a radio frequency (RF) transceiver, one or more amplifiers, a tuner, one or more oscillators, a digital signal processor, a coder-decoder (CODEC) chipset, a subscriber identity module (SIM) card, or a local buffer circuitry. The network interface **302** may be configured to communicate via wireless communication with networks, such as the Internet, an Intranet or a wireless network, such as a cellular telephone network, a wireless local area network (LAN), and a metropolitan area network (MAN). The wireless communication may be configured to use one or more of a plurality of communication standards, protocols and technologies, such as Global System for Mobile Communications (GSM), Enhanced Data GSM Environment (EDGE), wideband code division multiple access (W-CDMA), Long Term Evolution (LTE), 5th Generation New Radio (5G NR), code division multiple access (CDMA), time division multiple access (TDMA), Bluetooth, Wireless Fidelity (Wi-Fi) (such as IEEE 802.11a, IEEE 802.11b, IEEE 802.11g or IEEE 802.11n), voice over Internet Protocol (VoIP), light fidelity (Li-Fi), Worldwide Interoperability for Microwave Access (Wi-MAX), a protocol for email, instant messaging, and a Short Message Service (SMS).

(41) The electronic control device **304** may include suitable logic, circuitry, interfaces, and/or code that may be configured to activate or deactivate the first set of features or a second set of features associated with the first vehicle **104A** based on receipt of the second user input and a third user input, respectively from the electronic device **102**. The electronic control device **304** may be a specialized electronic circuitry that may include an electronic control unit (ECU) processor to control different functions, such as, but not limited to, engine operations, communication operations, and data acquisition of the first vehicle **104A**. The electronic control device **304** may control the first vehicle **104A** to activate or deactivate the first set of features or the second set of features of the first vehicle **104A**. The electronic control device **304** may be further configured to control a plurality of sensors (not shown) of the first vehicle **104A** to measure the health status information associated with the first vehicle **104A**, and further transmit the measured health status information to the electronic device **102**. The electronic control device **304** may be a microprocessor. Other examples of the electronic control device **304** may include, but are not limited to, a vehicle control system, an in-vehicle infotainment (IVI) system, an in-car entertainment (ICE) system, an automotive Head-up Display (HUD), an automotive dashboard, an embedded device, a smartphone, a human-machine interface (HMI), a computer workstation, a handheld computer, a cellular/mobile phone, a portable consumer electronic (CE) device, a server, and other computing devices. The electronic control device **304** may be included or integrated in the first vehicle **104A**.

(42) The memory **306** may include suitable logic, circuitry, and interfaces that may be configured to store the one or more instructions to be executed by the first vehicle **104A**. The memory **306** may be configured to store information associated with the first set of features and a second set of features associated with the first vehicle **104A**. The memory **306** may be further configured to store the health status information and the vehicle identification information associated with the first vehicle **104A**. Examples of implementation of the memory **306** may include, but are not limited to, Random Access Memory (RAM), Read Only Memory (ROM), Electrically Erasable Programmable Read-Only Memory (EEPROM), Hard Disk Drive (HDD), a Solid-State Drive (SSD), a CPU cache, and/or a Secure Digital (SD) card.

(43) The engine **308** may be configured to provide power to the first vehicle **104A**. The engine **308** may be an internal combustion engine with may include operations, for example, fuel injection, compression, ignition, or emission to power and drive the first vehicle **104A**. The engine **308** may include various parts, for example, but are not limited to, a crankshaft, a cylinder, a spark plug, a piston, camshaft, a valve, combustion chamber, etc. In some embodiments, the engine **308** may include a motor in case of an electric motorcycle. The engine **308** may be two-stroke or four-stroke

internal combustion engines. The engine **308** may include either one, two, three, four, or six cylinders. Examples of the engine **308** may include, but are not limited to, an inline engine (i.e. single cylinder, parallel twin, inline-triple, inline-four, inline-six), a V layout engine (i.e. V-twin engine, a V4 engine, a V8 engine), a flat (boxer) engine (i.e. flat-two, flat-four, flat-six), a lawn mower engine, a snow blower engine, or other motorcycle engines known in the art. A description of various parts of the engine **308** has been omitted from the disclosure for the sake of brevity.

(44) The battery **310** may be a source of electric power for one or more electric circuits or loads (not shown) of the first vehicle **104A**. For example, the battery **310** may be a source of electrical power to a control circuitry (not shown) of the first vehicle **104A**, the network interface **302**, the electronic control device **304**, the memory **306**, the engine **308**, the power system **312**, the steering system **314**, and the braking system **316**. The battery **310** may be a rechargeable battery. The battery **310** may be the source of electrical power to start the engine **308** of the first vehicle **104A**. In some embodiments, the battery **310** may correspond to a battery pack, which may have a plurality of clusters of batteries, which may be surrounded by a suitable coolant and a charge controller (not shown in FIG. 3). Examples of the battery **310** may include, but are not limited to, a lead acid battery, a nickel cadmium battery, a nickel-metal hydride battery, a lithium-ion battery, and other rechargeable batteries.

(45) The power system **312** may include suitable logic, circuitry, interfaces, and/or code that may be configured to control electric power which may be output to various electric circuits and loads of the first vehicle **104A**. The power system **312** may include a battery (such as the battery **310**) to provide the electric power to perform various electrical operations of the first vehicle **104A**. The power system **312** may provide the electric power for functioning of different components (such as, the electronic control device **304**, a communication system, the memory **306**, the steering system **314**, and the plurality of sensors) of the first vehicle **104A**. The power system **312** may be configured to receive control signals from the electronic control device **304** of the first vehicle **104A**. The power system **312** may be configured to control the charging and the discharging of the battery **310** and an auxiliary battery based on the received control signals. The power system **312** may be configured to control the transfer of the electric energy between the power system **312**, the memory **306**, the steering system **314**, the braking system **316**, and the plurality of sensors of the first vehicle **104A**. Examples of the power system **312** may include, but are not limited to, an electric charge/discharge controller, a charge regulator, a battery regulator, a battery management system, an electric circuit breaker, a power electronic drive control system, an Application-Specific Integrated Circuit (ASIC) processor, and/or other energy-control hardware processors.

(46) The steering system **314** may receive one or more control commands from the user **112**. The steering system **314** may include a steering wheel/handlebar and/or an electric motor (provided for a power-assisted steering) that may be used by a driver to control movement of the first vehicle **104A** in manual mode or a semi-autonomous mode. In accordance with an embodiment, the movement or steering of the first vehicle **104A** may be automatically controlled when the first vehicle **104A** is in autonomous mode. Examples of the steering system **314** may include, but are not limited to, an autonomous steering control, a power-assisted steering system, a vacuum/hydraulic-based steering system, an electro-hydraulic power-assisted system (EHPAS), or a “steer-by-wire” system, or an autonomous steering system, known in the art.

(47) The braking system **316** may be used to stop or slow down the first vehicle **104A** by application of resistive forces, such as electromagnetic and/or frictional forces. The braking system **316** may receive a command from a powertrain control system under the control of the control circuitry (or the electronic control device **304**) when the first vehicle **104A** is in an autonomous mode or a semi-autonomous mode. In accordance with an embodiment, the braking system **316** may receive a command from the control circuitry when the control circuitry (or the electronic control device **304**) preemptively detects intent of the user **112** to perform a specific task which requires the user **112** to apply brakes.

(48) The HVAC system **318** may include a heating system, a ventilation system, an air-conditioning system, and/or a thermostat system that may be configured to maintain a temperature, an air flow, and/or a humidity level of air inside a cabin (not shown) of the first vehicle **104A**. The HVAC system **318** may include a set of adjustable air vents that may be servo-controlled (e.g., controlled by one or more servo motors). The set of adjustable air vents may circulate air at a certain temperature, humidity, and pressure into the cabin of the first vehicle **104A** to maintain the temperature, air flow, and/or humidity level of the air inside the cabin of the first vehicle **104A**.

(49) FIGS. **4A** and **4B** are diagrams that collectively illustrate an execution scenario to control a first vehicle by use of the electronic device of FIG. **1**, in accordance with an embodiment of the disclosure. FIGS. **4A** and **4B** are explained in conjunction with elements from FIGS. **1**, **2** and **3**. With reference to FIGS. **4A** and **4B**, there is shown an execution scenario **400A-400B** of exemplary operations from **402** to **410** that may be executed by the circuitry **202** of the electronic device **102**.

(50) At **402**, a vehicle selection operation may be executed. In the vehicle selection operation, the circuitry **202** may be configured to receive from the user **112**, the first user input indicative of the selection of the first vehicle (e.g., the first vehicle **104A**) from the set of vehicles **104** associated with the user **112**. Based on the reception of the first user input from the user **112**, the circuitry **202** may select the first vehicle **104A** from the set of vehicles **104**. In an example, the first vehicle **104A** may be selected by using an auto populate user interface element (for example rendered on the display device **208A**). For example, the circuitry **202** of the electronic device **102** may receive one or more characters associated with a name of a vehicle (for example a model name) from the user **112** as the first user input. The circuitry **202** may select the first vehicle **104A** based on the received one or more characters about the first vehicle **104A**. In another example, the circuitry **202** may present a user interface **402A** on the display device **208A** to receive the first user input indicative of the selection of the first vehicle **104A**. The user interface **402A** may include, for example, a dropdown menu **412** that may include names or the vehicle identification information of each of the set of vehicles **104** as items of the dropdown menu **412**. For example, the dropdown menu **412** may include vehicle names, such as, “Vehicle 1”, “Vehicle 2”, “Vehicle 3”, and “Vehicle 4” as shown in FIG. **4A**. The circuitry **202** may receive the first user input based on selection of an item from the dropdown menu **412**. For example, as shown in FIG. **4A**, the circuitry **202** may receive a user input indicative of a selection of a first item **414** (such as, the “Vehicle 1”) as the first user input. Based on the selection of the first item **414** (such as, the “Vehicle 1”), the first vehicle **104A** may be selected. The selection of the first vehicle **104A** by use of the dropdown menu **412** in FIG. **4A** is for exemplary purposes and should not be construed to limit the scope of the disclosure. The first vehicle **104A** may be selected using various other user interface elements and/or using different selection techniques (e.g., a random selection, or an automatic selection by the circuitry **202** based on past vehicle selection history of the user **112** or other users associated with the user **112**), without departure from the scope of the disclosure.

(51) At **404**, a tactile gesture reception operation may be executed. In the tactile gesture reception operation, the circuitry **202** may be configured to receive the second user input including the tactile gesture. The second user input may be indicative of the instruction to remotely control the first set of features on the selected first vehicle **104A**. The first set of features may be critical features of the selected first vehicle **104A** that may be remotely controlled.

(52) In an embodiment, the first set of features of the selected first vehicle **104A** may correspond to at least one of, but are not limited to, an engine control feature, a door control feature, or a window control feature, a luggage compartment control feature, an infotainment control feature, or a heating ventilation and air-conditioning (HVAC) system control feature, associated with the selected first vehicle **104A**. The engine control feature may be selected to activate or deactivate the engine of the selected first vehicle **104A** based on the tactile gesture. For example, the engine control feature may be used in a cold region to remotely start the engine (say in advance) and warm the engine of the selected first vehicle **104A** before the user **112** rides the first vehicle **104A**. The

door control feature may be used to remotely open or close one or more doors of the selected first vehicle **104A** to enable another person to wait inside the selected first vehicle **104A** until the user **112** arrives at a location of the first vehicle **104A**. The window control feature may be used to remotely open or close one or more windows of the selected first vehicle **104A** (for example to enable ventilation of the first vehicle **104A** before the user **112** rides). The luggage compartment control feature may be used to remotely open or close the luggage compartment of the first vehicle **104A** to enable loading of luggage to or unloading of luggage from the first vehicle **104A** by a person (e.g., a porter or the user **112**). The infotainment control feature may be used to remotely activate or deactivate an infotainment system of the first vehicle **104A** for individuals seated in the first vehicle **104A**. The heating ventilation and air-conditioning (HVAC) system control feature may be used to increase or decrease a temperature of the cabin of the first vehicle **104A**. For example, the HVAC system control feature may be used in summer season to cool the cabin of the selected first vehicle **104A** before the user **112** rides the selected first vehicle **104A**. Alternatively, the HVAC system control feature may be used in winter season to warm the cabin of the selected first vehicle **104A** before the user **112** rides the selected first vehicle **104A**. In another example, the HVAC system control feature may be used to cool or warm the cabin of the first vehicle **104A** for individuals who may be present in the first vehicle **104A**.

(53) In an embodiment, one or more features of the first set of features may be remotely controlled based on the received second user input. The circuitry **202** may present a user interface **404A** on the display device **208A** to enable the selection of the one or more features to be controlled. The user interface **402A** may include, for example, a dropdown menu **416** including the first set of features. For example, as shown in FIG. 4A, the first set of features in the dropdown menu **416** may include “Feature 1”, “Feature 2”, “Feature 3”, and “Feature 4”. The circuitry **202** may receive a user input (i.e., second user input) indicative of a selection of one or more features (that are to be controlled) of the first set of features from the dropdown menu **416**. For example, as shown in FIG. 4A, the circuitry **202** may receive the user input indicative of a selection of a second item **418** (such as, the “Feature 2”) as the selected one or more features to be remotely controlled. Based on the selection of the second item **418** (such as, the “Feature 2”), the feature, such as, the engine control feature of the first vehicle **104A**, may be selected. The selection of the engine control feature by use of the dropdown menu **416** in FIG. 4A is for exemplary purposes and should not be construed to limit the scope of the disclosure. The engine control feature or any other feature of the first set of features may be selected using various other user interface elements or using selection techniques (e.g., an automatic selection by the circuitry **202** based on past feature selection history of the user **112** or other users associated with the user **112**), without departure from the scope of the disclosure.

(54) In an embodiment, the circuitry **202** may be further configured to control the display device **208A** to display a user interface **404B** with a displayed pattern and to receive the tactile gesture as the second user input along the displayed pattern. The tactile gesture may include the first swipe input and the second swipe input. The circuitry **202** may receive the first swipe input, via the haptic device **106**, that may include a swipe input of the user **112** (using an anatomic region of the user **112**, such as, a finger, e.g., a forefinger) in the first direction **116A**. For example, the first direction **116A** may correspond to a direction that may be parallel to a first edge of the haptic device **106** as shown, for example, in FIG. 4A. For example, the first swipe input may be a swipe input of the user **112** from a bottom-right end to a top-right end of the haptic device **106**. The circuitry **202** may further receive the second swipe input, via the haptic device **106**, that may include a swipe input of the user **112** (using the anatomic region of the user **112**, such as, the forefinger) in the second direction **116B** that may be perpendicular to the first direction **116A**. For example, the second direction **116B** may correspond to a direction that may be parallel to a second edge of the haptic device **106**, wherein the second edge may be perpendicular to the first edge of the haptic device **106**. For example, the second swipe input may be a swipe input of the user **112** from a top-right end to a top-left end of the haptic device **106**. As an example, the tactile gesture may be in various

shaped swipe configurations such as, an L-shaped swipe configuration, a vertically inverted L-shaped swipe configuration (as shown in FIG. 4A for example), a horizontally inverted L-shaped swipe configuration a T-shaped swipe configuration, or an inverted T-shaped swipe configuration. The tactile gesture may include a predetermined pattern of swipe inputs that may be displayed on the display device **208A**, which may be a non-trivial user-input for the user **112** and may require some effort on part of the user **112**. Thus, the use of the tactile gestures (i.e., including the first swipe input in a direction perpendicular to a direction of the second swipe input) to control the first set of features may reduce a likelihood of an accidental or unintentional activation or deactivation of the first set of features, as compared to conventional user interface inputs. In some embodiments, the user **112** may define different tactile gestures for different set of features to be controlled on the first vehicle **104A**. For example, the L-shaped swipe gesture may be defined for the door lock/unlock, a vertically inverted L-shaped swipe gesture may be defined for engine start/stop, T-shaped swipe gesture may be defined for window open/close and so on.

(55) At **406**, a feature control operation of a vehicle may be executed. In the feature control operation of the vehicle, the circuitry **202** may remotely control the first set of features on the selected first vehicle **104A** based on the received second user input including the tactile gesture. For example, the second user input may correspond to an instruction to start an engine of the first vehicle **104A**. Based on the vehicle identification information of the first vehicle **104A** and the received second user input, the circuitry **202** may query the server **108** (or the database **110**) for information related to the instructions to start the engine of the first vehicle **104A**. Based on the query, the circuitry **202** may receive the information (such as one or more wireless commands), related to the instructions to start the engine of the first vehicle **104A**, from the server **108** (or the database **110**). The circuitry **202** may further transmit the instructions to start the engine of the first vehicle **104A** to the first vehicle **104A**, based on the information received from the server **108** (or the database **110**). In some embodiments, the electronic device **102** may store different instructions related to the first set of features (i.e., related to the first vehicle **104A**) in the memory **204** and may not query the server **108** (or the database **110**). In such case, the circuitry **202** may retrieve the corresponding instructions to control one of the first set of features from the memory **204**, based on the received second user input. The first vehicle **104A** may further start the engine of the first vehicle **104A** on receipt of the instructions from the circuitry **202**, and thereby the circuitry **202** may remotely control the first vehicle **104A** to start the engine (as shown in FIG. 4B). In some embodiment, the circuitry **202** may control the display device **208A** to show one or more icons (shown, for example, in FIGS. 5-7 and 10A-10B) indicating to the user **112** that the selected feature is being controlled on the selected first vehicle **104A**. For example, the icon may indicate that the engine of the first vehicle **104A** is now started, or a door of the first vehicle **104A** is unlocked (or locked) based on the control performed as per the second user input, by the disclosed electronic device **102**. In further embodiment, the icon may further indicate a time period (in seconds or minutes) taken to completely control the selected feature, for example, 10 seconds to be taken to start the engine of the first vehicle **104A**. The circuitry **202** may further control a countdown timer (as further described in FIGS. 5-6) to indicate a remaining time (i.e. out of the total time period) to complete the control of the selected feature. The remaining time for the completion of the control of the selected feature (for example door unlock or engine start) may be indicated by a user interface element (not shown), for example, a progress bar.

(56) In an embodiment, the circuitry **202** may be further configured to receive from the selected first vehicle **104A**, a confirmation (as described at **408**) indicative of the control of the first set of features (e.g., an enablement or starting of an engine) on the selected first vehicle **104A**, based on the received second user input. The circuitry **202** may be further configured to control the haptic device **106** associated with the electronic device **102** to output haptic feedback (as described at **410**), based on the received confirmation.

(57) At **408**, a reception confirmation operation may be executed. In the reception confirmation

operation, the circuitry **202** may be configured to receive from the electronic control device **304** of the selected first vehicle **104A**, confirmation information (i.e. related to a confirmation) indicative of the reception of the instructions to control the first set of features at the selected first vehicle **104A**. For example, once the selected first vehicle **104A** receives the instructions for the control of the first set of features on the selected first vehicle **104A** from the electronic device **102**, the selected first vehicle **104A** may control the first set of features (i.e., engine start) based on the instructions. Further, the selected first vehicle **104A** may transmit to the electronic device **102**, the confirmation indicative of the reception of the instructions from the electronic device **102**. The circuitry **202** may receive the confirmation transmitted by the selected first vehicle **104A**.

(58) At **410**, a haptic feedback output operation may be executed. In the haptic feedback output operation, the circuitry **202** may be configured to control the haptic device **106** associated with the electronic device **102** to output a haptic feedback, based on the received confirmation. The haptic feedback may provide an indication to the user **112** that the first set of features have been controlled on the selected first vehicle **104A**. In an embodiment, feedback (such as visual feedback) may be provided based on a blinking of the display device **208A** or light emitting diodes (LEDs) associated with the electronic device **102** to inform the user **112** that the first set of features have been controlled on the selected first vehicle **104A**. In another embodiment, the feedback may be provided as a notification, or a message displayed on the display device **208A**. The notification or message may indicate that the first set of features have been controlled on the selected first vehicle **104A** based on the second user input provided by the user **112** (for example using the L-shape gesture as shown in FIG. **4A**). In another embodiment, the haptic feedback may be provided as a vibration and/or as an audio output associated with the haptic device **106**. For example, the haptic device **106** may vibrate for a certain time period (e.g., 10 seconds). Further, an audio notification may also be output through the haptic device **106** (or via an audio generating component, such as a speaker inbuilt in the electronic device **102**) to indicate the control of the first set of features on the selected first vehicle **104A**.

(59) In an embodiment, the electronic device **102** or the haptic device **106** may be a user wearable device. The user wearable device may be worn by the user **112** associated with the electronic device **102** to remotely control the selected first vehicle **104A**. Example of the user wearable device may include a head band, a wrist band, a head-mounted device, a smart watch, and the like. The use of the user wearable device as the electronic device **102** may facilitate the user **112** to easily carry the electronic device **102** and/or the haptic device **106** to remotely control the set of vehicles **104**, without a worry for misplacing the electronic device **102** and/or the haptic device **106**.

(60) FIG. **5** is a diagram that illustrates an exemplary scenario of a user interface of the electronic device of FIG. **1** to stop a started engine of a first vehicle. FIG. **5** is explained in conjunction with elements from FIGS. **1**, **2**, **3**, **4A**, and **4B**. With reference to FIG. **5**, there is shown an exemplary scenario of a user interface (UI) **500**. The UI **500** may include a set of UI elements including a first UI element **502**, a second UI element **504**, a third UI element **506**, and a fourth UI element **508**. The circuitry **202** may be configured to control the display device **208A** to display the UI **500** including the set of UI elements. A set of operations associated with the exemplary scenario is described herein.

(61) In an embodiment, the circuitry **202** may be configured to receive a third user input indicative of a time duration after which a started engine (e.g., the engine **308**) of the selected first vehicle (e.g., the first vehicle **104A**) is to be stopped. The circuitry **202** may be further configured to control the selected first vehicle **104A** to stop the started engine **308** of the selected first vehicle **104A**, based on the received third user input. The third user input may be received in several ways. In an example, the circuitry **202** may enable the user **112** to provide a swipe input through the UI **500** on the display device **208A** such that the swipe input may correspond to the third user input. In another example, the circuitry **202** may present a UI element on the display device **208A** that may accept a tap input from the user **112** as the third user input. For example, as shown in FIG. **5**, the

circuitry **202** may present the first UI element **502** (such as, a dropdown menu list) through the display device **208A** to the user **112**. The first UI element **502** may include a plurality of items, each of which may indicate a certain time interval after which the engine **308** is to be stopped. For example, the first UI element **502** may include time interval options, such as, “5 minutes”, “10 minutes”, “20 minutes”, and “40 minutes”. The circuitry **202** may receive the third user input as a selection of one of the items of the first UI element **502**. For example, the circuitry **202** may receive a selection of the second UI element **504** (e.g., an item that may correspond to a time interval of “10 minutes”) from the user **112**. In such case, the time interval of “10 minutes” may be selected as a time interval after which the started engine **308** of the selected vehicle **104A** is to be stopped. In another example, the circuitry **202** may receive the third user input as a tactile gesture from the user **112** through at least one of the haptic device **106** and/or the display device **208A**. The third user input may indicate the time duration after which the started engine **308** of the selected first vehicle **104A** may be stopped.

(62) Once the third user input is received, the circuitry **202** may be configured to start a countdown timer based on the time interval indicated in the third user input. For example, in case the time interval of “10 minutes” is selected through the second UI element **504**, the countdown timer may start from “10 minutes”. As shown in FIG. 5, there is shown an exemplary user interface element, such as, the third UI element **506** that may present the current time left (e.g., “55 seconds”) for expiration of the started countdown timer. In an embodiment, the circuitry **202** may receive, through the third UI element **506**, a user input to reset the time interval of the countdown timer to the initially set value (e.g., “10 minutes” as the third user input). For example, the circuitry **202** may receive a single tap user input through the third UI element **506** from the user **112**. The single tap user input may be the user input to reset the time interval of the countdown timer to the initially set value. In an embodiment, the circuitry **202** may receive, through the third UI element **506**, a user input to pause the countdown timer to a current value (e.g., “55 seconds”). For example, the circuitry **202** may receive a first double tap user input through the third UI element **506** from the user **112** to pause the countdown timer to the current value. Further, through the third UI element **506**, the circuitry **202** may receive another user input to resume the paused countdown time, in case the countdown timer is paused. For example, the circuitry **202** may receive a second double tap user input through the third UI element **506** from the user **112**. The second double tap user input may be received after the first double tap user input. Based on the receipt of the second double tap user input, the circuitry **202** may resume the paused countdown timer. For example, the countdown timer may resume from the current value. In an embodiment, during the operation of the countdown timer, the circuitry **202** may receive a user input from the user **112** to edit the time interval of the countdown timer (for example increase or decrease of certain seconds/minutes in the time duration indicated by the third user input). Once the countdown timer expires (i.e., reaches zero value), the circuitry **202** may be configured to remotely control the selected first vehicle **104A** to stop the started engine **308** of the selected first vehicle **104A**. For example, once the engine **308** is stopped on the selected first vehicle **104A**, the circuitry **202** may further control the display device **208A** to render the fourth UI element **508** indicative of a status of the engine **308** (i.e., “Engine Stopped”). It should be noted that the UI **500** of FIG. 5 is for exemplary purposes and should not be construed to limit the scope of the disclosure.

(63) FIG. 6 is a diagram that illustrates an exemplary scenario of a user interface of the electronic device of FIG. 1 to start a stopped engine of a first vehicle. FIG. 6 is explained in conjunction with elements from FIGS. 1, 2, 3, 4A, 4B, and 5. With reference to FIG. 6, there is shown an exemplary scenario of a user interface (UI) **600**. The UI **600** may include a set of UI elements including a first UI element **602**, a second UI element **604**, a third UI element **606**, and a fourth UI element **608**. The circuitry **202** may be configured to control the display device **208A** of the electronic device **102** to display the UI **600** including the set of UI elements. A set of operations associated with the exemplary scenario is described herein.

(64) In an embodiment, the circuitry **202** may be configured to receive a third user input indicative of a time duration after which a stopped engine (e.g., the engine **308**) of the selected first vehicle **104A** is to be started. The circuitry **202** may be further configured to control the selected first vehicle **104A** to start the stopped engine **308** of the selected first vehicle **104A** based on the received third user input. In an example, the circuitry **202** may enable the user **112** to provide a swipe input through the UI **600** on the display device **208A** such that the swipe input may correspond to the third user input. In another example, the circuitry **202** may present a UI element on the display device **208A** that may accept a tap input from the user **112** as the third user input. For example, as shown in FIG. 6, the circuitry **202** may present the first UI element **602** (such as, a dropdown menu list) through the display device **208A** to the user **112**. The first UI element **602** may include a plurality of items, each of which may indicate a certain time interval after which the engine **308** is to be started. For example, the first UI element **602** may include time interval options, such as, “5 minutes”, “10 minutes”, “20 minutes”, and “40 minutes”. The circuitry **202** may receive the third user input as a selection of one of the items of the first UI element **602**. For example, the circuitry **202** may receive a selection of the second UI element **604** (e.g., an item that may correspond to a time interval of “10 minutes”) from the user **112**. In such case, the time interval of “10 minutes” may be selected as a time interval after which the stopped engine **308** of the selected vehicle **104A** is to be started. In another example, the circuitry **202** may receive the third user input as a tactile gesture from the user **112** through at least one of the haptic device **106** and/or the display device **208A**. The third user input may provide the time duration after which the stopped engine **308** of the selected first vehicle **104A** may be started. For example, in areas where temperature is considerably low (e.g., less than 0 degrees Celsius), the engine oil of the first vehicle **104A** may thicken, and the engine **308** may need to be turned on to warm up the engine **308** before the user **112** rides the first vehicle **104A**. Thus, to warm up the engine **308** prior to a start of a journey of the first vehicle **104A**, the engine **308** of the first vehicle **104A** may be required to be started at a certain time before the user **112** rides the first vehicle **104A**.

(65) Once the third user input is received, the circuitry **202** may be configured to start a countdown timer based on the time interval indicated in the third user input. For example, in case the time interval of “10 minutes” is selected through the second UI element **604**, the countdown timer may start from “10 minutes”. As shown in FIG. 6, there is shown an exemplary user interface element, such as, the third UI element **606** that may present the current time left (e.g., “55 seconds”) for expiration of the started countdown timer. In an embodiment, the circuitry **202** may receive, through the third UI element **606**, a user input to reset the time interval of the countdown timer to the initially set value (e.g., “10 minutes” as the third user input). For example, the circuitry **202** may receive a single tap user input through the third UI element **606** from the user **112**. The single tap user input may be the user input to reset the time interval of the countdown timer to the initially set value of. In an embodiment, the circuitry **202** may receive, through the third UI element **606**, a user input to pause the countdown timer to a current value (e.g., “55 seconds”). For example, the circuitry **202** may receive a first double tap user input through the third UI element **606** from the user **112** to pause the countdown timer to the current value. Further, through the third UI element **606**, the circuitry **202** may receive another user input to resume the paused countdown time. For example, the circuitry **202** may receive a second double tap user input through the third UI element **606** from the user **112** to resume the paused countdown timer. Once the countdown timer expires (i.e., reaches zero value), the circuitry **202** may be configured to remotely control the selected first vehicle **104A** to start the stopped engine **308** of the selected first vehicle **104A**. For example, once the engine **308** is started on the selected first vehicle **104A**, the circuitry **202** may further control the display device **208A** to render the fourth UI element **608** indicative of a status of the engine (i.e., “Engine Started”). It should be noted that the UI **600** of FIG. 6 is for exemplary purposes and should not be construed to limit the scope of the disclosure.

(66) FIG. 7 is a diagram that illustrates an exemplary scenario of a user interface of the electronic

device of FIG. 1 to start a stopped heating ventilation and air-condition (HVAC) system of a first vehicle, in accordance with an embodiment of the disclosure. FIG. 7 is explained in conjunction with elements from FIGS. 1, 2, 3, 4A, 4B, 5, and 6. With reference to FIG. 7, there is shown an exemplary scenario of a user interface (UI) **700**. The UI **700** may include a set of UI elements including a first UI element **702**, a second UI element **704**, a third UI element **706**, and a fourth UI element **708**. The circuitry **202** may be configured to control the display device **208A** of the electronic device **102** to display the UI **700** including the set of UI elements. A set of operations associated with the exemplary scenario is described herein.

(67) In an embodiment, the circuitry **202** is further configured to receive a third user input indicative of a time duration after which a stopped HVAC system (e.g., the HVAC system **318**) of the selected first vehicle **104A** is to be started. The circuitry **202** is further configured to remotely control the selected first vehicle **104A** to start the stopped HVAC **318** system of the selected first vehicle **104A**, based on the received third user input. In an example, the circuitry **202** may enable the user **112** to provide a swipe input through the UI **700** on the display device **208A** such that the swipe input may correspond to the third user input. For example, as shown in FIG. 6, the circuitry **202** may present the first UI element **702** (such as, a dropdown menu list) through the display device **208A** to the user **112**. The first UI element **702** may include a plurality of items, each of which may indicate a certain time interval after which the HVAC system **318** is to be started. For example, the first UI element **702** may include time interval options, such as, “5 minutes”, “10 minutes”, “20 minutes”, and “40 minutes”. The circuitry **202** may receive the third user input as a selection of one of the items of the first UI element **702**. For example, the circuitry **202** may receive a selection of the second UI element **704** (e.g., an item that may correspond to a time interval of “10 minutes”) from the user **112** as the third user input. In such case, the time interval of “10 minutes” may be selected as a time interval after which the stopped HVAC system **318** of the selected vehicle **104A** is to be started. In another example, the circuitry **202** may receive the third user input as a tactile gesture from the user **112** through at least one of the haptic device **106** and/or the display device **208A**. The third user input may provide the time duration after which the stopped HVAC system **318** of the selected first vehicle **104A** may be started. For example, in the winter or in certain areas where temperature is low (e.g., less than 0 degrees Celsius), the HVAC system **318** of the selected first vehicle **104A** may be required to be started to warm the cabin of the selected first vehicle **104A**, for comfort of the user **112** and other occupants of the first vehicle **104A**, before the ride of the selected first vehicle **104A** starts. Similarly, during summers or in certain areas where the temperature is high (e.g., more than 35 degrees Celsius), the HVAC system of the selected first vehicle **104A** may be required to be started to cool the cabin of the selected first vehicle **104A**, for the comfort of the user **112** and other occupants of the first vehicle **104A**, before the ride of the selected first vehicle **104A** starts.

(68) As described in FIGS. 5-6, once the third user input is received, the circuitry **202** may be configured to start a countdown timer based on the time interval indicated in the third user input. For example, in case the time interval of “10 minutes” is selected through the second UI element **704**, the countdown timer may start from “10 minutes”. As shown in FIG. 7, there is shown an exemplary user interface element, such as, the third UI element **706** that may present the current time left (e.g., “55 seconds”) for expiration of the started countdown timer. In an embodiment, the circuitry **202** may receive, through the third UI element **706**, a user input to reset the time interval of the countdown timer to the initially set value (e.g., “10 minutes”). Once the countdown timer expires (i.e., reaches zero value), the circuitry **202** may be configured to remotely control the selected first vehicle **104A** to start the stopped HVAC system **318** of the selected first vehicle **104A**. For example, once the HVAC system **318** is started on the selected first vehicle **104A**, the circuitry **202** may present the fourth UI element **708** indicative of a status of the HVAC system **318** (i.e., “HVAC Started”). It should be noted that the UI **700** of FIG. 7 is for exemplary purposes and should not be construed to limit the scope of the disclosure.

(69) FIG. 8 is a diagram that illustrates an execution scenario to remotely control a second set of features on a first vehicle, in accordance with an embodiment of the disclosure. FIG. 8 is explained in conjunction with elements from FIGS. 1, 2, 3, 4A, 4B, 5, 6, and 7. With reference to FIG. 8, there is shown an execution scenario **800** of exemplary operations from **802** to **806** performed by the electronic device **102** or by the circuitry **202**.

(70) At **802**, a vehicle selection operation may be executed. In the vehicle selection operation, the circuitry **202** may be configured to receive the first user input indicative of the selection of the first vehicle (e.g., the first vehicle **104A**) from the set of vehicles **104** associated with the user **112**. For example, the first vehicle **104A** may be selected for remote control of a second set of features on the selected first vehicle **104A**. Details related to the vehicle selection operation are described further, for example, in FIG. 4, at operation **402**.

(71) At **804**, a second feature selection operation may be executed. In the second feature selection operation, the circuitry **202** may be configured to receive a fourth user input indicative of an instruction to remotely control a second set of features on the selected first vehicle **104A**. For example, the second set of features correspond to at least one of, but is not limited to, a head light control feature, a wiper control feature, a sunroof control feature, a seat temperature control feature, or a horn control feature associated with the selected first vehicle **104A**. The circuitry **202** may be further configured remotely control the second set of features on the selected first vehicle based on the received fourth user input. For example, the second set of features of the selected first vehicle **104A** may be features that may not be critical features. The second set of features have been separated to distinguish from the first set of features that are critical and may need to be activated and deactivated with care.

(72) The electronic device **102** may remotely control the second set of features based on the fourth user input. The head light control feature may be used to activate or deactivate a headlight of the selected first vehicle **104A** remotely. The wiper control feature may be used to activate or deactivate a wiper of the selected first vehicle **104A** remotely. For example, the wiper control feature may be employed to activate the wiper of the selected first vehicle **104A** to remotely clean a windshield of the selected first vehicle **104A** before the user **112** rides the selected first vehicle **104A**. The sunroof control feature may be used to open or close a sunroof of the selected first vehicle **104A** remotely. For example, the sunroof control feature may be used to open the sunroof of the selected first vehicle **104A** remotely for ventilation and sunlight. The seat temperature control feature may be used to activate or deactivate heating or cooling of one or more seats of the selected first vehicle **104A** remotely. For example, the seat temperature control feature may be used to activate a seat heater of the selected first vehicle **104A** to remotely warm the seat before the user **112** rides the selected first vehicle **104A**. The horn control feature may be used to activate or deactivate a horn of the selected first vehicle **104A** remotely. For example, when the first vehicle **104A** is positioned in a parking and the user **112** wishes to clear the traffic near the selected first vehicle **104A**, the horn control feature may be activated (for example for 30 seconds). The fourth user input may be received in a manner similar to the reception of the second user input, as described, for example, at **404** of FIG. 4. The fourth user input may be received via one of, but is not limited to, an auto-populate user interface element, a dropdown menu, a tap-based user input, a swipe-based user input, or a tactile gesture user input through the I/O device **208**. Based on the received fourth user input, the circuitry **202** of the electronic device **102** may control the second set of features of the selected first vehicle **104A**.

(73) At **806**, a second feature control operation of the vehicle may be executed. In the second feature control operation of the vehicle, the circuitry **202** may remotely control the second set of features on the selected first vehicle **104A** based on the received fourth user input. For example, the fourth user input may correspond to an instruction to blow a horn of the first vehicle **104A** for certain time period (say for 10 seconds). Based on the vehicle identification information of the first vehicle **104A** and the received fourth user input, the circuitry **202** may query the server **108** (or the

database **110**) for information related to the instructions to blow the horn of the first vehicle **104A** for a certain time (e.g., 10 seconds). Based on the query, the circuitry **202** may receive the information (such as one or more wireless commands), related to the instructions to start the horn of the first vehicle **104A**, from the server **108** (or the database **110**). The circuitry **202** may further transmit the instructions to blow the horn of the first vehicle **104A** to the first vehicle **104A**, based on the information received from the server **108** (or the database **110**). In some embodiments, the electronic device **102** may store different instructions related to the second set of features (i.e., related to the first vehicle **104A**) in the memory **204** and may not query the server **108** (or the database **110**). In such case, the circuitry **202** may retrieve the corresponding instructions to control one of the second set of features from the memory **204**, based on the received fourth user input. The first vehicle **104A** may further blow the horn of the first vehicle **104A** on receipt of the instructions from the circuitry **202**, and thereby the circuitry **202** may remotely control the first vehicle **104A**. Post the control of the second set of features, the circuitry **202** may receive a confirmation indicative of the activation or deactivation of a feature (of the second set of features) on the first vehicle **104A**, as described, for example, at **408** in FIG. 4. Further, the circuitry **202** may control the haptic device **106** to output a haptic feedback, based on the reception of the confirmation, as described, for example, at **410** in FIG. 4. The haptic feedback may indicate that the second set of features have been controlled on the selected first vehicle **104A**.

(74) FIG. 9 is a diagram that illustrates an exemplary scenario of a user interface of the electronic device of FIG. 1 to display health status information and vehicle identification information, in accordance with an embodiment of the disclosure. FIG. 9 is explained in conjunction with elements from FIGS. 1, 2, 3, 4A, 4B, 5, 6, 7, and 8. With reference to FIG. 9 there is shown an exemplary scenario of a user interface (UI) **900**. The UI **900** may include a set of UI elements including a first UI element **902** and a second UI element **904**. The circuitry **202** may be configured to control the display device **208A** of the electronic device **102** to display the UI **900** including the set of UI elements. A set of operations associated with the exemplary scenario is described herein.

(75) In an embodiment, the circuitry **202** may be configured to receive the vehicle identification information associated with each of the set of vehicles **104** associated with (such as owned or used by) the user **112**. The circuitry **202** may be further configured to control a display screen (e.g., the display device **208A**) of the electronic device **102** to display the received vehicle identification information associated with each of the set of vehicles **104** or associated with the selected first vehicle **104A**. For example, the received vehicle identification information may include at least one of, but is not limited to, a vehicle name, a vehicle manufacturer, a vehicle model, a vehicle color, a year of manufacture, a vehicle chassis number, a vehicle engine number, or a vehicle registration number, associated with each of the set of vehicles **104**. The vehicle name may be a name given to the vehicle at the time of registration. The vehicle name of the vehicle may be a user-defined name of the vehicle that may be defined or changed from a settings menu (not shown) of the UI **900**. The vehicle manufacturer of the vehicle may be a name of the manufacturer of the vehicle. The vehicle model of the vehicle may be a model number associated with the vehicle. The vehicle color of the vehicle may be a body color of the vehicle such as, black, white, coral, and the like. The year of manufacture of the vehicle may be a year in which the vehicle is manufactured by the manufacturer. The vehicle registration number of the vehicle may be a unique number that may be associated with a license plate number of the vehicle. The vehicle chassis number and the vehicle engine number may be a unique number that may be associated with a chassis and an engine of the vehicle, respectively. The vehicle identification information associated with each of the set of vehicles **104** may be received as a user input from the user **112** at the time of registration of the vehicle and may be stored in the memory **204** of the electronic device **102**. The vehicle identification information of each vehicle may be also stored in the memory **306** of the respective vehicle.

(76) The circuitry **202** may retrieve the vehicle identification information of the first vehicle **104A** from the memory **204** or receive the vehicle identification information from the first vehicle **104A**,

which may store the vehicle identification information in the memory **306**. The first UI element **902** on the UI **900** may display the vehicle identification information. For example, as shown in FIG. **9**, the vehicle identification information of the selected first vehicle **104A** may be “2022 TLX”. For example, the year of manufacture may be “2022” and the vehicle model may be “TLX”. In an embodiment, the circuitry **202** may be further configured to receive from the selected first vehicle **104A**, health status information associated with the selected first vehicle **104A** based on the received first user input. The circuitry **202** may transmit one or more requests to the electronic control device **304** of the first vehicle **104A** to provide the health status information. In some embodiments, the electronic control device **304** may capture the health status information of the first vehicle **104A** from the plurality of sensors associated with the first vehicle **104A**. In an embodiment, the health status information may include time-stamp information that may indicate real-time date and time of the capture of vehicle-related data from the plurality of sensors. The circuitry **202** may be further configured to control a display screen (e.g., the display device **208A**) of the electronic device **102** to display the received health status information (i.e., associated with the selected first vehicle **104A**) and the time-stamp information related to the last update of the health status information of the first vehicle **104A**. For example, the received health status information may include at least one of, but is not limited to, an engine parameter status, a vehicle-related alert, a tire pressure status, a vehicle range, odometer reading information, a fuel status, or an oil life, associated with the selected first vehicle **104A**. The health status information may provide information related to an operational condition of the selected first vehicle **104A** so that the user **112** may take proper actions according to the requirements of the selected first vehicle **104A**. The displayed time-stamp information (not shown) may provide the last update of the operational/health conditions of the first vehicle **104A** (for example health/condition status updated 1 hour ago or on a particular date/time). The engine parameter status may provide information related to, but is not limited to, power, torque, fuel consumption and the like of the engine. The vehicle-related alert may indicate different conditions related to the selected first vehicle **104A** that may be needed to be taken care for the selected first vehicle **104A** to function properly. The tire pressure status may provide information related to a pressure of the tires of the selected first vehicle **104A**. For example, a message ‘ok’ may be provided under tire pressure status on the display device **208A** to denote that the tire pressure of all the tires of the selected first vehicle **104A** is within recommended pressure values. In another example, a value of the tire pressure may be provided to indicate the tire pressure status. The odometer reading information may provide a total already distance covered by the selected first vehicle **104A**. For example, 5000 Kilometers may be displayed under the odometer reading information in case the first vehicle **104A** has covered a total of 5000 Km distance since purchase. The fuel status may indicate information related to the fuel left in a fuel tank of the selected first vehicle **104A**. The oil life may denote a quality/quantity of the oil present in the engine and may be provided in a percentage.

(77) In an embodiment, the fuel status may indicate at least one of, but is not limited to, an amount of fuel left in the selected first vehicle **104A**, a time duration for which an engine (e.g., the engine **308**) of the selected first vehicle **104A** is on, or a distance that can be covered by the selected first vehicle **104A** based on the amount of fuel left in the selected first vehicle **104A**. The amount of fuel left in the fuel tank of the selected first vehicle **104A** may be indicated in liters that may be depicted on the UI **900**. In some cases, instead of displaying a value of the exact amount of fuel left, a graphical representation of the amount of fuel left (for e.g., in the form of bars, pie charts, and the like) may be displayed. The time duration for which the engine **308** of the selected first vehicle **104A** may be on (with the amount of fuel left in the selected first vehicle **104A**) may be also displayed in the UI **900**. Further, the distance that may be covered by the selected first vehicle **104A** based on the amount of fuel left may be also displayed in the UI **900**.

(78) In an embodiment, the vehicle-related alert may include one or more recommendations for the selected first vehicle **104A**. For example, the one or more recommendations may be associated with

an operation and maintenance of the selected first vehicle **104A**. The vehicle-related alerts may indicate different conditions related to the selected first vehicle **104A** that may need to be taken care for the selected first vehicle **104A** to function smoothly. The one or more recommendations associated with the operation and maintenance of the selected first vehicle may be corrective recommendations, preventive recommendations, risk-based or condition-based recommendations. (79) For example, as shown in the UI **900**, the health status information associated with the selected first vehicle **104A** may be displayed in the second UI element **904**. The second UI element **904** may include a UI element **904A** to display the fuel status. For example, the fuel status may be indicative of the amount of fuel left in the selected first vehicle **104A**. The UI element **904A** may also provide a distance (e.g., 48 miles) that may be traversed by the selected first vehicle **104A** with the amount of the fuel left in the selected first vehicle **104A**. The second UI element **904** may further include a UI element **904B** to display information related to the oil life of the selected first vehicle **104A**. For example, the information related to the oil life may indicate a 95 percent oil life of the first vehicle **104A**. The information related to the oil life may be also provided graphically as bar charts, pie charts, and the like. The second UI element **904** may further include a UI element **904C** to display information related to the vehicle-related alerts of the selected first vehicle **104A**. For example, the information related to the vehicle-related alerts may indicate a message such as, “Brake Service Due” for selected first vehicle **104A**. Based on such vehicle-related alert, the user **112** may book for servicing or repair of the brakes of the first vehicle **104A**.

(80) In an embodiment, the circuitry **202** may be further configured to control the display device **208A** to render information about a walk back and time alert feature to the user **112**. Such feature may determine current location of the electronic device **102** (or the user **112**) and provide a path to the selected first vehicle **104A** (for example when the user **112** wants to reach to the vehicle parked at a parking location). The walk back and time alert feature may be also provided for electric vehicles. For example, when an electric vehicle of the user **112** is being charged, the circuitry **202** may control the display device **208A** to display a notification to the user **112**, that may indicate that the user **112** should walk back to the electric vehicle in case the vehicle is about to be fully charged. Such notification may prevent the user **112** from overpaying for charging of the electric vehicle. For example, charging of electric vehicles for certain time duration may be free, for example, for 6 minutes. However, if the electric vehicle is still plugged beyond the particular time duration (e.g., 6 minutes), the user **112** may have to pay for the additional charging time. An example of such notification may include a message, such as, ‘you are 8 minutes away and your vehicle will be charged in 8 minutes, so please start walking back towards your vehicle’. The electronic device **102** may also guide the user **112** back to the selected first vehicle **104A**, based on a display of a path from the current location of the user **112** to the first vehicle **104A**.

(81) FIG. **10A** is a diagram that illustrates an exemplary scenario of a first user interface of the electronic device of FIG. **1** to control features of the selected first vehicle, in accordance with an embodiment of the disclosure. FIG. **10A** is explained in conjunction with elements from FIGS. **1**, **2**, **3**, **4A**, **4B**, **5**, **6**, **7**, **8**, and **9**. With reference to FIG. **10A** there is shown an exemplary scenario of a first user interface (UI) **1000A**. The first UI **1000A** may include a set of UI elements including a first UI element **1002A**, a second UI element **1004A**, a third UI element **1006A**, a fourth UI element **1008A**, a fifth UI element **1010A**, a sixth UI element **1012A**, and a seventh UI element **1014A**. The circuitry **202** may be configured to control the display device **208A** of the electronic device **102** to display the first UI **1000A** including the set of UI elements. A set of operations associated with the exemplary scenario is described herein.

(82) In an embodiment, the circuitry **202** may be configured to control a display screen (e.g., the display device **208A**) associated with the electronic device **102** to display a first user interface (e.g., the first UI **1000A**) indicating first information about the first set of features and/or the health status information of the selected first vehicle **104A**. For example, the first UI **1000A** may include the first UI element **1002A** that may display an image or icon of the selected first vehicle **104A**. The

first UI **1000A** may further include the second UI element **1004A** that may display the vehicle identification information associated with the first vehicle **104A**. For example, as shown in FIG. **10A**, the second UI element **1004A** may display a vehicle model (e.g., “TLX”) and a year of manufacture (e.g., “2022”) of the first vehicle **104A**. In some embodiments, the vehicle identification information may be displayed on the first UI **1000A** in a particular color corresponding to the vehicle color of the first vehicle **104A**. The first UI **1000A** may further include the third UI element **1006A** that may display the health status information associated with the first vehicle **104A**. For example, the health status information may include a fuel status (e.g., a range of “48 miles”), an oil life (e.g., “95% oil life”), and a vehicle-related alert (e.g., a message such as, “Brake Service Due”) associated with the first vehicle **104A** as described, for example, in FIG. **9**. The first UI **1000A** may further include the fourth UI element **1008A** that may display information related to the first set of features controlled for the first vehicle **104A**. Such information may correspond to the first information about the first set of features controlled on the first vehicle **104A**. For example, the fourth UI element **1008A** may display an operation status of the engine **308** of the first vehicle **104A** (i.e., controlled by the electronic device **102**), such as, a message indicating “Engine Started” to denote that the engine **308** of the first vehicle **104A** is on. The first UI **1000A** may further include the fifth UI element **1010A** and the sixth UI element **1012A** that, once selected by the user **112**, may be used to navigate to other user interfaces (of the display device **208A**) related to other vehicles in the set of vehicles **104**. The first UI **1000A** may further include the seventh UI element **1014A** that, once selected by the user **112**, may be used to view secondary or additional data related to the first information. The secondary data may be the data included in the first information that may not be displayed on the display device **208A** due to size constraint of the display device **208A**. It may be noted that instead of the fifth UI element **1010A**, the sixth UI element **1012A**, and the seventh UI element **1014A**, user input modes such as, a swipe user input mode, a tactile gesture user input mode, or a tap user input mode may be also provided for the same purpose of switching the user interfaces (related to different vehicles) on the display device **208A**. It should be noted that the first UI **1000A** of FIG. **10A** is for exemplary purpose and should not be construed to limit the scope of the disclosure.

(83) In the exemplary scenario, the first set of features of the selected first vehicle **104A** may be controlled based on a receipt of the second user input via the first UI **1000A**. The control of the first set of features of the selected first vehicle **104A** is described further, for example, in FIGS. **4A** and **4B**. In certain cases, more than one vehicle may be associated with user **112** (such as the user **112** owns and controls multiple vehicles). In some cases, the electronic device **102** may be used to remotely control more than one vehicle at a time based on a set of user inputs received from the user **112**. For example, the user **112** may wish to control the first vehicle **104A** and a second vehicle **104B**, which is different from the first vehicle **104A**. In such cases, the circuitry **202** may receive the second user input through the first UI **1000A** to control the first set of features on the first vehicle **104A**, as described in the aforementioned (for example in FIGS. **4A** and **4B**). The circuitry **202** may be further configured to receive a third user input to display second information about a first set of features controlled on a second vehicle (e.g., the second vehicle **104B**) of the set of vehicles **104**. Based on the received third user input, the circuitry **202** may be further configured to control the display screen (e.g., the display device **208A**) to display, via a second user interface (e.g., a second UI **1000B** of FIG. **10B**), the second information of the second vehicle **104B** and at least one of an icon or a highlighted portion, which notifies the user **112** about the first information indicated on the first UI **1000A** or about the controlled first set of features of the first vehicle **104A**. The first information may provide data related to the first set of features which may be controlled for the first vehicle **104A**. The second information may provide data related to the first set of features which may be controlled for the second vehicle **104B**.

(84) FIG. **10B** is a diagram that illustrates an exemplary scenario of a second user interface of the electronic device of FIG. **1** to control features of a second vehicle, in accordance with an

embodiment of the disclosure. FIG. 10B is explained in conjunction with elements from FIGS. 1, 2, 3, 4A, 4B, 5, 6, 7, 8, 9, and 10A. With reference to FIG. 10B, there is shown an exemplary scenario of a second user interface (UI) **1000B**. The second UI **1000B** may include a set of UI elements including a first UI element **1002B**, a second UI element **1004B**, a third UI element **1006B**, a fourth UI element **1008B**, a fifth UI element **1010B**, a sixth UI element **1012B**, a seventh UI element **1014B**, an eighth UI element **1016**, and a ninth UI element **1018**. The circuitry **202** may be configured to control the display device **208A** of the electronic device **102** to display the second UI **1000B** including the set of UI elements. A set of operations associated with the exemplary scenario is described herein.

(85) It may be noted that the second UI **1000B** may be displayed on the display device **208A** when the sixth UI element **1012A** is selected on the first UI **1000A**. The second UI **1000B** may display the second information related to the second vehicle **104B**. For example, the second UI **1000B** may include the first UI element **1002B** that may display an image or icon of the second vehicle **104B**. The second UI **1000B** may further include the second UI element **1004B** that may display the vehicle identification information of the second vehicle **104B**. For example, as shown in FIG. 10B, the second UI element **1004B** may display a vehicle model (e.g., “RDX”) and a year of manufacture (e.g., “2019”) of the second vehicle **104B**. In some embodiments, the vehicle identification information may be displayed on the second UI **1000B** in a particular color corresponding to the vehicle color of the second vehicle **104B**. The second UI **1000B** may further include the third UI element **1006B** that may display the health status information associated with the second vehicle **104B**. For example, the health status information may include a fuel status (e.g., a range of “210 miles”), an oil life (e.g., “90% oil life”), and a vehicle-related alert (e.g., NIL in case of no vehicle-related alerts) associated with the second vehicle **104B**. The second UI **1000B** may further include the fourth UI element **1008A** that may display information related to the first set of features controlled for the second vehicle **104B**. Such information may correspond to the second information about the first set of features controlled on the second vehicle **104B**. For example, the fourth UI element **1008B** may display an operation status of an HVAC system that may be remotely controlled for the second vehicle **104B**, such as, a message indicating ‘HVAC Started’ to denote that the HVAC of the second vehicle **104B** is on. The second UI **1000B** may further include the fifth UI element **1010B** and the sixth UI element **1012B** that may have functionalities (i.e., to navigate between user interfaces (UIs) related to different vehicles) that may be similar to functionalities of the fifth UI element **1010A** and the sixth UI element **1012A**, described in FIG. 10A. The second UI **1000B** may further include the seventh UI element **1014B** that may be similar to the seventh UI element **1014A** in FIG. 10A and may be used to view secondary/additional data related to the second information for the second vehicle **104B**. It may be noted that instead of the fifth UI element **1010B**, the sixth UI element **1012B**, and the seventh UI element **1014B**, user input modes such as, a swipe user input mode, a tactile gesture user input mode, or a tap user input mode may be also provided for the same purpose of switching the user interfaces (related to different vehicles) on the display device **208A**.

(86) The second UI **1000B** may further include the eighth UI element **1016** that may indicate the icon to notify the user **112** about the first information indicated on the first UI **1000A** or about the first set of features currently controlled for the first vehicle **104A**. For example, the eighth UI element **1016** may notify to the user **112** that a vehicle-related alert (or health status information) is present for the first vehicle **104A** on the first UI **1000A** and/or notify the user **112** about the ‘Engine Started’ operation controlled for the first vehicle **104A** at the same time. In an embodiment, the display device **208A** may include the ninth UI element **1018** that may be the highlighted portion that may indicate the first information related to the controlled first set of features of the first vehicle **104A**. For example, the ninth UI element **1018** may notify to the user **112** about the vehicle-related alert (i.e., “Break Service Due”) and/or that the engine **308** of the first vehicle **104A** is on. In an embodiment, the highlighted portion may be of a color similar to the vehicle color of

the first vehicle **104A** to indicate about the first vehicle **104A**. Similarly, if the user **112** has three vehicles and the first set of features on the first vehicle **104A** and a third vehicle are being controlled remotely at same time, then the second UI **1000B** may further include a tenth UI element (such as another icon, not shown) and/or an eleventh UI element (such as another highlighted portion, not shown) to provide notification to the user **112** about the third controlled vehicle, similar to the eighth UI element **1016** and the ninth UI element **1018**, respectively used to provide notification about the first vehicle **104A**. For example, the tenth UI element may indicate information about the vehicle-related alerts or health status information present for the third vehicle in a third UI associated with the third vehicle. The eleventh UI element may further indicate information related to the controlled first set of features of the third vehicle and may be of a color similar to the vehicle color of the third vehicle.

(87) Based on such real-time notifications provided to the user **112** about the first set of features being controlled for another vehicle (e.g., the first vehicle **104A**) and/or about the vehicle-alerts (or health status information) related to the other vehicle (e.g., the first vehicle **104A**) shown on another user interface (such as the first UI **1000A**), while a different UI (i.e., second UI **1000B**) related to different vehicle (i.e. second vehicle **104B**) is rendered, the user **112** may be made aware that the other vehicle (e.g., the first vehicle **104A**) needs appropriate attention of the user **112** as well at the same time. This may enhance the user experience of the user **112** and also provide timely notifications to the user **112**, which may result in cost savings for the user **112** and effective handling and maintenance in the long run for different remotely controlled vehicles by the disclosed electronic device **102**. In an embodiment, the circuitry **202** may control the display device **208A** to render at least one of the eighth and tenth UI elements or the ninth and eleventh UI elements, to provide the notification to the user **112** about the information currently rendered on different user interfaces (UI) related to different vehicles.

(88) In an embodiment, the circuitry **202** may be further configured to receive a fourth user input, via the second UI **1000B**, to select one feature of the first set of features for the second vehicle **104B**. The circuitry **202** may be further configured to control the selected one feature of the first set of features on the second vehicle **104B** based on the fourth user input, received via the second UI. The fourth user input may be received in a way similar to the second user input, as described, for example, at **404** in FIG. **4A**. The circuitry **202** may further select the feature to be remotely controlled from the first set of features of the second vehicle **104B**, based on the fourth user input of the user **112**, received through the second UI **1000B**. In an embodiment, the fourth user input may include a tactile gesture similar to the tactile gesture described, for example, at **404** in FIG. **4A**. Based on the received fourth input including the tactile gesture, the circuitry **202** may control the selected feature of the second vehicle **104B**. For example, through the second UI **1000B**, the user **112** may select the air-conditioning (i.e., the HVAC) system control feature and may provide a tactile gesture including a first swipe input in the first direction **116A** and a second swipe input in the second direction **116B** that may be, for example, perpendicular to the first direction **116A** on the second UI **1000B** described, for example, at **404** in FIG. **4A**. Based on the fourth user input including the tactile gesture, the circuitry **202** may switch on the HVAC (or any device such as engine, door, window, luggage compartment, or infotainment device) of the second vehicle **104B**.

(89) FIG. **11** is a flowchart that illustrates exemplary operations to control features of a vehicle, in accordance with an embodiment of the disclosure. With reference to FIG. **11**, there is shown a flowchart **1100**. The flowchart **1100** is described in conjunction with FIGS. **1**, **2**, **3**, **4A**, **4B**, **5**, **6**, **7**, **8**, **9**, **10A**, and **10B**. The operations from **1102** to **1108** may be implemented, for example, by the circuitry **202** of the electronic device **102** of FIG. **2**. The operations of the flowchart **1100** may start at **1102** and proceed to **1104**.

(90) At **1104**, the first user input indicative of the selection of the first vehicle **104A** from the set of vehicles **104** associated with the user **112**, may be received. For example, the set of vehicles **104** may be vehicles owned and/or operated by the user **112**. In an embodiment, the circuitry **202** may

be configured to receive the first user input indicative of the selection of the first vehicle **104A** from the set of vehicles **104**. Details related to the reception of the first user input are provided, for example, in FIG. **4A** (at **402**).

(91) At **1106**, the second user input including the tactile gesture may be received via the haptic device **106** associated with the electronic device **102**. For example, the second user input may be indicative of the instruction to remotely control the first set of features on the selected first vehicle **104A**. The tactile gesture may include the first swipe input along the first direction **116A** associated with the haptic device **106** and may include the second swipe input along the second direction **116B**, for example, perpendicular to the first direction **116A**. In an embodiment, the circuitry **202** may be configured to receive the second user input including the tactile gesture, via the haptic device **106** associated with the electronic device **102**. The second user input may be provided once a feature, which is to be controlled is selected from the first set of features. For example, the tactile gesture may be in swipe-input shape configurations such as, an L-shaped swipe configuration, a vertically inverted L-shaped swipe configuration, a horizontally inverted L-shaped swipe configuration, a T-shaped swipe configuration, or an inverted T-shaped swipe configuration. Details related to the reception of the second user input are provided, for example, in FIG. **4A** (at **404**).

(92) At **1108**, the first set of features may be controlled on the selected first vehicle **104A** based on the received second user input. In an embodiment, the circuitry **202** may be configured to control the first set of features on the selected first vehicle **104A** based on the second user input including the tactile gesture. For example, the circuitry **202** may transmit the instructions (i.e., associated with the control of the first set of features) to the electronic control device **304** of the selected first vehicle **104A**. The instructions may be transmitted, so that the selected first vehicle **104A** may perform one or more operations needed to control the selected feature on the selected first vehicle **104A**. For example, the engine **308** of the selected first vehicle **104A** may be turned on based on the second user input. Details related to the control of the first set of features on the selected first vehicle **104A** are provided, for example, in FIG. **4A** (at **406**). Control may pass to end.

(93) Although the flowchart **1100** is illustrated as discrete operations, such as **1104**, **1106**, and **1108** the disclosure is not so limited. Accordingly, in certain embodiments, such discrete operations may be further divided into additional operations, combined into fewer operations, or eliminated, depending on the particular implementation without detracting from the essence of the disclosed embodiments.

(94) Various embodiments of the disclosure may provide a non-transitory, computer-readable medium and/or storage medium, and/or a non-transitory machine readable medium and/or storage medium stored thereon, a set of instructions executable by a machine and/or a computer (such as, the electronic device **102**) to control a first set of features on a selected first vehicle remotely. The instructions may cause the machine and/or computer (for example, the electronic device **102**) to perform operations that include reception of the first user input indicative of the selection of the first vehicle **104A** from the set of vehicles **104** associated with the user **112**. The operations may further include reception of the second user input including the tactile gesture via the haptic device **106** associated with the electronic device **102**. For example, second user input may be indicative of the instruction to remotely control the first set of features on the selected first vehicle **104A**. The tactile gesture may include the first swipe input along the first direction **116A** associated with the haptic device **106** and may include the second swipe input along the second direction **116B** that may be perpendicular to the first direction **116A**. The operations may further include control of the first set of features on the selected first vehicle **104A** based on the received second user input.

(95) The present disclosure may be realized in hardware, or a combination of hardware and software. The present disclosure may be realized in a centralized fashion, in at least one computer system, or in a distributed fashion, where different elements may be spread across several interconnected computer systems. A computer system or other apparatus adapted for carrying out the methods described herein may be suited. A combination of hardware and software may be a

general-purpose computer system with a computer program that, when loaded and executed, may control the computer system such that it carries out the methods described herein. The present disclosure may be realized in hardware that includes a portion of an integrated circuit that also performs other functions. It may be understood that, depending on the embodiment, some of the steps described above may be eliminated, while other additional steps may be added, and the sequence of steps may be changed.

(96) The present disclosure may also be embedded in a computer program product, which includes all the features that enable the implementation of the methods described herein, and which when loaded in a computer system is able to carry out these methods. Computer program, in the present context, means any expression, in any language, code or notation, of a set of instructions intended to cause a system with an information processing capability to perform a particular function either directly, or after either or both of the following: a) conversion to another language, code or notation; b) reproduction in a different material form. While the present disclosure has been described with reference to certain embodiments, it will be understood by those skilled in the art that various changes may be made, and equivalents may be substituted without departing from the scope of the present disclosure. In addition, many modifications may be made to adapt a particular situation or material to the teachings of the present disclosure without departing from its scope. Therefore, it is intended that the present disclosure not be limited to the particular embodiment disclosed, but that the present disclosure will include all embodiments that fall within the scope of the appended claims.

Claims

1. An electronic device, comprising: circuitry configured to: receive a first user input indicative of a selection of a first vehicle from a set of vehicles associated with a user; receive, via a haptic device associated with the electronic device, a second user input including a tactile gesture, wherein the second user input is indicative of an instruction to remotely control a first set of features on the selected first vehicle, and the tactile gesture includes a first swipe input along a first direction associated with the haptic device and includes a second swipe input along a second direction perpendicular to the first direction; control the first set of features on the selected first vehicle based on the received second user input; control a display screen associated with the electronic device to display a first user interface (UI) indicating first information about the first set of features of the selected first vehicle, wherein the first set of features of the first vehicle are controlled based on a receipt of the second user input via the first UI; receive a third user input to display second information about a first set of features controlled on a second vehicle of the set of vehicles, wherein the second vehicle is different from the first vehicle; and control, based on the received third user input, the display screen to display a second user interface (UI) indicating the second information about the first set of features of the second vehicle and at least a highlighted portion which notifies the user about the controlled first set of features of the first vehicle.
2. The electronic device according to claim 1, wherein the circuitry is further configured to: receive, from the selected first vehicle, a confirmation indicative of the control of the first set of features on the selected first vehicle, based on the received second user input; and control the haptic device associated with the electronic device to output a haptic feedback, based on the received confirmation.
3. The electronic device according to claim 1, wherein the first set of features of the selected first vehicle correspond to at least one of: an engine control feature, a door control feature, or a window control feature, a luggage compartment control feature, an infotainment control feature, or a heating ventilation and air-conditioning (HVAC) system control feature, associated with the selected first vehicle.
4. The electronic device according to claim 1, wherein the circuitry is further configured to: receive

a fourth user input indicative of a time duration after which a started engine of the selected first vehicle is to be stopped; and control the selected first vehicle to stop the started engine of the selected first vehicle, based on the received fourth user input.

5. The electronic device according to claim 1, wherein the circuitry is further configured to: receive a fourth user input indicative of a time duration after which a stopped engine of the selected first vehicle is to be started; and control the selected first vehicle to start the stopped engine of the selected first vehicle, based on the received fourth user input.

6. The electronic device according to claim 1, wherein the circuitry is further configured to: receive a fourth user input indicative of a time duration after which a stopped HVAC system of the selected first vehicle is to be started; and control the selected first vehicle to start the stopped HVAC system of the selected first vehicle, based on the received fourth user input.

7. The electronic device according to claim 1, wherein the electronic device is a user wearable device.

8. The electronic device according to claim 1, wherein the circuitry is further configured to: receive a fourth user input indicative of an instruction to remotely control a second set of features on the selected first vehicle, wherein the second set of features correspond to at least one of: a head light control feature, a wiper control feature, a sunroof control feature, seat temperature control feature, or a horn control feature associated with the selected first vehicle; and control the second set of features on the selected first vehicle based on the received fourth user input.

9. The electronic device according to claim 1, wherein the circuitry is further configured to: receive, from the selected first vehicle, health status information associated with the selected first vehicle based on the received first user input; and control a display screen of the electronic device to display the received health status information associated with the selected first vehicle, wherein the received health status information includes at least one of: an engine parameter status, a vehicle-related alert, a tire pressure status, a vehicle range, odometer reading information, a fuel status, or an oil life, associated with the selected first vehicle.

10. The electronic device according to claim 9, wherein the vehicle-related alert includes one or more recommendations for the selected first vehicle, and wherein the one or more recommendations are associated with an operation and maintenance of the selected first vehicle.

11. The electronic device according to claim 9, wherein the fuel status indicates at least one of: an amount of fuel left in the selected first vehicle, a time duration for which an engine of the selected first vehicle is on, or a distance that can be covered by the selected first vehicle based on the amount of fuel left in the selected first vehicle.

12. The electronic device according to claim 1, wherein the circuitry is further configured to: receive vehicle identification information associated with each of the set of vehicles associated with the user; and control a display screen of the electronic device to display the received vehicle identification information associated with each of the set of vehicles, wherein the received vehicle identification information includes at least one of: a vehicle name, a vehicle manufacturer, a vehicle model, a vehicle color, a year of manufacture, or a vehicle registration number, associated with each of the set of vehicles.

13. The electronic device according to claim 1, wherein the circuitry is further configured to: receive a fourth user input, via the second UI, to select one feature of the first set of features for the second vehicle; and control the selected one feature of the first set of features on the second vehicle based on the fourth user input, received via the second UI.

14. A method, comprising: in an electronic device: receiving a first user input indicative of a selection of a first vehicle from a set of vehicles associated with a user; receiving, via a haptic device associated with the electronic device, a second user input including a tactile gesture, wherein the second user input is indicative of an instruction to remotely control a first set of features on the selected first vehicle, and the tactile gesture includes a first swipe input along a first direction associated with the haptic device and includes a second swipe input along a second

direction perpendicular to the first direction; and controlling the first set of features on the selected first vehicle based on the received second user input; controlling a display screen associated with the electronic device to display a first user interface (UI) indicating first information about the first set of features of the selected first vehicle, wherein the first set of features of the first vehicle are controlled based on a receipt of the second user input via the first UI; receiving a third user input to display second information about a first set of features controlled on a second vehicle of the set of vehicles, wherein the second vehicle is different from the first vehicle; and controlling, based on the received third user input, the display screen to display a second user interface (UI) indicating the second information about the first set of features of the second vehicle and at least a highlighted portion which notifies the user about the controlled first set of features of the first vehicle.

15. The method according to claim 14, wherein the first set of features of the selected first vehicle correspond to at least one of: an engine control feature, a door control feature, or a window control feature, a luggage compartment control feature, an infotainment control feature, or a heating ventilation and air-conditioning (HVAC) system control feature, associated with the selected first vehicle.

16. The method according to claim 14, further comprising: receiving, from the selected first vehicle, a confirmation indicative of the control of the first set of features on the selected first vehicle, based on the received second user input; and controlling the haptic device associated with the electronic device to output a haptic feedback, based on the received confirmation.

17. An electronic device, comprising: circuitry configured to: receive a first user input indicative of a selection of a first vehicle from a set of vehicles associated with a user; control a display screen associated with the electronic device to display a first user interface (UI) indicating first information about a first set of features of the selected first vehicle; receive a second user input, via the first UI, to remotely control the first set of features of the selected first vehicle; receive a third user input to display second information about a first set of features controlled on a second vehicle of the set of vehicles, wherein the second vehicle is different from the first vehicle; and control, based on the received third user input, the display screen to display a second user interface (UI) different from the first UI, indicating the second information about the first set of features of the second vehicle and at least a highlighted portion which notifies the user about the controlled first set of features of the first vehicle.

18. The electronic device according to claim 17, wherein the circuitry is further configured to: receive a fourth user input, via the second UI, to select one feature of the first set of features for the second vehicle; and control the selected one feature of the first set of features on the second vehicle based on the fourth user input, received via the second UI.

19. The electronic device according to claim 17, wherein the first set of features correspond to at least one of: an engine control feature, a door control feature, or a window control feature, a luggage compartment control feature, an infotainment control feature, or a heating ventilation and air-conditioning (HVAC) system control feature, associated with the selected first vehicle.
