

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12409977
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Zhang; Man

Childproof containing bag

Abstract

A childproof containing bag is provided, which includes a main bag body, a first sealing strip, and a second sealing assembly. The first and second bag bodies are in an open state, and the first and second bag bodies are enclosed to form a containing space. The first sealing strip and the second sealing assembly are both arranged in the containing space. The second sealing strip and the first sealing strip are detachably sealed and connected. When the second sealing strip is sealed and connected to the first sealing strip, the sealing area between the second sealing strip and the first sealing strip separates the containing space into a first containing area and a second containing area. Children are unable to open the second and first sealing strips by pulling on the second bag body and the first bag body.

Inventors:	Zhang; Man (Dongguan, CN)
Applicant:	TedPack Company Limited (Dongguan, CN)
Family ID:	87610216
Assignee:	TedPack Company Limited (Dongguan, CN)
Appl. No.:	18/451041
Filed:	August 16, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20250019125 A1	Jan. 16, 2025

Foreign Application Priority Data

CN	202310864867.0	Jul. 14, 2023
----	----------------	---------------

Publication Classification

Int. Cl.: B65D33/25 (20060101)

U.S. Cl.:

CPC B65D33/25 (20130101); B65D2215/06 (20130101)

Field of Classification Search

CPC: B65D (33/25); B65D (2215/06)

USPC: 383/63; 383/9; 383/203

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5100000	12/1991	Huseman	383/65	B65D 33/2508
10005592	12/2017	Takigawa	N/A	B65D 33/2566
11305917	12/2021	Aryanpanah	N/A	B65D 33/2566
11718456	12/2022	Shen	383/35	B65D 33/2508
11932454	12/2023	Aryanpanah	N/A	B65D 33/2558
2008/0226203	12/2007	Dais	383/63	B65D 33/2541
2018/0118414	12/2017	Martial	N/A	B65D 33/255
2021/0114777	12/2020	Lee	N/A	B65D 33/2541
2023/0036651	12/2022	Jiang	N/A	A44B 17/0058
2023/0150731	12/2022	Plourde	383/63	B65B 69/0008

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
206580034	12/2016	CN	N/A
207434097	12/2017	CN	N/A
209441923	12/2018	CN	N/A
3090593	12/2019	FR	B65D 33/2508

OTHER PUBLICATIONS

Machine translation CN-206580034-U. (Year: 2017). cited by examiner

Primary Examiner: Pascua; Jes F

Background/Summary

TECHNICAL FIELD

(1) This application relates to the technical field of containing bags, in particular to the application of a childproof containing bag.

BACKGROUND

(2) With the development of technology, containing bags are applied in people's daily lives to contain solid or powdery objects. The containing bags include a first bag body and a second bag body, which are connected to each other and contain objects through the connection of the first and

second bag bodies. In existing technology, the first and second bag bodies are sealed by sealing strips, the first and second bag bodies in a sealed state to store objects, and the containing bag is placed in various places when storing objects, such as coffee tables, sofas, etc. In scenes with children, children sometimes may take the containing bag and pull on the first and second bag bodies through their hands, and the first and second bag bodies are easy to open under the pull of children's hands, causing the existing containing bag to be easily opened by children.

SUMMARY

(3) The objective of the present application is to provide a childproof containing bag applied to solve the problems mentioned in the background.

(4) To achieve the above objective, the present application provides the following technical solution:

(5) A childproof containing bag, including: a main bag body, comprising a first bag body and a second bag body connected to each other, wherein the first bag body and the second bag body are enclosed to form a containing space, and the containing space is provided with a first opening; a first sealing strip connected to the first bag body, wherein the first sealing strip is located at an opposite position between the first bag body and the second bag body, and is arranged in the containing space; a second sealing assembly connected to the second bag body and embedded in the containing space, wherein the second sealing assembly comprises a third bag body and a second sealing strip, the third bag body is located in the containing space, the third bag body is connected to the second bag body, the second sealing strip is connected to the third bag body and arranged corresponding to the first sealing strip, and the second sealing strip is detachably sealed and connected to the first sealing strip; when the second sealing strip is sealed and connected to the first sealing strip, a sealing area between the second sealing strip and the first sealing strip separates the containing space into a first containing area and a second containing area; the first containing area is used to accommodate solid or powdery objects, and to seal and preserve the solid or powdery objects; the second containing area is used to accommodate hands of non child characters that extend through the first opening.

(6) Optionally, the first bag body and the second bag body are in an open state, the third bag body is placed in the containing space, the second sealing strip detaches from the first sealing strip as the third bag body is moved; a top of the third bag body does not exceed a top of the second bag body or a top of the first bag body; the third bag body is provided with a pulling part, wherein the pulling part is located on one side of the second sealing strip and faces the first opening of the containing space, and the pulling part is used for pulling the hands of the non child characters; when the pulling part is pulled by the hands of the non child characters, the third bag body and the first bag body are moved in an opposite direction, and the second sealing strip detaches from the first sealing strip as the third bag body is moved.

(7) Optionally, the second bag body and the first bag body are moved in the opposite direction when the second bag body is pulled by hands of children, and the second bag body and the third bag body gradually open, while the second sealing strip and the first sealing strip in the third bag body are still in a sealed connection.

(8) Optionally, there is a safety distance between a top of the pulling part and the top of the second bag body, so that hands of children are unable to touch the pulling part; and the safety distance is greater than a distance grasped by thumbs of the children.

(9) Optionally, a surface roughness of the pulling part is inconsistent with an inner surface roughness of the second bag body, and the surface roughness of the pulling part is greater than the inner surface roughness of the second bag body.

(10) Optionally, the surface of the pulling part is provided with a friction layer, and the friction layer is configured for contact by the hands of the non child characters.

(11) Optionally, the friction layer is provided with a plurality of arc-shaped bump regions, the plurality of the arc-shaped bump regions are arranged at intervals along a length direction of the

friction layer, each of the plurality of the arc-shaped bump regions is provided with a plurality of bumps, and the plurality of bumps are arranged in concentric circles.

(12) Optionally, the pulling part is provided with a gap, the gap is located in a middle of the pulling part and guides the hands of non child characters to pass through, so as to guide the hands of non child characters to contact the pulling part; and the gap is an arc-shaped groove or an irregular groove.

(13) Optionally, an inner surface of the second bag body is provided with a second guide edge, the second guide edge extends along a length direction of the second bag body to a top of the pulling part and guides the hands of non child characters to contact the pulling part; an inner surface of the first bag body is provided with a first guide edge, the first guide edge extends along a length direction of the first bag body to the first sealing strip, and the first guide edge is arranged opposite to the second guide edge.

(14) Optionally, the first sealing strip extends along a width direction of the first bag body; a first reinforcement strip is arranged between the first bag body and the first sealing strip, and the first reinforcement strip is arranged corresponding to the connection between the first bag body and the first sealing strip to reinforce the connection between the first bag body and the first sealing strip.

(15) Optionally, the third bag body is movably connected to the second bag body, one end of the third bag body is connected to the second bag body, and the other end of the third bag body is detached from the second bag body, so that there is a motion space between the third bag body and the second bag body; an inner surface of the second bag body is connected with a masking sheet, the masking sheet faces the other end of the third bag body; and the masking sheet is movably connected to the inner surface of the second bag body and shelters or detaches from the other end of the third bag body.

(16) Optionally, one end of the masking sheet is connected to the inner surface of the second bag body, and an elastic member is connected between the masking sheet and the second bag body; two ends of the elastic member are respectively connected to the masking sheet and the second bag body, the elastic member applies elastic force to the masking sheet, and the masking sheet contacts with the other end of the third bag body under the elastic force of the elastic member, so that the third bag body is against the second bag body.

(17) Optionally, a second reinforcement strip is arranged between the third bag body and the second bag body, the second reinforcement strip is arranged corresponding to the connection between the third bag body and the second bag body, to reinforce the connection between the third bag body and the second bag body.

(18) Optionally, one of the first sealing strip and the second sealing strip is provided with a first snap part, the other is provided with a second snap part, and the first snap part is provided with an elliptical snap hook; the second snap part is provided with an elliptical snap groove; and the snap hook is located in the snap groove and mutually snapped when the second snap part and the first snap part are detachably snapped and connected; the first snap part and the second snap part form a set of snap assembly; a plurality of the snap assemblies are arranged at intervals along a width direction of the third bag body, and the first snap part is alternately placed on the first sealing strip or the second sealing strip according to an arrangement of the plurality of the snap assemblies.

(19) Optionally, the snap hook is provided with two oblique hooks arranged symmetrically, and the two oblique hooks respectively snap at both ends of the snap groove and engage at both ends of the snap groove.

(20) Optionally, when the first snap part is in the first sealing strip and the second snap part is in the second sealing strip, the first snap part extends in a wavy manner along a length direction of the first sealing strip, and the second snap part extends in a wavy manner along a length direction of the second sealing strip.

(21) Optionally, at least one of the first bag body, the second bag body, and the third bag body is made of degradable material.

(22) Optionally, the first bag body, the second bag body, and the third bag body are all made of non degradable materials.

(23) Optionally, the first bag body is connected to the second bag body; a connection between the first bag body and the second bag body is provided with a tear opening located on one side of the main bag body and near an end of the main bag body.

(24) Optionally, the second bag body is provided with a positioning hole, the positioning hole is located at a top of the second bag body and above the third bag body; the positioning hole is a circular or irregular hole and configured for threading the positioning hook connected to the wall; when the positioning hook penetrates the positioning hole of the second bag body, the second bag body is connected to the positioning hook and suspended, and the main bag body is at a height that children are unable to reach.

(25) Compared with the prior art, the advantageous effects of the present application are as following:

(26) The present application provides a childproof containing bag, wherein the first and second bag bodies are enclosed to form a containing space, and both the first sealing strip and the second sealing assembly are arranged in the containing space; the second sealing assembly includes a third bag body and a second sealing strip, the third bag body is located in the containing space, and the third bag body is connected to the second bag body. The second sealing strip is connected to the third bag body and arranged corresponding to the first sealing strip, and the second sealing strip is detachably sealed and connected to the first sealing strip. When the second sealing strip is sealed and connected to the first sealing strip, the sealing area between the second sealing strip and the first sealing strip separates the containing space into a first containing area and a second containing area. The first containing area is used to accommodate solid or powdered objects, and seal and store solid or powdery objects, thereby achieving the sealing and storage function of a childproof containing bag, while the second containing area is used to accommodate the hands of adult that extends through the first opening. Wherein, since the first sealing strip and the second sealing assembly are both arranged in the containing space, not exposed to the first and second bag bodies, so as to prevent children from opening the third and second bag bodies when they see the bag. It is necessary to pull on the third and first bag bodies to open the second and first sealing strips, children cannot open the second and first sealing strips when pulling on the second and first bag bodies, such that the sealing and storage function of the childproof containing bag is ensured, preventing children from opening the childproof containing bag.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) In order to provide a clearer illustration of the technical solution in the embodiments of this application, a brief introduction will be given below to the accompanying drawings required in the description of the embodiments. It is apparent that the accompanying drawings in the following description are only some embodiments of the present application. For those skilled in the art, other accompanying drawings can be obtained based on these drawings without any creative labor.

(2) In order to provide a more complete understanding of this application and its advantageous effects, the following will be illustrated in conjunction with the accompanying drawings. In the following description, the same reference numerals refer to the same parts.

(3) FIG. 1 is a schematic diagram showing of the open state of a childproof containing bag provided in the first embodiment of the present application.

(4) FIG. 2 is a schematic diagram shown that the childproof containing bag in the first embodiment of the present application is opened by hands of an adult.

(5) FIG. 3 is a front view showing of the childproof containing bag provided in the first

embodiment of the present application.

(6) FIG. 4 is a cross-sectional view of the FIG. 3 which is taken along the section A.

(7) FIG. 5 is a schematic diagram shown that a child tries to open the childproof containing bag provided in the first embodiment of the present application.

(8) FIG. 6 is an enlarged partial view of the part B in FIG. 5.

(9) FIG. 7 is a schematic diagram of the pulling part of the childproof containing bag provided in the second embodiment of the present application.

(10) FIG. 8 is a schematic diagram of the friction layer of the childproof containing bag provided in the third embodiment of the present application.

(11) FIG. 9 is a schematic diagram of the arc-shaped bump region of the childproof containing bag provided in the third embodiment of the present application.

(12) FIG. 10 is a schematic diagram of the gap in the childproof containing bag provided in the third embodiment of this application.

(13) FIG. 11 is a schematic diagram of the gap provided in the third embodiment of the present application when the childproof containing bag is used by an adult.

(14) FIG. 12 is a schematic diagram of the second edge and the first guide edge of the childproof containing bag provided in the fourth embodiment of the present application.

(15) FIG. 13 is a schematic diagram of the second reinforcement strip and the first reinforcement strip of the childproof containing bag provided in the fifth embodiment of the present application.

(16) FIG. 14 is a schematic diagram of a masking sheet of the childproof containing bag provided in the sixth embodiment of the present application.

(17) FIG. 15 is a schematic diagram of the fourth bag body of the childproof containing bag provided in the seventh embodiment of the present application.

(18) FIG. 16 is a schematic diagram of the hook of the childproof containing bag provided in the seventh embodiment of this application.

REFERENCE NUMERALS IN THE ATTACHED DRAWINGS

(19) **100**—childproof containing bag, **200**—wall, **210**—positioning hook; **10**—main bag body, **10a**—containing space, **10b**—the first opening, **10c**—the first containing area, **10d**—the second containing area, **11**—the first bag body, **111**—tear opening, **112**—the first guide edge, **113**—the first reinforcement strip, **12**—the second bag body, **121**—the second guide edge, **122**—the second reinforcement strip, **123**—masking sheet, **124**—elastic member, **125**—positioning hole; **20**—the first sealing strip, **21**—the first snap part, **211**—snap hook, **212**—oblique hook; **30**—the second sealing assembly, **31**—the third bag body, **311**—pulling part, **312**—friction layer, **3121**—arc-shaped bump region, **3122**—bump, **313**—gap, **32**—the second sealing strip, **321**—the second snap part, **322**—snap groove.

DETAILED DESCRIPTION OF THE EMBODIMENTS

(20) The following will provide a clear and complete description of the technical solution in the embodiments of the present application in conjunction with the accompanying drawings. It is apparent that the described embodiments are only a part of the embodiments of this application, not all of them. Based on the embodiments in this application, all other embodiments obtained by those skilled in the art without creative labor fall within the scope in this application.

Embodiment 1

(21) Please refer to FIG. 1 to FIG. 6, the embodiments of this application provide a childproof containing bag **100**, which is suitable for use in daily life and can accommodate solid or powdered objects while preventing children from opening. In this case, the childproof containing bag **100** includes a main bag body **10**, a first sealing strip **20**, and a second sealing assembly **30**, and the first sealing strip **20** and the second sealing assembly **30** are respectively connected to the main bag body **10**.

(22) The main bag body **10** serves as the main part of the childproof containing bag **100**. The main bag body **10** includes a first bag body **11** and a second bag body **12** which are connected to each

other. In the present embodiment, the edge of the first bag body **11** and the edge of the second bag body **12** are connected by hot pressing.

(23) The first bag body **11** and the second bag body **12** are in an open state, and the first bag body **11** and the second bag body **12** are enclosed to form a containing space **10a**. The containing space **10a** has a first opening **10b**, when the childproof containing bag **100** is in a vertical direction, the first opening **10b** is at the top of the main bag body **10**.

(24) The first sealing strip **20** is connected to the first bag body **11**, and the first sealing strip **20** is located at the opposite position between the first bag body **11** and the second bag body **12** and is arranged in the containing space **10a**. In the present embodiment, the first sealing strip **20** is located within the containing space **10a**, and the first sealing strip **20** extends along the width direction of the first bag body **11**. The first sealing strip **20** is located above the middle of the second bag body **12**.

(25) The second sealing assembly **30** is connected to the second bag body **12** and is arranged in the containing space **10a**. In the present embodiment, the first sealing strip **20** and the second sealing assembly **30** are both arranged in the containing space **10a**, and are arranged corresponding to the first bag body **11** and the second bag body **12** to avoid exposure to the external environment and direct contact with children.

(26) Wherein, the second sealing assembly **30** includes a third bag body **31** and a second sealing strip **32**, the third bag body **31** is located in the containing space **10a**, and the third bag body **31** is connected to the second bag body **12**. The second sealing strip **32** is connected to the third bag body **31** and arranged corresponding to the first sealing strip **20**. The second sealing strip **32** is detachably sealed with the first sealing strip **20**, or the second sealing strip **32** detaches from the first sealing strip **20** as the third bag body **31** is moved.

(27) When the second sealing strip **32** is sealed and connected to the first sealing strip **20**, a sealing area between the second sealing strip **32** and the first sealing strip **20** separates the containing space **10a** into a first containing area **10c** and a second containing area **10d**. The first containing area **10c** is used to accommodate solid or powdery objects, and to seal and preserve the solid or powdery objects, while the second containing area **10d** is used to accommodate hands of non child characters that extend through the first opening.

(28) Wherein, since the first sealing strip **20** and the second sealing assembly **30** are both arranged in the containing space **10a** and not exposed to the first bag body **11** and the second bag body **12**, children are prevented from opening the third bag body **31** and the second bag body **12** when they see the childproof containing bag **100**. At the same time, it is necessary to pull the third bag body **31** and the first bag body **11** to open the second sealing strip **32** and the first scaling strip **20**, thus children are unable to open the second sealing strip **32** and the first sealing strip **20** while pulling on the second bag body **12** and the first bag body **11**, so as to ensure the sealing and storage function of the childproof containing bag **100** and to prevent children from opening the childproof containing bag **100**.

(29) Therefore, the sealing connection between the first sealing strip **20** and the second sealing strip **32** separates the containing space **10a**, and divides the containing space **10a** into the first containing area **10c** and the second containing area **10d**. The first containing area **10c** is used to accommodate solid or powder objects, and to seal and store the solid or powder objects. The distinction between the first containing area **10c** and the second containing area **10d** ensures the sealing effect of the first containing area **10c** on solid or powdery objects, avoiding the separation of solid or powdery objects from the first containing area **10c**, while the second containing area **10d** is used to accommodate the hands of non children's characters pass through the first opening, and to restrict the hands of non children's characters, thereby avoiding children's hands from contacting the third bag body **31**. Thus, children's hands are restricted from simultaneously pulling on the third bag body **31** and the first bag body **11**, in order to prevent children from opening the childproof containing bag **100**.

(30) In the present embodiment, the third bag body **31** is arranged in the containing space **10a**, and the top of the third bag body **31** does not exceed the top of the second bag body **12** or the top of the first bag body **11**, so that the third bag body **31** is hidden between the second bag body **12** and the first bag body **11**, and is out of reach of children's hands, further preventing children from opening the childproof containing bag **100** and improving the functional effect of the childproof containing bag **100**.

(31) In addition, the third bag body **31** is movably connected to the second bag body **12**, one end of the third bag body **31** is connected to the second bag body **12**, and the other end is detached from the second bag body **12**. In the present embodiment, one end of the third bag body **31** is hot pressed onto the surface of the second bag body **12**, and the other end of the third bag body **31** is not connected to the surface of the second bag body **12**, and there is a motion space between the third bag body **31** and the second bag body **12**. Thus, the motion space facilitates the movement of the third bag body **31** relative to the second bag body **12**, and affects the sealing connection between the third bag body **31** and the first bag body **11** when pulling the second bag body **12**. This ensures that children cannot open the second sealing strip **32** and the first sealing strip **20** when pulling the second bag body **12** and the first bag body **11**, thereby ensuring the sealing function of the first containing area **10c** for solid or powder objects. Optionally, solid or powdered objects may be medicinal powder, and there are no restrictions here.

(32) In addition, one of the first sealing strip **20** and the second sealing strip **32** is provided with a first snap part **21**, and the other is provided with a second snap part **321**. Optionally, the first sealing strip **20** is provided with a first snap part **21**, and the second sealing strip **32** is provided with a second snap part **321**, which is not limited here.

(33) The first snap part **21** is provided with an elliptical snap hook **211**, and the second snap part **321** is provided with an elliptical snap groove **322**. The snap hook **211** is located in the snap groove **322** and mutually snapped when the second snap part **321** and the first snap part **21** are detachably snapped and connected, so as to facilitate the detachable sealing connection between the first sealing strip **20** and the second sealing strip **32** through the snap connection between the first snap part **21** and the second snap part **321**.

(34) In the present embodiment, the first snap part **21** and the second snap part **321** form a set of snap assembly. A plurality of the snap assemblies are arranged at intervals along the width direction of the third bag body **31**, and the first snap part **21** is alternately placed on the first sealing strip **20** or the second sealing strip **32** according to an arrangement of the plurality of the snap assemblies. Thus, the alternating arrangement of the first snap part **21** and the second snap part **321** improves the overall effect of the first sealing strip **20** and the second sealing strip **32**, ensuring the sealing effect of the first sealing strip **20** and the second sealing strip **32**. Optionally, the snap hook **211** is provided with two oblique hooks **212** arranged symmetrically, and the two oblique hooks **212** respectively snap at both ends of the snap groove **322** and engage at both ends of the snap groove **322**, thereby achieving a snap connection between the first snap part **21** and the second snap part **321** through the engagement of the two oblique hooks **212** at the snap groove **322**.

(35) Optionally, when the first snap part **21** is in the first sealing strip **20** and the second snap part **321** is in the second sealing strip **32**, the first snap part **21** extends in a wavy manner along the length direction of the first sealing strip **20**, and the second snap part **321** extends in a wavy manner along the length direction of the second sealing strip **32**. The first snap part **21** matches with the second snap part **321**.

(36) In addition, at least one of the first bag body **11**, the second bag body **12** and the third bag body **31** is made of degradable materials. In the present embodiment, the degradable materials may be polylactic acid material, butylene adipate-co-butylene terephthalate material, polybutylenes succinate material, polypropylene carbonate material, aliphatic copolyester material or polyglycolic acid material, which are not limited here. Alternatively, the first bag body **11**, the second bag body **12**, and the third bag body **31** are all made of non degradable materials, in this case, the non

degradable material may be PET film material or polyethylene material, and there is no restriction here.

(37) In addition, there is a tear opening **111** at the connection between the first bag body **11** and the second bag body **12**. The tear opening **111** is located to one side of the main bag body **10** and is close to the end slot of the main bag body **10**. In the present embodiment, the tear opening **111** is used for the hands of non child characters to tear the bag, so as to reduce the distance between the top of the second bag body **12** and the top of the third bag body **31** after tearing, thereby facilitating the hands of non child characters to contact the third bag body **31**. Thus, it facilitates the hands of non child characters to pull the third bag body **31** and the first bag body **11**.

Embodiment 2

(38) Please refer to FIG. 7, compared to the first embodiment, the third bag body **31** is provided with a pulling part **311**. The pulling part **311** is located on one side of the second sealing strip **32** and faces the first opening **10b** of the containing space **10a**. In the present embodiment, the third bag body **31** is far away from the connection between the third bag body **31** and the second bag body **12**. The pulling part **311** is used for pulling the hands of non children characters, as children's hands cannot contact the third bag body **31**, as a result, it is impossible to contact the pulling part **311** of the third bag body **31**, avoiding children from pulling on the third bag body **31** and the second bag body **12**. Optional, non child characters may be adults, middle-aged people, or elderly people.

(39) When the pulling part **311** is pulled by the hands of non child characters, both the pulling part **311** and the first bag body **11** are subjected to the pulling force of the hands of non child characters, and the third bag body **31** and the first bag body **11** move in the opposite direction. The distance between the third bag body **31** and the first bag body **11** gradually increases, and the second sealing strip **32** detaches from the first sealing strip **20** with the movement of the third bag body **31**.

(40) Alternatively, when the second bag body **12** is pulled by the hands of a child, both the second bag body **12** and the first bag body **11** are subjected to the pulling force of the hands of a non child. The second bag body **12** and the first bag body **11** move in the opposite direction, the second bag body **12** and the third bag body **31** gradually open, and the distance between the third bag body **31** and the first bag body **11** remains unchanged, while the second sealing strip **32** and the first sealing strip **20** located in the third bag body **31** still form a sealed connection. Thus, the pulling between the second bag body **12** and the first bag body **11** will not affect the distance between the third bag body **31** and the first bag body **11**, and the sealing connection between the second sealing strip **32** and the first sealing strip **20** will not be affected by the pulling between the second bag body **12** and the first bag body **11**, ensuring the sealing performance of the first containing area **10c** to solid or powder objects.

(41) Optionally, there is a safety distance between the top of the pulling part **311** and the top of the second bag body **12**, so that children's hands cannot touch the pulling part **311**. The safety distance is greater than the distance grasped by the children's thumb. In this case, the safety distance may be greater than 20 centimeters, and the safety distance can be adjusted according to the actual situation.

Embodiment 3

(42) Please refer to FIG. 8 to FIG. 11, compared to the second embodiment, the surface roughness of the pulling part **311** is inconsistent with the roughness of the inner surface of the second bag body **12**. Wherein the surface roughness of the pulling part **311** is greater than the roughness of the inner surface of the second bag body **12**. In the present embodiment, the surface roughness of the pulling part **311** is inconsistent with the roughness of the inner surface of the second bag body **12**, which facilitates the hand feel recognition of non children's characters. Because the pulling part **311** is provided in the containing space **10a** and is hidden between the second bag body **12** and the first bag body **11**, it is easy to identify the pulling part **311** and the second bag body **12** through the hand feel of non children's characters, making it easy for the hands of non children's characters to find

the pulling part **311**, so that the hands of non children's characters can act on the pulling part **311** and the second bag body **12**, thereby improving the operational convenience of the childproof containing bag **100**.

(43) In addition, the surface of the pulling part **311** is provided with a friction layer **312**, and the friction layer **312** is configured for contact by the hands of the non child characters. Optionally, the friction layer **312** is a friction plate that attaches to the surface of the pulling part **311**. Wherein, the friction layer **312** is provided with a plurality of arc-shaped bump regions **3121**, the plurality of the arc-shaped bump regions **3121** are arranged at intervals along the length direction of the friction layer **312**. Each of the plurality of the arc-shaped bump regions **3121** is provided with a plurality of bumps **3122**, and the plurality of bumps **3122** are arranged in concentric circles. In the present embodiment, one arc-shaped bump regions **3121** is formed by the plurality of bumps **3122**, and based on the contact between the plurality of bumps **3122** and the hands of non children's characters, the tactile sensation of the pulling part **311** is improved, thereby facilitating the hands of non children's characters to find the pulling part **311**, and thus facilitating the operation of the pulling part **311** by the hands of non children's characters.

(44) Optionally, the pulling part **311** is provided with a gap **313**, the gap **313** is located in the middle of the pulling part **311**, in the present embodiment, the hands of non children's characters enter the second containing area **10d**, and the pulling part **311** can be found when touching the gap **313**, such that it is easier for the hands of non children's characters to find the pulling part **311**, so as to facilitate the use of the pulling part **311** and the second bag body **12** by the hands of non children's characters, improving the operational convenience of the childproof containing bag **100**. In the present embodiment, the gap **313** of the pulling part **311** guides the hands of non child characters to pass through, so as to guide the hands of non child characters to contact the pulling part. Optionally, the gap **313** is an arc-shaped groove or an irregular groove.

Embodiment 4

(45) Please refer to FIG. **12**, compared to the second embodiment, the inner surface of the second bag body **12** is provided with a second guide edge **121**. The second guide edge **121** extends along the length direction of the second bag body **12** to the top of the pulling part **311** and guides the hands of non child characters to contact the pulling part **311**. At this point, the second guide edge **121** can be a straight strap protruding on the inner surface of the second bag body **12**, guiding the hands of non children characters through the second guide edge **121**, in order to facilitate the hands of non children characters to find the pulling part **311** along the second guide edge **121**.

(46) Optionally, the inner surface of the first bag body **11** is provided with a first guide edge **112**, which extends along the length direction of the first bag body **11** to the first sealing strip **20**. The first guide edge **112** is arranged opposite to the second guide edge. At this point, the first guide edge **112** can be a straight strap protruding from the inner surface of the first bag body **11**. By guiding the hands of non children characters through the first guide edge **112**, the position of the second guide edge **121** can be determined for the hands of non children characters, so that the hands of non children characters can find the pulling part **311** through the guidance of the second guide edge **121**.

Embodiment 5

(47) Please refer to FIG. **13**, compared to the first embodiment, there is a first reinforcement strip **113** between the first bag body **11** and the first sealing strip **20**. The first reinforcement strip **113** is arranged corresponding to the connection between the first bag body **11** and the first sealing strip **20**, so as to reinforce the connection between the first bag body **11** and the first sealing strip **20** to increase the service life of the connection between the first bag body **11** and the first scaling strip **20** through the first reinforcement strip **113** and avoid damage due to frequent pulling.

(48) In addition, there is a second reinforcement strip **122** between the third bag body **31** and the second bag body **12**. The second reinforcement strip **122** is arranged corresponding to the connection between the third bag body **31** and the second bag body **12**, so as to reinforce the

connection between the third bag body **31** and the second bag body **12** to increase the service life of the connection between the third bag body **31** and the second sealing strip **32** through the second reinforcement strip **122** and avoid damage due to frequent pulling.

Embodiment 6

(49) Please refer to FIG. **14**, compared to the first embodiment, the inner surface of the second bag body **12** is connected with a masking sheet **123**, and the masking sheet **123** faces the other end of the third bag body **31**. The masking sheet **123** is movably connected to the inner surface of the second bag body **12** and shelters from the other end of the third bag body **31** or detaches from the other end of the third bag body **31**. In the present embodiment, when the masking sheet **123** shelters the other end of the third bag body **31**, the third bag body **31** is in a hidden state to avoid contact with children's hands. When the third bag body **31** needs to be pulled, the hands of non children's characters flip the masking sheet **123** to show the third bag body **31** to facilitate the third bag body **31** being pulled by the hands of non children's characters, thereby the hands of non children's characters pull the third bag body **31** and the first bag body **11** to further unseal the sealing state of the second sealing strip **32** and the first sealing strip **20**, in order to facilitate the removal of solid or powder objects in the first containing area **10c**.

(50) In addition, one end of the masking sheet **123** is connected to the inner surface of the second bag body **12**, and an elastic member **124** is connected between the masking sheet **123** and the second bag body **12**. The two ends of the elastic member **124** are respectively connected to the masking sheet **123** and the second bag body **12**, the elastic member applies elastic force to the masking sheet **123**, and the masking sheet **123** contacts with the other end of the third bag body **31** under the elastic force of the elastic member **124**, so that the third bag body **31** is against the second bag body **12**, to facilitate the continuous contact of the masking sheet **123** to the third bag body **31** under the elastic action of the elastic member **124**, ensuring the concealed effect of the masking sheet **123** on the third bag body **31**. Optionally, the elastic member **124** is a leaf spring.

Embodiment 7

(51) Please refer to FIG. **15** and FIG. **16**, compared to the first embodiment, the surface of the first bag body **11** facing away from the second bag body **12** is connected with a fourth bag body **40**. The fourth bag body **40** is exposed to the first bag body **11**, and the fourth bag body **40** is provided with a holding groove **41** for accommodating objects. At this time, the fourth bag body **40** is added to the first bag body **11**, and the holding groove **41** is added to improve the holding effect of the childproof containing bag **100**.

(52) In addition, the second bag body **12** is provided with a positioning hole **125**, which is located at the top of the second bag body **12** and above the third bag body **31**. The positioning hole **125** is a circular or irregular hole, and is used for threading the positioning hook **210** connected to the wall **200**. When the positioning hook **210** penetrates through the positioning hole **125** of the second bag body **12**, the second bag body **12** is connected to the positioning hook **210** and suspended in the air, and the main bag body **10** is at a height that children cannot reach, thereby ensuring that the main bag body **10** is in a suspended state to avoid children's contact, and ensuring that the childproof containing bag **100** has high safety due to being inaccessible to children.

(53) In the above embodiments, the descriptions of each embodiment have their own emphasis. For the parts that are not detailed in one embodiment, please refer to the relevant descriptions of other embodiments.

(54) In the description of this application, the terms “first” and “second” are only used for descriptive purposes and cannot be understood as indicating or implying relative importance or implying the quantity of indicated technical features. Therefore, features limited to “first” and “second” can explicitly or implicitly include one or more features.

(55) This application applies specific embodiments to explain the principles and implementation methods of this application. The above embodiments are only used to help understand the methods and ideas of this application. Meanwhile, for skilled person in the art, there may be changes in the

specific implementation methods and application scope based on the ideas of this application. In summary, the content of this specification should not be understood as a limitation on this application.

Claims

1. A childproof containing bag, comprising: a main bag body, comprising a first bag body and a second bag body connected to each other, wherein the first bag body and the second bag body are enclosed to form a containing space, and the containing space is provided with a first opening; a first sealing strip connected to the first bag body, wherein the first sealing strip is located at an opposite position between the first bag body and the second bag body, and is arranged in the containing space; a first sealing assembly connected to the second bag body and embedded in the containing space, wherein the first sealing assembly comprises a third bag body and a second sealing strip, the third bag body is located in the containing space, the third bag body is connected to the second bag body, the second sealing strip is connected to the third bag body and arranged corresponding to the first sealing strip, and the second sealing strip is detachably sealed and connected to the first sealing strip; when the second sealing strip is sealed and connected to the first sealing strip, a sealing area between the second sealing strip and the first sealing strip separates the containing space into a first containing area and a second containing area; the first containing area is used to accommodate solid or powdery objects, and to seal and preserve the solid or powdery objects; the second containing area is used to accommodate hands of non child characters that extend through the first opening; the first bag body and the second bag body are in an open state, the third bag body is placed in the containing space, the second sealing strip detaches from the first sealing strip as the third bag body is moved; a top of the third bag body does not exceed a top of the second bag body or a top of the first bag body; the third bag body is provided with a pulling part, wherein the pulling part is located on one side of the second sealing strip and faces the first opening of the containing space, and the pulling part is used for pulling the hands of the non child characters; when the pulling part is pulled by the hands of the non child characters, the third bag body and the first bag body are moved in an opposite direction, and the second sealing strip detaches from the first sealing strip as the third bag body is moved; the surface of the pulling part is provided with a friction layer, and the friction layer is configured for contact by the hands of the non child characters; the friction layer is provided with a plurality of arc-shaped bump regions, the plurality of the arc-shaped bump regions are arranged at intervals along a length direction of the friction layer, each of the plurality of the arc-shaped bump regions is provided with a plurality of bumps, and the plurality of bumps are arranged in concentric circles.
2. The childproof containing bag according to claim 1, wherein the second bag body and the first bag body are moved in the opposite direction when the second bag body is pulled by hands of children, and the second bag body and the third bag body gradually open, while the second sealing strip and the first sealing strip in the third bag body are still in a sealed connection.
3. The childproof containing bag according to claim 1, wherein a surface roughness of the pulling part is inconsistent with an inner surface roughness of the second bag body, and the surface roughness of the pulling part is greater than the inner surface roughness of the second bag body.
4. The childproof containing bag according to claim 1, wherein the pulling part is provided with a gap, the gap is located in a middle of the pulling part and guides the hands of non child characters to pass through, so as to guide the hands of non child characters to contact the pulling part.
5. The childproof containing bag according to claim 1, wherein an inner surface of the second bag body is provided with a second guide edge, the second guide edge extends along a length direction of the second bag body to a top of the pulling part and guides the hands of non child characters to contact the pulling part; an inner surface of the first bag body is provided with a first guide edge, the first guide edge extends along a length direction of the first bag body to the first sealing strip,

and the first guide edge is arranged opposite to the second guide edge.

6. The childproof containing bag according to claim 1, wherein the first sealing strip extends along a width direction of the first bag body; a first reinforcement strip is arranged between the first bag body and the first sealing strip, and the first reinforcement strip is arranged corresponding to the connection between the first bag body and the first sealing strip to reinforce the connection between the first bag body and the first sealing strip.

7. The childproof containing bag according to claim 6, wherein a second reinforcement strip is arranged between the third bag body and the second bag body, the second reinforcement strip is arranged corresponding to the connection between the third bag body and the second bag body, to reinforce the connection between the third bag body and the second bag body.

8. The childproof containing bag according to claim 1, wherein the third bag body is movably connected to the second bag body, one end of the third bag body is connected to the second bag body, and the other end of the third bag body is detached from the second bag body, so that there is a motion space between the third bag body and the second bag body; an inner surface of the second bag body is connected with a masking sheet, the masking sheet faces the other end of the third bag body; and the masking sheet is movably connected to the inner surface of the second bag body and shelters or detaches from the other end of the third bag body.

9. The childproof containing bag according to claim 8, wherein one end of the masking sheet is connected to the inner surface of the second bag body, and an elastic member is connected between the masking sheet and the second bag body; two ends of the elastic member are respectively connected to the masking sheet and the second bag body, the elastic member applies elastic force to the masking sheet, and the masking sheet contacts with the other end of the third bag body under the elastic force of the elastic member, so that the third bag body is against the second bag body.

10. The childproof containing bag according to claim 1, wherein one of the first sealing strip and the second sealing strip is provided with a first snap part, the other is provided with a second snap part, and the first snap part is provided with an elliptical snap hook; the second snap part is provided with an elliptical snap groove; and the snap hook is located in the snap groove and mutually snapped when the second snap part and the first snap part are detachably snapped and connected; the first snap part and the second snap part form a set of snap assembly; a plurality of the snap assemblies are arranged at intervals along a width direction of the third bag body, and the first snap part is alternately placed on the first sealing strip or the second sealing strip according to an arrangement of the plurality of the snap assemblies.

11. The childproof containing bag according to claim 10, wherein the snap hook is provided with two oblique hooks arranged symmetrically, and the two oblique hooks respectively snap at both ends of the snap groove and engage at both ends of the snap groove.

12. The childproof containing bag according to claim 1, wherein at least one of the first bag body, the second bag body, and the third bag body is made of degradable material.

13. The childproof containing bag according to claim 1, wherein the first bag body, the second bag body, and the third bag body are all made of non degradable materials.

14. The childproof containing bag according to claim 1, wherein the first bag body is connected to the second bag body; a connection between the first bag body and the second bag body is provided with a tear opening located on one side of the main bag body and near an end of the main bag body.

15. The childproof containing bag according to claim 1, wherein the second bag body is provided with a positioning hole, the positioning hole is located at a top of the second bag body and above the third bag body; the positioning hole is configured for threading the positioning hook connected to a wall; when the positioning hook penetrates the positioning hole of the second bag body, the second bag body is connected to the positioning hook and suspended, and the main bag body is at a height that children are unable to reach.
