

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12411085
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Ballance; Timothy George et al.

Miniature atomic spectroscopy reference cell system

Abstract

A spectroscopy system is described. The spectroscopy system includes a cell, a photodiode, and mirrors. The cell has walls forming a chamber therein. The chamber is configured to receive laser signal(s) and retaining a vapor therein. The vapor fluoresces in response to the laser signal(s). The mirrors are configured to direct fluorescent light from the vapor toward the photodiode. In some embodiments, the spectroscopy system is incorporated with a photonic integrated circuit.

Inventors: Ballance; Timothy George (Oxford, GB), Salim; Evan (Lafayette, CO), Bowman; David (Oxford, GB)

Applicant: ColdQuanta, Inc. (Boulder, CO); COLDQUANTA UK LIMITED (Oxford, GB)

Family ID: 87559444

Assignee: ColdQuanta, Inc. (Boulder, CO); COLDQUANTA UK LIMITED (N/A, N/A)

Appl. No.: 18/106455

Filed: February 06, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230258562 A1	Aug. 17, 2023

Related U.S. Application Data

us-provisional-application US 63308849 20220210

Publication Classification

Int. Cl.: G01N21/64 (20060101)

U.S. Cl.:

CPC **G01N21/6404** (20130101); G01N2201/068 (20130101)

Field of Classification Search

CPC: G01J (3/4406)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3858980	12/1974	West	356/312	G01N 21/74
3897155	12/1974	Smythe	356/325	G01N 21/6404
4350661	12/1981	Davis	73/147	G01N 21/6402
4432644	12/1983	Demers	356/316	G01N 21/6404
6300638	12/2000	Groger	250/458.1	G01N 21/7703
6489609	12/2001	Baba	250/281	G01N 21/6404
10753863	12/2019	Hug	N/A	G01J 3/2803
2005/0134836	12/2004	Paldus	356/73	G01J 3/10
2008/0278710	12/2007	Schmidt	356/73	G04F 5/145
2009/0242804	12/2008	Obara	250/461.1	G01N 21/274
2011/0036995	12/2010	Binnie	250/461.1	G01N 15/1404
2012/0014837	12/2011	Fehr	385/12	G01N 21/75
2014/0204382	12/2013	Christensen	356/402	G01N 21/3504
2014/0368826	12/2013	Abbott, Jr.	356/454	G01N 21/255
2015/0316412	12/2014	Bond	356/437	G01J 3/0218
2016/0028210	12/2015	O'Shaughnessy	372/34	H01S 3/2383
2016/0084761	12/2015	Rothberg	506/4	C12Q 1/6869
2016/0214107	12/2015	Viasnoff	N/A	G02B 21/361
2016/0231244	12/2015	Camargo	N/A	G01N 21/031
2016/0305882	12/2015	Goeders	N/A	B82Y 20/00
2017/0191932	12/2016	Kokkin	N/A	G01J 3/433
2017/0248514	12/2016	Pavey	N/A	G01N 33/0063
2019/0049300	12/2018	Gu	N/A	G01J 3/44
2019/0302024	12/2018	Sun	N/A	G01N 21/0303
2021/0218224	12/2020	Dyer	N/A	H01S 5/0427
2021/0389321	12/2020	Kaushik	N/A	G01N 21/64
2022/0136962	12/2021	Kosterev	356/319	G01N 21/31

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
209690172	12/2018	CN	N/A

OTHER PUBLICATIONS

John Kitching, Chip-Scale Atomic Devices, Applied Physics Review 5, 031302 (2018), published Aug. 14, 2018. cited by applicant

Zoe Z. Yan, Nonlinear Spectroscopy of Rubidium and Frequency Stabilization of a 1560 nm Diode

Primary Examiner: Makiya; David J

Assistant Examiner: Kefayati; Soorena

Attorney, Agent or Firm: Young Basile Hanlon & MacFarlane, P.C.

Background/Summary

CROSS REFERENCE TO OTHER APPLICATIONS (1) This application claims priority to U.S. Provisional Patent Application No. 63/308,849 entitled MINIATURE ATOMIC SPECTROSCOPY REFERENCE CELL SYSTEM filed Feb. 10, 2022 which is incorporated herein by reference for all purposes.

BACKGROUND OF THE INVENTION

(1) Saturated absorption spectroscopy may be utilized to produce a doppler-free atomic reference for stabilizing laser systems. Typically, a saturated atomic absorption spectroscopy cell utilizes pump and probe laser beams transmitted in opposite directions through a vapor in the cell. When the lasers are appropriately tuned, the vapor absorbs light from the pump and probe lasers. The intensity of the beam diminishes. The probe beam is tapped and the portion of the probe beam provided to a photodiode for measurement. Thus, the reduction in intensity of the tapped probe beam provides a measure of the absorption of the probe beam. The frequency of the tapped probe beam can be used in stabilizing and/or calibrating other laser systems.

(2) However, there may be significant drawbacks to such spectroscopy. Measurement of absorption utilizes a relatively small change (i.e. the absorption) in a relatively large signal (i.e. intensity of the laser). Thus, the signal-to-noise ratio may be small. Photon shot noise in the absorption beam may further reduce the signal-to-noise ratio. Moreover, the relative absorption signal is dependent upon the path length in the cell. As a result, the saturated atomic absorption spectroscopy cell is desired to be longer, often on the order of five to ten centimeters or more. Such a cell does not lend itself to miniaturization or use with technologies such photonic integrated circuits. To implement a saturated atomic absorption spectroscopy cell, the pump and probe lasers are frequently taken from a single laser. Thus, the optical components such as splitters are used in conjunction with the atomic absorption spectroscopy cell. This also complicates integration of the cell with other technologies. Accordingly, what is needed is an improved technique for atomic spectroscopy.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) Various embodiments of the invention are disclosed in the following detailed description and the accompanying drawings.

(2) FIG. 1 is a diagram depicting an embodiment of a system for performing atomic fluorescence spectroscopy.

(3) FIGS. 2A-2C depict side, end, and top views of an embodiment of a system for performing atomic fluorescence spectroscopy.

(4) FIGS. 3A-3C depict side, end, and top views of an embodiment of a system for performing atomic fluorescence spectroscopy.

(5) FIG. 4 depicts an end view of an embodiment of a system for performing atomic fluorescence

spectroscopy.

(6) FIG. 5 depicts an end view of an embodiment of a system for performing atomic fluorescence spectroscopy.

(7) FIG. 6 depicts an end view of an embodiment of a system for performing atomic fluorescence spectroscopy.

(8) FIG. 7A-7B depict side and end views of an embodiment of a system for performing atomic fluorescence spectroscopy.

(9) FIG. 8 depicts a perspective view of an embodiment of a system for performing atomic fluorescence spectroscopy.

(10) FIG. 9 is a flow-chart depicting an embodiment of a method for providing an atomic fluorescence spectroscopy system.

DETAILED DESCRIPTION

(11) The invention can be implemented in numerous ways, including as a process; an apparatus; a system; a composition of matter; a computer program product embodied on a computer readable storage medium; and/or a processor, such as a processor configured to execute instructions stored on and/or provided by a memory coupled to the processor. In this specification, these implementations, or any other form that the invention may take, may be referred to as techniques. In general, the order of the steps of disclosed processes may be altered within the scope of the invention. Unless stated otherwise, a component such as a processor or a memory described as being configured to perform a task may be implemented as a general component that is temporarily configured to perform the task at a given time or a specific component that is manufactured to perform the task. As used herein, the term 'processor' refers to one or more devices, circuits, and/or processing cores configured to process data, such as computer program instructions.

(12) A detailed description of one or more embodiments of the invention is provided below along with accompanying figures that illustrate the principles of the invention. The invention is described in connection with such embodiments, but the invention is not limited to any embodiment. The scope of the invention is limited only by the claims and the invention encompasses numerous alternatives, modifications and equivalents. Numerous specific details are set forth in the following description in order to provide a thorough understanding of the invention. These details are provided for the purpose of example and the invention may be practiced according to the claims without some or all of these specific details. For the purpose of clarity, technical material that is known in the technical fields related to the invention has not been described in detail so that the invention is not unnecessarily obscured.

(13) A spectroscopy system is described. The spectroscopy system includes a cell, a photodiode, and mirrors. The cell has walls forming a chamber therein. The chamber is configured to receive laser signal(s) and retaining a vapor therein. The vapor fluoresces in response to the laser signal(s). The mirrors are configured to direct fluorescent light from the vapor toward the photodiode. In some embodiments, the mirrors are internal to the chamber, while in other embodiments, some or all of the mirrors may be external to the chamber. The spectroscopy system may also include first and second mirrors, which may be mounted on opposite ends of the chamber. The first and second mirrors are configured to reflect the laser signal(s) such that laser beams propagate in opposing directions in the chamber. In some embodiments, the spectroscopy system is incorporated with a photonic integrated circuit (PIC).

(14) A photonic integrated circuit (PIC) is described. The PIC includes output gratings on a substrate and a PIC spectroscopy system coupled to a surface of the PIC. The output gratings are configured to couple laser signal(s) out-of-plane with respect to the substrate. Thus, out-of-plane laser signal(s) are provided. The spectroscopy system includes a cell, a photodiode, and mirrors. The cell has walls forming a chamber therein. The chamber is aligned with the output gratings and retains a vapor. The vapor fluoresces in response to the out-of-plane laser signal(s). The mirrors are configured to direct fluorescent light from the vapor to the photodiode.

(15) A method for providing a spectroscopy system is described. The method includes providing a cell having walls and a chamber therein. The chamber is configured to receive laser signal(s) and to retain a vapor therein. The vapor fluoresces in response to the laser signal(s). The method also includes coupling mirrors to the walls and providing a photodiode. The mirrors are oriented to direct fluorescent light from the vapor toward the photodiode. The method may also include providing first and second mirrors. The second mirror is opposite to the first mirror. The first and second mirrors reflecting the laser signal(s) such that laser beams propagate in opposing directions in the chamber.

(16) FIG. 1 is a block diagram depicting an embodiment of system **100** for performing atomic fluorescence spectroscopy. Because FIG. 1 is a block diagram, the location of components of system **100** in FIG. 1 are not intended represent positions in space. System **100** includes atomic spectroscopy cell **110** having a chamber **112** therein, one or more mirrors **130**, and one or more photodiodes **120**. Chamber **112** retains a vapor, such as Rb, which undergoes fluorescence if light of the appropriate frequency is incident on the vapor. More specifically, the vapor absorbs light of the frequency corresponding to a transition between electronic levels. The vapor fluoresces and, therefore, emits light. Photodiode **120** senses light. Also shown are laser signal(s) **140** that traverse chamber **112**. Laser signal(s) **140** thus provide the light that causes vapor in chamber **112** to fluoresce. In some embodiments, laser signal(s) **140** entering chamber **112** may be formed from a free space beam. In some embodiments, laser signal(s) **140** may be from a waveguide grating coupler (not shown) that is bonded onto the input window of cell **110**.

(17) Mirror(s) **130** may be considered to be any mechanism that can redirect the fluoresced light. For example, mirror(s) **130** may simple be simple reflectors or may have a more complicated structure. Mirror(s) **130** may be mounted internal to chamber **112** or may be external to chamber **112**. In such embodiments, the walls of cell **110** are transparent to the fluoresced light.

(18) In operation, laser signal(s) **140** pass through chamber **112**. Thus, some or all of at least one of the walls of cell **110** may be transparent. In some embodiments, a single laser signal enters chamber **112** from a one wall, e.g. through a window, a use of a transparent wall, or other mechanism. The laser signal **140** passes through chamber **112** and is reflected from a mirror (not shown) on the opposing wall. Mirrors (not shown) on one or both opposing walls of chamber **112** allow laser signal(s) **140** to traverse chamber **112** multiple times. In other embodiments, multiple laser sources are used. Thus, laser signal(s) **140** may propagate in opposite directions. This may allow for Doppler-free measurements. This also provides additional opportunity for laser signal(s) **140** to excite vapor and, therefore, for vapor to emit fluoresced light.

(19) If laser signal(s) **140** are tuned to transition(s) of the vapor in chamber **112**, the vapor absorbs light, reaches an excited state, and emits photons. The vapor in chamber **112** thus undergoes atomic fluorescence. Photodiode **120** senses light. Further, photodiode **120** is mounted such that laser signal(s) **140** are not incident on photodiode. Thus, the light sensed by photodiode **120** may be mostly or completely limited to the fluoresced light. Stated differently, the photocurrent of photodiode **120** arising directly from laser signal(s) **140** may be minimized. Shot noise may also be reduced or minimized.

(20) However, fluoresced light from the vapor travels in a variety of directions. Without more, the signal detected by photodiode **120** may be lower than desired. Mirror(s) **130** redirect the fluoresced light toward photodiode **120**. Mirror(s) **130** may thus improve the collection efficiency of photodiode **120**. In some embodiments at least fifty percent of the fluoresced light is incident on photodiode(s) **120** because of the use of mirror(s) **130**. In some embodiments, at least seventy percent of the fluoresced light is incident on photodiode(s) **120**. In some such embodiments, at least ninety percent (e.g. close to one hundred percent) of the fluoresced light is incident on photodiode(s) **120**. Consequently, a higher fluorescence signal may be detected. In some embodiments, the line width of the fluorescence signal detected may be as low as 2 MHz or 1 MHz. In some embodiments, the line width of the fluorescence signal may be lower. For example,

0.5 MHz or 0.1 MHz might be possible in some embodiments. The detected fluorescence may be used to calibrate an apparatus or as a reference signal for other apparatus. For example, spectroscopy system **100** may be used as a reference to stabilize 780 nm laser for laser cooling, or 1560 nm C-band lasers for coherent signal transmission (such as QAM).

(21) In addition to having a higher signal-to-noise ratio, system **100** may be more readily miniaturized. For example, the length of chamber **112**, and thus cell **110**, in the direction of propagation of laser signal(s) **140** may be not more than ten millimeters. In some embodiments, this length is not more than five millimeters. In some embodiments, the length is not longer than one millimeter. The reduction in length may be due to mirrors (not shown) at opposing ends of chamber **110**, which allows laser signal(s) **140** to traverse chamber **112** multiple times. Because it may be miniaturized, spectroscopy system **100** may be more readily used with other technologies. For example, system **100** may be more readily integrated with a photonic integrated circuit (PIC). In addition, a smaller-sized spectroscopy cell may be warmed up and stabilized more rapidly than a larger system. For example, in some embodiments, system **100** may be stabilized and ready for use in less than one minute (e.g. five to ten seconds), instead of hours. Thus, system **100** is more rapidly usable. Thus, system **100** may be more readily used for reference and/or calibration of lasers, as well as for other applications.

(22) FIGS. 2A-2C depict side, end, and top views of an embodiment of system **200** for performing atomic fluorescence spectroscopy. For simplicity, system **200** is not to scale. System **200** is analogous to system **100**. Consequently, analogous components have similar labels. System **200** includes spectroscopy cell **210**, photodiode **220**, and mirror(s) **230** that are analogous to cell **110**, photodiode(s) **120**, and mirror(s) **130**. Also shown are laser signal(s) **240** that are analogous to laser signal(s) **140**.

(23) Spectroscopy cell **210** may be a vacuum substrate (e.g. a silicon substrate) and has chamber **212** therein. In some embodiments, chamber **212** is formed by removing a portion of the vacuum substrate. For example, a v-groove may be formed in the substrate to form chamber **212** having a triangular cross-section. Chamber **212** is sealed by the substrate on which photodiode **220** is mounted. Further, photodiode **220** is mounted such that laser signal(s) **240** are not incident on photodiode. Thus, the light sensed by photodiode **220** may be mostly or completely limited to the fluoresced light. Chamber **212** retains a vapor, such as Rb, which undergoes fluorescence if light of the appropriate frequency (i.e. laser signal(s) **240** tuned to the appropriate frequency) is incident on the vapor.

(24) Mirror(s) **230** are aligned to redirect the fluoresced light toward photodiode **220**. In some embodiments, mirror(s) **220** may be mounted on the internal walls of chamber **212**. In some embodiments, mirror(s) **220** may be a reflective material that is deposited on the inner walls of chamber **212**. Thus, two walls hold mirror(s) **230**, while the third wall holds (or is formed by) photodiode **220** and the substrate to which photodiode **220** is attached or formed on. Because of the cross-section of chamber **212**, mirror(s) **230** redirect toward photodiode **220** light fluoresced by the vapor that would otherwise travel away from photodiode **220**.

(25) In operation, laser signal(s) **240** pass through chamber **212**. In the embodiment shown, counter propagating laser beams are used for laser signal(s) **240**. In some embodiments, the frequency of laser signal(s) **240** is swept through a range including the appropriate signal for fluorescence of the vapor. Laser signal(s) **240** having the appropriate frequency excite vapor. In response, the vapor emits fluoresced light. Some of the fluoresced light is incident directly on photodiode **220**. Some or all of the fluoresced light is emitted in directions away from photodiode **220**. Mirror(s) **230** redirect most or all of this fluoresced light toward photodiode **220**. Photodiode **220** senses this light and outputs a photocurrent. Consequently, a higher fluorescence signal may be detected. In some embodiments, the line width of the fluorescence signal detected may be in the ranges described and higher the signal-to-noise ratio described herein may be achieved. Moreover, system **200** may be more readily miniaturized. For example, the length, L, in the direction of propagation of the laser

signal(s) **240** may be in the ranges (e.g. not more than one, five, or ten millimeters) described herein. Therefore, system **200** may not only have improved performance, but may also be more readily integrated with technologies, such as a PIC. In addition, system **200** may be more rapidly stabilized and readily used.

(26) FIGS. **3A-3C** depict side, end, and top views of an embodiment of system **300** for performing atomic fluorescence spectroscopy. For simplicity, system **300** is not to scale. System **300** is analogous to systems **100** and/or **200**. Consequently, analogous components have similar labels. System **300** includes spectroscopy cell **310**, photodiode **320**, and mirror(s) **330** that are analogous to cells **110** and **210**, photodiode(s) **120** and **220**, and mirror(s) **130** and **230**. Also shown are laser signal(s) **340** that are analogous to laser signal(s) **140** and **240**.

(27) In addition, system **300** includes mirrors **350** and **352** on opposing sides of chamber **312**. Mirrors **350** and **352** are configured to reflect laser signal(s) **340**. In the embodiment shown, mirror **352** may include a window or other feature that allow some of the laser signal(s) **340** to enter chamber **312**. Thus, a single laser signal may be used for system **300**. In some embodiments, mirror **350** and/or **352** might be omitted.

(28) System **300** operates in an analogous manner to systems **100** and **200**. In particular, laser signal(s) **340** pass through chamber **312** and are reflected by mirrors **350** and **352**. When tuned to the appropriate frequency, laser signal(s) excite the vapor in chamber **312**. In response, the vapor emits fluoresced light. Some of the fluoresced light is incident directly on photodiode **320**. Some or all of the fluoresced light emitted in directions away from photodiode **320** may be redirected by mirror(s) **330** toward photodiode **320**. Consequently, a higher fluorescence signal may be detected by photodiode **320**. In some embodiments, the line width of the fluorescence signal detected may be in the range described and the higher signal-to-noise ratio described herein may be achieved. Moreover, system **300** may be more readily miniaturized. For example, the length of chamber **330** in the direction of propagation of the laser signal(s) **240** may be in the ranges described herein. Therefore, system **300** may not only have improved performance, but may also be more readily integrated with technologies, such as a PIC. In addition, system **300** may be more rapidly stabilized and readily used.

(29) FIGS. **4-6** depict end views of embodiments of systems **400**, **500**, and **600**, respectively, for performing atomic fluorescence spectroscopy. For simplicity, FIGS. **4-6** are not to scale. Systems **400**, **500**, and **600** are analogous to systems **100**, **200**, and/or **300**. Consequently, analogous components have similar labels. Systems **400**, **500**, and **600** each includes spectroscopy cells **410**, **510**, and **610**; photodiodes **420**, **520**, and **620**; and mirror(s) **430**, **530** and **532**, and **630** that are analogous to cells **110**, **210** and **310**, photodiode(s) **120** and **220**, and mirror(s) **130**, **230**, and **330**. Also shown are laser signal(s) **440**, **540**, and **640** that are analogous to laser signal(s) **140**, **240**, and **340**. In some embodiments, systems **400**, **500**, and/or **600** may have mirrors at opposite ends, analogous to mirrors(s) **350** and **352**. Systems **400**, **500**, and **600** operate in an analogous manner to systems **100**, **200**, and/or **300**.

(30) Systems **400**, **500**, and **600** indicate that the mirrors **420**, **530** and **532**, and **630** may have various configurations. For example, mirror **420** is trapezoidal in shape. Mirrors **530** and **532** are triangular in cross-section. However, mirrors **530** and **532** differ from mirrors **220** and **320** in that separate mirrors instead of a single mirror are used. Mirror **630** is parabolic in shape. Other configurations may be used.

(31) Systems **400**, **500**, and **600** may thus share the benefits of the systems **100**, **200**, and **300**. For example, higher signal-to-noise ratios may be achieved for smaller cell sizes. Therefore, systems **400**, **500**, and **600** may not only have improved performance, but may also be more readily integrated with technologies, such as a PIC. System **400**, **500**, and **600** may also be more rapidly stabilized and readily used.

(32) FIGS. **7A-7B** depict side and end views of an embodiment of system **700** for performing atomic fluorescence spectroscopy. For simplicity, FIGS. **7A-7B** are not to scale. System **700** is

analogous to systems **100, 200, 300, 400, 500, and/or 600**. Consequently, analogous components have similar labels. System **700** includes spectroscopy cell **710**, photodiode **720**, and mirror(s) **730, 732, 734, 736, and 738**, that are analogous to cells **110, 210, 310, 410, 510, and 610**; photodiode(s) **120, 220, 320, 420, and 520**; and mirror(s) **130, 230, 330, 430, 530 and 532, and 630**. Also shown are laser signal(s) **740** that are analogous to laser signal(s) **140, 240, 340, 440, 540, and 640**. In some embodiments, system **700** may have mirrors at opposite ends, analogous to mirrors(s) **350 and 352**. System **700** operates in an analogous manner to systems **100, 200, 300, 400, 500, and/or 600**.

(33) In system **700**, mirrors **730, 732, 734, 736, and 738** are external to chamber **712**. Thus, walls of chamber **712** may be transparent to fluorescent light from the vapor within chamber **712**.

However, mirrors **730, 732, 734, 736, and 738** still direct fluorescent light toward photodiode **720**.

(34) System **700** may thus share the benefits of the systems **100, 200, 300, 400, 500, and 600**. For example, higher signal-to-noise ratios may be achieved for smaller cell sizes. Therefore, system **700** may not only have improved performance, but may also be more readily integrated with technologies, such as a PIC.

(35) FIG. **8** depicts a perspective view of an embodiment of system **801** that incorporates a system for performing atomic fluorescence spectroscopy and a PIC. For simplicity, FIG. **8** is not to scale. System **801** includes atomic fluorescence spectroscopy system **800** and PIC **850**. System **800** is analogous to systems **100, 200, 300, 400, 500, 600, and/or 700**. Consequently, analogous components have similar labels. System **800** includes spectroscopy cell **810**, photodiode **820**, and mirror(s) **830** that are analogous to cells **110, 210, 310, 410, 510, 610, and 710**; photodiode(s) **120, 220, 320, 420, 520, and 620**; and mirror(s) **130, 230, 330, 430, 530 and 532, 630, and 730, 732, 734, 736, and 738**. Also shown is transparent cover **816** that is part of cell **810**. Thus, in the embodiment shown, photodiode **820** is external to chamber **812**. Photodiode **820** may be affixed to or part of PIC **850**. In some embodiments, therefore, photodiode **820** might be considered part of PIC **850**. In some embodiments, system **800** may have mirrors at opposite ends, analogous to mirrors(s) **350 and 352**.

(36) PIC **850** includes waveguides **852 and 854** as well as output gratings **860 and 862**. Waveguides **852 and 854** guide laser signals through PIC **850**. Output gratings **860 and 862** couple optical signals in waveguides **852 and 854** out-of-plane and into chamber **812** as laser signal(s) **840**.

Similarly, output gratings **860 and 862** couple laser signal(s) **840** in chamber **812** into waveguides **852 and 854**. Thus, although termed output gratings, components **860 and 862** couple laser signals between PIC **850** and chamber **812**. Although not shown, PIC **850** may include additional and/or different components.

(37) System **800** operates in an analogous manner to systems **100, 200, 300, 400, 500, 600, and/or 700**. Thus, PIC **850** carries laser signals in waveguides **852 and 854**. The laser signals are output via output gratings **860 and 862**. Laser signal(s) **840** reflect off of mirrors at opposite ends of chamber **812** and are transmitted to output gratings **862 and 860**. Laser signal(s) **840** cause vapor in chamber **812** to fluoresce. Mirror(s) **830** reflect fluoresced light to photodiode **820**.

(38) System **800** may thus share the benefits of the systems **100, 200, 300, 400, 500, 600, and 700**. For example, higher signal-to-noise ratios may be achieved for smaller cell sizes. Therefore, system **800** may not only have improved performance, but may also be more readily integrated with PIC **850** into system **801**. In addition, system **800** may be more rapidly and readily used. Moreover, system **800** and PIC **850** may be readily assembled. For example, system **800** may be aligned and affixed to PIC **850**. Consequently, fabrication of systems **800 and 801** may be facilitated.

(39) FIG. **9** is a flow chart depicting an embodiment of method **900** for providing an atomic fluorescence spectroscopy system. Steps of method **900** are shown in a particular order. In some embodiments, another order may be used. Further additional steps may be performed and/or some steps omitted. Steps of method **900** may also include substeps.

(40) A chamber for an atomic fluorescence spectroscopy cell is provided, at **902**. In some

embodiments, **902** includes removing a portion of a substrate. Other shapes may be used. Mirrors are provided for the system, at **904**. In some embodiments, such mirrors include mirrors used to redirect fluorescent light. In some embodiments, **904** also include forming mirrors used to direct laser signal(s). Mirrors for redirecting laser signal(s) may be provided, at **906**. In some embodiments, **904** and **906** may be combined. For example, **906** may include coating the inner surface of the chamber with reflective material.

(41) A photodiode for the system is provided, at **908**. In some embodiments, **908** includes sealing the chamber formed in **902** using the photodiode provided at **908**. In such embodiments, **908** also includes introducing the desired vapor into the chamber. In some embodiments, the photodiode may be formed as part of a different device, such as a PIC.

(42) The spectroscopy system may be integrated with another device, at **910**. For example, the system may be sealed, aligned with the desired structures, and affixed to the other device. Thus, using method **900**, an improved atomic fluorescence spectroscopy system may be provided.

(43) For example, system **300** may be formed using method **900**. At **902**, a v-groove is formed in a substrate. At **904**, mirrors **330** are formed. Mirrors **350** and **352** may also be formed, at **906**. In some embodiments, **904** and **906** are combined. For example, the interior surfaces of cell **310** may be coated with a reflective material. At **908** photodiode **320** may be provided. As part of **908**, photodiode **320** is affixed to cell **310** after a vapor has been introduced and mirrors **330**, **350** and **352** formed. In other embodiments, the chamber may be sealed separately from the photodiode being provided. For example, for spectroscopy system **800**, glass cover **816** may be used to seal chamber **812**. Photodiode **820** may be provided as part of formation of PIC **850**. At **910**, the spectroscopy system may be integrated with another device. For example, system **800** may be placed such that chamber **812** is aligned with output gratings **860** and **862** and affixed to PIC **850**.

(44) Thus, method **900** may be used to fabricate an atomic fluorescence spectroscopy system, such as system(s) **100**, **200**, **300**, **400**, **500**, **600**, **700**, and/or **800**. Consequently, the benefits of such systems may be achieved.

(45) Although the foregoing embodiments have been described in some detail for purposes of clarity of understanding, the invention is not limited to the details provided. There are many alternative ways of implementing the invention. The disclosed embodiments are illustrative and not restrictive.

Claims

1. A spectroscopy system, comprising: a cell having a plurality of walls and forming a chamber therein, the chamber being configured to receive at least one laser signal and retaining a vapor therein, the vapor fluorescing in response to the at least one laser signal; a photodiode; and a plurality of mirrors configured to direct fluorescent light from the vapor toward the photodiode; wherein the chamber has a length in a direction of propagation of the at least one laser signal not exceeding ten millimeters.
2. The spectroscopy system of claim 1, further comprising: a first mirror; and a second mirror opposite to the first mirror, the first mirror and the second mirror reflecting the at least one laser signal such that laser beams propagate in opposing directions in the chamber.
3. The spectroscopy system of claim 1, wherein the plurality of mirrors is external to the chamber.
4. The spectroscopy system of claim 1, wherein the length does not exceed five millimeters.
5. The spectroscopy system of claim 1, wherein the cell is integrated with a photonic integrated circuit.
6. The spectroscopy system of claim 1, wherein a mirror cross section of the plurality of mirrors forms a first portion of a geometric shape in a plane perpendicular to a direction of propagation of the at least one laser signal and a photodiode cross section forms a second portion of the geometric shape in the plane perpendicular to the direction of propagation, the second portion being opposite

to the first portion, the geometric shape being selected from a triangle, a trapezoid, and a paraboloid.

7. The spectroscopy system of claim 2, wherein the plurality of mirrors is internal to the chamber.

8. The spectroscopy system of claim 5, wherein the photonic integrated circuit further includes: a first output grating for coupling a first laser signal of the at least one laser signal to the chamber; and a second output grating for coupling a second laser signal of the at least one laser signal to the chamber.

9. A photonic integrated circuit (PIC), comprising: a plurality of output gratings residing on a substrate, the plurality of output gratings being configured to couple at least one laser signal out-of-plane with respect to the substrate, thereby providing at least one out-of-plane laser signal; and a PIC spectroscopy system coupled to a surface of the PIC, the PIC spectroscopy system including a cell, a photodiode, and a plurality of mirrors, the cell having a plurality of walls and forming a chamber therein, the chamber being aligned with the plurality of output gratings and retaining a vapor, the vapor fluorescing in response to the at least one out-of-plane laser signal, the plurality of mirrors being configured to direct fluorescent light from the vapor to the photodiode.

10. The PIC of claim 9, wherein the PIC spectroscopy system further includes: a first mirror; and a second mirror opposite to the first mirror, the first mirror and the second mirror reflecting the at least one out-of-plane laser signal such that laser beams propagate in opposing directions in the chamber.

11. The PIC of claim 9, wherein the chamber has a length in a direction of propagation of the at least one out-of-plane laser signal not exceeding five millimeters.

12. The PIC of claim 9, wherein a mirror cross section of the plurality of mirrors forms a first portion of a geometric shape and a photodiode cross section forms a second portion of the geometric shape in a plane perpendicular to a direction of propagation of the at least one out-of-plane laser signal, the second portion being opposite to the first portion, the geometric shape being selected from a triangle, a trapezoid, and a paraboloid.

13. The PIC of claim 10, wherein the first mirror, the second mirror, and the plurality of mirrors are internal to the chamber.

14. A method for providing a spectroscopy system, comprising: providing a cell having a plurality of walls and forming a chamber therein, the chamber being configured to receive at least one laser signal and to retain a vapor therein, the vapor fluorescing in response to the at least one laser signal; coupling a plurality of mirrors to the plurality of walls; providing a photodiode, the plurality of mirrors being oriented to direct fluorescent light from the vapor toward the photodiode; and mounting the cell on a photonic integrated circuit, where the mounting includes aligning the chamber with a plurality of output gratings for the photonic integrated circuit.

15. The method of claim 14, further comprising: providing a first mirror; and providing a second mirror opposite to the first mirror, the first mirror and the second mirror reflecting the at least one laser signal such that laser beams propagate in opposing directions in the chamber.

16. The method of claim 14, wherein the providing the cell further includes removing a portion of a vacuum chamber substrate to provide the chamber; and wherein the providing the photodiode further includes: mounting the photodiode to the vacuum chamber substrate.

17. The method of claim 15, wherein the providing the plurality of mirrors further includes: mounting plurality of mirrors on at least a portion of the plurality of walls of the chamber.
