

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12411488
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Suehiro; Yuki et al.

Control device, control method, and non-transitory computer-readable recording medium

Abstract

A control device controls a moving body being a target of a remote operation performed by a remote operator. During the remote operation of the moving body, the control device performs a communication with a remote operator terminal on the remote operator side to receive remote operation information including a first operation amount caused by the remote operator. The control device acquires a delay amount of a communication from the remote operator terminal to the moving body based on a result of reception of the remote operation information. The control device executes a delay compensation process that compensates for a delay of the first operation amount based on the delay amount to calculate a first correction operation amount. The control device controls the moving body based on the first correction operation amount.

Inventors:	Suehiro; Yuki (Ichikawa, JP), Watanabe; Toshinobu (Tokyo-to, JP)
Applicant:	TOYOTA JIDOSHA KABUSHIKI KAISHA (Toyota, JP)
Family ID:	87558491
Assignee:	TOYOTA JIDOSHA KABUSHIKI KAISHA (Toyota, JP)
Appl. No.:	18/081122
Filed:	December 14, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230259124 A1	Aug. 17, 2023

Foreign Application Priority Data

JP	2022-020780	Feb. 14, 2022
----	-------------	---------------

Publication Classification

Int. Cl.: G05D1/00 (20240101)

U.S. Cl.:

CPC G05D1/0022 (20130101); G05D1/0061 (20130101);

Field of Classification Search

CPC: G05D (1/0022); G05D (1/0061); G05B (19/0423); G05B (2219/25257)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2005/0119801	12/2004	Florentin	348/148	G05D 1/0282
2017/0192423	12/2016	Rust	N/A	G05D 1/0212
2017/0293295	12/2016	Tani	N/A	N/A
2019/0146485	12/2018	Yoneda et al.	N/A	N/A
2019/0361436	12/2018	Ueda	N/A	G08G 1/09
2021/0037495	12/2020	Pfadler	N/A	H04W 56/0065
2022/0135067	12/2021	Pfadler	701/23	G07C 5/008

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2004-295360	12/2003	JP	N/A
2016-071585	12/2015	JP	N/A
2019012514	12/2018	JP	N/A
2021-061516	12/2020	JP	N/A

OTHER PUBLICATIONS

Yaakov Bar-Shalom, "Update with Out-of-Sequence Measurements in Tracking: Exact Solution", IEEE Transactions on Aerospace and Electronic Systems, Jul. 2002, pp. 769-778, vol. 38, No. 3. cited by applicant

Keshu Zhang et al., "Optimal Update with Out-of-Sequence Measurements", IEEE Transactions on Signal Processing, Jun. 2005, pp. 1992-2004, vol. 53, No. 6. cited by applicant

Primary Examiner: Antonucci; Anne Marie

Assistant Examiner: Mohl; Patrick Daniel

Attorney, Agent or Firm: Sughrue Mion, PLLC

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION

(1) This application claims priority to Japanese Patent Application No. 2022-020780 filed on Feb.

14, 2022, the entire contents of which are incorporated by reference herein.

BACKGROUND

Technical Field

(2) The present disclosure relates to a technique for controlling a moving body that is a target of a remote operation performed by a remote operator.

Background Art

(3) Patent Literature 1 discloses a driving control system for remotely controlling a vehicle. A remote operation device and a driving control device on the vehicle side perform wireless communication. The driving control device calculates a delay time of the wireless communication with the remote operation device. When the delay time is equal to or longer than a threshold, the driving control device changes driving control of the vehicle from normal control to safety control. For example, the safety control decreases the vehicle speed as compared with the case of the normal control.

(4) In addition, techniques related to a remote operation of a vehicle are disclosed in Patent Literature 2 and Patent Literature 3.

(5) In a field of metrology, a Kalman filter is generally known. The Kalman filter estimates a state of a system from measurement data. However, there is a gap between a data measurement timing and an operation timing of the Kalman filter, and the estimation accuracy decreases as the gap increases.

(6) Non-Patent Literature 1 and Non-Patent Literature 2 disclose a “delayed Kalman filter” that can be applied to measurement data including a delay. The delayed Kalman filter is also called OOSM (Out-of-Sequence Measurement).

LIST OF RELATED ART

(7) Patent Literature 1: Japanese Laid-Open Patent Application No. JP-2016-071585

(8) Patent Literature 2: Japanese Laid-Open Patent Application No. JP-2004-295360

(9) Patent Literature 3: Japanese Laid-Open Patent Application No. JP-2021-061516

(10) Non-Patent Literature 1: Yaakov Bar-Shalom, “Update with Out-of-Sequence Measurements in Tracking: Exact Solution,” IEEE Transactions on Aerospace and Electronic Systems, VOL. 38, No. 3, pp. 769-778, July 2002.

(11) Non-Patent Literature 2: Keshu Zhang et “Optimal Update with Out-of-Sequence Measurements,” IEEE Transactions on Signal Process, Vol. 53, No. 6, pp. 1992-2004, June 2005.

SUMMARY

(12) A remote operation of a moving body (e.g., a vehicle, a robot) performed by a remote operator is considered. A remote operation system includes a moving body being a target of the remote operation and a remote operator terminal on the remote operator side. During the remote operation, the moving body and the remote operator terminal communicate with each other. The moving body acquires information of an operation amount caused by the remote operator from the remote operator terminal and performs control in accordance with the operation amount.

(13) There is a delay in a communication from the remote operator terminal to the moving body. Therefore, it takes time for the operation amount input by the remote operator to be actually reflected in moving body control. As a result, the remote operation of the moving body by the remote operator may be awkward. In some case, the moving body may meander. This is not preferable from a view point of safety of the remote operation of the moving body.

(14) An object of the present disclosure is to provide a technique that enables a remote operator to perform a remote operation of a moving body more smoothly and more safely.

(15) A first aspect is directed to a control device that controls a moving body being a target of a remote operation performed by a remote operator.

(16) The control device includes one or more processors.

(17) The one or more processors are configured to:

(18) during the remote operation of the moving body, perform a communication with a remote

operator terminal on a side of the remote operator to receive remote operation information including a first operation amount caused by the remote operator;

(19) acquire a delay amount of a communication from the remote operator terminal to the moving body based on a result of reception of the remote operation information;

(20) execute a delay compensation process that compensates for a delay of the first operation amount based on the delay amount to calculate a first correction operation amount; and

(21) control the moving body based on the first correction operation amount.

(22) A second aspect is directed to a control method for controlling a moving body being a target of a remote operation performed by a remote operator.

(23) The control method includes:

(24) during the remote operation of the moving body, performing a communication with a remote operator terminal on a side of the remote operator to receive remote operation information including a first operation amount caused by the remote operator;

(25) acquiring a delay amount of a communication from the remote operator terminal to the moving body based on a result of reception of the remote operation information;

(26) a delay compensation process that compensates for a delay of the first operation amount based on the delay amount to calculate a first correction operation amount; and

(27) controlling the moving body based on the first correction operation amount.

(28) A third aspect is directed to a control program for controlling a moving body being a target of a remote operation performed by a remote operator.

(29) The control program, when executed by a computer, causes the computer to:

(30) during the remote operation of the moving body, perform a communication with a remote operator terminal on a side of the remote operator to receive remote operation information including a first operation amount caused by the remote operator;

(31) acquire a delay amount of a communication from the remote operator terminal to the moving body based on a result of reception of the remote operation information;

(32) execute a delay compensation process that compensates for a delay of the first operation amount based on the delay amount to calculate a first correction operation amount; and

(33) control the moving body based on the first correction operation amount.

(34) According to the present disclosure, the delay compensation process that compensates for the delay of the first operation amount caused by the remote operator is executed in the moving body. The moving body is controlled based on the first correction operation amount acquired by the delay compensation process. As a result, the remote operator is able to perform the remote operation of the moving body more smoothly and more safely. Meandering of the moving body also is suppressed. That is, according to the present disclosure, safety of the remote operation of the moving body is improved.

Description

BRIEF DESCRIPTION OF DRAWINGS

- (1) FIG. 1 is a schematic diagram showing a configuration example of a remote operation system according to an embodiment of the present disclosure;
- (2) FIG. 2 is a block diagram showing a configuration example of a vehicle according to an embodiment of the present disclosure;
- (3) FIG. 3 is a conceptual diagram for explaining a problem;
- (4) FIG. 4 is a conceptual diagram for explaining a delay compensation process in a vehicle according to an embodiment of the present disclosure;
- (5) FIG. 5 is a conceptual diagram for explaining a delay compensation process and an upsampling process in a vehicle according to an embodiment of the present disclosure;

- (6) FIG. 6 is a block diagram showing an example of a functional configuration related to a delay compensation process in a vehicle according to the embodiment of the present disclosure;
- (7) FIG. 7 is a block diagram showing a configuration example of a delay compensation unit according to an embodiment of the present disclosure;
- (8) FIG. 8 is a conceptual diagram for explaining an abnormality determination process and an operation amount coordinating process in a vehicle according to the embodiment of the present disclosure;
- (9) FIG. 9 is a block diagram showing an example of a functional configuration related to an abnormality determination process and an operation amount coordinating process in a vehicle according to an embodiment of the present disclosure;
- (10) FIG. 10 is a flowchart showing an example of a communication abnormality determination process according to an embodiment of the present disclosure;
- (11) FIG. 11 is a flowchart showing an example of a communication abnormality determination process according to an embodiment of the present disclosure;
- (12) FIG. 12 is a flowchart showing an example of a terminal abnormality determination process according to an embodiment of the present disclosure;
- (13) FIG. 13 is a flowchart showing an example of a vehicle abnormality determination process according to an embodiment of the present disclosure;
- (14) FIG. 14 is a diagram for explaining an example of an operation amount coordinating process according to an embodiment of the present disclosure;
- (15) FIG. 15 is a block diagram showing an example of a functional configuration related to a variety of processes in a vehicle according to an embodiment of the present disclosure; and
- (16) FIG. 16 is a block diagram showing a configuration example of a remote operator terminal according to an embodiment of the present disclosure.

EMBODIMENTS

(17) Embodiments of the present disclosure will be described with reference to the accompanying drawings.

1. OVERVIEW OF REMOTE OPERATION SYSTEM

(18) A remote operation (remote driving) of a moving body is considered. Examples of the moving body being a target of the remote operation include a vehicle, a robot, a flying object, and the like. The vehicle may be an autonomous driving vehicle or may be a vehicle driven by a driver. Examples of the robot include a logistics robot, a work robot, and the like. Examples of the flying object include an airplane, a drone, and the like.

(19) As an example, in the following description, a case where the moving body being the target of the remote operation is a vehicle will be considered. When generalizing, “vehicle” in the following description shall be deemed to be replaced with “moving body.”

(20) FIG. 1 is a schematic diagram showing a configuration example of a remote operation system 1 according to the present embodiment. The remote operation system 1 includes a vehicle 100, a remote operator terminal 200, and a management device 300. The vehicle 100 is the target of the remote operation. The remote operator terminal 200 is a terminal device used by a remote operator O when remotely operating the vehicle 100. The remote operator terminal 200 can also be referred to as a remote operation human machine interface (HMI). The management device 300 manages the remote operation system 1. The management of the remote operation system 1 includes, for example, assigning a remote operator O to a vehicle 100 that requires the remote operation. The management device 300 is able to communicate with the vehicle 100 and the remote operator terminal 200 via a communication network. Typically, the management device 300 is a management server on a cloud. The management server may be configured by a plurality of servers that perform distributed processing.

(21) Various sensors including a camera are installed on the vehicle 100. The camera images a situation around the vehicle 100 to acquire image information indicating the situation around the

vehicle **100**. Vehicle information VCL is information acquired by the various sensors and includes the image information captured by the camera. The vehicle **100** transmits the vehicle information VCL to the remote operator terminal **200** via the management device **300**. That is, the vehicle **100** transmits the vehicle information VCL to the management device **300**, and the management device **300** transfers the received vehicle information VCL to the remote operator terminal **200**.

(22) The remote operator terminal **200** receives the vehicle information VCL transmitted from the vehicle **100**. The remote operator terminal **200** presents the vehicle information VCL to the remote operator O. More specifically, the remote operator terminal **200** includes a display device, and displays the image information and the like on the display device. The remote operator O views the displayed information, recognizes the situation around the vehicle **100**, and performs remote operation of the vehicle **100**. The remote operation information OPE is information relating to remote operation by the remote operator O. For example, the remote operation information OPE includes an amount of operation performed by the remote operator O. The remote operator terminal **200** transmits the remote operation information OPE to the vehicle **100** via the management device **300**. That is, the remote operator terminal **200** transmits the remote operation information OPE to the management device **300**, and the management device **300** transfers the received remote operation information OPE to the vehicle **100**.

(23) The vehicle **100** receives the remote operation information OPE transmitted from the remote operator terminal **200**. The vehicle **100** performs vehicle travel control in accordance with the received remote operation information OPE. In this manner, the remote operation of the vehicle **100** is realized.

2. EXAMPLE OF VEHICLE

2-1. Configuration Example

(24) FIG. 4 is a block diagram showing a configuration example of the vehicle **100**. The vehicle **100** includes a communication device **101**, a sensor group **102**, a travel device **103**, and a control device (controller) **105**.

(25) The communication device **101** communicates with the outside of the vehicle **100**. For example, the communication device **101** communicates with the remote operator terminal **200** and the management device **300**.

(26) The sensor group **102** includes a recognition sensor, a vehicle state sensor, a position sensor, and the like. The recognition sensor recognizes (detects) a situation around the vehicle **100**. Examples of the recognition sensor include the camera, a laser imaging detection and ranging (LIDAR), a radar, and the like. The vehicle state sensor detects a state of the vehicle **100**. Examples of the vehicle state sensor include a speed sensor, an acceleration sensor, a yaw rate sensor, a steering angle sensor, and the like. The position sensor detects a position and an orientation of the vehicle **100**. For example, the position sensor includes a global navigation satellite system (GNSS).

(27) The travel device **103** includes a steering device, a driving device, and a braking device. The steering device turns wheels. For example, the steering device includes an electric power steering (EPS) device. The driving device is a power source that generates a driving force. Examples of the drive device include an engine, an electric motor, an in-wheel motor, and the like. The braking device generates a braking force.

(28) The control device **105** is a computer that controls the vehicle **100**. The control device **105** includes one or more processors **106** (hereinafter simply referred to as a processor **106**) and one or more memory devices **107** (hereinafter simply referred to as a memory device **107**). The processor **106** executes a variety of processing. For example, the processor **106** includes a central processing unit (CPU). The memory device **107** stores a variety of information necessary for the processing by the processor **106**. Examples of the memory device **107** include a volatile memory, a non-volatile memory, a hard disk drive (HDD), a solid state drive (SSD), and the like. The control device **105** may include one or more electronic control units (ECUs).

(29) A vehicle control program PROG1 is a computer program executed by the processor **106**. The

functions of the control device **105** are implemented by the processor **106** executing the vehicle control program **PROG1**. The vehicle control program **PROG1** is stored in the memory device **107**. The vehicle control program **PROG1** may be recorded on a non-transitory computer-readable recording medium.

2-2. Driving Environment Information

(30) The control device **105** uses the sensor group **102** to acquire driving environment information **ENV** indicating a driving environment for the vehicle **100**. The driving environment information **ENV** is stored in the memory device **107**.

(31) The driving environment information **ENV** includes surrounding situation information indicating a result of recognition by the recognition sensor. For example, the surrounding situation information includes the image information captured by the camera. The surrounding situation information further includes object information regarding an object around the vehicle **100**. Examples of the object around the vehicle **100** include a pedestrian, another vehicle (e.g., a preceding vehicle, a parked vehicle, etc.), a white line, a traffic signal, a sign, a roadside structure, and the like. The object information indicates a relative position and a relative velocity of the object with respect to the vehicle **100**.

(32) In addition, the driving environment information **ENV** includes vehicle state information indicating the vehicle state detected by the vehicle state sensor.

(33) Furthermore, the driving environment information **ENV** includes vehicle position information indicating the position and the orientation of the vehicle **100**. The vehicle position information is acquired by the position sensor. Highly accurate vehicle position information may be acquired by performing a well-known localization using map information and the surrounding situation information (the object information).

2-3. Vehicle Travel Control

(34) The control device **105** executes vehicle travel control that controls travel of the vehicle **100**. The vehicle travel control includes steering control, driving control, and braking control. The control device **105** executes the vehicle travel control by controlling the travel device **103** (i.e., the steering device, the driving device, and the braking device).

(35) The control device **105** may execute autonomous driving control based on the driving environment information **ENV**. More specifically, the control device **105** generates a travel plan of the vehicle **100** based on the driving environment information **ENV**. Further, the control device **105** generates, based on the driving environment information **ENV**, a target trajectory required for the vehicle **100** to travel in accordance with the travel plan. The target trajectory includes a target position and a target speed. Then, the control device **105** executes the vehicle travel control such that the vehicle **100** follows the target trajectory.

2-4. Processing Related to Remote Operation

(36) Hereinafter, the case where the remote operation of the vehicle **100** is performed will be described. The control device **105** communicates with the remote operator terminal **200** via the communication device **101**.

(37) The control device **105** transmits the vehicle information **VCL** to the remote operator terminal **200**. The vehicle information **VCL** is information necessary for the remote operation by the remote operator **O**, and includes at least a part of the driving environment information **ENV** described above. For example, the vehicle information **VCL** includes the surrounding situation information (especially, the image information). The vehicle information **VCL** may further include the vehicle state information and the vehicle position information.

(38) In addition, the control device **105** receives the remote operation information **OPE** from the remote operator terminal **200**. The remote operation information **OPE** is information regarding the remote operation by the remote operator **O**. For example, the remote operation information **OPE** includes an amount of operation performed by the remote operator **O**. The control device **105** performs the vehicle travel control in accordance with the received remote operation information

OPE.

(39) Hereinafter, improvement in safety of the remote operation of the vehicle **100** will be described in detail.

3. DELAY COMPENSATION PROCESS AND UPSAMPLING PROCESS

3-1. Overview

(40) First, a problem to be examined in this section will be described with reference to a comparative example shown in FIG. 3. A horizontal axis represents time, and a vertical axis represents the operation amount caused by the remote operator O. The operation amount caused by the remote operator O is hereinafter referred to as a “first operation amount X1.” The first operation amount X1 is included in the remote operation information OPE transmitted from the remote operator terminal **200** to the vehicle **100**. The control device **105** of the vehicle **100** performs the vehicle travel control in accordance with the first operation amount X1 included in the received remote operation information OPE.

(41) An upper diagram of FIG. 3 illustrates a time variation of the first operation amount X1 on the remote operator O side. A circle in the upper diagram indicates the first operation amount X1 to be transmitted to the vehicle **100** and a transmission timing thereof. On the other hand, a lower diagram illustrates a time variation of the first operation amount X1 used for the control in the vehicle **100**. A circle in the lower diagram indicates the first operation amount X1 received by the vehicle **100** and a reception timing thereof.

(42) A first problem is a delay of the communication from the remote operator terminal **200** to the vehicle **100**. A delay amount DL of the communication is not constant but varies depending on the communication state. As shown in FIG. 3, the first operation amount X1 on the vehicle **100** side is delayed from the first operation amount X1 on the remote operator O side by the delay amount DL. That is, it takes at least the time of the delay amount DL for the first operation amount X1 input by the remote operator O to be actually reflected in the vehicle control. As a result, the remote operation of the vehicle **100** by the remote operator O may be awkward. In some cases, the vehicle **100** may meander. These are undesirable from the viewpoint of the safety of the remote operation of the vehicle **100**.

(43) A second problem is a difference between a communication cycle and a control cycle. In general as shown in FIG. 3, the communication cycle of the remote operation information OPE (i.e., the first operation amount X1) is longer than the control cycle for controlling the vehicle **100**. In other words, a control frequency of controlling the vehicle **100** is higher than a communication frequency of the remote operation information OPE. Therefore, the first operation amount X1 used for the controlling in the vehicle **100** deviates from an actual first operation amount X1 input by the remote operator O. The deviation of the first operation amount X1 increases as the difference between the communication cycle and the control cycle increases. Further, the deviation of the first operation amount X1 increases as the delay amount DL of the communication increases. Such the deviation of the first operation amount X1 may also cause the awkward remote operation of the vehicle **100** by the remote operator O. In some cases, the vehicle **100** may meander. These are undesirable from the viewpoint of the safety of the remote operation of the vehicle **100**.

(44) The vehicle **100** according to the present embodiment is configured to solve at least one of the problems described above.

(45) FIG. 4 is a conceptual diagram for explaining a “delay compensation process” in the vehicle **100** according to the present embodiment. The control device **105** of the vehicle **100** is configured to compensate for the delay of the first operation amount X1 on the vehicle **100** side. More specifically, the control device **105** acquires information of the delay amount DL of the communication based on a result of reception of the remote operation information OPE from the remote operator terminal **200**. Then, the control device **105** compensates for the delay of the first operation amount X1 based on the delay amount DL. This process is the delay compensation process. The control device **105** controls the vehicle **100** based on the first operation amount X1

after the delay compensation process. The first problem is solved by the delay compensation process. It should be noted that a specific example of the delay compensation process will be described later.

(46) FIG. 5 is a conceptual diagram for explaining an “upsampling process” in the vehicle **100** according to the present embodiment. The control device **105** of the vehicle **100** is configured to increase a sampling frequency (sampling rate) of the first operation amount X1 by estimating (predicting) the first operation amount X1 in a non-sampling period. This process is the upsampling process. In particular, the control device **105** may perform the upsampling process such that a difference between the sampling cycle (the sampling frequency) of the first operation amount X1 and the control cycle (the control frequency) becomes smaller than the difference between the communication cycle (the communication frequency) and the control cycle (the control frequency). For example, the control device **105** performs the upsampling process such that the sampling cycle (the sampling frequency) of the first operation amount X1 coincides with the control cycle (the control frequency). The second problem is solved by the upsampling process. It should be noted that a specific example of the upsampling process will be described later.

(47) The control device **105** of the vehicle **100** according to the present embodiment is configured to execute at least one of the delay compensation process and the upsampling process. The control device **105** may be configured to perform both the delay compensation process and the upsampling process. As a result, the remote operator O is able to perform the remote operation of the vehicle **100** more smoothly and more safely. The meandering of the vehicle **100** also is suppressed. That is, according to the present embodiment, the safety of the remote operation of the vehicle **100** is improved.

3-2. Functional Configuration Example

(48) FIG. 6 is a block diagram showing an example of a functional configuration related to the delay compensation process in the vehicle **100**. The vehicle **100** includes, as functional blocks, a reception unit **110**, a delay compensation unit **120**, and a control unit **130**. These functional blocks are realized by the communication device **101** and the control device **105**.

(49) The reception unit **110** receives the remote operation information OPE transmitted from the remote operator terminal **200** during the remote operation of the vehicle **100**. The remote operation information OPE includes information on the first operation amount X1 caused by the remote operator O. The reception unit **110** grasps a state of the communication with the remote operator terminal **200** based on a result of reception of the remote operation information OPE. Examples of the communication state include presence or absence of data reception, the delay amount DL, a transmission speed, a radio wave reception intensity, and the like.

(50) The delay compensation unit **120** executes the delay compensation process. More specifically, the delay compensation unit **120** acquires the information on the first operation amount X1 and the delay amount DL from the reception unit **110**. The delay amount DL is not constant but varies depending on the communication state. The delay compensation unit **120** compensates for the delay of the first operation amount X1 based on the delay amount DL. Hereinafter, the first operation amount X1 whose delay is compensated for is referred to as a “first correction operation amount X1C.” It can be said that the delay compensation unit **120** calculates the first correction operation amount X1C by compensating for the delay of the first operation amount X1 based on the delay amount DL. The delay compensation unit **120** may perform the delay compensation process while performing the upsampling process. A specific example of the delay compensation unit **120** will be described in the following Section 3-3.

(51) The control unit **130** receives the first correction operation amount X1C after the delay compensation process. The control unit **130** performs the vehicle travel control in accordance with the first correction operation amount X1C.

3-3. Example of Delay Compensation Unit

(52) FIG. 7 is a block diagram showing a configuration example of the delay compensation unit

120. The delay compensation unit **120** shown in FIG. 7 is configured to perform the delay compensation process while performing the upsampling process. More specifically, the delay compensation unit **120** includes a correction unit **121**, an estimation unit **122**, and an output unit **123**.

(53) The correction unit **121** acquires the information of the first operation amount X_1 caused by the remote operator O that is received from the remote operator terminal **200**. Moreover, the correction unit **121** acquires information on the delay amount DL . The delay amount DL is not constant but varies depending on the communication state. The correction unit **121** performs the delay compensation process based on the first operation amount X_1 and the delay amount DL to calculate the first correction operation amount X_{1C} . The output unit **123** outputs the first correction operation amount X_{1C} .

(54) The estimation unit **122** estimates (predicts) the first correction operation amount X_{1C} in the non-sampling period based on the first correction operation amount X_{1C} output from the output unit **123**. That is, the estimation unit **122** performs the upsampling process. In particular, the estimation unit **122** performs the upsampling process such that a difference between the sampling frequency of the first correction operation amount X_{1C} and the control frequency becomes smaller than the difference between the communication frequency and the control frequency.

(55) For example, the estimation unit **122** holds an equation of motion representing a motion of the vehicle **100**. An estimate value of the first correction operation amount X_{1C} output from the estimation unit **122** is fed back to the estimation unit **122** through the output unit **123**. The estimation unit **122** estimates (predicts) a first correction operation amount X_{1C} of the next timing based on the equation of motion and the fed-back estimate value of the first correction operation amount X_{1C} . However, the estimate value of the first correction operation amount X_{1C} includes an error. The error is corrected by the correction unit **121**.

(56) More specifically, the estimate value of the first correction operation amount X_{1C} output from the estimation unit **122** is also input to the correction unit **121**. Meanwhile, the first operation amount X_1 (actual value) caused by the remote operator O that is received from the remote operator terminal **200** is also input to the correction unit **121**. Since the communication cycle is longer than the control cycle and the control frequency is higher than the communication frequency as described above, the first operation amount X_1 (actual value) is input to the correction unit **121** at a lower frequency than the estimate value of the first correction operation amount X_{1C} . The correction unit **121** calculates the first correction operation amount X_{1C} by correcting the estimate value of the first correction operation amount X_{1C} based on the first operation amount X_1 (actual value) while performing the delay compensation process based on the delay amount DL . The first correction operation amount X_{1C} calculated by the correction unit **121** is fed back to the estimation unit **122** through the output unit **123**. The estimation unit **122** performs the upsampling process based on the first correction operation amount X_{1C} output from the output unit **123**.

(57) As described above, the delay compensation unit **120** shown in FIG. 7 performs the delay compensation process while performing the upsampling process. The delay compensation unit **120** estimates the first correction operation amount X_{1C} in the non-sampling period by feeding back the estimate value of the first correction operation amount X_{1C} acquired by the upsampling process and the first correction operation amount X_1 acquired by the delay compensation process. Further, the delay compensation unit **120** calculates the first correction operation amount X_{1C} by correcting the estimate value of the first correction operation amount X_{1C} based on the first operation amount X_1 (actual value) while performing the delay compensation process based on the delay amount DL .

(58) The delay compensation unit **120** performing the upsampling process and the delay compensation process can be realized by using, for example, a delayed Kalman filter. The delayed Kalman filter is also called OOSM (Out-of-Sequence Measurement). For details of the delayed Kalman filter, refer to Non-Patent Literature 1 and Non-Patent Literature 2. The delayed Kalman filter can be applied also to the first operation amount X_1 whose delay amount DL varies. The

delay compensation unit **120** executes the upsampling process and the delay compensation process by applying a delayed Kalman filter to the first operation amount X1 whose delay amount DL varies.

(59) Supplementary information SUP may be used for improving accuracy of the estimation of the first correction operation amount X1C by the estimation unit **122**. For example, the supplementary information SUP includes a shape of a road on which the vehicle **100** moves. For example, when the vehicle **100** travels on a curved road, information on the shape of the curved road is used for estimating a future operation amount. The road shape is acquired, for example, from the surrounding situation information. Alternatively, the road shape may be acquired from the vehicle position information and map information. The supplementary information SUP may include a vehicle travel control amount which is a control amount of the travel device **103** (actuators) of the vehicle **100**. The vehicle travel control amount also is useful for the estimation process by the estimation unit **122**. The supplementary information SUP is provided from the control unit **130** to the delay compensation unit **120**. The estimation unit **122** estimates (predicts) the first correction operation amount X1C in consideration of the supplementary information SUP. Thus, the estimation accuracy of the first correction operation amount X1C is further improved.

3-4. Effects

(60) As described above, the control device **105** of the vehicle **100** according to the present embodiment is configured to execute at least one of the delay compensation process and the upsampling process. The control device **105** may be configured to perform both the delay compensation process and the upsampling process. As a result, the remote operator O is able to perform the remote operation of the vehicle **100** more smoothly and more safely. The meandering of the vehicle **100** also is suppressed. That is, according to the present embodiment, the safety of the remote operation of the vehicle **100** is improved.

4. ABNORMALITY DETERMINATION PROCESS AND OPERATION AMOUNT COORDINATING PROCESS

4-1. Overview

(61) Next, an “abnormality” that may occur in the remote operation system **1** will be considered. The abnormality is a concept including failure, malfunction, insufficiency, and trouble. Examples of the abnormality in the remote operation system **1** include a “communication abnormality” that is an abnormality in the communication between the vehicle **100** and the remote operator terminal **200**, a “vehicle abnormality” that is an abnormality in the vehicle **100**, and a “terminal abnormality” that is an abnormality in the remote operator terminal **200**.

(62) FIG. **8** is a conceptual diagram for explaining processing related to the abnormality in the remote operation system **1**. The control device **105** of vehicle **100** according to the present embodiment executes an “abnormality determination process” that determines whether or not the abnormality occurs in the remote operation system **1**. In particular, the control device **105** makes the determination while distinguishing the communication abnormality, the vehicle abnormality, and the terminal abnormality from each other. That is, the control device **105** determines whether or not at least one of the communication abnormality, the vehicle abnormality, and the user equipment abnormality occurs.

(63) When the abnormality occurs during the remote operation of the vehicle **100**, it is desirable to appropriately control the vehicle **100** to secure safety. Here, it is not always appropriate to control the vehicle **100** in accordance with the first operation amount X1 caused by the remote operator O. The reason is that, for example, when the terminal abnormality occurs, the first operation amount X1 transmitted from the remote operator terminal **200** may be abnormal. In some cases, it may be safer to delegate the vehicle driving to the autonomous driving function (autonomous travel function) of the vehicle **100**.

(64) In view of the above, the control device **105** of the vehicle **100** according to the present embodiment executes an “operation amount coordinating process” that appropriately determines a

final operation amount X according to a state of the abnormality. The first operation amount X1 is an operation amount caused by the remote operator O and is included in the remote operation information OPE. On the other hand, a second operation amount X2 is an operation amount determined (required) by the autonomous driving function of the vehicle **100**. In the operation amount coordinating process, the control device **105** determines a “final operation amount X” based on at least one of the first operation amount X1 and the second operation amount X2 according to a result of the abnormality determination process (that is, the state of the abnormality). Then, the control device **105** controls the vehicle **100** in accordance with the determined operation amount X.

(65) For example, when the terminal abnormality occurs, the safety is improved by controlling the vehicle **100** in accordance with the second operation amount X2 instead of the first operation amount X1. As another example, when the communication abnormality occurs, the safety is improved by controlling the vehicle **100** in accordance with the second operation amount X2 instead of the first operation amount X1.

(66) As described above, according to the present embodiment, the control device **105** of the vehicle **100** is configured to execute the abnormality determination process and the operation amount coordinating process. In the operation amount coordinating process, the control device **105** determines the “final operation amount X” based on at least one of the first operation amount X1 and the second operation amount X2 according to the result of the abnormality determination process. Then, the vehicle **100** is controlled in accordance with the determined operation amount X. It is thus possible to appropriately control the vehicle **100** in consideration of the state of the abnormality when the abnormality occurs in the remote operation system **1**.

4-2. Functional Configuration Example

(67) FIG. **9** is a block diagram showing an example of a functional configuration related to the abnormality determination process and the operation amount coordinating process in the vehicle **100**. The vehicle **100** includes, as functional blocks, a reception unit **110**, a control unit **130**, a communication abnormality determination unit **160**, a terminal abnormality determination unit **170**, and a vehicle abnormality determination unit **180**. These functional blocks are realized by the communication device **101** and the control device **105**.

(68) The reception unit **110** receives the remote operation information OPE transmitted from the remote operator terminal **200** during the remote operation of the vehicle **100**. The remote operation information OPE includes information on the first operation amount X1 caused by the remote operator O. The reception unit **110** grasps a state of the communication with the remote operator terminal **200** based on a result of reception of the remote operation information OPE. Examples of the communication state include presence or absence of data reception, the delay amount DL, a transmission speed, a radio wave reception intensity, and the like.

(69) The control unit **130** receives the information on the first operation amount X1 through the reception unit **110**. Moreover, the control unit **130** includes an autonomous driving control unit **140** and an operation amount coordinating unit **150**. The autonomous driving control unit **140** performs the above-described autonomous driving control based on the driving environment information ENV. An operation amount required by the autonomous driving control is the second operation amount X2. The operation amount coordinating unit **150** executes the operation amount coordinating process. That is, the operation amount coordinating unit **150** determines the “final operation amount X” based on at least one of the first operation amount X1 and the second operation amount X2.

(70) The communication abnormality determination unit **160** performs a “communication abnormality determination process.” More specifically, the communication abnormality determination unit **160** acquires information on the communication state from the reception unit **110**. Then, the communication abnormality determination unit **160** determines, based on the communication state, whether or not an abnormality occurs in the communication from the remote

operator terminal **200** to the vehicle **100**. A specific example of the communication abnormality determination process will be described later (see Section 4-3). A communication abnormality flag FL-C is information indicating a result of the communication abnormality determination process. The communication abnormality determination unit **160** outputs the communication abnormality flag FL-C to the operation amount coordinating unit **150**.

(71) The terminal abnormality determination unit **170** performs a “terminal abnormality determination process.” More specifically, the terminal abnormality determining unit **170** determines whether or not an abnormality occurs in the remote operator terminal **200** based on the first operation amount X1 included in the remote operation information OPE. A specific example of the terminal abnormality determination process will be described later (see Section 4-4). A terminal abnormality flag FL-T is information indicating a result of the terminal abnormality determination process. The terminal abnormality determination unit **170** outputs the terminal abnormality flag FL-T to the operation amount coordinating unit **150**.

(72) The vehicle abnormality determination unit **180** performs a “vehicle abnormality determination process.” More specifically, the vehicle abnormality determination unit **180** receives information on a vehicle travel control amount calculated by the control unit **130**. Then, the vehicle abnormality determination unit **180** determines, based on the vehicle travel control amount, whether or not an abnormality occurs in the vehicle travel control. A specific example of the vehicle abnormality determination process will be described later (see Section 4-5). A vehicle abnormality flag FL-V is information indicating a result of the vehicle abnormality determination process. The vehicle abnormality determination unit **180** outputs the vehicle abnormality flag FL-V to the operation amount coordinating unit **150**.

(73) The operation amount coordinating unit **150** executes the operation amount coordinating process based on the variety of abnormality flags FL-C, FL-T, and FL-V. That is, the operation amount coordinating unit **150** executes the operation amount coordinating process according to the results of the variety of abnormality determination processes. A specific example of the operation amount coordinating process will be described later (see Section 4-6).

(74) The control unit **130** controls the vehicle **100** in accordance with the final operation amount X output from the operation amount coordinating unit **150**.

4-3. Example of Communication Abnormality Determination Process

(75) FIG. **10** is a flowchart showing an example of the communication abnormality determination process performed by the communication abnormality determination unit **160**.

(76) In Step S110, the communication abnormality determination unit **160** determines whether or not the reception unit **110** receives data. When the reception unit **110** receives data (Step S110; Yes), the processing proceeds to Step S120. Otherwise (Step S110; No), the processing proceeds to Step S130.

(77) In Step S120, the communication abnormality determination unit **160** determines whether a reception state is good or not. The reception state is represented by a parameter such as the transmission speed, the radio wave reception intensity, and the like. When the parameter is equal to or greater than a predetermined threshold (Step S120; Yes), it is determined that the reception state is good, and the processing proceeds to Step S160. Otherwise (Step S120; No), the processing proceeds to Step S130.

(78) In Step S130, the communication abnormality determination unit **160** determines whether or not the non-data reception state or the not-good reception state continues for Ta seconds. When such the bad state continues for Ta seconds (Step S130; Yes), the processing proceeds to Step S140. On the other hand, when such the bad state has not yet continued for Ta seconds (Step S130; No), the processing proceeds to Step S150.

(79) In Step S140, the communication abnormality determination unit **160** determines (asserts) that the communication abnormality occurs.

(80) In Step S150, the communication abnormality determination unit **160** sets a current state to

“communication abnormality determination in progress” without confirming the determination.

After that, the processing returns to Step S110.

(81) FIG. 11 is a flowchart showing an example of Step S160. In Step S160, a delay amount DL of the communication is taken into consideration.

(82) In Step S161, the communication abnormality determination unit 160 acquires information on the delay amount DL of the communication from the reception unit 110.

(83) In Step S162, the communication abnormality determination unit 160 determines whether or not the delay amount DL exceeds a first threshold value DL_th1. The first threshold value DL_th1 is a delay amount DL where it can be determined that the communication abnormality occurs. For example, the first threshold value DL_th1 is a delay amount DL that cannot normally occur. When the delay amount DL exceeds the first threshold value DL_th1 (Step S162; Yes), the processing proceeds to Step S163. On the other hand, when the delay amount DL is equal to or less than the first threshold value DL_th1 (Step S162; No), the processing proceeds to Step S164.

(84) In Step S163, the communication abnormality determination unit 160 determines (asserts) that the communication abnormality occurs.

(85) In Step S164, the communication abnormality determination unit 160 determines whether or not the delay amount DL exceeds a second threshold value DL_th2. The second threshold value DL_th2 is smaller than the first threshold value DL_th1 described above. For example, the second threshold value DL_th2 is an upper limit value of an allowable range of the delay amount DL. When the delay amount DL exceeds the second threshold value DL_th2 (Step S164 Yes), the processing proceeds to Step S165. On the other hand, when the delay amount DL is equal to or less than the second threshold value DL_th2 (Step S164; No), the processing proceeds to Step S167.

(86) In Step S165, the communication abnormality determination unit 160 determines whether or not the state in which the delay amount DL exceeds the second threshold value DL_th2 continues for Tb seconds. When such the state continues for Tb seconds (Step S165; Yes), the processing proceeds to Step S163. On the other hand, when such the state has not yet continued for Tb seconds (Step S165; No), the processing proceeds to Step S166.

(87) In Step S166, the communication abnormality determination unit 160 sets the current state to “communication abnormality determination in progress” without confirming the determination. After that, the processing returns to Step S110.

(88) In Step S167, the communication abnormality determination unit 160 determines that no communication abnormality occurs and the communication is normal. After that, the processing returns to Step S110.

4-4. Example of Terminal Abnormality Determination Process

(89) FIG. 12 is a flowchart showing an example of the terminal abnormality determination process performed by the terminal abnormality determination unit 170.

(90) In Step S171, the terminal abnormality determination unit 170 receives the remote operation information OPE. Then, the terminal abnormality determination unit 170 acquires an “operation amount variation DX” that is a variation from a previous value of the first operation amount X1 caused by the remote operator O.

(91) In Step S172, the terminal abnormality determination unit 170 determines whether or not the operation amount variation DX exceeds a first threshold value DX_th1. The First threshold value DX_th1 is an operation amount variation DX where it can be determined that the terminal abnormality occurs. For example, the first threshold value DX_th1 is an operation amount variation DX that cannot normally occur. When the operation amount variation DX exceeds the First threshold value DX_th1 (Step S172; Yes), the processing proceeds to Step S173. On the other hand, when the operation amount variation DX is equal to or less than the first threshold value DX_th1 (Step S172; No), the processing proceeds to Step S174.

(92) In Step S173, the terminal abnormality determination unit 170 determines (asserts) that the terminal abnormality occurs.

(93) In Step S174, the terminal abnormality determination unit **170** determines whether or not the operation amount variation DX exceeds a second threshold value DX_th2. The second threshold value DX_th2 is smaller than the first threshold value DX_th1 described above. For example, the second threshold value DX_th2 is an upper limit value of an allowable range of the operation amount variation DX. When the operation amount variation DX exceeds the second threshold value DX_th2 (Step S174; Yes), the processing proceeds to Step S175. On the other hand, when the operation amount variation DX is equal to or less than the second threshold value DX_th2 (Step S174; No), the processing proceeds to Step S177.

(94) In Step S175, the terminal abnormality determination unit **170** determines whether or not the state in which the operation amount variation DX exceeds the second threshold value DX_th2 continues for Tc seconds. When such the state continues for Tc seconds (Step S175; Yes), the processing proceeds to Step S173. On the other hand, when such the state has not yet continued for Tc seconds (Step S175; No), the processing proceeds to Step S176.

(95) In Step S176, the terminal abnormality determination unit **170** sets the current state to “terminal abnormality determination in progress” without confirming the determination. After that, the processing returns to Step S171.

(96) In Step S177, the terminal abnormality determination unit **170** determines that no terminal abnormality occurs and the remote operator terminal **200** is normal. After that, the processing returns to Step S171.

4-5. Example of Vehicle Abnormality Determination Process

(97) FIG. **13** is a flowchart showing an example of the vehicle abnormality determination process performed by the vehicle abnormality determination unit **180**.

(98) In Step S181, the vehicle abnormality determination unit **180** receives information on the vehicle travel control amount calculated by the control unit **130**. Then, the vehicle abnormality determination unit **180** acquires a “control amount variation DC” that is a variation from a previous value of the vehicle travel control amount.

(99) In Step S182, the vehicle abnormality determination unit **180** determines whether or not the control amount variation DC exceeds a first threshold value DC_th1. The first threshold value DC_th1 is a control amount variation DC where it can be determined that the vehicle abnormality occurs. For example, the first threshold value DC_th1 is a control amount variation DC that cannot normally occur. When the control amount variation DC exceeds the first threshold value DC_th1 (Step S182; Yes), the processing proceeds to Step S183. On the other hand, when the control amount variation DC is equal to or less than the first threshold value DC_th1 (Step S182; No), the processing proceeds to Step S184.

(100) In Step S183, the vehicle abnormality determination unit **180** determines (asserts) that the vehicle abnormality occurs.

(101) In Step S184, the vehicle abnormality determination unit **180** determines whether or not the control amount variation DC exceeds a second threshold value DC_th2. The second threshold value DC_th2 is smaller than the first threshold value DC_th1 described above. For example, the second threshold value DC_th2 is an upper limit value of an allowable range of the control amount variation DC. When the control amount variation DC exceeds the second threshold value DC_th2 (Step S184; Yes), the processing proceeds to Step S185. On the other hand, when the control amount variation DC is equal to or less than the second threshold value DC_th2 (Step S184; No), the processing proceeds to Step S187.

(102) In Step S185, the vehicle abnormality determination unit **180** determines whether or not the state in which the control amount variation DC exceeds the second threshold value DC_th2 continues for Td seconds. When such the state continues for Td seconds (Step S185; Yes), the processing proceeds to Step S183. On the other hand, when such the state has not yet continued for Td seconds (Step S185; No), the processing proceeds to Step S186.

(103) In Step S186, the vehicle abnormality determination unit **180** sets the current state to “vehicle

abnormality determination in progress” without confirming the determination. After that, the processing returns to Step S181.

(104) In Step S187, the vehicle abnormality determination unit 180 determines that no vehicle abnormality occurs and the vehicle 100 is normal. After that, the processing returns to Step S181.

4-6. Example of Operation Amount Coordinating Process

(105) FIG. 14 is a diagram for explaining an example of the operation amount coordinating process performed by the operation amount coordinating unit 150. In FIG. 14, a circle indicates “normal (no abnormality occurs)”, a cross indicates “abnormality confirmed (abnormality occurs)”, and a triangle indicates “determination in progress.” As exemplified in the above FIGS. 10 to 13, a period of determination-in-progress is a period after a provisional abnormality condition (e.g., Step S174 in FIG. 12, “ $DX > DX_{th2}$ ”) is satisfied and in which a state where the provisional abnormality condition is satisfied continues. In other words, the period of determination-in-progress is a period from when possibility of the occurrence of the abnormality is detected to when whether or not the abnormality occurs is determined.

(106) The first operation amount X1 is an operation amount caused by the remote operator O. The second operation amount X2 is an operation amount determined by the autonomous driving function of the vehicle 100 in a case of the normal state. A third operation amount X3 is a combination of the first operation amount X1 and the second operation amount X2, and is represented by “ $X3 = a \times X1 + (1-a) \times X2$.” Here, the coefficient is a real number greater than 0 and less than 1. A fourth operation amount X4, which is a kind of the second operation amount X2 determined by the autonomous driving function of the vehicle 100, is an operation amount used particularly in case of emergency. For example, the fourth operation amount X4 is an operation amount for making the vehicle 100 safely stop or evacuate.

(107) The operation amount coordinating unit 150 determines any one of the first operation amount X1, the second operation amount X2, the third operation amount X3, and the fourth operation amount X4 as the final operation amount X according to the results of the variety of abnormality determination processes.

(108) First, for the sake of simplicity, a combination of the communication state and the terminal state is considered. When neither the communication abnormality nor the terminal abnormality occurs, the first operation amount X1 is selected (see Nos. 1 and 2). When it is determined that the terminal abnormality occurs, the second operation amount X2 is selected instead of the first operation amount X1 (see Nos. 7, 8, 16, 17, 25, and 26). This improves the safety. When it is determined that the communication abnormality occurs, the second operation amount X2 is selected instead of the first operation amount X1 (see Nos. 19, 20, 22, 23, 25, and 26). This improves the safety.

(109) A “first determination-in-progress period” is the above-mentioned period of determination-in-progress regarding the terminal abnormality. When it is determined that no communication abnormality occurs during the first determination-in-progress period, the third operation amount X3 is selected (see Nos. 4 and 5). Since the second operation amount X2 partially contributes to the operation amount X, it is possible to improve the safety in a case where the terminal abnormality actually occurs. Moreover, since the operation amount is not completely switched to the second operation amount X2 and thus an influence of the first operation amount X1 remains, it is possible to suppress the remote operator O's sense of discomfort in a case where no terminal abnormality actually occurs.

(110) A “second determination-in-progress period” is the above-mentioned period of determination-in-progress regarding the communication abnormality. When it is determined that no terminal abnormality occurs during the second determination-in-progress period, the first operation amount X1 is selected (see Nos. 10 and 11). Continuing to use the first operation amount X1 even during the determination of the communication abnormality is in progress makes it possible to improve continuity of the remote operation by the remote operator O.

(111) During a period in which the first determination-in-progress period and the second determination-in-progress period overlap, the third operation amount X3 is selected (see Nos. 13 and 14). Since the second operation amount X2 partially contributes to the operation amount X, it is possible to improve the safety in a case where the terminal abnormality actually occurs. Moreover, since the operation amount is not completely switched to the second operation amount X2 and thus an influence of the first operation amount X1 remains, it is possible to suppress the remote operator O's sense of discomfort in a case where no terminal abnormality actually occurs. (112) Next, a combination of the communication state, the terminal state, and the vehicle state is considered. The same as in the above-described cases is applied to a case when no vehicle abnormality occurs and a case where the determination of the vehicle abnormality is progress. On the other hand, when it is determined that the vehicle abnormality occurs, the fourth operation amount X4 which is the second operation amount X2 in case of emergency is basically selected (see Nos. 3, 6, 12, 15, 18, 21 24, and 27). It is thus possible to make the vehicle **100** stop safely. However, even when the vehicle abnormality occurs, if the camera mounted on the vehicle **100** is normal, the first operation amount X1 or the third operation amount X3 may be selected (see Nos. 3, 6, 12, and 15).

4-7. Effects

(113) As described above, according to the present embodiment, the control device **105** of the vehicle **100** is configured to execute the abnormality determination process and the operation amount coordinating process. In the operation amount coordinating process, the control device **105** determines the “final operation amount X” from among the first operation amount X1, the second operation amount X2, the third operation amount X3, and the fourth operation amount X4 according to the result of the abnormality determination process. Then, the vehicle **100** is controlled in accordance with the determined operation amount X. It is thus possible to appropriately control the vehicle **100** in consideration of the state of the abnormality when the abnormality occurs in the remote operation system **1**.

5. CONFIGURATION EXAMPLE OF COMBINATION

(114) It is also possible to combine the delay compensation process described in the above Section 3 and the abnormality determination process and the operation amount coordinating process described in the above Section 4. FIG. **15** shows a functional configuration example in the case of the combination. The vehicle **100** includes the reception unit **110**, the delay compensation unit **120**, the control unit **130**, the communication abnormality determination unit **160**, the terminal abnormality determination unit **170**, and the vehicle abnormality determination unit **180**.

(115) The delay compensation unit **120** calculates the first correction operation amount X1C based on the first operation amount X1 and the delay amount DL. The operation amount coordinating unit **150** receives the first correction operation amount X1C instead of the first operation amount X1. Then, the operation amount coordinating unit **150** executes the operation amount coordinating process based on the first correction operation amount X1C and the second operation amount X2 to determine the final operation amount X.

(116) As a result, both the effect of the Section 3 and the effect of the Section 4 can be obtained. That is, the safety of the remote operation of the vehicle **100** is further improved.

6. EXAMPLE OF REMOTE OPERATOR TERMINAL

(117) FIG. **16** is a block diagram showing a configuration example of the remote operator terminal **200**. The remote operator terminal **200** includes a communications device **210**, a display **220**, an input device **230**, and a control device (controller) **250**.

(118) The communication device **210** communicates with the vehicle **100** and the management device **300**.

(119) The display device **220** presents a variety of information to the remote operator O by displaying the variety of information.

(120) The input device **230** receives an input from the remote operator O. For example, the input

device **230** includes a remote operation member that is operated by the remote operator O when remotely operating the vehicle **100**. The remote operation member includes a steering wheel, an accelerator pedal, a brake pedal, a direction indicator, and the like.

(121) The control device **250** controls the remote operator terminal **200**. The control device **250** includes one or more processors **260** (hereinafter simply referred to as a processor **260**) and one or more memory devices **270** (hereinafter simply referred to as a memory device **270**). The processor **260** executes a variety of processing. For example, the processor **260** includes a CPU. The memory device **270** stores a variety of information necessary for the processing by the processor **260**.

Examples of the memory device **270** include a volatile memory, a non-volatile memory, an HDD, an SSD, and the like.

(122) A remote operation program PROG2 is a computer program executed by the processor **260**. The functions of the control device **250** are implemented by the processor **260** executing the remote operation program PROG2. The remote operation program PROG2 is stored in the memory device **270**. The remote operation program PROG2 may be recorded on a non-transitory computer-readable recording medium. The remote operation program PROG2 may be provided via a network.

(123) The control device **250** communicates with the vehicle **100** via the communication device **210**. The control device **250** receives the vehicle information VCL transmitted from the vehicle **100**. The control device **250** presents the vehicle information VCL to the remote operator O by displaying the vehicle information VCL including the image information on the display device. The remote operator O is able to recognize the state of the vehicle **100** and the situation around the vehicle **100** based on the vehicle information VCL displayed on the display device.

(124) The remote operator O operates the remote operation member of the input device **230**. An operation amount of the remote operation member is detected by a sensor installed on the remote operation member. The control device **250** generates the remote operation information OPE reflecting the operation amount of the remote operation member operated by the remote operator O. Then, the control device **250** transmits the remote operation information OPE to the vehicle **100** via the communication device **210**.

Claims

1. A control device that controls a moving body being a target of a remote operation performed by a remote operator, the control device comprising one or more processors mounted on the moving body and configured to: during the remote operation of the moving body, perform a communication with a remote operator terminal on a side of the remote operator to receive remote operation information including a first operation amount caused by the remote operator; acquire a delay amount of a communication from the remote operator terminal to the moving body based on a result of reception of the remote operation information; execute a delay compensation process that compensates for a delay of the first operation amount based on the delay amount to calculate a first correction operation amount; execute an upsampling process that increases a sampling frequency of the first correction operation amount by estimating the first correction operation amount in a non-sampling period; and control the moving body based on the first correction operation amount.

2. The control device according to claim 1, wherein: a control frequency of controlling the moving body is higher than a communication frequency of the remote operation information, and the one or more processors are configured to execute the upsampling process such that a difference between the sampling frequency of the first correction operation amount and the control frequency becomes smaller than a difference between the communication frequency and the control frequency.

3. The control device according to claim 1, wherein: the one or more processors are configured to: estimate the first correction operation amount in the non-sampling period by feeding back an estimate value of the first correction operation amount acquired by the upsampling process and the

first correction operation amount acquired by the delay compensation process; and calculate the first correction operation amount by correcting the estimate value of the first correction operation amount based on the first operation amount received from the remoter operator terminal while performing the delay compensation process based on the delay amount.

4. The control device according to claim 3, wherein: the one or more processors are configured to execute the upsampling process and the delay compensation process by applying a delayed Kalman filter to the first operation amount.

5. The control device according to claim 1, wherein: in the upsampling process, the one or more processors are configured to estimate the first correction operation amount further based on supplementary information including at least one of a shape of a road on which the moving body moves and a control amount of the moving body.

6. The control device according to claim 1, wherein: the moving body has an autonomous driving function, and the one or more processors are further configured to: execute a communication abnormality determination process that determines, based on a state of the communication with the remote operator terminal, whether or not an abnormality occurs in the communication with the remote operator terminal; execute a terminal abnormality determination process that determines, based on the first operation amount, whether or not an abnormality occurs in the remote operator terminal; execute an operation amount coordinating process that determines an operation amount based on at least one of the first correction operation amount and a second operation amount determined by the autonomous driving function according to results of the communication abnormality determination process and the terminal abnormality determination process; and control the moving body in accordance with the determined operation amount.

7. A control method for controlling a moving body being a target of a remote operation performed by a remote operator, the control method comprising: during the remote operation of the moving body, performing a communication with a remote operator terminal on a side of the remote operator to receive remote operation information including a first operation amount caused by the remote operator; acquiring a delay amount of a communication from the remote operator terminal to the moving body based on a result of reception of the remote operation information; a delay compensation process that compensates for a delay of the first operation amount based on the delay amount to calculate a first correction operation amount; an upsampling process that increases a sampling frequency of the first correction operation amount by estimating the first correction operation amount in a non-sampling period; and controlling the moving body based on the first correction operation amount.

8. A non-transitory computer-readable recording medium on which a control program is recorded, the control program being a compute program for controlling a moving body being a target of a remote operation performed by a remote operator, the control program, when executed by a computer mounted on the moving body, causing the computer to: during the remote operation of the moving body, perform a communication with a remote operator terminal on a side of the remote operator to receive remote operation information including a first operation amount caused by the remote operator; acquire a delay amount of a communication from the remote operator terminal to the moving body based on a result of reception of the remote operation information; execute a delay compensation process that compensates for a delay of the first operation amount based on the delay amount to calculate a first correction operation amount; an upsampling process that increases a sampling frequency of the first correction operation amount by estimating the first correction operation amount in a non-sampling period; and control the moving body based on the first correction operation amount.
