

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12413924
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Franco; Alfredo Fernandez

Motion detection of speaker units

Abstract

In various embodiments, a computer-implemented method comprises detecting that a speaker unit has moved to a first location, determining, based on positioning information associated with the speaker unit, a position and an orientation of the speaker unit relative to a target listening area, filtering, using a filter determined based on the position and the orientation, an input audio signal to generate a filtered audio signal, and outputting the filtered audio signal using one or more loudspeakers.

Inventors: Franco; Alfredo Fernandez (Sherman Oaks, CA)

Applicant: HARMAN INTERNATIONAL INDUSTRIES, INCORPORATED (Stamford, CT)

Family ID: 87136379

Assignee: Harman International Industries, Incorporated (Stamford, CT)

Appl. No.: 17/859444

Filed: July 07, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20240015459 A1	Jan. 11, 2024

Publication Classification

Int. Cl.: H04S7/00 (20060101)

U.S. Cl.:

CPC H04S7/30 (20130101);

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
9398392	12/2015	Ridihalgh	N/A	N/A
10728683	12/2019	Shi	N/A	N/A
10945090	12/2020	Choisel et al.	N/A	N/A
2012/0027226	12/2011	Desenberg	N/A	N/A
2013/0329921	12/2012	Salsman	N/A	N/A
2015/0023533	12/2014	Johnson et al.	N/A	N/A
2016/0077549	12/2015	Wang	710/304	G06F 1/1632
2016/0286330	12/2015	Kofman et al.	N/A	N/A
2017/0055098	12/2016	Lim	N/A	H04R 3/04
2017/0105069	12/2016	Mezzomo	N/A	H04R 1/026
2017/0171702	12/2016	Hansson	N/A	H04W 4/02
2017/0280265	12/2016	Po	N/A	N/A
2018/0122396	12/2017	Lee	N/A	H04R 5/04
2018/0367939	12/2017	Fischer	N/A	H04S 7/305
2020/0059724	12/2019	Walther et al.	N/A	N/A
2020/0252738	12/2019	Wolti	N/A	H04R 1/02
2021/0168552	12/2020	Walther	N/A	H04R 27/00
2021/0337340	12/2020	Wey	N/A	H04S 7/303
2022/0312136	12/2021	Yamaji	N/A	H04S 7/302

Primary Examiner: Nguyen; Duc

Assistant Examiner: Mohammed; Assad

Attorney, Agent or Firm: Artegis Law Group, LLP

Background/Summary

BACKGROUND

Field of the Various Embodiments

(1) The various embodiments relate generally to audio output devices and, more specifically, to motion detection of speaker units.

Description of the Related Art

(2) It is often desirable to output audio through a sound system, such as groups of speakers. The audio output devices are often positioned at certain locations within a physical space. For example, a given room includes a soundbar centered near a video playback device, such as a television or a computer, with additional satellite speakers positioned proximate to the soundbar. In another example, a room can include speakers that are organized as a home theater, where a center speaker is positioned near the center of a front wall of the room, and front left, front right, rear left, and rear

right speakers are each positioned in a corresponding corner of the room. The video playback device transmits a signal to each speaker so that a listener within the physical space hears the combined output of all of the speakers.

(3) During operation of the conventional sound system, the speakers positioned in the listening environment generate a sound field. The sound field of the conventional sound system is highly dependent on the positioning and orientation of the speakers. A typical sound field includes one or more “sweet spots.” A sweet spot generally corresponds to a target location for a listener to be positioned in the listening environment. In the sound field, the sweet spots are generally tuned to yield desirable sound quality. Therefore, a listener positioned within in a sweet spot hears the best sound quality that the sound system in the listening environment can offer. As such, the one or more sweet spots are often highly dependent on the positioning and orientation of the speakers

(4) For example, FIG. 1 is a schematic diagram illustrating a prior art modular speaker system **100**. As shown, the modular speaker system **100** includes a hub speaker unit **102**, and speaker units **104**. The hub speaker unit **102** includes loudspeakers **112**. The speaker units **104** include loudspeakers **114** and subwoofer **116**. For explanatory purposes, multiple instances of like objects are denoted with reference numbers identifying the object and additional numbers in parentheses identifying the instance where needed.

(5) The modular speaker system **100** operates in multiple arrangements. For example, the modular speaker system **100** can operate in a first arrangement **110** as a soundbar with multiple speaker units **104** (e.g., **104(1)** and **104(2)**) attached and/or proximate to the hub speaker unit **102**. A movement **120** of the speaker units **104** causes the modular speaker system **100** to operate in a second arrangement **130**, where the speaker units **104** are in distinct locations within a listening environment.

(6) In various embodiments, the loudspeakers **112** (e.g., **112(1)**, **112(2)**, **112(3)**) of the hub speaker unit **102** and the loudspeakers **114** (e.g., **114(1)**, **114(2)**, **114(3)**, etc.) of the respective speaker units **102**, **104** reproduce an audio signal by generating soundwaves that generate a sound field. The hub speaker unit **102** and/or the speaker units speaker unit **104** drive the respective loudspeakers **112**, **114** to generate soundwaves in specific directions to generate a sound field in a specific location. For example, the loudspeakers **112** included in the hub speaker unit **102** generate separate soundwaves **132** (e.g., **132(1)**, **132(2)**, **132(3)**) that combine to generate the sweet spot **136** around a target listening area **140**.

(7) Notably, when the speaker units **104** are positioned at locations remote to the hub speaker unit **102**, the speaker units **104** may not generate soundwaves that combine to generate the sound field to create a sweet spot **136** at the target listening area **140**. For example, the speaker units **104(1)**, **104(2)** could drive the respective sets of loudspeakers **114** to generate soundwaves **134(1)**, **134(2)** in a direction where the respective soundwaves **134(1)**, **134(2)** combine with the soundwaves **132** produced by the hub speaker unit **102** to generate a sweet spot **136** that does not encompass the target listening area **140**. As a result, listeners positioned within the target listening area **140** do not hear the optimized version of the sound wave and therefore have a degraded listening experience. Accordingly, the positioning of speaker units **104** of the modular speaker system **100** results in sub-optimal generation of a sound field in an area of the listening environment.

(8) Further, another drawback with conventional sound systems is that setting up a conventional sound system in a listening environment is a slow and delicate process. During set-up, speakers are manually placed in the listening environment, where the placement of the speakers affects the location of the sweet spot. As a result, a listener is required to execute iterative, manual adjustments to one or more speakers to determine whether a specific position and orientation sounds better than an alternative. Alternatively, the listener conducts various testing, uses various tuning equipment, and/or perform various calculations to determine possible desirable positioning and orientations of the speakers. Once those possible desirable positioning and orientations are determined, the listener manually adjusts the positioning and orientation of each speaker accordingly. Determining,

positioning, and orienting can be a slow process.

(9) In addition, a listener is required to perform such processes each time a speaker changes position. Due to the difficult calibration process, the listener is discouraged from moving any of the calibrated speakers, including portable speakers that are otherwise configured operate in a wide range of positions within the listening environment.

(10) As the foregoing illustrates, what is needed are more effective techniques for providing audio from multiple speakers that have changed position.

SUMMARY

(11) In various embodiments, a computer-implemented method comprises detecting that a speaker unit has moved to a first location, determining, based on positioning information associated with the speaker unit, a position and an orientation of the speaker unit relative to a target listening area, filtering, using a filter determined based on the position and the orientation, an input audio signal to generate a filtered audio signal, and outputting the filtered audio signal using one or more loudspeakers.

(12) Further embodiments provide, among other things, non-transitory computer-readable storage media storing instructions for implementing the method set forth above, as well as a system configured to implement the method set forth above.

(13) At least one technical advantage of the disclosed techniques relative to the prior art is that, with the disclosed techniques, the modular speaker system calibrates the speaker units in the system to generate an optimized sound field without a user having to perform iterative positioning and calibrating processes. In particular, the disclosed techniques automatically calibrate the modular speaker system whenever a speaker unit is moved. Further, the disclosed techniques reduce the number of times that the positions of the speaker units are determined, which provide an optimized sound field while using less processing resources and consuming less power than conventional calibration approaches. These technical advantages provide one or more technological improvements over prior art approaches.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) So that the manner in which the above recited features of the various embodiments can be understood in detail, a more particular description of the inventive concepts, briefly summarized above, may be had by reference to various embodiments, some of which are illustrated in the appended drawings. It is to be noted, however, that the appended drawings illustrate only typical embodiments of the inventive concepts and are therefore not to be considered limiting of scope in any way, and that there are other equally effective embodiments.

(2) FIG. 1 is a schematic diagram illustrating a prior art modular speaker system;

(3) FIG. 2 is a conceptual block diagram of a modular speaker system configured to implement one or more aspects of the present disclosure;

(4) FIG. 3 is a schematic diagram of the speaker units included in the modular speaker system of FIG. 2 operating to transmit positioning information to a hub speaker unit, according to various embodiments of the present disclosure;

(5) FIG. 4 is a schematic diagram of the hub speaker and the additional speaker units included in the modular speaker system of FIG. 2 operating to generate a sound field for a target listening area, according to various embodiments of the present disclosure;

(6) FIG. 5 is a flowchart of method steps for a hub speaker unit determining a position of a speaker unit based on positioning information to generate a filter for reproducing an audio signal, according to various embodiments of the present disclosure;

(7) FIG. 6 is a flowchart of method steps for a speaker unit transmitting sensor data to identify a

new position associated with generating a filtered audio signal, according to various embodiments of the present disclosure;

(8) FIG. 7 is a flowchart of method steps for a speaker unit processing positioning information to generate a filter for generating a filtered audio signal, according to various embodiments of the present disclosure; and

(9) FIG. 8 is a flowchart of method steps for a hub speaker unit generating one or more filters for generating one or more filtered audio signals, according to various embodiments of the present disclosure.

DETAILED DESCRIPTION

(10) In the following description, numerous specific details are set forth to provide a more thorough understanding of the various embodiments. However, it will be apparent to one of skilled in the art that the inventive concepts may be practiced without one or more of these specific details.

(11) System Overview

(12) FIG. 2 is a conceptual block diagram of a modular speaker system **200** configured to implement one or more aspects of the present disclosure. As shown, and without limitation, the modular speaker system **200** includes a hub speaker unit **202**, a speaker unit **204** (e.g., **204(1)**), a network **208**, and an audio source **206**. The hub speaker unit **202** includes, without limitation, loudspeakers **210**, one or more sensors **216**, input/output (I/O) device interface **218**, a processor **212**, and a memory **214**. The memory **214** includes, without limitation, a control module **220**, a filter **222**, and position data **224**. The speaker unit **204** includes, without limitation, a processor **242**, a memory **244**, loudspeakers **248**, one or more sensors **246**, I/O device interface **250**, and one or more motion sensors **252**. The memory **214** includes, without limitation, a positioning module **260**, a filter **222(1)**, position data **224(1)**, and output rendering module **270**. The modular speaker system **100** can include multiple instances of elements, even when not shown, and still be within the scope of the disclosed embodiments.

(13) In operation, the hub speaker unit **202** and/or speaker unit **204** tracks the movement of the speaker unit **204** based on positioning information **254** generated from sensor data acquired by one or more of the sensors **216**, **246**, and/or the motion sensors **252**. Based on the positioning information **254**, the control module **220** and/or the positioning module **260** determine the current position of the speaker unit **204**. The control module **220** and/or the positioning module **260** generates a filter **222(1)** for the speaker unit **204**. The output rendering module **270** uses the filter **222(1)** to process the audio signal **256** to generate a filtered audio signal. The output rendering module **270** renders the filtered audio signal by driving the loudspeakers **248** to generate a soundwave specified in the filtered audio signal. In various embodiments, the output rendering module **226** uses one or more filters **222** to generate a separate set of filtered audio signals. The output rendering module **226** drives the loudspeakers **210** with the set of filtered audio signals to generate one or more soundwaves in the respective filtered audio signals. The soundwaves generated by the hub speaker unit **202** and speaker unit **204** combine to generate a sound field that creates a sweet spot that encompasses a target listening area.

(14) The hub speaker unit **202** is a device that drives loudspeakers **210** to generate, in part, a sound field. In various embodiments, the hub speaker unit **202** includes a control module **220** that determines the positions of each speaker unit **204** included in the modular speaker system **200** and stores the positions as position data **224**. In some embodiments, the control module **220** uses the position data **224** to generate a set of filters **222**, where the hub speaker unit **202** and each speaker unit **204** use the filters to generate directional soundwaves to generate a sound field at a specific location within the listening environment. In some embodiments, the hub speaker unit **202** can transmit the position data **224** and/or the motion sensors **252** via the network **208** to one or more cloud-based computing resources, such as an online optimization service, to determine the positions of the speaker unit **204** and/or the filters **222**.

(15) In various embodiments, the hub speaker unit **202** can be a central unit in a home theater

system, a soundbar, and/or another device that communicates with the one or more speaker units **204**. The hub speaker unit **202** is included in one or more devices, such as consumer products (e.g., portable speakers, gaming, gambling, etc. products), smart home devices (e.g., smart lighting systems, security systems, digital assistants, etc.), communications systems (e.g., conference call systems, video conferencing systems, speaker amplification systems, etc.), and so forth. In various embodiments, the hub speaker unit **202** is located in various environments including, without limitation, indoor environments (e.g., living room, conference room, conference hall, home office, etc.), and/or outdoor environments, (e.g., patio, rooftop, garden, etc.).

(16) Additionally or alternatively, in some embodiments, the hub speaker unit **202** includes a reference position. For example, a specific point of the hub speaker unit **202** can act as an anchoring reference position from which other positions within the environment are determined. In such instances, the position data **224** includes the position of the speaker unit **204** as a specific distance and angle (e.g., $\{d, \theta\}$) and an orientation (e.g., $\{\mu, \phi, \psi\}$) relative to the reference position. Similarly, the position data **224** includes the target listening area as a specific distance and angle from the reference point. In some embodiments, the control module **220** and/or the positioning module **260** estimate the target listening area as a specific distance directly in front of the reference point. For example, when the reference point is the location a center loudspeaker included in the hub speaker unit **202** (e.g., loudspeakers **210**), the control module **220** and/or the positioning module **260** can estimate the target listening area as area located at a specific distance (e.g., 3 m) in front of the reference point.

(17) The processor **212** can be any suitable processor, such as a central processing unit (CPU), a graphics processing unit (GPU), an application-specific integrated circuit (ASIC), a field programmable gate array (FPGA), a digital signal processor (DSP), and/or any other type of processing unit, or a combination of different processing units, such as a CPU configured to operate in conjunction with a GPU. In general, the processor **212** can be any technically-feasible hardware unit capable of processing data and/or executing software applications.

(18) Memory **214** can include a random-access memory (RAM) module, a flash memory unit, or any other type of memory unit or combination thereof. The processor **212** is configured to read data from and write data to memory **214**. In various embodiments, the memory **214** includes non-volatile memory, such as optical drives, magnetic drives, flash drives, or other storage. In some embodiments, separate data stores, such as an external included in the network **208** (“cloud storage”) can supplement the memory **214**. The control module **220** and/or the output rendering module **226** within memory **214** can be executed by the processor **212** to implement the overall functionality of the hub speaker unit **202** and, thus, to coordinate the operation of the modular speaker system **200** as a whole. In various embodiments, an interconnect bus (not shown) connects the processor **212**, the memory **214**, the loudspeakers **210**, the I/O device interface **218**, the sensors **216**, and any other components of the hub speaker unit **202**.

(19) The control module **220** executes various techniques to determine positions of the speaker units **204** included in the listening environment and generates one or more filters **222** to generate the sound field to encompass the target listening area. In various embodiments, the control module **220** receives positioning information **254** from the speaker unit **204** and/or generate positioning information **254** and processes the positioning information **254** in order to generate the position data **224**. For example, the control module **220** can periodically receive the positioning information **254** from the speaker unit **204** while the speaker unit **204** is in motion. In another example, the control module **220** can acquire the positioning information **254** internally from the sensors **216** (e.g., received optical data and/or auditory data received in response to test signals generated by the hub speaker unit **202**).

(20) In various embodiments, the control module **220** aggregates the positioning information **254** to track the movement of the speaker unit **204** within the environment. In some embodiments, the control module **220** aggregates a series of positioning information **254** received from the speaker

unit **204** in order to track the change in position that the speaker unit **204** experiences over a given time period. In such instances, the control module **220** processes the aggregated positioning information **254** to determine the current position of the speaker unit **204**. For example, the control module **220** compares successive sets of positioning information **254** to determine that the speaker unit **204** is no longer in motion. Upon determining that the speaker unit **204** is stationary, the control module **220** uses the aggregated positioning information **254** to determine the overall change in position and determine the current position of the now-stationary speaker unit **204**. The control module **220** additionally uses the current position of the speaker unit **204** to determine the direction of the target listening area relative to the speaker unit **204**.

(21) In various embodiments, the control module **220** generates a set of filters **222** for the hub speaker unit **202** and/or the speaker units **204**. The filters **222** include one or more filters that modify an input audio signal. In various embodiments, a given filter **222** modifies the input audio signal by adding directivity information to the audio signal. For example, the filter **222** can include various digital signal processing (DSP) coefficients that steer the generated soundwave in a specific direction. In such instances, the generated filtered audio signal is used to generate a soundwave in the direction specified in the filtered audio signal. For example, the hub speaker unit **202** can generate a filter **222(1)** for the speaker unit **204**. When the output rendering module **270** uses the filter on the positioning information **254**, the generated filtered audio signal includes directivity information corresponding to the direction of the target listening area relative to the speaker unit **204**. When the output rendering module **270** subsequently drives the loudspeakers **248** with the filtered audio signal, the loudspeakers **248** generate a soundwave in the direction specified in the filtered audio signal.

(22) In some embodiments, the control module **220** generates separate filters **222** for each loudspeaker **210** or subsets of the loudspeakers **248**. In some embodiments, the control module **220** does not generate the filters for the speaker units **204**. In such instances, the control module **220** generates one or more filters **222** for the loudspeakers **210** while the positioning module **260** operating on each of the respective speaker units **202**, **204** generates one or more filters **222** for the loudspeakers **248** included in the speaker unit **204**. Alternatively, the control module **220** generates a set of filters for each speaker unit **202**, **204** and update the filters for a specific speaker unit **204** when the speaker unit **204** moves. For example, the control module **220** can initially generate a set of filters **222** that includes separate filters for each respective loudspeakers **210** included in the hub speaker unit **202**. Upon determining that a specific speaker unit **204** has moved, the control module **220** then determines the current position of the speaker unit **204** and generates a separate filter (e.g., the filter **222(1)**) for the subset of loudspeakers **248** included in the speaker unit **204** to generate a soundwave in a specific direction.

(23) In some embodiments, the control module **220** generates each of the filters independently. For example, upon determining that the speaker unit **204(1)** has moved, the control module **220** generates an updated filter **222(1)** for the specific speaker unit **204(1)**. Alternatively, the control module **220** updates multiple filters **222**. For example, upon determining that the speaker unit **204(1)** has moved, the control module **220** can determine each of the positions in a given arrangement and update each of the filters **222** in order for the respective speaker units **202**, **204** to generate a sound field in the target listening area. In some embodiments, the output rendering module **226** uses multiple filters to modify the audio signal. For example, the output rendering module **226** can use the filter **222** to add directivity information to the audio signal and can use separate filters (not shown), such as equalization filters, spatialization filters, etc., to further modify the audio signal.

(24) The position data **224** is a dataset that includes positional information for one or more locations within the listening environment. In some embodiments, the position data **224** includes specific coordinates relative to a reference point. For example, the position data **224** can store the current positions and/or orientations of each respective speaker unit **204** and/or each of the specific

loudspeakers **248** within each respective speaker unit **204** as a distance and angle from a specific reference point. In some embodiments, the position data **224** can include additional orientation information, such as a set of angles (e.g., $\{\mu, \phi, \psi\}$) relative to a normal orientation. In such instances, the position and orientation of a given loudspeaker **210, 248** and/or speaker unit **202, 204** is stored in the position data **224** as a set of distances and angles relative to a reference point. In various embodiments, the position data **224** also includes computed directions between points. For example, the control module **220** can compute the direction of the target listening area relative to the position and orientation of the speaker unit **204** and can store the direction as a vector in the position data **224**. In such instances, the control module **220** retrieves the stored direction when generating the filter **222(1)** for the speaker unit **204**.

(25) In various embodiments, the hub speaker unit **202**, the speaker unit **204**, or a combination of hub speaker unit **202** and speaker unit **204** process various sensor data to generate the position data **224** that is used to determine positions and/or orientations of various units within the listening environment. In such instances, the hub speaker unit **202** or the speaker unit **204** process the position data **224(1)** for the speaker unit **204** to generate the filter **222(1)** for the speaker unit. Additionally or alternatively, the hub speaker unit **202** or the speaker unit **204** use the filter **222** to generate a filtered audio signal from a given input audio signal. The speaker unit **204** reproduces the filtered audio signal to generate soundwaves within the listening environment.

(26) In various embodiments, the hub speaker unit **202** or the speaker unit **204** determines the position data **224(1)** from aggregating a set of positioning information **254**. In one example, the speaker unit **204** transmits a series of messages to the hub speaker unit **202** that includes positioning information **254** at various times during the motion of the speaker unit **204**. In such instances, the control module **220** determines whether the speaker unit **204** has stopped moving and, upon making the determination, aggregates the positioning information **254** to determine the trajectory from a starting location and the position of the now-stationary speaker unit **204**.

Aggregating and processing the positioning information **254** upon determining that the speaker unit **204** has stopped moving reduces the processing resources that the hub speaker unit **202** employs, such as processor threads, cache memory, and so forth, to determine the position of the speaker unit **204**, as the hub speaker unit **202** can determine an endpoint position of the speaker unit **204** in lieu of continually determining the position of the speaker unit **204** as the speaker is moving.

(27) In another example, the speaker unit **204** generates sensor data at various times during the motion as positioning information **254**. Upon determining that the speaker unit **204** is no longer in motion, the positioning module **260** aggregates the positioning information from the location where an initial motion was detected to determine the current position. Upon determining the current position, the positioning module **260** stores the current position of the speaker unit **204** in the position data **224(1)** and/or transmits the current position as positioning information **254** to control module **220**.

(28) Alternatively, in some embodiments, the hub speaker unit **202** and/or the speaker unit **204** determine the position data **224(1)** for the speaker unit **204** using other types of positioning algorithms. In various examples, the hub speaker unit **202** and/or the speaker unit **204** execute various types of triangulation algorithms to determine the current position of the speaker unit **204** upon determining that the speaker unit **204** is no longer moving. When performing such triangulation algorithms, the hub speaker unit **202** and/or the speaker unit **204** use various quantities of emitters and/or detectors to acquire various types of data (e.g., synchronization signals, timing signals, auditory sensor data, optical sensor data, angular rotation data, etc.) to determine the current position and/or current orientation of the now-stationary speaker unit **204**. Performing such positioning algorithms reduces the computing resources that the hub speaker unit **202** and/or the speaker unit **204** use to determine the position of the speaker unit **204**. For example, by performing the positioning algorithms just to the times where the speaker unit **204** has stopped moving reduces the processing resources that the hub speaker unit **202** and/or the speaker unit **204**

employs to performing the positioning algorithms. Further, the modular speaker system **200** frees bandwidth associated with transmitting messages between the hub speaker unit **202** and the speaker unit **204** that are used to determine the position of the speaker unit **204**, as the modular speaker system **200** does not transmit messages when the speaker unit **204** does not move.

(29) In some embodiments, the hub speaker unit **202** includes a single emitter and the speaker unit **204** includes multiple detectors. The hub speaker unit **202** emits one or more types of signals, such as subsonic pulses, ultrasonic pulses, and so forth. In such instances, the speaker unit **204** generates positioning information **254** that includes the times at which each of the detectors included in the speaker unit **204** receives the signal emitted by the hub speaker unit **202**. By comparing the times at which each of detectors included in the speaker unit **204** receives the signal to the time when the hub speaker unit **202** emitted the signal, a respective distance between the emitter in the hub speaker unit **202** and the detectors included in the speaker unit **204** is determined. The respective distances and the known separation between the detectors are then used to determine the current position of the speaker unit **204** relative to the hub speaker unit **202**. In some examples, the time when the hub speaker unit **202** emits the signal is communicated to the speaker unit **204** by sending a message with the time of emission or emitting a pulse (e.g., using RF, infrared, and/or some other speed of light medium) to the speaker unit **204** when the signal is emitted. In some embodiments, the speaker unit **204** transmits the positioning information **254** for processing by the control module **220** to determine the current position of the speaker unit **204** and store the current position as position data **224**. Alternatively, in some embodiments, the positioning module **260** operating in the speaker unit **204** processes the information and stores the determined current position as the position data **224(1)**.

(30) In some embodiments, the speaker unit **204** includes a single emitter and the hub speaker unit **202** includes multiple detectors. The speaker unit **204** emits one or more types of signals, such as subsonic pulses, ultrasonic pulses, and so forth. In such instances, the hub speaker unit **202** generates positioning information **254** that includes the times at which each of the detectors included in the hub speaker unit **202** receives the signal emitted by the speaker unit **204**. By comparing the times at which each of detectors included in the hub speaker unit **202** receives the signal to the time when the speaker unit **204** emitted the signal, a respective distance between the emitter in the speaker unit **204** and the detectors included in the hub speaker unit **202** is determined. The respective distances and the known separation between the detectors are then used to determine the current position of the speaker unit **204** relative to the hub speaker unit **202**. In some examples, the time when the speaker unit **204** emits the signal is communicated to the hub speaker unit **202** by sending a message with the time of emission or emitting a pulse (e.g., using RF, infrared, and/or some other speed of light medium) to the hub speaker unit **202** when the signal is emitted. In some embodiments, the hub speaker unit **202** transmits the positioning information **254** for processing by the positioning module **260** to determine the current position and/or orientation of the speaker unit **204** and store the current position and/or orientation as position data **224(1)**. Alternatively, in some embodiments, the control module **220** operating in the hub speaker unit **202** processes the information and stores the determined current position and/or orientation as a portion of the position data **224**.

(31) In some embodiments, the hub speaker unit **202** includes multiple emitters and the speaker unit **204** includes a single detector. The hub speaker unit **202** emits one or more types of signals, such as subsonic pulses, ultrasonic pulses, and so forth, from each of the respective emitters. In such instances, the speaker unit **204** generates positioning information **254** that includes the times at which the detector included in the speaker unit **204** receives each of the respective signals emitted by the emitters. By comparing the times at which the detector included in the speaker unit **204** receives the respective signals to the time when the hub speaker unit **202** emitted the respective signals, a respective distance between the respective emitters in the hub speaker unit **202** and the detector included in the speaker unit **204** is determined. The respective distances and the known

separation between the emitters are then used to determine the current position of the speaker unit **204** relative to the hub speaker unit **202**. In some examples, the time or times when the hub speaker unit **202** emits the respective signals is communicated to the speaker unit **204** by sending a message with the time(s) of emission or emitting a pulse (e.g., using RF, infrared, and/or some other speed of light medium) to the speaker unit **204** when the respective signals are emitted. In some embodiments, the speaker unit **204** transmits the positioning information **254** for processing by the control module **220** to determine the current position of the speaker unit **204** and store the current position as a portion of the position data **224**. Alternatively, in some embodiments, the positioning module **260** operating in the hub speaker unit **202** processes the information and stores the determined current position as the position data **224(1)**.

(32) In some embodiments, the speaker unit **204** includes multiple emitters and the hub speaker unit **202** includes a single detector. The speaker unit **204** emits one or more types of signals, such as subsonic pulses, ultrasonic pulses, infrared signals, and so forth, from each of the respective emitters. In such instances, the hub speaker unit **202** generates positioning information **254** that includes the times at which the detector included in the hub speaker unit **202** receives each of the respective signals emitted by the emitters. By comparing the times at which the detector included in the hub speaker unit **202** receives the respective signals to the time when the speaker unit **204** emitted the respective signals, a respective distance between the respective emitters in the speaker unit **204** and the detector included in the hub speaker unit **202** is determined. The respective distances and the known separation between the emitters are then used to determine the current position of the speaker unit **204** relative to the hub speaker unit **202**. In some examples, the time or times when the speaker unit **204** emits the respective signals is communicated to the hub speaker unit **202** by sending a message with the time(s) of emission or emitting a pulse (e.g., using RF, infrared, and/or some other speed of light medium) to the hub speaker unit **202** when the respective signals are emitted. In some embodiments, the hub speaker unit **202** transmits the positioning information **254** for processing by the positioning module **260** to determine the current position and/or orientation of the speaker unit **204** and store the current position and/or orientation as the position data **224(1)**. Alternatively, in some embodiments, the control module **220** operating in the hub speaker unit **202** processes the information and stores the determined current position and/or orientation as a portion of the position data **224**.

(33) In some embodiments, the speaker unit **204** includes one or more magnetometers or other orientation sensors that are used to determine an orientation of the speaker unit **204** relative to a fixed direction (e.g., magnetic north). Similar sensors in the hub speaker unit **202** are used to determine an orientation of the hub speaker unit relative to the same fixed direction. The difference between the orientation of the speaker unit **204** and the orientation of the hub speaker unit **202** is then used to determine the orientation of the speaker unit **204** relative to the hub speaker unit **202**. In some other embodiments, the speaker unit **204** or the hub speaker unit **202** include directional detectors that are usable to determine the direction(s) from which the signals used to determine the position of the speaker unit **204** are received. The direction(s) from which the signals are received are then used to determine the orientation of the speaker unit **204** relative to the hub speaker unit **202**.

(34) In some embodiments, the hub speaker unit **202** computes the orientation of the speaker unit **204**. In such instances, the control module **220** stores the orientation as a portion of the position data **224**, or transmits the orientation in the positioning information **254** for the positioning module **260** to store the orientation as the position data **224(1)**. Alternatively, in some embodiments, the positioning module **260** operating in the speaker hub determines the orientation. In such instances, the positioning module **260** stores the orientation in the position data **224(1)**, or transmits the orientation in the positioning information **254** for the control module **220** to store the orientation as a portion of the position data **224**.

(35) The output rendering module **226** processes an audio signal and renders the audio signal by

driving the loudspeakers **210** to generate one or more soundwaves corresponding to the audio signal. In various embodiments, the output rendering module **226** is a DSP that processes a given input audio signal by using a filter **222** having specific DSP coefficients to generate a filtered audio signal that steer a generated soundwave in a specific direction. In such instances, the output rendering module **226** renders the filtered audio signal to generate soundwaves. As discussed above, using the filters **222** adds directivity information to the filtered audio signal such that the hub speaker unit **202** rendering of the filtered audio signal generates a soundwave in a specific direction. In some embodiments, the output rendering module **226** processes the audio by separating the audio signal into separate spatialized audio signals. In such instances, the produced soundwaves cause the listener to hear portions of the audio as originating at a specific location (e.g., an explosion occurring on the right side of the listening environment).

(36) The sensors **216** include various types of sensors that acquire data about the listening environment. For example, the hub speaker unit **202** can include auditory sensors to receive several types of sound (e.g., subsonic pulses, ultrasonic sounds, speech commands, etc.). In some embodiments, the sensors **216** includes other types of sensors. Other types of sensors include optical sensors, such as RGB cameras, time-of-flight cameras, infrared cameras, depth cameras, a quick response (QR) code tracking system, motion sensors, such as an accelerometer or an inertial measurement unit (IMU) (e.g., a three-axis accelerometer, gyroscopic sensor, and/or magnetometer), pressure sensors, and so forth. In addition, in some embodiments, sensor(s) **216** can include wireless sensors, including radio frequency (RF) sensors (e.g., sonar and radar), and/or wireless communications protocols, including Bluetooth, Bluetooth low energy (BLE), cellular protocols, and/or near-field communications (NFC).

(37) In various embodiments, the control module **220** uses the sensor data acquired by the sensors **216** to generate the positioning information **254** and/or the position data **224**. For example, the hub speaker unit **202** includes one or more emitters that emit the positioning signals described above, where the hub speaker unit **202** and/or the speaker unit **204** include detectors that generate auditory data that includes the positioning signals. The control module **220** processes the received auditory data. The control module **220** determines that the auditory data represents the speaker unit **204** reflecting the positioning signals and uses timing data, such as the time between the emission of positioning signals and the reflection of the positioning signal, in order to determine the position and/or orientation of the speaker unit **204**. In some embodiments, the control module **220** combines multiple types of sensor data to track the motion of the speaker unit **204**. For example, the control module **220** can combine auditory data and optical data (e.g., camera images or infrared data) in order to determine the position and orientation of the speaker unit **204** at a given time.

(38) The I/O device interface **218** includes any number of different I/O adapters or interfaces used to provide the functions described herein. For example, the I/O device interface **218** could include wired and/or wireless connections, and can use various formats or protocols. In another example, the hub speaker unit **202**, through the I/O device interface **218**, could receive sensor data from the sensors **216**, input signals, and/or messages via input devices, and can provide output signals to output device(s) to produce outputs in various forms (e.g., ultrasonic pulses generated an ultrasonic emitter).

(39) The speaker unit **204** is included in a group of one or more speaker units **204** that operate in conjunction with the hub speaker unit **202**. In various embodiments, the speaker unit **204** is a wireless device that includes a separate power source than the hub speaker unit **202** and can drive the loudspeakers **248** using the power source, for example, the speaker unit **204** can include one or more batteries that provide power to the processor **242** and the loudspeakers **248**. In various embodiments, the speaker unit **204** use one or more sensors **246** and/or the motion sensors **252** to detect that the speaker unit **204** is moving. In such instances, the one or more sensors **246** and/or the motion sensors **252** acquire sensor data. The positioning module **260** processes the acquired sensor data to generate the positioning information **254**. In some embodiments, the positioning

module **260** uses the positioning information **254** to generate the position data **224(1)** and generate the filter **222(1)** for the speaker unit **204**. Alternatively, in some embodiments, the speaker unit **204** transmits the positioning information **254** to the hub speaker unit **202** as one or more messages and/or data packets using a wired or wireless communications media. For example, the speaker unit **204**, upon acquiring a set of positioning information **254** can generate a message that includes the positioning information **254** in the payload and wirelessly transmits the message over a WiFi or Bluetooth communication channel. In such instances, the control module **220** generates the filter **222(1)**. In such instances, the speaker unit **204** receives the filter **222(1)** from the hub speaker unit **202** for use by the output rendering module **270**.

(40) The processor **242** can be any suitable processor, such as a central processing unit (CPU), a graphics processing unit (GPU), an application-specific integrated circuit (ASIC), a field programmable gate array (FPGA), a digital signal processor (DSP), and/or any other type of processing unit, or a combination of different processing units, such as a CPU configured to operate in conjunction with a GPU. In general, the processor **242** can be any technically-feasible hardware unit capable of processing data and/or executing software applications.

(41) Memory **244** can include a random-access memory (RAM) module, a flash memory unit, or any other type of memory unit or combination thereof. The processor **242** is configured to read data from and write data to memory **244**. In various embodiments, the memory **244** includes non-volatile memory, such as optical drives, magnetic drives, flash drives, or other storage. In some embodiments, separate data stores, such as an external included in the network **208** can supplement the memory **214**. The positioning module **260** and/or the output rendering module **270** within memory **244** can be executed by the processor **242** to implement the overall functionality of the speaker unit **204** and, thus, to coordinate the operation of the modular speaker system **200** as a whole. In various embodiments, an interconnect bus (not shown) connects the processor **242**, the memory **244**, the loudspeakers **248**, the I/O device interface **218**, the sensors **216**, and any other components of the speaker unit **204**.

(42) The positioning module **260** has similar functionality to the control module **220** operating in the hub speaker unit **202**. In various embodiments, the positioning module **260** processes sensor data acquired by the sensors **246** and/or the motion sensors **252** to generate the positioning information **254**. In some embodiments, the positioning module **260** transmits the positioning information **254** to the hub speaker unit **202** using one or more messages and/or data packets using a wired or wireless communications medium for processing by the control module **220**. In such instances, the speaker unit **204** receives the position data **224(1)** from the hub speaker unit **202**. Alternatively, in some embodiments, the positioning module **260** processes the positioning information **254** to determine the current position of the speaker unit **204** and stores the current position as the position data **224(1)**.

(43) In some embodiments, the positioning module **260** determines whether the speaker unit **204** is moving or is stationary in lieu of the hub speaker unit **202**. For example, the positioning module **260** can receive an indication that the speaker unit **204** is moving from another component in the speaker unit **204**. For example, when the speaker unit **204** is a detachable speaker, the positioning module **260** can receive an indication signal that the speaker unit **204** has become detached from a connection point to the hub speaker unit **202**, such as a charging port on the hub speaker unit **202**, or another fixed point. In another example, the speaker unit **204** can receive acceleration data from one or more accelerometers and/or an inertial measurement unit indicating movement from a stationary position. In such instances, the positioning module **260** causes the motion sensors **252** to activate and acquire sensor data associated with the movement of the speaker unit **204**.

(44) Additionally or alternatively, in some embodiments, the positioning module **260** generates the filter **222(1)** based on the position data **224(1)** in lieu of receiving the filter **222(1)** from the hub speaker unit **202**. For example, the positioning module **260** can use the position data **224(1)** stored in the memory **244** to determine a direction of the target listening area relative to the current

position of the speaker unit **204**. The positioning module **260** then generates a filter **222(1)** for the output rendering module **270** to use to add the direction to a given audio signal when generating a filtered audio signal.

(45) The sensors **246** include various types of sensors that acquire data about the listening environment. For example, the sensors **246** can include auditory sensors to receive various types of sound (e.g., subsonic pulses, ultrasonic sounds, speech commands, etc.). In some embodiments, the sensors **246** can include other types of sensors. Other types of sensors include optical sensors, such as RGB cameras, time-of-flight cameras, infrared cameras, depth cameras, and/or a quick response (QR) code tracking system. In addition, in some embodiments, the sensor(s) **246** can include wireless sensors, including radio frequency (RF) sensors (e.g., sonar and radar), and/or wireless communications protocols, including Bluetooth, Bluetooth low energy (BLE), cellular protocols, and/or near-field communications (NFC).

(46) In various embodiments, the positioning module **260** uses the sensor data acquired by the sensors **246** to generate the position data **224(1)**. For example, when the hub speaker unit **202** uses one or more emitters to emit positioning signals, the speaker unit **204** includes one or more detectors that generates auditory data that includes the positioning signals and the positioning module **260** processes the received auditory data. The positioning module **260** determines that the auditory data corresponds to the speaker unit **204** receiving the positioning signals at the current position and/or orientation and uses the timing data, such as a determined time between the emitters transmitting the positioning signals and the time that the detectors received the positioning signals to determine the current position and/or orientation of the speaker unit **204**.

(47) The I/O device interface **250** includes any number of different I/O adapters or interfaces used to provide the functions described herein. For example, the I/O device interface **250** could include wired and/or wireless connections, and can use various formats or protocols. In another example, the speaker unit **204**, through the I/O device interface **250**, could receive sensor data from the sensors **246** and/or the motion sensors **252**, input signals, and/or messages via input devices, and can provide output signals to output device(s) to produce outputs in various types (e.g., ultrasonic pulses generated an ultrasonic emitter).

(48) The motion sensors **252** include one or more position sensors, such as one or more accelerometers and/or an IMU. The IMU is a device like a three-axis accelerometer, gyroscopic sensor, and/or magnetometer. In some embodiments, the motion sensors **252** include multiple types of sensors and a sensor fusion hub that combines different types of sensor data. For example, the sensor fusion hub can combine changes detected by the IMU with acceleration data from the accelerometer. Other configurations of the motion sensors **252** are possible. For example, the speaker unit **204** includes a set of optical sensors, a set of auditory sensors, and/or timing circuits as part of the motion sensors **252**. In such instances, the hub speaker unit **202** and/or the speaker unit **204** include the set of optical sensors and/or set of auditory sensors or detectors to acquire various types of test signals and use the timing circuit to perform various triangulation techniques to determine the current position of the speaker unit **204**, such as is described in further detail above. For example, the motion sensors **252** includes auditory sensors that detect auditory signals, such as subsonic or ultrasonic pulses generated by the hub speaker unit **202** at specific times. In such instances, the sensor fusion hub combines the auditory data with timing data generated by the timing circuit to determine the current position and/or orientation of the speaker unit **204**.

(49) In some embodiments, the positioning module **260** processes the multiple types of sensor data to generate the positioning information **254** corresponding to the motion of the speaker unit **204**. For example, the positioning module **260** can process the data provided by the sensor fusion hub to determine the amount of movement (e.g., change in distance and/or orientation) that has occurred since a previous measurement. In some embodiments, the positioning module **260** combines sensor data acquired from the motion sensors **252** with sensor data acquired from the other sensors **246**.

(50) In some embodiments, the speaker unit **204** activates the motion sensors **252** upon detecting a

detachment of the speaker unit **204** from a connection point. In such instances, the positioning module **260** activates the motion sensors **252** to acquire sensor data upon detecting the detachment and deactivate the motion sensors **252** upon determining that the speaker unit **204** is no longer moving.

(51) The output rendering module **270** operates similarly to the output rendering module **226** by processing the audio signal **256** and rendering the audio signal **256**. The output rendering module **270** renders the audio signal **256** by driving the loudspeakers **248** to generate one or more soundwaves corresponding to the audio signal **256**. In some embodiments, the output rendering module **270** receives the audio signal **256** directly from the audio source **206**. Alternatively, the hub speaker unit **202** streams the audio signal **256** to the speaker unit **204** over a media channel, such as a wired or wireless media channel. In various embodiments, the output rendering module **270** is a DSP that processes a given input audio signal by using a filter **222(1)** to generate a filtered audio signal. In such instances, the output rendering module **270** renders the filtered audio signal to generate soundwaves. As discussed above, using the filter **222(1)** adds directivity information to the filtered audio signal such that the speaker unit **204** rendering of the filtered audio signal generates a soundwave in a specific direction. In some embodiments, the output rendering module **270** processes the audio by separating the audio signal into separate spatialized audio signals. In such instances, the produced soundwaves cause the listener to hear portions of the audio as originating at a specific location (e.g., an explosion occurring on the right side of the listening environment).

(52) The network **208** includes a plurality of network communications systems, such as routers and switches, configured to facilitate data communication between the hub speaker unit **202**, the speaker unit **204**, and or other external devices. Persons skilled in the art will recognize that many technically-feasible techniques exist for building the network **208**, including technologies practiced in deploying an Internet communications network. For example, the network **208** can include a wide-area network (WAN), a local-area network (LAN), and/or a wireless (Wi-Fi) network, among others.

(53) The audio source **206** generates one or more audio source signals to be delivered to at least one of hub speaker unit **202** and/or the speaker unit **204**. The audio source **206** can be any type of audio device, such as a personal media player, a smartphone, a portable computer, a television, etc. In some embodiments, the hub speaker unit **202** and/or speaker unit **204** receive one or more audio source signals directly from audio source **206**. The respective output rendering module **226** and/or the output rendering module **270** included in the respective speaker units **202**, **204** can then generate soundwaves based on the audio signal **256** received from the audio source **206** to generate the sound field at the target listening area.

(54) Motion Detection of Satellite Speaker Devices

(55) FIG. 3 is a schematic diagram **300** of the speaker units included in the modular speaker system **200** of FIG. 2 operating to transmit positioning information to a hub speaker unit, according to various embodiments of the present disclosure. In operation, the modular speaker system **200** changes from a first arrangement to a second arrangement when one or more speaker units **204** (e.g., **204(1)**, **204(2)**) move from first locations **302** (e.g., **302(1)**, **302(2)**) to second locations **306** (e.g., **306(1)**, **306(2)**). When a given speaker unit **204** is moving, the positioning information **254** generated reflects the trajectory **304** of the speaker unit **204**. In various embodiments, the position and/or orientation of the speaker unit **204** at the second location **306** is determined using the positioning information **254**.

(56) In various embodiments, at least one of the hub speaker unit **202** or speaker unit **204** generates the positioning information **254**. For example, as shown, each of the speaker units **204** generate positioning information **254** (e.g., **254(1)**, **254(2)**) that indicate the respective trajectories **304** (e.g., **304(1)**, **304(2)**) of the movement that speaker unit **204** experienced when moving from the first location **302**. In such instances, the speaker units **204** transmits the positioning information **254** to

the hub speaker unit **202** and the hub speaker unit **202** generates filters for the speaker units **204** based on the respective position and orientation at the second location **306**.

(57) Alternatively, in some embodiments, the hub speaker unit **202** generates the positioning information **254** based on sensor data acquired by the hub speaker unit **202**. For example, the control module **220** can process optical data (e.g., camera images, infrared data, etc.) to determine changes in the position of the speaker unit **204(2)** over a given time period. In such instances, the control module **220** determines relative coordinates and/or orientations over successive periods to determine the trajectory **304(2)** of the speaker unit **204(2)**.

(58) In various embodiments, the position and/or orientation of the speaker unit **204** is determined as a relative change with respect to the position and/or orientation of the speaker unit **204** at the first location. For example, when the control module **220** processes the positioning information **254(1)**, the current position and orientation of the speaker unit **204(1)** can be stored as a series of position information P.sub.1, P.sub.2 that includes initial coordinates and orientation, and a relative change between the first position and the second position:

$P_{\text{sub.1}} = \{0, 0, 0, 0, 0\}$  $P_{\text{sub.2}} = \{6.5 \text{ m}, 20^\circ, 180^\circ, 0^\circ, 0^\circ\}$ (1)

(59) Where the P.sub.1 in (1) represents the initial set and P.sub.2 represents the relative change from P.sub.1. The relative change indicates that the position and orientation of the speaker unit **204(1)** at the second location **306(1)** is modified by a distance of 6.5 m and 20° from the initial location **302(1)**. The relative change also indicates that the orientation of the speaker unit **204(1)** has been moved 180° from the orientation at the first location **302(1)**.

(60) Alternatively, in some embodiments, the position and/or orientation of the speaker unit **204** can be determined as a relative change with respect to a reference point **308**. In such instances, the reference point is a relatively fixed point, such as a location on the hub speaker unit **202** that is set during initial calibration. In such instances, the control module **220** and/or the output rendering module **270** determines the position of the speaker unit **204** at any given location **302**, **306** as a relative change in position from the reference point **308**.

(61) In various embodiments, when a given speaker unit **204** changes from the second position to a third position (not shown), the hub speaker unit **202** and/or speaker unit **204** detects the motion from the second position. For example, one or more of the motion sensors **252**, such the accelerometer and/or the IMU in the speaker unit **204**, can detect a change in acceleration. In another example, the hub speaker unit **202** can compare camera images and detect a change in position. In some embodiments, the hub speaker unit **202** and/or speaker unit **204** shuts off one or more of the sensors **216**, **246**, **252** upon determining that the speaker unit **204** is stationary. In such instances, the hub speaker unit **202** and/or speaker unit **204** activates sensors **216**, **246**, **252** to determine the positioning information **254** from the second location when motion to the third location is detected.

(62) FIG. 4 is a schematic diagram **400** of the hub speaker unit **202** and the speaker units **204(1)**, **204(2)** included in the modular speaker system **200** of FIG. 2 operating to generate a sound field **436** for a target listening area **440**, according to various embodiments of the present disclosure. In operation, each speaker unit **202**, **204**, includes one or more filters **222** that the control module **220** and/or the positioning module **260** generate. The filters include DSP coefficients that are based on directions generated between the target listening area **440** and the respective positions and orientations of the hub speaker unit **202** and the speaker units **204(1)**, **204(2)**. A given set of DSP coefficients enable the filtered audio signal generated from the filter **222** to steer a given soundwave **402**, **404** produced by one or more loudspeakers **210**, **248** in a specific direction. The respective soundwaves **402** (e.g., **402(1)**, **402(2)**, **402(3)**) and **404** (e.g., **404(1)**, **404(2)**) combine to generate a sound field **436** that encompasses the target listening area **440**.

(63) The target listening area **440** corresponds to the listening area for one or more listeners for the modular speaker system **200**. In some embodiments, the control module **220** and/or positioning module **260** estimate the target listening area **440**. For example, the control module **220** can

estimate the target listening area **440** as an area with a centroid at a predetermined distance and orientation (e.g., approximately 3 m and 0°) from the reference point **308**. Alternatively, the control module **220** can detect the target listening area **440** from other inputs and/or devices. For example, the control module **220** can analyze image data to estimate where the listeners are positioned. In another example, the control module **220** can receive passive infrared data from a remote control or can detect a listener and/or a token proximate to listener to approximate the location of the user. In such instances, the control module **220** determines the location of the target listening area **440**, store the location in the position data **224** and transmits a portion of the position data **224** as position data **224(1)** to the speaker units **204** using one or more messages and/or data packets using a wired or wireless communication medium for use when generating the filters **222**.

(64) In various embodiments, the control module **220** generates multiple filters (e.g., **222(3)**, **222(5)**, **222(5)**) for each of the respective loudspeakers **210** included in the hub speaker unit **202**. In such instances, each loudspeaker **210** produces a soundwave **402** that each have different directions. Alternatively, the control module **220** generates single filter **222** for the hub speaker unit **202**. In such instances, the loudspeakers **210** generates a combined soundwave (e.g., **402(2)**) that is directed towards the target listening area **440**. Additionally or alternatively, the control module **220** generates a filter **222(1)** for the speaker unit **204(1)** and a separate filter **222(2)** for the speaker unit **204(2)**. In such instances, the control module **220** transmits the respective filters **222(1)**, **222(2)** using one or more messages and/or data packets using a wired or wireless communication medium to each speaker unit **204** independently.

(65) When the positioning module **260** in a respective speaker unit **204** generates the filter **222** (e.g., the filter **222(2)** for the speaker unit **204(2)**), the positioning module **260** retrieves the location of the target listening area **440** from the position data **224(1)** and determines the direction of the target listening area **440** relative to the position and orientation of the speaker unit **204**. The positioning module **260** generates a filter **222** with DSP coefficients that steer a soundwave **404**, generated by a subset of the loudspeakers **248**, towards the target listening area **440**.

(66) In some embodiments, when reproducing an audio signal **256**, each of the hub speaker unit **202** and speaker unit **204** receives the positioning information **254** directly. Alternatively, in some embodiments, the hub speaker unit **202** transmits the positioning information **254** to each of the speaker units **204** using one or more messages and/or data packets using a wired or wireless communication medium. For example, as shown, the hub speaker unit **202** receives the audio signal **256** and wirelessly transmits copies of the audio signal **256** to each speaker unit **204** using a media stream. In various embodiments, each filter **222** generates a separate filtered audio signal that includes the directivity information to steer the soundwave that is to be produced. In some embodiments, each of the speaker units **202**, **204** is calibrated based on the distance to ensure that each soundwave **402**, **404** is produced with a specific intensity and a delay such that all of the soundwaves **402**, **404** reach the target listening area **440** synchronously to produce the sound field **436**. As the filters **222(2)** generate filtered audio signals that steer the soundwaves **404** of the speaker units **204** in the direction of the target listening area **440**, the generated sound field **436** encompasses the target listening area **440** and provides an improved listening experience for the listeners within the target listening area **440**.

(67) FIG. 5 is a flowchart of method steps for a hub speaker unit determining a position of a speaker unit based on positioning information to generate a filter for reproducing an audio signal, according to various embodiments of the present disclosure. Although the method steps are described with reference to the embodiments of FIGS. 1-4, persons skilled in the art will understand that any system configured to implement the method steps, in any order, falls within the scope of the present disclosure.

(68) As shown, method **500** begins at step **502**, where the hub speaker unit **202** optionally detects a detachment of the speaker unit **204**. In some embodiments, the hub speaker unit **202** optionally detects the speaker unit **204** being detached from a fixed point, such as a charging port on the hub

speaker unit **202**. In such instances, the hub speaker unit **202** communicates with the speaker unit **204** to receive positioning information **254** while the speaker unit **204** is moving and/or an indication that the speaker unit **204** has stopped moving. For example, the control module **220** receives a signal indicating that the speaker unit **204** has been detached from a connection point to the hub speaker unit **202**. In another example, the control module **220** processes received auditory data and determines that the auditory data includes a detachment sound corresponding to the speaker unit **204** being detached from the connection point. In such instances, the control module **220** communicates with the speaker unit **204** to receive positioning information **254** from the speaker unit **204**.

(69) At step **504**, the hub speaker unit **202** optionally receives positioning information **254** associated with the speaker unit **204**. In various embodiments, the control module **220** operating in the hub speaker unit **202** receives a signal indicating that the target listening area **440** is moving. In some embodiments, the signal corresponds to sensor data that the control module **220** interprets at an initiation of movement of the speaker unit **204**. Alternatively, in some embodiments, the hub speaker unit **202** receives a notification message from the speaker unit **204** that the speaker unit **204** is moving. In various embodiments, the hub speaker unit **202**, upon determining that the speaker unit **204** is moving, receives periodic messages from the speaker unit **204** that include the positioning information **254** corresponding to the movement of the speaker unit **204** through an environment over a time period.

(70) In some embodiments, the positioning information **254** includes sensor data generated by the IMU (e.g., acceleration measurements, magnetic field measurements, angular rates, etc.) on the speaker unit **204** while moving. In such instances, the control module **220** receives and aggregates the positioning information **254** included in messages transmitted by the speaker unit **204** and determines the trajectory **304** of the speaker unit **204**.

(71) At step **506**, the hub speaker unit **202** determines whether the speaker unit **204** is still moving. In some embodiments, the control module **220** processes the received positioning information **254** to determine whether the speaker unit **204** is still moving or is stationary. Alternatively, in some embodiments, the control module **220** receives a message from the speaker unit **204** indicating that the speaker unit **204** has stopped moving. For example, the positioning module **260**, upon determining that the speaker unit **204** is stationary, causes the speaker unit **204** to transmit a request for a filter **222(1)**. In such instances, the control module **220** interprets the received filter request as an indication that the speaker unit **204** has stopped moving and is stationary. When the control module **220** determines that the speaker unit **204** is still moving, the hub speaker unit **202** returns to step **504** to optionally receive additional positioning information **254**. Otherwise, the hub speaker unit **202** determines that the speaker unit **204** is stationary and proceeds to step **508**.

(72) At step **508**, the hub speaker unit **202** determines the current position of the speaker unit **204**. In various embodiments, the control module **220** processes positioning information **254** to determine the current position and/or orientation of the now-stationary speaker unit **204**. Upon determining the current position and/or orientation of the speaker unit **204**, the hub speaker unit **202** stores the current position and/or orientation as a portion of the position data **224**. In some embodiments, the control module **220** processes the positioning information **254** to determine the trajectory **304** of the speaker unit **204** from a previous location. The control module **220** uses various positioning techniques to identify the endpoint of the trajectory **304**, where the position and/or orientation of the speaker unit **204** at the endpoint of the trajectory **304** corresponds to the current position and/or orientation of the speaker unit **204**. The control module **220** then stores the current position and/or orientation as a portion of the position data **224**.

(73) Alternatively, in some embodiments, the control module **220** performs various positioning algorithms (e.g., triangulation using sensor data) to determine the current position and/or orientation of the now-stationary speaker unit **204**. For example, any of the positioning and/or orientation algorithms discussed above with respect to FIG. **2** can be used to determine the current

position and orientation at the second location **306** of the speaker unit **204**.

(74) In some embodiments, the position data **224** includes a reference position **308**. In such instances, the control module **220** determines the current position and/or orientation of the hub speaker unit **202** and/or the speaker unit **204** relative to the reference position **308**. For example, the hub speaker unit **202** determines a specific position of loudspeakers **210** within the hub speaker unit **202** relative to the reference position **308**. In such instances, the control module **220** also determines the current position and/or orientation of the speaker unit **204** as a distance and set of angles relative to the reference position **308**.

(75) At step **510**, the hub speaker unit **202** generates one or more filters **222** for the hub speaker unit **202** and the speaker unit **204**. In various embodiments, the control module **220** generates filters **222** for each of the hub speaker unit **202** and the speaker unit **204** to use when reproducing audio signals. In some embodiments, the control module **220** determines one or more directions towards a target listening area **440** relative to the positions and orientations of the loudspeakers **248** within the speaker unit **204**. In such instances, the control module **220** generates a filter **222(1)** for the output rendering module **270** to use to generate a filtered audio signal. When the output rendering module **270** drives the loudspeakers **248** included in the speaker unit **204** with the filtered audio signal, a soundwave **404** is steered toward the direction of the target listening area **440** to generate a sound field that includes a sweet spot that encompasses the target listening area **440**.

(76) In some embodiments, the control module **220** generates DSP coefficients for a given filter **222** based on the position of the hub speaker unit **202** and/or the speaker unit **204**. For example, the control module **220** generate a filter **222(1)** for the speaker unit **204**, where the filter **222(1)** includes DSP coefficients that cause the loudspeakers **248** to generate a smaller soundwave **404** when positioned at a location proximate to the hub speaker unit **202**. In another example, the control module **220** generates the filter **222(1)** with DSP coefficients that cause the loudspeakers **248** to generate a larger soundwave **404** when positioned at a more remote location.

(77) At step **512**, the hub speaker unit **202** transmits the filter **222(1)** to the speaker unit **204**. In various embodiments, the control module **220** generates a message that includes the filter **222(1)** in the payload. The filter **222(1)** included in the message is the filter that the control module **220** designed for the speaker unit **204** (e.g., the filter **222(1)** containing the applicable DSP coefficients). Upon generating the message, the hub speaker unit **202** transmits the message to the speaker unit **204**.

(78) At step **514**, the hub speaker unit **202** transmits an audio signal **256** to the speaker unit **204**. In various embodiments, the hub speaker unit **202** receives an input audio signal from an audio source (e.g., the audio source **206**). In some embodiments, the output rendering module **226** receives an input audio signal from the audio source **206** via a wire, a wireless stream, or via a network **208**. In such instances, the hub speaker unit **202** wirelessly transmits the input audio signal **256** to the speaker unit **204** in a stream using a media channel established between the hub speaker unit **202** and the speaker unit **204**.

(79) Alternatively, in some embodiments, the hub speaker unit **202** filters the audio signal **256** using the set of filters **222** that include the filters for the speaker units **204** (e.g., use the filter **222(1)** designed for the speaker unit **204(1)**) to generate a set of filtered audio signals for the hub speaker unit **202** and the speaker units **204**. In such instances, the hub speaker unit **202** transmits the set of filtered audio signals to the respective speaker units **204** in lieu of transmitting the respective filters **222** (e.g., transmitting the filter **222(1)** to the speaker unit **204(1)**) and subsequently transmitting the audio signal **256**. For example, when the hub speaker unit **202** includes more processing resources than a set of speaker units **104**, the hub speaker unit **202** filters the audio signal **256** to through the set of filters **222** in parallel. The hub speaker unit **202** then transmits each of the filtered audio signals to the corresponding speaker unit **204** for playback.

(80) At step **516**, the hub speaker unit **202** uses the filter **222** to generate a filtered audio signal. In various embodiments, the output rendering module **226** processes the input audio signal by using

the one or more filters 222 generated for the hub speaker unit 202 (e.g., the filters 222(3)-222(5)) to generate one or more filtered audio signals. In some embodiments, the one or more filtered audio signals includes directivity information corresponding to the respective directions towards the target listening area 440 relative to the reference position 308 and/or specific positions of the hub speaker unit 202 (e.g., the positions and/or orientations of the respective loudspeakers 210).

(81) At step 518, the hub speaker unit 202 reproduces the filtered audio signal. In various embodiments, the output rendering module 226 reproduces the one or more filtered audio signals by generating an audio output corresponding to the one or more filtered audio signals created by the one or more filters 222. For example, the output rendering module 226 can drive the loudspeakers 210 included in the hub speaker unit 202 to generate a set of soundwaves 402 in the direction(s) toward the target listening area 440. In various embodiments, the set of soundwaves that the loudspeakers 210 generates combine with one or more other soundwaves 404 provided by other speaker units 204 of the modular speaker system 200 to generate a sound field 436 that includes a sweet spot that encompasses the target listening area 440.

(82) Upon generating the set of soundwaves 402, the hub speaker unit 202 returns to step 502 or 504 to optionally detect an additional detachment and/or receive additional positioning information 254. For example, the hub speaker unit 202 returns to step 502 to detect a reattachment to the connection point to the hub speaker unit 202. In such instances, the speaker unit 204 repeats method 500 to acquire filters applicable to the new position of 248 speaker unit 204. Alternatively, the hub speaker unit 202 proceeds to step 504 to receive additional positioning information 254 associated with a move to a new location, or proceeds to step 506 to determine whether the speaker unit 204 stopped moving from additional motion.

(83) FIG. 6 is a flowchart of method steps for a speaker unit transmitting sensor data to identify a new position associated with generating a filtered audio signal, according to various embodiments of the present disclosure. Although the method steps are described with reference to the embodiments of FIGS. 1-4, persons skilled in the art will understand that any system configured to implement the method steps, in any order, falls within the scope of the present disclosure.

(84) As shown, method 600 begins at step 602, where the speaker unit 204 optionally transmits positioning information 254 to the hub speaker unit 102. In various embodiments, the positioning module 260 receives sensor data acquired by one or more motion sensors 252; the positioning module 260 causes the speaker unit 204 to transmit the sensor data in one or more messages to the hub speaker unit 202. In some embodiments, the motion sensors 252 includes multiple types of sensors (e.g., gyroscopes, infrared sensors, microphones, etc.) and a sensor fusion hub that combines the different types of data into a set of positioning information 254. For example, the positioning information 254 is sensor data generated by the IMU (e.g., acceleration measurements, magnetic field measurements, angular rates, etc.).

(85) In some embodiments, the speaker unit 204 detects a detachment of the speaker unit 204 from a connection point. In such instances, the positioning module 260 activates the motion sensors 252 to acquire sensor data associated with the movement of the speaker unit 204. The positioning module 260 produces positioning information 254 from the acquired sensor data and transmits the positioning information 254 in one or more messages to the hub speaker unit 202.

(86) At step 604, the speaker unit 204 determines whether the speaker unit 204 is still moving. In various embodiments, the positioning module 260 determines whether the speaker unit 204 has stopped moving and is stationary. For example, the positioning module 260 determines whether the sensor data indicates that the speaker unit has changed position from a previous time. When the positioning module 260 determines that the speaker unit 204 is still in motion, the speaker unit 204 returns to step 602 to optionally transmit positioning information 254 to the hub speaker unit 202. Otherwise, when the positioning module 260 determines that the speaker unit 204 has stopped moving, the positioning module 260 causes the speaker unit 204 to proceed to step 606.

(87) At step 604, the speaker unit 204 receives a filter 222(1) from the hub speaker unit 202. In

various embodiments, the speaker unit **204** communicates with the hub speaker unit **202** and/or coordinates with the hub speaker unit **202** to perform various positioning techniques to determine the current position and/or orientation of the speaker unit **204**, such as any of the techniques described above with respect to FIG. 2. When the hub speaker unit **202** determines the current position and/or orientation of the speaker unit **204**, the hub speaker unit **202** generates a filter **222(1)** for the speaker unit **204** and transmits a message including the filter **222(1)** to the speaker unit **204**.

(88) In some embodiments, the control module **220** generates the filter **222(1)** based on the positioning information **254** that the speaker unit **204** provides. For example, the control module **220** processes the positioning information **254** to determine that the speaker unit **204** is no longer moving. In such instances, the control module **220** of the hub speaker unit **104** uses the positioning information **254** to determine the current position and/or orientation of the speaker unit **204** (e.g., the arrangement of the speaker units **202**, **204** when the speaker unit is at the second location **306**) and generates a filter **222(1)** based on the current position and/or orientation.

(89) Alternatively, in some embodiments, the control module **220** determines that the speaker unit **204** has stopped moving and, in response, transmits a filter request message to the hub speaker unit **202**. In such instances, as discussed above for step **508**, the hub speaker unit **202** and/or the speaker unit **204** perform various positioning algorithms to determine the current position of the speaker unit **204**. The hub speaker unit **202** generates a filter **222(1)** for the speaker unit **204** based on the current position and/or orientation of the speaker unit **204** and transmits a message containing the filter **222(1)** to the speaker unit **204**.

(90) In some embodiments, the control module **220** determines a direction towards the target listening area **440** relative to the current position and/or orientation of the speaker unit **204**. In such instances, the control module **220** generates a filter **222(1)** operable by the output rendering module **270** to use when generating a filtered audio signal driving the loudspeakers **248** with the filtered audio signal. Driving the loudspeakers **248** with the filtered audio signal produces an audio output that has directivity corresponding to the direction toward the target listening area **440**. Upon generating the filters **222(1)**, the control module **220** transmits the filters **222** to the speaker unit **204**, where the speaker unit **204** stores the filter **222(1)** in memory **244**.

(91) At step **608**, the speaker unit **204** uses the filter **222(1)** to generate a filtered audio signal. In various embodiments, the output rendering module **270** processes a received audio signal **256** by using the filter **222(1)** to generate a filtered audio signal. In some embodiments, the filtered audio signal includes directivity information corresponding to the direction towards the target listening area **440**.

(92) At step **610**, the speaker unit **204** reproduces the filtered audio signal. In various embodiments, the output rendering module **270** reproduces the filtered audio signal by generating an audio output corresponding to the filtered audio signal. For example, the output rendering module **270** can drive a subset of the loudspeakers **248** to generate a soundwave in the direction of the target area. In various embodiments, the soundwave **404** that the speaker unit **204** generates combines with one or more other soundwaves provided by other units of the modular speaker system **200** to generate a sound field **436**. The sound field **436** includes a sweet spot that encompasses the target listening area **440**. Upon generating the soundwaves, the speaker unit **204** returns to step **702** to transmit messages including the sensor data to the hub speaker unit **202**.

(93) As discussed above and further emphasized here, FIGS. 5 and 6 are merely examples, which should not unduly limit the scope of the claims. Many variations, alternatives, and modifications are possible.

(94) In some embodiments, the hub speaker unit **202** acquires sensor data and/or positioning information **254**. The control module **220** determines the current position and/or orientation of the speaker unit **204** and stores determines the current position and/or orientation of the speaker unit **204** as a portion of the position data **224**. Alternatively, in some embodiments, the speaker unit **204**

acquires sensor data and generates positioning information **254**. The positioning module **260** determines the current position and/or orientation of the speaker unit **204** from the positioning information **254** and stores determines the current position and/or orientation of the speaker unit **204** as position data **224**.

(95) In some embodiments, the control module **220** uses the portion of the position data **224** for the current position and/or orientation of the speaker unit **204** to generate a filter **222** containing DSP coefficients for the speaker unit **204** (e.g., the filter **222(1)** for the speaker unit **204(1)**).

Alternatively, the positioning module **260** uses the position data **224** for the current position and/or orientation of the speaker unit **204** to generate the filter **222(1)** containing the DSP coefficients for the speaker unit **204**.

(96) In some embodiments, the output rendering module **226** operating on the hub speaker unit **202** applies the filter **222(1)** designed for the speaker unit **204** on a received audio signal **256** to generate a filtered audio signal that the speaker unit **204** is to reproduce. Upon generating the filtered audio signal, the output rendering module **226** causes the hub speaker unit **202** to transmit the filtered audio signal to the speaker unit **204** for reproduction by the speaker unit **204**.

Alternatively, the output rendering module **270** operating on the speaker unit **204** applies the filter **222(1)** on a received audio signal **256** to generate a filtered audio signal. The output rendering module **270** reproduces the filtered audio signal.

(97) FIG. 7 is a flowchart of method steps for a speaker unit processing positioning information to generate a filter for generating a filtered audio signal, according to various embodiments of the present disclosure. Although the method steps are described with reference to the embodiments of FIGS. 1-4, persons skilled in the art will understand that any system configured to implement the method steps, in any order, falls within the scope of the present disclosure.

(98) As shown, method **700** begins at step **702**, where the speaker unit **204** optionally detects a detachment of the speaker unit **204** has initiated movement. In various embodiments, the positioning module **260** operating in the speaker unit **204** detects a detachment of the speaker unit **204** from a static mount or a connection to another speaker unit (e.g., the hub speaker unit **202**), such as a charging port. In some embodiments, the positioning module **260** determines the position of the speaker unit **204** when the detachment is detected. In such instances, the positioning module **260** assigns the determined position as a starting position used to determine a change in relative positions based on the movement.

(99) At step **704**, the speaker unit **204** optionally activates the motion sensors **252**. In various embodiments, the speaker unit **204** responds to the detection of the detachment of the speaker unit **204** in step **502** by activating one or more motion sensors **252**. For example, the positioning module **260** operating in the speaker unit **204** responds to a detection of the speaker unit **204** detaching from the connection point by activating one or more motion sensors **252** to acquire sensor data and generate positioning information **254** from the sensor data. In some embodiments, the motion sensors **252** include multiple types of sensors (e.g., gyroscopes, infrared sensors, microphones, etc.) and a sensor fusion hub that combines the different types of data into a set of positioning information **254**.

(100) At step **706**, the speaker unit **204** processes the positioning information **254** acquired by the motion sensors **252**. In various embodiments, the positioning module **260** periodically generates positioning information **254** corresponding to different positions and/or orientations at different times (e.g., positioning information **254(1)** at time $t_{sub.1}$, positioning information **254(2)** at time t_2 , etc.). In such instances, the positioning module **260** aggregates the positioning information **254** to track the trajectory **304** of the speaker unit **204** relative to the starting position. In some embodiments, the motion data can be sensor data generated by the IMU (e.g., acceleration measurements, magnetic field measurements, angular rates, etc.). In such instances, the speaker unit **204** aggregates the sensor data and determines a trajectory of the speaker unit **204**.

(101) Alternatively, in some embodiments, the positioning module **260** performs various

positioning algorithms (e.g., triangulation using sensor data) to determine the current position and/or orientation of the now-stationary speaker unit **204**. For example, any of the positioning and/or orientation algorithms discussed above with respect to FIG. **2** can be used to determine the current position and orientation at the second location **306** of the speaker unit **204**.

(102) At step **708**, the speaker unit **204** determines whether the speaker unit **204** is still moving. In various embodiments, the positioning module **260** processes the positioning information **254** to determine the current position and/or orientation relative to the previous position and/or orientation associated with the positioning information **254** to determine whether the speaker unit **204** is stationary or remains in motion. When the positioning module **260** determines that the speaker unit **204** remains in motion, the positioning module **260** returns to step **706** to process additional positioning information **254**. Otherwise, the positioning module **260** determines that the speaker unit **204** is not in motion and proceeds to step **510**.

(103) At step **710**, the speaker unit **204** determines the current position of the speaker unit **204**. In various embodiments, the positioning module **260** processes the positioning information **254** to determine the current position and/or orientation of the speaker unit **204**. Alternatively, in some embodiments, as discussed in FIG. **2**, from the hub speaker unit **202** and/or speaker unit **204** performing various positioning algorithms to determine the current position and/or orientation of the speaker unit **204**. The positioning module **260** then stores the generates position data **224(1)** or receives the position data **224(1)** from the hub speaker unit **202** and stores the position data **224(1)**.

(104) In some embodiments, the current position and/or corresponds to an absolute position/orientation (e.g., specific coordinates of a location and/or orientation of the speaker unit **204**) within an environment. Alternatively, in some embodiments, the current position and/or orientation can correspond to a position relative to a reference point, such as the starting position of the speaker unit **204** determined in step **502**, or the position of the hub speaker unit **202**. For example, upon storing the starting position and/or orientation at the first location **302(1)** as a portion of the position data **224(1)**, the positioning module **260** can store the current position and/or orientation as a distance and a set of angles relative to the starting position and/or orientation at the first location **302(1)**.

(105) At step **712**, the speaker unit **204** generates a filter **222(1)** based on the current position and/or orientation. In various embodiments, the positioning module **260** generates a filter **222(1)** to use when reproducing audio signals. In some embodiments, the positioning module **260** determines a direction towards a target listening area **440** relative to the current position and/or orientation of the speaker unit **204**. In such instances, the speaker unit **204** generates a filter **222(1)** that the output rendering module **270** uses to drive the loudspeakers **248** to produce an audio output that has directivity corresponding to the determined direction towards the target listening area **440**.

(106) At step **714**, the speaker unit **204** uses the filter **222(1)** to generate a filtered audio signal. In various embodiments, the output rendering module **270** processes a received audio signal **256** by using the filter **222(1)** to generate a filtered audio signal. In some embodiments, the filtered audio signal includes directivity information corresponding to the direction towards the target listening area **440** relative to the current position and/or orientation

(107) At step **716**, the speaker unit **204** reproduces the filtered audio signal. In various embodiments, the output rendering module **270** reproduces the filtered audio signal by generating an audio output corresponding to the filtered audio signal. For example, the output rendering module **270** can drive a subset of the loudspeakers **248** to generate a soundwave **404** in the direction of the target listening area **440**. In various embodiments, the soundwave **404** that the speaker unit **204** generates combines with one or more other soundwaves **402**, **404** provided by other speaker units **202**, **204** of the modular speaker system **200** to generate a sound field **436**. The sound field **436** includes a sweet spot that encompasses the target listening area **440**.

(108) Upon generating the soundwaves **402**, **404** the speaker unit **204** returns to step **702-706** to optionally detect a reattachment to the connection point, activate the motion sensors **252**, and/or

process position information **254**. In such instances, the speaker unit **204** repeats method **700** to acquire a filter **222(1)** applicable to the new position of the speaker unit **204**.

(109) FIG. **8** is a flowchart of method steps for a hub speaker unit generating one or more filters for generating one or more filtered audio signals, according to various embodiments of the present disclosure. Although the method steps are described with reference to the embodiments of FIGS. **1-4**, persons skilled in the art will understand that any system configured to implement the method steps, in any order, falls within the scope of the present disclosure.

(110) As shown, method **800** begins at step **802**, where the hub speaker unit **202** optionally detects the detachment of the speaker unit **204**. In various embodiments, the control module **220** operating in the hub speaker unit **202** optionally detects that the speaker unit **204** is detached from a connection point.

(111) At step **804**, the hub speaker unit **202** optionally determines the position of the speaker unit **204**. In various embodiments, the control module **220** determines the position of the speaker unit **204** that after the speaker unit **204**. For example, upon determining that the speaker unit **204** is moving, the hub speaker unit **202** can receive periodic messages from the speaker unit **204** that include the positioning information **254** corresponding to the movement of the speaker unit **204** through an environment. In such instances, the control module **220** processes the positioning information **254** to track the movement of the speaker unit **204**. Alternatively, the hub speaker unit **202** determines that the speaker unit **204** has stopped moving. In such instances, the hub speaker unit **202** performs one or more positioning algorithms to determine the position of the speaker unit **204** and transmit a message to the speaker unit **204** that includes the current position and/or orientation of the speaker unit **204** in the payload.

(112) At step **806**, the hub speaker unit **202** generates one or more filters **222** for the hub speaker unit **202**. In various embodiments, the control module **220** generates one or more filters **222** for use by the output rendering module **226** when reproducing audio signals. In some embodiments, the control module **220** determines one or more directions towards a target listening area **440** relative to the reference position **308** and/or other positions of the loudspeakers **248** within the hub speaker unit **202**. In such instances, the control module **220** generates one or more filters **222** that the output rendering module **226** uses to drive the loudspeakers **248** to produce one or more audio outputs that respectively have directivity corresponding to the determined direction of the target listening area **440**.

(113) In some embodiments, the control module **220** generates the one or more filters **222** for the hub speaker unit **202** with DSP coefficients that are also based on the current position and/or orientation of the speaker unit **204**. For example, the control module **220** can generate one or more filters **222** that causes the loudspeakers **210** in the hub speaker unit **202** to generate smaller soundwaves **402** when the speaker unit **204** is positioned at a location proximate to the hub speaker unit **202**. In another example, the control module **220** can generate the one or more filters **222** for the hub speaker unit **202** that causes the loudspeakers **210** to generate larger soundwaves **402** when the speaker unit **204** is positioned at a more remote location.

(114) At step **808**, the hub speaker unit **202** transmits an audio signal to the speaker unit **204**. In various embodiments, the hub speaker unit **202** receives an input audio signal from an audio source (e.g., the audio source **206**). In some embodiments, the output rendering module **226** receives an input audio signal from the audio source **206** via a wire, a wireless stream, or via a network **208**. In some embodiments, the hub speaker unit **202** wirelessly transmits the input audio signal to the speaker unit **204** in a stream using a media channel established between the hub speaker unit **202** and the speaker unit **204**.

(115) At step **810**, the hub speaker unit **202** uses the one or more filter **222** to generate a filtered audio signal. In various embodiments, the output rendering module **226** processes the input audio signal by using the one or more filters **222** to generate one or more filtered audio signals. In some embodiments, the filtered audio signal can include directivity information corresponding to the

direction of the target listening area **440** relative to the reference position and/or positions of the hub speaker unit **202**.

(116) At step **812**, the hub speaker unit **202** reproduces the filtered audio signal. In various embodiments, the output rendering module **226** reproduces the filtered audio signal by generating an audio output corresponding to the filtered audio signal. For example, the output rendering module **226** can drive the loudspeakers **210** included in the hub speaker unit **202** to generate a set of soundwaves **402** in the direction toward the target listening area **440**. In various embodiments, the set of soundwaves **402** that the loudspeakers **210** generate combine with one or more other soundwaves **404** provided by the speaker units **204** of the modular speaker system **200** to generate a sound field **436**. The sound field **436** includes a sweet spot that encompasses the target listening area **440**. Upon generating the set of soundwaves **402**, the hub speaker unit **202** returns to steps **802-806** to optionally detect a detachment of the speaker unit **204** reattachment to the connection point, detachment from a separate connection point, determine a new position based on movement from the current position, or generate a new set of filters **222** for the hub speaker unit **202**.

(117) In sum, a modular speaker system determines a position for a speaker unit upon determining that the motion of one or more speaker units has stopped. In various embodiments, a positioning module operating on the speaker unit uses various sensor information and/or signals to determine the position of the speaker unit. The positioning module generates a filter of the speaker unit based on the position of the speaker unit when the speaker unit stops moving. In some embodiments, the filter includes digital signal processing components that provide directionality to an audio signal such that the speaker unit reproduces soundwaves that travel in the direction towards a target sound area.

(118) Alternatively, in some embodiments, a control module operating on the hub speaker unit processes the positioning information and uses the positioning information to generate a set of filters. The set of filters includes a filter to be used by the speaker unit to generate the filtered audio signal. In some embodiments, the set of filters includes a respective filter for use by each of the hub speaker unit and each of the speaker units. The speaker units use their respective filters to generate filtered audio signals and reproduce the audio signals by generating soundwaves corresponding to the filtered audio signals. The soundwaves combine within the listening environment to generate a sound field that covers a target listening area.

(119) At least one technical advantage of the disclosed techniques relative to the prior art is that, with the disclosed techniques, the modular speaker system calibrates the speaker units in the system to generate an optimized sound field without a user having to perform iterative positioning and calibrating processes. In particular, the disclosed techniques automatically calibrate the modular speaker system whenever a speaker is moved. Further, the disclosed techniques reduce the number of times that the positions of the speaker units are determined, which provide an optimized sound field while using less processing resources and consuming less power than conventional calibration approaches. These technical advantages provide one or more technological improvements over prior art approaches.

(120) 1. In various embodiments, a computer-implemented method detecting that a speaker unit has moved to a first location, determining, based on positioning information associated with the speaker unit, a position and an orientation of the speaker unit relative to a target listening area, filtering, using a filter that is determined using at least the position and the orientation, an input audio signal to generate a filtered audio signal, and outputting the filtered audio signal using one or more loudspeakers.

(121) 2. The computer-implemented method of clause 1, where the step of detecting that the speaker unit has moved to the first location comprises detecting that the speaker unit is stationary.

(122) 3. The computer-implemented method of clause 1 or 2, where the step of detecting that the speaker unit is stationary comprises determining, from the positioning information, that the speaker unit has not changed position from a previous location.

(123) 4. The computer-implemented method of any of clauses 1-3, where an inertial measurement unit included in the speaker unit generates a first subset of positioning information including at least one of acceleration measurements or magnetic field measurements, and the step of determining the position of the speaker unit comprises processing the first subset of positioning information to determine a change in position of the speaker unit from a previous location.

(124) 5. The computer-implemented method of any of clauses 1-4, where the inertial measurement unit generates a second subset of positioning information including at least one of magnetic field measurements or angular rates of change, and the step of determining the orientation of the speaker unit comprises processing the second subset of positioning information to determine a change in orientation from a previous orientation.

(125) 6. The computer-implemented method of any of clauses 1-5, where the step of determining the position of the speaker unit comprises using triangulation based on one or more signals emitted by the speaker unit or a hub unit.

(126) 7. The computer-implemented method of any of clauses 1-6, where the position and orientation of the speaker unit at the first location comprises a distance and a set of angles relative to one of a previous location of the speaker unit, or a reference location.

(127) 8. The computer-implemented method of any of clauses 1-7, further comprising transmitting the positioning information to a hub unit, where the positioning information is usable by the hub unit to determine the position and the orientation of the speaker unit.

(128) 9. The computer-implemented method of any of clauses 1-8, further comprising the speaker unit receiving the filter from the hub unit.

(129) 10. The computer-implemented method of any of clauses 1-9, further comprising generating, by the speaker unit, the filter based on the position and the orientation.

(130) 11. In various embodiments, a speaker unit comprises one or more loudspeakers, a memory storing instructions, and a processor coupled to the memory that executes the instructions to perform steps comprising detecting that the speaker unit has moved to a first location, determining, based on positioning information associated with the speaker unit, a position and an orientation of the speaker unit relative to a target listening area, filtering, using a filter that is determined using at least the position and the orientation, an input audio signal to generate a filtered audio signal, and outputting the filtered audio signal using the one or more loudspeakers.

(131) 12. The speaker unit of clause 11, where the speaker unit is detachable from a connection point of a hub unit, and the steps further comprise detecting that the speaker unit has become detached from the hub unit.

(132) 13. The speaker unit of clause 11 or 12, where the connection point is a charging port.

(133) 14. The speaker unit of any of clauses 11-13, further comprising one or more sensors that include at least one of an accelerometer, a gyroscopic sensor, an inertial management unit, or a magnetometer, where the position and the orientation of the speaker unit are determined from data collected using the one or more sensors.

(134) 15. The speaker unit of any of clauses 11-14, where the steps further comprise, in response to detecting that the speaker unit has become detached, activating the one or more sensors.

(135) 16. The speaker unit of any of clauses 11-15, where the step of detecting that the speaker unit has moved to the first location comprises detecting that the speaker unit is stationary.

(136) 17. The speaker unit of any of clauses 11-16, where the steps further comprise transmitting the positioning information to a hub unit, where the positioning information is usable by the hub unit to determine the position and the orientation of the speaker unit.

(137) 18. The speaker unit of any of clauses 11-17, where the steps further comprise receiving the filter from a hub unit, or generating the filter based on the position and the orientation.

(138) 19. One or more non-transitory computer-readable media storing instructions that, when executed by one or more processors associated with a hub unit of a speaker system, cause the one or more processors to perform the steps of receiving an indication that a speaker unit has become

stationary, and determining, based on positioning information associated with the speaker unit and in response to receiving the indication, a position and an orientation of the speaker unit relative to a target listening area, generating, based on the position and the orientation, a filter useable to filter an input audio signal to generate a filtered audio signal, wherein when the filtered audio signal is output by one or more loudspeakers in the speaker unit, the filtered audio signals generate a sweet spot in a sound field in the target listening area.

(139) 20. The one or more non-transitory computer-readable media of claim **19**, the steps further comprising transmitting the filter to the speaker unit.

(140) Any and all combinations of any of the claim elements recited in any of the claims and/or any elements described in this application, in any fashion, fall within the contemplated scope of the present invention and protection.

(141) The descriptions of the various embodiments have been presented for purposes of illustration, but are not intended to be exhaustive or limited to the embodiments disclosed. Many modifications and variations will be apparent to those of ordinary skill in the art without departing from the scope and spirit of the described embodiments.

(142) Aspects of the present embodiments may be embodied as a system, method or computer program product. Accordingly, aspects of the present disclosure may take the form of an entirely hardware embodiment, an entirely software embodiment (including firmware, resident software, micro-code, etc.) or an embodiment combining software and hardware aspects that may all generally be referred to herein as a “module,” a “system,” or a “computer.” In addition, any hardware and/or software technique, process, function, component, engine, module, or system described in the present disclosure may be implemented as a circuit or set of circuits. Furthermore, aspects of the present disclosure may take the form of a computer program product embodied in one or more computer readable medium(s) having computer readable program code embodied thereon.

(143) Any combination of one or more computer readable medium(s) may be utilized. The computer readable medium may be a computer readable signal medium or a computer readable storage medium. A computer readable storage medium may be, for example, but not limited to, an electronic, magnetic, optical, electromagnetic, infrared, or semiconductor system, apparatus, or device, or any suitable combination of the foregoing. More specific examples (a non-exhaustive list) of the computer readable storage medium would include the following: an electrical connection having one or more wires, a portable computer diskette, a hard disk, a random access memory (RAM), a read-only memory (ROM), an erasable programmable read-only memory (EPROM or Flash memory), an optical fiber, a portable compact disc read-only memory (CD-ROM), an optical storage device, a magnetic storage device, or any suitable combination of the foregoing. In the context of this document, a computer readable storage medium may be any tangible medium that can contain, or store a program for use by or in connection with an instruction execution system, apparatus, or device.

(144) Aspects of the present disclosure are described above with reference to flowchart illustrations and/or block diagrams of methods, apparatus (systems) and computer program products according to embodiments of the disclosure. It will be understood that each block of the flowchart illustrations and/or block diagrams, and combinations of blocks in the flowchart illustrations and/or block diagrams, can be implemented by computer program instructions. These computer program instructions may be provided to a processor of a general-purpose computer, special purpose computer, or other programmable data processing apparatus to produce a machine. The instructions, when executed via the processor of the computer or other programmable data processing apparatus, enable the implementation of the functions/acts specified in the flowchart and/or block diagram block or blocks. Such processors may be, without limitation, general purpose processors, special-purpose processors, application-specific processors, or field-programmable gate arrays.

(145) The flowchart and block diagrams in the figures illustrate the architecture, functionality, and operation of possible implementations of systems, methods and computer program products according to various embodiments of the present disclosure. In this regard, each block in the flowchart or block diagrams may represent a module, segment, or portion of code, which comprises one or more executable instructions for implementing the specified logical function(s). It should also be noted that, in some alternative implementations, the functions noted in the block may occur out of the order noted in the figures. For example, two blocks shown in succession may, in fact, be executed substantially concurrently, or the blocks may sometimes be executed in the reverse order, depending upon the functionality involved. It will also be noted that each block of the block diagrams and/or flowchart illustration, and combinations of blocks in the block diagrams and/or flowchart illustration, can be implemented by special purpose hardware-based systems that perform the specified functions or acts, or combinations of special purpose hardware and computer instructions.

(146) While the preceding is directed to embodiments of the present disclosure, other and further embodiments of the disclosure may be devised without departing from the basic scope thereof, and the scope thereof is determined by the claims that follow.

Claims

1. A computer-implemented method comprising: detecting that a speaker unit has moved to a first location; determining, based on positioning information associated with the speaker unit, a position and an orientation of the speaker unit relative to a target listening area; receiving, by the speaker unit from a hub unit, a message including a filter, wherein; the filter is generated based on at least the position and the orientation, and the filter includes a plurality of digital signal processor (DSP) coefficients that were generated by the hub unit based on the positioning information; receiving, by the speaker unit, an input audio signal; filtering, by the speaker unit using the filter, the input audio signal to generate a filtered audio signal, wherein the filter with the plurality of DSP coefficients steers the filtered audio signal to the target listening area; and outputting, by the speaker unit, the filtered audio signal using one or more loudspeakers to generate at least a portion of a sound field that includes a sweet spot in the target listening area.
2. The computer-implemented method of claim 1, wherein the step of detecting that the speaker unit has moved to the first location comprises detecting that the speaker unit is stationary.
3. The computer-implemented method of claim 2, wherein the step of detecting that the speaker unit is stationary comprises determining, from the positioning information, that the speaker unit has not changed position from a previous location.
4. The computer-implemented method of claim 1, wherein: an inertial measurement unit included in the speaker unit generates a first subset of positioning information including at least one of acceleration measurements or magnetic field measurements; and the step of determining the position of the speaker unit comprises processing the first subset of positioning information to determine a change in position of the speaker unit from a previous location.
5. The computer-implemented method of claim 4, wherein: the inertial measurement unit generates a second subset of positioning information including at least one of magnetic field measurements or angular rates of change; and the step of determining the orientation of the speaker unit comprises processing the second subset of positioning information to determine a change in orientation from a previous orientation.
6. The computer-implemented method of claim 1, wherein the step of determining the position of the speaker unit comprises using triangulation based on one or more signals emitted by the speaker unit or a hub unit.
7. The computer-implemented method of claim 1, wherein the position and orientation of the speaker unit at the first location comprises a distance and a set of angles relative to one of a

previous location of the speaker unit, or a reference location.

8. The computer-implemented method of claim 1, further comprising: transmitting, by the speaker unit, the positioning information to the hub unit, wherein the positioning information is usable by the hub unit to determine the position and the orientation of the speaker unit.

9. The computer-implemented method of claim 1, further comprising generating, by the speaker unit, a second filter based on the position and the orientation.

10. A speaker unit comprising: one or more loudspeakers; a memory storing instructions; and a processor coupled to the memory that executes the instructions to perform steps comprising: detecting that the speaker unit has moved to a first location; determining, based on positioning information associated with the speaker unit, a position and an orientation of the speaker unit relative to a target listening area; receiving, from a hub unit, a filter, wherein: the filter is generated based on at least the position and the orientation, and the filter includes a plurality of digital signal processor (DSP) coefficients that were generated by the hub unit based on the positioning information; receiving an input audio signal; filtering, using the filter, the input audio signal to generate a filtered audio signal, wherein the filter with the plurality of DSP coefficients steers the filtered audio signal to the target listening area; and outputting the filtered audio signal using the one or more loudspeakers to generate at least a portion of a sound field that includes a sweet spot in the target listening area.

11. The speaker unit of claim 10, wherein: the speaker unit is detachable from a connection point of a hub unit; and the steps further comprise detecting that the speaker unit has become detached from the hub unit.

12. The speaker unit of claim 11, wherein the connection point is a charging port.

13. The speaker unit of claim 11, further comprising: one or more sensors that include at least one of an accelerometer, a gyroscopic sensor, an inertial management unit, or a magnetometer; wherein the position and the orientation of the speaker unit are determined from data collected using the one or more sensors.

14. The speaker unit of claim 13, wherein the steps further comprise, in response to detecting that the speaker unit has become detached, activating the one or more sensors.

15. The speaker unit of claim 11, wherein the step of detecting that the speaker unit has moved to the first location comprises detecting that the speaker unit is stationary.

16. The speaker unit of claim 10, wherein the steps further comprise: transmitting the positioning information to the hub unit, wherein the positioning information is usable by the hub unit to determine the position and the orientation of the speaker unit.

17. The speaker unit of claim 10, wherein the steps further comprise generating a second filter based on the position and the orientation.

18. One or more non-transitory computer-readable media storing instructions that, when executed by one or more processors associated with a hub unit of a speaker system, cause the one or more processors to perform the steps of: receiving an indication that a speaker unit has become stationary; determining, based on positioning information associated with the speaker unit and in response to receiving the indication, a position and an orientation of the speaker unit relative to a target listening area; generating, based on the position and the orientation of the speaker unit relative to the target listening area, a plurality of digital signal processor (DSP) coefficients; generating, based on the DSP coefficients, a filter useable by the speaker unit to filter an input audio signal to generate one or more filtered audio signals, wherein the filter with the DSP coefficients steers an audio signal to the target listening area; transmitting a message including the filter to the speaker unit; and upon transmitting the filter to the speaker unit: receiving the input audio signal, and transmitting the input audio signal to the speaker unit.

19. The computer-implemented method of claim 1, wherein: the speaker unit includes a second filter that comprises one of an equalization filter or a spatialization filter, and generating the filtered audio signal comprises: filtering, using the filter, the input audio signal to add directivity

information, and filtering, by the speaker unit using the second filter, to modify the input audio signal to generate the filtered audio signal.
