

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12414126
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Takeda; Kazuki et al.

Scheduled cell identification for multi-cell scheduling

Abstract

Methods, systems, and devices for wireless communications are described. A user equipment (UE) may receive a multi-cell downlink control information (MC-DCI) that via a scheduling cell may schedule communications for more than one scheduled cells. The overhead of a DCI (e.g., an MC-DCI) may be reduced by compressing or removing the carrier indication field (CIF). For example, radio resource control signaling may indicate, to a UE, a DCI payload size, control channel elements (CCE)s, and/or physical downlink control channel (PDCCH) candidates per scheduled cell or per group of scheduled cells. If the DCI payload sizes, CCEs, and/or PDCCH candidates are different for the scheduled cells indicated in the radio resource control message, the UE may determine to which scheduled cell(s) a DCI received in a PDCCH monitoring occasion applies based on the payload size and/or CCEs of the PDCCH monitoring occasion without using a CIF.

Inventors:	Takeda; Kazuki (Tokyo, JP), Chen; Wanshi (San Diego, CA)
Applicant:	QUALCOMM Incorporated (San Diego, CA)
Family ID:	87429387
Assignee:	QUALCOMM Incorporated (San Diego, CA)
Appl. No.:	17/883560
Filed:	August 08, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20240049244 A1	Feb. 08, 2024

Publication Classification

Int. Cl.: H04W72/23 (20230101)

U.S. Cl.:

CPC H04W72/23 (20230101);

Field of Classification Search

CPC: H04W (72/23); H04W (16/14); H04W (88/10); H04W (88/06)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2020/0067675	12/2019	Takeda	N/A	H04L 5/0053
2021/0391955	12/2020	He	N/A	H04L 5/0053
2022/0086867	12/2021	Papasakellariou	N/A	N/A
2022/0103288	12/2021	Matsumura	N/A	H04L 5/0035
2022/0329366	12/2021	Kim	N/A	H04L 1/1887
2023/0144002	12/2022	Kim et al.	N/A	N/A
2023/0156700	12/2022	Liu	370/329	H04W 24/08
2023/0354332	12/2022	Cirik	N/A	H04W 72/23
2024/0040429	12/2023	MolavianJazi	N/A	H04W 28/06
2024/0080929	12/2023	Matsumura	N/A	H04W 76/20
2024/0267931	12/2023	Zhou	N/A	H04L 5/0092
2025/0016794	12/2024	Park	N/A	H04W 72/12
2025/0024458	12/2024	Liu	N/A	H04L 5/0053

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
WO-2021206422	12/2020	WO	N/A

OTHER PUBLICATIONS

International Search Report and Written Opinion—PCT/US2023/069088—ISA/EPO—Oct. 16, 2023. cited by applicant

Samsung: “Multi-Cell PUSCH/POSCH Scheduling with a Single DCI”, 3GPP TSG RAN WG1 #109-e, R1-2203925, 3rd Generation Partnership Project (3GPP), Mobile Competence Centre, 650, Route Des Lucioles, F-06921 Sophia-Antipolis Cedex, France, vol. RAN WG1, No. e-Meeting, May 9, 2022-May 20, 2022, Apr. 29, 2022, 9 Pages, XP052143996, Section 1, p. 1, Section 5, p. 5-p. 6. cited by applicant

Primary Examiner: Lee; Andrew

Attorney, Agent or Firm: Holland & Hart LLP

Background/Summary

(1) The following relates to wireless communications relating to scheduled cell identification for multi-cell scheduling. Wireless communications systems are widely deployed to provide various types of communication content such as voice, video, packet data, messaging, broadcast, and so on.

These systems may be capable of supporting communication with multiple users by sharing the available system resources (e.g., time, frequency, and power). Examples of such multiple-access systems include fourth generation (4G) systems such as Long Term Evolution (LTE) systems, LTE-Advanced (LTE-A) systems, or LTE-A Pro systems, and fifth generation (5G) systems which may be referred to as New Radio (NR) systems. These systems may employ technologies such as code division multiple access (CDMA), time division multiple access (TDMA), frequency division multiple access (FDMA), orthogonal FDMA (OFDMA), or discrete Fourier transform spread orthogonal frequency division multiplexing (DFT-S-OFDM). A wireless multiple-access communications system may include one or more base stations, each supporting wireless communication for communication devices, which may be known as user equipment (UE).

SUMMARY

(2) The described techniques relate to improved methods, systems, devices, and apparatuses that support scheduled cell identification for multi-cell scheduling. For example, the described techniques provide for multi-cell downlink control information (MC-DCI) with reduced overhead. A user equipment (UE) may receive an MC-DCI via a scheduling cell that may schedule communications for more than one scheduled cell. As an MC-DCI conveys more information than a single-cell DCI in order to schedule communications on multiple cells, the overhead of a MC-DCI may be increased as compared to a single-cell DCI. The overhead of a DCI may be reduced by compressing or removing the carrier indication field (CIF). For example, radio resource control (RRC) signaling may indicate, to a UE, a DCI payload size, control channel elements (CCE)s, and/or physical downlink control channel (PDCCH) candidates per scheduled cell or per group of scheduled cells. If the DCI payload sizes, CCEs, and/or PDCCH candidates are different for the scheduled cells indicated in the RRC message, the UE may determine to which scheduled cell(s) a DCI received in a PDCCH monitoring occasion applies based on the payload size and/or CCEs of the PDCCH monitoring occasion without using a CIF field. In some aspects, if the DCI payload sizes, CCEs, and PDCCH candidates for two or more scheduled cells or groups of scheduled cells are the same, the UE may determine the scheduled cell(s) for a PDCCH monitoring occasion without a CIF based on one or more configured rules. In some aspects, if the DCI payload sizes, CCEs, and PDCCH candidates for two or more scheduled cells or groups of scheduled cells are the same, the UE may determine the corresponding scheduled cell or group of scheduled cells for a PDCCH monitoring occasion without a CIF based on determining the radio network temporary identifier (RNTI) that was used to scramble the cyclic redundancy check (CRC) for the PDCCH monitoring occasion and matching the RNTI to a scheduled cell or group of scheduled cells.

(3) A method for wireless communications at a first network node is described. The method may include receiving control signaling including an indication of a respective DCI payload size for each subset of scheduled cells of a set of scheduled cells, where the set of scheduled cells are associated with a scheduling cell, and where the control signaling further includes an indication of a respective set of CCEs for each subset of scheduled cells, determining, based on first comparison information corresponding to the respective DCI payload sizes and second comparison information corresponding to the respective sets of CCEs, a DCI format for a downlink control channel monitoring occasion in the scheduling cell, where the DCI format is associated with a subset of scheduled cells of the set of scheduled cells, where the DCI format includes an absence or a presence of an indication of the subset of scheduled cells, and receiving, via the downlink control channel monitoring occasion, DCI in accordance with the determined DCI format.

(4) A first network node for wireless communications is described. The first network node may a memory and at least one processor coupled to the memory. The at least one processor may be configured to receive control signaling including an indication of a respective DCI payload size for each subset of scheduled cells of a set of scheduled cells, where the set of scheduled cells are associated with a scheduling cell, and where the control signaling further includes an indication of a respective set of CCEs for each subset of scheduled cells, determine, based on first comparison

information corresponding to the respective DCI payload sizes and second comparison information corresponding to the respective sets of CCEs, a DCI format for a downlink control channel monitoring occasion in the scheduling cell, where the DCI format is associated with a subset of scheduled cells of the set of scheduled cells, where the DCI format includes an absence or a presence of an indication of the subset of scheduled cells, and receive, via the downlink control channel monitoring occasion, DCI in accordance with the determined DCI format.

(5) Another apparatus for wireless communications at a first network node is described. The apparatus may include means for receiving control signaling including an indication of a respective DCI payload size for each subset of scheduled cells of a set of scheduled cells, where the set of scheduled cells are associated with a scheduling cell, and where the control signaling further includes an indication of a respective set of CCEs for each subset of scheduled cells, means for determining, based on first comparison information corresponding to the respective DCI payload sizes and second comparison information corresponding to the respective sets of CCEs, a DCI format for a downlink control channel monitoring occasion in the scheduling cell, where the DCI format is associated with a subset of scheduled cells of the set of scheduled cells, where the DCI format includes an absence or a presence of an indication of the subset of scheduled cells, and means for receiving, via the downlink control channel monitoring occasion, DCI in accordance with the determined DCI format.

(6) A non-transitory computer-readable medium having code for wireless stored thereon is described. The code when executed by a first network node, causes the network node to receive control signaling including an indication of a respective DCI payload size for each subset of scheduled cells of a set of scheduled cells, where the set of scheduled cells are associated with a scheduling cell, and where the control signaling further includes an indication of a respective set of CCEs for each subset of scheduled cells, determine, based on first comparison information corresponding to the respective DCI payload sizes and second comparison information corresponding to the respective sets of CCEs, a DCI format for a downlink control channel monitoring occasion in the scheduling cell, where the DCI format is associated with a subset of scheduled cells of the set of scheduled cells, where the DCI format includes an absence or a presence of an indication of the subset of scheduled cells, and receive, via the downlink control channel monitoring occasion, DCI in accordance with the determined DCI format.

(7) In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, determining the DCI format may include operations, features, means, or instructions for determining the DCI format based on the third comparison information.

(8) In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, determining the DCI format may include operations, features, means, or instructions for determining the DCI format based on a payload size for the downlink control channel monitoring occasion that matches a respective DCI payload size of the subset scheduled cells.

(9) In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, determining the DCI format may include operations, features, means, or instructions for determining the DCI format based on a set of CCEs for the downlink control channel monitoring occasion that matches a respective set of CCEs for the subset of scheduled cells.

(10) Some examples of the method, apparatuses, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for determining, based on the first comparison information being indicative that at least two respective DCI payload sizes for at least two subsets of scheduled cells may be equal and further based on the second comparison information being indicative that respective sets of CCEs for the at least two subsets of scheduled cells may be equal, that the DCI includes the presence of the indication of the subset of scheduled cells, where the indication of the subset of scheduled cells includes an explicit indication

of the subset of scheduled cells.

(11) Some examples of the method, apparatuses, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for determining, based on the first comparison information being indicative that at least two respective DCI payload sizes for at least two subsets of scheduled cells may be equal and further based on the second comparison information being indicative that respective sets of CCEs for the at least two subsets of scheduled cells may be equal, that the DCI includes the presence of the indication of the subset of scheduled cells, where the indication of the subset of scheduled cells includes a rule-based indication of the subset of scheduled cells.

(12) In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, the rule-based indication includes information indicative of a rule to select the subset of scheduled cells of the set of scheduled cells based on one of a component carrier index associated with one or more scheduled cells within the subset of scheduled cells, a subcarrier spacing associated with one or more scheduled cells within the subset of scheduled cells, the subset of scheduled cells including a primary cell for the first network node, the subset of scheduled cells including the scheduling cell, or a number of cells associated with the subset of scheduled cells.

(13) Some examples of the method, apparatuses, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for determining, based on the first comparison information being indicative that at least two respective DCI payload sizes for at least two subsets of scheduled cells may be equal and further based on the second comparison information being indicative that respective sets of CCEs for the at least two subsets of scheduled cells may be equal, that the DCI includes the presence of the indication of the subset of scheduled cells, where the indication of the subset of scheduled cells includes a radio network identifier used to scramble a cyclic redundancy check of the downlink control channel monitoring occasion.

(14) In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, the control signaling further includes an indication of an association between respective radio network identifiers and each subset of scheduled cells.

(15) In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, DCI includes scheduling information for one or more communications with the subset of scheduled cells.

(16) In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, the control signaling further includes an indication of a respective carrier indicator associated with each scheduled cell of the set of scheduled cells and a determination of the scheduling information may be based on the indication of the respective carrier indicator associated with each scheduled cell of the set of scheduled cells.

(17) Some examples of the method, apparatuses, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for comparing the respective DCI payload sizes and generating the first comparison information based on the comparison of the respective DCI payload sizes.

(18) Some examples of the method, apparatuses, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for comparing the respective sets of CCEs and generating the second comparison information based on the comparison of the respective sets of CCEs.

(19) A method for wireless communications at a first network node is described. The method may include transmitting, to a second network node, control signaling including an indication of a respective DCI payload size for each subset of scheduled cells of a set of scheduled cells, where the set of scheduled cells are associated with a scheduling cell, and where the control signaling further includes an indication of a respective set of CCEs for each subset of scheduled cells, determining, based on first comparison information corresponding to the respective DCI payload sizes and

second comparison information corresponding to the respective sets of CCEs, a DCI format for a downlink control channel monitoring occasion in the scheduling cell, where the DCI format is associated with a subset of scheduled cells of the set of scheduled cells, where the downlink control channel format includes an absence or a presence of an indication of the subset of scheduled cells, and transmitting, via the downlink control channel monitoring occasion, a DCI in accordance with the determined DCI format.

(20) A first network node for wireless communications is described. The first network node may have a memory and at least one processor coupled to the memory. The at least one processor may be configured to cause the apparatus to transmit, to a second network node, control signaling including an indication of a respective DCI payload size for each subset of scheduled cells of a set of scheduled cells, where the set of scheduled cells are associated with a scheduling cell, and where the control signaling further includes an indication of a respective set of CCEs for each subset of scheduled cells, determine, based on first comparison information corresponding to the respective DCI payload sizes and second comparison information corresponding to the respective sets of CCEs, a DCI format for a downlink control channel monitoring occasion in the scheduling cell, where the DCI format is associated with a subset of scheduled cells of the set of scheduled cells, where the downlink control channel format includes an absence or a presence of an indication of the subset of scheduled cells, and transmit, via the downlink control channel monitoring occasion, a DCI in accordance with the determined DCI format.

(21) Another apparatus for wireless communications at a first network node is described. The apparatus may include means for transmitting, to a second network node, control signaling including an indication of a respective DCI payload size for each subset of scheduled cells of a set of scheduled cells, where the set of scheduled cells are associated with a scheduling cell, and where the control signaling further includes an indication of a respective set of CCEs for each subset of scheduled cells, means for determining, based on first comparison information corresponding to the respective DCI payload sizes and second comparison information corresponding to the respective sets of CCEs, a DCI format for a downlink control channel monitoring occasion in the scheduling cell, where the DCI format is associated with a subset of scheduled cells of the set of scheduled cells, where the downlink control channel format includes an absence or a presence of an indication of the subset of scheduled cells, and means for transmitting, via the downlink control channel monitoring occasion, a DCI in accordance with the determined DCI format.

(22) A non-transitory computer-readable medium having code for wireless stored thereon is described. The code when executed by a first network node, causes the network node to transmit, to a second network node, control signaling including an indication of a respective DCI payload size for each subset of scheduled cells of a set of scheduled cells, where the set of scheduled cells are associated with a scheduling cell, and where the control signaling further includes an indication of a respective set of CCEs for each subset of scheduled cells, determine, based on first comparison information corresponding to the respective DCI payload sizes and second comparison information corresponding to the respective sets of CCEs, a DCI format for a downlink control channel monitoring occasion in the scheduling cell, where the DCI format is associated with a subset of scheduled cells of the set of scheduled cells, where the downlink control channel format includes an absence or a presence of an indication of the subset of scheduled cells, and transmit, via the downlink control channel monitoring occasion, a DCI in accordance with the determined DCI format.

(23) In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, determining the DCI format may include operations, features, means, or instructions for determining the DCI format based on the third comparison information.

(24) In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, determining the DCI format may include operations, features, means, or instructions for determining the DCI format based on a payload size for the downlink control

channel monitoring occasion that matches a respective DCI payload size of the subset scheduled cells.

(25) In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, determining the DCI format may include operations, features, means, or instructions for determining the DCI format based on a set of CCEs for the downlink control channel monitoring occasion that matches a respective set of CCEs for the subset of scheduled cells.

(26) Some examples of the method, apparatuses, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for determining, based on the first comparison information being indicative that at least two respective DCI payload sizes for at least two subsets of scheduled cells may be equal and further based on the second comparison information being indicative that respective sets of CCEs for the at least two subsets of scheduled cells may be equal, that the DCI includes the presence of the indication of the subset of scheduled cells, where the indication of the subset of scheduled cells includes an explicit indication of the subset of scheduled cells.

(27) Some examples of the method, apparatuses, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for determining, based on the first comparison information being indicative that at least two respective DCI payload sizes for at least two subsets of scheduled cells may be equal and further based on the second comparison information being indicative that respective sets of CCEs for the at least two subsets of scheduled cells may be equal, that the DCI includes the presence of the indication of the subset of scheduled cells, where the indication of the subset of scheduled cells includes a rule-based indication of the subset of scheduled cells.

(28) In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, the rule-based indication includes information indicative of a rule to select the subset of scheduled cells of the set of scheduled cells based on one of a component carrier index associated with one or more scheduled cells within the subset of scheduled cells, a subcarrier spacing associated with one or more scheduled cells within the subset of scheduled cells, the subset of scheduled cells including a primary cell for the first network node, the subset of scheduled cells including the scheduling cell, or a number of cells associated with the subset of scheduled cells.

(29) Some examples of the method, apparatuses, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for determining, based on the first comparison information being indicative that at least two respective DCI payload sizes for at least two subsets of scheduled cells may be equal and further based on the second comparison information being indicative that respective sets of CCEs for the at least two subsets of scheduled cells may be equal, that the DCI includes the presence of the indication of the subset of scheduled cells, where the indication of the subset of scheduled cells includes a radio network identifier used to scramble a cyclic redundancy check of the downlink control channel monitoring occasion.

(30) In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, the control signaling further includes an indication of an association between respective radio network identifiers and each subset of scheduled cells.

(31) In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, DCI includes scheduling information for one or more communications with the subset of scheduled cells.

(32) In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, the control signaling further includes an indication of a respective carrier indicator associated with each scheduled cell of the set of scheduled cells and a determination of the scheduling information may be based on the indication of the respective carrier indicator associated with each scheduled cell of the set of scheduled cells.

- (33) Some examples of the method, apparatuses, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for comparing the respective DCI payload sizes and generating the first comparison information based on the comparison of the respective DCI payload sizes.
- (34) Some examples of the method, apparatuses, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for comparing the respective sets of CCEs and generating the second comparison information based on the comparison of the respective sets of CCEs.
-

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 illustrates an example of a wireless communications system that supports scheduled cell identification for multi-cell scheduling in accordance with one or more aspects of the present disclosure.
- (2) FIG. 2 illustrates an example of a scheduling diagram that supports scheduled cell identification for multi-cell scheduling in accordance with one or more aspects of the present disclosure.
- (3) FIG. 3 illustrates an example of a scheduling diagram that supports scheduled cell identification for multi-cell scheduling in accordance with one or more aspects of the present disclosure.
- (4) FIG. 4 illustrates an example of a wireless communications system that supports scheduled cell identification for multi-cell scheduling in accordance with one or more aspects of the present disclosure.
- (5) FIG. 5 illustrates an example of a resource diagram that supports scheduled cell identification for multi-cell scheduling in accordance with one or more aspects of the present disclosure.
- (6) FIG. 6 illustrates an example of a process flow that supports scheduled cell identification for multi-cell scheduling in accordance with one or more aspects of the present disclosure.
- (7) FIGS. 7 and 8 show block diagrams of devices that support scheduled cell identification for multi-cell scheduling in accordance with one or more aspects of the present disclosure.
- (8) FIG. 9 shows a block diagram of a communications manager that supports scheduled cell identification for multi-cell scheduling in accordance with one or more aspects of the present disclosure.
- (9) FIG. 10 shows a diagram of a system including a device that supports scheduled cell identification for multi-cell scheduling in accordance with one or more aspects of the present disclosure.
- (10) FIGS. 11 and 12 show block diagrams of devices that support scheduled cell identification for multi-cell scheduling in accordance with one or more aspects of the present disclosure.
- (11) FIG. 13 shows a block diagram of a communications manager that supports scheduled cell identification for multi-cell scheduling in accordance with one or more aspects of the present disclosure.
- (12) FIG. 14 shows a diagram of a system including a device that supports scheduled cell identification for multi-cell scheduling in accordance with one or more aspects of the present disclosure.
- (13) FIGS. 15 and 16 show flowcharts illustrating methods that support scheduled cell identification for multi-cell scheduling in accordance with one or more aspects of the present disclosure.

DETAILED DESCRIPTION

- (14) Some wireless communications may implement cross-carrier scheduling, where a downlink control information (DCI) received via a physical downlink control channel (PDCCH) occasion on a scheduling cell schedules a communication for a different cell (the scheduled cell). A cross-

carrier DCI may include an indication of the scheduled cell in a carrier indication field (CIF). Some wireless communications systems may support multi-cell DCI (MC-DCI), meaning a single DCI received via a scheduling cell may schedule communications for more than one scheduled cells. As an MC-DCI conveys more information than a single-cell DCI in order to schedule communications on multiple cells, the overhead of a MC-DCI may be increased as compared to a single-cell DCI.

(15) The overhead of a DCI may be reduced by compressing or removing the CIF. For example, radio resource control (RRC) signaling may indicate, to a user equipment (UE), a DCI payload size, control channel elements (CCE)s, and/or PDCCH candidates per scheduled cell or per group of scheduled cells. If the DCI payload sizes, CCEs, and/or PDCCH candidates are different for the scheduled cells indicated in the RRC, the UE may determine to which scheduled cell(s) a DCI received in a PDCCH monitoring occasion applies based on the payload size and/or CCEs of the PDCCH monitoring occasion without using a CIF field. Accordingly, the size of the DCI may be reduced by removing the CIF field.

(16) In some aspects, if the DCI payload sizes, CCEs, and PDCCH candidates for two or more scheduled cells or groups of scheduled cells are the same, the UE may determine the scheduled cell(s) for a PDCCH monitoring occasion without a CIF based on one or more configured rules. For example, if the DCI payload size, the CCEs, and the PDCCH monitoring occasion matches two or more scheduled cells or groups of scheduled cells, the UE may determine that the PDCCH monitoring occasion corresponds to the scheduled cell(s) with the lower/higher component carrier index, the lower/higher subcarrier spacing (SCS), the group of scheduled cells that includes the Primary cell, the group of scheduled cells that includes the scheduling cell, or the group of cells that includes the most/least amount of cells.

(17) In some aspects, if the DCI payload sizes, CCEs, and PDCCH candidates for two or more scheduled cells or groups of scheduled cells are the same, the UE may determine the corresponding scheduled cell or group of scheduled cells for a PDCCH monitoring occasion without a CIF based on determining the radio network temporary identifier (RNTI) that was used to scramble the cyclic redundancy check (CRC) for the PDCCH monitoring occasion and matching the RNTI to a scheduled cell or group of scheduled cells.

(18) Aspects of the disclosure are initially described in the context of wireless communications systems. Aspects of the disclosure are further illustrated by and described with reference to scheduling diagrams, resource diagrams, and process flows. Aspects of the disclosure are further illustrated by and described with reference to apparatus diagrams, system diagrams, and flowcharts that relate to scheduled cell identification for multi-cell scheduling.

(19) FIG. 1 illustrates an example of a wireless communications system **100** that supports scheduled cell identification for multi-cell scheduling in accordance with one or more aspects of the present disclosure. The wireless communications system **100** may include one or more network entities **105**, one or more UEs **115**, and a core network **130**. In some aspects, the wireless communications system **100** may be a Long Term Evolution (LTE) network, an LTE-Advanced (LTE-A) network, an LTE-A Pro network, a New Radio (NR) network, or a network operating in accordance with other systems and radio technologies, including future systems and radio technologies not explicitly mentioned herein.

(20) The network entities **105** may be dispersed throughout a geographic area to form the wireless communications system **100** and may include devices in different forms or having different capabilities. In various aspects, a network entity **105** may be referred to as a network element, a mobility element, a radio access network (RAN) node, or network equipment, among other nomenclature. In some aspects, network entities **105** and UEs **115** may wirelessly communicate via one or more communication links **125** (e.g., a radio frequency (RF) access link). For example, a network entity **105** may support a coverage area **110** (e.g., a geographic coverage area) over which the UEs **115** and the network entity **105** may establish one or more communication links **125**. The coverage area **110** may be an example of a geographic area over which a network entity **105** and a

UE **115** may support the communication of signals according to one or more radio access technologies (RATs).

(21) The UEs **115** may be dispersed throughout a coverage area **110** of the wireless communications system **100**, and each UE **115** may be stationary, or mobile, or both at different times. The UEs **115** may be devices in different forms or having different capabilities. Some example UEs **115** are illustrated in FIG. **1**. The UEs **115** described herein may be capable of supporting communications with various types of devices, such as other UEs **115** or network entities **105**, as shown in FIG. **1**.

(22) As described herein, a node (which may be referred to as a node, a network node, a network entity, or a wireless node) may include, be, or be included in (e.g., be a component of) a base station (e.g., any base station described herein), a UE (e.g., any UE described herein), a network controller, an apparatus, a device, a computing system, an integrated access and backhauling (IAB) node, a distributed unit (DU), a central unit (CU), a remote/radio unit (RU) (which may also be referred to as a remote radio unit (RRU)), and/or another processing entity configured to perform any of the techniques described herein. For example, a network node may be a UE. As another example, a network node may be a base station or network entity. As another example, a first network node may be configured to communicate with a second network node or a third network node. In one aspect of this example, the first network node may be a UE, the second network node may be a base station, and the third network node may be a UE. In another aspect of this example, the first network node may be a UE, the second network node may be a base station, and the third network node may be a base station. In yet other aspects of this example, the first, second, and third network nodes may be different relative to these examples. Similarly, reference to a UE, base station, apparatus, device, computing system, or the like may include disclosure of the UE, base station, apparatus, device, computing system, or the like being a network node. For example, disclosure that a UE is configured to receive information from a base station also discloses that a first network node is configured to receive information from a second network node. Consistent with this disclosure, once a specific example is broadened in accordance with this disclosure (e.g., a UE is configured to receive information from a base station also discloses that a first network node is configured to receive information from a second network node), the broader example of the narrower example may be interpreted in the reverse, but in a broad open-ended way. In the example above where a UE is configured to receive information from a base station also discloses that a first network node is configured to receive information from a second network node, the first network node may refer to a first UE, a first base station, a first apparatus, a first device, a first computing system, a first set of one or more one or more components, a first processing entity, or the like configured to receive the information; and the second network node may refer to a second UE, a second base station, a second apparatus, a second device, a second computing system, a second set of one or more components, a second processing entity, or the like.

(23) As described herein, communication of information (e.g., any information, signal, or the like) may be described in various aspects using different terminology. Disclosure of one communication term includes disclosure of other communication terms. For example, a first network node may be described as being configured to transmit information to a second network node. In this example and consistent with this disclosure, disclosure that the first network node is configured to transmit information to the second network node includes disclosure that the first network node is configured to provide, send, output, communicate, or transmit information to the second network node. Similarly, in this example and consistent with this disclosure, disclosure that the first network node is configured to transmit information to the second network node includes disclosure that the second network node is configured to receive, obtain, or decode the information that is provided, sent, output, communicated, or transmitted by the first network node.

(24) As described herein, a node of the wireless communications system **100**, which may be referred to as a network node, or a wireless node, may be a network entity **105** (e.g., any network

entity described herein), a UE **115** (e.g., any UE described herein), a network controller, an apparatus, a device, a computing system, one or more components, or another suitable processing entity configured to perform any of the techniques described herein. For example, a node may be a UE **115**. As another example, a node may be a network entity **105**. As another example, a first node may be configured to communicate with a second node or a third node. In one aspect of this example, the first node may be a UE **115**, the second node may be a network entity **105**, and the third node may be a UE **115**. In another aspect of this example, the first node may be a UE **115**, the second node may be a network entity **105**, and the third node may be a network entity **105**. In yet other aspects of this example, the first, second, and third nodes may be different relative to these examples. Similarly, reference to a UE **115**, network entity **105**, apparatus, device, computing system, or the like may include disclosure of the UE **115**, network entity **105**, apparatus, device, computing system, or the like being a node. For example, disclosure that a UE **115** is configured to receive information from a network entity **105** also discloses that a first node is configured to receive information from a second node.

(25) In some aspects, network entities **105** may communicate with the core network **130**, or with one another, or both. For example, network entities **105** may communicate with the core network **130** via one or more backhaul communication links **120** (e.g., in accordance with an S1, N2, N3, or other interface protocol). In some aspects, network entities **105** may communicate with one another via a backhaul communication link **120** (e.g., in accordance with an X2, Xn, or other interface protocol) either directly (e.g., directly between network entities **105**) or indirectly (e.g., via a core network **130**). In some aspects, network entities **105** may communicate with one another via a midhaul communication link **162** (e.g., in accordance with a midhaul interface protocol) or a fronthaul communication link **168** (e.g., in accordance with a fronthaul interface protocol), or any combination thereof. The backhaul communication links **120**, midhaul communication links **162**, or fronthaul communication links **168** may be or include one or more wired links (e.g., an electrical link, an optical fiber link), one or more wireless links (e.g., a radio link, a wireless optical link), among other examples or various combinations thereof. A UE **115** may communicate with the core network **130** via a communication link **155**.

(26) One or more of the network entities **105** described herein may include or may be referred to as a base station **140** (e.g., a base transceiver station, a radio base station, an NR base station, an access point, a radio transceiver, a NodeB, an eNodeB (eNB), a next-generation NodeB or a giga-NodeB (either of which may be referred to as a gNB), a 5G NB, a next-generation eNB (ng-eNB), a Home NodeB, a Home eNodeB, or other suitable terminology). In some aspects, a network entity **105** (e.g., a base station **140**) may be implemented in an aggregated (e.g., monolithic, standalone) base station architecture, which may be configured to utilize a protocol stack that is physically or logically integrated within a single network entity **105** (e.g., a single RAN node, such as a base station **140**).

(27) In some aspects, a network entity **105** may be implemented in a disaggregated architecture (e.g., a disaggregated base station architecture, a disaggregated RAN architecture), which may be configured to utilize a protocol stack that is physically or logically distributed among two or more network entities **105**, such as an integrated access backhaul (IAB) network, an open RAN (O-RAN) (e.g., a network configuration sponsored by the O-RAN Alliance), or a virtualized RAN (vRAN) (e.g., a cloud RAN (C-RAN)). For example, a network entity **105** may include one or more of a central unit (CU) **160**, a distributed unit (DU) **165**, a radio unit (RU) **170**, a RAN Intelligent Controller (RIC) **175** (e.g., a Near-Real Time RIC (Near-RT RIC), a Non-Real Time RIC (Non-RT RIC)), a Service Management and Orchestration (SMO) **180** system, or any combination thereof. An RU **170** may also be referred to as a radio head, a smart radio head, a remote radio head (RRH), a remote radio unit (RRU), or a transmission reception point (TRP). One or more components of the network entities **105** in a disaggregated RAN architecture may be co-located, or one or more components of the network entities **105** may be located in distributed locations (e.g., separate

physical locations). In some aspects, one or more network entities **105** of a disaggregated RAN architecture may be implemented as virtual units (e.g., a virtual CU (VCU), a virtual DU (VDU), a virtual RU (VRU)).

(28) The split of functionality between a CU **160**, a DU **165**, and an RU **170** is flexible and may support different functionalities depending on which functions (e.g., network layer functions, protocol layer functions, baseband functions, RF functions, and any combinations thereof) are performed at a CU **160**, a DU **165**, or an RU **170**. For example, a functional split of a protocol stack may be employed between a CU **160** and a DU **165** such that the CU **160** may support one or more layers of the protocol stack and the DU **165** may support one or more different layers of the protocol stack. In some aspects, the CU **160** may host upper protocol layer (e.g., layer 3 (L3), layer 2 (L2)) functionality and signaling (e.g., RRC, service data adaptation protocol (SDAP), Packet Data Convergence Protocol (PDCP)). The CU **160** may be connected to one or more DUs **165** or RUs **170**, and the one or more DUs **165** or RUs **170** may host lower protocol layers, such as layer 1 (L1) (e.g., physical (PHY) layer) or L2 (e.g., radio link control (RLC) layer, medium access control (MAC) layer) functionality and signaling, and may each be at least partially controlled by the CU **160**. Additionally, or alternatively, a functional split of the protocol stack may be employed between a DU **165** and an RU **170** such that the DU **165** may support one or more layers of the protocol stack and the RU **170** may support one or more different layers of the protocol stack. The DU **165** may support one or multiple different cells (e.g., via one or more RUs **170**). In some cases, a functional split between a CU **160** and a DU **165**, or between a DU **165** and an RU **170** may be within a protocol layer (e.g., some functions for a protocol layer may be performed by one of a CU **160**, a DU **165**, or an RU **170**, while other functions of the protocol layer are performed by a different one of the CU **160**, the DU **165**, or the RU **170**). A CU **160** may be functionally split further into CU control plane (CU-CP) and CU user plane (CU-UP) functions. A CU **160** may be connected to one or more DUs **165** via a midhaul communication link **162** (e.g., F1, F1-c, F1-u), and a DU **165** may be connected to one or more RUs **170** via a fronthaul communication link **168** (e.g., open fronthaul (FH) interface). In some aspects, a midhaul communication link **162** or a fronthaul communication link **168** may be implemented in accordance with an interface (e.g., a channel) between layers of a protocol stack supported by respective network entities **105** that are in communication via such communication links.

(29) In wireless communications systems (e.g., wireless communications system **100**), infrastructure and spectral resources for radio access may support wireless backhaul link capabilities to supplement wired backhaul connections, providing an IAB network architecture (e.g., to a core network **130**). In some cases, in an IAB network, one or more network entities **105** (e.g., IAB nodes **104**) may be partially controlled by each other. One or more IAB nodes **104** may be referred to as a donor entity or an IAB donor. One or more DUs **165** or one or more RUs **170** may be partially controlled by one or more CUs **160** associated with a donor network entity **105** (e.g., a donor base station **140**). The one or more donor network entities **105** (e.g., IAB donors) may be in communication with one or more additional network entities **105** (e.g., IAB nodes **104**) via supported access and backhaul links (e.g., backhaul communication links **120**). IAB nodes **104** may include an IAB mobile termination (IAB-MT) controlled (e.g., scheduled) by DUs **165** of a coupled IAB donor. An IAB-MT may include an independent set of antennas for relay of communications with UEs **115**, or may share the same antennas (e.g., of an RU **170**) of an IAB node **104** used for access via the DU **165** of the IAB node **104** (e.g., referred to as virtual IAB-MT (vIAB-MT)). In some aspects, the IAB nodes **104** may include DUs **165** that support communication links with additional entities (e.g., IAB nodes **104**, UEs **115**) within the relay chain or configuration of the access network (e.g., downstream). In such cases, one or more components of the disaggregated RAN architecture (e.g., one or more IAB nodes **104** or components of IAB nodes **104**) may be configured to operate according to the techniques described herein.

(30) For instance, an access network (AN) or RAN may include communications between access

nodes (e.g., an IAB donor), IAB nodes **104**, and one or more UEs **115**. The IAB donor may facilitate connection between the core network **130** and the AN (e.g., via a wired or wireless connection to the core network **130**). That is, an IAB donor may refer to a RAN node with a wired or wireless connection to core network **130**. The IAB donor may include a CU **160** and at least one DU **165** (e.g., and RU **170**), in which case the CU **160** may communicate with the core network **130** via an interface (e.g., a backhaul link). IAB donor and IAB nodes **104** may communicate via an F1 interface according to a protocol that defines signaling messages (e.g., an F1 AP protocol). Additionally, or alternatively, the CU **160** may communicate with the core network via an interface, which may be an example of a portion of backhaul link, and may communicate with other CUs **160** (e.g., a CU **160** associated with an alternative IAB donor) via an Xn-C interface, which may be an example of a portion of a backhaul link.

(31) An IAB node **104** may refer to a RAN node that provides IAB functionality (e.g., access for UEs **115**, wireless self-backhauling capabilities). A DU **165** may act as a distributed scheduling node towards child nodes associated with the IAB node **104**, and the IAB-MT may act as a scheduled node towards parent nodes associated with the IAB node **104**. That is, an IAB donor may be referred to as a parent node in communication with one or more child nodes (e.g., an IAB donor may relay transmissions for UEs through one or more other IAB nodes **104**). Additionally, or alternatively, an IAB node **104** may also be referred to as a parent node or a child node to other IAB nodes **104**, depending on the relay chain or configuration of the AN. Therefore, the IAB-MT entity of IAB nodes **104** may provide a Uu interface for a child IAB node **104** to receive signaling from a parent IAB node **104**, and the DU interface (e.g., DUs **165**) may provide a Uu interface for a parent IAB node **104** to signal to a child IAB node **104** or UE **115**.

(32) For example, IAB node **104** may be referred to as a parent node that supports communications for a child IAB node, or referred to as a child IAB node associated with an IAB donor, or both. The IAB donor may include a CU **160** with a wired or wireless connection (e.g., a backhaul communication link **120**) to the core network **130** and may act as parent node to IAB nodes **104**. For example, the DU **165** of IAB donor may relay transmissions to UEs **115** through IAB nodes **104**, or may directly signal transmissions to a UE **115**, or both. The CU **160** of IAB donor may signal communication link establishment via an F1 interface to IAB nodes **104**, and the IAB nodes **104** may schedule transmissions (e.g., transmissions to the UEs **115** relayed from the IAB donor) through the DUs **165**. That is, data may be relayed to and from IAB nodes **104** via signaling via an NR Uu interface to MT of the IAB node **104**. Communications with IAB node **104** may be scheduled by a DU **165** of IAB donor and communications with IAB node **104** may be scheduled by DU **165** of IAB node **104**.

(33) In the case of the techniques described herein applied in the context of a disaggregated RAN architecture, one or more components of the disaggregated RAN architecture may be configured to support scheduled cell identification for multi-cell scheduling as described herein. For example, some operations described as being performed by a UE **115** or a network entity **105** (e.g., a base station **140**) may additionally, or alternatively, be performed by one or more components of the disaggregated RAN architecture (e.g., IAB nodes **104**, DUs **165**, CUs **160**, RUs **170**, RIC **175**, SMO **180**).

(34) A UE **115** may include or may be referred to as a mobile device, a wireless device, a remote device, a handheld device, or a subscriber device, or some other suitable terminology, where the “device” may also be referred to as a unit, a station, a terminal, or a client, among other examples. A UE **115** may also include or may be referred to as a personal electronic device such as a cellular phone, a personal digital assistant (PDA), a tablet computer, a laptop computer, or a personal computer. In some aspects, a UE **115** may include or be referred to as a wireless local loop (WLL) station, an Internet of Things (IoT) device, an Internet of Everything (IoE) device, or a machine type communications (MTC) device, among other examples, which may be implemented in various objects such as appliances, or vehicles, meters, among other examples.

(35) The UEs **115** described herein may be able to communicate with various types of devices, such as other UEs **115** that may sometimes act as relays as well as the network entities **105** and the network equipment including macro eNBs or gNBs, small cell eNBs or gNBs, or relay base stations, among other examples, as shown in FIG. 1.

(36) The UEs **115** and the network entities **105** may wirelessly communicate with one another via one or more communication links **125** (e.g., an access link) using resources associated with one or more carriers. The term “carrier” may refer to a set of RF spectrum resources having a defined physical layer structure for supporting the communication links **125**. For example, a carrier used for a communication link **125** may include a portion of a RF spectrum band (e.g., a bandwidth part (BWP)) that is operated according to one or more physical layer channels for a given radio access technology (e.g., LTE, LTE-A, LTE-A Pro, NR). Each physical layer channel may carry acquisition signaling (e.g., synchronization signals, system information), control signaling that coordinates operation for the carrier, user data, or other signaling. The wireless communications system **100** may support communication with a UE **115** using carrier aggregation or multi-carrier operation. A UE **115** may be configured with multiple downlink component carriers and one or more uplink component carriers according to a carrier aggregation configuration. Carrier aggregation may be used with both frequency division duplexing (FDD) and time division duplexing (TDD) component carriers. Communication between a network entity **105** and other devices may refer to communication between the devices and any portion (e.g., entity, sub-entity) of a network entity **105**. For example, the terms “transmitting,” “receiving,” or “communicating,” when referring to a network entity **105**, may refer to any portion of a network entity **105** (e.g., a base station **140**, a CU **160**, a DU **165**, a RU **170**) of a RAN communicating with another device (e.g., directly or via one or more other network entities **105**).

(37) In some aspects, such as in a carrier aggregation configuration, a carrier may also have acquisition signaling or control signaling that coordinates operations for other carriers. A carrier may be associated with a frequency channel (e.g., an evolved universal mobile telecommunication system terrestrial radio access (E-UTRA) absolute RF channel number (EARFCN)) and may be identified according to a channel raster for discovery by the UEs **115**. A carrier may be operated in a standalone mode, in which case initial acquisition and connection may be conducted by the UEs **115** via the carrier, or the carrier may be operated in a non-standalone mode, in which case a connection is anchored using a different carrier (e.g., of the same or a different radio access technology).

(38) The communication links **125** shown in the wireless communications system **100** may include downlink transmissions (e.g., forward link transmissions) from a network entity **105** to a UE **115**, uplink transmissions (e.g., return link transmissions) from a UE **115** to a network entity **105**, or both, among other configurations of transmissions. Carriers may carry downlink or uplink communications (e.g., in an FDD mode) or may be configured to carry downlink and uplink communications (e.g., in a TDD mode).

(39) A carrier may be associated with a particular bandwidth of the RF spectrum and, in some aspects, the carrier bandwidth may be referred to as a “system bandwidth” of the carrier or the wireless communications system **100**. For example, the carrier bandwidth may be one of a set of bandwidths for carriers of a particular radio access technology (e.g., 1.4, 3, 5, 10, 15, 20, 40, or 80 megahertz (MHz)). Devices of the wireless communications system **100** (e.g., the network entities **105**, the UEs **115**, or both) may have hardware configurations that support communications using a particular carrier bandwidth or may be configurable to support communications using one of a set of carrier bandwidths. In some aspects, the wireless communications system **100** may include network entities **105** or UEs **115** that support concurrent communications using carriers associated with multiple carrier bandwidths. In some aspects, each served UE **115** may be configured for operating using portions (e.g., a sub-band, a BWP) or all of a carrier bandwidth.

(40) Signal waveforms transmitted via a carrier may be made up of multiple subcarriers (e.g., using

multi-carrier modulation (MCM) techniques such as orthogonal frequency division multiplexing (OFDM) or discrete Fourier transform spread OFDM (DFT-S-OFDM)). In a system employing MCM techniques, a resource element may refer to resources of one symbol period (e.g., a duration of one modulation symbol) and one subcarrier, in which case the symbol period and subcarrier spacing may be inversely related. The quantity of bits carried by each resource element may depend on the modulation scheme (e.g., the order of the modulation scheme, the coding rate of the modulation scheme, or both), such that a relatively higher quantity of resource elements (e.g., in a transmission duration) and a relatively higher order of a modulation scheme may correspond to a relatively higher rate of communication. A wireless communications resource may refer to a combination of an RF spectrum resource, a time resource, and a spatial resource (e.g., a spatial layer, a beam), and the use of multiple spatial resources may increase the data rate or data integrity for communications with a UE **115**.

(41) One or more numerologies for a carrier may be supported, and a numerology may include a subcarrier spacing (Δf) and a cyclic prefix. A carrier may be divided into one or more BWPs having the same or different numerologies. In some aspects, a UE **115** may be configured with multiple BWPs. In some aspects, a single BWP for a carrier may be active at a given time and communications for the UE **115** may be restricted to one or more active BWPs.

(42) The time intervals for the network entities **105** or the UEs **115** may be expressed in multiples of a basic time unit which may, for example, refer to a sampling period of $T_{\text{sub.s}} = 1/(\Delta f_{\text{sub.max}} \cdot N_{\text{sub.f}})$ seconds, for which $\Delta f_{\text{sub.max}}$ may represent a supported subcarrier spacing, and $N_{\text{sub.f}}$ may represent a supported discrete Fourier transform (DFT) size. Time intervals of a communications resource may be organized according to radio frames each having a specified duration (e.g., 10 milliseconds (ms)). Each radio frame may be identified by a system frame number (SFN) (e.g., ranging from 0 to 1023).

(43) Each frame may include multiple consecutively-numbered subframes or slots, and each subframe or slot may have the same duration. In some aspects, a frame may be divided (e.g., in the time domain) into subframes, and each subframe may be further divided into a quantity of slots. Alternatively, each frame may include a variable quantity of slots, and the quantity of slots may depend on subcarrier spacing. Each slot may include a quantity of symbol periods (e.g., depending on the length of the cyclic prefix prepended to each symbol period). In some wireless communications systems **100**, a slot may further be divided into multiple mini-slots associated with one or more symbols. Excluding the cyclic prefix, each symbol period may be associated with one or more (e.g., $N_{\text{sub.f}}$) sampling periods. The duration of a symbol period may depend on the subcarrier spacing or frequency band of operation.

(44) A subframe, a slot, a mini-slot, or a symbol may be the smallest scheduling unit (e.g., in the time domain) of the wireless communications system **100** and may be referred to as a transmission time interval (TTI). In some aspects, the TTI duration (e.g., a quantity of symbol periods in a TTI) may be variable. Additionally, or alternatively, the smallest scheduling unit of the wireless communications system **100** may be dynamically selected (e.g., in bursts of shortened TTIs (sTTIs)).

(45) Physical channels may be multiplexed for communication using a carrier according to various techniques. A physical control channel and a physical data channel may be multiplexed for signaling via a downlink carrier, for example, using one or more of time division multiplexing (TDM) techniques, frequency division multiplexing (FDM) techniques, or hybrid TDM-FDM techniques. A control region (e.g., a control resource set (CORESET)) for a physical control channel may be defined by a set of symbol periods and may extend across the system bandwidth or a subset of the system bandwidth of the carrier. One or more control regions (e.g., CORESETs) may be configured for a set of the UEs **115**. For example, one or more of the UEs **115** may monitor or search control regions for control information according to one or more search space sets, and each search space set may include one or multiple control channel candidates in one or more

aggregation levels arranged in a cascaded manner. An aggregation level for a control channel candidate may refer to an amount of control channel resources (e.g., CCEs) associated with encoded information for a control information format having a given payload size. Search space sets may include common search space sets configured for sending control information to multiple UEs **115** and UE-specific search space sets for sending control information to a specific UE **115**.

(46) A network entity **105** may provide communication coverage via one or more cells, for example a macro cell, a small cell, a hot spot, or other types of cells, or any combination thereof. The term “cell” may refer to a logical communication entity used for communication with a network entity **105** (e.g., using a carrier) and may be associated with an identifier for distinguishing neighboring cells (e.g., a physical cell identifier (PCID), a virtual cell identifier (VCID), or others). In some aspects, a cell also may refer to a coverage area **110** or a portion of a coverage area **110** (e.g., a sector) over which the logical communication entity operates. Such cells may range from smaller areas (e.g., a structure, a subset of structure) to larger areas depending on various factors such as the capabilities of the network entity **105**. For example, a cell may be or include a building, a subset of a building, or exterior spaces between or overlapping with coverage areas **110**, among other examples.

(47) A macro cell generally covers a relatively large geographic area (e.g., several kilometers in radius) and may allow unrestricted access by the UEs **115** with service subscriptions with the network provider supporting the macro cell. A small cell may be associated with a lower-powered network entity **105** (e.g., a lower-powered base station **140**), as compared with a macro cell, and a small cell may operate using the same or different (e.g., licensed, unlicensed) frequency bands as macro cells. Small cells may provide unrestricted access to the UEs **115** with service subscriptions with the network provider or may provide restricted access to the UEs **115** having an association with the small cell (e.g., the UEs **115** in a closed subscriber group (CSG), the UEs **115** associated with users in a home or office). A network entity **105** may support one or multiple cells and may also support communications via the one or more cells using one or multiple component carriers.

(48) In some aspects, a carrier may support multiple cells, and different cells may be configured according to different protocol types (e.g., MTC, narrowband IoT (NB-IoT), enhanced mobile broadband (eMBB)) that may provide access for different types of devices.

(49) In some aspects, a network entity **105** (e.g., a base station **140**, an RU **170**) may be movable and therefore provide communication coverage for a moving coverage area **110**. In some aspects, different coverage areas **110** associated with different technologies may overlap, but the different coverage areas **110** may be supported by the same network entity **105**. In some other examples, the overlapping coverage areas **110** associated with different technologies may be supported by different network entities **105**. The wireless communications system **100** may include, for example, a heterogeneous network in which different types of the network entities **105** provide coverage for various coverage areas **110** using the same or different radio access technologies.

(50) The wireless communications system **100** may support synchronous or asynchronous operation. For synchronous operation, network entities **105** (e.g., base stations **140**) may have similar frame timings, and transmissions from different network entities **105** may be approximately aligned in time. For asynchronous operation, network entities **105** may have different frame timings, and transmissions from different network entities **105** may, in some aspects, not be aligned in time. The techniques described herein may be used for either synchronous or asynchronous operations.

(51) Some UEs **115**, such as MTC or IoT devices, may be low cost or low complexity devices and may provide for automated communication between machines (e.g., via Machine-to-Machine (M2M) communication). M2M communication or MTC may refer to data communication technologies that allow devices to communicate with one another or a network entity **105** (e.g., a base station **140**) without human intervention. In some aspects, M2M communication or MTC may include communications from devices that integrate sensors or meters to measure or capture

information and relay such information to a central server or application program that uses the information or presents the information to humans interacting with the application program. Some UEs **115** may be designed to collect information or enable automated behavior of machines or other devices. Examples of applications for MTC devices include smart metering, inventory monitoring, water level monitoring, equipment monitoring, healthcare monitoring, wildlife monitoring, weather and geological event monitoring, fleet management and tracking, remote security sensing, physical access control, and transaction-based business charging.

(52) Some UEs **115** may be configured to employ operating modes that reduce power consumption, such as half-duplex communications (e.g., a mode that supports one-way communication via transmission or reception, but not transmission and reception concurrently). In some aspects, half-duplex communications may be performed at a reduced peak rate. Other power conservation techniques for the UEs **115** include entering a power saving deep sleep mode when not engaging in active communications, operating using a limited bandwidth (e.g., according to narrowband communications), or a combination of these techniques. For example, some UEs **115** may be configured for operation using a narrowband protocol type that is associated with a defined portion or range (e.g., set of subcarriers or resource blocks (RBs)) within a carrier, within a guard-band of a carrier, or outside of a carrier.

(53) The wireless communications system **100** may be configured to support ultra-reliable communications or low-latency communications, or various combinations thereof. For example, the wireless communications system **100** may be configured to support ultra-reliable low-latency communications (URLLC). The UEs **115** may be designed to support ultra-reliable, low-latency, or critical functions. Ultra-reliable communications may include private communication or group communication and may be supported by one or more services such as push-to-talk, video, or data. Support for ultra-reliable, low-latency functions may include prioritization of services, and such services may be used for public safety or general commercial applications. The terms ultra-reliable, low-latency, and ultra-reliable low-latency may be used interchangeably herein.

(54) In some aspects, a UE **115** may be configured to support communicating directly with other UEs **115** via a device-to-device (D2D) communication link **135** (e.g., in accordance with a peer-to-peer (P2P), D2D, or sidelink protocol). In some aspects, one or more UEs **115** of a group that are performing D2D communications may be within the coverage area **110** of a network entity **105** (e.g., a base station **140**, an RU **170**), which may support aspects of such D2D communications being configured by (e.g., scheduled by) the network entity **105**. In some aspects, one or more UEs **115** of such a group may be outside the coverage area **110** of a network entity **105** or may be otherwise unable to or not configured to receive transmissions from a network entity **105**. In some aspects, groups of the UEs **115** communicating via D2D communications may support a one-to-many (1: M) system in which each UE **115** transmits to each of the other UEs **115** in the group. In some aspects, a network entity **105** may facilitate the scheduling of resources for D2D communications. In some other examples, D2D communications may be carried out between the UEs **115** without an involvement of a network entity **105**.

(55) In some systems, a D2D communication link **135** may be an example of a communication channel, such as a sidelink communication channel, between vehicles (e.g., UEs **115**). In some aspects, vehicles may communicate using vehicle-to-everything (V2X) communications, vehicle-to-vehicle (V2V) communications, or some combination of these. A vehicle may signal information related to traffic conditions, signal scheduling, weather, safety, emergencies, or any other information relevant to a V2X system. In some aspects, vehicles in a V2X system may communicate with roadside infrastructure, such as roadside units, or with the network via one or more network nodes (e.g., network entities **105**, base stations **140**, RUs **170**) using vehicle-to-network (V2N) communications, or with both.

(56) The core network **130** may provide user authentication, access authorization, tracking, Internet Protocol (IP) connectivity, and other access, routing, or mobility functions. The core network **130**

may be an evolved packet core (EPC) or 5G core (5GC), which may include at least one control plane entity that manages access and mobility (e.g., a mobility management entity (MME), an access and mobility management function (AMF)) and at least one user plane entity that routes packets or interconnects to external networks (e.g., a serving gateway (S-GW), a Packet Data Network (PDN) gateway (P-GW), or a user plane function (UPF)). The control plane entity may manage non-access stratum (NAS) functions such as mobility, authentication, and bearer management for the UEs **115** served by the network entities **105** (e.g., base stations **140**) associated with the core network **130**. User IP packets may be transferred through the user plane entity, which may provide IP address allocation as well as other functions. The user plane entity may be connected to IP services **150** for one or more network operators. The IP services **150** may include access to the Internet, Intranet(s), an IP Multimedia Subsystem (IMS), or a Packet-Switched Streaming Service.

(57) The wireless communications system **100** may operate using one or more frequency bands, which may be in the range of 300 megahertz (MHz) to 300 gigahertz (GHz). Generally, the region from 300 MHz to 3 GHz is known as the ultra-high frequency (UHF) region or decimeter band because the wavelengths range from approximately one decimeter to one meter in length. UHF waves may be blocked or redirected by buildings and environmental features, which may be referred to as clusters, but the waves may penetrate structures sufficiently for a macro cell to provide service to the UEs **115** located indoors. Communications using UHF waves may be associated with smaller antennas and shorter ranges (e.g., less than 100 kilometers) compared to communications using the smaller frequencies and longer waves of the high frequency (HF) or very high frequency (VHF) portion of the spectrum below 300 MHz.

(58) The wireless communications system **100** may also operate using a super high frequency (SHF) region, which may be in the range of 3 GHz to 30 GHz, also known as the centimeter band, or using an extremely high frequency (EHF) region of the spectrum (e.g., from 30 GHz to 300 GHz), also known as the millimeter band. In some aspects, the wireless communications system **100** may support millimeter wave (mmW) communications between the UEs **115** and the network entities **105** (e.g., base stations **140**, RUs **170**), and EHF antennas of the respective devices may be smaller and more closely spaced than UHF antennas. In some aspects, such techniques may facilitate using antenna arrays within a device. The propagation of EHF transmissions, however, may be subject to even greater attenuation and shorter range than SHF or UHF transmissions. The techniques disclosed herein may be employed across transmissions that use one or more different frequency regions, and designated use of bands across these frequency regions may differ by country or regulating body.

(59) The wireless communications system **100** may utilize both licensed and unlicensed RF spectrum bands. For example, the wireless communications system **100** may employ License Assisted Access (LAA), LTE-Unlicensed (LTE-U) radio access technology, or NR technology using an unlicensed band such as the 5 GHz industrial, scientific, and medical (ISM) band. While operating using unlicensed RF spectrum bands, devices such as the network entities **105** and the UEs **115** may employ carrier sensing for collision detection and avoidance. In some aspects, operations using unlicensed bands may be based on a carrier aggregation configuration in conjunction with component carriers operating using a licensed band (e.g., LAA). Operations using unlicensed spectrum may include downlink transmissions, uplink transmissions, P2P transmissions, or D2D transmissions, among other examples.

(60) A network entity **105** (e.g., a base station **140**, an RU **170**) or a UE **115** may be equipped with multiple antennas, which may be used to employ techniques such as transmit diversity, receive diversity, multiple-input multiple-output (MIMO) communications, or beamforming. The antennas of a network entity **105** or a UE **115** may be located within one or more antenna arrays or antenna panels, which may support MIMO operations or transmit or receive beamforming. For example, one or more base station antennas or antenna arrays may be co-located at an antenna assembly,

such as an antenna tower. In some aspects, antennas or antenna arrays associated with a network entity **105** may be located at diverse geographic locations. A network entity **105** may include an antenna array with a set of rows and columns of antenna ports that the network entity **105** may use to support beamforming of communications with a UE **115**. Likewise, a UE **115** may include one or more antenna arrays that may support various MIMO or beamforming operations. Additionally, or alternatively, an antenna panel may support RF beamforming for a signal transmitted via an antenna port.

(61) The network entities **105** or the UEs **115** may use MIMO communications to exploit multipath signal propagation and increase spectral efficiency by transmitting or receiving multiple signals via different spatial layers. Such techniques may be referred to as spatial multiplexing. The multiple signals may, for example, be transmitted by the transmitting device via different antennas or different combinations of antennas. Likewise, the multiple signals may be received by the receiving device via different antennas or different combinations of antennas. Each of the multiple signals may be referred to as a separate spatial stream and may carry information associated with the same data stream (e.g., the same codeword) or different data streams (e.g., different codewords). Different spatial layers may be associated with different antenna ports used for channel measurement and reporting. MIMO techniques include single-user MIMO (SU-MIMO), for which multiple spatial layers are transmitted to the same receiving device, and multiple-user MIMO (MU-MIMO), for which multiple spatial layers are transmitted to multiple devices.

(62) Beamforming, which may also be referred to as spatial filtering, directional transmission, or directional reception, is a signal processing technique that may be used at a transmitting device or a receiving device (e.g., a network entity **105**, a UE **115**) to shape or steer an antenna beam (e.g., a transmit beam, a receive beam) along a spatial path between the transmitting device and the receiving device. Beamforming may be achieved by combining the signals communicated via antenna elements of an antenna array such that some signals propagating along particular orientations with respect to an antenna array experience constructive interference while others experience destructive interference. The adjustment of signals communicated via the antenna elements may include a transmitting device or a receiving device applying amplitude offsets, phase offsets, or both to signals carried via the antenna elements associated with the device. The adjustments associated with each of the antenna elements may be defined by a beamforming weight set associated with a particular orientation (e.g., with respect to the antenna array of the transmitting device or receiving device, or with respect to some other orientation).

(63) A network entity **105** or a UE **115** may use beam sweeping techniques as part of beamforming operations. For example, a network entity **105** (e.g., a base station **140**, an RU **170**) may use multiple antennas or antenna arrays (e.g., antenna panels) to conduct beamforming operations for directional communications with a UE **115**. Some signals (e.g., synchronization signals, reference signals, beam selection signals, or other control signals) may be transmitted by a network entity **105** multiple times along different directions. For example, the network entity **105** may transmit a signal according to different beamforming weight sets associated with different directions of transmission. Transmissions along different beam directions may be used to identify (e.g., by a transmitting device, such as a network entity **105**, or by a receiving device, such as a UE **115**) a beam direction for later transmission or reception by the network entity **105**.

(64) Some signals, such as data signals associated with a particular receiving device, may be transmitted by transmitting device (e.g., a transmitting network entity **105**, a transmitting UE **115**) along a single beam direction (e.g., a direction associated with the receiving device, such as a receiving network entity **105** or a receiving UE **115**). In some aspects, the beam direction associated with transmissions along a single beam direction may be determined based on a signal that was transmitted along one or more beam directions. For example, a UE **115** may receive one or more of the signals transmitted by the network entity **105** along different directions and may report to the network entity **105** an indication of the signal that the UE **115** received with a highest signal

quality or an otherwise acceptable signal quality.

(65) In some aspects, transmissions by a device (e.g., by a network entity **105** or a UE **115**) may be performed using multiple beam directions, and the device may use a combination of digital precoding or beamforming to generate a combined beam for transmission (e.g., from a network entity **105** to a UE **115**). The UE **115** may report feedback that indicates precoding weights for one or more beam directions, and the feedback may correspond to a configured set of beams across a system bandwidth or one or more sub-bands. The network entity **105** may transmit a reference signal (e.g., a cell-specific reference signal (CRS), a channel state information reference signal (CSI-RS)), which may be precoded or unprecoded. The UE **115** may provide feedback for beam selection, which may be a precoding matrix indicator (PMI) or codebook-based feedback (e.g., a multi-panel type codebook, a linear combination type codebook, a port selection type codebook). Although these techniques are described with reference to signals transmitted along one or more directions by a network entity **105** (e.g., a base station **140**, an RU **170**), a UE **115** may employ similar techniques for transmitting signals multiple times along different directions (e.g., for identifying a beam direction for subsequent transmission or reception by the UE **115**) or for transmitting a signal along a single direction (e.g., for transmitting data to a receiving device).

(66) A receiving device (e.g., a UE **115**) may perform reception operations in accordance with multiple receive configurations (e.g., directional listening) when receiving various signals from a receiving device (e.g., a network entity **105**), such as synchronization signals, reference signals, beam selection signals, or other control signals. For example, a receiving device may perform reception in accordance with multiple receive directions by receiving via different antenna subarrays, by processing received signals according to different antenna subarrays, by receiving according to different receive beamforming weight sets (e.g., different directional listening weight sets) applied to signals received at multiple antenna elements of an antenna array, or by processing received signals according to different receive beamforming weight sets applied to signals received at multiple antenna elements of an antenna array, any of which may be referred to as “listening” according to different receive configurations or receive directions. In some aspects, a receiving device may use a single receive configuration to receive along a single beam direction (e.g., when receiving a data signal). The single receive configuration may be aligned along a beam direction determined based on listening according to different receive configuration directions (e.g., a beam direction determined to have a highest signal strength, highest signal-to-noise ratio (SNR), or otherwise acceptable signal quality based on listening according to multiple beam directions).

(67) The wireless communications system **100** may be a packet-based network that operates according to a layered protocol stack. In the user plane, communications at the bearer or PDCP layer may be IP-based. An RLC layer may perform packet segmentation and reassembly to communicate via logical channels. A MAC layer may perform priority handling and multiplexing of logical channels into transport channels. The MAC layer also may implement error detection techniques, error correction techniques, or both to support retransmissions to improve link efficiency. In the control plane, an RRC layer may provide establishment, configuration, and maintenance of an RRC connection between a UE **115** and a network entity **105** or a core network **130** supporting radio bearers for user plane data. A PHY layer may map transport channels to physical channels.

(68) The UEs **115** and the network entities **105** may support retransmissions of data to increase the likelihood that data is received successfully. Hybrid automatic repeat request (HARQ) feedback is one technique for increasing the likelihood that data is received correctly via a communication link (e.g., a communication link **125**, a D2D communication link **135**). HARQ may include a combination of error detection (e.g., using a CRC), forward error correction (FEC), and retransmission (e.g., automatic repeat request (ARQ)). HARQ may improve throughput at the MAC layer in poor radio conditions (e.g., low signal-to-noise conditions). In some aspects, a device may support same-slot HARQ feedback, in which case the device may provide HARQ

feedback in a specific slot for data received via a previous symbol in the slot. In some other examples, the device may provide HARQ feedback in a subsequent slot, or according to some other time interval.

(69) The wireless communications system **100** may implement cross-carrier scheduling and/or multi-cell scheduling by a single DCI (e.g., MC-DCI). The overhead of a DCI may be reduced by compressing or removing the CIF. For example, RRC may indicate, to a UE **115**, a DCI payload size, CCEs, and/or PDCCH candidates per scheduled cell or per group of scheduled cells. If the DCI payload sizes, CCEs, and/or PDCCH candidates are different for the scheduled cells indicated in the RRC signaling, the UE **115** may determine to which scheduled cell(s) a DCI received in a PDCCH monitoring occasion applies based on the payload size and/or CCEs of the PDCCH monitoring occasion without using a CIF field. Accordingly, the size of the DCI may be reduced by removing the CIF field.

(70) In some aspects, if the DCI payload sizes, CCEs, and PDCCH candidates for two or more scheduled cells or groups of scheduled cells are the same, the UE **115** may determine the scheduled cell(s) for a PDCCH monitoring occasion without a CIF based on one or more configured rules. For example, if the DCI payload size, the CCEs, and the PDCCH monitoring occasion matches two or more scheduled cells or groups of scheduled cells, the UE **115** may determine that the PDCCH monitoring occasion corresponds to the scheduled cell(s) with the lower/higher component carrier index, the lower/higher SCS, the group of scheduled cells that includes the Primary cell, the group of scheduled cells that includes the scheduling cell, or the group of cells that includes the most/least amount of cells.

(71) In some aspects, if the DCI payload sizes, CCEs, and PDCCH candidates for two or more scheduled cells or groups of scheduled cells are the same, the UE **115** may determine the corresponding scheduled cell or group of scheduled cells for a PDCCH monitoring occasion without a CIF based on determining the RNTI that was used to scramble the CRC for the PDCCH monitoring occasion and matching the RNTI to a scheduled cell or group of scheduled cells.

(72) FIG. 2 illustrates an example of a scheduling diagram **200** that supports scheduled cell identification for multi-cell scheduling in accordance with one or more aspects of the present disclosure. In some aspects, the scheduling diagram **200** may implement aspects of wireless communications systems **100**.

(73) In a self-scheduling mode, a DCI received in a PDCCH occasion via a carrier includes scheduling information for a data communication for that carrier. An RRC message may indicate the number of blind decoding (BD) capabilities and the number of CCEs the UE may process per PDCCH occasion. The RRC may indicate up to 6 different DCI formats (e.g., 4 of 0_1, 1_1, 1_1, 0_2, and 1_2) for a given PDCCH occasion and a UE may process up to 3 payload sizes of DCI formats for cell-RNTI (C-RNTI) and 1 DCI payload size for the other RNTIs for a cell.

(74) In a cross-carrier scheduling mode, as shown in the scheduling diagram **200**, one carrier is used to schedule data communications on different carriers. For example, in a PDCCH occasion **205**, a first DCI **210-a** may schedule a data communication **215-a** on a first carrier (e.g., cell), a second DCI **210-b** may schedule a data communication **215-b** on a second carrier, and a third DCI **210-c** may schedule a data communication **215-c** on a third carrier. An RRC message may indicate the number of BD capabilities and the number of CCEs the UE may process per PDCCH occasion. The RRC may indicate up to 6 different DCI formats (e.g., 4 of 0_0, 1_0, 1_1, 0_2, and 1_2) for a given PDCCH occasion and a UE may process up to 3 payload sizes of DCI formats for C-RNTI and 1 DCI payload size for the other RNTIs for a scheduled cell. A parameter *nci* differentiates the DCI (e.g., the first DCI **210-a**, the second DCI **210-b**, or the third DCI **210-c**) for the scheduled cells. In other words, *nci* is used to distinguish which DCI is associated with which scheduled cell.

(75) Cross-carrier scheduling may be configured by the RRC field *CrossCarrierSchedulingConfig*, which may be configured for each scheduled cell. If the *CrossCarrierSchedulingConfig* is configured with a parameter “other,” that indicates to the UE that the scheduled cell is configured

for cross-carrier scheduling. The CrossCarrierSchedulingConfig field may provide which cell is the scheduling cell and the CIF/n.sub.ci associated with the scheduled cell. For example, a field schedulingCellID may indicate the serving cell index to indicate the scheduling cell and a field cif-InSchedulingCell may indicate the CIF/n.sub.ci associated with the scheduled cell.

(76) A given PDCCH occasion may include a quantity of CCEs, and the n.sub.ci may indicate which CCEs to monitor for a given scheduled cell. For example, for a search space set s associated with a control resource set (CORESET) p , the CCE indexes for aggregation level L corresponding to PDCCH candidate m .sub. s ,n.sub.CI of the search space set in slot n .sub. s ,f.sup. μ for an active DL BWP of a serving cell corresponding to carrier indicator field value n .sub.CI are given by equation 1, where for any common search space (CSS), Y .sub. p ,n.sub. s ,f.sup. μ =0; for a UE-specific search space (USS), Y .sub. p ,n.sub. s ,f.sup. μ =(A .sub. p .Math. Y .sub. p ,n.sub. s ,f.sup. μ .sub.-1)mod D , Y .sub. p ,-1= n .sub.RNTI $\neq 0$, A .sub. p =39827 for p mod3=0, A .sub. p =39829 for p mod3=1, A .sub. p =39839 for p mod3=2, and D =65537; i =0, . . . , L -1; N .sub.CCE, p is the number of CCEs, numbered from 0 to N .sub.CCE, p -1, in CORESET p and, if any, per resource block (RB) set; n .sub.CI is the carrier indicator field value if the UE is configured with a carrier indicator field by CrossCarrierSchedulingConfig for the serving cell on which PDCCH is monitored; otherwise, including for any CSS, n .sub.CI=0, m .sub. s ,n.sub.CI=0, . . . M .sub. s ,n.sub.CI.sup.(L)-1, where M .sub. s ,n.sub.CI.sup.(L) is the number of PDCCH candidates the UE is configured to monitor for aggregation level L of a search space set s for a serving cell corresponding to n .sub.CI; for any CSS, M .sub. s ,max.sup.(L)= M .sub. s ,0.sup.(L); for a USS, M .sub. s ,max.sup.(L) is the maximum of M .sub. s ,n.sub.CI.sup.(L) over all configured n .sub.CI values for a CCE aggregation level L of search space set s .

(77)

$$L \cdot \text{Math.} \{ (Y_{p, n_{s,f}} + \text{Math.} \frac{m_{s, n_{ci}} \cdot \text{Math.} N_{\text{CCE}, p}}{L \cdot \text{Math.} M_{s, \max}^{(L)}} \cdot \text{Math.} + n_{ci}) \text{mod} \text{Math.} N_{\text{CCE}, p} / L \cdot \text{Math.} \} + i \quad (1)$$

(78) For cross-carrier scheduling, although the UE monitors PDCCH on the same scheduling cell for multiple scheduled cells, CCEs for PDCCH candidates for different scheduled cells may not be overlapped (as long as there are a sufficient number of CCEs in the CORESET). For example, Table 1 below shows an example with 96 CCEs, L =4, and M =4 for 3 scheduled cells with n .sub.ci=0, 1, and 2, respectively, and where Y .sub. P =0.

(79) TABLE-US-00001 TABLE 1 n.sub.ci M CCE indexes for the (scheduled cell) (index of PDCCH candidate) PDCCH candidate 0 1 0-3 2 24-27 3 48-51 4 72-75 1 1 4-7 2 28-31 3 52-55 4 76-79 2 1 8-11 2 32-35 3 56-59 4 80-83

(80) FIG. 3 illustrates an example of a scheduling diagram 300 that supports scheduled cell identification for multi-cell scheduling in accordance with one or more aspects of the present disclosure. In some aspects, the scheduling diagram 300 may implement aspects of wireless communications systems 100.

(81) An MC-DCI 310 received in a PDCCH occasion 305 may schedule communications (e.g., physical downlink shared channel (PDSCH) or physical uplink shared channel (PUSCH) transmissions) on more than one cell via the same MC-DCI 310. For example, the MC-DCI 310 may schedule a first communication 315-a on a first cell, a second communication 315-b on a second cell, and a third communication 315-c on a third cell. An RRC message may indicate the number of BD capabilities and the number of CCEs the UE may process per PDCCH occasion. MC-DCI may be implemented in intra-band or inter-band carrier aggregation operations. MC-DCI may be implemented in frequency range 1 (FR1) or frequency range 2 (FR2). In some aspects, a single MC-DCI may be used for 3 or more cells for multi-cell PUSCH and/or PDSCH scheduling.

(82) A UE may determine whether a PDCCH candidate is being used for a MC-DCI or a single-cell DCI before the UE decodes the PDCCH candidate. The CIF/n.sub.ci framework may be used to indicate whether a PDCCH candidate is being used for a MC-DCI or a single-cell DCI. For example, RRC may configure an association between a CIF/n.sub.ci value and a set of cells that

may be scheduled by an MC-DCI. For example, in Table 2 below, CIF/n.sub.ci value 2 is configured to be associated with cells 2, 3, and 4 (e.g., indicates a MC-DCI for cells 2, 3, and 4), CIF/n.sub.ci value 1 is configured to be associated with cell 1 (e.g., indicates single-cell DCI for cell 1), and CIF/n.sub.ci value 0 is configured to be associated with cell 0 (e.g., indicates single-cell DCI for cell 0). Accordingly, in the scenario shown in Table 2, an MC-DCI has a CIF field that indicates a value 2 when the MC-DCI targets cells 2, 3, and 4 as co-scheduled cells. For example, Table 2 shows an example with 96 CCEs, L=4, and M=4 for 5 scheduled cells with n.sub.ci=0, 1, and 2, (where value 2 is associated with cells 2, 3, and 4), and where Y.sub.p=0.

(83) TABLE-US-00002 TABLE 2 n.sub.ci M CCE indexes for the (scheduled cells) (index of PDCCH candidate) PDCCH candidate 0 1 0-3 (0) 2 24-27 3 48-51 4 72-75 1 1 4-7 (1) 2 28-31 3 52-55 4 76-79 2 1 8-11 (2, 3, 4) 2 32-35 3 56-59 4 80-83

(84) FIG. 4 illustrates an example of a wireless communications system 400 that supports scheduled cell identification for multi-cell scheduling in accordance with one or more aspects of the present disclosure. The wireless communications system 400 may implement aspects of wireless communications system 100. The wireless communications system 400 may include a UE 115-a, which may be an example of a UE 115 as described herein. The wireless communications system 400 may include a network entity 105-a, which may be an example of a network entity 105 as described herein.

(85) The UE 115-a may communicate with the network entity 105-a using a communication link 125-a, which may be an example of an NR or LTE link between the UE 115-a and the network entity 105-a. The communication link 125-a may include a bi-directional link that enables both uplink and downlink communication. For example, the UE 115-a may transmit uplink transmissions 405, such as uplink control signals or uplink data signals, to the network entity 105-a using the communication link 125-a and the network entity 105-a may transmit downlink transmissions 410, such as downlink control signals or downlink data signals, to the UE 115-a using the communication link 125-a.

(86) The wireless communications system 400 may implement multi-cell scheduling with a single DCI 430 as described herein. For example, a DCI 430 received via a scheduling cell 415 may schedule communications (e.g., a downlink communication 435-a or an uplink communication 435-b) with one or more of the scheduling cell 415, a first cell 420-a, a second cell 420-b, a third cell 420-c, a fourth cell 420-d, a fifth cell 420-e, a sixth cell 420-f, a seventh cell 420-g, or an eighth cell 420-h.

(87) As an MC-DCI conveys more information than a single-cell DCI in order to schedule communications on the multiple cells, the overhead of an MC-DCI may be higher as compared to a single-cell DCI. To compress the overhead of an MC-DCI, the CIF field may be compressed or removed. In some example wireless communications systems, however, CIF is configured to always be included in a scheduling DCI 430 so that the UE 115-a may determine which scheduled cell(s) a DCI 430 corresponds to. However, other means may be used to distinguish whether a DCI 430 decoded on a set of CCEs is for particular scheduled cell(s) without the use of a CIF, and accordingly, in some aspects, the CIF field may not be used (e.g., may be removed from the DCI 430).

(88) For example, RRC signaling 425 may indicate the payload sizes, CCEs, and/or PDCCH occasions associated with different DCI formats for different cells or subsets of scheduled cells (e.g., one or more of the scheduling cell 415, the first cell 420-a, the second cell 420-b, the third cell 420-c, the fourth cell 420-d, the fifth cell 420-e, the sixth cell 420-f, the seventh cell 420-g, or the eighth cell 420-h). For example, if the payload sizes of DCI formats for different sets of scheduled cell(s) are not the same, the UE 115-a may identify for which scheduled cell(s) a decoded DCI 430 is intended based on the CRC check of the multiple hypotheses of the DCI sizes. As another example, if the sets of CCEs for the PDCCH candidates for different scheduled cell(s) are different, the UE 115-a may identify for which scheduled cell(s) a decoded DCI 430 is intended

based on the CCEs where each PDCCH candidate is mapped. In other words, in some aspects, the CIF field may be used to identify the scheduled cell(s) if: (1) the payload of DCI formats for different scheduled cells is the same; and (2) the set of CCEs for PDCCH candidates for different scheduled cells is the same.

(89) Accordingly in some aspects, the CIF field may be used to identify the scheduled cell(s) if: (1) the UE is configured to monitor two or more DCI formats, on the same scheduling cell, that are configured to schedule PDSCHs or PUSCHs on different (sets of) scheduled cells and the payload/size of the two or more DCI formats different (sets of) scheduled cells is the same; and (2) the UE is configured to decode a PDCCH candidate for one of the two or more DCI formats on a set of CCEs and another PDCCH candidate for another of the two or more DCI formats on the same set of CCEs on the same scheduling cell. Conditions (1) and (2) may be controlled via configurations in RRC signaling **425**, and whether the conditions are met may be identified by the UE **115-a** (and in some aspects by the network entity **105-a**) by the configurations. For example, DCI payload size may depend on various parameters in fields PDSCH-Config, PUCCH-Config, or PUSCH-Config in RRC signaling **425**. A set of CCEs for a PDCCH candidate may depend on parameters in the field PDCCH-Config in RRC signaling **425**. In some aspects, the UE **115-a** (and in some aspects the network entity **105-a**) may compare DCI payload sizes associated with different scheduled cell(s) to generate payload size comparison information to determine whether condition (1) is met. In some aspects, the UE **115-a** (and in some aspects the network entity **105-a**) may compare CCEs associated with PDCCH candidates for the different DCI formats to generate CCE comparison information to determine whether condition (2) is met.

(90) In some aspects, the CIF field may be used to identify the scheduled cell(s) if: (1) the UE is configured to monitor two or more DCI formats, on the same scheduling cell, that are configured to schedule PDSCHs or PUSCHs on different (sets of) scheduled cells and the payload/size of the two or more DCI formats different (sets of) scheduled cells is the same; (2) the UE is configured to decode a PDCCH candidate for one of the two or more DCI formats on a set of CCEs and another PDCCH candidate for another of the two or more DCI formats on the same set of CCEs on the same scheduling cell; and (3) the PDCCH candidates for the two or more DCI formats are monitored at the same PDCCH monitoring occasion. Conditions (1), (2), and (3) may be controlled via configurations in RRC signaling **425**, and whether the conditions are met may be identified by the UE **115-a** (and in some aspects by the network entity **105-a**) by the configurations. PDCCH monitoring occasions may be configured in the field PDCCH-Config in RRC signaling **425**. As illustrated in FIG. 5, due to condition (3), if the PDCCH candidates are monitored in different periodicities for different DCI formats, a CIF field may be included in a DCI **430** in a PDCCH monitoring occasion when condition (3) is satisfied but may not be included in another DCI **430** in a PDCCH monitoring occasion where condition (3) is not satisfied.

(91) In some aspects, a CIF may not be included in a DCI **430** even when conditions (1) and (2) (and in some aspects condition (3)) are satisfied (e.g., at least for MC-DCI). For example, the UE **115-a** (and the network entity **105-a**) may apply one or more rules to determine to which scheduled cell(s) a DCI **430** in a PDCCH monitoring occasion applies. For example, if the DCI payload size, the CCEs, and the PDCCH monitoring occasion matches two or more scheduled cells or groups of scheduled cells, the UE **115-a** (and network entity **105-a**) may determine that the PDCCH monitoring occasion corresponds to the scheduled cell(s) with the lower/higher component carrier index, the lower/higher SCS, the group of scheduled cells that includes the Primary cell, the group of scheduled cells that includes the scheduling cell **415**, or the group of cells that includes the most/least amount of cells.

(92) In some aspects, if the DCI payload sizes, CCEs, and PDCCH candidates for two or more scheduled cells or groups of scheduled cells are the same, the UE **115-a** (and network entity **105-a**) may determine the corresponding scheduled cell or group of scheduled cells for a PDCCH monitoring occasion without a CIF based on determining the RNTI that was used to scramble the

CRC parity bits) for the PDCCH monitoring occasion and matching the RNTI to a scheduled cell or group of scheduled cells. For example, the UE **115-a** may be configured with a UE-specific (virtual) RNTI value (e.g., via the RRC signaling **425**) that is used to scramble the CRC of PDCCH. If conditions (1) and (2) (or conditions (1), (2), and (3)) are satisfied, the UE **115-a** may check both legacy RNTI(s) (e.g., C-RNTI, configured scheduling RNTI (CS-RNTI), modulation and coding scheme cell RNTI (MCS-C-RNTI)) and the additional UE-specific (virtual) RNTI. Depending on which RNTI was used to scramble the CRC, the UE **115-a** may identify which DCI format was used in the PDCCH monitoring occasion (and accordingly to which scheduled cell(s) the DCI **430** applies). The RRC signaling **425** may configure an association between a DCI format and the additional UE-specific virtual RNTI.

(93) In some aspects, the *n.sub.ci* value in equation 1 used to determine which CCEs correspond to which DCI formats (and accordingly which scheduled cell(s) may be independent of the CIF field in a DCI **430**, for example, because the DCI **430** may not include a CIF field. An *n.sub.ci* value may be indicated in RRC signaling **425** per scheduled cell or group of scheduled cells (e.g., for MC-DCI). If a CIF field is present in DCI **430**, the CIF field matches the *n.sub.ci* value for the scheduled cell or group of scheduled cells.

(94) In some aspects, the term DCI format 0_X may be used for an MC-DCI scheduling multiple PUSCHs on multiple cells with one PUSCH per cell. In some aspects, the term DCI format 1_X may be used for an MC-DCI scheduling multiple PDSCHs on multiple cells with one PDSCH per cell. Different transport blocks (TB)s may be scheduled on different cells by a DCI having DCI format 0_X or DCI format 1_X. In some aspects, fallback DCI (e.g., DCI formats 0_0 and 1_0) may not support multi-cell scheduling. In some aspects, the DCI form multi-cell scheduling may be monitored only in a USS set. In some aspects, a PDSCH may not be scheduled by a DCI having DCI format 0_X. In some aspects, a PUSCH may not be scheduled by a DCI having DCI format 1_X. In some aspects, all of the co-scheduled cells by a DCI having DCI format 1_X and the scheduling cell may be included in the same physical uplink control channel (PUCCH) group. In some aspects, all of the co-scheduled cells by a DCI having DCI format 0_X and the scheduling cell may be included in the same cell or PUCCH group. In some aspects, a DCI having a DCI format 0-X or 1-X on a scheduling cell may be used to schedule PUSCHs or PDSCHs on multiple cells including the scheduling cell. In some aspects, a DCI having a DCI format 0-X or 1-X on a scheduling cell may be used to schedule PUSCHs or PDSCHs on multiple cells not including the scheduling cell. In some aspects, for the UE **115-a**, the maximum number of cells scheduled by a DCI having DCI format 0_X may be the same or different than the maximum number of cells scheduled by a DCI having DCI format 1_X.

(95) In some aspects, one value for the maximum number of co-scheduled cells scheduled by a DCI having DCI format 0_X may be selected from {3, 4, 8}. In some aspects, one value for the maximum number of co-scheduled cells scheduled by a DCI having DCI format 0_X may be smaller than or equal to {3, 4, 8}. In some aspects, one value for the maximum number of co-scheduled cells scheduled by a DCI having DCI format 1_X may be selected from {3, 4, 8}. In some aspects, one value for the maximum number of co-scheduled cells scheduled by a DCI having DCI format 1_X may be smaller than or equal to {3, 4, 8}.

(96) In some aspects, the DCI format 0_X may be used for single cell PUSCH scheduling. In some aspects, the DCI format 1_X may be used for single cell PDSCH scheduling. The UE **115-a** may monitor one or both multi-cell scheduling DCI and single-cell scheduling DCI for a scheduled cell. In some aspects, DCI having DCI format 0_X or 1_X be transmitted via a Primary cell. In some aspects, DCI having DCI format 0_X or 1_X be transmitted via a Secondary cell, at least when the DCI having DCI format 0_X or 1_X does not schedule a PUSCH or PDSCH on the Primary cell.

(97) FIG. 5 illustrates an example of a resource diagram **500** that supports scheduled cell identification for multi-cell scheduling in accordance with one or more aspects of the present disclosure. In some aspects, the resource diagram **500** may implement aspects of wireless

communications systems **100** or **400**.

(98) A first PDCCH candidate for a DCI format X that schedules PDSCHs or PUSCHs on a cell set A may be monitored on every slot (e.g., in PDCCH monitoring occasion **505-a** in slot 0, in PDCCH monitoring occasion **505-b** in slot 1, in PDCCH monitoring occasion **505-c** in slot 2, and in PDCCH monitoring occasion **505-d** in slot 3). A second PDCCH candidate for a DCI format Y that schedules PDSCHs on a cell set B may be monitored on every other slot (e.g., in PDCCH monitoring occasion **505-a** in slot 0 and in PDCCH monitoring occasion **505-c** in slot 2). If the DCI formats X and Y are both associated with CCE 4, CCE 5, CCE 6 and CCE 7, and both have the same DCI payload size, the UE **115** may determine that the DCI received in PDCCH monitoring occasion **505-b** and the DCI received in PDCCH monitoring occasion **505-d** schedules PDSCHs or PUSCHs on a cell set A without a CIF as PDCCH monitoring occasion **505-b** and PDCCH monitoring occasion **505-d** are not configured for DCI format Y. For PDCCH monitoring occasion **505-a** and PDCCH monitoring occasion **505-c**, however, a CIF may be used to indicate whether a DCI in PDCCH monitoring occasion **505-a** and PDCCH monitoring occasion **505-c** schedules PDSCHs or PUSCHs on the cell set A or the cell set B (e.g., whether the DCI has DCI format X or DCI format Y).

(99) FIG. **6** illustrates an example of a process flow **600** that supports scheduled cell identification for multi-cell scheduling in accordance with one or more aspects of the present disclosure. The process flow **600** may include a UE **115-b**, which may be an example of a UE **115** as described herein. The process flow **600** may include a network entity **105-b**, which may be an example of a network entity **105** as described herein. In the following description of the process flow **600**, the operations between the network entity **105-b** and the UE **115-b** may be transmitted in a different order than the example order shown, or the operations performed by the network entity **105-b** and the UE **115-b** may be performed in different orders or at different times. Some operations may also be omitted from the process flow **600**, and other operations may be added to the process flow **600**.

(100) At **605**, the UE **115-b** may receive, from the network entity **105-b**, control signaling including an indication of a respective DCI payload size for each subset of scheduled cells of a set of scheduled cells, where the set of scheduled cells are associated with a scheduling cell, and where the control signaling further includes an indication of a respective set of CCEs for each subset of scheduled cells.

(101) At **610**, the UE **115-b** (and in some aspects the network entity **105-b**) may determine, based on first comparison information corresponding to the respective DCI payload sizes and second comparison information corresponding to the respective sets of CCEs, a DCI format for a downlink control channel monitoring occasion in the scheduling cell. The DCI format is associated with a subset of scheduled cells of the set of scheduled cells, and the DCI format includes an absence or a presence of an indication of the subset of scheduled cells.

(102) At **615**, the UE **115-b** may receive, from the network entity **105-b** via the DCI monitoring occasion, DCI in accordance with the determined DCI format.

(103) In some aspects, the control signaling further includes an indication of a respective set of downlink control channels for each subset of scheduled cells, and third comparison information corresponds to the respective sets of downlink control channels. The UE **115-b** (and in some aspects the network entity **105-b**) may determine the DCI format based on the third comparison information.

(104) In some aspects, the first comparison information is indicative that each respective DCI payload size for each subset of scheduled cells is different. Determining the DCI format may include determining the DCI format based on a payload size for the downlink control channel monitoring occasion that matches a respective DCI payload size of the subset of scheduled cells.

(105) In some aspects, the second comparison information is indicative that each respective set of CCEs for each subset of scheduled cells is different. Determining the DCI format may include determining the DCI format based on a set of CCEs for the downlink control channel monitoring

occasion that matches a respective set of CCEs for the subset of scheduled cells.

(106) In some aspects, the first comparison information is indicative that at least two respective DCI payload sizes for at least two subsets of scheduled cells are equal, wherein the second comparison information is indicative that respective sets of CCEs for the at least two subsets of scheduled cells are equal. The UE **115-b** (and in some aspects the network entity **105-b**) may determine, based on the first comparison information being indicative that the at least two respective DCI payload sizes are equal and the second comparison information being indicative that the respective sets of CCEs are equal, that the DCI includes the presence of the indication of the subset of scheduled cells. The indication of the subset of scheduled cells may include an explicit indication of the subset of scheduled cells.

(107) In some aspects, the first comparison information is indicative that at least two respective DCI payload sizes for at least two subsets of scheduled cells are equal, wherein the second comparison information is indicative that respective sets of CCEs for the at least two subsets of scheduled cells are equal. The UE **115-b** (and in some aspects the network entity **105-b**) may determine, based on the first comparison information being indicative that the at least two respective DCI payload sizes are equal and the second comparison information being indicative that the respective sets of CCEs are equal, that the DCI includes the presence of the indication of the subset of scheduled cells. The indication of the subset of scheduled cells may include a rule-based indication of the subset of scheduled cells. In some aspects, the rule-based indication includes information indicative of a rule to select the subset of scheduled cells of the set of scheduled cells based on one of a component carrier index associated with one or more scheduled cells within the subset of scheduled cells, a subcarrier spacing associated with one or more scheduled cells within the subset of scheduled cells, the subset of scheduled cells including a primary cell for the first network node, the subset of scheduled cells including the scheduling cell, or a number of cells associated with the subset of scheduled cells.

(108) In some aspects, the first comparison information is indicative that at least two respective DCI payload sizes for at least two subsets of scheduled cells are equal, wherein the second comparison information is indicative that respective sets of CCEs for the at least two subsets of scheduled cells are equal. The UE **115-b** (and in some aspects the network entity **105-b**) may determine, based on the first comparison information being indicative that the at least two respective DCI payload sizes are equal and the second comparison information being indicative that the respective sets of CCEs are equal, that the DCI includes the presence of the indication of the subset of scheduled cells. The indication of the subset of scheduled cells may include a radio network identifier used to scramble a CRC of the downlink control channel monitoring occasion. In some aspects, the control signaling further includes an indication of an association between respective radio network identifiers and each subset of scheduled cells.

(109) In some aspects, the DCI includes scheduling information for one or more communications with the subset of scheduled cells. At **620**, the UE **115-b** may communicate the one or more communications with the subset of scheduled cells. In some aspects, the control signaling further includes an indication of a respective carrier indicator associated with each scheduled cell of the set of scheduled cells, and a determination of the scheduling information is based on the indication of the respective carrier indicator associated with each scheduled cell of the set of scheduled cells.

(110) In some aspects, the UE **115-b** (and in some aspects the network entity **105-b**) may compare the respective DCI payload sizes and generate the first comparison information based on the comparison of the respective DCI payload sizes. In some aspects, the UE **115-b** (and in some aspects the network entity **105-b**) may compare the respective sets of CCEs; and generate the second comparison information based on the comparison of the respective sets of CCEs.

(111) FIG. 7 shows a block diagram **700** of a device **705** that supports scheduled cell identification for multi-cell scheduling in accordance with one or more aspects of the present disclosure. The device **705** may be an example of aspects of a UE **115** as described herein. The device **705** may

include a receiver **710**, a transmitter **715**, and a communications manager **720**. The device **705** may also include a processor. Each of these components may be in communication with one another (e.g., via one or more buses).

(112) The receiver **710** may provide a means for receiving information such as packets, user data, control information, or any combination thereof associated with various information channels (e.g., control channels, data channels, information channels related to scheduled cell identification for multi-cell scheduling). Information may be passed on to other components of the device **705**. The receiver **710** may utilize a single antenna or a set of multiple antennas.

(113) The transmitter **715** may provide a means for transmitting signals generated by other components of the device **705**. For example, the transmitter **715** may transmit information such as packets, user data, control information, or any combination thereof associated with various information channels (e.g., control channels, data channels, information channels related to scheduled cell identification for multi-cell scheduling). In some aspects, the transmitter **715** may be co-located with a receiver **710** in a transceiver module. The transmitter **715** may utilize a single antenna or a set of multiple antennas.

(114) The communications manager **720**, the receiver **710**, the transmitter **715**, or various combinations thereof or various components thereof may be examples of means for performing various aspects of scheduled cell identification for multi-cell scheduling as described herein. For example, the communications manager **720**, the receiver **710**, the transmitter **715**, or various combinations or components thereof may support a method for performing one or more of the functions described herein.

(115) In some aspects, the communications manager **720**, the receiver **710**, the transmitter **715**, or various combinations or components thereof may be implemented in hardware (e.g., in communications management circuitry). The hardware may include a processor, a digital signal processor (DSP), a central processing unit (CPU), an application-specific integrated circuit (ASIC), a field-programmable gate array (FPGA) or other programmable logic device, a microcontroller, discrete gate or transistor logic, discrete hardware components, or any combination thereof configured as or otherwise supporting a means for performing the functions described in the present disclosure. In some aspects, a processor and memory coupled with the processor may be configured to perform one or more of the functions described herein (e.g., by executing, by the processor, instructions stored in the memory).

(116) Additionally, or alternatively, in some aspects, the communications manager **720**, the receiver **710**, the transmitter **715**, or various combinations or components thereof may be implemented in code (e.g., as communications management software or firmware) executed by a processor. If implemented in code executed by a processor, the functions of the communications manager **720**, the receiver **710**, the transmitter **715**, or various combinations or components thereof may be performed by a general-purpose processor, a DSP, a CPU, an ASIC, an FPGA, a microcontroller, or any combination of these or other programmable logic devices (e.g., configured as or otherwise supporting a means for performing the functions described in the present disclosure).

(117) In some aspects, the communications manager **720** may be configured to perform various operations (e.g., receiving, obtaining, monitoring, outputting, transmitting) using or otherwise in cooperation with the receiver **710**, the transmitter **715**, or both. For example, the communications manager **720** may receive information from the receiver **710**, send information to the transmitter **715**, or be integrated in combination with the receiver **710**, the transmitter **715**, or both to obtain information, output information, or perform various other operations as described herein.

(118) The communications manager **720** may support wireless communications at a first network node in accordance with examples as disclosed herein. For example, the communications manager **720** may be configured as or otherwise support a means for receiving control signaling including an indication of a respective DCI payload size for each subset of scheduled cells of a set of scheduled cells, where the set of scheduled cells are associated with a scheduling cell, and where the control

signaling further includes an indication of a respective set of CCEs for each subset of scheduled cells. The communications manager **720** may be configured as or otherwise support a means for determining, based on first comparison information corresponding to the respective DCI payload sizes and second comparison information corresponding to the respective sets of CCEs, a DCI format for a downlink control channel monitoring occasion in the scheduling cell, where the DCI format is associated with a subset of scheduled cells of the set of scheduled cells, where the DCI format includes an absence or a presence of an indication of the subset of scheduled cells. The communications manager **720** may be configured as or otherwise support a means for receiving, via the downlink control channel monitoring occasion, DCI in accordance with the determined DCI format.

(119) By including or configuring the communications manager **720** in accordance with examples as described herein, the device **705** (e.g., a processor controlling or otherwise coupled with the receiver **710**, the transmitter **715**, the communications manager **720**, or a combination thereof) may support techniques for more efficient utilization of communication resources.

(120) FIG. **8** shows a block diagram **800** of a device **805** that supports scheduled cell identification for multi-cell scheduling in accordance with one or more aspects of the present disclosure. The device **805** may be an example of aspects of a device **705** or a UE **115** as described herein. The device **805** may include a receiver **810**, a transmitter **815**, and a communications manager **820**. The device **805** may also include a processor. Each of these components may be in communication with one another (e.g., via one or more buses).

(121) The receiver **810** may provide a means for receiving information such as packets, user data, control information, or any combination thereof associated with various information channels (e.g., control channels, data channels, information channels related to scheduled cell identification for multi-cell scheduling). Information may be passed on to other components of the device **805**. The receiver **810** may utilize a single antenna or a set of multiple antennas.

(122) The transmitter **815** may provide a means for transmitting signals generated by other components of the device **805**. For example, the transmitter **815** may transmit information such as packets, user data, control information, or any combination thereof associated with various information channels (e.g., control channels, data channels, information channels related to scheduled cell identification for multi-cell scheduling). In some aspects, the transmitter **815** may be co-located with a receiver **810** in a transceiver module. The transmitter **815** may utilize a single antenna or a set of multiple antennas.

(123) The device **805**, or various components thereof, may be an example of means for performing various aspects of scheduled cell identification for multi-cell scheduling as described herein. For example, the communications manager **820** may include a scheduled cell manager **825**, a DCI format manager **830**, a DCI manager **835**, or any combination thereof. The communications manager **820** may be an example of aspects of a communications manager **720** as described herein. In some aspects, the communications manager **820**, or various components thereof, may be configured to perform various operations (e.g., receiving, obtaining, monitoring, outputting, transmitting) using or otherwise in cooperation with the receiver **810**, the transmitter **815**, or both. For example, the communications manager **820** may receive information from the receiver **810**, send information to the transmitter **815**, or be integrated in combination with the receiver **810**, the transmitter **815**, or both to obtain information, output information, or perform various other operations as described herein.

(124) The communications manager **820** may support wireless communications at a first network node in accordance with examples as disclosed herein. The scheduled cell manager **825** may be configured as or otherwise support a means for receiving control signaling including an indication of a respective DCI payload size for each subset of scheduled cells of a set of scheduled cells, where the set of scheduled cells are associated with a scheduling cell, and where the control signaling further includes an indication of a respective set of CCEs for each subset of scheduled

cells. The DCI format manager **830** may be configured as or otherwise support a means for determining, based on first comparison information corresponding to the respective DCI payload sizes and second comparison information corresponding to the respective sets of CCEs, a DCI format for a downlink control channel monitoring occasion in the scheduling cell, where the DCI format is associated with a subset of scheduled cells of the set of scheduled cells, where the DCI format includes an absence or a presence of an indication of the subset of scheduled cells. The DCI manager **835** may be configured as or otherwise support a means for receiving, via the downlink control channel monitoring occasion, DCI in accordance with the determined DCI format.

(125) FIG. **9** shows a block diagram **900** of a communications manager **920** that supports scheduled cell identification for multi-cell scheduling in accordance with one or more aspects of the present disclosure. The communications manager **920** may be an example of aspects of a communications manager **720**, a communications manager **820**, or both, as described herein. The communications manager **920**, or various components thereof, may be an example of means for performing various aspects of scheduled cell identification for multi-cell scheduling as described herein. For example, the communications manager **920** may include a scheduled cell manager **925**, a DCI format manager **930**, a DCI manager **935**, a downlink control channel manager **940**, a DCI payload size manager **945**, a DCI CCE manager **950**, a scheduled cell indication manager **955**, a rule-based scheduled cell manager **960**, a network identifier manager **965**, or any combination thereof. Each of these components may communicate, directly or indirectly, with one another (e.g., via one or more buses).

(126) The communications manager **920** may support wireless communications at a first network node in accordance with examples as disclosed herein. The scheduled cell manager **925** may be configured as or otherwise support a means for receiving control signaling including an indication of a respective DCI payload size for each subset of scheduled cells of a set of scheduled cells, where the set of scheduled cells are associated with a scheduling cell, and where the control signaling further includes an indication of a respective set of CCEs for each subset of scheduled cells. The DCI format manager **930** may be configured as or otherwise support a means for determining, based on first comparison information corresponding to the respective DCI payload sizes and second comparison information corresponding to the respective sets of CCEs, a DCI format for a downlink control channel monitoring occasion in the scheduling cell, where the DCI format is associated with a subset of scheduled cells of the set of scheduled cells, where the DCI format includes an absence or a presence of an indication of the subset of scheduled cells. The DCI manager **935** may be configured as or otherwise support a means for receiving, via the downlink control channel monitoring occasion, DCI in accordance with the determined DCI format.

(127) In some aspects, to support determining the DCI format, the downlink control channel manager **940** may be configured as or otherwise support a means for determining the DCI format based on the third comparison information.

(128) In some aspects, to support determining the DCI format, the DCI payload size manager **945** may be configured as or otherwise support a means for determining the DCI format based on a payload size for the downlink control channel monitoring occasion that matches a respective DCI payload size of the subset of scheduled cells.

(129) In some aspects, to support determining the DCI format, the DCI CCE manager **950** may be configured as or otherwise support a means for determining the DCI format based on a set of CCEs for the downlink control channel monitoring occasion that matches a respective set of CCEs for the subset of scheduled cells.

(130) In some aspects, the scheduled cell indication manager **955** may be configured as or otherwise support a means for determining, based on the first comparison information being indicative that at least two respective DCI payload sizes for at least two subsets of scheduled cells are equal and further based on the second comparison information being indicative that respective sets of CCEs for the at least two subsets of scheduled cells are equal, that the DCI includes the

presence of the indication of the subset of scheduled cells, where the indication of the subset of scheduled cells includes an explicit indication of the subset of scheduled cells.

(131) In some aspects, the rule-based scheduled cell manager **960** may be configured as or otherwise support a means for determining, based on the first comparison information being indicative that at least two respective DCI payload sizes for at least two subsets of scheduled cells are equal and further based on the second comparison information being indicative that respective sets of CCEs for the at least two subsets of scheduled cells are equal, that the DCI includes the presence of the indication of the subset of scheduled cells, where the indication of the subset of scheduled cells includes a rule-based indication of the subset of scheduled cells.

(132) In some aspects, the rule-based indication includes information indicative of a rule to select the subset of scheduled cells of the set of scheduled cells based on one of a component carrier index associated with one or more scheduled cells within the subset of scheduled cells, a subcarrier spacing associated with one or more scheduled cells within the subset of scheduled cells, the subset of scheduled cells including a primary cell for the first network node, the subset of scheduled cells including the scheduling cell, or a number of cells associated with the subset of scheduled cells.

(133) In some aspects, the network identifier manager **965** may be configured as or otherwise support a means for determining, based on the first comparison information being indicative that at least two respective DCI payload sizes for at least two subsets of scheduled cells are equal and further based on the second comparison information being indicative that respective sets of CCEs for the at least two subsets of scheduled cells are equal, that the DCI includes the presence of the indication of the subset of scheduled cells, where the indication of the subset of scheduled cells includes a radio network identifier used to scramble a CRC of the downlink control channel monitoring occasion.

(134) In some aspects, the control signaling further includes an indication of an association between respective radio network identifiers and each subset of scheduled cells.

(135) In some aspects, DCI includes scheduling information for one or more communications with the subset of scheduled cells.

(136) In some aspects, the control signaling further includes an indication of a respective carrier indicator associated with each scheduled cell of the set of scheduled cells. In some aspects, a determination of the scheduling information is based on the indication of the respective carrier indicator associated with each scheduled cell of the set of scheduled cells.

(137) In some aspects, the DCI payload size manager **945** may be configured as or otherwise support a means for comparing the respective DCI payload sizes. In some aspects, the DCI payload size manager **945** may be configured as or otherwise support a means for generating the first comparison information based on the comparison of the respective DCI payload sizes.

(138) In some aspects, the DCI CCE manager **950** may be configured as or otherwise support a means for comparing the respective sets of CCEs. In some aspects, the DCI CCE manager **950** may be configured as or otherwise support a means for generating the second comparison information based on the comparison of the respective sets of CCEs.

(139) FIG. **10** shows a diagram of a system **1000** including a device **1005** that supports scheduled cell identification for multi-cell scheduling in accordance with one or more aspects of the present disclosure. The device **1005** may be an example of or include the components of a device **705**, a device **805**, or a UE **115** as described herein. The device **1005** may communicate (e.g., wirelessly) with one or more network entities **105**, one or more UEs **115**, or any combination thereof. The device **1005** may include components for bi-directional voice and data communications including components for transmitting and receiving communications, such as a communications manager **1020**, an input/output (I/O) controller **1010**, a transceiver **1015**, an antenna **1025**, a memory **1030**, code **1035**, and a processor **1040**. These components may be in electronic communication or otherwise coupled (e.g., operatively, communicatively, functionally, electronically, electrically) via one or more buses (e.g., a bus **1045**).

(140) The I/O controller **1010** may manage input and output signals for the device **1005**. The I/O controller **1010** may also manage peripherals not integrated into the device **1005**. In some cases, the I/O controller **1010** may represent a physical connection or port to an external peripheral. In some cases, the I/O controller **1010** may utilize an operating system such as iOS®, ANDROID®, MS-DOS®, MS-WINDOWS®, OS/2®, UNIX®, LINUX®, or another known operating system. Additionally, or alternatively, the I/O controller **1010** may represent or interact with a modem, a keyboard, a mouse, a touchscreen, or a similar device. In some cases, the I/O controller **1010** may be implemented as part of a processor, such as the processor **1040**. In some cases, a user may interact with the device **1005** via the I/O controller **1010** or via hardware components controlled by the I/O controller **1010**.

(141) In some cases, the device **1005** may include a single antenna **1025**. However, in some other cases, the device **1005** may have more than one antenna **1025**, which may be capable of concurrently transmitting or receiving multiple wireless transmissions. The transceiver **1015** may communicate bi-directionally, via the one or more antennas **1025**, wired, or wireless links as described herein. For example, the transceiver **1015** may represent a wireless transceiver and may communicate bi-directionally with another wireless transceiver. The transceiver **1015** may also include a modem to modulate the packets, to provide the modulated packets to one or more antennas **1025** for transmission, and to demodulate packets received from the one or more antennas **1025**. The transceiver **1015**, or the transceiver **1015** and one or more antennas **1025**, may be an example of a transmitter **715**, a transmitter **815**, a receiver **710**, a receiver **810**, or any combination thereof or component thereof, as described herein.

(142) The memory **1030** may include random access memory (RAM) and read-only memory (ROM). The memory **1030** may store computer-readable, computer-executable code **1035** including instructions that, when executed by the processor **1040**, cause the device **1005** to perform various functions described herein. The code **1035** may be stored in a non-transitory computer-readable medium such as system memory or another type of memory. In some cases, the code **1035** may not be directly executable by the processor **1040** but may cause a computer (e.g., when compiled and executed) to perform functions described herein. In some cases, the memory **1030** may contain, among other things, a basic I/O system (BIOS) which may control basic hardware or software operation such as the interaction with peripheral components or devices.

(143) The processor **1040** may include an intelligent hardware device (e.g., a general-purpose processor, a DSP, a CPU, a microcontroller, an ASIC, an FPGA, a programmable logic device, a discrete gate or transistor logic component, a discrete hardware component, or any combination thereof). In some cases, the processor **1040** may be configured to operate a memory array using a memory controller. In some other cases, a memory controller may be integrated into the processor **1040**. The processor **1040** may be configured to execute computer-readable instructions stored in a memory (e.g., the memory **1030**) to cause the device **1005** to perform various functions (e.g., functions or tasks supporting scheduled cell identification for multi-cell scheduling). For example, the device **1005** or a component of the device **1005** may include a processor **1040** and memory **1030** coupled with or to the processor **1040**, the processor **1040** and memory **1030** configured to perform various functions described herein.

(144) The communications manager **1020** may support wireless communications at a first network node in accordance with examples as disclosed herein. For example, the communications manager **1020** may be configured as or otherwise support a means for receiving control signaling including an indication of a respective DCI payload size for each subset of scheduled cells of a set of scheduled cells, where the set of scheduled cells are associated with a scheduling cell, and where the control signaling further includes an indication of a respective set of CCEs for each subset of scheduled cells. The communications manager **1020** may be configured as or otherwise support a means for determining, based on first comparison information corresponding to the respective DCI payload sizes and second comparison information corresponding to the respective sets of CCEs, a

DCI format for a downlink control channel monitoring occasion in the scheduling cell, where the DCI format is associated with a subset of scheduled cells of the set of scheduled cells, where the DCI format includes an absence or a presence of an indication of the subset of scheduled cells. The communications manager **1020** may be configured as or otherwise support a means for receiving, via the downlink control channel monitoring occasion, DCI in accordance with the determined DCI format.

(145) By including or configuring the communications manager **1020** in accordance with examples as described herein, the device **1005** may support techniques for more efficient utilization of communication resources.

(146) In some aspects, the communications manager **1020** may be configured to perform various operations (e.g., receiving, monitoring, transmitting) using or otherwise in cooperation with the transceiver **1015**, the one or more antennas **1025**, or any combination thereof. Although the communications manager **1020** is illustrated as a separate component, in some aspects, one or more functions described with reference to the communications manager **1020** may be supported by or performed by the processor **1040**, the memory **1030**, the code **1035**, or any combination thereof. For example, the code **1035** may include instructions executable by the processor **1040** to cause the device **1005** to perform various aspects of scheduled cell identification for multi-cell scheduling as described herein, or the processor **1040** and the memory **1030** may be otherwise configured to perform or support such operations.

(147) FIG. **11** shows a block diagram **1100** of a device **1105** that supports scheduled cell identification for multi-cell scheduling in accordance with one or more aspects of the present disclosure. The device **1105** may be an example of aspects of a network entity **105** as described herein. The device **1105** may include a receiver **1110**, a transmitter **1115**, and a communications manager **1120**. The device **1105** may also include a processor. Each of these components may be in communication with one another (e.g., via one or more buses).

(148) The receiver **1110** may provide a means for obtaining (e.g., receiving, determining, identifying) information such as user data, control information, or any combination thereof (e.g., I/Q samples, symbols, packets, protocol data units, service data units) associated with various channels (e.g., control channels, data channels, information channels, channels associated with a protocol stack). Information may be passed on to other components of the device **1105**. In some aspects, the receiver **1110** may support obtaining information by receiving signals via one or more antennas. Additionally, or alternatively, the receiver **1110** may support obtaining information by receiving signals via one or more wired (e.g., electrical, fiber optic) interfaces, wireless interfaces, or any combination thereof.

(149) The transmitter **1115** may provide a means for outputting (e.g., transmitting, providing, conveying, sending) information generated by other components of the device **1105**. For example, the transmitter **1115** may output information such as user data, control information, or any combination thereof (e.g., I/Q samples, symbols, packets, protocol data units, service data units) associated with various channels (e.g., control channels, data channels, information channels, channels associated with a protocol stack). In some aspects, the transmitter **1115** may support outputting information by transmitting signals via one or more antennas. Additionally, or alternatively, the transmitter **1115** may support outputting information by transmitting signals via one or more wired (e.g., electrical, fiber optic) interfaces, wireless interfaces, or any combination thereof. In some aspects, the transmitter **1115** and the receiver **1110** may be co-located in a transceiver, which may include or be coupled with a modem.

(150) The communications manager **1120**, the receiver **1110**, the transmitter **1115**, or various combinations thereof or various components thereof may be examples of means for performing various aspects of scheduled cell identification for multi-cell scheduling as described herein. For example, the communications manager **1120**, the receiver **1110**, the transmitter **1115**, or various combinations or components thereof may support a method for performing one or more of the

functions described herein.

(151) In some aspects, the communications manager **1120**, the receiver **1110**, the transmitter **1115**, or various combinations or components thereof may be implemented in hardware (e.g., in communications management circuitry). The hardware may include a processor, a DSP, a CPU, an ASIC, an FPGA or other programmable logic device, a microcontroller, discrete gate or transistor logic, discrete hardware components, or any combination thereof configured as or otherwise supporting a means for performing the functions described in the present disclosure. In some aspects, a processor and memory coupled with the processor may be configured to perform one or more of the functions described herein (e.g., by executing, by the processor, instructions stored in the memory).

(152) Additionally, or alternatively, in some aspects, the communications manager **1120**, the receiver **1110**, the transmitter **1115**, or various combinations or components thereof may be implemented in code (e.g., as communications management software or firmware) executed by a processor. If implemented in code executed by a processor, the functions of the communications manager **1120**, the receiver **1110**, the transmitter **1115**, or various combinations or components thereof may be performed by a general-purpose processor, a DSP, a CPU, an ASIC, an FPGA, a microcontroller, or any combination of these or other programmable logic devices (e.g., configured as or otherwise supporting a means for performing the functions described in the present disclosure).

(153) In some aspects, the communications manager **1120** may be configured to perform various operations (e.g., receiving, obtaining, monitoring, outputting, transmitting) using or otherwise in cooperation with the receiver **1110**, the transmitter **1115**, or both. For example, the communications manager **1120** may receive information from the receiver **1110**, send information to the transmitter **1115**, or be integrated in combination with the receiver **1110**, the transmitter **1115**, or both to obtain information, output information, or perform various other operations as described herein.

(154) The communications manager **1120** may support wireless communications at a first network node in accordance with examples as disclosed herein. For example, the communications manager **1120** may be configured as or otherwise support a means for transmitting, to a second network node, control signaling including an indication of a respective DCI payload size for each subset of scheduled cells of a set of scheduled cells, where the set of scheduled cells are associated with a scheduling cell, and where the control signaling further includes an indication of a respective set of CCEs for each subset of scheduled cells. The communications manager **1120** may be configured as or otherwise support a means for determining, based on first comparison information corresponding to the respective DCI payload sizes and second comparison information corresponding to the respective sets of CCEs, a DCI format for a downlink control channel monitoring occasion in the scheduling cell, where the DCI format is associated with a subset of scheduled cells of the set of scheduled cells, where the DCI format includes an absence or a presence of an indication of the subset of scheduled cells. The communications manager **1120** may be configured as or otherwise support a means for transmitting, via the downlink control channel monitoring occasion, a DCI in accordance with the determined DCI format.

(155) By including or configuring the communications manager **1120** in accordance with examples as described herein, the device **1105** (e.g., a processor controlling or otherwise coupled with the receiver **1110**, the transmitter **1115**, the communications manager **1120**, or a combination thereof) may support techniques for more efficient utilization of communication resources.

(156) FIG. **12** shows a block diagram **1200** of a device **1205** that supports scheduled cell identification for multi-cell scheduling in accordance with one or more aspects of the present disclosure. The device **1205** may be an example of aspects of a device **1105** or a network entity **105** as described herein. The device **1205** may include a receiver **1210**, a transmitter **1215**, and a communications manager **1220**. The device **1205** may also include a processor. Each of these components may be in communication with one another (e.g., via one or more buses).

(157) The receiver **1210** may provide a means for obtaining (e.g., receiving, determining, identifying) information such as user data, control information, or any combination thereof (e.g., I/Q samples, symbols, packets, protocol data units, service data units) associated with various channels (e.g., control channels, data channels, information channels, channels associated with a protocol stack). Information may be passed on to other components of the device **1205**. In some aspects, the receiver **1210** may support obtaining information by receiving signals via one or more antennas. Additionally, or alternatively, the receiver **1210** may support obtaining information by receiving signals via one or more wired (e.g., electrical, fiber optic) interfaces, wireless interfaces, or any combination thereof.

(158) The transmitter **1215** may provide a means for outputting (e.g., transmitting, providing, conveying, sending) information generated by other components of the device **1205**. For example, the transmitter **1215** may output information such as user data, control information, or any combination thereof (e.g., I/Q samples, symbols, packets, protocol data units, service data units) associated with various channels (e.g., control channels, data channels, information channels, channels associated with a protocol stack). In some aspects, the transmitter **1215** may support outputting information by transmitting signals via one or more antennas. Additionally, or alternatively, the transmitter **1215** may support outputting information by transmitting signals via one or more wired (e.g., electrical, fiber optic) interfaces, wireless interfaces, or any combination thereof. In some aspects, the transmitter **1215** and the receiver **1210** may be co-located in a transceiver, which may include or be coupled with a modem.

(159) The device **1205**, or various components thereof, may be an example of means for performing various aspects of scheduled cell identification for multi-cell scheduling as described herein. For example, the communications manager **1220** may include a scheduled cell manager **1225**, a DCI format manager **1230**, a DCI manager **1235**, or any combination thereof. The communications manager **1220** may be an example of aspects of a communications manager **1120** as described herein. In some aspects, the communications manager **1220**, or various components thereof, may be configured to perform various operations (e.g., receiving, obtaining, monitoring, outputting, transmitting) using or otherwise in cooperation with the receiver **1210**, the transmitter **1215**, or both. For example, the communications manager **1220** may receive information from the receiver **1210**, send information to the transmitter **1215**, or be integrated in combination with the receiver **1210**, the transmitter **1215**, or both to obtain information, output information, or perform various other operations as described herein.

(160) The communications manager **1220** may support wireless communications at a first network node in accordance with examples as disclosed herein. The scheduled cell manager **1225** may be configured as or otherwise support a means for transmitting, to a second network node, control signaling including an indication of a respective DCI payload size for each subset of scheduled cells of a set of scheduled cells, where the set of scheduled cells are associated with a scheduling cell, and where the control signaling further includes an indication of a respective set of CCEs for each subset of scheduled cells. The DCI format manager **1230** may be configured as or otherwise support a means for determining, based on first comparison information corresponding to the respective DCI payload sizes and second comparison information corresponding to the respective sets of CCEs, a DCI format for a downlink control channel monitoring occasion in the scheduling cell, where the DCI format is associated with a subset of scheduled cells of the set of scheduled cells, where the DCI format includes an absence or a presence of an indication of the subset of scheduled cells. The DCI manager **1235** may be configured as or otherwise support a means for transmitting, via the downlink control channel monitoring occasion, a DCI in accordance with the determined DCI format.

(161) FIG. **13** shows a block diagram **1300** of a communications manager **1320** that supports scheduled cell identification for multi-cell scheduling in accordance with one or more aspects of the present disclosure. The communications manager **1320** may be an example of aspects of a

communications manager **1120**, a communications manager **1220**, or both, as described herein. The communications manager **1320**, or various components thereof, may be an example of means for performing various aspects of scheduled cell identification for multi-cell scheduling as described herein. For example, the communications manager **1320** may include a scheduled cell manager **1325**, a DCI format manager **1330**, a DCI manager **1335**, a downlink control channel manager **1340**, a DCI payload size manager **1345**, a DCI CCE manager **1350**, a scheduled cell indication manager **1355**, a rule-based scheduled cell manager **1360**, a network identifier manager **1365**, or any combination thereof. Each of these components may communicate, directly or indirectly, with one another (e.g., via one or more buses) which may include communications within a protocol layer of a protocol stack, communications associated with a logical channel of a protocol stack (e.g., between protocol layers of a protocol stack, within a device, component, or virtualized component associated with a network entity **105**, between devices, components, or virtualized components associated with a network entity **105**), or any combination thereof.

(162) The communications manager **1320** may support wireless communications at a first network node in accordance with examples as disclosed herein. The scheduled cell manager **1325** may be configured as or otherwise support a means for transmitting, to a second network node, control signaling including an indication of a respective DCI payload size for each subset of scheduled cells of a set of scheduled cells, where the set of scheduled cells are associated with a scheduling cell, and where the control signaling further includes an indication of a respective set of CCEs for each subset of scheduled cells. The DCI format manager **1330** may be configured as or otherwise support a means for determining, based on first comparison information corresponding to the respective DCI payload sizes and second comparison information corresponding to the respective sets of CCEs, a DCI format for a downlink control channel monitoring occasion in the scheduling cell, where the DCI format is associated with a subset of scheduled cells of the set of scheduled cells, where the DCI format includes an absence or a presence of an indication of the subset of scheduled cells. The DCI manager **1335** may be configured as or otherwise support a means for transmitting, via the downlink control channel monitoring occasion, a DCI in accordance with the determined DCI format.

(163) In some aspects, to support determining the DCI format, the downlink control channel manager **1340** may be configured as or otherwise support a means for determining the DCI format based on the third comparison information.

(164) In some aspects, to support determining the DCI format, the DCI payload size manager **1345** may be configured as or otherwise support a means for determining the DCI format based on a payload size for the downlink control channel monitoring occasion that matches a respective DCI payload size of the subset of scheduled cells.

(165) In some aspects, to support determining the DCI format, the DCI CCE manager **1350** may be configured as or otherwise support a means for determining the DCI format based on a set of CCEs for the downlink control channel monitoring occasion that matches a respective set of CCEs for the subset of scheduled cells.

(166) In some aspects, the scheduled cell indication manager **1355** may be configured as or otherwise support a means for determining, based on the first comparison information being indicative that at least two respective DCI payload sizes for at least two subsets of scheduled cells are equal and further based on the second comparison information being indicative that respective sets of CCEs for the at least two subsets of scheduled cells are equal, that the DCI includes the presence of the indication of the subset of scheduled cells, where the indication of the subset of scheduled cells includes an explicit indication of the subset of scheduled cells.

(167) In some aspects, the rule-based scheduled cell manager **1360** may be configured as or otherwise support a means for determining, based on the first comparison information being indicative that at least two respective DCI payload sizes for at least two subsets of scheduled cells are equal and further based on the second comparison information being indicative that respective

sets of CCEs for the at least two subsets of scheduled cells are equal, that the DCI includes the presence of the indication of the subset of scheduled cells, where the indication of the subset of scheduled cells includes a rule-based indication of the subset of scheduled cells.

(168) In some aspects, the rule-based indication includes information indicative of a rule to select the subset of scheduled cells of the set of scheduled cells based on one of a component carrier index associated with one or more scheduled cells within the subset of scheduled cells, a subcarrier spacing associated with one or more scheduled cells within the subset of scheduled cells, the subset of scheduled cells including a primary cell for the first network node, the subset of scheduled cells including the scheduling cell, or a number of cells associated with the subset of scheduled cells.

(169) In some aspects, the network identifier manager **1365** may be configured as or otherwise support a means for determining, based on the first comparison information being indicative that at least two respective DCI payload sizes for at least two subsets of scheduled cells are equal and further based on the second comparison information being indicative that respective sets of CCEs for the at least two subsets of scheduled cells are equal, that the DCI includes the presence of the indication of the subset of scheduled cells, where the indication of the subset of scheduled cells includes a radio network identifier used to scramble a CRC of the downlink control channel monitoring occasion.

(170) In some aspects, the control signaling further includes an indication of an association between respective radio network identifiers and each subset of scheduled cells.

(171) In some aspects, DCI includes scheduling information for one or more communications with the subset of scheduled cells.

(172) In some aspects, the control signaling further includes an indication of a respective carrier indicator associated with each scheduled cell of the set of scheduled cells. In some aspects, a determination of the scheduling information is based on the indication of the respective carrier indicator associated with each scheduled cell of the set of scheduled cells.

(173) In some aspects, the DCI payload size manager **1345** may be configured as or otherwise support a means for comparing the respective DCI payload sizes. In some aspects, the DCI payload size manager **1345** may be configured as or otherwise support a means for generating the first comparison information based on the comparison of the respective DCI payload sizes.

(174) In some aspects, the DCI CCE manager **1350** may be configured as or otherwise support a means for comparing the respective sets of CCEs. In some aspects, the DCI CCE manager **1350** may be configured as or otherwise support a means for generating the second comparison information based on the comparison of the respective sets of CCEs.

(175) FIG. **14** shows a diagram of a system **1400** including a device **1405** that supports scheduled cell identification for multi-cell scheduling in accordance with one or more aspects of the present disclosure. The device **1405** may be an example of or include the components of a device **1105**, a device **1205**, or a network entity **105** as described herein. The device **1405** may communicate with one or more network entities **105**, one or more UEs **115**, or any combination thereof, which may include communications over one or more wired interfaces, over one or more wireless interfaces, or any combination thereof. The device **1405** may include components that support outputting and obtaining communications, such as a communications manager **1420**, a transceiver **1410**, an antenna **1415**, a memory **1425**, code **1430**, and a processor **1435**. These components may be in electronic communication or otherwise coupled (e.g., operatively, communicatively, functionally, electronically, electrically) via one or more buses (e.g., a bus **1440**).

(176) The transceiver **1410** may support bi-directional communications via wired links, wireless links, or both as described herein. In some aspects, the transceiver **1410** may include a wired transceiver and may communicate bi-directionally with another wired transceiver. Additionally, or alternatively, in some aspects, the transceiver **1410** may include a wireless transceiver and may communicate bi-directionally with another wireless transceiver. In some aspects, the device **1405** may include one or more antennas **1415**, which may be capable of transmitting or receiving

wireless transmissions (e.g., concurrently). The transceiver **1410** may also include a modem to modulate signals, to provide the modulated signals for transmission (e.g., by one or more antennas **1415**, by a wired transmitter), to receive modulated signals (e.g., from one or more antennas **1415**, from a wired receiver), and to demodulate signals. In some implementations, the transceiver **1410** may include one or more interfaces, such as one or more interfaces coupled with the one or more antennas **1415** that are configured to support various receiving or obtaining operations, or one or more interfaces coupled with the one or more antennas **1415** that are configured to support various transmitting or outputting operations, or a combination thereof. In some implementations, the transceiver **1410** may include or be configured for coupling with one or more processors or memory components that are operable to perform or support operations based on received or obtained information or signals, or to generate information or other signals for transmission or other outputting, or any combination thereof. In some implementations, the transceiver **1410**, or the transceiver **1410** and the one or more antennas **1415**, or the transceiver **1410** and the one or more antennas **1415** and one or more processors or memory components (for example, the processor **1435**, or the memory **1425**, or both), may be included in a chip or chip assembly that is installed in the device **1405**. In some aspects, the transceiver may be operable to support communications via one or more communications links (e.g., a communication link **125**, a backhaul communication link **120**, a midhaul communication link **162**, a fronthaul communication link **168**).

(177) The memory **1425** may include RAM and ROM. The memory **1425** may store computer-readable, computer-executable code **1430** including instructions that, when executed by the processor **1435**, cause the device **1405** to perform various functions described herein. The code **1430** may be stored in a non-transitory computer-readable medium such as system memory or another type of memory. In some cases, the code **1430** may not be directly executable by the processor **1435** but may cause a computer (e.g., when compiled and executed) to perform functions described herein. In some cases, the memory **1425** may contain, among other things, a BIOS which may control basic hardware or software operation such as the interaction with peripheral components or devices.

(178) The processor **1435** may include an intelligent hardware device (e.g., a general-purpose processor, a DSP, an ASIC, a CPU, an FPGA, a microcontroller, a programmable logic device, discrete gate or transistor logic, a discrete hardware component, or any combination thereof). In some cases, the processor **1435** may be configured to operate a memory array using a memory controller. In some other cases, a memory controller may be integrated into the processor **1435**. The processor **1435** may be configured to execute computer-readable instructions stored in a memory (e.g., the memory **1425**) to cause the device **1405** to perform various functions (e.g., functions or tasks supporting scheduled cell identification for multi-cell scheduling). For example, the device **1405** or a component of the device **1405** may include a processor **1435** and memory **1425** coupled with the processor **1435**, the processor **1435** and memory **1425** configured to perform various functions described herein. The processor **1435** may be an example of a cloud-computing platform (e.g., one or more physical nodes and supporting software such as operating systems, virtual machines, or container instances) that may host the functions (e.g., by executing code **1430**) to perform the functions of the device **1405**. The processor **1435** may be any one or more suitable processors capable of executing scripts or instructions of one or more software programs stored in the device **1405** (such as within the memory **1425**). In some implementations, the processor **1435** may be a component of a processing system. A processing system may generally refer to a system or series of machines or components that receives inputs and processes the inputs to produce a set of outputs (which may be passed to other systems or components of, for example, the device **1405**). For example, a processing system of the device **1405** may refer to a system including the various other components or subcomponents of the device **1405**, such as the processor **1435**, or the transceiver **1410**, or the communications manager **1420**, or other components or combinations of components of the device **1405**. The processing system of the device **1405** may interface with other

components of the device **1405**, and may process information received from other components (such as inputs or signals) or output information to other components. For example, a chip or modem of the device **1405** may include a processing system and one or more interfaces to output information, or to obtain information, or both. The one or more interfaces may be implemented as or otherwise include a first interface configured to output information and a second interface configured to obtain information, or a same interface configured to output information and to obtain information, among other implementations. In some implementations, the one or more interfaces may refer to an interface between the processing system of the chip or modem and a transmitter, such that the device **1405** may transmit information output from the chip or modem. Additionally, or alternatively, in some implementations, the one or more interfaces may refer to an interface between the processing system of the chip or modem and a receiver, such that the device **1405** may obtain information or signal inputs, and the information may be passed to the processing system. A person having ordinary skill in the art will readily recognize that a first interface also may obtain information or signal inputs, and a second interface also may output information or signal outputs.

(179) In some aspects, a bus **1440** may support communications of (e.g., within) a protocol layer of a protocol stack. In some aspects, a bus **1440** may support communications associated with a logical channel of a protocol stack (e.g., between protocol layers of a protocol stack), which may include communications performed within a component of the device **1405**, or between different components of the device **1405** that may be co-located or located in different locations (e.g., where the device **1405** may refer to a system in which one or more of the communications manager **1420**, the transceiver **1410**, the memory **1425**, the code **1430**, and the processor **1435** may be located in one of the different components or divided between different components).

(180) In some aspects, the communications manager **1420** may manage aspects of communications with a core network **130** (e.g., via one or more wired or wireless backhaul links). For example, the communications manager **1420** may manage the transfer of data communications for client devices, such as one or more UEs **115**. In some aspects, the communications manager **1420** may manage communications with other network entities **105**, and may include a controller or scheduler for controlling communications with UEs **115** in cooperation with other network entities **105**. In some aspects, the communications manager **1420** may support an X2 interface within an LTE/LTE-A wireless communications network technology to provide communication between network entities **105**.

(181) The communications manager **1420** may support wireless communications at a first network node in accordance with examples as disclosed herein. For example, the communications manager **1420** may be configured as or otherwise support a means for transmitting, to a second network node, control signaling including an indication of a respective DCI payload size for each subset of scheduled cells of a set of scheduled cells, where the set of scheduled cells are associated with a scheduling cell, and where the control signaling further includes an indication of a respective set of CCEs for each subset of scheduled cells. The communications manager **1420** may be configured as or otherwise support a means for determining, based on first comparison information corresponding to the respective DCI payload sizes and second comparison information corresponding to the respective sets of CCEs, a DCI format for a downlink control channel monitoring occasion in the scheduling cell, where the DCI format is associated with a subset of scheduled cells of the set of scheduled cells, where the DCI format includes an absence or a presence of an indication of the subset of scheduled cells. The communications manager **1420** may be configured as or otherwise support a means for transmitting, via the downlink control channel monitoring occasion, a DCI in accordance with the determined DCI format.

(182) By including or configuring the communications manager **1420** in accordance with examples as described herein, the device **1405** may support techniques for more efficient utilization of communication resources.

(183) In some aspects, the communications manager **1420** may be configured to perform various operations (e.g., receiving, obtaining, monitoring, outputting, transmitting) using or otherwise in cooperation with the transceiver **1410**, the one or more antennas **1415** (e.g., where applicable), or any combination thereof. Although the communications manager **1420** is illustrated as a separate component, in some aspects, one or more functions described with reference to the communications manager **1420** may be supported by or performed by the transceiver **1410**, the processor **1435**, the memory **1425**, the code **1430**, or any combination thereof. For example, the code **1430** may include instructions executable by the processor **1435** to cause the device **1405** to perform various aspects of scheduled cell identification for multi-cell scheduling as described herein, or the processor **1435** and the memory **1425** may be otherwise configured to perform or support such operations.

(184) FIG. **15** shows a flowchart illustrating a method **1500** that supports scheduled cell identification for multi-cell scheduling in accordance with one or more aspects of the present disclosure. The operations of the method **1500** may be implemented by a UE or its components as described herein. For example, the operations of the method **1500** may be performed by a UE **115** as described with reference to FIGS. **1** through **10**. In some aspects, a UE may execute a set of instructions to control the functional elements of the UE to perform the described functions. Additionally, or alternatively, the UE may perform aspects of the described functions using special-purpose hardware.

(185) At **1505**, the method may include receiving control signaling including an indication of a respective DCI payload size for each subset of scheduled cells of a set of scheduled cells, where the set of scheduled cells are associated with a scheduling cell, and where the control signaling further includes an indication of a respective set of CCEs for each subset of scheduled cells. The operations of **1505** may be performed in accordance with examples as disclosed herein. In some aspects, aspects of the operations of **1505** may be performed by a scheduled cell manager **925** as described with reference to FIG. **9**.

(186) At **1510**, the method may include determining, based on first comparison information corresponding to the respective DCI payload sizes and second comparison information corresponding to the respective sets of CCEs, a DCI format for a downlink control channel monitoring occasion in the scheduling cell, where the DCI format is associated with a subset of scheduled cells of the set of scheduled cells, where the DCI format includes an absence or a presence of an indication of the subset of scheduled cells. The operations of **1510** may be performed in accordance with examples as disclosed herein. In some aspects, aspects of the operations of **1510** may be performed by a DCI format manager **930** as described with reference to FIG. **9**.

(187) At **1515**, the method may include receiving, via the downlink control channel monitoring occasion, DCI in accordance with the determined DCI format. The operations of **1515** may be performed in accordance with examples as disclosed herein. In some aspects, aspects of the operations of **1515** may be performed by a DCI manager **935** as described with reference to FIG. **9**.

(188) FIG. **16** shows a flowchart illustrating a method **1600** that supports scheduled cell identification for multi-cell scheduling in accordance with one or more aspects of the present disclosure. The operations of the method **1600** may be implemented by a network entity or its components as described herein. For example, the operations of the method **1600** may be performed by a network entity as described with reference to FIGS. **1** through **6** and **11** through **14**. In some aspects, a network entity may execute a set of instructions to control the functional elements of the network entity to perform the described functions. Additionally, or alternatively, the network entity may perform aspects of the described functions using special-purpose hardware.

(189) At **1605**, the method may include transmitting, to a second network node, control signaling including an indication of a respective DCI payload size for each subset of scheduled cells of a set of scheduled cells, where the set of scheduled cells are associated with a scheduling cell, and where

the control signaling further includes an indication of a respective set of CCEs for each subset of scheduled cells. The operations of **1605** may be performed in accordance with examples as disclosed herein. In some aspects, aspects of the operations of **1605** may be performed by a scheduled cell manager **1325** as described with reference to FIG. **13**.

(190) At **1610**, the method may include determining, based on first comparison information corresponding to the respective DCI payload sizes and second comparison information corresponding to the respective sets of CCEs, a DCI format for a downlink control channel monitoring occasion in the scheduling cell, where the DCI format is associated with a subset of scheduled cells of the set of scheduled cells, where the DCI format includes an absence or a presence of an indication of the subset of scheduled cells. The operations of **1610** may be performed in accordance with examples as disclosed herein. In some aspects, aspects of the operations of **1610** may be performed by a DCI format manager **1330** as described with reference to FIG. **13**.

(191) At **1615**, the method may include transmitting, via the downlink control channel monitoring occasion, a DCI in accordance with the determined DCI format. The operations of **1615** may be performed in accordance with examples as disclosed herein. In some aspects, aspects of the operations of **1615** may be performed by a DCI manager **1335** as described with reference to FIG. **13**. The following provides an overview of aspects of the present disclosure:

(192) Aspect 1: A method for wireless communications at a first network node, comprising: receiving control signaling including an indication of a respective DCI payload size for each subset of scheduled cells of a set of scheduled cells, wherein the set of scheduled cells are associated with a scheduling cell, and wherein the control signaling further includes an indication of a respective set of CCEs for each subset of scheduled cells; determining, based on first comparison information corresponding to the respective DCI payload sizes and second comparison information corresponding to the respective sets of CCEs, a DCI format for a downlink control channel monitoring occasion in the scheduling cell, wherein the DCI format is associated with a subset of scheduled cells of the set of scheduled cells, wherein the DCI format includes an absence or a presence of an indication of the subset of scheduled cells; and receiving, via the downlink control channel monitoring occasion, DCI in accordance with the determined DCI format.

(193) Aspect 2: The method of aspect 1, wherein the control signaling further includes an indication of a respective set of downlink control channels for each subset of scheduled cells, wherein third comparison information corresponds to the respective sets of downlink control channels, and wherein determining the DCI format comprises: determining the DCI format based on the third comparison information.

(194) Aspect 3: The method of any of aspects 1 through 2, wherein the first comparison information is indicative that each respective DCI payload size for each subset of scheduled cells is different, wherein determining the DCI format comprises: determining the DCI format based on a payload size for the downlink control channel monitoring occasion that matches a respective DCI payload size of the subset scheduled cells.

(195) Aspect 4: The method of any of aspects 1 through 3, wherein the second comparison information is indicative that each respective set of CCEs for each subset of scheduled cells is different, and wherein determining the DCI format comprises: determining the DCI format based on a set of CCEs for the downlink control channel monitoring occasion that matches a respective set of CCEs for the subset of scheduled cells.

(196) Aspect 5: The method of any of aspects 1 through 2, further comprising: determining, based on the first comparison information being indicative that at least two respective DCI payload sizes for at least two subsets of scheduled cells are equal and further based on the second comparison information being indicative that respective sets of CCEs for the at least two subsets of scheduled cells are equal, that the DCI includes the presence of the indication of the subset of scheduled cells, wherein the indication of the subset of scheduled cells comprises an explicit indication of the

subset of scheduled cells.

(197) Aspect 6: The method of any of aspects 1 through 2, further comprising: determining, based on the first comparison information being indicative that at least two respective DCI payload sizes for at least two subsets of scheduled cells are equal and further based on the second comparison information being indicative that respective sets of CCEs for the at least two subsets of scheduled cells are equal, that the DCI includes the presence of the indication of the subset of scheduled cells, wherein the indication of the subset of scheduled cells comprises a rule-based indication of the subset of scheduled cells.

(198) Aspect 7: The method of aspect 6, wherein the rule-based indication comprises information indicative of a rule to select the subset of scheduled cells of the set of scheduled cells based on one of a component carrier index associated with one or more scheduled cells within the subset of scheduled cells, a subcarrier spacing associated with one or more scheduled cells within the subset of scheduled cells, the subset of scheduled cells including a primary cell for the first network node, the subset of scheduled cells including the scheduling cell, or a number of cells associated with the subset of scheduled cells.

(199) Aspect 8: The method of any of aspects 1 through 2, further comprising: determining, based on the first comparison information being indicative that at least two respective DCI payload sizes for at least two subsets of scheduled cells are equal and further based on the second comparison information being indicative that respective sets of CCEs for the at least two subsets of scheduled cells are equal, that the DCI includes the presence of the indication of the subset of scheduled cells, wherein the indication of the subset of scheduled cells comprises a radio network identifier used to scramble a cyclic redundancy check of the downlink control channel monitoring occasion.

(200) Aspect 9: The method of aspect 8, wherein the control signaling further includes an indication of an association between respective radio network identifiers and each subset of scheduled cells.

(201) Aspect 10: The method of any of aspects 1 through 9, wherein DCI includes scheduling information for one or more communications with the subset of scheduled cells.

(202) Aspect 11: The method of aspect 10, wherein the control signaling further includes an indication of a respective carrier indicator associated with each scheduled cell of the set of scheduled cells, and a determination of the scheduling information is based on the indication of the respective carrier indicator associated with each scheduled cell of the set of scheduled cells.

(203) Aspect 12: The method of any of aspects 1 through 11, further comprising: comparing the respective DCI payload sizes; and generating the first comparison information based on the comparison of the respective DCI payload sizes.

(204) Aspect 13: The method of any of aspects 1 through 12, further comprising: comparing the respective sets of CCEs; and generating the second comparison information based on the comparison of the respective sets of CCEs.

(205) Aspect 14: A method for wireless communications at a first network node, comprising: transmitting, to a second network node, control signaling including an indication of a respective DCI payload size for each subset of scheduled cells of a set of scheduled cells, wherein the set of scheduled cells are associated with a scheduling cell, and wherein the control signaling further includes an indication of a respective set of CCEs for each subset of scheduled cells; determining, based on first comparison information corresponding to the respective DCI payload sizes and second comparison information corresponding to the respective sets of CCEs, a DCI format for a downlink control channel monitoring occasion in the scheduling cell, wherein the DCI format is associated with a subset of scheduled cells of the set of scheduled cells, wherein the downlink control channel format includes an absence or a presence of an indication of the subset of scheduled cells; and transmitting, via the downlink control channel monitoring occasion, a DCI in accordance with the determined DCI format.

(206) Aspect 15: The method of aspect 14, wherein the control signaling further includes an

indication of a respective set of downlink control channels for each subset of scheduled cells, wherein third comparison information corresponds to the respective sets of downlink control channels, and wherein determining the DCI format comprises: determining the DCI format based on the third comparison information.

(207) Aspect 16: The method of any of aspects 14 through 15, wherein the first comparison information is indicative that each respective DCI payload size for each subset of scheduled cells is different, wherein determining the DCI format comprises: determining the DCI format based on a payload size for the downlink control channel monitoring occasion that matches a respective DCI payload size of the subset scheduled cells.

(208) Aspect 17: The method of any of aspects 14 through 16, wherein the second comparison information is indicative that each respective set of CCEs for each subset of scheduled cells is different, and wherein determining the DCI format comprises: determining the DCI format based on a set of CCEs for the downlink control channel monitoring occasion that matches a respective set of CCEs for the subset of scheduled cells.

(209) Aspect 18: The method of any of aspects 14 through 15, further comprising: determining, based on the first comparison information being indicative that at least two respective DCI payload sizes for at least two subsets of scheduled cells are equal and further based on the second comparison information being indicative that respective sets of CCEs for the at least two subsets of scheduled cells are equal, that the DCI includes the presence of the indication of the subset of scheduled cells, wherein the indication of the subset of scheduled cells comprises an explicit indication of the subset of scheduled cells.

(210) Aspect 19: The method of any of aspects 14 through 15, further comprising: determining, based on the first comparison information being indicative that at least two respective DCI payload sizes for at least two subsets of scheduled cells are equal and further based on the second comparison information being indicative that respective sets of CCEs for the at least two subsets of scheduled cells are equal, that the DCI includes the presence of the indication of the subset of scheduled cells, wherein the indication of the subset of scheduled cells comprises a rule-based indication of the subset of scheduled cells.

(211) Aspect 20: The method of aspect 19, wherein the rule-based indication comprises information indicative of a rule to select the subset of scheduled cells of the set of scheduled cells based on one of a component carrier index associated with one or more scheduled cells within the subset of scheduled cells, a subcarrier spacing associated with one or more scheduled cells within the subset of scheduled cells, the subset of scheduled cells including a primary cell for the first network node, the subset of scheduled cells including the scheduling cell, or a number of cells associated with the subset of scheduled cells.

(212) Aspect 21: The method of any of aspects 14 through 15, further comprising: determining, based on the first comparison information being indicative that at least two respective DCI payload sizes for at least two subsets of scheduled cells are equal and further based on the second comparison information being indicative that respective sets of CCEs for the at least two subsets of scheduled cells are equal, that the DCI includes the presence of the indication of the subset of scheduled cells, wherein the indication of the subset of scheduled cells comprises a radio network identifier used to scramble a cyclic redundancy check of the downlink control channel monitoring occasion.

(213) Aspect 22: The method of aspect 21, wherein the control signaling further includes an indication of an association between respective radio network identifiers and each subset of scheduled cells.

(214) Aspect 23: The method of any of aspects 14 through 22, wherein DCI includes scheduling information for one or more communications with the subset of scheduled cells.

(215) Aspect 24: The method of aspect 23, wherein the control signaling further includes an indication of a respective carrier indicator associated with each scheduled cell of the set of

scheduled cells, and a determination of the scheduling information is based on the indication of the respective carrier indicator associated with each scheduled cell of the set of scheduled cells.

(216) Aspect 25: The method of any of aspects 14 through 24, further comprising: comparing the respective DCI payload sizes; and generating the first comparison information based on the comparison of the respective DCI payload sizes.

(217) Aspect 26: The method of any of aspects 14 through 25, further comprising: comparing the respective sets of CCEs; and generating the second comparison information based on the comparison of the respective sets of CCEs.

(218) Aspect 27: A first network node for wireless communication, comprising: a memory; and at least one processor coupled to the memory, wherein the at least one processor is configured to: perform a method of any of aspects 1 through 13.

(219) Aspect 28: An apparatus for wireless communications at a first network node, comprising at least one means for performing a method of any of aspects 1 through 13.

(220) Aspect 29: A non-transitory computer-readable medium having code for wireless communication stored thereon that, when executed by a network node, causes the network node to perform a method of any of aspects 1 through 13.

(221) Aspect 30: A first network node for wireless communication, comprising: a memory; and at least one processor coupled to the memory, wherein the at least one processor is configured to: perform a method of any of aspects 14 through 26.

(222) Aspect 31: An apparatus for wireless communications at a first network node, comprising at least one means for performing a method of any of aspects 14 through 26.

(223) Aspect 32: A non-transitory computer-readable medium having code for wireless communication stored thereon that, when executed by a network node, causes the network node to perform a method of any of aspects 14 through 26.

(224) The methods described herein describe possible implementations, the operations and the steps may be rearranged or otherwise modified, and other implementations are possible. Further, aspects from two or more of the methods may be combined.

(225) Although aspects of an LTE, LTE-A, LTE-A Pro, or NR system may be described for purposes of example, and LTE, LTE-A, LTE-A Pro, or NR terminology may be used in much of the description, the techniques described herein are applicable beyond LTE, LTE-A, LTE-A Pro, or NR networks. For example, the described techniques may be applicable to various other wireless communications systems such as Ultra Mobile Broadband (UMB), Institute of Electrical and Electronics Engineers (IEEE) 802.11 (Wi-Fi), IEEE 802.16 (WiMAX), IEEE 802.20, Flash-OFDM, as well as other systems and radio technologies not explicitly mentioned herein.

(226) Information and signals described herein may be represented using any of a variety of different technologies and techniques. For example, data, instructions, commands, information, signals, bits, symbols, and chips that may be referenced throughout the description may be represented by voltages, currents, electromagnetic waves, magnetic fields or particles, optical fields or particles, or any combination thereof.

(227) The various illustrative blocks and components described in connection with the disclosure herein may be implemented or performed using a general-purpose processor, a DSP, an ASIC, a CPU, an FPGA or other programmable logic device, discrete gate or transistor logic, discrete hardware components, or any combination thereof designed to perform the functions described herein. A general-purpose processor may be a microprocessor but, in the alternative, the processor may be any processor, controller, microcontroller, or state machine. A processor may also be implemented as a combination of computing devices (e.g., a combination of a DSP and a microprocessor, multiple microprocessors, one or more microprocessors in conjunction with a DSP core, or any other such configuration).

(228) The functions described herein may be implemented using hardware, software executed by a processor, firmware, or any combination thereof. If implemented using software executed by a

processor, the functions may be stored as or transmitted using one or more instructions or code of a computer-readable medium. Other examples and implementations are within the scope of the disclosure and claims. For example, due to the nature of software, functions described herein may be implemented using software executed by a processor, hardware, firmware, hardwiring, or combinations of any of these. Features implementing functions may also be physically located at various positions, including being distributed such that portions of functions are implemented at different physical locations.

(229) Computer-readable media includes both non-transitory computer storage media and communication media including any medium that facilitates transfer of a computer program from one location to another. A non-transitory storage medium may be any available medium that may be accessed by a general-purpose or special-purpose computer. By way of example, and not limitation, non-transitory computer-readable media may include RAM, ROM, electrically erasable programmable ROM (EEPROM), flash memory, compact disk (CD) ROM or other optical disk storage, magnetic disk storage or other magnetic storage devices, or any other non-transitory medium that may be used to carry or store desired program code means in the form of instructions or data structures and that may be accessed by a general-purpose or special-purpose computer, or a general-purpose or special-purpose processor. Also, any connection is properly termed a computer-readable medium. For example, if the software is transmitted from a website, server, or other remote source using a coaxial cable, fiber optic cable, twisted pair, digital subscriber line (DSL), or wireless technologies such as infrared, radio, and microwave, then the coaxial cable, fiber optic cable, twisted pair, DSL, or wireless technologies such as infrared, radio, and microwave are included in the definition of computer-readable medium. Disk and disc, as used herein, include CD, laser disc, optical disc, digital versatile disc (DVD), floppy disk and Blu-ray disc. Disks may reproduce data magnetically, and discs may reproduce data optically using lasers. Combinations of the above are also included within the scope of computer-readable media.

(230) As used herein, the term “or” is an inclusive “or” unless limiting language is used relative to the alternatives listed. For example, reference to “X being based on A or B” shall be construed as including within its scope X being based on A, X being based on B, and X being based on A and B. In this regard, reference to “X being based on A or B” refers to “at least one of A or B” or “one or more of A or B” due to “or” being inclusive. Similarly, reference to “X being based on A, B, or C” shall be construed as including within its scope X being based on A, X being based on B, X being based on C, X being based on A and B, X being based on A and C, X being based on B and C, and X being based on A, B, and C. In this regard, reference to “X being based on A, B, or C” refers to “at least one of A, B, or C” or “one or more of A, B, or C” due to “or” being inclusive. As an example of limiting language, reference to “X being based on only one of A or B” shall be construed as including within its scope X being based on A as well as X being based on B, but not X being based on A and B. Also, as used herein, the phrase “based on” shall not be construed as a reference to a closed set of information, one or more conditions, one or more factors, or the like. In other words, the phrase “based on A” (where “A” may be information, a condition, a factor, or the like) shall be construed as “based at least on A” unless specifically recited differently. Also, as used herein, the phrase “a set” shall be construed as including the possibility of a set with one member. That is, the phrase “a set” shall be construed in the same manner as “one or more” or “at least one of.”

(231) The term “determine” or “determining” encompasses a variety of actions and, therefore, “determining” can include calculating, computing, processing, deriving, investigating, looking up (such as via looking up in a table, a database or another data structure), ascertaining and the like. Also, “determining” can include receiving (e.g., receiving information), accessing (e.g., accessing data stored in memory) and the like. Also, “determining” can include resolving, obtaining, selecting, choosing, establishing, and other such similar actions.

(232) In the figures, similar components or features may have the same reference label. Further,

various components of the same type may be distinguished by following the reference label by a dash and a second label that distinguishes among the similar components. If just the first reference label is used in the specification, the description is applicable to any one of the similar components having the same first reference label irrespective of the second reference label, or other subsequent reference label.

(233) The description set forth herein, in connection with the drawings, describes example configurations and does not represent all the examples that may be implemented or that are within the scope of the claims. The term “aspect” or “example” used herein means “serving as an aspect, example, instance, or illustration,” and not “preferred” or “advantageous over other aspects.” The detailed description includes specific details for the purpose of providing an understanding of the described techniques. These techniques, however, may be practiced without these specific details. In some instances, structures and devices are shown in block diagram form in order to avoid obscuring the concepts of the described examples.

(234) The description herein is provided to enable a person having ordinary skill in the art to make or use the disclosure. Various modifications to the disclosure will be apparent to a person having ordinary skill in the art, and the generic principles defined herein may be applied to other variations without departing from the scope of the disclosure. Thus, the disclosure is not limited to the examples and designs described herein but is to be accorded the broadest scope consistent with the principles and novel features disclosed herein.

Claims

1. A first network node for wireless communication, comprising: a memory; and at least one processor coupled to the memory, wherein the at least one processor is configured to: receive control signaling including an indication of a respective downlink control information payload size for each subset of scheduled cells of a set of scheduled cells, wherein the set of scheduled cells are associated with a scheduling cell, and wherein the control signaling further includes an indication of a respective set of control channel elements for each subset of scheduled cells; determine, based on first comparison information corresponding to the respective downlink control information payload sizes and second comparison information corresponding to the respective sets of control channel elements, a downlink control information format for a downlink control channel monitoring occasion in the scheduling cell, wherein the downlink control information format is associated with a subset of scheduled cells of the set of scheduled cells, wherein the downlink control information format includes an absence or a presence of an indication of the subset of scheduled cells; and receive, via the downlink control channel monitoring occasion, downlink control information in accordance with the determined downlink control information format.
2. The first network node of claim 1, wherein the control signaling further includes an indication of a respective set of downlink control channels for each subset of scheduled cells, wherein third comparison information corresponds to the respective sets of downlink control channels, and wherein, to determine the downlink control information format, the at least one processor is configured to: determine the downlink control information format based on the third comparison information.
3. The first network node of claim 1, wherein the first comparison information is indicative that each respective downlink control information payload size for each subset of scheduled cells is different, wherein, to determine the downlink control information format, the at least one processor is configured to: determine the downlink control information format based on a payload size for the downlink control channel monitoring occasion that matches a respective downlink control information payload size of the subset of scheduled cells.
4. The first network node of claim 1, wherein the second comparison information is indicative that each respective set of control channel elements for each subset of scheduled cells is different,

wherein, to determine the downlink control information format, the at least one processor is configured to: determine the downlink control information format based on a set of control channel elements for the downlink control channel monitoring occasion that matches a respective set of control channel elements for the subset of scheduled cells.

5. The first network node of claim 1, wherein the first comparison information is indicative that at least two respective downlink control information payload sizes for at least two subsets of scheduled cells are equal, wherein the second comparison information is indicative that respective sets of control channel elements for the at least two subsets of scheduled cells are equal, and wherein the at least one processor is configured to: determine, based on the first comparison information being indicative that the at least two respective downlink control information payload sizes are equal and the second comparison information being indicative that the respective sets of control channel elements are equal, that the downlink control information includes the presence of the indication of the subset of scheduled cells, wherein the indication of the subset of scheduled cells comprises an explicit indication of the subset of scheduled cells.

6. The first network node of claim 1, wherein the first comparison information is indicative that at least two respective downlink control information payload sizes for at least two subsets of scheduled cells are equal, wherein the second comparison information is indicative that respective sets of control channel elements for the at least two subsets of scheduled cells are equal, and wherein the at least one processor is configured to: determine, based on the first comparison information being indicative that the at least two respective downlink control information payload sizes are equal and the second comparison information being indicative that the respective sets of control channel elements are equal, that the downlink control information includes the presence of the indication of the subset of scheduled cells, wherein the indication of the subset of scheduled cells comprises a rule-based indication of the subset of scheduled cells.

7. The first network node of claim 6, wherein the rule-based indication comprises information indicative of a rule to select the subset of scheduled cells of the set of scheduled cells based on one of a component carrier index associated with one or more scheduled cells within the subset of scheduled cells, a subcarrier spacing associated with one or more scheduled cells within the subset of scheduled cells, the subset of scheduled cells including a primary cell for the first network node, the subset of scheduled cells including the scheduling cell, or a number of cells associated with the subset of scheduled cells.

8. The first network node of claim 1, wherein the first comparison information is indicative that at least two respective downlink control information payload sizes for at least two subsets of scheduled cells are equal, wherein the second comparison information is indicative that respective sets of control channel elements for the at least two subsets of scheduled cells are equal, and wherein the at least one processor is configured to: determine, based on the first comparison information being indicative that the at least two respective downlink control information payload sizes are equal and the second comparison information being indicative that the respective sets of control channel elements are equal, that the downlink control information includes the presence of the indication of the subset of scheduled cells, wherein the indication of the subset of scheduled cells comprises a radio network identifier used to scramble a cyclic redundancy check of the downlink control channel monitoring occasion.

9. The first network node of claim 8, wherein the control signaling further includes an indication of an association between respective radio network identifiers and each subset of scheduled cells.

10. The first network node of claim 1, wherein the downlink control information includes scheduling information for one or more communications with the subset of scheduled cells.

11. The first network node of claim 10, wherein the control signaling further includes an indication of a respective carrier indicator associated with each scheduled cell of the set of scheduled cells, and wherein a determination of the scheduling information is based on the indication of the respective carrier indicator associated with each scheduled cell of the set of scheduled cells.

12. The first network node of claim 1, wherein the at least one processor is configured to: compare the respective downlink control information payload sizes; and generate the first comparison information based on the comparison of the respective downlink control information payload sizes.

13. The first network node of claim 1, wherein the at least one processor is configured to: compare the respective sets of control channel elements; and generate the second comparison information based on the comparison of the respective sets of control channel elements.

14. A first network node for wireless communication, comprising: a memory; and at least one processor coupled to the memory, wherein the at least one processor is configured to: transmit, to a second network node, control signaling including an indication of a respective downlink control information payload size for each subset of scheduled cells of a set of scheduled cells, wherein the set of scheduled cells are associated with a scheduling cell, and wherein the control signaling further includes an indication of a respective set of control channel elements for each subset of scheduled cells; determine, based on first comparison information corresponding to the respective downlink control information payload sizes and second comparison information corresponding to the respective sets of control channel elements, a downlink control information format for a downlink control channel monitoring occasion in the scheduling cell, wherein the downlink control information format is associated with a subset of scheduled cells of the set of scheduled cells, wherein the downlink control information format includes an absence or a presence of an indication of the subset of scheduled cells; and transmit, via the downlink control channel monitoring occasion, a downlink control information in accordance with the determined downlink control information format.

15. The first network node of claim 14, wherein the control signaling further includes an indication of a respective set of downlink control channels for each subset of scheduled cells, wherein third comparison information corresponds to the respective sets of downlink control channels, and wherein, to determine the downlink control information format, the at least one processor is configured to: determine the downlink control information format based on the third comparison information.

16. The first network node of claim 14, wherein the first comparison information is indicative that each respective downlink control information payload size for each subset of scheduled cells is different, wherein to determine the downlink control information format, the at least one processor is configured to: determine the downlink control information format based on a payload size for the downlink control channel monitoring occasion that matches a respective downlink control information payload size of the subset of scheduled cells.

17. The first network node of claim 14, wherein the second comparison information is indicative that each respective set of control channel elements for each subset of scheduled cells is different, wherein to determine the downlink control information format, the at least one processor is configured to: determine is based on a set of control channel elements for the downlink control channel monitoring occasion that matches a respective set of control channel elements for the subset of scheduled cells.

18. The first network node of claim 14, wherein the first comparison information is indicative that at least two respective downlink control information payload sizes for at least two subsets of scheduled cells are equal, wherein the second comparison information is indicative that respective sets of control channel elements for the at least two subsets of scheduled cells are equal, and wherein the at least one processor is configured to: determine, based on the first comparison information being indicative that the at least two respective downlink control information payload sizes are equal and the second comparison information being indicative that the respective sets of control channel elements are equal, that the downlink control information includes the presence of the indication of the subset of scheduled cells, wherein the indication of the subset of scheduled cells comprises an explicit indication of the subset of scheduled cells.

19. The first network node of claim 14, wherein the first comparison information is indicative that

at least two respective downlink control information payload sizes for at least two subsets of scheduled cells are equal, wherein the second comparison information is indicative that respective sets of control channel elements for the at least two subsets of scheduled cells are equal, and wherein the at least one processor is configured to: determine, based on the first comparison information being indicative that the at least two respective downlink control information payload sizes are equal and the second comparison information being indicative that the respective sets of control channel elements are equal, that the downlink control information includes the presence of the indication of the subset of scheduled cells, wherein the indication of the subset of scheduled cells comprises a rule-based indication of the subset of scheduled cells.

20. The first network node of claim 19, wherein the rule-based indication comprises information indicative of a rule to select the subset of scheduled cells of the set of scheduled cells based on one of a component carrier index associated with one or more scheduled cells within the subset of scheduled cells, a subcarrier spacing associated with one or more scheduled cells within the subset of scheduled cells, the subset of scheduled cells including a primary cell for the first network node, the subset of scheduled cells including the scheduling cell, or a number of cells associated with the subset of scheduled cells.

21. The first network node of claim 14, wherein the first comparison information is indicative that at least two respective downlink control information payload sizes for at least two subsets of scheduled cells are equal, wherein the second comparison information is indicative that respective sets of control channel elements for the at least two subsets of scheduled cells are equal, and wherein the at least one processor is configured to: determine, based on the first comparison information being indicative that the at least two respective downlink control information payload sizes are equal and the second comparison information being indicative that the respective sets of control channel elements are equal, that the downlink control information includes the presence of the indication of the subset of scheduled cells, wherein the indication of the subset of scheduled cells comprises a radio network identifier used to scramble a cyclic redundancy check of the downlink control channel monitoring occasion.

22. The first network node of claim 21, wherein the control signaling further includes an indication of an association between respective radio network identifiers and each subset of scheduled cells.

23. The first network node of claim 14, wherein the downlink control information includes scheduling information for one or more communications between the second network node and the subset of scheduled cells.

24. The first network node of claim 23, wherein the control signaling further includes an indication of a respective carrier indicator associated with each scheduled cell of the set of scheduled cells, and wherein a determination of the scheduling information is based on the indication of the respective carrier indicator associated with each scheduled cell of the set of scheduled cells.

25. The first network node of claim 14, wherein the at least one processor is configured to: compare the respective downlink control information payload sizes; and generate the first comparison information based on the comparison of the respective downlink control information payload sizes.

26. The first network node of claim 14, wherein the at least one processor is configured to: compare the respective sets of control channel elements; and generate the second comparison information based on the comparison of the respective sets of control channel elements.

27. A method for wireless communications at a first network node, comprising: receiving control signaling including an indication of a respective downlink control information payload size for each subset of scheduled cells of a set of scheduled cells, wherein the set of scheduled cells are associated with a scheduling cell, and wherein the control signaling further includes an indication of a respective set of control channel elements for each subset of scheduled cells; determining, based on first comparison information corresponding to the respective downlink control information payload sizes and second comparison information corresponding to the respective sets

of control channel elements, a downlink control information format for a downlink control channel monitoring occasion in the scheduling cell, wherein the downlink control information format is associated with a subset of scheduled cells of the set of scheduled cells, wherein the downlink control information format includes an absence or a presence of an indication of the subset of scheduled cells; and receiving, via the downlink control channel monitoring occasion, downlink control information in accordance with the determined downlink control information format.

28. The method of claim 27, wherein the control signaling further includes an indication of a respective set of downlink control channels for each subset of scheduled cells, wherein third comparison information corresponds to the respective sets of downlink control channels, and wherein determining the downlink control information format comprises: determining the downlink control information format based on the third comparison information.

29. The method of claim 27, wherein the first comparison information is indicative that each respective downlink control information payload size for each subset of scheduled cells is different, wherein determining the downlink control information format comprises: determining the downlink control information format based on a payload size for the downlink control channel monitoring occasion that matches a respective downlink control information payload size of the subset of scheduled cells.

30. A method for wireless communications at a first network node, comprising: transmitting, to a second network node, control signaling including an indication of a respective downlink control information payload size for each subset of scheduled cells of a set of scheduled cells, wherein the set of scheduled cells are associated with a scheduling cell, and wherein the control signaling further includes an indication of a respective set of control channel elements for each subset of scheduled cells; determining, based on first comparison information corresponding to the respective downlink control information payload sizes and second comparison information corresponding to the respective sets of control channel elements, a downlink control information format for a downlink control channel monitoring occasion in the scheduling cell, wherein the downlink control information format is associated with a subset of scheduled cells of the set of scheduled cells, wherein the downlink control information format includes an absence or a presence of an indication of the subset of scheduled cells; and transmitting, via the downlink control channel monitoring occasion, a downlink control information in accordance with the determined downlink control information format.
