

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12416942
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Rothkopf; Fletcher R. et al.

Bi-stable spring with flexible display

Abstract

A wearable accessory device is disclosed. The wearable accessory device includes a flexible display coupled to a bi-stable spring. Coupling the display to the bi-stable spring allows the accessory device to be easily worn in a number of convenient locations.

Inventors: Rothkopf; Fletcher R. (Los Altos, CA), Wright; Derek W. (San Francisco, CA), Myers; Scott A. (Saratoga, CA)

Applicant: Apple Inc. (Cupertino, CA)

Family ID: 1000008822169

Appl. No.: 18/778128

Filed: July 19, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240370053 A1	Nov. 07, 2024

Related U.S. Application Data

continuation parent-doc US 17670002 20220211 US 12079033 child-doc US 18778128
continuation parent-doc US 14869867 20150929 US 11275406 20220315 child-doc US 17670002
continuation parent-doc US 13212045 20110817 US 9176530 20151103 child-doc US 14869867

Publication Classification

Int. Cl.: G06F1/16 (20060101); G06F3/041 (20060101); G06F3/0488 (20220101); H04N7/18 (20060101)

U.S. Cl.:

CPC **G06F1/163** (20130101); **G06F1/1635** (20130101); **G06F1/1643** (20130101);
G06F1/1652 (20130101); **G06F1/1698** (20130101); **G06F3/041** (20130101);
G06F3/0488 (20130101); **H04N7/18** (20130101);

Field of Classification Search

CPC: G06F (1/163); G06F (1/1635); G06F (1/1643); G06F (1/1652); G06F (1/1698); G06F
(3/041); G06F (3/0488); H04N (7/18)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5931764	12/1998	Freeman et al.	N/A	N/A
6728166	12/2003	Grupp	N/A	N/A
7618260	12/2008	Daniel et al.	N/A	N/A
8089605	12/2011	Nagata et al.	N/A	N/A
8477464	12/2012	Visser et al.	N/A	N/A
8982051	12/2014	Rosenfeld et al.	N/A	N/A
9100493	12/2014	Zhou et al.	N/A	N/A
2001/0043513	12/2000	Grupp	N/A	N/A
2003/0026171	12/2002	Brewer et al.	N/A	N/A
2003/0066308	12/2002	Radley-Smith	N/A	N/A
2003/0201999	12/2002	Lin et al.	N/A	N/A
2003/0214481	12/2002	Xiong	N/A	N/A
2004/0262179	12/2003	Gartrell et al.	N/A	N/A
2005/0174302	12/2004	Ishii	N/A	N/A
2005/0285963	12/2004	Misawa et al.	N/A	N/A
2006/0061555	12/2005	Mullen	N/A	N/A
2006/0121963	12/2005	Gartrell et al.	N/A	N/A
2007/0158376	12/2006	Radley-Smith	N/A	N/A
2007/0247439	12/2006	Daniel	345/173	G06F 1/1694
2008/0166519	12/2007	Leung	N/A	N/A
2008/0258917	12/2007	Boyd et al.	N/A	N/A
2008/0273040	12/2007	Dryer et al.	N/A	N/A
2008/0291225	12/2007	Arneson	N/A	N/A
2008/0309640	12/2007	Hong	N/A	N/A
2008/0310094	12/2007	Burns	N/A	N/A
2009/0122036	12/2008	Miles	N/A	N/A
2009/0132093	12/2008	Arneson et al.	N/A	N/A
2009/0251888	12/2008	Douglas	N/A	N/A
2010/0097561	12/2009	Nagata et al.	N/A	N/A
2010/0117972	12/2009	Zhao et al.	N/A	N/A
2010/0117975	12/2009	Cho	N/A	N/A
2010/0134503	12/2009	Sampsell et al.	N/A	N/A
2010/0164888	12/2009	Okumura et al.	N/A	N/A
2010/0208417	12/2009	Visser et al.	N/A	N/A
2010/0242274	12/2009	Rosenfeld et al.	N/A	N/A
2010/0245246	12/2009	Rosenfeld et al.	N/A	N/A

2010/0302179	12/2009	Ahn et al.	N/A	N/A
2010/0317409	12/2009	Jiang et al.	N/A	N/A
2011/0007042	12/2010	Miyaguchi	N/A	N/A
2011/0037907	12/2010	Miles	N/A	N/A
2011/0043431	12/2010	Reinhold et al.	N/A	N/A
2011/0054565	12/2010	Wacnik et al.	N/A	N/A
2011/0109567	12/2010	Kim	N/A	N/A
2011/0134145	12/2010	Moriwaki	N/A	N/A
2011/0148797	12/2010	Huitema et al.	N/A	N/A
2011/0183722	12/2010	Vartanian	N/A	N/A
2011/0187681	12/2010	Kim et al.	N/A	N/A
2011/0199389	12/2010	Lu et al.	N/A	N/A
2011/0215934	12/2010	Boyd et al.	N/A	N/A
2011/0227822	12/2010	Shai	345/156	G06F 1/1647
2011/0227855	12/2010	Kim et al.	N/A	N/A
2011/0252606	12/2010	Rothbaum et al.	N/A	N/A
2011/0261002	12/2010	Verthein	N/A	N/A
2011/0262055	12/2010	De Haan et al.	N/A	N/A
2011/0265564	12/2010	Acar et al.	N/A	N/A
2011/0265565	12/2010	Acar et al.	N/A	N/A
2011/0265566	12/2010	Acar et al.	N/A	N/A
2011/0298750	12/2010	Wang et al.	N/A	N/A
2012/0069232	12/2011	Chui et al.	N/A	N/A
2012/0115422	12/2011	Tziortzis et al.	N/A	N/A
2012/0242588	12/2011	Myers et al.	N/A	N/A
2012/0242592	12/2011	Rothkopf et al.	N/A	N/A
2012/0243151	12/2011	Lynch	N/A	N/A
2012/0314400	12/2011	Bohn et al.	N/A	N/A
2012/0314546	12/2011	Brewer et al.	N/A	N/A
2015/0229750	12/2014	Zhou et al.	N/A	N/A
2016/0147261	12/2015	Bohn et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2248473	12/1999	CA	G02C 7/02
101782804	12/2009	CN	G06F 1/163
102782637	12/2011	CN	H04M 1/72469
0689122	12/1994	EP	G06F 3/0338
1158375	12/2000	EP	N/A
1010037	12/2002	EP	N/A
2294937	12/2010	EP	N/A
2005250442	12/2004	JP	N/A
00/25193	12/1999	WO	N/A
2001088636	12/2000	WO	N/A
2008085818	12/2007	WO	N/A

Primary Examiner: Li; Tracy Y.

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. patent application Ser. No. 17/670,002, filed Feb. 11, 2022, which is a continuation of U.S. patent application Ser. No. 14/869,867, filed Sep. 29, 2015, now U.S. Pat. No. 11,275,406, which is a continuation of U.S. patent application Ser. No. 13/212,045, filed Aug. 17, 2011, now U.S. Pat. No. 9,176,530, which are hereby incorporated by reference herein in their entireties.

FIELD

(1) The described embodiments relate generally to portable electronic devices. In particular methods for expanding the functionality of electronic devices are disclosed.

RELATED ART

(2) Bi-stable springs have two equilibrium positions. This allows a device with a bi-stable spring to assume two distinct configurations. The most recent widespread use of such a device was the slap bracelet, also called the slap wrap. The slap bracelet consists of layered flexible steel bands sealed within a fabric cover. Typical slap bracelets are roughly one inch in width by nine inches in length. In a first equilibrium position they can be flat. The second equilibrium is typically reached by slapping the flat embodiment across the wrist, at which point the bracelet curls around the wrist and stays relatively secure in a roughly circular position. The slap bracelet has been used primarily as a decorative bracelet; however, other uses have included for example keeping a pant leg away from a bike chain, or even using a slap bracelet covered with reflective tape for providing increased visibility for pedestrians and bikers at night. Perhaps most usefully it is quite easy to wrap around a wrist or leg, and stays conveniently in place.

(3) Conversely conventional accessories for electronic devices do not tend to be easily wearable. They include various clips or may even rest precariously on an ear. In some cases accessory devices may even have to sit in a pant or coat pocket. Therefore an apparatus that capitalizes on the easily wearable nature of a bi-stable spring is desired.

SUMMARY

(4) This paper describes various embodiments that relate to an apparatus, method, and apparatus with a display and associated electronics.

(5) A wearable video device arranged to be worn by an end-user is disclosed. The wearable video device includes the following: (1) a flexible substrate having a flat state and a curled state; and (2) a flexible display disposed upon a first surface of the flexible substrate, where in the curled state the flexible substrate conforms to an appendage of the end-user. The flexible substrate also includes an electronic module in communication with the flexible display, the electronic module providing information to the display, at least a part of which is presented in real time for presentation by the display.

(6) A method for passing information between an accessory device disposed on one surface of a bi-stable spring substrate and a portable electronic device is disclosed. The accessory device includes a flexible display arranged to present a first set of visual information. The portable electronic device has a portable electronic device display arranged to present a second set of visual information. The method includes the following steps: (1) determining whether the accessory device is being worn by an end-user where the determining is accomplished by at least one sensor on the accessory device; (2) when it determined the accessory device is being worn by the end user, establishing a communication channel between the accessory device and the portable electronic device where the communication channel is arranged to provide a bi-directional communication link between the flexible display and the portable electronic device; (3) passing information between the portable electronic device and the accessory device by way of the bi-directional communication link, where at least a portion of the passed information is presented by the flexible

display as the first set of visual information; and (4) displaying the first set of visual information by the flexible display.

(7) A slap bracelet configured to display information wirelessly transmitted from a portable electronic device is disclosed. The slap bracelet includes at least the following components: (1) a communication link, allowing two-way communication between the slap bracelet and the portable electronic device; (2) a flexible display disposed over a portion of a first surface of the slap bracelet; (3) a touch sensitive user interface disposed over the top of the flexible display; and (4) an electronic module disposed on one end of the first surface of the slap bracelet. Information generated on either device can be displayed on either the host device display or the flexible display.

(8) A non-transitory computer readable medium for storing computer instructions executed by a processor in a portable electronic device for controlling a flexible accessory device mounted on a bi-stable spring substrate in wireless communication with the portable electronic device is disclosed. The non-transitory computer readable medium includes the following: computer code for establishing a communication channel between the flexible accessory device and the portable electronic device; computer code for receiving a user input on a first user interface built into the portable electronic device; computer code for interpreting the user input with the portable electronic device processor; computer code for sending display data across the communication channel; and computer code for displaying the display data on a flexible accessory device display.

(9) Other aspects and advantages of the invention will become apparent from the following detailed description taken in conjunction with the accompanying drawings which illustrate, by way of example, the principles of the described embodiments.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The described embodiments and the advantages thereof may best be understood by reference to the following description taken in conjunction with the accompanying drawings. These drawings in no way limit any changes in form and detail that may be made to the described embodiments by one skilled in the art without departing from the spirit and scope of the described embodiments.

(2) FIG. 1 shows a conventional slap bracelet with a flexible display fastened to one surface.

(3) FIGS. 2A and 2B show cross sectional views of an accessory device in accordance with the described embodiments.

(4) FIGS. 3A and 3B show perspective views of an accessory device in accordance with the described embodiments.

(5) FIGS. 4A and 4B show cross sectional views of an accessory device with an edge to edge flexible display in accordance with the described embodiments.

(6) FIGS. 5A and 5B show perspective views of an accessory device with an edge to edge flexible display in accordance with the described embodiments.

(7) FIG. 5C shows a cross sectional view of an accessory device with an end detection sensor in accordance with the described embodiments.

(8) FIGS. 6A and 6B show an accessory device with ambient light energy collectors disposed on an outer surface of the accessory device, in accordance with the described embodiments.

(9) FIGS. 7A and 7B show an alternative embodiment in which the electronic module is rigid.

(10) FIG. 8 shows a flow chart describing input on an accessory device which affects the operation of a host device.

(11) FIG. 9 shows a block diagram of an arrangement of functional modules utilized by an electronic device.

(12) FIG. 10 shows a block diagram of an electronic device suitable for use with the described embodiments.

DETAILED DESCRIPTION

(13) Representative applications of methods and apparatus according to the present application are described in this section. These examples are being provided solely to add context and aid in the understanding of the described embodiments. It will thus be apparent to one skilled in the art that the described embodiments may be practiced without some or all of these specific details. In other instances, well known process steps have not been described in detail in order to avoid unnecessarily obscuring the described embodiments. Other applications are possible, such that the following examples should not be taken as limiting.

(14) In the following detailed description, references are made to the accompanying drawings, which form a part of the description and in which are shown, by way of illustration, specific embodiments in accordance with the described embodiments. Although these embodiments are described in sufficient detail to enable one skilled in the art to practice the described embodiments, it is understood that these examples are not limiting; such that other embodiments may be used, and changes may be made without departing from the spirit and scope of the described embodiments.

(15) Accessories for portable computing devices have become quite common. Today typical portable electronic device accessories are passive in nature, the majority of which simply function to protect the screen, or perhaps support the device in some specific orientation. Although some devices such as Bluetooth headsets and keyboards do have limited interactive capability the majority of accessories are limited to more basic tasks. These accessories can be improved by including at least some of the following features: (1) a power source; (2) a communications protocol; (3) an input method; and (4) an independent storage medium.

(16) An accessory that takes a more active interaction role with the portable computing device would also typically need a power source to drive it. In some embodiments, a battery can be incorporated within the body of the accessory. The battery can take many forms. For example, the battery can be distributed in nature by which it is meant that portions of the battery can be placed in disparate locations in the accessory. In another example, the battery can be replaceable or otherwise accessible by the user. The operating time of a built in battery can be augmented by the addition of an auxiliary power supply such as a solar panel array to the accessory. A solar panel array spread across a surface of the accessory device can lengthen the amount of time the accessory device could be operated between recharging. A battery can also allow for the accessory device to continue nominal operations after the portable electronic device has been turned off or a communications channel between the two devices has been secured, especially with the inclusion of a small amount of storage space. For example, a simple screen saver could be displayed with an accessory device that includes a display. In another embodiment a short document or email could be reviewed. Other sources of power could include a kinetic power source similar to those found on some wristwatches. An accessory device designed to be worn on a leg or arm could greatly benefit from this sort of power generation, and could lengthen the amount of time between charging.

(17) Active communication between an accessory and a portable electronic device can be accomplished wirelessly. For example, a wireless data connection such as the 5 GHz 802.11n protocol can provide sufficient data transmission bandwidth to transmit a high quality video stream. The wireless protocol allows for robust communication between the two devices. The accessory device could also connect to the portable electronic device via Bluetooth. While it might not carry the same amount of data it may be preferable for situations in which only small amounts of data are being sent back and forth.

(18) In the simplest embodiment of the described embodiments a flexible display can be added to a conventionally designed slap bracelet, with the addition of a battery and a minimal number of electronic components. In FIG. 1 a cross section of a conventional slap bracelet **100** with an overlaid display is shown. A thin steel bi-stable spring **102** is covered by fabric covering **104**. The spring steel making up the bi-stable spring should be at least 0.006 inches thick. Fabric covering **104** is heat sealed around bi-stable spring **102** at sealing positions **106**. A thin, flexible display **108**

can then be overlaid with an adhesive on one surface of the slap bracelet. A printed circuit board with the aforementioned electronics (not shown) could be mounted at one end of slap bracelet **100**, so that the other end of the slap bracelet could completely cover the electronics module while a user wears it. Although mounting the described embodiments to a slap bracelet with a bi-stable spring does allow a convenient attachment method, it should be noted that the described embodiments could be mounted on any flexible substrate. For example a fabric substrate could be used that simply included snaps or velcro in order to secure itself around a human appendage.

(19) One problem with the design of the conventionally designed slap bracelet was that the fabric covering would occasionally separate at the heat sealed portions. Since the described embodiment will house valuable electronics, a manufacturer can create a more robust design. FIG. 2A shows a cross sectional view of a robust accessory device **200** in which flexible display **108** is adhered directly to one side of bi-stable spring **102**. Fabric covering **104** can then wrap all the way around the edge of bi-stable spring **102**, and provide a robust frame for flexible display **108**. It should be noted that although fabric similar to the conventional slap bracelet can be used, a thicker more cushioned fabric can also be utilized to increase user comfort. FIG. 2B shows another cross sectional view of accessory device **200**. In this view flexible electronic module **202** is depicted at one end of accessory device **200**, adhered directly to the surface of bi-stable spring **102** at one end of accessory device **200**. Since the cross section of a slap bracelet switches from convex to concave upon changing states it is important to note that the flexible electronic module **202** must contain components that are flexible in nature and resistant to fatigue. Flexible electronic module **202** can include a flexible printed circuit board with at least one wireless communications antenna, integrated circuits for driving the display, along with data and power connectors.

(20) With the aforementioned devices housed within flexible electronic module **202** a communication channel can be established and maintained with a portable electronic device. The portable electronic device and bi-stable spring mounted accessory device can form a cooperative electronic system in which the electronic devices can communicate with each other. This system can be further enhanced by the addition of additional sensors. For example in an accessory configuration which includes a touch screen overlaid on top of flexible display **108**, the end user could respond to alerts sent from the portable electronic device and even direct the operations of the portable electronic device to an extent limited by the accessory device user interface. With a touch screen user input a user can accomplish a number of different tasks including adjusting the order of a current playlist, and reviewing a list of recent phone calls. A response to a current text message can even be managed given a simple virtual keyboard configuration across the face of the flexible display **108**.

(21) FIGS. 3A and 3B show perspective views of both bi-stable spring states of accessory device **300** in accordance with the described embodiments. In FIG. 3A the bi-stable spring is arranged in a flat state. Flexible display **302** is overlaid on the surface of the accessory device with a thin border area **304** securing and protecting the edges of flexible display **302**. Flexible electronic module **306** is also shown located on one end of accessory device **300**. In FIG. 3B accessory device **300** is in a curled state and can be seen wrapped around the arm of a user. Accessory device **300** is wrapped around an arm in a way such that the flexible electronic module **306** is completely obscured by the wrap around flexible display **302**, leaving only a thin border to interrupt an otherwise continuous screen around the wrist. When accessory device **300** switches from the flat state shown in FIG. 3A to assume the curled state shown in FIG. 3B the bi-stable spring switches from a concave shape to a convex shape, bending both flexible display **302** and flexible electronic module **306**. Flexible electronic module **306** can be configured with a strain gauge to determine when changes in state occur. The determining done by the strain gauge allows accessory device **300** to adjust a user interface displayed on flexible display **302** from one layout to another based upon the state of the accessory device. It should also be noted that even though accessory device **300** is shown as a relatively narrow band around a user's wrist, the accessory device could be configured to be much

wider. As the accessory device widens its potential for functionality also increases. At a width of a few inches the display can function to temporarily view and manipulate the screen of the portable electronic device it is in communication with. This might be desirable when the portable electronic device is stored in an inconvenient location such as a cargo pocket, or the bottom of a backpack. A larger display is also more desirable for map viewing. The arm mounted location makes map viewing a desirable function for such a device, as a traveler or explorer can easily reference the information with a flick of the wrist while exploring. A wider overall device width also allows for a larger flexible electronic module **306**. This allows more space for a larger battery, and additional sensors which will be discussed later.

(22) FIGS. **4A** and **4B** show cross sectional views of an edge to edge flexible display **402** integrated into accessory device **400**. In FIG. **4A** flexible display **402** is shown wrapping around the edges of bi-stable spring **404**. Fabric covering **406** covers the bottom of bi-stable spring **404** and also covers the edges of flexible display **402**. Modern flexible display technology can be built particularly robustly and flexible display **402** can withstand repeated stresses put upon it by bi-stable spring **404** and day to day wear. The result is a strong edge to edge screen which has a number of advantages over the previously described embodiment. An increase in screen size is obtained in this configuration. Edge lighting is now also possible. For example a user could configure blue bordered edge lighting to surround the screen. Blinking lights displayed on the edges of the display can act as an event alert to a user that might be more effective since when the display is wrist or arm mounted it is the edge that generally is closest to the user, not the front. In yet another use an accessory device owner riding a bike could mount it on an arm or leg with some kind of bright pattern running along the screen for increased visibility. FIG. **4B** shows a cross sectional view of accessory device **400** showing how flexible display **402** and flexible electronic module **408** are attached to bi-stable spring **404** with an adhesive layer **410**. Also shown is fabric covering **406** which covers flexible electronic module **408** and secures the portion of flexible display **402** which extends over one end of bi-stable spring **404**.

(23) FIGS. **5A**, and **5B** show perspective views of both bi-stable spring states of accessory device **400** in accordance with the described embodiments. FIG. **5A** shows a view of accessory device **400** and how it appears with the edge to edge display described under FIG. **4**. In this flat state the accessory device can also be operated. The flat state has the advantage of showing more of flexible display **402** at once, and therefore might be a preferable state for activities such as parameter initialization or for establishing connections between it and another portable electronic device. The accessory device can contain a sensor which alerts the device as to which state it is in and then changes the user interface to optimize it for that state, as described under FIG. **3B**. Individual elements of flexible electronic module **408** are shown on the surface of flexible electronic module **408** for explanatory purposes. Kinetic energy gathering device **502** is shown on the right side of flexible electronic module **408**. One of the advantages of having the accessory device on an extremity is that it is an ideal location for gathering kinetic energy. The simple motion of a user's arm or leg allows the accessory device to harness some of that energy for charging battery **504**. Antenna **506** is for establishing and maintaining the connection between accessory device **400** and the portable electronic device. The antenna can be configured to pass data over WiFi, Bluetooth or any other suitable wireless protocol. Connector **508** allows accessory device **400** to be connected by wire to another electronic device for activities such as charging, performing firmware updates, or even for reconfiguring the device. Connector **508** can consist of a plug as shown, or could have a small tab that extended from the flexible electronic module for easily plugging into a computer port.

(24) FIG. **5B** shows accessory device **400** in its curled state, attached to a user's wrist. As can be seen the display wraps completely around the wrist in this state creating an uninterrupted screen. One sensor that could be added to the components illustrated is an inertial orientation sensor, such as a gyroscope, or accelerometer (not shown). By including an inertial orientation sensor displayed

information could be arranged so that it always faces up, or directly towards the user. This conveniently allows a user to continue viewing information on the accessory device while maneuvering the extremity it is located on. In a power saving mode the inertial orientation sensor can be configured to only activate the display when the accessory device is rotated into a specific viewing orientation, thereby saving the user the hassle of having to push a button to activate the screen while still allowing for the power savings of a standby mode. In another aspect of the power saving mode the inertial orientation sensor could generate power savings by deactivating portions of the screen oriented away from the user. Because the flexible display technology uses an active matrix light emitting diode (AMOLED) display the deactivation of unused portions of the display helps significantly. This is due to the fact that AMOLED displays can activate individual pixels, and save energy when the number of illuminated pixels is reduced.

(25) One challenge to overcome when making a continuous display that wraps all the way around an arm or leg is that these appendages invariably come in different sizes. FIG. 5C illustrates one solution to this challenge. By including an end-detection sensor on accessory device **400** the location of the end of the accessory device can be known, and the accessory device can properly configure the screen to deactivate covered portion **510** of the screen. In an embodiment with a touch screen sensor the touch screen itself can act as the end detection sensor. Capacitive elements **512** can be added to the end of accessory device **400** as illustrated, and when the touch screen is activate the touch screen can report the location of the capacitive elements and deactivate the covered portion of the screen. In this way the accessory device can be wrapped tightly around the wrist of any size user with no display discontinuity problems. A user can even switch between arm and leg mounting with out having to go through a time consuming recalibration process each time. As referenced in FIG. 5B the resulting deactivated portions have the additional advantage of saving accessory device power.

(26) FIGS. 6A and 6B show a configuration in which ambient light energy collectors replace a portion of the screen. While in the illustrated configurations this precludes a continuous wrap around screen it has the advantage of being able to provide additional power to the accessory device. In fact a device worn on the body is particularly well suited for gathering ambient light energy since it tends to be exposed and frequently oriented towards the sun or other strong light sources. FIG. 6A shows one embodiment where flexible display **602** only wraps around part of the arm. Starting at a rear portion of accessory device **600** a portion of flexible display **602** is replaced by ambient light energy collectors **604**. This configuration uses end detection sensors **606** to deactivate covered portions of flexible display **602** since ambient light energy collectors **604** may cover a portion of flexible display **602**. FIG. 6B shows an alternate embodiment **610** in which ambient light energy collectors **604** are arranged next to flexible electronic module **608**. This configuration prevents ambient light energy collectors **604** from covering any of flexible display **602** in a curled state; however, in a flat state having flexible display **602** separated from flexible electronic module **608** by ambient light energy collectors **604** might not be desirable since in some embodiments flexible electronic module **608** can have physical buttons a user might want to access in conjunction with flexible display **602**. In yet another ambient light energy collector embodiment the ambient light energy collectors can be arranged on one or both edges of flexible display **602**. In this way a continuous display can still be achieved while maintaining the benefit of receiving ambient light energy.

(27) FIG. 7A shows an alternative configuration **700** in which the electronic module is rigid. In FIG. 7A bi-stable spring **702** is shown attached to rigid electronic module **704**. Rigid electronic module **704** can include a slight curve to it as illustrated so that it conforms to a wrist or ankle more easily when in a curled state. Flexible display screen **706** is still adhered to bi-stable spring **702** by adhesive layer **708**. This configuration has a number of advantages over the previously described embodiments. First, by removing electronic module **704** from the bi-stable spring the electronic module can be rigid. A rigid module will generally not be subjected to the same fatigue stresses as a

flexible electronic module would be and the casing can be built a little more solidly as it doesn't have to flex or bend with the bi-stable spring. Second, rigid electronic module **704** can be taller without changing the overall form factor of the device, as it is not stacked on top of the device, and does not curl upwards with the curve of the bi-stable spring. Finally, the circuit board design can be easier as flexible regions need not be designed around when placing components. FIG. 7B shows a perspective view of alternative configuration **700**. The figure shows how one end of bi-stable spring **702** is anchored to rigid electronic module **704** at intersection **710**. In this configuration bi-stable spring **702** can still bend and flex, even though the attached end of bi-stable spring **702** might be somewhat less flexible near the intersection as a result.

(28) FIG. **8** shows flow chart **800** describing input on a flexible wearable communication device which affects the operation of a portable electronic device. In step **802** a flexible, wearable communication device is provided. In step **804** at least one sensor is used to determine if the device is being worn. The strain gauge identified earlier could be used to determine whether the flexible wearable device is in an open or closed state. A pressure sensor can be added to determine if there were any pressure on the inside surface of the flexible wearable communication device, thereby obtaining a good indication of whether or not the device is being worn. Step **806** is reached if the device is being worn in which case a communications link is established between the flexible wearable communication device and the portable electronic device. The communication link can be established through a wireless protocol, and can be established in a single direction or in two ways for fully cooperative interaction between the devices. In step **808** a user interface is presented by the flexible wearable communication device. The user interface could be a virtual keyboard or a specialized control set designed differently for each application. In step **810** a user input is received at the user interface. In step **812** a control signal is passed from the flexible wearable communication device to the portable electronic device. The control signal could operate to store items to the host device, to manipulate the host device display, or to accomplish any other desired change in state of the portable electronic device.

(29) FIG. **9** is a block diagram of an arrangement **900** of functional modules utilized by an electronic device. Arrangement **900** includes an electronic device **902** that is able to output media for a user of the portable media device but also store and retrieve data with respect to data storage **904**. Arrangement **900** also includes a graphical user interface (GUI) manager **906**. The GUI manager **906** operates to control information being provided to and displayed on a display device. Arrangement **900** also includes a communication module **908** that facilitates communication between the portable media device and an accessory device. Still further, arrangement **900** includes an accessory manager **910** that operates to authenticate and acquire data from an accessory device that can be coupled to the portable electronic device.

(30) FIG. **10** is a block diagram of an electronic device **1000** suitable for use with the described embodiments. Electronic device **1000** illustrates circuitry of a representative computing device. Electronic device **1000** includes a processor **1002** that pertains to a microprocessor or controller for controlling the overall operation of the electronic device **1000**. Electronic device **1000** stores media data pertaining to media items in a file system **1004** and a cache **1006**. The file system **1004** is, typically, a storage disk or a plurality of disks. The file system **1004** typically provides high capacity storage capability for the electronic device **1000**. However, since the access time to the file system **1004** is relatively slow, the electronic device **1000** can also include a cache **1006**. The cache **1006** is, for example, Random-Access Memory (RAM) provided by semiconductor memory. The relative access time to the cache **1006** is substantially shorter than for the file system **1004**. However, the cache **1006** does not have the large storage capacity of the file system **1004**. Further, the file system **1004**, when active, consumes more power than does the cache **1006**. The power consumption is often a concern when the electronic device **1000** is a portable media device that is powered by a battery **1008**. The electronic device **1000** can also include RAM **1010** and Read-Only Memory (ROM) **1012**. The ROM **1012** can store programs, utilities or processes to be executed in

a non-volatile manner. The RAM **1010** provides volatile data storage, such as for the cache **1006**. (31) The electronic device **1000** also includes a user input device **1014** that allows a user of the electronic device **1000** to interact with the electronic device **1000**. For example, the user input device **1014** can take a variety of forms, such as a button, keypad, dial, touch screen, audio input interface, visual/image capture input interface, input in the form of sensor data, etc. Still further, the electronic device **1000** includes a display **1016** (screen display) that can be controlled by the processor **1002** to display information to the user. A data bus **1018** can facilitate data transfer between at least the file system **1004**, the cache **1006**, the processor **1002**, and the CODEC **1020**. (32) The various aspects, embodiments, implementations or features of the described embodiments can be used separately or in any combination. Various aspects of the described embodiments can be implemented by software, hardware or a combination of hardware and software. The described embodiments can also be embodied as computer readable code on a computer readable medium for controlling manufacturing operations or as computer readable code on a computer readable medium for controlling a manufacturing line. The computer readable medium is any data storage device that can store data which can thereafter be read by a computer system. Examples of the computer readable medium include read-only memory, random-access memory, CD-ROMs, DVDs, magnetic tape, and optical data storage devices. The computer readable medium can also be distributed over network-coupled computer systems so that the computer readable code is stored and executed in a distributed fashion. (33) The foregoing description, for purposes of explanation, used specific nomenclature to provide a thorough understanding of the described embodiments. However, it will be apparent to one skilled in the art that the specific details are not required in order to practice the described embodiments. Thus, the foregoing descriptions of specific embodiments are presented for purposes of illustration and description. They are not intended to be exhaustive or to limit the described embodiments to the precise forms disclosed. It will be apparent to one of ordinary skill in the art that many modifications and variations are possible in view of the above teachings.

Claims

1. An electronic device, comprising: a housing movable between first and second configurations; a first display portion in the housing that faces and is configured to emit light in a direction when the housing is in the first configuration; and a second display portion in the housing that faces the direction when the housing is in the first and second configurations, wherein the second display portion is covered when the housing is in the first configuration and uncovered when the housing is in the second configuration, wherein the second display portion is configured to be deactivated when covered, and wherein the second display portion is configured to emit light when uncovered.
2. The electronic device defined in claim 1, wherein the first display portion overlaps the second display portion in the first configuration.
3. The electronic device defined in claim 2, wherein the first display portion is non-overlapping with the second display portion in the second configuration.
4. The electronic device defined in claim 1, further comprising: capacitive elements configured to detect that the second display portion is covered in the first configuration.
5. The electronic device defined in claim 1, wherein the second display portion comprises touch sensors and the touch sensors are configured to detect that the second display portion is covered in the first configuration.
6. The electronic device defined in claim 1, wherein the second display portion comprises a flexible display.
7. The electronic device defined in claim 6, wherein the flexible display is touch sensitive.
8. The electronic device defined in claim 6, wherein the flexible display is an organic light-emitting diode display.

9. The electronic device defined in claim 1, wherein the housing comprises a curved housing portion.

10. An electronic device, comprising: a housing bendable between a flat state and a bent state; a first display portion in the housing that faces a first direction when the housing is in the flat state and faces a second direction opposite the first direction when the housing is in the bent state; and a second display portion in the housing that faces the first direction when the housing is in the flat state and the bent state, wherein the second display portion is configured to emit light when the housing is in the flat state, and the second display portion is configured to be deactivated when the housing is in the bent state.

11. The electronic device defined in claim 10, wherein the first display portion is configured to emit light in the first direction when the housing is in the flat state.

12. The electronic device defined in claim 10, wherein the first and second display portions form a continuous display.

13. The electronic device defined in claim 12, wherein the continuous display comprises a flexible display.

14. The electronic device defined in claim 13, wherein the flexible display is touch sensitive.

15. The electronic device defined in claim 14, wherein the flexible display comprises an organic light-emitting diode display.

16. The electronic device defined in claim 13, wherein the flexible display is coupled to the housing with an adhesive.

17. An electronic device, comprising: a housing; a first display portion in the housing that faces a first direction; a second display portion in the housing that faces a second direction opposite the first direction; a third display portion in the housing that faces a third direction different from the second direction; and a sensor that obtains an orientation of the electronic device, wherein the first display portion is configured to emit light when the electronic device has a first orientation, and the second and third display portions are configured to emit light while the first display portion is deactivated when the electronic device has a second orientation different from the first orientation.

18. The electronic device defined in claim 17, wherein the second and third display portions are configured to be deactivated when the electronic device has the first orientation.

19. The electronic device defined in claim 17, wherein the sensor is selected from the group consisting of: a gyroscope and an accelerometer.

20. The electronic device defined in claim 17, wherein the second and third display portions comprise a flexible display.
