

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12417940
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Fitzgerald; Thomas

Vented susceptor

Abstract

A susceptor can include a face that is configured to support a substrate thereon and a plurality of channels extending into the face and radially outwardly relative to a center of the face. One or more of the plurality of channels may include an elongate portion and a flash-out portion. The elongate portion may have a width less than a threshold width along the entirety of the elongate portion. The flash-out portion may be in fluid communication with the elongate portion and may include a first section having a first width and a second section having a second width greater than the first width. The first section may be disposed radially inward of the second section.

Inventors:	Fitzgerald; Thomas (Gilbert, AZ)
Applicant:	ASM IP HOLDING B.V. (Almere, NL)
Family ID:	1000008822240
Assignee:	ASM IP Holding B.V. (Almere, NL)
Appl. No.:	17/354879
Filed:	June 22, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20210398843 A1	Dec. 23, 2021

Related U.S. Application Data

us-provisional-application US 63042974 20200623

Publication Classification

Int. Cl.: H01L21/687 (20060101); C23C16/455 (20060101); C23C16/458 (20060101);
H01L21/67 (20060101)

U.S. Cl.:

CPC H01L21/68785 (20130101); C23C16/4586 (20130101); H01L21/67109 (20130101);
H01L21/68735 (20130101); H01L21/68742 (20130101); C23C16/45544 (20130101)

Field of Classification Search

CPC: C23C (16/45521); C23C (16/45544); C23C (16/4581); C23C (16/4586); C23C (16/466);
H01J (37/32715); H01J (37/32724); H01L (21/67109); H01L (21/68735); H01L
(21/68742); H01L (21/6875); H01L (21/68785)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3407783	12/1967	Capita	N/A	N/A
3549847	12/1969	Clark et al.	N/A	N/A
3641974	12/1971	Yamada et al.	N/A	N/A
4522149	12/1984	Garbis et al.	N/A	N/A
4560420	12/1984	Lord	N/A	N/A
4710428	12/1986	Tamamizu et al.	N/A	N/A
4821674	12/1988	deBoer et al.	N/A	N/A
4958061	12/1989	Wakabayashi et al.	N/A	N/A
4978567	12/1989	Miller	N/A	N/A
4986215	12/1990	Yamada et al.	N/A	N/A
4990374	12/1990	Keeley et al.	N/A	N/A
5033407	12/1990	Mizuno et al.	N/A	N/A
5044943	12/1990	Bowman et al.	N/A	N/A
5098198	12/1991	Nulman et al.	N/A	N/A
5108792	12/1991	Anderson et al.	N/A	N/A
5119540	12/1991	Kong et al.	N/A	N/A
5119541	12/1991	Ohmi et al.	N/A	N/A
5121531	12/1991	Severns et al.	N/A	N/A
5156820	12/1991	Wong et al.	N/A	N/A
5188501	12/1992	Tomita et al.	N/A	N/A
5199483	12/1992	Bahng	N/A	N/A
5200157	12/1992	Toya et al.	N/A	N/A
5242501	12/1992	McDiarmid	N/A	N/A
5292554	12/1993	Sinha et al.	N/A	N/A
5298465	12/1993	Levy	N/A	N/A
5304248	12/1993	Cheng et al.	N/A	N/A
5306699	12/1993	Eddy	N/A	N/A
5308645	12/1993	Zachman et al.	N/A	N/A
5332442	12/1993	Kubodera et al.	N/A	N/A
5343938	12/1993	Schmidt	N/A	N/A

5354715	12/1993	Wang et al.	N/A	N/A
5356486	12/1993	Sugarman et al.	N/A	N/A
5370739	12/1993	Foster et al.	N/A	N/A
5383971	12/1994	Selbrede	N/A	N/A
5393349	12/1994	Ohkase	N/A	N/A
5403401	12/1994	Haafkens et al.	N/A	N/A
5421893	12/1994	Perlov	N/A	N/A
5427620	12/1994	deBoer et al.	N/A	N/A
5444217	12/1994	Moore et al.	N/A	N/A
5455069	12/1994	Lee	N/A	N/A
5456757	12/1994	Aruga et al.	N/A	N/A
5461214	12/1994	Peck et al.	N/A	N/A
5467220	12/1994	Xu	N/A	N/A
5492566	12/1995	Sumnitsch	N/A	N/A
5514439	12/1995	Sibley	N/A	N/A
5527393	12/1995	Sato et al.	N/A	N/A
5549756	12/1995	Sorensen et al.	N/A	N/A
5551985	12/1995	Brors et al.	N/A	N/A
5558717	12/1995	Zhao et al.	N/A	N/A
5584936	12/1995	Pickering et al.	N/A	N/A
5588827	12/1995	Muka	N/A	N/A
5620525	12/1996	van de Vens et al.	N/A	N/A
5645646	12/1996	Beinglass et al.	N/A	N/A
5656093	12/1996	Burkhart et al.	N/A	N/A
5683518	12/1996	Moore et al.	N/A	N/A
5690742	12/1996	Ogata et al.	N/A	N/A
5700725	12/1996	Hower et al.	N/A	N/A
5738165	12/1997	Imai	N/A	N/A
5738751	12/1997	Camerson	118/724	H01L 21/67103
5753132	12/1997	Shamouilian	216/33	H01L 21/6833
5761023	12/1997	Lue et al.	N/A	N/A
5800622	12/1997	Takemi et al.	N/A	N/A
5803977	12/1997	Tepman et al.	N/A	N/A
5810933	12/1997	Mountsier	118/728	H01L 21/67109
5822171	12/1997	Shamouilian	279/128	C23C 16/4586
5834737	12/1997	Hirose et al.	N/A	N/A
D404370	12/1998	Kimura	N/A	N/A
5895530	12/1998	Shrotriya et al.	N/A	N/A
5938850	12/1998	Arami et al.	N/A	N/A
5960159	12/1998	Ikeda et al.	N/A	N/A
6001183	12/1998	Gurary et al.	N/A	N/A
6020212	12/1999	Mathis	N/A	N/A
6077357	12/1999	Rossman et al.	N/A	N/A
6086680	12/1999	Foster et al.	N/A	N/A
6090212	12/1999	Mahawili	N/A	N/A

6093252	12/1999	Wengert et al.	N/A	N/A
6167834	12/2000	Wang et al.	N/A	N/A
6293749	12/2000	Raaijmakers et al.	N/A	N/A
6325858	12/2000	Wengert et al.	N/A	N/A
6343183	12/2001	Halpin et al.	N/A	N/A
6394797	12/2001	Sugaya et al.	N/A	N/A
6402850	12/2001	Beinglass et al.	N/A	N/A
6608287	12/2002	Halpin et al.	N/A	N/A
6634882	12/2002	Goodman	N/A	N/A
6709267	12/2003	Hawkins et al.	N/A	N/A
D496008	12/2003	Takahashi et al.	N/A	N/A
6893507	12/2004	Goodman et al.	N/A	N/A
7033445	12/2005	Keeton et al.	N/A	N/A
D525127	12/2005	Cogley et al.	N/A	N/A
7601224	12/2008	Foree	N/A	N/A
7602224	12/2008	Foree	N/A	N/A
7648579	12/2009	Goodman et al.	N/A	N/A
7705275	12/2009	Umotoy	219/401	C23C 16/466
8088225	12/2011	Goodman et al.	N/A	N/A
8394229	12/2012	Aggarwal et al.	N/A	N/A
8801857	12/2013	Aggarwal et al.	N/A	N/A
9972520	12/2017	Kuo et al.	N/A	N/A
2002/0011211	12/2001	Halpin	N/A	N/A
2002/0043337	12/2001	Goodman	156/345.12	H01L 21/68728
2002/0189940	12/2001	Tsai	118/724	C30B 25/12
2003/0000472	12/2002	Lim et al.	N/A	N/A
2003/0049580	12/2002	Goodman	N/A	N/A
2004/0060512	12/2003	Waldhauer et al.	N/A	N/A
2004/0229002	12/2003	Davis et al.	N/A	N/A
2005/0092439	12/2004	Keeton et al.	N/A	N/A
2005/0284372	12/2004	Murugesh et al.	N/A	N/A
2006/0057826	12/2005	De Boer	N/A	N/A
2009/0014323	12/2008	Yendler	204/298.33	H01J 37/20
2009/0280248	12/2008	Goodman et al.	N/A	N/A
2010/0031884	12/2009	Aggarwal et al.	N/A	N/A
2010/0107974	12/2009	Givens et al.	N/A	N/A
2011/0209660	12/2010	Myo	117/88	C23C 16/4586
2013/0109192	12/2012	Hawkins et al.	N/A	N/A
2015/0232983	12/2014	West et al.	N/A	N/A
2018/0094350	12/2017	Verghese et al.	N/A	N/A
2019/0139807	12/2018	White	N/A	H01L 21/68764
2023/0019718	12/2022	Larosa et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
------------	------------------	---------	-----

0339279	12/1988	EP	N/A
0448346	12/1990	EP	N/A
0445596	12/1990	EP	N/A
0634785	12/1994	EP	N/A
0669640	12/1994	EP	N/A
0766289	12/1996	EP	N/A
0840358	12/1997	EP	N/A
2181458	12/1986	GB	N/A
7-58039	12/1994	JP	N/A
2000-269310	12/1999	JP	N/A
2002-184843	12/2001	JP	N/A
2002-526915	12/2001	JP	N/A
2003-124167	12/2002	JP	N/A
2006-228802	12/2005	JP	N/A
2007-502022	12/2006	JP	N/A
10-1999-0069084	12/1998	KR	N/A
100460338	12/2003	KR	N/A
10-2007-0098025	12/2006	KR	N/A
WO 96/30713	12/1995	WO	N/A
WO 97/08743	12/1996	WO	N/A
WO 2010/016964	12/2009	WO	N/A

OTHER PUBLICATIONS

“Shaping the Future in Semiconductor Processing.” Advertisement for Morton International, Inc., *Ceramic Solutions*. vol. 73, No. 7, Jul. 1994: advertisements (circa 1993). cited by applicant

Primary Examiner: Kendall; Benjamin

Attorney, Agent or Firm: Snell & Wilmer L.L.P.

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application claims the priority benefit under 35 U.S.C. § 119(e) of U.S. Provisional Application No. 63/042,974, filed Jun. 23, 2020, the entirety of which is hereby incorporated by reference herein.

BACKGROUND

Field of the Disclosure

(1) This disclosure relates generally to semiconductor processing, and more particularly to susceptors for supporting semiconductor substrates in process chambers.

Description of the Related Art

(2) Semiconductor fabrication processes are typically conducted with the substrates supported within a reaction chamber on a susceptor under controlled process conditions. For many processes, semiconductor substrates (e.g., wafers) are heated inside the reaction chamber. A number of quality control issues related to the physical interaction between the substrate and the susceptor can arise during processing.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 schematically illustrates an embodiment of a semiconductor processing apparatus comprising a reaction chamber and a loading chamber with a susceptor in a loading position.
- (2) FIG. 2 shows the apparatus of FIG. 1 with the susceptor in a processing position.
- (3) FIG. 3 shows an example susceptor that may be used to support a substrate (e.g., wafer).
- (4) FIG. 4A shows another example susceptor, according to some embodiments.
- (5) FIG. 4B shows a perspective view of the back surface of the susceptor shown in FIG. 4A.
- (6) FIG. 5 shows a detail view of a portion of the susceptor shown in FIG. 4A.
- (7) FIG. 6 shows a cross sectional view of an example channel.
- (8) FIGS. 7A, 7B, and 7C show various perspectives of vector maps showing magnitudes and directions of velocities of gas flow through a channel.
- (9) FIG. 8 shows a heat map of pressure across an example susceptor.

DETAILED DESCRIPTION

(10) Susceptors are commonly formed by machining graphite into a desired shape and applying a silicon carbide (SiC) coating or by sintering layers of Aluminum Nitride. Susceptors can be formed in different shapes, but many are circular.

(11) As noted above, a number of quality control issues can arise during processing, relating to the physical interaction between the substrate and the susceptor. These issues can include, for example, substrate sliding, sticking, and curling, and backside deposition. Such quality control issues can decrease the overall quality of the substrates and semiconductor devices, resulting in reduced yield and increased costs.

(12) Backside deposition occurs when process gases flow into the space between the substrate and the susceptor and deposit on a back surface of the substrate. Because the flow of the process gases is not controlled between the substrate and the susceptor, random deposition can occur on the backside of the substrate. This random deposition can create thickness inconsistencies on the backside, which can affect local site flatness on the front side, and ultimately cause device uniformity issues.

(13) In a typical process, a reactant gas is passed over the heated wafer, causing the atomic layer deposition (ALD) of a thin layer of reactant material on the wafer. Through sequential processing, multiple layers are made into integrated circuits. Other exemplary processes include sputter deposition, photolithography, dry etching, plasma processing, and high temperature annealing. Many of these processes require high temperatures and can be performed in the same or similar reaction chambers.

(14) Wafers may be processed at various temperatures to promote high quality deposition. Temperature control is especially helpful at temperatures below the mass transport regime, such as about 500° C. to 900° C. for silicon CVD using silane. In this kinetic regime, if the temperature is not uniform across the surface of the wafer, the deposited film thickness will be uneven. However, lower temperatures may sometimes be used in certain scenarios.

(15) Wafers may be made of silicon, most commonly with a diameter of about 150 mm (about 6 inches) or of about 200 mm (about 8 inches) and with a thickness of about 0.725 mm. Recently, larger silicon wafers with a diameter of about 300 mm (about 12 inches) and a thickness of about 0.775 mm have been utilized because they exploit the benefits of single-wafer processing even more efficiently. Even larger wafers are expected in the future. A typical single-wafer susceptor includes a pocket or recess within which the wafer rests during processing. In many cases, the recess is shaped to receive the wafer very closely.

(16) There are a variety of quality control problems associated with handling of substrates. These problems include substrate slide, stick, and curl. These problems primarily occur during placement and subsequent removal of substrates in high temperature process chambers, particularly single-wafer chambers.

(17) A substrate may be moved within the reaction chamber, for example, to and from a susceptor, by an effector or other robotic substrate handling device, such as a Bernoulli wand. A Bernoulli wand is described in U.S. Pat. No. 5,997,588, the entire disclosure of which is hereby incorporated by reference herein for all purposes.

(18) Substrate “slide” or “skate” occurs during substrate unload when a cushion of gas in the susceptor on the upper surface of the susceptor, for example, in the susceptor's recess or pocket is unable to escape fast enough to allow the substrate to quickly and precisely transfer onto the susceptor from the effector. The substrate floats momentarily above the susceptor as the gas slowly escapes, and it tends to drift off-center. Thus, the substrate may not rest in the center of the pocket as normally intended, and uneven heating of the substrate can result. Such drifting of the substrate to the edge of a susceptor can result in poor thickness uniformity, poor resistivity uniformity, and crystallographic slip, depending on the nature of the layer being deposited.

(19) In some embodiments, a plurality of protrusions (e.g., pins, prongs, etc.) may lift the substrate from the susceptor, to facilitate transfer to or from the susceptor by an effector. During substrate unload, “stick” can occur when the substrate clings to the underlying support because gas is slow to flow into the small space between the substrate and the surface of the substrate support pocket. This creates a vacuum effect between the substrate and the substrate support as the substrate is lifted. Stick can contribute to particle contamination due to scratching against the substrate support and, in extreme cases, can cause lifting of the substrate holder on the order of 1 to 2 mm.

(20) Substrate “curl” is warping of the substrate caused by radial and axial temperature gradients in the substrate. Severe curl can cause a portion of the substrate to contact the bottom side of a Bernoulli wand, for example, when a cold substrate is initially dropped onto a hot substrate support such as a susceptor. Curl can similarly affect interaction with other robotic substrate handling devices. In the case of a Bernoulli wand, the top side of the substrate can scratch the Bernoulli wand, causing particulate contamination on the substrate. This significantly reduces yield.

(21) A susceptor can include flow channels or perforated designs to reduce slide, stick, curl, backside deposition, and other substrate processing quality issues. For example, an upper surface of a susceptor can include channels that allow generally horizontal flow along the upper surface to reduce these issues. However, susceptors that include radially channeled grid designs can still cause backside damage on the substrate. A perforated susceptor can include additional vent channels that allow flow through an upper surface of the susceptor (e.g., vertically) to prevent such damage. Nonetheless, in some susceptors, backside deposition may still occur on perforated substrates that include such vents. Additionally, vent holes may have disadvantageous locations or be incompatible with grids or other channeled structures that allow gases to access the backside of the susceptor. Embodiments of horizontal channels that provide improved venting, and/or with reduced substrate stick may be a solution to these problems, as described in more detail below. Some embodiments may also provide aesthetically pleasing benefits.

(22) Reference will now be made to the Figures. FIG. 1 schematically illustrates an embodiment of a semiconductor processing apparatus **100** comprising a reaction chamber **101** and a loading chamber **102**. Together, the reaction chamber **101** and the loading chamber **102** may be considered a process module, for example, to be implemented into multi-module “cluster” tools. In the illustrated embodiment, the reaction chamber **101** is disposed above the loading chamber **102**, and they are separated by a baseplate **107** and a movable pedestal or workpiece support **109**, described in more detail below. The workpiece support **109** can comprise a susceptor, as used elsewhere herein.

(23) In some embodiments, the reaction chamber **101** may be substantially smaller than the loading chamber **102**, contrary to the schematic drawings, which are not drawn to scale. For a single wafer process module, as shown, the reaction chamber **101** may have a volume between about 0.25 liters and 3 liters. In some embodiments, the reaction chamber **101** may have a volume of less than about 1 liter. In some embodiments, the reaction chamber **101** may be about 900 mm long, 600 mm wide,

and 5 mm high. In some embodiments, the loading chamber **102** may have a volume between about 30 liters and about 50 liters. In some embodiments, the loading chamber **102** may have a volume of about 40 liters. In some embodiments, the loading chamber **102** may have a volume about 35-45 times the volume of the reaction chamber **101**.

(24) In some embodiments, the reaction chamber **101** may comprise one or more inlets **103** (one shown) and one or more outlets **104** (one shown). During processing, gases such as reactants and purge gases may flow into the reaction chamber **101** through the reaction chamber inlet **103**, and gases such as excess reactants, reactant byproducts, and purge gases may flow out of the reaction chamber **101** through the reaction chamber outlet **104**. In some embodiments, the loading chamber **102** may comprise one or more inlets **105** (one shown) and one or more outlets **106** (one shown). In operation, gases such as purge gases may flow into the loading chamber **102** through the loading chamber inlet **105**, and gases such as excess reactants, reactant byproducts, and purge gases may flow out of the loading chamber **102** through the loading chamber outlet **106**. The depicted configuration, such as the positions of the inlets **103**, **105** and outlets **104**, **106** are merely schematic, and may be adjusted based on, for example, the process to be performed in the reaction chamber **101**, the desired flow path of the gases, etc. Purge gases can include a single purge gas or a mixture of purge gases. For example, in some embodiments, the purge gas can consist essentially of one or more inert gases, such as one or more noble gases (e.g., helium, argon, neon, xenon, etc.). The purge gas can include one or more inert gases without any reactive gases. In other embodiments, the purge gas can include, for example, one or more inert gases and one or more other non-inert gases. The purge gas can include an inert gas mixed with a reactive gas, such as hydrogen. The purge gas may include a mixture of hydrogen and argon, for example. In some embodiments, a first purge gas consisting essentially of one or more inert gases (i.e., without any reactive gases) can be used in a first purge step, and a second purge gas comprising a mixture of one or more inert gases mixed with one or more reactive gases can be used in a second purge step. In some embodiments, this second purge step sequentially follows this first purge step. Using a purge step that includes one or more inert gases with one or more reactive gases may help improve the distribution of a reactant across the substrate. For example, a delivery system (e.g., shower or showerhead) may generally concentrate the reactant near a center of the substrate. The delivery system can cause gas to flow substantially perpendicularly to a face of the substrate. During a second purge step, a mixture of inert and reactive gases can provide a better distribution of reactant near, for example, the edges of the substrate. In some embodiments, a gas, such as a purge gas, can be flowed through, within, and/or along a portion of the workpiece support **109**. Such embodiments can provide purge gas along a backside of a substrate positioned on support **109**, to prevent backside substrate deposition.

(25) In the illustrated embodiment, the reaction chamber **101** comprises a baseplate **107** including an opening **108**. An interior edge of the baseplate **107** defines the opening **108**. In some embodiments, the baseplate **107** may comprise titanium. In the illustrated embodiment, the reaction chamber inlet **103** is located approximately opposite to the reaction chamber outlet **104**, such that reaction gas that flows from the reaction chamber inlet **103** to the reaction chamber outlet **104** travels approximately parallel to a face of the workpiece **W**, and thus parallel to the upper surface of the moveable support. Such reactors are sometimes referred to as “cross-flow” or horizontal laminar flow reactors. In some embodiments, the reaction chamber **101** can include an inlet, or plurality of inlets, such as a showerhead **120**, positioned above the susceptor, to form a vertical flow reactor, or “showerhead” reactor, which provides reactant directed perpendicular to an upper surface of a substrate. For example, the top wall of chamber **101** as shown can be configured as a showerhead **120**, or can include a showerhead attached thereto. An example of a showerhead implemented within a reaction chamber is described in U.S. Pat. App. Pub. No. 2019/0139807, the entire disclosure of which is hereby incorporated by reference herein for all purposes.

(26) In some embodiments, the apparatus **100** may be an atomic layer deposition (ALD) reactor,

such that it includes valves controlled by a control system **113** to separately provide pulses of reactants. In some embodiments, apparatus **100** may include two or more valves independently controlled by control system **113** to allow regulation of relative pressure and/or the direction of flow between reaction chamber **101** and loading chamber **102**. In some embodiments, the reaction chamber inlet **103** may comprise a distribution system such to distribute gas in a desirable pattern. In some embodiments, the reaction chamber **101** may taper near the reaction chamber outlet **104**, such that the height of the reaction chamber **101** decreases near the reaction chamber outlet **104**, thereby constricting air flow through the reaction chamber outlet **104**. Although the apparatus **100** may be described herein with respect to vapor deposition (e.g., chemical vapor deposition, or CVD, and/or atomic layer vapor deposition, or ALD) reactors, the apparatus **100** may alternatively comprise other semiconductor processing tools, including, but not limited to, dry etchers, ashers, rapid thermal annealers, etc.

(27) The apparatus **100** further comprises the moveable support **109**, configured to be moved between a loading position and a processing position by operation of a drive mechanism **110**. FIG. **1** depicts the support **109** in the loading position, according to one embodiment. The support **109** may be configured to hold a workpiece (semiconductor workpiece W see FIG. **2**), such as a silicon wafer. The workpiece W may be loaded and unloaded into the support **109** in various ways, such as with an end effector of a robot. The support **109** may comprise lift-pins **111** and/or cutouts to aid in loading and unloading of the workpiece W with a paddle or fork. The support **109** may comprise a vacuum system that holds the workpiece W in place after loading, or gravity alone may hold the workpiece W in a pocket that is sized and shaped to accommodate the workpiece W. The apparatus **100** may further comprise one or more gate valves **112** (one shown) for loading and unloading of workpieces W to and from the support **109**. The gate valve **112** may allow access to, for example, a transfer chamber, load lock, processing chamber, clean room, etc.

(28) The control system **113** is also configured or programmed to control the drive mechanism **110**. In some embodiments, the drive mechanism **110** may comprise a piston or elevator that imparts vertical movement to the support **109**. The drive mechanism **110** is therefore configured to move the support **109**, and thus the workpiece W disposed on the support **109**, into the processing position during a reactor closure operation and into the loading position during a reactor opening operation. The drive mechanism **110** can also be configured to rotate the workpiece W disposed on the support **109**.

(29) FIG. **2** schematically illustrates the apparatus **100** with the support **109** shown in the processing position, according to one embodiment. When in the processing position, the support **109** engages the baseplate **107**, effectively isolating or separating the interior of the reaction chamber **101** from the loading chamber **102**. Such isolation can reduce contamination between the reaction chamber **101** and the loading chamber **102**. In some embodiments, engaging may comprise creating a hard metal-on-metal seal between the baseplate **107** and the support **109**. In some embodiments, engaging may comprise compression of pliable material, such as an O-ring, on either part, to create a soft seal between the baseplate **107** and the support **109**. In some embodiments, engaging may comprise maintaining a gap between the support **109** and the baseplate **107**, such that there is no absolute seal. Even where engaging comprises maintaining a gap between the support **109** and the baseplate **107**, the support may still effectively separate the reaction chamber **101** from the loading chamber **102** by creating a substantial barrier to fluid communication between the reaction chamber **101** and the loading chamber **102** when apparatus **100** is in the processing position.

(30) FIG. **3** shows a fluid volume of an example susceptor **200** that may be used to support a substrate (e.g., wafer). The susceptor **200** can include an outer edge **208** forming an outer perimeter around a face **204**. The face **204** can include a channel region **212** positioned outwardly from an inner region **214**. The face **204** may further include one or more channels **220**. The susceptor **200** may comprise one or more materials, such as elemental or molecular materials. Such materials can

include non-oxide ceramics, such as silicon carbide (SiC or SiSi), graphite, or any other ceramic. Other materials may be used, such as metal. In some embodiments, the susceptor **200** may include a silicon carbide coating, such as silicon-carbide-coated graphite. The face **204** may be configured to hold or support the substrate (not shown).

(31) The rim region **217** can be positioned radially outwardly from the channel region, and may provide additional structural integrity and/or easier access to portions of the susceptor **200** as needed. The rim region **217** may be bounded between the edge **208** and an outer radial boundary of the channel region **212**. In some embodiments, the functionality of the rim region **217** may be performed by the baseplate **107** of FIG. 2. The channel region **212** may be bounded by the outer rim **216** and an inner boundary, such as an inner rim **232** or inner channel ring. Any “boundary” described herein may be a subtle difference in rise angle, material, curvature/concavity, smoothness, and/or other difference between adjacent regions. The rim region **217** may be substantially flat and/or smooth. For example, the rim region **217** may be substantially free of channels, protrusions, holes, and/or other irregularities in the surface of the rim region **217**. The rim region **217** can have a radial width (defined as the radial distance between the edge **208** and the outer radial boundary) of between about 15 mm and 35 mm.

(32) The channel region **212** can be positioned between the outer rim **216** and the inner rim **232**. One or both of the outer rim **216** and/or the inner rim **232** may be round, such as substantially a circle or other rounded shape (e.g., oval). The inner region **214** may be substantially flat and/or smooth. For example, the inner region **214** may be substantially free of channels, protrusions, and/or other irregularities. The inner region **214** can be shaped and/or sized to provide additional structural integrity to the susceptor **200**. For example, an inclusion of irregularities within the inner region **214** may reduce the strength of the inner region **214**. In some embodiments, the inner region **214** is recessed relative to the surrounding channel region **212**.

(33) The channel region **212** may be disposed adjacent and/or radially inward of the rim region **217**. The channel region **212** may be disposed between the rim region **217** and the inner region **214**. Within the channel region **212**, one or more channels **220** may be formed within the face **204**, but for convenience, reference will be made to a plurality of channels **220** throughout. The channels **220** may extend radially outwardly relative to a center of the face **204** or from near a center of the face **204** towards (and in some embodiments, to and through) the edge **208**. In some embodiments, the channels **220** can extend from or near the inner rim **232** to or near the outer rim **216**. In some embodiments, the channels **220** may extend substantially radially from the center of the face **204** and/or to and through the edge **208**. In some embodiments, consecutive channels **220** may form an angular separation or angle **240**. Consecutive channels may be referred to as “adjacent” or “neighboring.” The angle **240** can be an acute angle. For example, the angle **240** may be between about 5° and 35° and in some embodiments is about 15° between at least two consecutive channels **220**. Consecutive channels **220** may be referred to as successive or adjacent channels **220** herein. A plurality of regularly spaced consecutive channels **220** may have a substantially the same angle **240** between each set of consecutive channels **220**. As shown, the face **204** may include multiple sets of such pluralities of consecutive channels **220**. The regularity of angle **240** may be interrupted, for example, by one or more irregularities in the channel region **212**. For example, as shown, one or more apertures **256** and/or raised features **234** (shown in FIG. 4A) may be included in the channel region. The apertures **256** may be configured to allow raisers (e.g., pins, prongs, rods, etc.) therethrough. The raisers may be used by a susceptor support apparatus (e.g., a spider) (not shown) to raise a wafer up from the susceptor **200** without raising the susceptor **200** itself. Accordingly, an angle **240** between consecutive channels **220** where irregularities may be found can be greater, such as double the angle **240** described above. Such increased angular separation can provide additional structural integrity to those portions of the susceptor which include apertures **256**, and/or can provide additional space to avoid interference with the raisers and susceptor support apparatus.

(34) The channel region **212** can form a “pocket” or recess into which the substrate may rest. The

outer rim **216** or other outer boundary can form the outer boundary of this pocket. The channel region **212** may have a sloped and/or concave surface, which forms an elevated portion, relative to the inner region **214**, to limit the amount of the substrate (e.g., an edge or rim of the substrate) that is touching the susceptor **200**. The majority of surface area of the channel region **212** may be substantially flat and/or smooth. One or more portions of the channel region disposed between consecutive channels **220** may increase in area moving from the inner rim **232** to the outer rim **216**. One or more of the channels **220** may be substantially straight. The number of channels **220** within the channel region can be between about 3 and 72, or between about 18 and 30, but other variants are also possible. In some embodiments, the number of channels is 36.

(35) The channel region **212** may be tapered, such that it is disposed at a slight incline to allow a substrate to rest on only a portion of the channel region **212**. A rise angle of the channel region **212** relative to the back surface **206** may be between about 0.5° and 5° and in some embodiments is about 3° . The rise angle can be an absolute value (for example, when the inner channel region **124** is substantially flat). In some embodiments, the cross sectional shape (e.g., the cross section shown in FIG. 3) of channel region **212** can be recessed, e.g., concave. The channel region **212** may thus be configured to provide edge support of a substrate, and thus reduce substrate contact with the susceptor **200**.

(36) The susceptor may be surface-treated to improve performance. For example, one or more regions of the face **204** may be polished to reduce the likelihood of deformities (e.g., caused by substrate sticking) to affect the substrate. Portions of the susceptor **200** may be coated to improve performance. For example, the face **204** may be coated with silicon carbide.

(37) FIG. 3 also shows how each of the channels **220** can include a corresponding elongate portion **224** and a flash-out portion **228**. A width and/or cross sectional area of each of the elongate portions **224** may be substantially constant along a radial length of the elongate portion **224**. Each elongate portion **224** may have a width that is less than or equal to a threshold width along the entirety of the elongate channel portion. The threshold width may be about 0.01 mm, about 0.05 mm, about 0.1 mm, about 0.2 mm, about 0.3 mm, about 0.5 mm, about 0.7 mm, about 0.9 mm, about 1 mm, about 1.2 mm, about 1.5 mm, about 1.8 mm, about 2 mm, about 2.5 mm, about 3 mm, about 4 mm, about 5 mm, about 7 mm, about 10 mm, about 15 mm, about 20 mm, any value therein, or fall within a range having endpoints therein. The cross sectional area of the elongate portion may be substantially constant along a radial length of the elongate portion **224**. For example, the cross-sectional area may be within (e.g., above or below) a threshold, such as the threshold width above, by a threshold percentage. The threshold percentage may be about 1%, about 3%, about 5%, about 10%, about 15%, about 20%, about 25%, or some other percentage.

(38) One or more of the channels **220** may include a respective flash-out portion **228**. The flash-out **228** portion can be in fluid communication with the elongate portion **224**. Other details of the flash-out portion **228** are provided below with reference to FIG. 5. In some embodiments, the flash-out portion **228** is disposed radially outward of the elongate portion **224**. The flash-out portion **228** can be triangle shaped (e.g., pie-shaped). A distal end of the channels **220** (e.g., the distal end of the flash-out portions **228** and the portions of the face therebetween) can form a purge perimeter **226**. The substrate can be supported upon this purge perimeter **226**, and during purge, the purge gas flows around this purge perimeter and the edge of the substrate, to prevent backside deposition. The flash-out portions **228** increase the uniformity of flow (e.g., uniformity of velocity and/or pressure) around the purge perimeter **226**, to improve yield and reduce backside deposition.

(39) Consecutive elongate portions **224** may form an angle **290** therebetween. The elongate portion **224** may be an acute angle in some embodiments. The elongate portion **224** may be about 10° , about 15° , about 18° , about 20° , about 22° , about 25° , about 27° , about 30° , about 32° , about 33° , about 35° , about 40° , about 42° , about 45° , about 50° , about 55° , about 60° , about 65° , about 70° , about 75° , about 80° , about 90° , about 100° , about 110° , about 120° , about 180° , any value therein, or fall within a range having endpoints therein. The quantity of channels **220**, the angles **290**

therebetween, the width of the channels, and/or the cross sectional shape and area of the channels **220** may be selected within a range that provides improved uniformity in heat transfer within the susceptor.

(40) FIG. 4A shows another example susceptor **200**, according to some embodiments. The susceptor **200** shown in FIG. 4A shows a plurality of protrusions **234** and apertures **256**. The protrusions **234** may extend upwardly relative to a surrounding portion of the face **204**, to provide a small separation between the substrate and the surrounding portion of the front face **204**. This separation may improve the functionality and efficacy of any applied or inherent vacuum. The protrusions **234** may help reduce sticking of the substrate to the susceptor **200**, and/or may reduce direct contact with the backside of the substrate, which in turn can reduce contamination or potential substrate damage. The protrusions **234** may also improve the uniformity of heat conduction to the substrate.

(41) As shown in FIG. 4A, one or more apertures **256** may be included in the susceptor **200**. The apertures **256** may be lift pin holes that allow for lift pins to extend through the susceptor **200**. The apertures **256** may allow a substrate (e.g., a wafer) to be placed on the face **204** and/or removed therefrom. The apertures **256** may be disposed radially inward of an outer boundary of the susceptor **200** (e.g., the outer rim **216** shown in FIG. 3, the edge **208**, etc.). In some embodiments, the apertures **256** are radially outward from the outer boundary. In some embodiments, there are three lift apertures **256**, but another number is possible. The apertures **256** may extend between the face and the back surface and may be configured to allow for pins to extend therethrough. The apertures **256** may be disposed between consecutive elongate portions of a plurality of channels. An angular separation between each radially consecutive aperture may be substantially equal. For example, the angular separation between consecutive apertures where there are three apertures may be about 120°. Other variants are possible. An inner diameter of each of the apertures **256** may be between about 35 mm and 400 mm and in some embodiments is about 160 mm. FIG. 4B shows a perspective view of the back surface **206** of the susceptor **200** shown in FIG. 4A. As shown, the apertures **256** may pass through to the back surface **206**.

(42) FIG. 5 shows a detail view of a portion of the susceptor **200** shown in FIG. 4A. The channels **220** in the face **204** of the susceptor **200** may extend radially outwardly from an inner rim **232**. In some embodiments, the channels **220** can extend from the inner radial boundary such as a ring channel **230** or the inner rim **232**. The ring channel **230** can extend into the face **204** and be disposed radially inward of and in fluid communication with at least one of the plurality of channels **220**. The ring channel **230** can form a volume configured to receive gas (e.g., purge gas) through an opening **235**, and provide better pressure uniformity in flow of the gas supply to the plurality of channels **220**. The channels **220** may extend substantially radially from the ring channel **230**. In some embodiments, consecutive channels **220** may form an angle **240**, as shown. The angle **240** can form an acute angle. For example, the angle **240** may be between about 3° and 30° and in some embodiments is about 7.5° between at least two consecutive channels **220**. Consecutive channels **220** may be referred to as successive or adjacent channels **220** herein. A plurality of regularly spaced consecutive channels **220** may have substantially the same angle **240** between each set of consecutive channels **220**. Though not shown, the face **204** may include multiple sets of such pluralities of consecutive channels **220**. The regularity of angle **240** may be interrupted, for example, by one or more irregularities in the face **204**. For example, one or more apertures **256** may be included in the channel region. Accordingly, an angle **240** between consecutive channels **220** where irregularities may be found can be greater, such as double the angle **240** described above. Such increased angular separation can provide additional structural integrity and/or can provide additional space to avoid interference with the raisers and susceptor support apparatus. Two consecutive elongate portions **224a**, **224b** of the plurality of channels can form an angle **240** of about 1°, about 2°, about 3°, about 5°, about 7°, about 10°, about 12°, about 15°, about 18°, about 20°, about 22°, about 25°, about 28°, about 30°, about 33°, about 35°, about 40°, about 45°,

any angle therein, or fall within a range having endpoints therein.

(43) Consecutive flash-out portions **228a**, **228b** can form various angles additionally or alternatively. As shown, a first channel can include a first flash-out portion **228a** having a first edge **276** and a second edge **280**. The first edge **276** and the second edge **280** can form an angle **290**. The angle **290** can be about 1°, about 2°, about 3°, about 5°, about 7°, about 10°, about 12°, about 15°, about 18°, about 20°, about 22°, about 25°, about 28°, about 30°, about 33°, about 35°, about 40°, about 45°, any angle therein, or fall within a range having endpoints therein. As shown, the first edge **276** and the second edge **280** need not come into contact to form the angle **290**.

(44) A second flash-out portion **228b** may include a corresponding first edge **284** and second edge **288**. The second edge **280** of the first flash-out portion **228a** may form an angle **272** with the first edge **284** of the second flash-out portion **228b**. The angle **272** can be about 1°, about 2°, about 3°, about 5°, about 7°, about 10°, about 12°, about 15°, about 18°, about 20°, about 22°, about 25°, about 28°, about 30°, about 33°, about 35°, about 40°, about 45°, any angle therein, or fall within a range having endpoints therein. As shown, the second edge **280** and the first edge **284** need not come into contact to form the angle **290**. For example, a substantially flat connector portion may connect the second edge **280** and the first edge **284**.

(45) FIG. 6 shows a cross sectional view of an example channel **220**. Other shapes of the cross section are possible. As shown, the channel **220** can include curvilinear sidewalls. The sidewalls may form substantially a semi-circle along the cross section. The radius **288** of curvature may be between about 0.1 mm and 2.5 mm and is about 0.6 mm in some embodiments. Curved sidewalls as shown may be helpful in preventing the accumulation of gas therein during deposition. The width **264** of the channel **220** may be between about 0.1 mm and 5 mm and in some embodiments is about 1.2 mm. The depth **266** of the channel **220** may be between about 0.05 mm and 1.5 mm and in some embodiments is about 0.6 mm. In some embodiments, the channel **220** can include substantially flat sidewalls. The sidewalls may form an angle such as an acute angle.

(46) FIGS. 7A, 7B, and 7C show various perspectives of vector map simulations showing magnitudes and directions of velocities of gas flow through a channel. FIG. 7B shows a higher magnitude of velocities of gas particles immediately exiting the elongate portion of the corresponding channel. Beyond the exit of the elongate portion, velocities decrease, and further decrease within the flash-out portion as the width and cross-sectional area expands. This allows the velocities of gas particles to be substantially uniform around a purge perimeter (e.g., the purge perimeter **226**) formed by the distal ends of the plurality of channels, at the outlet of the flash-out portions. The term “substantially uniform” may include producing respective velocities for at least a certain percentage (e.g., 50%, 75%, 80%, 90%, 95%, etc.) of the gas particles that do not vary by more than a standard deviation from a mean velocity of the gas particles.

(47) FIGS. 7A-7C and 8 show a perspective of a vector map showing magnitudes and directions of gas flow through a channel. FIG. 8 shows similar results as FIGS. 7A-7C, but for pressure. In sum, FIG. 8 shows a higher magnitude of pressure of gas particles immediately exiting the elongate portion of the corresponding channel, which decreases and spreads out through the flash out portion. Pressures further decrease within the flash-out portion as the width and cross-sectional area expands. This allows the pressures of gas to be substantially uniform around the purge perimeter formed by the distal ends of the plurality of channels, at the outlet of the flash-out portions. The term “substantially uniform” may include producing respective pressures for at least a certain percentage (e.g., 50%, 75%, 80%, 90%, 95%, etc.) of the gas particles that do not vary by more than a standard deviation from a mean velocity of the gas particles. FIGS. 7A-8 demonstrate how configurations of susceptors with embodiments of the channels herein can provide improved uniformity in flow, including pressure and velocity, around the perimeter of a substrate supported on the susceptor. This improved uniformity in flow can in turn reduce backside deposition onto the susceptor, improving substrate yield and reducing substrate waste.

(48) The present aspects and implementations may be described in terms of functional block

components and various processing steps. Such functional blocks may be realized by any number of hardware or software components configured to perform the specified functions and achieve the various results. For example, the present aspects may employ various sensors, detectors, flow control devices, heaters, and the like, which may carry out a variety of functions. In addition, the present aspects and implementations may be practiced in conjunction with any number of processing methods, and the apparatus and systems described may employ any number of processing methods, and the apparatus and systems described are merely examples of applications of the invention.

Claims

1. A susceptor comprising: a face configured to support a substrate thereon; an inner region, wherein the inner region centered on a center of the face; and a channel region, wherein the channel region is disposed radially outward from the inner region, wherein the channel region comprises a plurality of channels, a plurality of elevated regions, and an outer rim disposed radially outward from the plurality of channels, wherein the plurality of channels extends into the face and radially outwardly from the inner region to the outer rim, wherein each of the plurality of channels spans between two elevated regions, each of the plurality of channels comprising: an elongate portion having an elongate portion width; and a flash-out portion in fluid communication with the elongate portion, the flash-out portion comprising a distal end at the outer rim, a first section having a first width and a second section having a second width greater than the first width, wherein the first section is disposed radially inward of the second section, and wherein each of the plurality of channels spans the second width, and wherein the plurality of elevated regions extend radially outwardly from the inner region to the outer rim, wherein each of the plurality of elevated regions spans between two adjacent channels, wherein each of the plurality of channels spans between two adjacent elevated regions.
2. The susceptor of claim 1, wherein the channel region comprises a recess configured to support a substrate, wherein the outer rim comprises an outer boundary of the recess.
3. The susceptor of claim 1, wherein the elongate portion width is substantially constant along a radial length of the elongate portion.
4. The susceptor of claim 1, wherein the plurality of channels are regularly spaced.
5. The susceptor of claim 1, wherein a width of the flash-out portion is greatest at the outer rim.
6. The susceptor of claim 1, wherein the flash-out portion comprises a substantially triangular shape from the elongated portion to the outer rim.
7. The susceptor of claim 1, wherein the flash-out portion comprises a first edge and a second edge, the first edge oriented relative to the second edge at an angle of between about 25° and 110°.
8. The susceptor of claim 7, wherein the plurality of channels comprises a first channel and a second channel consecutive with the first channel, wherein the first edge of the second channel and the second edge of the first channel are disposed at an angle therebetween of between about 15° and 100°.
9. The susceptor of claim 7, wherein the plurality of channels comprises a first channel and a second channel consecutive with the first channel, wherein the angle between the first edge and the second edge of the first channel flash-out portion is different from an angle between the first edge and the second edge of the second channel flash-out portion.
10. The susceptor of claim 1, wherein the elongate portion has a depth of between about 0.05 mm and 1.5 mm.
11. The susceptor of claim 4, wherein each set of consecutive channels of the plurality of channels has the same angle between the consecutive channels.
12. The susceptor of claim 1, wherein two consecutive elongate portions of the plurality of channels form an angle of between about 3° and 25°.

13. The susceptor of claim 1, further comprising: a back surface opposite the face; and one or more apertures extending between the face and the back surface, the one or more apertures configured to allow for pins to extend therethrough and lift a substrate from the face of the susceptor.
 14. The susceptor of claim 13, wherein the one or more apertures are disposed between the first elongate portion and a consecutive elongate portion of a second channel of the plurality of channels.
 15. The susceptor of claim 13, wherein the one or more apertures comprises at least three apertures, and wherein an angular separation between each radially consecutive aperture of the at least three apertures is substantially equal.
 16. The susceptor of claim 1, wherein a cross section of the elongate portion comprises: first and second sidewalls, each of the first and second sidewalls being substantially flat, wherein the first and second sidewalls are disposed at an acute angle relative to each other.
 17. The susceptor of claim 1, further comprising a ring channel extending into the face and disposed radially inward of and in fluid communication with at least one of the plurality of channels.
 18. A susceptor comprising: a face configured to support a substrate thereon; a plurality of channels extending into the face and radially outwardly relative to a center of the face, each of the plurality of channels comprising a distal end, the distal ends of the plurality of channels forming an annular purge perimeter, the plurality of channels configured to produce at least one of a substantially uniform velocity and pressure of gas around the purge perimeter, during a radial flow of gas through the channels; and a plurality of elevated regions extending radially outwardly to the purge perimeter, wherein each of the plurality of elevated regions spans between two channels, wherein a width of each of the plurality of channels is greatest at the distal end, and wherein each of the plurality of channels spans a width of the distal end.
 19. The susceptor of claim 18, wherein the plurality of channels are configured such that the at least one of substantially uniform velocity and pressure of gas around the purge perimeter comprises maintaining, for each of at least 75% of particles of the gas, a velocity that does not vary by more than a standard deviation from a mean velocity of all of the gas particles.
 20. A reaction chamber comprising the susceptor of claim 1, further comprising a showerhead configured to direct a flow of gas substantially perpendicular to the face.
-