

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12418744
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Aboud; Stephen et al.

Speaker with sound dispersing cone

Abstract

An apparatus (100), including: a speaker (152, 154); a baffle (104) surrounding the speaker; and a dispersion cone (106) positioned forward of, aligned with, and pointing toward the speaker and having a dispersion surface (120) with: a dispersion surface central section (122); a dispersion surface surrounding section (124) therearound; and a transition (126) therebetween. From a tip (122T) of the dispersion cone outward the dispersion surface central section defines a concave cross-sectional shape (170), the dispersion surface surrounding section defines a less concave cross-sectional shape (172) than the concave cross-sectional shape of the dispersion surface central section, and the transition comprises an inflection point (124IP). A distance of each section of the dispersion surface forward of the speaker progressively increases with increasing radial distance from a radial center of the dispersion surface.

Inventors: Aboud; Stephen (Cocoa Beach, FL), Brumbaugh; Colin (Merritt Island, FL), Lankes; Carter (Merritt Island, FL), Wilson; Darrick (Edmonton, CA)

Applicant: Roswell U.S. LLC. (Rockledge, FL)

Family ID: 1000008822251

Assignee: Roswell U.S., LLC (Rockledge, FL)

Appl. No.: 18/239246

Filed: August 29, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20250080903 A1	Mar. 06, 2025

Publication Classification

Int. Cl.: H04R1/34 (20060101)

U.S. Cl.:

CPC **H04R1/345** (20130101);

Field of Classification Search

CPC: H04R (1/345)

USPC: 381/339

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2271100	12/1941	Scott	N/A	N/A
2820525	12/1957	Fountain	181/187	H04R 1/345
3326321	12/1966	Valuch	N/A	N/A
3329235	12/1966	Shaper	N/A	N/A
3816672	12/1973	Gefvert	N/A	N/A
4348549	12/1981	Berlant	N/A	N/A
4620317	12/1985	Anderson	N/A	N/A
5115882	12/1991	Woody	N/A	N/A
5129006	12/1991	Hill	N/A	N/A
5131052	12/1991	Hill	N/A	N/A
5525767	12/1995	Fields	N/A	N/A
5673329	12/1996	Wiener	381/89	H04R 1/34
5721401	12/1997	Sim	N/A	N/A
5988314	12/1998	Negishi	N/A	N/A
6996243	12/2005	Welker	N/A	N/A
8098852	12/2011	Harwood	N/A	N/A
9226058	12/2014	Harwood	N/A	N/A
10129636	12/2017	Kim	N/A	N/A
11317183	12/2021	Shen	N/A	N/A
11395063	12/2021	Wang	N/A	G10K 11/28
2002/0011379	12/2001	Taylor	N/A	N/A
2003/0141142	12/2002	Christiansen	N/A	N/A
2005/0093970	12/2004	Abe	N/A	N/A
2012/0076328	12/2011	Harwood	N/A	N/A
2016/0227315	12/2015	Kim	N/A	N/A
2016/0337748	12/2015	Goksel	N/A	N/A
2017/0006376	12/2016	Tan	N/A	N/A
2018/0242061	12/2017	Honda	N/A	N/A
2019/0121405	12/2018	Pennington, Jr.	N/A	N/A
2020/0280797	12/2019	Combest	N/A	N/A

Primary Examiner: Nguyen; Sean H

Attorney, Agent or Firm: WOLTER, VAN DYKE, DAVIS PLLC

Background/Summary

FIELD OF THE INVENTION

(1) The invention relates to a speaker having a dispersion cone to redirect sound.

BACKGROUND OF THE INVENTION

(2) Dispersion cones are used on speakers, such as those mounted to a tower on a boat, to redirect sound emanating from a tweeter in an outward direction. However, in this context, known dispersion cone assemblies do not redirect the sound from other speaker elements such as a woofer and the like. In addition to diffusing only a portion of the sound from the speaker, the coverage area of the sound that is redirected is limited. Moreover, the dispersion cone itself and its supporting structure may interfere with the sound stage. Consequently, there is room for improvement in the art.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The invention is explained in the following description in view of the drawings that show:
- (2) FIG. 1 is a side view of an example embodiment of a speaker assembly.
- (3) FIG. 2 is a lower perspective view of the speaker assembly of FIG. 1.
- (4) FIG. 3 is a bottom view of the speaker assembly of FIG. 1.
- (5) FIG. 4 is a side sectional view of select components of the speaker assembly of FIG. 1.
- (6) FIG. 5 is a closeup view of the sectional view of FIG. 4.
- (7) FIG. 6 is another closeup view of the sectional view of FIG. 5.
- (8) FIG. 7 is an elevated perspective and sectional closeup view of an example embodiment of a dispersion cone.
- (9) FIG. 8 is a lower perspective and sectional closeup view of an example embodiment of a dispersion cone.
- (10) FIG. 9 is another closeup view of the sectional view of FIG. 4 showing various groupings of streamlines.
- (11) FIG. 10 is a side view of the speaker assembly of FIG. 1 showing streamlines that converge at a relatively close point in space.
- (12) FIG. 11 is a side view of the speaker assembly of FIG. 1 showing streamlines that converge at a relatively distant point in space.

DETAILED DESCRIPTION OF THE INVENTION

(13) The present Inventors have developed an improved speaker assembly with a sound dispersion cone ideally suited for mounting to a tower of a boat. The sound dispersion cone distributes sound from the entire speaker evenly over 360 degrees for listeners located around the speaker. In addition, the sound dispersion cone is sufficiently acoustically transparent to pass sound through to listeners located in front of the speaker. This is ideal for a boat tower mounted speaker that is aimed downward because boat passengers are often spread out around and below the speaker. The improved speaker assembly enables everyone to enjoy a more uniform sound presentation regardless of their location on the boat. Moreover, changes in the sound presentation resulting from moving around the boat are minimized.

(14) The speaker assembly achieves the improved sound distribution via a unique arrangement in which the dispersion cone cooperates with the speaker housing to distribute the full range of sound emanating from the speaker. This is done by positioning the dispersion cone in front of all the speaker elements (not just the tweeter). An example arrangement includes a speaker having a concentrically positioned tweeter and woofer assembled together with a dispersion cone. The

dispersion cone is positioned concentric with and in front of the tweeter and woofer and is large enough in diameter to receive and redirect all sound emanating from both the tweeter and the woofer. Sound from the speaker is immediately redirected radially by one portion of the dispersion cone, and sound is redirected back to the speaker housing and then redirected radially and forward by another portion of the dispersion cone.

(15) In addition, the dispersion cone is configured to act as a passive radiator and pass sound therethrough. Together, the distributed sound and the radiated sound present a more uniform sound presentation for all listeners.

(16) FIG. 1 to FIG. 3 are views of an example embodiment of a speaker assembly **100** having a speaker housing **102**, a baffle **104**, a dispersion cone **106**, and ribs **108** connecting the dispersion cone **106** to the baffle **104** (or optionally to the speaker housing **102**), and a speaker housing opening **110** in which a speaker (not shown in FIG. 1 to FIG. 3) is positioned.

(17) The dispersion cone **106** is positioned forward of, is aligned with, and points toward the speaker. The dispersion cone **106** includes dispersion surface **120** having a dispersion surface central section **122**, a dispersion surface surrounding section **124** therearound, and a dispersion cone transition **126** therebetween.

(18) The dispersion cone **106** further includes a forward-facing radiating surface **130** having a radiating surface central section **132** that defines a concave overall shape, a radiating surface surrounding section **134** that surrounds the radiating surface central section **132**, and the dispersion cone transition **126** therebetween.

(19) In an example embodiment, the radiating surface central section **132** corresponds to the dispersion surface central section **122**, though this is not necessary. Corresponds means that the radiating surface central section **132** defines a concave overall shape and is disposed inside the dispersion surface central section **122**, which defines a convex overall shape. Corresponding may further mean that the radiating surface central section **132** has a shape that matches a shape of the dispersion surface central section **122**. Such may be the case when the dispersion cone **106** has a uniform thickness between the radiating surface central section **132** and the dispersion surface central section **122**.

(20) In an example embodiment, the radiating surface surrounding section **134** corresponds to the dispersion surface surrounding section **124**, though this is not necessary. Corresponds means that the radiating surface surrounding section **134** has a shape that matches a shape of the dispersion surface surrounding section therearound **124**. Such may be the case when the dispersion cone **106** has a uniform thickness between the radiating surface surrounding section **134** and the dispersion surface surrounding section **124**.

(21) In an example embodiment, the respective shapes/curves defined by the dispersion surface central section **122** and the dispersion surface surrounding section **124** are different from each other. The dispersion cone transition **126** connects the two. The dispersion cone transition **126** may be a gentle curve that smoothly connects the shapes/curves defined by the dispersion surface central section **122** and the dispersion surface surrounding section **124**. Alternately, the dispersion cone transition **126** may be as abrupt as fabrication allows.

(22) Speaker assembly mounts **136** permit easy mounting of this example speaker to a tower on, for example, a boat. Such a mount aims the speaker downward. When so mounted, the dispersion surface central section **122** directs sound laterally (radially outward), the dispersion surface surrounding section **124** cooperates with the baffle **104** to direct the sound laterally and downward (forward), and the dispersion cone **106** also radiates sound therethrough downward.

(23) FIG. 4 is a sectional view of select components of the speaker assembly **100** of FIG. 1. Visible are the speaker **150**, the baffle **104**, a tweeter **152**, a woofer **154** having a woofer cone **156**, a speaker frame **158**, and a surround **160** between the woofer cone **156** and the speaker frame **158**. Also shown are the dispersion cone **106** and ribs **108** connecting the dispersion cone **106** to the baffle **104**. In this example, the tweeter is a driver and the woofer **154** is a second driver, but there

can be any number of drivers. Some, all, or none of the number of drivers may be concentrically aligned. Alternately, the speaker **150** may include a single, full (frequency) range driver.

(24) The tweeter **152**, the woofer **154**, and the dispersion cone **106** are all concentric with a central axis CA. In this example embodiment, an outer diameter **162** of the dispersion cone **106** is at least as large as an outer diameter **164** of the woofer cone **156**, although this is not necessary. In this example embodiment, the outer diameter **162** of the dispersion cone **106** is also at least as large as an outer diameter **166** of the surround **160**. Hence, in the example embodiment, the outer diameter **162** of the dispersion cone **106** is at least as large as an outer diameter of all moving components of the speaker **150**, namely the tweeter **152**, the woofer cone **156**, and the surround **160**. This allows for very effective dispersion of the sound from the speaker **150**. In alternate embodiments, the outer diameter **162** of the dispersion cone **106** may be larger than, smaller than, or equal to the outer diameter **164** of the woofer cone **156** or larger than, smaller than, or equal to the outer diameter **166** of the surround **160**.

(25) FIG. 5 is a closeup view of the sectional view of FIG. 4. As can be seen in FIG. 5, the dispersion surface central section **122** has a convex (conical pointed) overall shape. However, in this side sectional view, from a tip **122T** of the dispersion cone **106** and moving in the forward direction **176** and the radial direction **178**, the dispersion surface central section **122** defines a concave cross-sectional shape **170**. Due to the various vibration modes occurring across the surface of a speaker, certain frequencies will tend to be strongest at certain locations of a speaker cone. Generally speaking, higher frequencies are stronger towards the center of the cone and lower frequencies get stronger towards the perimeter. The shape of the dispersion cone **106** is such that it attempts to capture these frequencies at their strongest point and redirect them in the same general direction while providing an equal (or as close to equal as possible) length signal path through the air to the listener's ear. This is critical in minimizing comb filtering, which is the result of certain frequencies arriving out-of-phase relative to the remainder of the intended audio signal, resulting in unwanted peaks and dips in the perceived sound.

(26) In this side sectional view and moving in the forward direction **176** and the radial direction **178**, moving from a radially inner perimeter **124IP** of the dispersion surface surrounding section **124** outward, the dispersion surface surrounding section **124** defines a less concave cross-sectional shape **172** than the cross-sectional shape **170** of the dispersion surface central section **122**. In the example embodiment shown, the cross-sectional shape **172** of the dispersion surface surrounding section is linear (flat).

(27) Both the dispersion surface central section **122** and the dispersion surface surrounding section **124** progressively increase their distance in the forward direction **176** from the speaker **150** with increasing distance in the radial direction **178**. In other words, both sections progressively taper away from the speaker **150** with increasing radial distance from the central axis CA. These tapers allow for radial dispersion of the sound waves impacting the tapered sections.

(28) The cross-sectional shape **170** of the dispersion surface central section **122** is configured to redirect sound waves emanating from a central region **180** of the (drivers of the) speaker **150** radially outward and through an annular opening **182** between the baffle **104** and the dispersion surface surrounding section **124**. For sake of simplicity, sound waves are illustrated herein as dashed streamlines that originate at the moving parts (drivers) of the speaker **150** (the tweeter **152**, the woofer **154**, and the surround **160**) and travel in the forward direction **176** until encountering the dispersion surface **120**. In an example embodiment, a local curvature of the cross-sectional shape **170** may be tied to distance in the radial direction **178** from the central axis CA. As the radial distance increases, the shape transitions from having a more vertical slope to having a more horizontal slope. This may be necessary to ensure the redirected sounds of the central region **180** bypass the dispersion surface surrounding section **124** and pass directly through the annular opening **182** without encountering any other surface such as the dispersion surface surrounding section **124**.

- (29) In an example embodiment, the shape of the dispersion surface central section **122** is further configured to redirect all the sound waves emanating from the central region **180** of the (drivers of the) speaker **150** in the same radial direction and/or within a certain angular envelope. For example, the cross-sectional shape **170** may be configured so that an angle **184** between any two redirected central region streamlines **186** may be less than a threshold value.
- (30) FIG. **6** is another closeup view of the sectional view of FIG. **4** and shows sound streamlines emanating from a peripheral region **188** of the (drivers of the) speaker **150**. The dispersion surface surrounding section **124** is configured to receive the sound emanating from the peripheral region **188** and to redirect it radially outward and back toward the baffle **104**. The baffle **104**, in turn, further redirects the sound radially outward and forward (downward).
- (31) In this side sectional view and moving in the radial direction **178** from a radially inner perimeter **104IP** to a radially outer perimeter **104OP**, a cross sectional shape **190** of a baffle reflecting surface **192** of the baffle **104** may be concave to focus the sound within a narrower radial distance, convex to disperse the sound over a greater radial distance, or straight (as is shown in FIG. **6**). In addition, the orientations/angles of the dispersion surface surrounding section **124** and the baffle reflecting surface **192** may be adjusted to best target the redirected sound to certain radial locations etc.
- (32) In an example embodiment, the shape of the dispersion surface central section **122**, the cross-sectional shape **172** of the dispersion surface surrounding section **124**, and the surface of the dispersion cone transition **126** therebetween are all free of convex shapes. In such an example embodiment, such as that shown, the cross-sectional shape of the entire dispersion surface **120** is free of convex shapes.
- (33) The dispersion cone **106** itself is configured to act as a passive radiator to radiate sound waves impacting the dispersion surface **120** from the forward-facing radiating surface **130** and directly to the surrounding environment. The sound radiated by the dispersion cone **106** will best reach listeners disposed directly forward of (under) the speaker.
- (34) The dispersion cone **106** is configured to resonate with the sounds impacting the dispersion surface **120**. Resonation is enabled by securing the ribs **108** to the outermost periphery of the dispersion cone **106**. The dispersion cone **106** is then akin to a cone of a speaker, and the ribs **108** act somewhat like a speaker surround. This restraint of the periphery alone allows the dispersion cone **106** freedom to move/resonate and thereby transmit sound as a passive radiator. A suitable dispersion cone **106** may be thin with a lower mass/inertia.
- (35) The dispersion cone itself may also be at least partly composed of a material that is acoustically transparent. Such materials will allow sound waves to travel through the dispersion cone **106** with little loss of sonic quality.
- (36) Materials selected for the dispersion cone **106** should be suitably reflective so that sound impacting the dispersion surface **120** are properly dispersed/reflected as disclosed above. The materials should also be suitably resilient so that the dispersion cone **106** can resonate as disclosed above. The materials may also have a degree of acoustic transparency. Such a material should be structurally homogenous to allow the material to vibrate consistently throughout its shape across a broad frequency range, as well as lightweight enough to allow sound traveling through the air between the woofer **154**/tweeter **152** and the dispersion cone **106** to be sufficient to generate such vibrations. The surface of the material should also be sufficiently dense and smooth enough to reflect sound outward. Finally, the material should have sufficient internal damping that it does not continue to resonate once a force is no longer being applied. These combined requirements could be fulfilled by a range of materials. Given the additional requirements of being on a boat, being cost effective, water resistant, and durable, in an example embodiment the dispersion cone **106** is formed of injection-molded polypropylene.
- (37) In an example embodiment, the dispersion cone transition **126** may be thinned and/or made of a relatively more flexible material relative to a thickness between the radiating surface central

section **132** and the dispersion surface central section **122** and/or between the radiating surface surrounding section **134** and the dispersion surface surrounding section **124**. The dispersion cone transition **126** may then act like a speaker surround and allow the radiating surface central section **132** to resonate more freely relative to the radiating surface central section **132**.

(38) The ribs **108** are configured to present as small a profile as possible to the redirected sound. In addition, the ribs **108** may be composed of a relatively flexible material. Such a flexible material may flex and thereby provide greater freedom of movement for resonance of the dispersion cone **106**. For many of the same reasons injection-molded polypropylene is suitable for the dispersion cone **106**, injection-molded polypropylene is also suitable for the ribs **108**.

(39) FIG. 7 and FIG. 8 show sectional views of the dispersion cone **106**. Visible are the dispersion surface **120**, the dispersion surface central section **122**, the dispersion surface surrounding section **124**, the dispersion cone transition **126**, and a dispersion side inflection point **126D** defined by a dispersion side surface **126DS** of the dispersion cone transition **126**. Also visible are the forward-facing radiating surface **130**, the radiating surface central section **132**, the radiating surface surrounding section **134**, the dispersion cone transition **126**, and a radiating side inflection point **126R** defined by a radiating side surface **126RS** of the dispersion cone transition **126**. Optional reinforcing ribs **196** help maintain a shape of the dispersion cone **106**.

(40) The example dispersion cone transition **126** shown includes a dispersion side radially inner perimeter **126DSIP** that indicates a boundary between a smooth cross-sectional shape of the dispersion surface central section **122** and the smooth cross-sectional shape of the dispersion side surface **126DS** of the dispersion cone transition **126**. The example dispersion cone transition **126** also shows a dispersion side radially outer perimeter **126DSOP** that indicates a boundary between a smooth cross-sectional shape of the dispersion side surface **126DS** of the dispersion cone transition **126** and a smooth cross-sectional shape of the dispersion surface surrounding section **124**.

(41) The example dispersion cone transition **126** shown includes a radiating side radially inner perimeter **126RSIP** that indicates a boundary between a smooth cross-sectional shape of the radiating surface central section **132** and the smooth cross-sectional shape of the radiating side surface **126RS** of the dispersion cone transition **126**. The example dispersion cone **126** transition also shows a radiating side radially outer perimeter **126RSOP** that indicates a boundary between a smooth cross-sectional shape of the radiating side surface **126RS** of the dispersion cone transition **126** and a smooth cross-sectional shape of the radiating surface surrounding section **134**.

(42) FIG. 9 is another closeup view of the sectional view of FIG. 4 showing various groupings of streamlines. A Range streamlines (**A1a+A1b**; **A2a+A2b**) emanate from a driver **900** of the tweeter **152** and reflect off the dispersion surface central section **122** enroute to a listener. B Range streamlines (**B1a+B1b**; **B2a+B2b**) emanate from the woofer cone **152** and reflect off the dispersion surface central section **122** enroute to a listener. C Range streamlines (**C1a+C1b+C1c**; **C2a+C2b+C2c**) emanate from the woofer cone **152**, reflect off the dispersion surface surrounding section **124**, and then reflect off the baffle **104** enroute to a listener.

(43) FIG. 10 is a side view of the speaker assembly of FIG. 1 showing relatively short streamlines that converge at a relatively close point **1000** in space. As used herein, a streamline length starts at a point of origin (e.g., a baffle surface) and terminates at a point of convergence (such as a listener's ear). The dispersion cone **106** and the baffle **104** are configured such that a relatively short A Range streamline **A3a+A3b** has a relatively short A Range streamline length, a relatively short B Range streamline **B3a+B3b** has a relatively short B Range streamline length, and a relatively short C Range streamline **C3a+C3b+C3c** has a relatively short C Range streamline length. In the example embodiment shown, the relatively short A Range streamline length, the relatively short B Range streamline length, and the relatively short C Range streamline length are within four (4) inches of each other.

(44) FIG. 11 is a side view of the speaker assembly of FIG. 1 showing relatively long streamlines that converge at a relatively distant point **1000** in space. The dispersion cone **106** and the baffle **104**

are configured such that a relatively long A Range streamline $A4a+A4b$ has a relatively long A Range streamline length, a relatively long B Range streamline $B4a+B4b$ has a relatively long B Range streamline length, and a relatively long C Range streamline $C4a+C4b+C4c$ has a relatively long C Range streamline length. In the example embodiment shown, the relatively long A Range streamline length, the relatively long B Range streamline length, and the relatively long C Range streamline length are within four (4) inches of each other.

(45) In the example embodiment shown, the relatively short A Range streamline length, the relatively short B Range streamline length, and the relatively short C Range streamline length, and the relatively long A Range streamline length, the relatively long B Range streamline length, and the relatively long C Range streamline length are all within four (4) inches of each other.

(46) In an example embodiment, for all listening points, all A Range streamline lengths are within four (4) inches of each other. In an example embodiment, for all listening points, all B Range streamline lengths are within four (4) inches of each other. In an example embodiment, for all listening points, all C Range streamline lengths are within four (4) inches of each other.

(47) In various example embodiments, for all listening points, any two of all the A Range streamline lengths, all the B Range streamline lengths, and all the C Range streamline lengths are within four (4) inches of each other.

(48) In an example embodiment, for all listening points, all the A Range streamline lengths, all the B Range streamline lengths, and all the C Range streamline lengths are within four (4) inches of each other.

(49) Having the streamline lengths so close to each other throughout the sound field ensures a consistent sound experience regardless of the listener's position.

(50) For at least the reasons disclosed herein, the dispersion cone **106** and the baffle **104** of the speaker assembly **100** provide a more uniform and superior sound presentation for listeners at various positions relative to the speaker as well as those moving relative to the speaker.

Consequently, this represents an improvement in the art.

(51) While various embodiments of the present invention have been shown and described herein, it will be obvious that such embodiments are provided by way of example only. Numerous variations, swapping of features among embodiments, changes, and substitutions may be made without departing from the invention herein. Accordingly, it is intended that the invention be limited only by the spirit and scope of the appended claims.

Claims

1. An apparatus, comprising: a speaker; a baffle surrounding the speaker; and a dispersion cone positioned forward of, aligned with, and pointing toward the speaker and comprising a dispersion surface comprising: a dispersion surface central section; a dispersion surface surrounding section therearound; and a transition therebetween; wherein from a tip of the dispersion cone outward the dispersion surface central section defines a concave cross-sectional shape, the dispersion surface surrounding section defines a less concave cross-sectional shape than the concave cross-sectional shape of the dispersion surface central section, and the transition comprises an inflection point; and wherein a distance of each section of the dispersion surface forward of the speaker progressively increases with increasing radial distance from a radial center of the dispersion surface.
2. The apparatus of claim 1, wherein the cross-sectional shape of the dispersion surface surrounding section is straight.
3. The apparatus of claim 1, wherein the dispersion surface central section is configured to redirect sound waves emanating from a central region of the speaker radially outward and between the baffle and the dispersion surface surrounding section.
4. The apparatus of claim 1, wherein the dispersion surface surrounding section is configured to redirect sound waves emanating from a peripheral region of the speaker radially outward and

axially back toward the baffle surrounding the speaker.

5. The apparatus of claim 4, wherein a baffle reflecting surface of the baffle is configured to receive the sound waves redirected by the dispersion surface surrounding section and to redirect the sound waves radially outward and axially forward.

6. The apparatus of claim 5, wherein from an inner perimeter to an outer perimeter a cross-sectional shape of the baffle reflecting surface is straight.

7. The apparatus of claim 1, wherein the dispersion surface surrounding section is secured to the baffle via a plurality of ribs.

8. The apparatus of claim 1, wherein the dispersion cone further comprises a forward-facing radiating surface disposed opposite the dispersion surface, and wherein the dispersion cone is configured to act as a passive radiator to radiate sound waves impacting the dispersion surface from the forward-facing radiating surface directly to a surrounding environment.

9. The apparatus of claim 8, wherein the forward-facing radiating surface comprises: a radiating surface central section that corresponds to the dispersion surface central section and that comprises a concave overall shape; and a radiating surface surrounding section that corresponds to the dispersion surface surrounding section.

10. The apparatus of claim 9, wherein from the tip of the dispersion cone outward the radiating surface central section defines a convex cross-sectional shape that matches the concave cross-sectional shape of the dispersion surface central section; and wherein from a radiating surface surrounding section inner perimeter outward the radiating surface surrounding section defines a cross-sectional shape that matches the cross-sectional shape of the dispersion surface surrounding section.

11. The apparatus of claim 1, wherein the speaker comprises a two-way speaker comprising a tweeter and a second speaker, wherein both the tweeter and the second speaker are disposed concentric with the dispersion cone.

12. The apparatus of claim 11, wherein the dispersion surface surrounding section is radially aligned with a surround of the speaker or a perimeter of a cone of the second speaker.

13. An apparatus, comprising: a speaker; a baffle surrounding the speaker; and a dispersion cone positioned forward of, aligned with, and pointing toward the speaker, wherein the dispersion cone is configured to redirect sound waves emanating from a central region of the speaker radially outward, configured to redirect sound waves emanating from a peripheral region the speaker radially outward and axially back toward the baffle surrounding the speaker, and configured to act as a passive radiator to radiate sound waves emanating from the speaker via a resonance of the dispersion cone.

14. The apparatus of claim 13, wherein the dispersion cone is held concentric with the speaker via ribs secured to a perimeter of the dispersion cone.

15. The apparatus of claim 13, wherein the dispersion cone comprises a dispersion surface comprising a dispersion surface central section, a dispersion surface surrounding section therearound, and a transition therebetween; wherein from a tip of the dispersion cone outward the dispersion surface central section defines a concave cross-sectional shape, the dispersion surface surrounding section defines a less concave cross-sectional shape than the concave cross-sectional shape of the dispersion surface central section, and wherein the transition comprises an inflection point; and wherein the concave cross-sectional shape of the dispersion surface central section and the cross-sectional shape of the dispersion surface surrounding section both taper away from the speaker with increasing distance from a radial center of the dispersion surface.

16. The apparatus of claim 15, wherein the cross-sectional shape of the dispersion surface surrounding section is straight.

17. The apparatus of claim 15, wherein the wherein the dispersion cone comprises a radiating surface disposed opposite the dispersion surface, and wherein the radiating surface comprises: a radiating surface central section that corresponds to the dispersion surface central section and that

comprises a concave shape.

18. The apparatus of claim 17, wherein from the tip of the dispersion cone outward the radiating surface central section defines a convex cross-sectional shape that matches the concave cross-sectional shape of the dispersion surface central section.

19. The apparatus of claim 17, wherein the radiating surface further comprises radiating surface surrounding section that corresponds to the dispersion surface surrounding section and that from the tip of the dispersion cone outward defines a cross-sectional shape that matches the cross-sectional shape of the dispersion surface surrounding section.
