

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250271095

Kind Code

A1

Publication Date

August 28, 2025

Inventor(s)

YANG; Faan

CLIP AND PHOTOGRAPHY KIT

Abstract

Disclosed are a clip and a photography kit. The clip includes: a seat, a pressing plate and a rotation assembly. One end of the seat is a fixed clamping portion; the pressing plate rotatably is provided on the seat, one end of the pressing plate is a movable clamping portion, the pressing plate is provided with a protruding inclined surface, the protruding inclined surface has a highest point and a lowest point, and a continuous inclined surface is provided between the lowest point and the highest point of the protruding inclined surface. The rotation assembly is abutted against the protruding inclined surface through rotation. The fixed clamping portion is cooperated with the movable clamping portion to form a clamping slot, and the pressing plate is configured to rotate on the seat to open or close the clamping slot.

Inventors: YANG; Faan (Shenzhen, CN)

Applicant: SHENZHEN NEEWER TECHNOLOGY CO. LTD (Shenzhen, CN)

Family ID: 1000007756500

Assignee: SHENZHEN NEEWER TECHNOLOGY CO. LTD (Shenzhen, CN)

Appl. No.: 18/610661

Filed: March 20, 2024

Foreign Application Priority Data

CN 202420334154.3

Feb. 22, 2024

Publication Classification

Int. Cl.: F16M11/04 (20060101); F16B2/06 (20060101); G03B17/56 (20210101)

U.S. Cl.:

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] The present application claims priority to Chinese Patent Application No. 202420334154.3, filed on Feb. 22, 2024, the entire contents of which are incorporated herein by reference.

TECHNICAL FIELD

[0002] The present application relates to the technical field of photographic equipment, and in particular to a clip and a photography kit.

BACKGROUND

[0003] At present, the photography kit includes a clip and a handle, and the clip in the related art generally does not have the design of the self-locking function. When the clip clamps the rabbit cage that is accommodated with a mobile phone and people use the mobile phone to take pictures or record videos, the fingers are easy to touch and open the clip by mistake, so that the rabbit cage and the mobile phone installed in the rabbit cage may move or even fall because of losing the grip of the clip, that is, the current clip lacks the self-locking function, resulting in a problem of a low clamping security of the clip.

SUMMARY

[0004] The main purpose of the present application is to provide a clip, aiming to improve the clamping security of the clip.

[0005] In order to achieve the above purpose, the clip provided in the present application includes: a seat, a pressing plate and a rotation assembly; one end of the seat is a fixed clamping portion; the pressing plate rotatably is provided on the seat, one end of the pressing plate is a movable clamping portion, the pressing plate is provided with a protruding inclined surface, the protruding inclined surface has a highest point and a lowest point, and a continuous inclined surface is provided between the lowest point and the highest point of the protruding inclined surface; and the rotation assembly is abutted against the protruding inclined surface through rotation; the fixed clamping portion is cooperated with the movable clamping portion to form a clamping slot, and the pressing plate is configured to rotate on the seat to open or close the clamping slot; in response to that the clamping slot is closed and the rotation assembly is abutted against the protruding inclined surface through rotation, the movable clamping portion is configured to move towards the fixed clamping portion, and the movable clamping portion is pressed to lock the clip.

[0006] In an embodiment, the pressing plate is provided with a long through hole, a length of the long through hole extends towards the movable clamping portion, the rotation assembly is installed on the seat through the long through hole, and a rotation axis of the pressing plate is perpendicular to an extension direction of the long through hole.

[0007] In an embodiment, the rotation assembly includes: a fixed column and a knob, the fixed column is installed on the seat through the long through hole; and an abutting arm is provided on a circumferential direction of the knob, and the knob is configured to rotate to make the abutting arm be abutted against the protruding inclined surface.

[0008] In an embodiment, the rotation assembly further includes two limiting members, the two limiting members are provided on the fixed column and are arranged at intervals, the knob is installed on the fixed column and is provided between the two limiting members, and each limiting member is an elastic pad.

[0009] In an embodiment, a diameter of the long through hole is greater than a diameter of the fixed column.

[0010] In an embodiment, an extending arm is provided on the circumferential direction of the

knob, the extending arm is spaced apart from the abutting arm, and the extending arm is spaced apart from the protruding inclined surface at height.

[0011] In an embodiment, the pressing plate is provided with a limiting baffle configured for blocking the abutting arm to limit a rotation of the knob, and the extending arm is spaced apart from the limiting baffle at height.

[0012] In an embodiment, the pressing plate is rotatably connected to the seat through a rotation shaft, and the pressing plate is configured to rotate along the rotation shaft to drive the movable clamping portion to rotate, so as to open the clamping slot.

[0013] In an embodiment, one side of the seat close to the pressing plate is provided with a cavity, an elastic member is provided in the cavity, one end of the elastic member is abutted against the seat, the other end of the elastic member is abutted against the pressing plate, and the elastic member and the movable clamping portion are provided on two sides of the rotation shaft.

[0014] In an embodiment, one side of the pressing plate away from the seat is provided with a pressing structure, and the pressing structure and the movable clamping portion are respectively provided at the two sides of the rotation shaft.

[0015] In an embodiment, two rotation shafts are provided, and the two rotation shafts are in a same straight line and are arranged relative to two sides of the pressing plate.

[0016] In an embodiment, the protruding inclined surface includes: an inclined surface and a spiral surface, the inclined surface is a continuous straight inclined surface, and the inclined surface has a lowest point and a highest point; and the spiral surface is a continuous arc inclined surface, and a lowest point of the spiral surface is smoothly connected to the highest point of the inclined surface.

[0017] The present application also provides a photography kit, including a handle and the clip, and the clip is installed on the handle.

[0018] In the present application, the clip includes a seat, a pressing plate and a rotation assembly, one end of the seat is a fixed clamping portion, the pressing plate is installed on the seat, and one end of the pressing plate is a movable clamping portion. The pressing plate is provided with a protruding inclined surface having the highest point and the lowest point, and a continuous inclined surface is provided between the lowest point and the highest point of the protruding inclined surface. The rotation assembly is abutted against the protruding inclined surface through rotation, and the fixed clamping portion is cooperated with the movable clamping portion to form the clamping slot. When the rotation assembly is abutted against the protruding inclined surface through rotation, the rotation assembly resists the pressing plate and exerts a pressure on the pressing plate, so that the pressing plate is squeezed by the rotation assembly and the movable clamping portion moves towards the fixed clamping portion, making the clamping force of the clamping slot larger and tighter. At the same time, the pressing plate has a pressure reaction force on the rotation assembly, which makes the rotation assembly not easy to be rotated at this time, and the rotation assembly can be relatively stable in this position, so as to realize the locking of the clip and improve the clamping security of the clip.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0019] In order to illustrate the technical solutions in the embodiments of the present application or in the related art more clearly, the following briefly introduces the accompanying drawings required for the description of the embodiments or the related art. Obviously, the drawings in the following description are only part of embodiments of the present application. For those skilled in the art, other drawings can also be obtained according to the structures shown in these drawings without any creative effort.

[0020] FIG. 1 is a schematic structural view of a photography kit according to an embodiment of

the present application.

[0021] FIG. 2 is a schematic structural view of a clip according to an embodiment of the present application.

[0022] FIG. 3 is a schematic structural view of a seat according to an embodiment of the present application.

[0023] FIG. 4 is a schematic structural view of a pressing plate according to an embodiment of the present application.

[0024] FIG. 5 is a schematic structural view of a knob according to an embodiment of the present application.

[0025] FIG. 6 is a schematic structural view of the photography kit according to an embodiment of the present application.

[0026] FIG. 7 is a schematic structural view of the photography kit according to an embodiment of the present application.

[0027] FIG. 8 is a schematic structural view of the photography kit according to an embodiment of the present application.

[0028] FIG. 9 is a schematic structural view of the photography kit according to an embodiment of the present application.

[0029] FIG. 10 is a schematic structural view of a protruding inclined surface according to an embodiment of the present application.

[0030] FIG. 11 is a schematic structural view of the protruding inclined surface according to an embodiment of the present application.

[0031] FIG. 12 is a schematic structural view of the protruding inclined surface according to an embodiment of the present application.

[0032] The realization of the objective, functional characteristics, and advantages of the present application are further described with reference to the accompanying drawings.

DETAILED DESCRIPTION OF THE EMBODIMENTS

[0033] The technical solutions of the embodiments of the present application will be described in more detail below with reference to the accompanying drawings. It is obvious that the embodiments to be described are only some rather than all of the embodiments of the present application. All other embodiments obtained by persons skilled in the art based on the embodiments of the present application without creative efforts shall fall within the scope of the present application.

[0034] It should be noted that all directional indications (such as up, down, left, right, front, back, etc.) in the embodiments of the present application are only used to explain the relative positional relationship, the movement situation, etc. among various assemblies under a certain posture as shown in the drawings. If the specific posture changes, the directional indication also changes accordingly.

[0035] In addition, the descriptions of “first”, “second”, etc. are only for the purpose of description, and should not be construed as indicating or implying relative importance or implicitly indicating the number of technical features indicated. Thus, a feature delimited with “first”, “second” may expressly or implicitly include at least one of that feature. Besides, the meaning of “and/or” appearing in the application includes three parallel scenarios. For example, “A and/or B” includes only A, or only B, or both A and B. In addition, the technical solutions between the various embodiments can be combined with each other, but must be based on the realization by those skilled in the art. When the combination of technical solutions is contradictory or cannot be realized, it should be considered that the combination of such technical solutions does not exist or fall within the scope of protection claimed in the present application.

[0036] The present application provides a clip **100**, aiming to improve the clamping security of the clip **100**.

[0037] In an embodiment of the present application, with reference to FIG. 1 to FIG. 2, the clip **100**

includes a seat **10**, a pressing plate **20** and a rotation assembly **30**. One end of the seat **10** is a fixed clamping portion **11**, and the pressing plate **20** is rotatably installed at the seat **10**. One end of the pressing plate **20** is a movable clamping portion **21**, and the pressing plate **20** is provided with a protruding inclined surface **22** having a highest point and a lowest point. A continuous inclined surface is provided between the highest point and the lowest point of the protruding inclined surface **22**, and the rotation assembly **30** is abutted against the protruding inclined surface **22** through rotation. The fixed clamping portion **11** is cooperated with the movable clamping portion **21** to form a clamping slot, and the pressing plate **20** rotates on the seat **10** to open the clamping slot. When the clamping slot is closed and the rotation assembly **30** is abutted against the protruding inclined surface **22** through rotation, the movable clamping portion **21** moves towards the fixed clamping portion **11** and presses the movable clamping portion **21** to lock the clip **100**. [0038] It should be understood that the fixed clamping portion **11** is fixed on the seat **10**, and the movable clamping portion **21** is fixed on the pressing plate **20**. There is a gap between the pressing plate **20** and the seat **10**, and the pressing plate **20** can be driven to move towards the seat **10** by applying a force to the pressing plate **20** towards the seat **10**, so as to drive the movable clamping portion **21** to move towards the fixed clamping portion **11**, so that the space of the clamping slot is compressed, and the clamped mobile phone **6** is locked. The rotation assembly **30** can be abutted against the protruding inclined surface **22** through rotation. When the rotation assembly **30** is abutted against the protruding inclined surface **22**, the rotation assembly **30** applies pressure towards the seat **10** to the pressing plate **20**, and the pressing plate **20** applies a reaction force to the rotation assembly **30**, thus the abutting force between the rotation assembly **30** and the protruding inclined surface **22** increases, and the static friction between the rotation assembly **30** and protruding inclined surface **22** increases. The rotation assembly **30** will not easily slide off from the highest point of the protruding inclined surface **22**, so as to clamp and lock the clip **100**.

[0039] In an embodiment, the rotation assembly **30** is a knob **33** with a rotation arm, and the knob **33** rotates to drive the rotation arm to rotate around its center. The rotation arm can be abutted against the protruding inclined surface **22** after being rotated. The rotation arm continuously applies pressure to the protruding inclined surface **22** during the rotation process, so that the movable clamping portion **21** moves towards the fixed clamping portion **11**, thereby reducing the space of the clamping slot, thus achieving the self-locking effect of the clip **100**.

[0040] In an embodiment, the height of the rotation assembly **30** is fixed, that is, the rotation assembly **30** can only rotate at one horizontal height. Since the continuous inclined surface is between the lowest point and the highest point of the protruding inclined surface **22**, when rotating at the fixed height, the rotation assembly **30** will be abutted against a certain point of the protruding inclined surface **22**. When abutted against the protruding inclined surface **22**, the rotation assembly **30** applies pressure to the pressing plate **20** and drives the movable clamping portion **21** to move towards the fixed clamping portion **11** to achieve the self-locking of the clip **100**.

[0041] In an embodiment, the height of the rotation assembly **30** is not fixed, and the rotation assembly **30** may be a screw. When the rotation assembly **30** rotates in one direction, it can move toward the pressing plate **20**, and when the rotation assembly **30** rotates in another direction, it can move away from the pressing plate **20**. In this way, the rotation assembly **30** can rotate to move towards the pressing plate **20** and be abutted against the protruding inclined surface **22**, so that the rotation assembly **30** can apply pressure to the pressing plate **20** to achieve the self-locking of the clip **100**.

[0042] Further, referring to FIG. 1 to FIG. 4, in an embodiment, the pressing plate **20** is provided with a long through hole **23**, the length of the long through hole **23** extends towards the movable clamping portion **21**, the rotation assembly **30** is installed at the seat **10** through the long through hole **23**, and the rotation axis of the pressing plate **20** is perpendicular to the extension direction of the long through hole **23**.

[0043] In this way, the long through hole **23** is provided on the pressing plate **20**, and the rotation

assembly **30** can be installed on the seat **10** through the long through hole **23**, so that when the rotation assembly **30** applies pressure to the pressing plate **20**, and the length of the long through hole **23** extends towards the movable clamping portion **21**. In this way, the pressing plate **20** does not easily touch the fixed column **31** when rotating, and the reaction force of the pressing plate **20** to the rotation assembly **30** can be transferred to the seat **10** through the seat **10**, so that the rotation assembly **30** can be more stable at one height, avoiding the deviation of the height of the rotation assembly **30** and affecting the self-locking function of the clip **100**.

[0044] In an embodiment, one side of the seat **10** close to the pressing plate **20** is provided with an installation column, and the rotation shaft **40** of the rotation assembly **30** breaks through the long through hole **23** and is inserted on the installation column, which is similar to nailing. The interference fit between the installation column and the rotation shaft **40** makes it easier to install the rotation assembly **30** on the seat **10**, which also prevents the rotation assembly **30** from displacing too much in height, further improving the self-locking performance of the clip **100**.

[0045] In an embodiment, referring to FIG. 4, the long through hole **23** can be with shapes such as annular groove or ellipse, so that it is relatively easy to process the long through hole **23** on the pressing plate **20**, the processing cost of the pressing plate **20** is reduced, and the annular groove or elliptical shape can also provide a larger avoidance area of the long through hole **23**. The fixed column **31** interferes with the edge of the long through hole **23**.

[0046] Further, referring to FIG. 1 to FIG. 5, in an embodiment, the rotation assembly **30** includes a fixed column **31** and a knob **33**. The fixed column **31** is installed at the seat **10** through the long through hole **23**, an abutting arm **331** is arranged in a circumferential direction of the knob **33**, and the knob **33** is configured to rotate to make the abutting arm **331** be abutted against the protruding inclined surface **22**.

[0047] It should be understood that the fixed column **31** is inserted on the seat **10** through the long through hole **23**, and the knob **33** rotates with the fixed column **31** as the rotation shaft **40**, so that when the pressing plate **20** rotates on the seat **10**, the fixed column **31** will not easily interfere with the edge of long through hole **23**.

[0048] In an embodiment, the length of the abutting arm **331** is less than the maximum radius of the protruding inclined surface **22** but greater than the minimum radius, so that the abutting arm **331** falls exactly on the protruding inclined surface **22** after rotation, so as to avoid the outline of the entire clip **100** being affected due to the excessive length of the abutting arm **331**, and avoid the problem that the abutting arm **331** is too short to be abutted against the protruding inclined surface **22**.

[0049] Further, referring to FIG. 1 to FIG. 4, in an embodiment, the rotation assembly **30** further includes a limiting member **32**, and two limiting members **32** are provided on the fixed column **31** and spaced apart. The knob **33** is installed on the fixed column **31** and is located between the two limiting members **32**, and the limiting member **32** is an elastic pad.

[0050] In this way, the two limiting members **32** are provided on the fixed column **31**, and the two limiting members **32** are abutted against the upper and lower ends of the knob **33** to limit the displacement of the knob **33** on the height of the fixed column **31**, and prevent the gap after the knob **33** is installed on the fixed column **31** due to processing and assembly, that is, the knob **33** cannot be channeled in the axial direction of the fixed column **31**, so as to avoid the excessive channeling momentum of the knob **33** in the axial direction of the fixed column **31**, which may otherwise cause the extrusion effect of the pressing plate **20** to deteriorate, and affects the self-locking effect of the clip **100**.

[0051] In an embodiment, in order to facilitate the installation and adjustment of the two limiting members **32** on the fixed column **31**, the limiting member **32** adopts an elastic material, so that the limiting member **32** can be installed on the fixed column **31** through the elastic performance, and its elastic performance can also absorb the gap that occurs due to the processing and assembly of the knob **33**, which further improve the self-locking performance of the clip **100**.

[0052] Further, referring to FIG. 1 to FIG. 4, in an embodiment, the diameter of the long through hole **23** is greater than the diameter of the fixed column **31**.

[0053] In this way, when the pressing plate **20** rotates on the seat **10**, the long through hole **23** does not interfere with the fixed column **31** due to the rotation of the pressing plate **20**.

[0054] In an embodiment, in order to prevent the long through hole **23** interfere with the fixed column **31** when the rotation angle of the pressing plate **20** is relatively large, the long through hole **23** adopts an elliptical hole or a long strip-shaped round hole, and the long axis direction of the long through hole **23** is perpendicular to the direction of rotation shaft of the pressing plate **20**, so that there is large gap between the long through hole **23** and the fixed column **31**. Even if the rotation angle of the pressing plate **20** is too large, it will not interfere with the fixed column **31**. At the same time, the area can be smaller than the round hole, so as to avoid more dust, garbage, etc. falling into the seat **10**.

[0055] Further, referring to FIG. 1 to FIG. 5, in an embodiment, an extending arm **332** is provided on a circumferential direction of the knob **33**. The extending arm **332** is spaced apart from the abutting arm **331**, and the extending arm **332** is spaced apart from the protruding inclined surface **22** at height.

[0056] In this way, the extending arm **332** is provided on the knob **33**, the length of the extending arm **332** is longer than the length of the abutting arm **331**, so that when the knob **33** rotates, the force acting on the tail end of the extending arm **332** can be more labor-saving, which is convenient for the user to operate the knob **33**. At the same time, the extending arm **332** is spaced apart from the protruding inclined surface **22** at height to prevent from interfering with the protruding inclined surface **22** when the knob **33** rotates, which may otherwise affect the knob **33** to rotate further.

[0057] In an embodiment, the angle between the extending arm **332** and the abutting arm **331** is at **180°**, that is, the extending arm **332** and the abutting arm **331** are in a same straight line, so that the angle between the extending arm **332** and the abutting arm **331** is prevented from being too small to operate the extending arm **332**, which can also improve the aesthetics of the knob **33** at the same time.

[0058] In an embodiment, the height of the bottom of the extending arm **332** gradually decreases along the end of its tail end towards the rotation center of the knob **33** to form an inclined surface, so that the extending arm **332** can better avoid the protruding inclined surface **22**, and the length of the extending arm **332** is retained as much as possible, thus the structure of the extending arm **332** is guaranteed to meet the use requirements.

[0059] Further, referring to FIG. 1 to FIG. 3, in an embodiment, the pressing plate **20** is provided with a limiting baffle **24** configured to block the abutting arm **331** to limit the rotation of the knob **33**, and the extending arm **332** is spaced apart from the limiting baffle **24** at height.

[0060] In this way, the knob **33** will be blocked by the limiting baffle **24** after one rotation, that is, the knob **33** can only rotate for a maximum of one rotation on the pressing plate **20** to avoid over-rotation of the knob **33**.

[0061] In an embodiment, the position of the limiting baffle **24** on the pressing plate **20** is close to the lowest point of the protruding inclined surface **22**. One side of the knob **33** is the limiting baffle **24**, and the other side of the knob **33** is the lowest point of the protruding inclined surface **22**. In this way, the knob **33** can completely contact the entire protruding inclined surface **22** through the unidirectional rotation, avoiding the limiting baffle **24** blocking the knob **33** on the protruding inclined surface **22**, so that the knob **33** needs to rotate in two directions to be abutted against a higher point on the protruding inclined surface **22**.

[0062] Further, referring to FIG. 6 to FIG. 9, in an embodiment, the pressing plate **20** is rotatably connected to the seat **10** through the rotation shaft **40**, and the pressing plate **20** can be rotated along the rotation shaft **40** to drive the movable clamping portion **21** to rotate, thereby opening the clamping slot.

[0063] It should be understood that in order to realize the clamping and self-locking function of the

clip **100**, the pressing plate **20** needs to be rotated to open the clamping slot, and the clip **100** is locked by the rotation assembly **30** after the clamping is completed. As shown in FIG. **6**, when the clip **100** is in the initial state, the clamping slot is not opened. As shown in FIG. **7** to FIG. **8**, the first step of clamping is to press one end of the pressing plate **20** away from the movable clamping portion **21**, so that one end of the pressing plate **20** close to the movable clamping portion **21** up-warps to fully open the clamping slot, and one edge of the mobile phone rabbit cage **5** is put in. As shown in FIG. **9**, the second step is to return the pressing plate **20** to its original position, so that the clamping slot is closed again and clamp the edge of the mobile phone rabbit cage **5**. In the last step, the rotation assembly **30** is rotated to abut against the protruding inclined surface **22**, so that the rotation assembly **30** applies pressure to the pressing plate **20**, and the pressing plate **20** moves towards the seat **10** to reduce the space of the clamping slot. In this way, the clamping slot can clamp the edge of the mobile phone rabbit cage **5**, and at the same time, there is an interaction force between the rotation assembly **30** and the protruding inclined surface **22**, and the static friction between the two is larger. The rotation assembly **30** will not easily slide from the abutting point, so as to clamp and lock the clip **100**.

[0064] In this way, the pressing plate **20** is connected to the base plate through the rotation shaft **40**, so that the pressing plate **20** can rotate around the rotation shaft **40** to make one end of the movable clamping portion **21** up-warp, and the clamping slot is opened, making it convenient to put in the mobile phone rabbit cage **5**.

[0065] In an embodiment, in order to avoid that the pressure is too large to cause the rotation shaft **40** to break when the rotation assembly **30** rotates to apply pressure to the pressing plate **20**, the rotation shaft **40** adopts the material with better rigidity, so that the rotation shaft **40** will not be prone to fracture even if it is bent frequently.

[0066] Further, referring to FIG. **3** and FIG. **6** to FIG. **9**, in an embodiment, one side of the seat **10** close to the pressing plate **20** is provided with a cavity **12**, and an elastic member is provided in the cavity **12**. One end of the elastic member **121** is abutted against the seat **10**, and the other end of the elastic member **121** is abutted against the pressing plate **20**. The elastic member **121** and the movable clamping portion **21** are located on both sides of the rotation shaft **40**.

[0067] In this way, the elastic member **121** is provided between the seat **10** and the pressing plate **20**, and the elastic member **121** and the movable clamping portion **21** are provided on both sides of the rotation shaft **40**, so that when one end of the movable clamping portion **21** up-warps, the pressing plate **20** will squeeze the elastic member **121**. When the pressing plate **20** needs to be restored, the elastic member **121** will release elastic performance to rebound the pressing plate **20**, and the elastic member **121** will also abut against the pressing plate **20**, providing a force blocking the pressing plate **20** from up-warping, which avoids the misoperation that opens the clamping slot.

[0068] In an embodiment, in order to make the clip **100** cheaper to produce and to facilitate the replacement of the elastic member **121**, the elastic member **121** is a spring.

[0069] Further, referring to FIG. **1** to FIG. **2** and FIG. **6** to FIG. **9**, in an embodiment, a pressing structure **25** is provided on one side of the pressing plate **20** away from the seat **10**, and the pressing structure **25** and the movable clamping portion **21** are respectively located on two sides of the rotation shaft **40**.

[0070] In this way, the pressing structure **25** and the movable clamping portion **21** are located on both sides of rotation shaft **40**, that is, the pressing structure **25** and the elastic member **121** are respectively located on the front and back of the pressing plate **20**, so that when the user presses the pressing plate **20** to up-warp the pressing plate **20**, the pressing structure **25** provides the user with a point of force, so as to avoid an occasion where the user does not press the pressing plate **20** hard and causes the slip of hands when the elastic member **121** rebounds too strongly.

[0071] In an embodiment, in order to make pressing structure **25** more suitable for habits of human use, an inclined surface is provided on the pressing structure **25**, so that the user's finger can be placed on the inclined surface of the pressing structure **25**. When the pressing plate **20** up-warps

and the pressing structure **25** sinks into the seat **10**, the inclined surface becomes a horizontal surface due to the rotation, and the fingers can exert force on this surface relatively easily to maintain the up-warping of the pressing plate **20**.

[0072] Further, referring to FIG. **1** to FIG. **4**, in an embodiment, two rotation shafts **40** are provided in the same straight line and relative to the two sides of the pressing plate **20**.

[0073] In this way, two rotation shafts **40** are provided in the same straight line and relative to the two sides of the pressing plate **20**, so that the length of the rotation shaft **40** is greatly reduced, which not only maintains the rotation and support function of the rotating shaft **40**, but also avoids the situation where the rotating shaft **40** is easy to be squeezed and lead to fracture due to excessive length.

[0074] In an embodiment, in order to facilitate the installation of rotation shaft **40**, the two sides of the pressing plate **20** are provided with hinged lugs. The two hinged lugs are first aligned with the inserting hole of the rotation shaft **40** on both sides on the seat **10**, and two rotation shafts **40** are inserted respectively to connect to the seat **10** and the pressing plate **20**.

[0075] Further, referring to FIG. **10** to FIG. **12**, in an embodiment, the protruding inclined surface **22** includes an inclined surface **221** and a spiral surface **222**. The inclined surface **221** is a continuous straight inclined surface and has a lowest point and a highest point. The spiral surface **222** is a continuous arc inclined surface, and the lowest point of the spiral surface **222** is smoothly connected to the highest point of the inclined surface **221**.

[0076] It should be understood that in this embodiment, the protruding inclined surface **22** includes the inclined surface **221** and the spiral surface **222**, or the protruding inclined surface **22** can also have only one of the inclined surface **221** and the spiral surface **222**.

[0077] In this way, the highest part of the inclined surface **221** is connected to the lowest part of the spiral surface **222**, and the spiral surface **222** continues to be raised upwards by the inclined surface **221**, which can increase the rotation formation of the knob **30**. If an axial clearance of the knob **30** in the direction of the fixed column **31** appears due to use, and the height of the inclined surface **221** is not enough, it can continue to slide towards the spiral surface **222**.

[0078] In an embodiment, the protruding inclined surface **22** is only provided with the spiral surface **222**, and the spiral surface **222** is bounded by the long through hole **23**. The rotation assembly **30** is abutted against the lowest point of the spiral surface **222**, and the rotation assembly **30** can be abutted against the spiral surface **222** when rotating, so as to achieve the self-locking effect of the clip **100**, so that the abutting of the rotation assembly **30** and the protruding inclined surface **22** is smoother, which makes it easier for the rotation assembly **30** to rotate.

[0079] In an embodiment, the protruding inclined surface **22** is only provided with the inclined surface **221**, and the inclined surface **221** is provided with two segments. The highest points of the two segments of the inclined surface **221** are connected to form a triangular protrusion on the pressing plate **20**, and the rotation assembly **30** can be abutted against the inclined surface **221** by rotation to achieve the self-locking effect of the clip **100**, so that the inclined surface **221** is easier to form on the pressing plate **20**, which is convenient for the production of the clip **100**.

[0080] The present application also provides a photography kit **200**, including a handle **210** and a clip **100**, the specific structure of the clip **100** refers to the above-mentioned embodiments. Since the photography kit **200** adopts all the technical solutions of all the above-mentioned embodiments, it has at least all the beneficial effects brought by the technical solutions of the above-mentioned embodiments, which will not be repeated herein.

[0081] The above descriptions are only embodiments of the present application, and are not intended to limit the scope of the present application. Under the inventive concept of the present application, any equivalent structural transformations made by using the contents of the description and drawings of the present application, or direct/indirect applications in other related technical fields, are included in the scope of the present application.

Claims

1. A clip, comprising: a seat, wherein one end of the seat is a fixed clamping portion; a pressing plate rotatably provided on the seat, wherein one end of the pressing plate is a movable clamping portion, the pressing plate is provided with a protruding inclined surface, the protruding inclined surface has a highest point and a lowest point, and a continuous inclined surface is provided between the lowest point and the highest point of the protruding inclined surface; and a rotation assembly configured to be abutted against the protruding inclined surface through rotation; wherein the fixed clamping portion is cooperated with the movable clamping portion to form a clamping slot, and the pressing plate is configured to rotate on the seat to open or close the clamping slot; in response to that the clamping slot is closed and the rotation assembly is abutted against the protruding inclined surface through rotation, the movable clamping portion is configured to move towards the fixed clamping portion, and the movable clamping portion is pressed to lock the clip.
2. The clip of claim 1, wherein the pressing plate is provided with a long through hole, a length of the long through hole extends towards the movable clamping portion, the rotation assembly is installed on the seat and passing through the long through hole, and a rotation axis of the pressing plate is perpendicular to an extension direction of the long through hole.
3. The clip of claim 2, wherein the rotation assembly comprises: a fixed column installed on the seat through the long through hole; and a knob, wherein an abutting arm is provided on a circumferential direction of the knob, and the knob is configured to rotate to make the abutting arm be abutted against the protruding inclined surface.
4. The clip of claim 3, wherein the rotation assembly further comprises two limiting members, the two limiting members are provided on the fixed column and are arranged at intervals, the knob is installed on the fixed column and is provided between the two limiting members, and each limiting member is an elastic pad.
5. The clip of claim 2, wherein a diameter of the long through hole is greater than a diameter of the fixed column.
6. The clip of claim 3, wherein an extending arm is provided on the circumferential direction of the knob, the extending arm is spaced apart from the abutting arm, and the extending arm is spaced apart from the protruding inclined surface at height.
7. The clip of claim 6, wherein the pressing plate is provided with a limiting baffle configured for blocking the abutting arm to limit a rotation of the knob.
8. The clip of claim 1, wherein the pressing plate is rotatably connected to the seat through a rotation shaft, and the pressing plate is configured to rotate along the rotation shaft to drive the movable clamping portion to rotate, so as to open or close the clamping slot.
9. The clip of claim 8, wherein one side of the seat close to the pressing plate is provided with a cavity, an elastic member is provided in the cavity, one end of the elastic member is abutted against the seat, the other end of the elastic member is abutted against the pressing plate, and the elastic member and the movable clamping portion are provided on two opposite ends of the rotation shaft.
10. The clip of claim 9, wherein one side of the pressing plate away from the seat is provided with a pressing structure, and the pressing structure and the movable clamping portion are respectively provided at the two opposite ends of the rotation shaft.
11. The clip of claim 8, wherein two rotation shafts are provided, and the two rotation shafts are in a same straight line and are arranged relative to two sides of the pressing plate.
12. The clip of claim 8, wherein the protruding inclined surface comprises: an inclined surface, wherein the inclined surface is a continuous straight inclined surface, and the inclined surface has a lowest point and a highest point; and a spiral surface, wherein the spiral surface is a continuous arc inclined surface, and a lowest point of the spiral surface is smoothly connected to the highest point of the inclined surface.

13. A photography kit, comprising a handle and the clip of claim 1, wherein the clip is installed on the handle.
