

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250271315

Kind Code

A1

Publication Date

August 28, 2025

Inventor(s)

D'SOUZA; Riseley

APPARATUS AND METHOD FOR MEASURING TORSION

Abstract

A system and method for method for measuring torsion on a rotating shaft are disclosed. The method comprises: obtaining two or more optical encoder tapes or magnetic of a predetermined pattern; securing the two or more tapes a predetermined distance apart on a shaft; for each of the one of the two or more tapes, placing a corresponding sensor proximate each tape; sensing a signal from for each of the one of the two or more tapes to obtain corresponding sensor data; and computing power from the sensor data. The system comprises a first magnetic tape and a second magnetic tape secured on the rotating shaft a predetermined distance apart, a first Hall effect sensor and a second Hall effect sensor placed proximate to the first magnetic tape and the second magnetic tape respectively, and a computing device for computing power output from received sensor data.

Inventors: D'SOUZA; Riseley (Richmond, CA)

Applicant: Iotella Solutions Inc. (Richmond, CA)

Family ID: 1000007767269

Appl. No.: 18/590791

Filed: February 28, 2024

Publication Classification

Int. Cl.: G01L3/10 (20060101); G01R33/07 (20060101)

U.S. Cl.:

CPC G01L3/102 (20130101); G01R33/07 (20130101);

Background/Summary

TECHNICAL FIELD

[0001] The specification relates generally to apparatuses and methods of measuring torsion generally and in particular to a non-contact apparatus and method of measuring torsion in a shaft.

BACKGROUND

[0002] Torsion is a measure of twisting to an object resulting from applied torque, such as that observed in rotating shafts. The measurement of torsion has been traditionally done using strain gauges. A strain gauge utilizes a sensor whose electrical resistance varies as a function of applied force.

[0003] Other torsion meters and associated apparatuses and methods of measuring torsion are also known. These methods of torsion measurement, particularly for rotating shafts often rely on contact sensors or magnetic pickup. In one set of known torsion meters, contact sensors are used detect phase displacement that is proportional to the torsion between two or more triggers placed at distinct locations on the shaft. A disadvantage of contact torsion sensors is that they suffer wear due to friction.

[0004] Other disadvantages include the difficulty of retrofitting the sensors onto existing machines, and limited angular resolution.

[0005] A magnetic pickup torsion sensing system, described in U.S. Pat. No. 4,450,729, uses differential magnetic resistor sensors for non-contact measurement. However, the device still requires retrofitting of toothed wheels onto the shaft. Another embodiment described in the aforementioned patent uses inductive sensors instead of magnetic resistors. However, while useful when installed upon manufacture of the shaft, the non-contact magnetic pickup or inductive sensor detection systems are only practical at moderate rotation speeds. Moreover, toothed wheels, are difficult to manufacture uniformly, so that the toothed wheel-based devices have limited resolution. Magnetic pick-up detectors are also limited in high-speed applications, and spurious signals may be produced due to operating environment conditions such as electromagnetic interference and high temperatures.

[0006] Accordingly, although basic approaches for building torsion meters for measuring torsion are known, improvements are desired. It is desirable to improve upon one or more of efficiency, cost, ease of retrofitting, resolution and speed.

SUMMARY OF THE DISCLOSURE

[0007] In accordance with one aspect of the present disclosure, there is provided, a method for measuring torsion on a shaft. The method includes: obtaining a first and a second tape; securing the first tape and the second tape on the shaft, a predetermined distance apart; placing a first sensor proximate the first tape and placing a second sensor proximate the second tape; sensing a signal from each of the first tape and the second tape using the first sensor and the second sensor respectively to obtain corresponding sensor data; and computing power from the sensor data.

[0008] In accordance with another aspect of the present disclosure, there is provided, a system for measuring torsion on a rotating shaft, the system including: a first encoder tape secured on the rotating shaft; a second encoder tape secured on the rotating shaft a predetermined distance away from the first encoder tape; a first optical sensor disposed proximate the first encoder tape; a second optical sensor disposed proximate the second encoder tape; and a computing device including a processor and memory, the memory for storing instructions for computing at least one of twist angle, torque and power in electrical communication with the first optical sensor and the second optical sensor, wherein the first encoder tape and the second encoder tape comprise a first and second pattern respectively and wherein the first optical sensor and the second optical sensor transmit data to the computing device indicative of rotational speed for the first encoder tape and second encoder tape respectively, and wherein the computing device computes power from the sensor data.

[0009] In accordance with yet another aspect of the present disclosure, there is provided, a system

for measuring torsion on a rotating shaft, the system including: a first magnetic tape secured on the rotating shaft; a second magnetic tape secured on the rotating shaft a predetermined distance away from the first magnetic tape; a first Hall effect sensor disposed proximate the first magnetic tape; a second Hall effect sensor disposed proximate the second magnetic tape; and a computing device including a processor and memory, the memory for storing instructions for computing at least one of twist angle, torque and power in electrical communication with the first and second magnetic sensors, wherein the first and second Hall effect sensors transmit sensor data to the computing device indicative of rotational speed for the first magnetic tape and second magnetic tape respectively, and wherein the computing device computes power from the sensor data.

[0010] Other technical advantages may become readily apparent to one of ordinary skill in the art after review of the following figures and description.

Description

BRIEF DESCRIPTIONS OF THE DRAWINGS

[0011] For a better understanding of the embodiments described herein and to show more clearly how the embodiments may be carried into effect, reference will now be made, by way of example only, to the accompanying drawings in which:

[0012] FIG. 1 is a schematic block diagram representation of a non-contact non-intrusive system for measuring torsion on a rotating shaft using encoder tapes and corresponding optical sensors, in one embodiment of the present disclosure;

[0013] FIG. 2 is a schematic block diagram of several hardware and data forming part of the computing device shown as part of the system of FIG. 1;

[0014] FIG. 3 is a flowchart of a method for measuring torsion on a rotating shaft using the encoder tapes and corresponding optical sensors of the system of FIG. 1; and

[0015] FIG. 4 is a schematic block diagram representation of a system for measuring torsion on a rotating shaft using magnetic tapes and corresponding Hall effect sensors, in another embodiment of the present disclosure.

[0016] Unless otherwise specifically noted, articles depicted in the drawings are not necessarily drawn to scale.

DETAILED DESCRIPTION

[0017] Directional terms such as “top,” “bottom,” “upwards,” “downwards,” “vertically,” and “laterally” are used in the following description for the purpose of providing relative reference only, and are not intended to suggest any limitations on how any article is to be positioned during use, or to be mounted in an assembly or relative to an environment. The use of the word “a” or “an” when used herein in conjunction with the term “comprising” may mean “one,” but it is also consistent with the meaning of “one or more,” “at least one” and “one or more than one.” Any element expressed in the singular form also encompasses its plural form. Any element expressed in the plural form also encompasses its singular form. The term “plurality” as used herein means more than one, for example, two or more, three or more, four or more, and the like.

[0018] In this disclosure, the terms “comprising”, “having”, “including”, and “containing”, and grammatical variations thereof, are inclusive or open-ended and do not exclude additional, un-recited elements and/or method steps. The term “consisting essentially of” when used herein in connection with a composition, use or method, denotes that additional elements, method steps or both additional elements and method steps may be present, but that these additions do not materially affect the manner in which the recited composition, method, or use functions. The term “consisting of” when used herein in connection with a composition, use, or method, excludes the presence of additional elements and/or method steps.

[0019] For clarity of illustration, where considered appropriate, reference numerals may be

repeated among the Figures to indicate corresponding or analogous elements. In addition, numerous specific details are set forth in order to provide a thorough understanding of the embodiment or embodiments described herein. However, it will be understood by those of ordinary skill in the art that the embodiments described herein may be practiced without these specific details. In other instances, well-known methods, procedures and components have not been described in detail so as not to obscure the embodiments described herein. It should be understood at the outset that, although embodiments are illustrated in the figures and described below, the principles of the present disclosure may be implemented using any number of techniques, whether currently known or not. The present disclosure should in no way be limited to the implementations and techniques illustrated in the drawings and described in this disclosure.

[0020] Various terms used throughout the present description may be read and understood as follows, unless the context indicates otherwise: “or” as used throughout is inclusive, as though written “and/or”; singular articles and pronouns as used throughout include their plural forms, and vice versa; similarly, gendered pronouns include their counterpart pronouns so that pronouns should not be understood as limiting anything described herein to use, implementation, performance, etc. by a single gender; “exemplary” should be understood as “illustrative” or as a non-limiting example, and not necessarily as “preferred” over other embodiments. Further definitions for terms may be set out herein; these may apply to prior and subsequent instances of those terms, as will be understood from a reading of the present description. It will also be noted that the use of the term “a” or “an” will be understood to denote “at least one” in all instances unless explicitly stated otherwise or unless it would be understood to be obvious that it must mean “one”.

[0021] Modifications, additions, or omissions may be made to the systems, apparatuses, and methods described herein without departing from the scope of the disclosure. For example, the components of the systems and apparatuses may be integrated or separated. Moreover, the operations of the systems and apparatuses disclosed herein may be performed by more, fewer, or other components and the methods described may include more, fewer, or other steps. Additionally, steps may be performed in any suitable order. As used in this document, “each” refers to each member of a set or each member of a subset of a set.

[0022] Any module, unit, component, server, computer, terminal, engine or device exemplified herein that executes instructions may include or otherwise have access to computer readable media such as storage media, computer storage media, or data storage devices (removable and/or non-removable) such as, for example, magnetic disks, optical disks, or tape. Computer storage media may include volatile and non-volatile, removable and non-removable media implemented in any method or technology for storage of information, such as computer readable instructions, data structures, program modules, or other data. Examples of computer storage media include RAM, ROM, EEPROM, flash memory or other memory technology, CD-ROM, digital versatile disks (DVD) or other optical storage, magnetic cassettes, magnetic tape, magnetic disk storage or other magnetic storage devices, or any other medium which can be used to store the desired information and which can be accessed by an application, module, or both. Any such computer storage media may be part of the device or accessible or connectable thereto. Further, unless the context clearly indicates otherwise, any processor or controller set out herein may be implemented as a singular processor or as a plurality of processors. The plurality of processors may be arrayed or distributed, and any processing function referred to herein may be carried out by one or by a plurality of processors, even though a single processor may be exemplified. Any method, application or module herein described may be implemented using computer readable/executable instructions that may be stored or otherwise held by such computer readable media and executed by the one or more processors.

[0023] According to a first embodiment of the present disclosure, a non-contact non-intrusive system **10** for measuring torsion is illustrated in FIG. 1. The depicted system **10** is suitable for

measuring torque on a rotating shaft **20** using optical sensors **24a**, **24b** (individually and collectively “optical sensors **24**”).

[0024] As depicted in FIG. **1**, corresponding high contrast encoder tapes **22a**, **22b** (individually and collectively “encoder tapes **22**”) respectively are secured to the shaft **20** and rotate along with the shaft. Optical sensors **24a**, **24b** are disposed near encoder tapes **22a**, **22b** respectively, to pick up varying light intensities reflected by the portions of encoder tapes **22**.

[0025] High contrast encoder tapes **22** include an alternating pattern of contrasting optical properties such as dark/bright, or black/white, or non-reflective/reflective etc. These patterns lead to an alternating intensity of reflected light to be picked up by the corresponding optical sensors **24**. Each optical sensor **24** may be secured to a mounting bracket to ensure its proximate placement to the corresponding encoder tape **22** on the shaft **20**. Encoder tapes **22**, in the depicted embodiment depicted in FIG. **1**, are wrapped around the entire circumference of shaft **20**. In other embodiments, encoder tapes may be wrapped partially but not entirely around the circumference of the shaft.

[0026] In the depicted embodiment the gap **26** between the optical sensors **24** disposed proximate encoder tapes **22** is about 0.8 mm to 12 mm and the shaft **20** is greater than 100 mm in diameter. For example, a shaft of about 258 mm in diameter can be used. In other embodiments, other diameters or gap distances may be used. In the depicted embodiment, the shaft **20** is solid. In other embodiments, partially hollow shafts may be used.

[0027] As depicted in the embodiment shown in FIG. **1**, the alternating pattern of optical properties etched onto the encoder tapes **22** is uniform. However, in alternate embodiments, other patterns may be used.

[0028] Encoder tapes **22** are disposed on a rotating shaft **20** whose torque is to be computed, at a predetermined distance apart. In the depicted embodiment, the drive-end of shaft **20** is on the right side, while the non-drive end is on the left side. Alternately, in other embodiments, the drive and non-drive ends may be reversed.

[0029] Each corresponding optical sensor **24a**, **24b** is placed proximate the respective tape **22a**, **22b** to provide an electrical signal that provides a measure of the rotation of each tape **22a**, **22b** based on the corresponding sensor readings. In the depicted embodiment, optical sensors **24** are optical line sensors. Common formats of the output of the lines sensors include the standard high transistor logic (HTL) and transistor-to-transistor logic (TTL).

[0030] Computations of torque and power are then automatically carried out using a computing device **14** which includes a processor, and memory storing processor executable instruction that implement a high-speed timer/counter module. [In the depicted embodiment, a programmable logic controller (PLC) is used for the high-speed timing. In other embodiments, a dedicated processor/timing circuit/FPGA may be used for all the timing and a PLC is used for processing and computing]. Computing device **14** is in electrical communication with each of the sensors **24**. In the depicted embodiment, a room **12** (e.g., an engine room in a vessel) may house the computing device **14** and a display unit **16**; and an electrical panel **18** may be disposed between computing device **14** and the sensors **24**. Processing of the timing is performed in close proximity to the optical sensors **22** irrespective of the method chosen (PLC/FPGA etc). HMI/Display can be located anywhere depending on installation requirements.

[0031] A data link **28**, which in the depicted embodiment is a Modbus TCP/RTU, is used for data communications. The communication over data link **28** using Modbus TCP/RTU may include communication of system **10** with another system that measures torsion in another shaft (similar to shaft **20**) or communicate with another system (example alarm/monitoring system). In other embodiments, other types of wired or wireless data link, may be used.

[0032] Display unit **16** in embodiments that are implemented in a vessel or a ship may be powered by a 24VDC and may be in an engine control room **12**. Display unit **16** may display power in BHP (brake horsepower) or other units. As may be appreciated by a person of skill in the art, various user interfaces may be used to display the computed figures using graphical or numerical

representations. Other embodiments of system **10** need not be implemented in ships but may be deployed on land or in other settings.

[0033] In computing device **14**, a high-speed timer/counter module is used for signal processing. As noted above, in the depicted embodiment, computing device **14** is formed as a PLC which is an industrial microprocessor-based controller with programmable memory used to store program instructions. The timer/counter module is used to read in the sensor signals and process them to compute and display (e.g. on display unit **16**) various parameters including torque and power. In other embodiments, other forms of computing devices or processing circuits may be used.

[0034] FIG. **2** depicts a simplified block diagram of various elements of computer system **14**. As shown, computer system **14** has several physical and logical components including a processor **44**, which may be the form of a microcontroller, microprocessor, or a central processing unit (“CPU”), as well as random access memory (“RAM”) **48**, an input/output (“I/O”) interface **52**, a network interface **56**, and non-volatile storage **60**. A high-speed interface circuit **64** enables processor **44** to communicate with the other components. Processor **44** executes processor executable instructions in the form of at least an operating system, and a one or more applications including software modules for computing twist angle, torque and power as will be elaborated below.

[0035] RAM **48** provides relatively responsive volatile storage to processor **44**. I/O interface **52** allows input to be received from one or more peripheral devices, such as a keyboard, a mouse, etc., and outputs information to output devices, such as a display and/or speakers. Network interface **56** permits wired or wireless communication with other computing devices over computer networks such as the Internet. Non-volatile storage **60** stores the operating system and programs, including computer-executable instructions for implementing the software implemented portions of modules in computing device **14** and associated code, data structures and objects. During operation of computing device **14**, the operating system, the programs and the data may be retrieved from non-volatile storage **60** and placed in RAM **48** to facilitate execution.

[0036] In operation, each optical sensor **24** picks up optical signals from the corresponding encoder tape **22**. The signal is then fed into a high-speed timer/counter module in computing device **14** which is in data communication with the sensors **24**.

[0037] In one embodiment, system **10** samples and measures revolutions per minute (RPM) and phase differences (e.g., in microseconds) from the sensor pulses. Several pulses are generated per shaft revolution. Torque and power calculations are computed over a predetermined number of shaft revolutions. In the depicted embodiment, a 5 mm incremental encoder tape is used. Accordingly, the number of pulses depends on the diameter and speed of the shaft and varies from 20-250 pulses/revolution. Torque and power are calculated using a moving average over a time period that is user defined, and ranges from 1-2 seconds for the depicted embodiment.

[0038] After initial set up, system **10** may require no further calibration unless the position of the sensors **24** or their mounting brackets have changed, or the encoder tapes are replaced.

[0039] For power calculations, the twist angle θ which measures the twist of the shaft **20** between the sensors **24** is first computed as:

$$[00001] \theta = 2 * \theta_{\text{sensor}} * (\text{RPM}) * (\text{TimeDifference}) / 60,000,000 \text{ rad} \quad (1)$$

[0040] Time Difference is the moving average time difference between the edge transitions between each sensor. This angle is then used to compute the torque T:

$$[00002] T = G * J * \theta / I \quad (2)$$

[0041] where T=Torque (Nm), G=Modulus of Rigidity, J=Polar area moment of Inertia, θ =Angle of twist (rad) and I=distance between sensors.

[0042] The power P is then computed as:

$$[00003] P = 2 * \theta_{\text{sensor}} * (\text{AverageRPM}) * T / 60. \quad (3)$$

[0043] In the depicted embodiment, averages are computed to account for variations in torque transmitted, differences due to torsional vibrations and for easier viewing. The processor **44** and

memory in computing device **14** as well as the patterns and dimensions of encoder tapes **24** are chosen to ensure the signals are capable of being processed by the hardware.

[0044] In the depicted optical embodiment of system **10**, the encoder tapes **22** are made from scratch. The dimensions of the encoder tapes may depend on the diameter of shaft **20**. In the depicted embodiment the length of the tapes has intervals of 5 mm or higher. In other embodiments intervals of 10 mm can be used.

[0045] It is desirable to provide optical encoder tapes of appropriate size, shape and pattern and to ensure that the processing circuitry of device **14** and software can provide accurate computation without requiring large computing resources. In some embodiments, custom encoder tapes at specified pitches can be manufactured. In other embodiments, standard tapes may be used. Embodiments of the present disclosure are used to calculate brake specific fuel consumption which is a good indicator of efficiency as well as a method to compute and track green house gas (GHG) emissions.

[0046] Advantageously, the torsionmeter system **10** works in a non-contact/non-intrusive way whereby only application of the tape to the shaft of interest is needed to operate, and the rest of the system can be completely decoupled from the engine or motor or its operations.

[0047] As a generalization of the embodiment of FIG. **1**, multi-engine applications driving single or multiple shafts may be realized in which, power from each prime mover may be calculated in order to better control load sharing between prime movers.

[0048] FIG. **3** depicts a flowchart summarizing the steps of a method, which is an example of an embodiment of a method, utilizing the system of FIG. **1** or another embodiment described with reference to FIG. **4**. As depicted, the method **100** starts by preparing optical encoder tapes of a predetermined pattern or magnetic tapes (step **102**).

[0049] The method then applies or secures the tapes a predetermined distance apart on a shaft such as shaft **20** of FIG. **1** (step **104**). The distance between the tapes will be used for determination of power and torque and other figures as noted above.

[0050] The method then places optical or magnetic sensors (e.g., sensors **24** or sensors **84**) proximate each of the tapes (e.g., tapes **22** or tapes **82** respectively) at step **106**.

[0051] As can be appreciated, the steps **102**, **104**, **106** allow for ease of retrofitting an existing shaft and permit non-contact non-intrusive measurement.

[0052] In the embodiment of FIG. **1**, the opening gap or distance between optical sensors **24** and encoder tapes **22** on the shaft may range from 0.8 mm to 12 mm. For magnetic tapes **82** and corresponding sensors **84** depicted in FIG. **4**, the gap may range from 0.5 mm to 5.0 mm.

[0053] At step **108**, sensor data is sent to a computing device (e.g. device **14**) and at step **110** twist angle, torque and power are computed.

[0054] At step **112** it is determined whether to continue reading data from the sensors, and if not, the method then terminates.

Hall Effect Sensors

[0055] In another embodiment of the present disclosure, Hall effect sensors may be used with corresponding magnetic tapes.

[0056] According to a second embodiment of the present disclosure, a system **70** for measuring torsion is illustrated in FIG. **4**. The depicted system **70** is suitable for measuring torque on a rotating shaft **80** using Hall effect sensors **84a**, **84b** (individually and collectively “Hall effect sensors **84**”). Aspects and components of system **70** that are similar to corresponding components in system **10** will not further described.

[0057] As depicted in FIG. **4**, corresponding high contrast magnetic tapes **82a**, **82b** (individually and collectively “magnetic tapes **82**”) respectively are secured to the shaft **80** and rotate along with the shaft. Hall effect sensors **84a**, **84b** disposed near magnetic tapes **82a**, **82b** respectively, to pick up varying voltages corresponding to the magnetic field generated by the portions of the rotating magnetic tapes **82**.

[0058] A Hall effect sensor detects and generates an output voltage when magnetic flux density in the area surrounding the Hall sensor reaches a certain threshold. A Hall sensor includes a small rectangular slice of p-type semiconductor material (a Hall plate), such as gallium arsenide (GaAs), indium antimonide (InSb), or indium arsenide (InAs), that carries a continuous current. A Hall effect sensor functions as an analog sensor returning voltage. Hall sensor's separation from the Hall plate can be calculated using the known magnetic field. The relative position of the magnets can be determined using the sensor set.

[0059] Magnetic tapes **84** are disposed on a rotating shaft **80** whose torque is to be computed, at a predetermined distance apart. In the depicted embodiment, the drive-end of shaft **80** is on the right side, while the non-drive end is on the left side. Alternately, in other embodiments, the drive and non-drive ends may be reversed.

[0060] Each corresponding Hall effect sensor **84a**, **84b** is placed proximate the respective tape **82a**, **82b** to provide an electrical signal that provides an individual measure of the rotation of each tape **82a**, **82b** based on the Hall sensor readings.

[0061] Computations of torque and power are then automatically carried out using a computing device **74** that includes a processor and a high-speed timer/counter module, in electrical communication with each of the sensors **84**. In the depicted embodiment, a room **72** (e.g., an engine room in a vessel) may house the computing device **84** and a display unit **76**; and an electrical panel **78** may be disposed between computing device **74** and the sensors **84**.

[0062] A data link **88**, which in the depicted embodiment is a Modbus TCP/RTU, is used for data communications. The communication over data link **88** using Modbus TCP/RTU may include communication of system **70** with another system that measures torsion in another shaft (similar to shaft **80**). In other embodiments, other types of wired or wireless data link, may be used.

[0063] Similar to FIG. 1 display unit **76** in embodiments that are implemented in a vessel or a ship may be powered by a 24VDC and may be in an engine control room **72**. Display unit **76** may display power in BHP (brake horsepower) or other units. As may be appreciated by a person of skill in the art, various user interfaces may be used to display the computed figures using graphical or numerical representations. Other embodiments of system **70** need not be implemented in ships but may be deployed on land or in other settings. In computing device **74**, a high-speed timer/counter module is used for signal processing. As noted above, in the depicted embodiment, computing device **74** is formed as a PLC. The timer/counter module is used to read in the sensor signals and process them to compute and display various parameters including torque and power. In other embodiments, other forms of computing devices or processing circuits may be used. In this embodiment, the opening gap or distance between sensors **84** and tapes **82** on the shaft **80** ranges from 0.5 mm to 5 mm.

[0064] In operation, the computation of power in the Hall effect embodiment of FIG. 4 is the same as that described for the embodiment of FIG. 1 and uses equations (1), (2) and (3) as illustrated above to compute the twist angle θ using the Time Difference; the torque T ; and the power P respectively.

Combined Optical and Hall Effect Sensors

[0065] Embodiments of the present disclosure include two unique methods of measuring the pulse times: namely a first method of utilising optical sensors with corresponding encoder tapes and a second method of utilizing Hall sensors with corresponding magnetic tapes.

[0066] Either the optical or magnetic embodiments of the torsionmeter can be used with flowmeters for the prime mover to calculate brake specific fuel consumption with data logging either locally or remotely i.e., on a server via a network or on the cloud.

[0067] The integration the optical and magnetic methods with flowmeters for the prime mover can be used to calculate Brake Specific Fuel Consumption with local or cloud data logging. Flowmeters calculate the fuel oil consumption. If power is known, then the brake specific fuel oil consumption=gm/kWh where gm denotes grams of fuel used.

[0068] Although specific advantages have been enumerated above, various embodiments may include some, none, or all of the enumerated advantages.

[0069] Persons skilled in the art will appreciate that there are yet more alternative implementations and modifications possible, and that the above examples are only illustrations of one or more implementations. The scope, therefore, is only to be limited by the claims appended hereto and any amendments made thereto.

Claims

1. A method for measuring torsion on a shaft, the method comprising: (a) obtaining a first and a second tape; (b) securing the first tape and the second tape on the shaft, a predetermined distance apart; (c) placing a first sensor proximate the first tape and placing a second sensor proximate the second tape; (d) sensing a signal from each of the first tape and the second tape using the first sensor and the second sensor respectively to obtain corresponding sensor data; and (e) computing power from the sensor data.
2. The method of claim 1, wherein the first tape is a first encoder tape, the second tape is a second encoder tape, the first sensor is a first optical sensor, and the second sensor is a second optical sensor.
3. The method of claim 1, wherein the first tape is a first magnetic tape, the second tape is a second magnetic tape, the first sensor is a first Hall effect sensor, and the second sensor is a second Hall effect sensor.
4. The method of claim 2, wherein the first encoder tape and the second encoder tape each comprise a predetermined pattern and wherein the predetermined pattern comprises alternating light and dark portions.
5. The method of claim 4, wherein the predetermined pattern comprising the alternating light and dark portions is uniform.
6. The method of claim 1, wherein said computing said power comprises computing a twist angle θ as: $\theta = 2 * \text{RPM} * (\text{TimeDifference}) / 60,000,000 \text{ rad}$ wherein RPM is revolutions per minute of the shaft and Time Difference is a moving average of time difference between corresponding edge transitions from the first sensor and the second sensor.
7. The method of claim 6, wherein said computing said power further comprises: computing a torque T as $T = G * J * \theta / I$ wherein the torque is measured in Nm, G=Modulus of Rigidity, J=polar area moment of inertia, θ =angle of twist in radians (rad) and I=said predetermined distance between the first tape and the second tape.
8. The method of claim 7, further comprising computing the power P as:
$$P = 2 * \text{RPM} * T / 60.$$
9. The method of claim 8, wherein the torque T and the power P are computed over a predetermined number of revolutions of the shaft.
10. The method of claim 9, wherein the predetermined number of revolutions is 50.
11. A system for measuring torsion on a rotating shaft, the system comprising: (a) a first encoder tape secured on the rotating shaft; (b) a second encoder tape secured on the rotating shaft a predetermined distance away from the first encoder tape; (c) a first optical sensor disposed proximate the first encoder tape; (d) a second optical sensor disposed proximate the second encoder tape; and (e) a computing device comprising a processor and memory, the memory for storing instructions for computing at least one of twist angle, torque and power in electrical communication with the first optical sensor and the second optical sensor, wherein the first encoder tape and the second encoder tape comprise a first and second pattern respectively and wherein the first optical sensor and the second optical sensor transmit data to the computing device indicative of rotational speed for the first encoder tape and second encoder tape respectively, and wherein the

computing device computes power from the sensor data.

12. The system of claim 11, wherein the first encoder tape comprises a first pattern, the second encoder tape comprises a second pattern, the first pattern comprises alternating light and dark portions, and the second pattern comprises alternating light and dark portions.

13. The system of claim 11, wherein the first pattern and the second pattern are the same.

14. The system of claim 11, wherein the first pattern and the second pattern are different.

15. The system of claim 11, wherein a distance between the first optical sensor and the first encoder tape ranges from about 0.8 mm to about 12 mm.

16. The system of claim 11, wherein a distance between the second optical sensor and the second encoder tape ranges from about 0.8 mm to about 12 mm.

17. A system for measuring torsion on a rotating shaft, the system comprising: (a) a first magnetic tape secured on the rotating shaft; (b) a second magnetic tape secured on the rotating shaft a predetermined distance away from the first magnetic tape; (c) a first Hall effect sensor disposed proximate the first magnetic tape; (d) a second Hall effect sensor disposed proximate the second magnetic tape; and (e) a computing device comprising a processor and memory, the memory for storing instructions for computing at least one of twist angle, torque and power in electrical communication with the first and second magnetic sensors, wherein the first and second Hall effect sensors transmit sensor data to the computing device indicative of rotational speed for the first magnetic tape and second magnetic tape respectively, and wherein the computing device computes power from the sensor data.

18. The system, of claim 17, wherein a distance between the first Hall effect sensor and the first magnetic tape ranges from about 0.5 mm to about 5 mm.

19. The system, of claim 17, wherein a distance between the second Hall effect sensor and the second magnetic tape ranges from about 0.5 mm to about 5.0 mm.
