

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250273531

Kind Code

A1

Publication Date

August 28, 2025

Inventor(s)

LIEN; Hong-Te et al.

PACKAGE STRUCTURE

Abstract

An electronic structure includes a package structure, a first heat dissipating structure and a second heat dissipating structure. The package structure has a top surface including a first region and a second region. A first predetermined temperature at the first region is higher than a second predetermined temperature at the second region. The first heat dissipating structure includes a first portion disposed on the first region. The second heat dissipating structure includes a first portion disposed on the second region. The first portion of the first heat dissipating structure and the first portion of the second heat dissipating structure are concurrently formed through a 3D printing technique. A thickness of the first portion of the first heat dissipating structure is greater than a thickness of the first portion of the second heat dissipating structure.

Inventors: LIEN; Hong-Te (Kaohsiung, TW), CHEN; Yi-Chieh (Kaohsiung, TW), HUANG; Wen Hung (Kaohsiung, TW), CHANG; Yu-Hsun (Kaohsiung, TW)

Applicant: Advanced Semiconductor Engineering, Inc. (Kaohsiung, TW)

Family ID: 1000007758966

Assignee: Advanced Semiconductor Engineering, Inc. (Kaohsiung, TW)

Appl. No.: 18/586405

Filed: February 23, 2024

Publication Classification

Int. Cl.: H01L23/367 (20060101); H01L23/00 (20060101); H01L23/498 (20060101);
H01L25/065 (20230101)

U.S. Cl.:

CPC H01L23/3675 (20130101); H01L23/49816 (20130101); H01L23/49822 (20130101);
H01L24/08 (20130101); H01L24/16 (20130101); H01L25/0652 (20130101);

Background/Summary

BACKGROUND

1. Field of the Disclosure

[0001] The present disclosure relates to a package structure and a manufacturing method, and to a package structure including a heat dissipating structure, and a method for manufacturing the same.

2. Description of the Related Art

[0002] In a semiconductor electronic structure, a semiconductor package structure is mounted to a substrate, and a heat dissipating structure is formed or disposed on a top surface of the semiconductor package structure so as to dissipate the heat generated from the semiconductor device(s) in the semiconductor package structure during operation to a heat sink disposed over the heat dissipating structure. The design of the heat dissipating structure will influence the heat dissipation efficiency of the semiconductor electronic structure, and will affect the reliability, yield and lifetime of the semiconductor electronic structure.

SUMMARY

[0003] In some embodiments, an electronic structure includes a package structure, a first heat dissipating structure and a second heat dissipating structure. The package structure has a top surface including a first region and a second region. A first predetermined temperature at the first region is higher than a second predetermined temperature at the second region. The first heat dissipating structure includes a first portion disposed on the first region. The second heat dissipating structure includes a first portion disposed on the second region. The first portion of the first heat dissipating structure and the first portion of the second heat dissipating structure are concurrently formed through a 3D printing technique. A thickness of the first portion of the first heat dissipating structure is greater than a thickness of the first portion of the second heat dissipating structure.

[0004] In some embodiments, an electronic structure includes a package structure, a heat sink, a first heat dissipating structure and a second heat dissipating structure. The package structure includes a first electronic device and a second electronic device encapsulated by an encapsulant. The heat sink is disposed over the package structure. The first heat dissipating structure is disposed over the first electronic device, and has a first thermal path toward heat sink. The second heat dissipating structure is disposed over the second electronic device, and has a second thermal path toward heat sink. The first thermal path is thermally insulated from the second thermal path. The first thermal path is non-parallel with the second thermal path.

[0005] In some embodiments, an electronic structure includes a package structure. The package structure includes an electronic device, an encapsulant and a vertical conductive structure. The encapsulant encapsulates the electronic device. The vertical conductive structure is encapsulated in the encapsulant and has a discontinuous lateral surface.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0006] Aspects of some embodiments of the present disclosure are readily understood from the following detailed description when read with the accompanying figures. It is noted that various structures may not be drawn to scale, and dimensions of the various structures may be arbitrarily

increased or reduced for clarity of discussion.

[0007] FIG. 1 illustrates a cross-sectional view of an electronic structure according to some embodiments of the present disclosure.

[0008] FIG. 2 illustrates a cross-sectional view of an electronic structure according to some embodiments of the present disclosure.

[0009] FIG. 3 illustrates a cross-sectional view of an electronic structure according to some embodiments of the present disclosure.

[0010] FIG. 4 illustrates a cross-sectional view of an electronic structure according to some embodiments of the present disclosure.

[0011] FIG. 5 illustrates a cross-sectional view of an electronic structure according to some embodiments of the present disclosure.

[0012] FIG. 6 illustrates a cross-sectional view of an electronic structure according to some embodiments of the present disclosure.

[0013] FIG. 7 illustrates a perspective view of the electronic structure of FIG. 6.

[0014] FIG. 7A illustrates a top view of FIG. 7.

[0015] FIG. 8 illustrates a cross-sectional view of an electronic structure according to some embodiments of the present disclosure.

[0016] FIG. 8A illustrates an enlarged view of a region “A” in FIG. 8.

[0017] FIG. 9 illustrates a cross-sectional view of an electronic structure according to some embodiments of the present disclosure.

[0018] FIG. 9A illustrates an enlarged view of a region “B” in FIG. 9.

[0019] FIG. 9B illustrates a cross-sectional view of an electronic structure according to some embodiments of the present disclosure.

[0020] FIG. 10 illustrates a cross-sectional view of an electronic structure according to some embodiments of the present disclosure.

[0021] FIG. 11 illustrates a cross-sectional view of an electronic structure according to some embodiments of the present disclosure.

[0022] FIG. 12 illustrates a cross-sectional view of an electronic structure according to some embodiments of the present disclosure.

[0023] FIG. 13 illustrates a cross-sectional view of an electronic structure according to some embodiments of the present disclosure.

[0024] FIG. 14 illustrates a cross-sectional view of an electronic structure according to some embodiments of the present disclosure.

[0025] FIG. 15 illustrates a cross-sectional view of an electronic structure according to some embodiments of the present disclosure.

[0026] FIG. 16 illustrates a cross-sectional view of an electronic structure according to some embodiments of the present disclosure.

[0027] FIG. 17 illustrates one or more stages of an example of a method for manufacturing an electronic structure according to some embodiments of the present disclosure.

[0028] FIG. 18 illustrates one or more stages of an example of a method for manufacturing an electronic structure according to some embodiments of the present disclosure.

[0029] FIG. 19 illustrates one or more stages of an example of a method for manufacturing an electronic structure according to some embodiments of the present disclosure.

[0030] FIG. 20 illustrates one or more stages of an example of a method for manufacturing an electronic structure according to some embodiments of the present disclosure.

[0031] FIG. 21 illustrates one or more stages of an example of a method for manufacturing an electronic structure according to some embodiments of the present disclosure.

[0032] FIG. 22 illustrates one or more stages of an example of a method for manufacturing an electronic structure according to some embodiments of the present disclosure.

DETAILED DESCRIPTION

[0033] Common reference numerals are used throughout the drawings and the detailed description to indicate the same or similar components. Embodiments of the present disclosure will be readily understood from the following detailed description taken in conjunction with the accompanying drawings.

[0034] The following disclosure provides many different embodiments, or examples, for implementing different features of the provided subject matter. Specific examples of components and arrangements are described below to explain certain aspects of the present disclosure. These are, of course, merely examples and are not intended to be limiting. For example, the formation of a first feature over or on a second feature in the description that follows may include embodiments in which the first and second features are formed or disposed in direct contact, and may also include embodiments in which additional features may be formed or disposed between the first and second features, such that the first and second features may not be in direct contact. In addition, the present disclosure may repeat reference numerals and/or letters in the various examples. This repetition is for the purpose of simplicity and clarity and does not in itself dictate a relationship between the various embodiments and/or configurations discussed.

[0035] At least some embodiments of the present disclosure provide for a package structure which has an improved crack resistance. In some embodiments, an electronic structure includes such package structure so as to improve a reliability or a yield thereof. At least some embodiments of the present disclosure further provide for techniques for manufacturing the package structure and the electronic structure.

[0036] FIG. 1 illustrates a cross-sectional view of an electronic structure 4 according to some embodiments of the present disclosure. The electronic structure 4 may be also referred to as “an assembly structure” or “a semiconductor package”. The electronic structure 4 may include a base substrate 40, a package structure 3, a second protection material 44, a thermal structure 47 (including a first heat dissipating structure 5 and a second heat dissipating structure 6), a thermal material 48, a heat sink 46 and a plurality of external connectors 49.

[0037] The base substrate 40 may include a glass reinforced epoxy material (such as FR4), bismaleimide triazine (BT), epoxy resin, silicon, printed circuit board (PCB) material, glass, ceramic or photoimageable dielectric (PID) material. The base substrate 40 may have a first surface 401 and a second surface 402 opposite to the first surface 401.

[0038] The package structure 3 may include a wiring structure 1, a first electronic device 24, a second electronic device 26, a first protection material 32, an encapsulant 34 and a plurality of solder materials 36. In some embodiments, the package structure 3 may include one first electronic device 24 and two second electronic devices 26 disposed side by side. However, the amounts of the first electronic device(s) 24 and the second electronic device(s) 26 are not limited in the present disclosure.

[0039] The wiring structure 1 may have a first surface 11, a second surface 12 opposite to the first surface 11, a lateral side surface 13 extending between the first surface 11 and the second surface 12, and a high density region 16 (or a fine line region) between the first electronic device 24 and the second electronic device 26. The wiring structure 1 may include at least one dielectric layer 14, at least one circuit layer 15 in contact with the dielectric layer 14, and a plurality of protrusion pads 20. For example, the wiring structure 1 includes a first dielectric layer 141, a first circuit layer 151, a second dielectric layer 142, a second circuit layer 152, a third dielectric layer 143, a third circuit layer 153, a fourth dielectric layer 144, a fourth circuit layer 154, and a fifth dielectric layer 145.

[0040] The first dielectric layer 141 may be a topmost dielectric layer or an outermost dielectric layer of the wiring structure 1. The first circuit layer 151 may be a topmost circuit layer or an outermost circuit layer of the wiring structure 1. A material of the first circuit layer 151 may include, for example, copper, another conductive metal, or an alloy thereof. A material of the first dielectric layer 141 may include an insulating material, a passivation material, a dielectric material or a solder resist material, such as, for example, a benzocyclobutene (BCB) based polymer or a

polyimide (PI). In some embodiments, the first dielectric layer **141** may be made of a photoimageable material. In addition, the first surface **11** of the wiring structure **1** may be a top surface of the first dielectric layer **141**. The first circuit layer **151** is disposed adjacent to the top surface of the first dielectric layer **141**. In some embodiments, the first circuit layer **151** is embedded in the first dielectric layer **141**, and is exposed from the top surface of the first dielectric layer **141**. That is, the first dielectric layer **141** covers the first circuit layer **151**, and defines a plurality of openings to expose portions of the first circuit layer **151**.

[0041] Further, the first circuit layer **151** may include an interconnection portion **15a** and a periphery portion **15b**. The interconnection portion **15a** is located in the high density region **16**, and the periphery portion **15b** is located outside the high density region **16** (e.g., a low density region). For example, the second electronic device **26** may be electrically connected to the first electronic device **24** through the interconnection portion **15a** of the first circuit layer **151**. The second electronic device **26** and the first electronic device **24** may be electrically connected to the solder materials **36** on the second surface **12** of the wiring structure **1** through the periphery portion **15b** of the first circuit layer **151**. A line width/line space (L/S) of the traces of the interconnection portion **15a** may be less than an L/S of the traces of the periphery portion **15b**. For example, an L/S of the traces of the interconnection portion **15a** may be less than or equal to about 5 μm /about 5 μm , or less than or equal to about 2 μm /about 2 μm , or less than or equal to about 0.8 μm /about 0.8 μm . An L/S of the traces of the periphery portion **15b** may be less than or equal to about 10 μm /about 10 μm , or less than or equal to about 7 μm /about 7 μm , or less than or equal to about 5 μm /about 5 μm .

[0042] The first dielectric layer **141** and the first circuit layer **151** may be disposed on the second dielectric layer **142**. In addition, the second dielectric layer **142** may cover the second circuit layer **152**. A portion (i.e., a via portion **17**) of the first circuit layer **151** extends through the second dielectric layer **142** to electrically connect the second circuit layer **152**. A material of the second dielectric layer **142** may be the same as or similar to the material of the first dielectric layer **141**. The second circuit layer **152** may also include an interconnection portion located in the high density region **16**, and a periphery portion located outside the high density region **16**. In some embodiments, the via portion **17** of the first circuit layer **151** may extend from the periphery portion **15b**, and they may be formed concurrently and integrally.

[0043] Similarly, the second dielectric layer **142** and the second circuit layer **152** may be disposed on the third dielectric layer **143**. In addition, the third dielectric layer **143** may cover the third circuit layer **153**. A portion (i.e., a via portion **17**) of the second circuit layer **152** extends through the third dielectric layer **143** to electrically connect the third circuit layer **153**. A material of the third dielectric layer **143** may be the same as or similar to the material of the second dielectric layer **142**. The third circuit layer **153** may also include an interconnection portion located in the high density region **16**, and a periphery portion located outside the high density region **16**. In some embodiments, the via portion **17** of the second circuit layer **152** may extend from the periphery portion, and they may be formed concurrently and integrally.

[0044] Similarly, the third dielectric layer **143** and the third circuit layer **153** may be disposed on the fourth dielectric layer **144**. In addition, the fourth dielectric layer **144** may cover the fourth circuit layer **154**. A portion (i.e., a via portion **17**) of the third circuit layer **153** extends through the fourth dielectric layer **144** to electrically connect the fourth circuit layer **154**. A material of the fourth dielectric layer **144** may be the same as or similar to the material of the third dielectric layer **143**. The fourth circuit layer **154** may also include an interconnection portion located in the high density region **16**, and a periphery portion located outside the high density region **16**.

[0045] The fourth dielectric layer **144** and the fourth circuit layer **154** may be disposed on the fifth dielectric layer **145**. A portion (i.e., a via portion **17**) of the fourth circuit layer **154** extends through the fifth dielectric layer **145** to be exposed from a bottom surface of the fifth dielectric layer **145** (e.g., the second surface **12** of the wiring structure **1**). A material of the fifth dielectric layer **145**

may be the same as or similar to the material of the fourth dielectric layer **144**. As shown in FIG. **1**, the second electronic device **26** may be electrically connected to the first electronic device **24** through the interconnection portions **15a** of the circuit layers **15** (including, for example, the interconnection portions **15a** of the first circuit layer **151**, the second circuit layer **152**, the third circuit layer **153** and the fourth circuit layer **154**). The second electronic device **26** and the first electronic device **24** may be electrically connected to the solder materials **36** through the via portions **17** of the periphery portions **15b** of the circuit layers **15** (including, for example, the periphery portions **15b** of the first circuit layer **151**, the second circuit layer **152**, the third circuit layer **153** and the fourth circuit layer **154**).

[0046] The protrusion pads **20** may be disposed on and protrude from the first dielectric layer **141** (i.e., the topmost dielectric layer or the outermost dielectric layer) of the wiring structure **1**. The protrusion pads **20** may be disposed on and protrude from the first surface **11** of the wiring structure **1**, and extend through the first dielectric layer **141** (i.e., the topmost dielectric layer or the outermost dielectric layer) to electrically connect the first circuit layer **151**. The protrusion pads **20** may include a plurality of first protrusion pads **21** corresponding to the first electronic device **24** and a plurality of second protrusion pads **22** corresponding to the second electronic device **26**.

[0047] The first electronic device **24** and the second electronic device **26** are disposed adjacent to the first surface **11** of the wiring structure **1** side by side, and are electrically connected to the circuit layer **15** of the wiring structure **1**. The first electronic device **24** may be a semiconductor device such as an application specific integrated circuit (ASIC) die. The first electronic device **24** may have a first surface **241**, a second surface **242** opposite to the first surface **241**, and a lateral side surface **243** extending between the first surface **241** and the second surface **242**. Further, the first electronic device **24** may include a plurality of circuit layers **248** and a plurality of first electrical contacts **244** disposed adjacent to the first surface **241**. The circuit layer **248** may be embedded in the first electronic device **24**, and may include a seed layer **246** and a conductive material **247** disposed on the seed layer **246**. The seed layer **246** may be formed by physical vapor deposition (PVD). The first electrical contacts **244** may be electrically connected to the circuit layers **248**, and may be exposed or may protrude from the first surface **241** for electrical connection. The first electrical contacts **244** may be pads, bumps, studs, pillars or posts. In some embodiments, the first electrical contacts **244** of the first electronic device **24** may be electrically connected and physically connected to the first protrusion pads **21** through a plurality of solder materials **245**. In other words, the first electronic device **24** may be electrically connected to the wiring structure **1** by flip-chip bonding. For example, the first electrical contacts **244** may include copper, gold, platinum, and/or other suitable material. The first electronic device **24** will generate relatively more heat during operation.

[0048] The second electronic device **26** may be a semiconductor device such as a high bandwidth memory (HBM) die or an ASIC die. The second electronic device **26** may have a first surface **261**, a second surface **262** opposite to the first surface **261**, and a lateral side surface **263** extending between the first surface **261** and the second surface **262**. Further, the second electronic device **26** may include a plurality of second electrical contacts **264** disposed adjacent to the first surface **261**. The second electrical contacts **264** may be exposed or may protrude from the first surface **261** for electrical connection. The second electrical contacts **264** may be pads, bumps, studs, pillars or posts. In some embodiments, the second electrical contacts **264** of the second electronic device **26** may be electrically connected and physically connected to the second protrusion pads **22** through a plurality of solder materials **265**. In other words, the second electronic device **26** may be electrically connected to the wiring structure **1** by flip-chip bonding. For example, the second electrical contact **264** may include copper, gold, platinum, and/or other suitable material. The second electronic device **26** will generate relatively less heat during operation. The amount of heat generated by the second electronic device **26** may be less than the amount of heat generated by the first electronic device **24**.

[0049] The first protection material **32** (i.e., an underfill) is disposed in the first space **25** between the first electronic device **24** and the wiring structure **1** and the second space **27** between the second electronic device **26** and the wiring structure **1** so as to cover and protect the joints formed by the first electrical contacts **244**, the first protrusion pads **21** and the solder materials **245**, and the joints formed by the second electrical contacts **264**, the second protrusion pads **22** and the solder materials **265**. In some embodiments, the first protection material **32** may extend from the first space **25** to the second space **27**. In addition, the first protection material **32** may further extend into a gap **30** between the lateral side surface **243** of the first electronic device **24** and the lateral side surface **263** of the second electronic device **26**. The gap **30** may be less than about 100 μm , less than about 80 μm , less than about 70 μm , less than about 60 μm , or less than about 50 μm . Thus, the first protection material **32** may fill the gap **30** due to capillarity. The first protection material **32** has a top surface **321**.

[0050] The encapsulant **34** may encapsulate the wiring structure **1**, the first electronic device **24**, the second electronic device **26** and the first protection material **32**. Alternatively, the encapsulant **34** may cover at least a portion of the first surface **11** of the wiring structure **1**, at least a portion of the first electronic device **24**, at least a portion of the second electronic device **26** and the first protection material **32**. A material of the encapsulant **34** may be a molding compound with or without fillers. The encapsulant **34** has a first surface **341** (e.g., a top surface) and a lateral side surface **343**. The first surface **341** of the encapsulant **34**, the second surface **242** of the first electronic device **24**, the second surface **262** of the second electronic device **26** and the top surface **321** of the first protection material **32** in the gap **30** may be substantially aligned with or coplanar with each other so as to form a top surface **31** of the package structure **3**. In addition, the lateral side surface **343** of the encapsulant **34** may be substantially aligned with or coplanar with the lateral side surface **13** of the wiring structure **1**.

[0051] The solder materials **36** (e.g., solder balls) are disposed adjacent to the second surface **12** of the wiring structure **1** for external connection. The solder materials **36** are disposed on the exposed portions (i.e., the bottom portions of the via portions) of the fourth circuit layer **154**. The package structure **3** may be electrically connected to the first surface **401** of the base substrate **40** through the solder materials **36**. The second protection material **44** (i.e., an underfill) may be disposed in a space between the package structure **3** and the base substrate **40** so as to cover and protect the solder materials **36**.

[0052] In some embodiments, the package structure **3** may include a first region **3'** and a second region **3''** different from the first region **3'**. For example, the top surface **31** of the package structure **3** may include the first region **3'** and the second region **3''**. The first electronic device **24** may be disposed corresponding to or disposed in the first region **3'**, and may generate heat causing a first predetermined temperature. From a top view, the first electronic device **24** may be disposed within the first region **3'**. The second electronic device **26** may be disposed corresponding to or disposed in the second region **3''**, and may be configured to generate heat causing a second predetermined temperature. From a top view, the second electronic device **26** may be disposed within the second region **3''**.

[0053] The first predetermined temperature at the first region **3'** is higher than a second predetermined temperature at the second region **3''** during the operation of the package structure **3**. Thus, the first region **3'** may be also referred to as “a hot region”, “a high temperature region”, “a hot area”, “a high temperature area”, “a first portion”, “a high temperature portion” or “a hot portion”. The first electronic device **24** may include the first region **3'**. Since the encapsulant **34** and/or the first protection material **32** may encapsulate the first electronic device **24**, the range or area of the first region **3'** may include a portion of the encapsulant **34** and/or the first protection material **32** that surrounds the first electronic device **24**. That is, a width of the first region **3'** may be greater than a width of the first electronic device **24** from a cross-sectional view and a top view.

[0054] The second region **3''** may be also referred to as “a cold region”, “a low temperature

region”, “a cold area”, “a low temperature area”, “a second portion”, “a low temperature portion” or “a cold portion”. The second electronic device **26** may include the second region **3”**. Since the encapsulant **34** and/or the first protection material **32** may encapsulate the second electronic device **26**, the range or area of the second region **3”** may include a portion of the encapsulant **34** and/or the first protection material **32** that surrounds the second electronic device **26**. That is, a width of the second region **3”** may be greater than a width of the second electronic device **26** from a cross-sectional view and a top view.

[0055] The thermal structure **47** may include a first heat dissipating structure **5** and a second heat dissipating structure **6**, and may be disposed on the top surface **31** of the package structure **3** (e.g., the first surface **341** of the encapsulant **34**, the second surface **242** of the first electronic device **24**, the second surface **262** of the second electronic device **26** and the top surface **321** of the first protection material **32**). The first heat dissipating structure **5** and the second heat dissipating structure **6** may be formed through a chemical deposition process such as a 3D printing technique. A material of the first heat dissipating structure **5** and the second heat dissipating structure **6** may be metal such as copper. A grain size of the material of the first heat dissipating structure **5** and the second heat dissipating structure **6** may be greater than a grain size of the material of the seed layer **246** of the circuit layer **248** of the first electronic device **24**. For example, the grain size of the material of the first heat dissipating structure **5** and the second heat dissipating structure **6** may be greater than five times, ten times, or twenty times the grain size of the material of the seed layer **246** of the circuit layer **248** of the first electronic device **24**.

[0056] The first heat dissipating structure **5** may be disposed over or disposed on the first region **3’** of the first electronic device **24**. The first heat dissipating structure **5** may include a first portion **51** disposed on the first region **3’**. The first portion **51** of the first heat dissipating structure **5** may directly contact the first surface **341** of the encapsulant **34**, the second surface **242** of the first electronic device **24** and the top surface **321** of the first protection material **32**. The first portion **51** of the first heat dissipating structure **5** may include a lower portion **511** and an upper portion **512** disposed on the lower portion **511**. A thickness of the upper portion **512** may be less than a thickness of the lower portion **511**. There may be a visible interface or an obvious interface (e.g., the top surface **513** of the lower portion **511**) formed between the lower portion **511** and the upper portion **512**. In another embodiment, there may be no obvious interface or visible interface formed between the lower portion **511** and the upper portion **512**. In addition, the upper portion **512** of the first portion **51** of the first heat dissipating structure **5** may include a rounded corner.

[0057] The second heat dissipating structure **6** may be disposed over or disposed on the second region **3”** of the second electronic device **26**. The second heat dissipating structure **6** may include a first portion **61** disposed on the second region **3”**. The first portion **61** of the second heat dissipating structure **6** may directly contact the first surface **341** of the encapsulant **34**, the second surface **262** of the second electronic device **26** and the top surface **321** of the first protection material **32**. A portion of the first portion **61** of the second heat dissipating structure **6** may extend to contact the lateral side surface **343** of the encapsulant **34**.

[0058] In the illustrated embodiment, a size (e.g., thickness) of the heat dissipating structure may be determined according to the amount of heat generated by the electronic device. For example, the amount of heat generated by the first electronic device **24** may be greater than the amount of heat generated by the second electronic device **26**, thus, the size (e.g., a thickness from a cross-sectional view or a coverage area from a top view) of the first heat dissipating structure **5** on the first region **3’** may be greater than the size (e.g., a thickness from a cross-sectional view or a coverage area from a top view) of the second heat dissipating structure **6** on the second region **3”**.

[0059] The first portion **51** of the first heat dissipating structure **5** and the first portion **61** of the second heat dissipating structure **6** may be concurrently formed through a chemical deposition process. A thickness of the first portion **51** of the first heat dissipating structure **5** is greater than a thickness of the first portion **61** of the second heat dissipating structure **6**. In some embodiments,

the lower portion **511** of the first portion **51** of the first heat dissipating structure **5** and the first portion **61** of the second heat dissipating structure **6** may be concurrently formed through a chemical deposition process. A thickness of the lower portion **511** of the first portion **51** of the first heat dissipating structure **5** is equal to the thickness of the first portion **61** of the second heat dissipating structure **6**.

[0060] The thermal material **48** (e.g., a thermal interface material (TIM)) may cover the first heat dissipating structure **5** and the second heat dissipating structure **6**. The heat sink **46** may be a cap or hat structure, and may define a cavity **461** for accommodating the package structure **3**. A material of the heat sink **46** may include metal such as copper, aluminum, and/or other suitable material. The heat sink **46** may be disposed over the package structure **3**. A portion of the heat sink **46** may be attached to the top surface **31** of the package structure **3** through the thermal material **48** (e.g., thermal interface material (TIM)) so as to dissipate the heat generated by the first electronic device **24** and the second electronic device **26**. Thus, the heat sink **46** may contact the thermal material **48** (e.g., thermal interface material (TIM)). The heat sink **46** may not directly contact the first heat dissipating structure **5** and the second heat dissipating structure **6**. The heat sink **46** is spaced apart from the first heat dissipating structure **5** and the second heat dissipating structure **6**. The heat sink **46** may be thermally connected with the first heat dissipating structure **5** and the second heat dissipating structure **6** through the thermal material **48**. Another portion (e.g., bottom portion) of the heat sink **46** may be attached to or thermally connected to the base substrate **40** through an adhesive material. In addition, the external connectors **49** (e.g., solder balls) are formed or disposed on the second surface **402** of the base substrate **40** for external connection.

[0061] In the embodiment illustrated in FIG. **1**, a first thermal path may be formed from the first region **3'** (e.g., the first electronic device **24**) to the heat sink **46** by the first heat dissipating structure **5** and a first portion of the thermal material **48** on the first heat dissipating structure **5**. A second thermal path may be formed from the second region **3''** (e.g., the second electronic device **26**) to the heat sink **46** by the second heat dissipating structure **6** and a second portion of the thermal material **48** on the second heat dissipating structure **6**. During the operation of the package structure **3**, the temperature of the first region **3'** (e.g., the first electronic device **24**) may be higher than the temperature of the second region **3''** (e.g., the second electronic device **26**). However, since the thickness of the first heat dissipating structure **5** is greater than the thickness of the second heat dissipating structure **6**, a heat dissipation efficiency (or thermal conductivity) of the first thermal path is greater than a heat dissipation efficiency (or thermal conductivity) of the second thermal path. Thus, the heat of the first region **3'** (e.g., the heat generated by the first electronic device **24**) and the heat of the second region **3''** (e.g., the heat generated by the second electronic device **26**) may be dissipated or conducted to the heat sink **46** substantially evenly. Therefore, the heat of the first region **3'** (e.g., the heat generated by the first electronic device **24**) will not accumulate at the first region **3'**, and the performance of the package structure **3** may be improved. Therefore, the reliability, yield and lifetime of the electronic structure **4** is improved.

[0062] In addition, the first heat dissipating structure **5** and the second heat dissipating structure **6** are formed through a chemical deposition process (e.g., 3D printing technology) rather than a physical vapor deposition (PVD). Thus, the manufacturing cost of the first heat dissipating structure **5** and the second heat dissipating structure **6** may be reduced, and the manufacturing cost of the electronic structure **4** may be also reduced. Further, since the first heat dissipating structure **5** and the second heat dissipating structure **6** are formed through the chemical deposition process (e.g., 3D printing technique or 3D printing technology), the pattern, profile and shape of the first heat dissipating structure **5** and the second heat dissipating structure **6** may be formed flexibly. That is, the first thermal path and the second thermal path may be designed as desired. By adjusting the direction of length of the first thermal path and the second thermal path, the heat dissipation efficiency of the package structure **3** may be optimized. Compared to the metal formed by physical vapor deposition (PVD), an advantage of the 3D printing technique is that different geometries and

sizes of the heat dissipating structure may be selected or chosen to be formed on different regions. Thus, the design flexibility is improved.

[0063] FIG. 2 illustrates a cross-sectional view of an electronic structure **4a** according to some embodiments of the present disclosure. The electronic structure **4a** of FIG. 2 is similar to the electronic structure **4** of FIG. 1, except for the structure of the first heat dissipating structure **5a** of the thermal structure **47a**. As shown in FIG. 2, there may be no obvious interface or visible interface between the lower portion **511** and the upper portion **512**.

[0064] FIG. 3 illustrates a cross-sectional view of an electronic structure **4b** according to some embodiments of the present disclosure. The electronic structure **4b** of FIG. 3 is similar to the electronic structure **4** of FIG. 1, except for the structure of the thermal structure **47b**. As shown in FIG. 3, the thickness of the first portion **51** of the first heat dissipating structure **5b** is greater than a thickness of the first portion **61** of the second heat dissipating structure **6b**. The thickness of the upper portion **512** may be greater than the thickness of the lower portion **511**. The thickness of the lower portion **511** of the first portion **51** of the first heat dissipating structure **5b** is equal to the thickness of the first portion **61** of the second heat dissipating structure **6b**.

[0065] FIG. 4 illustrates a cross-sectional view of an electronic structure **4c** according to some embodiments of the present disclosure. The electronic structure **4c** of FIG. 4 is similar to the electronic structure **4b** of FIG. 3, and the differences therebetween are described as follows. The first heat dissipating structure **5b** may be physically separated from and or thermally insulated from the second heat dissipating structure **6b**. The thermal material **48** (e.g., thermal interface material (TIM)) may extend between the first heat dissipating structure **5b** and the second heat dissipating structure **6b**, and may connect to the heat sink **46**. For example, the lower portion **511** of the first portion **51** of the first heat dissipating structure **5b** may be spaced apart from the first portion **61** of the second heat dissipating structure **6b**. In addition, the thermal structure **47c** may further include a third heat dissipating structure **7** connecting to a periphery portion of the first portion **61** of the second heat dissipating structure **6b**. A thickness of the third heat dissipating structure **7** may be greater than the thickness of the upper portion **512** of the first portion **51** of the first heat dissipating structure **5b**. Thus, a level of a top end of the third heat dissipating structure **7** may be higher than a top end of the first heat dissipating structure **5b** and a top end of the second heat dissipating structure **6b**. An elevation of a top surface of the third heat dissipating structure **7** may be higher than an elevation of a top surface of the first heat dissipating structure **5b** and an elevation of a top surface of the second heat dissipating structure **6b**. In some embodiments, the third heat dissipating structure **7** may include a first portion **71** disposed on the first portion **61** of the second heat dissipating structure **6b** and a second portion **72** disposed on the first portion **71**. A width of the first portion **71** may be less than a width of the second portion **72**. In some embodiments, the third heat dissipating structure **7** may be formed through the chemical deposition process (e.g., 3D printing technique or 3D printing technology). The heat sink **46** may contact the third heat dissipating structure **7**.

[0066] FIG. 5 illustrates a cross-sectional view of an electronic structure **4d** according to some embodiments of the present disclosure. The electronic structure **4d** of FIG. 5 is similar to the electronic structure **4b** of FIG. 3, except that the thermal structure **47d** may further include a third heat dissipating structure **7d**. The third heat dissipating structure **7d** may be disposed around and connected to the first heat dissipating structure **5b** and the second heat dissipating structure **6b**. The third heat dissipating structure **7d** may be configured to support the heat sink **46**. The third heat dissipating structure **7d** and the heat sink **46** may collectively define an accommodation space **75** for accommodating the thermal material **48** (e.g., thermal interface material (TIM)). For example, the third heat dissipating structure **7d** may be disposed on and may connect to a periphery portion of the first portion **61** of the second heat dissipating structure **6b** and a periphery portion of the lower portion **511** of the first portion **51** of the first heat dissipating structure **5b**. A thickness of the third heat dissipating structure **7d** may be greater than the thickness of the upper portion **512** of the

first portion **51** of the first heat dissipating structure **5b**. Thus, a level of a top end of the third heat dissipating structure **7d** may be higher than a top end of the first heat dissipating structure **5b** and a top end of the second heat dissipating structure **6b**. In some embodiments, the third heat dissipating structure **7** may include a first portion **71** disposed on the first portion **61** of the second heat dissipating structure **6b** and a second portion **72** disposed on the first portion **71**. A width of the first portion **71** may be less than a width of the second portion **72**. The heat sink **46** may contact the third heat dissipating structure **7d**. In addition, the thermal material **48** may be outflanked or surrounded by the third heat dissipating structure **7d**.

[0067] FIG. **6** illustrates a cross-sectional view of an electronic structure **4e** according to some embodiments of the present disclosure. FIG. **7** illustrates a perspective view of the electronic structure **4e** of FIG. **6**. FIG. **7A** illustrates a top view of FIG. **7**. The electronic structure **4e** of FIG. **6** and FIG. **7** is similar to the electronic structure **4d** of FIG. **5**, except that the first portion **61** of the second heat dissipating structure **6e** of the thermal structure **47e** may include a lower portion **611** and an upper portion **612** disposed on the lower portion **611**. A thickness of the upper portion **612** may be greater than or equal to a thickness of the lower portion **611**. There may be a visible interface or an obvious interface formed between the lower portion **611** and the upper portion **612**. The thickness of the lower portion **511** of the first portion **51** of the first heat dissipating structure **5b** is equal to a thickness of the lower portion **611** of the first portion **61** of the second heat dissipating structure **6e**. The thickness of the upper portion **512** of the first portion **51** of the first heat dissipating structure **5b** is greater than a thickness of the upper portion **612** of the first portion **61** of the second heat dissipating structure **6e**. As shown in FIG. **7**, the thermal material **48** may be outflanked or surrounded by the third heat dissipating structure **7d**.

[0068] FIG. **8** illustrates a cross-sectional view of an electronic structure **4f** according to some embodiments of the present disclosure. The electronic structure **4f** of FIG. **8** is similar to the electronic structure **4** of FIG. **1**, except for the structure of the thermal structure **47f**. The thermal structure **47f** may include a first heat dissipating structure **5f** and a second heat dissipating structure **6f** separated from the first heat dissipating structure **5f**. The first heat dissipating structure **5f** may include a first portion **51**, a plurality of second portions **52**, a plurality of third portions **53** and a plurality of fourth portions **54**. The second portions **52** may be disposed on the first portion **51**. Each of the third portions **53** may be disposed on each of the second portions **52**. Each of the fourth portions **54** may be disposed on each of the third portions **53**. A width of the first portion **51** may be greater than a width of the second portion **52**. A width of the third portion **53** may be greater than a width of the second portion **52**. A width of the fourth portion **54** may be greater than a width of the third portion **53**. The portions **51**, **52**, **53**, **54** of the first heat dissipating structure **5f** have different widths. Thus, a thermal path may be formed by the arrangement of stacking along a certain direction.

[0069] The second heat dissipating structure **6f** may include a first portion **61**, a second portion **62**, a third portion **63** and a fourth portion **64**. The second portion **62** may be disposed on the first portion **61**. The third portion **63** may be disposed on the second portion **62**. The fourth portion **64** may be disposed on the third portions **63**. A width of the first portion **61** may be greater than a width of the second portion **62**. A width of the third portion **63** may be greater than a width of the second portion **62**. A width of the fourth portion **64** may be greater than a width of the third portion **63**. The portions **61**, **62**, **63**, **64** of the second heat dissipating structure **6f** have different widths. A thickness of the first portion **61** of the second heat dissipating structure of may be less than a thickness of the first portion **51** of the first heat dissipating structure **5f**.

[0070] FIG. **8A** illustrates an enlarged view of a region "A" in FIG. **8**. In some embodiments, an end of an upper one of the portions **52**, **53**, **54** extends beyond a lateral surface of a lower one of the portions **52**, **53**, **54** under the upper one of the portions **52**, **53**, **54**. Thus, an end of an upper one of the portions **52**, **53**, **54** does not vertically overlap a lower one of the portions **52**, **53**, **54** under the upper one of the portions **52**, **53**, **54**. For example, the third portion **53** may be an upper portion

corresponding to the second portion **52** (such as a lower portion) under the third portion **53**. A first end **533** of the third portion **53** (e.g., the upper portion) may extend beyond a first lateral surface **521** of the second portion **52** (e.g., the lower portion). A second end **534** of the third portion **53** (e.g., the upper portion) may extend beyond a second lateral surface **522** of the second portion **52** (e.g., the lower portion). The first end **533** is opposite to the second end **534**, and the first lateral surface **521** is opposite to the second lateral surface **522**. The first end **533** and the second end **534** do not vertically overlap the second portion **52**. Each of the first end **533** and the second end **534** is an overhanging portion.

[0071] Similarly, the fourth portion **54** may be an upper portion corresponding to the third portion **53** (such as a lower portion) under the fourth portion **54**. A first end **543** of the fourth portion **54** (e.g., the upper portion) may extend beyond a first lateral surface **531** of the third portion **53** (e.g., the lower portion). A second end **544** of the fourth portion **54** (e.g., the upper portion) may extend beyond a second lateral surface **532** of the third portion **53** (e.g., the lower portion). The first end **543** is opposite to the second end **544**, and the first lateral surface **531** is opposite to the second lateral surface **532**. The first end **543** and the second end **544** do not vertically overlap the third portion **53**. Each of the first end **543** and the second end **544** is an overhanging portion. In addition, the thermal material **48** may define a plurality of first voids **481** located at a corner formed by a top surface of the first portion **51** and the lateral surfaces **521**, **522** of the second portion **52**, at a corner formed by a bottom surface of the third portion **53** and the lateral surfaces **521**, **522** of the second portion **52**, and at a corner formed by a bottom surface of the fourth portion **54** and the lateral surfaces **531**, **532** of the third portion **53**.

[0072] FIG. **9** illustrates a cross-sectional view of an electronic structure **4g** according to some embodiments of the present disclosure. The electronic structure **4g** of FIG. **9** is similar to the electronic structure **4f** of FIG. **8**, except for the structure of the thermal structure **47g**. The thermal structure **47g** may include a first heat dissipating structure **5g** and a second heat dissipating structure **6g**. The first heat dissipating structure **5g** may include a first portion **51**, a second portion **52**, a third portion **53**, a fourth portion **54**, a fifth portion **55** and a sixth portion **56**. The second portion **52** may be disposed on the first portion **51**. The third portion **53** may be disposed on the second portion **52**. The fourth portion **54** may be disposed on the third portion **53**. A thickness and a width of the first portion **51** may be greater than a thickness and a width of the second portion **52**. The second portion **52**, the third portion **53**, the fourth portion **54**, the fifth portion **55** and the sixth portion **56** may be stacked on one another.

[0073] The second heat dissipating structure **6g** may include a first portion **61**, a second portion **62**, a third portion **63**, a fourth portion **64** and a fifth portion **65**. The second portion **62** may be disposed on the first portion **61**. A width of the first portion **61** may be greater than a width of the second portion **62**. The second portion **62**, the third portion **63**, the fourth portion **64** and the fifth portion **65** may be stacked on one another.

[0074] FIG. **9A** illustrates an enlarged view of a region “B” in FIG. **9**. The second portion **52**, the third portion **53**, the fourth portion **54**, the fifth portion **55** and the sixth portion **56** may have a substantially same width and thickness, and may be stacked on one another and laterally offset from one another in a first direction **D1**. In some embodiments, the second portion **52** may be also referred to as “a first portion”, the third portion **53** may be also referred to as “a second portion”, and the fourth portion **54** may be also referred to as “a third portion”. A first end **523** of the second portion **52** (e.g., the upper portion) may extend beyond a first lateral surface **519** of the first portion **51** (e.g., the lower portion). A second end **524** of the second portion **52** (e.g., the upper portion) may not extend beyond a lateral surface of the first portion **51** (e.g., the lower portion). A first end **533** (or a second end) of the third portion **53** (e.g., the upper portion) may not extend beyond a first lateral surface **521** (or a second lateral surface) of the second portion **52** (e.g., the lower portion). The first end **533** (or a second end) of the third portion **53** may be recessed from the first lateral surface **521** (or a second lateral surface) of the second portion **52**. A second end **534** (or a first end)

of the third portion 53 (e.g., the upper portion) may extend beyond a second lateral surface 522 (or a first lateral surface) of the second portion 52 (e.g., the lower portion). A first end 543 (or a second end) of the fourth portion 54 may not extend beyond a first lateral surface 531 (or a second lateral surface) of the third portion 53. The first end 543 (or a second end) of the fourth portion 54 may be recessed from the first lateral surface 531 (or a second lateral surface) of the third portion 53. A second end 544 (or a first end) of the fourth portion 54 may extend beyond a second lateral surface 532 (or a first lateral surface) of the third portion 53. The fourth portion 54 may have a first lateral surface 541 corresponding to the first end 543, and a second lateral surface 542 corresponding to the second end 544. In addition, the thermal material 48 (e.g., thermal interface material (TIM)) may extend to under the third portion 53. The thermal material 48 (e.g., thermal interface material (TIM)) may contact a bottom surface 535 of the third portion 53.

[0075] A length of the first thermal path 91 between or from the first region 3' (e.g., the first electronic device 24) to the heat sink 46 by the first heat dissipating structure 5g is not a shortest distance d (or vertical distance or vertical gap) between the first region 3' (e.g., the first electronic device 24) and the heat sink 46. The entire first thermal path 91 may be not a straight line. The entire first thermal path 91 may have at least one turning point. In some embodiments, the first heat dissipating structure 5 may be disposed over the first electronic device 24, and may have the first thermal path 91 extending from the first electronic device 24 toward heat sink 46. The extending direction of the first thermal path 91 may be away from a vertical projection of the second electronic device 26, so as to prevent the heat generated by the first electronic device 24 from influencing the heat dissipation efficiency over the second electronic device 26.

[0076] Similarly, the second portion 62, the third portion 63, the fourth portion 64 and the fifth portion 65 may have a substantially same width, and may be stacked on one another and laterally offset from one another in a second direction D2. The second direction D2 is opposite to the first direction D1. Thus, a length of the second thermal path 92 between or from the second region 3'' (e.g., the second electronic device 26) to the heat sink 46 by the second heat dissipating structure 6g is not a shortest distance d (or vertical distance or vertical gap) between the second region 3'' (e.g., the second electronic device 26) and the heat sink 46. The entire second thermal path 92 may be not a straight line. The entire second thermal path 92 may have at least one turning point. In some embodiments, the second heat dissipating structure 6 may be disposed over the second electronic device 26, and may have the second thermal path 92 extending from the second electronic device 26 toward heat sink 46. The first thermal path 91 is thermally insulated from the second thermal path 92, and the first thermal path 91 is non-parallel with the second thermal path 92. The extending direction of the second thermal path 92 may be away from a vertical projection of the first electronic device 24, so as to prevent the heat generated by the second electronic device 26 from influencing the heat dissipation efficiency over the first electronic device 24. A gap g between the first thermal path 91 and the second thermal path 92 increases toward the heat sink 46.

[0077] FIG. 9B illustrates a cross-sectional view of an electronic structure 4g' according to some embodiments of the present disclosure. The electronic structure 4g' of FIG. 9B is similar to the electronic structure 4g of FIG. 9, except that the first portion 51, the second portion 52, the third portion 53, the fourth portion 54, the fifth portion 55 and the sixth portion 56 of the first heat dissipating structure 5g may have different width, and the first portion 61, the second portion 62, the third portion 63, the fourth portion 64 and the fifth portion 65 may have different width. A width of the sixth portion 56 may be greater than a width of the fifth portion 55. The width of the fifth portion 55 may be greater than a width of the fourth portion 54. The width of the fourth portion 54 may be greater than a width of the third portion 53. The width of the third portion 53 may be greater than a width of the second portion 52, a width of the fifth portion 65 may be greater than a width of the fourth portion 64. The width of the fourth portion 64 may be greater than a width of the third portion 63.

[0078] FIG. 10 illustrates a cross-sectional view of an electronic structure 4g'' according to some

embodiments of the present disclosure. The electronic structure **4g''** of FIG. **10** is similar to the electronic structure **4g** of FIG. **9**, except that the first portion **51**, the second portion **52**, the third portion **53**, the fourth portion **54** and the fifth portion **55** of the first heat dissipating structure **5g** may have different thickness and width, and the first portion **61**, the second portion **62**, the third portion **63** and the fourth portion **64** may have different thickness and width.

[0079] FIG. **11** illustrates a cross-sectional view of an electronic structure **4h** according to some embodiments of the present disclosure. The electronic structure **4h** of FIG. **11** is similar to the electronic structure **4g** of FIG. **9**, except for the structure of the thermal structure **47h**. Each of the second portion **52**, the third portion **53**, the fourth portion **54**, the fifth portion **55** and the sixth portion **56** of the first heat dissipating structure **5h** may have a curved top surface and a curved bottom surface. Each of the second portion **62**, the third portion **63**, the fourth portion **64** and the fifth portion **65** of the second heat dissipating structure **6h** may have a curved top surface and a curved bottom surface.

[0080] FIG. **12** illustrates a cross-sectional view of an electronic structure **4j** according to some embodiments of the present disclosure. The electronic structure **4j** of FIG. **12** is similar to the electronic structure **4g** of FIG. **9**, except for the structure of the thermal structure **47j**. The third portion **53**, the fourth portion **54** and the fifth portion **55** of the first heat dissipating structure **5j** may be non-parallel with the first portion **51** and the second portion **52**. That is, the extending direction of the third portion **53**, the fourth portion **54** and the fifth portion **55** of the first heat dissipating structure **5j** may be non-parallel with the extending direction of the first portion **51** and the second portion **52**. The third portion **53**, the fourth portion **54** and the fifth portion **55** may be tilted. For example, the second portion **52** (or the first portion) and the third portion **53** (or the second portion) may be non-parallel with each other along a horizontal direction. A portion of the second portion **52** (or the first portion) may laterally overlap with a portion of the third portion **53** (or the second portion). In addition, the thermal material **48** may define a first void **481** located between the second portion **52** and the third portion **53**, and between the second portion **52** and the fourth portion **54**.

[0081] The third portion **63** and the fourth portion **64** of the second heat dissipating structure **6j** may be non-parallel with the first portion **61** and the second portion **62**. That is, the extending direction of the third portion **63** and the fourth portion **64** of the second heat dissipating structure **6j** may be non-parallel with the extending direction of the first portion **61** and the second portion **62**. The third portion **63** and the fourth portion **64** may be tilted. In addition, the thermal material **48** may define a second void **482** located between the second portion **62** and the third portion **63**, and between the second portion **62** and the fourth portion **64**.

[0082] FIG. **13** illustrates a cross-sectional view of an electronic structure **4k** according to some embodiments of the present disclosure. The electronic structure **4k** may be also referred to as “an assembly structure” or “a semiconductor package”. The electronic structure **4k** may include a package structure **3a**, a thermal structure **47k** (including a first heat dissipating structure **5k** and a second heat dissipating structure **6k**), an electrical structure **7k**, a dielectric layer **80**, a plurality of via structures **82** and an upper electronic device **84**.

[0083] The package structure **3a** may include a wiring structure **1a**, an electronic device **24**, a first protection material **32**, at least one vertical conductive structure **38**, at least one pillar **37**, an encapsulant **34** and a plurality of solder materials **36**. The wiring structure **1a** may be similar to the wiring structure **1** of FIG. **1**. The wiring structure **1a** may have a first surface **11** and a second surface **12** opposite to the first surface **11**. The wiring structure **1a** may include a plurality of dielectric layers **14**, a plurality of circuit layers **15** in contact with the dielectric layer **14**, and a plurality of protrusion pads **21**. The circuit layer **15** may include a seed layer **155** and a conductive material **156** disposed on the seed layer **155**. The topmost dielectric layer **14** may define a plurality of openings (including, for example, openings **146** and openings **147**) to expose portions of the topmost circuit layer **15**. The protrusion pads **21** may be disposed in the openings **146** and on the

exposed portions of the topmost circuit layer **15**.

[0084] The electronic device **24** may be the same as or similar to the first electronic device **24** of FIG. **1**. The electronic device **24** may be a semiconductor device such as an application specific integrated circuit (ASIC) die. The first electronic device **24** may have a first surface **241**, a second surface **242** opposite to the first surface **241**, and a lateral side surface **243** extending between the first surface **241** and the second surface **242**. Further, the first electronic device **24** may include a plurality of circuit layers **248** and a plurality of electrical contacts **244** disposed adjacent to the first surface **241**. The circuit layer **248** may be embedded in the electronic device **24**, and may include a seed layer **246** and a conductive material **247** disposed on the seed layer **246**. The seed layer **246** may be formed by physical vapor deposition (PVD). The electrical contacts **244** may be electrically connected to the circuit layers **248**, and may be exposed or may protrude from the first surface **241** for electrical connection. In some embodiments, the electrical contacts **244** of the electronic device **24** may be electrically connected and physically connected to the protrusion pads **21** through a plurality of solder materials **245**. In other words, the electronic device **24** may be electrically connected to the wiring structure **1a** by flip-chip bonding. The electronic device **24** may include a first region **3'** and a second region **3''** different from the first region **3'**. A first predetermined temperature at the first region **3'** is higher than a second predetermined temperature at the second region **3''** during the operation of the package structure **3a**.

[0085] The vertical conductive structure **38** may be disposed around the electronic device **24**, and may be formed through a first chemical deposition process such as a 3D printing technique or 3D printing technology. A portion of the vertical conductive structure **38** may be disposed in the opening **147**. The vertical conductive structure **38** may include a plurality of portions **380** built on one another or stacked on one another. In some embodiments, the portions **380** may be laterally offset from one another. That is, the vertical central axes of the portions **380** may be misaligned with each other. Adjacent two of the plurality of portions **380** may form a step structure. Each of the portions **380** may include a rounded corner. The vertical conductive structure **38** may be encapsulated in the encapsulant **34**. The vertical conductive structure **38** may have a discontinuous lateral surface **385** or a non-flat lateral surface. A recess **386** may be formed between adjacent two of the portions **380**, and the encapsulant **34** may extend into the recess **386**. The vertical conductive structure **38** may be configured to dissipate a heat generated by the electronic device **24**. That is, the vertical conductive structure **38** may be a portion of a thermal path. In some embodiments, the vertical conductive structure **38** may be configured to transmit signal or power. That is, the vertical conductive structure **38** may be a portion of a signal transmission path or a portion of a power transmission path.

[0086] In some embodiments, an end of an upper one of the portions **380** extends beyond a lateral surface of a lower one of the portions **380** under the upper one of the portions **380**. Thus, an end of an upper one of the portions **380** does not vertically overlap a lower one of the portions **380** under the upper one of the portions **380**. For example, the portions **380** of the vertical conductive structure **38** may include a first portion **381**, a second portion **382** disposed on the first portion **381**, and a third portion **383** disposed on the second portion **382**. The first portion **381** may have a lateral surface **3815**. The second portion **382** may have a lateral surface **3825**. The third portion **383** may have a lateral surface **3835**. The lateral surface **385** of the vertical conductive structure **38** may include the lateral surface **3815** of the first portion **381**, the lateral surface **3825** of the second portion **382**, and the lateral surface **3835** of the third portion **383**.

[0087] The third portion **383** may be an upper portion corresponding to the second portion **382** (e.g., the lower portion) under the third portion **383**. An end **3836** of the third portion **383** (e.g., the upper portion) may extend beyond the lateral surface **3825** of the second portion **382** (e.g., the lower portion). The second portion **382** may be an upper portion corresponding to the first portion **381** (e.g., the lower portion) under the second portion **382**. An end **3826** of the second portion **382** (e.g., the upper portion) may extend beyond the lateral surface **3815** of the first portion **381** (e.g.,

the lower portion). The recess **386** may be formed between the first portion **381** and the second portion **382**, and the encapsulant **34** may extend into the recess **386**.

[0088] The pillar **37** may be disposed around the electronic device **24** and the vertical conductive structure **38**, and may be formed by physical vapor deposition (PVD). A portion of the pillar **37** may be disposed in the opening **147**. The pillar **37** may be a monolithic structure, and may have a single continuous lateral surface. The pillar **37** may be encapsulated in the encapsulant **34**. The vertical conductive structure **38** may be closer to the electronic device **24** than the pillar **37** is. The pillar **37** may be configured to transmit signal or power. That is, the pillar **37** may be a portion of a signal transmission path or a portion of a power transmission path.

[0089] The encapsulant **34** may encapsulate the electronic device **24**, the vertical conductive structure **38**, the pillar **37** and the wiring structure **1a**. One end of the vertical conductive structure **38** may be exposed by a top surface of the encapsulant **34** (e.g., the top surface **31** of the package structure **3a**). One end of the pillar **37** may be exposed by a top surface of the encapsulant **34** (e.g., the top surface **31** of the package structure **3a**). Thus, both the vertical conductive structure **38** and the pillar **37** may extend through the encapsulant **34**.

[0090] The thermal structure **47k** may include a first heat dissipating structure **5k** and a second heat dissipating structure **6k**, and may be disposed on or disposed over the top surface **31** of the package structure **3a** (e.g., the first surface **341** of the encapsulant **34** and the second surface **242** of the first electronic device **24**). The first heat dissipating structure **5k** and the second heat dissipating structure **6k** may be configured to dissipate the heat generated by the electronic device **24**, and may be formed through a second chemical deposition process such as a 3D printing technique or 3D printing technology.

[0091] The first heat dissipating structure **5k** may be disposed over or disposed on the first region **3'** of the electronic device **24**. The first heat dissipating structure **5k** may include a first portion **51**, a second portion **52** and a third portion **53** stacked on one another. The first portion **51** may contact the first region **3'**. An end of the second portion **52** may extend beyond a lateral surface of the first portion **51**. An end of the third portion **53** may extend beyond a lateral surface of the second portion **52**. The extending direction of the third portion **53** may be non-parallel with the extending direction of the first portion **51** and the second portion **52**. The third portion **53** may be tilted. The third portion **53** may have an inconsistent thickness. The third portion **53** may have a wavy top surface and a wavy bottom surface.

[0092] The second heat dissipating structure **6k** may be disposed over or disposed on the second region **3''** of the electronic device **24**. The second heat dissipating structure **6k** may include a first portion **61**, a second portion **62**, a third portion **63** and a fourth portion **64**. The first portion **61** may contact the second region **3''** and the third portion **383** of the vertical conductive structure **38**. Thus, the second heat dissipating structure **6k** may be electrically connected to and/or thermally connected to the vertical conductive structure **38**. A thickness of the first portion **61** may be less than a thickness of the first portion **51**. The second portion **62**, the third portion **63** and the fourth portion **64** may have a substantially same width and thickness, and may be stacked on one another and laterally offset from one another in a direction.

[0093] The electrical structure **7k** may be disposed over or disposed on the pillar **37**. The electrical structure **7k** may be configured to transmit signal or power, and may be formed through the second chemical deposition process such as a 3D printing technology. That is, the electrical structure **7k**, the first heat dissipating structure **5k** and the second heat dissipating structure **6k** may be formed through a same chemical deposition process such as a 3D printing technology. The electrical structure **7k** may include a first portion **71**, a second portion **72** and a third portion **73**. The first portion **71** may contact the pillar **37**. Thus, the electrical structure **7k** may be electrically connected to the pillar **37**. The second portion **72** and the third portion **73** may have a substantially same width and thickness, and may be stacked on one another and laterally offset from one another.

[0094] The dielectric layer **80** may cover the thermal structure **47k** (including the first heat

dissipating structure **5k** and the second heat dissipating structure **6k**), the electrical structure **7k** and the package structure **3a**. The dielectric layer **80** may include a molding compound with or without filler. Alternatively, the dielectric layer **80** may be made of a cured photoimageable dielectric (PID) material such as epoxy or polyimide (PI) including photoinitiators. The dielectric layer **80** may include a top surface **801**. The dielectric layer **80** may define a plurality of openings recessed from the top surface **801** so as to expose a portion of the first heat dissipating structure **5k**, a portion of the second heat dissipating structure **6k** and a portion of the electrical structure **7k**.

[0095] The via strictures **82** may be disposed in the openings of the dielectric layer **80** to contact the first heat dissipating structure **5k**, the second heat dissipating structure **6k** and the electrical structure **7k**. Thus, the via strictures **82** may be embedded in the dielectric layer **80** and electrically connected or thermally connected to the first heat dissipating structure **5k**, the second heat dissipating structure **6k** and the electrical structure **7k**. The via stricture **82** may include a seed layer **821** and a conductive material **822** disposed on the seed layer **821**. The seed layer **821** may be formed by physical vapor deposition (PVD). The conductive material **822** may be formed by electroplating. The first heat dissipating structure **5k**, the second heat dissipating structure **6k** and the electrical structure **7k** do not include seed layer. A grain size and a lattice of the material of the first heat dissipating structure **5k**, the second heat dissipating structure **6k** and the electrical structure **7k** may be different from a grain size and a lattice of the material of the seed layer **821** of the via stricture **82**.

[0096] The upper electronic device **84** may be attached to the via strictures **82** through a plurality of reflowable materials **86** (such as solder materials). Thus, the upper electronic device **84** may be electrically connected or thermally connected to the first heat dissipating structure **5k**, the second heat dissipating structure **6k** and the electrical structure **7k** through the reflowable materials **86** and the via strictures **82**. In some embodiments, the upper electronic device **84** may include a semiconductor chip, a package structure, a patterned circuit layer, a substrate or an interposer.

[0097] FIG. **14** illustrates a cross-sectional view of an electronic structure **4m** according to some embodiments of the present disclosure. The electronic structure **4m** of FIG. **14** is similar to the electronic structure **4k** of FIG. **13**, except for the structure of the first heat dissipating structure **5m** of the thermal structure **47m**. The first heat dissipating structure **5m** may include a first portion **51**, a second portion **52**, a third portion **53** and a fourth portion **54** that may be the same as or similar to the first portion **51**, the second portion **52**, the third portion **53** and the fourth portion **54** of the first heat dissipating structure **5g** of FIG. **9**.

[0098] FIG. **15** illustrates a cross-sectional view of an electronic structure **4n** according to some embodiments of the present disclosure. The electronic structure **4n** of FIG. **15** is similar to the electronic structure **4m** of FIG. **14**, and the differences therebetween are described as follows. The package structure **3a** and the dielectric layer **80** may have a convex warpage (or crying warpage). The package structure **3a** and the dielectric layer **80** may be convex toward the upper electronic device **84**. Thus, the gap between the upper electronic device **84** and the top surface **801** of the dielectric layer **80** may gradually increase from a center portion of the top surface **801** of the dielectric layer **80** toward a periphery portion of the top surface **801** of the dielectric layer **80**.

[0099] In addition, in the vertical conductive structure **38n**, a width of an upper one of the portions **380** is less than a width of a lower one of the portions **380** under the upper one of the portions **380**. For example, the third portion **383** may be an upper portion corresponding to the second portion **382** (such as a lower portion) under the third portion **383**. A width of the third portion **383** (e.g., the upper portion) may be less than a width of the second portion **382** (e.g., the lower portion). The second portion **382** may be an upper portion corresponding to the first portion **381** (such as a lower portion) under the second portion **382**. A width of the second portion **382** (e.g., the upper portion) may be less than a width of the first portion **381** (e.g., the lower portion). The shape of the vertical conductive structure **38n** may reduce the warpage of the package structure **3a**.

[0100] FIG. **16** illustrates a cross-sectional view of an electronic structure **4p** according to some

embodiments of the present disclosure. The electronic structure **4p** of FIG. **16** is similar to the electronic structure **4m** of FIG. **14**, and the differences therebetween are described as follows. The package structure **3a** and the dielectric layer **80** may have a concave warpage (or smiling warpage). The package structure **3a** and the dielectric layer **80** may be concave toward the upper electronic device **84**. Thus, the gap between the upper electronic device **84** and the top surface **801** of the dielectric layer **80** may gradually decrease from a center portion of the top surface **801** of the dielectric layer **80** toward a periphery portion of the top surface **801** of the dielectric layer **80**.

[0101] In addition, in the vertical conductive structure **38p**, a width of an upper one of the portions **380** is greater than a width of a lower one of the portions **380** under the upper one of the portions **380**. For example, the third portion **383** may be an upper portion corresponding to the second portion **382** (such as a lower portion) under the third portion **383**. A width of the third portion **383** (e.g., the upper portion) may be greater than a width of the second portion **382** (e.g., the lower portion). The second portion **382** may be an upper portion corresponding to the first portion **381** (such as a lower portion) under the second portion **382**. A width of the second portion **382** (e.g., the upper portion) may be greater than a width of the first portion **381** (e.g., the lower portion). The shape of the vertical conductive structure **38p** may reduce the warpage of the package structure **3a**. [0102] FIG. **17** through FIG. **22** illustrate a method for manufacturing an electronic structure according to some embodiments of the present disclosure. In some embodiments, the method is for manufacturing the electronic structure **4** of FIG. **1**.

[0103] Referring to FIG. **17**, a package structure **3** is provided. The package structure **3** may be the same as or similar to the package structure **3** of FIG. **1** except that the encapsulant **34** may cover the second surface **242** of the first electronic device **24**, the second surface **262** of the second electronic device **26** and the top surface **321** of the first protection material **32** in the gap **30**.

[0104] Referring to FIG. **18**, a grinding process is conducted so that the first surface **341** of the encapsulant **34**, the second surface **242** of the first electronic device **24**, the second surface **262** of the second electronic device **26** and the top surface **321** of the first protection material **32** in the gap **30** may be substantially coplanar with each other so as to form a top surface **31** of the package structure **3**.

[0105] Referring to FIG. **19**, a singulation process may be conducted to form the package structure **3**. Then, a thermal structure **47** (including a first heat dissipating structure **5** and a second heat dissipating structure **6**) is formed or disposed on the top surface **31** of the package structure **3** (e.g., the first surface **341** of the encapsulant **34**, the second surface **242** of the first electronic device **24**, the second surface **262** of the second electronic device **26** and the top surface **321** of the first protection material **32**). In some embodiments, the singulation process may be conducted after the thermal structure **47** is formed.

[0106] The thermal structure **47** (including a first heat dissipating structure **5** and a second heat dissipating structure **6**) of FIG. **19** may be the same as or similar to the thermal structure **47** (including a first heat dissipating structure **5** and a second heat dissipating structure **6**) of FIG. **1**. The first heat dissipating structure **5** and the second heat dissipating structure **6** may be formed through a chemical deposition process such as a 3D printing technology through a 3D printing apparatus **9**. The first heat dissipating structure **5** may be formed or disposed over or disposed on the first region **3'** (e.g., the first electronic device **24**). The second heat dissipating structure **6** may be formed or disposed over or disposed on the second region **3''** (e.g., the second electronic device **26**).

[0107] Referring to FIG. **20**, the package structure **3** is electrically connected to a first surface **401** of a base substrate **40** through the solder materials **36**. Then, a second protection material **44** (i.e., an underfill) is formed or disposed in a space between the package structure **3** and the base substrate **40** so as to cover and protect the solder materials **36**.

[0108] Referring to FIG. **21**, a thermal material **48** (e.g., a thermal interface material (TIM)) is formed or disposed to cover the first heat dissipating structure **5** and the second heat dissipating

structure 6.

[0109] Referring to FIG. 22, the heat sink 46 is provided. The heat sink 46 may be a cap or hat structure, and may define a cavity 461 for accommodating the package structure 3. A portion of the heat sink 46 may be attached to the top surface 31 of the package structure 3 through the thermal material 48 (e.g., thermal interface material (TIM)). The heat sink 46 may be thermally connected with the first heat dissipating structure 5 and the second heat dissipating structure 6 through the thermal material 48. Another portion (e.g., bottom portion) of the heat sink 46 may be attached to or thermally connected to the base substrate 40 through an adhesive material.

[0110] Then, the external connectors 49 (e.g., solder balls) are formed or disposed on the second surface 402 of the base substrate 40 for external connection. Then, a singulation process may be conducted to the base substrate 40 so as to obtain a plurality of electronic structures 4 shown in FIG. 1.

[0111] Spatial descriptions, such as “above,” “below,” “up,” “left,” “right,” “down,” “top,” “bottom,” “vertical,” “horizontal,” “side,” “higher,” “lower,” “upper,” “over,” “under,” and so forth, are indicated with respect to the orientation shown in the figures unless otherwise specified. It should be understood that the spatial descriptions used herein are for purposes of illustration only, and that practical implementations of the structures described herein can be spatially arranged in any orientation or manner, provided that the merits of embodiments of this disclosure are not deviated from by such an arrangement.

[0112] As used herein, the terms “approximately,” “substantially,” “substantial” and “about” are used to describe and account for small variations. When used in conjunction with an event or circumstance, the terms can refer to instances in which the event or circumstance occurs precisely as well as instances in which the event or circumstance occurs to a close approximation. For example, when used in conjunction with a numerical value, the terms can refer to a range of variation less than or equal to $\pm 10\%$ of that numerical value, such as less than or equal to $\pm 5\%$, less than or equal to $\pm 4\%$, less than or equal to $\pm 3\%$, less than or equal to $\pm 2\%$, less than or equal to $\pm 1\%$, less than or equal to $\pm 0.5\%$, less than or equal to $\pm 0.1\%$, or less than or equal to $\pm 0.05\%$. For example, two numerical values can be deemed to be “substantially” the same or equal if a difference between the values is less than or equal to $\pm 10\%$ of an average of the values, such as less than or equal to $\pm 5\%$, less than or equal to $\pm 4\%$, less than or equal to $\pm 3\%$, less than or equal to $\pm 2\%$, less than or equal to $\pm 1\%$, less than or equal to $\pm 0.5\%$, less than or equal to $\pm 0.1\%$, or less than or equal to $\pm 0.05\%$.

[0113] Two surfaces can be deemed to be coplanar or substantially coplanar if a displacement between the two surfaces is no greater than 5 μm , no greater than 2 μm , no greater than 1 μm , or no greater than 0.5 μm .

[0114] As used herein, the singular terms “a,” “an,” and “the” may include plural referents unless the context clearly dictates otherwise.

[0115] As used herein, the terms “conductive,” “electrically conductive” and “electrical conductivity” refer to an ability to transport an electric current. Electrically conductive materials typically indicate those materials that exhibit little or no opposition to the flow of an electric current. One measure of electrical conductivity is Siemens per meter (S/m). Typically, an electrically conductive material is one having a conductivity greater than approximately 104 S/m, such as at least 105 S/m or at least 106 S/m. The electrical conductivity of a material can sometimes vary with temperature. Unless otherwise specified, the electrical conductivity of a material is measured at room temperature.

[0116] Additionally, amounts, ratios, and other numerical values are sometimes presented herein in a range format. It is to be understood that such range format is used for convenience and brevity and should be understood flexibly to include numerical values explicitly specified as limits of a range, but also to include all individual numerical values or sub-ranges encompassed within that range as if each numerical value and sub-range is explicitly specified.

[0117] While the present disclosure has been described and illustrated with reference to specific embodiments thereof, these descriptions and illustrations are not limiting. It should be understood by those skilled in the art that various changes may be made and equivalents may be substituted without departing from the true spirit and scope of the present disclosure as defined by the appended claims. The illustrations may not be necessarily drawn to scale. There may be distinctions between the artistic renditions in the present disclosure and the actual apparatus due to manufacturing processes and tolerances. There may be other embodiments of the present disclosure which are not specifically illustrated. The specification and drawings are to be regarded as illustrative rather than restrictive. Modifications may be made to adapt a particular situation, material, composition of matter, method, or process to the objective, spirit and scope of the present disclosure. All such modifications are intended to be within the scope of the claims appended hereto. While the methods disclosed herein have been described with reference to particular operations performed in a particular order, it will be understood that these operations may be combined, sub-divided, or re-ordered to form an equivalent method without departing from the teachings of the present disclosure. Accordingly, unless specifically indicated herein, the order and grouping of the operations are not limitations of the present disclosure.

Claims

1. An electronic structure, comprising: a package structure having a top surface including a first region and a second region, wherein a first predetermined temperature at the first region is higher than a second predetermined temperature at the second region; a first heat dissipating structure including a first portion disposed on the first region; and a second heat dissipating structure including a first portion disposed on the second region, wherein the first portion of the first heat dissipating structure and the first portion of the second heat dissipating structure are concurrently formed through a 3D printing technique, and wherein a thickness of the first portion of the first heat dissipating structure is greater than a thickness of the first portion of the second heat dissipating structure.
2. The electronic structure of claim 1, wherein the package structure includes: a first electronic device disposed corresponding to the first region, and is configured to generate the first predetermined temperature; a second electronic device disposed corresponding to the second region, and is configured to generate the second predetermined temperature; and an encapsulant encapsulating the first electronic device and the second electronic device.
3. The electronic structure of claim 2, wherein the first heat dissipating structure is separated from the second heat dissipating structure.
4. The electronic structure of claim 3, further comprising a thermal interface material extending between the first heat dissipating structure and the second heat dissipating structure, and connecting to a heat sink.
5. The electronic structure of claim 4, further comprising a third heat dissipating structure configured to support the heat sink, wherein the third heat dissipating structure and the heat sink collectively define an accommodation space for accommodating the thermal interface material.
6. The electronic structure of claim 5, wherein a level of a top end of the third heat dissipating structure is higher than a top end of the first heat dissipating structure and a top end of the second heat dissipating structure.
7. The electronic structure of claim 6, wherein the heat sink is spaced apart from the first heat dissipating structure and the second heat dissipating structure.
8. An electronic structure, comprising: a package structure including a first electronic device and a second electronic device encapsulated by an encapsulant; a heat sink disposed over the package structure; a first heat dissipating structure disposed over the first electronic device, and having a first thermal path toward heat sink; and a second heat dissipating structure disposed over the

second electronic device, and having a second thermal path toward heat sink, wherein the first thermal path is thermally insulated from the second thermal path, and the first thermal path is non-parallel with the second thermal path.

9. The electronic structure of claim 8, wherein a gap between the first thermal path and the second thermal path increases toward the heat sink.

10. The electronic structure of claim 8, wherein the first heat dissipating structure includes a first portion and a second portion disposed on the first portion, wherein a first end of the second portion extends beyond a first lateral surface of the first portion, and a second end of the second portion is recessed from a second lateral surface of the first portion.

11. The electronic structure of claim 10, wherein the first heat dissipating structure further includes a third portion disposed on the second portion, wherein a first end of the third portion extends beyond a first lateral surface of the second portion, and a second end of the third portion is recessed from a second lateral surface of the second portion.

12. The electronic structure of claim 10, wherein the first portion and the second portion are non-parallel with each other along a horizontal direction.

13. The electronic structure of claim 12, wherein a portion of the first portion laterally overlaps with a portion of the second portion.

14. The electronic structure of claim 10, wherein the second portion has an inconsistent thickness.

15. The electronic structure of claim 10, further comprising a thermal interface material extending to under the second portion.

16. The electronic structure of claim 8, wherein a length of the first thermal path between the first electronic device and the heat sink is not a shortest distance between the first electronic device and the heat sink, and a length of the second thermal path between the second electronic device and the heat sink is not a shortest distance between the second electronic device and the heat sink.

17. An electronic structure, comprising: a package structure including: an electronic device; an encapsulant encapsulating the electronic device; and a vertical conductive structure encapsulated in the encapsulant and having a discontinuous lateral surface.

18. The electronic structure of claim 17, wherein the vertical conductive structure includes a first portion and a second portion disposed on the first portion, and an end of the second portion extends beyond a lateral surface of the first portion.

19. The electronic structure of claim 17, wherein the package structure further comprises a pillar encapsulated in the encapsulant, wherein the vertical conductive structure is closer to the electronic device than the pillar is, the vertical conductive structure is configured to dissipate a heat, and the pillar is configured to transmit signal or power.

20. The electronic structure of claim 17, wherein the vertical conductive structure includes a first portion and a second portion disposed on the first portion, wherein a recess is formed between the first portion and the second portion, and the encapsulant extends into the recess.
