

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250280521

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

CHEN; Ching-Jen

EMI GASKET FOR CARD DEVICE FORM FACTORS

Abstract

An EMI gasket assembly is disclosed that blocks gaps between a device card and a slot in a chassis that allows insertion of the device card. The EMI gasket assembly is attachable to a front plate of the device card such as an OCP 3.0 Specification compliant device card. The EMI gasket assembly includes a fabric-over-foam gasket extending the width of the front plate. The EMI gasket assembly includes a plurality of finger gaskets attachable to the front plate. The finger gaskets are positioned to hold the fabric-over-foam gasket on the front plate.

Inventors: CHEN; Ching-Jen (Taoyuan City, TW)

Applicant: Quanta Computer Inc. (Taoyuan City, TW)

Family ID: 96880843

Appl. No.: 18/594577

Filed: March 04, 2024

Publication Classification

Int. Cl.: H05K9/00 (20060101)

U.S. Cl.:

CPC H05K9/0015 (20130101); H05K9/0062 (20130101); H05K9/009 (20130101);

Background/Summary

TECHNICAL FIELD

[0001] The present disclosure relates generally to a gasket that protects card devices from electromagnetic interference (EMI). More particularly, aspects of this disclosure relate to a foam

gasket that effectively provides EMI protection for a device card form factor.

BACKGROUND

[0002] Electronic devices, such as servers, include numerous electronic components that are powered by a common power supply. Generally, servers are directed toward specific functions such as storing large amounts of data or processing. Server design begins with a chassis that includes power components and general controllers such as a baseboard management controller. Current large server designs include expansion slots that accept expansion device cards that may be plugged in to perform additional server functions, such as storage or processing. For example, a storage server may include slots for accommodating additional solid state drive (SSD) device cards while a processing server may include slots for device cards with processing units or network interface components.

[0003] A current generation of device cards meet certain requirements such as the OCP 3.0 Specification that defines a form factor that allows the device cards to be inserted through the front of a server chassis. This allows convenient attachment of the device cards without removing the server chassis from a rack. For example, a form factor card according to the OCP 3.0 specification includes a circuit board that supports various electronic components including a network interface controller module. The circuit board has a form factor pluggable module that extends from one edge. An opposite edge of the circuit board includes an edge connector that may be inserted sideways through a slot in a front panel of a server system to mate with either a right angle socket or a straddle socket on a motherboard. When the expansion card is inserted in the chassis, the pluggable module of the card extends through an aperture on the side of the chassis. This allows communication connectors to be inserted to allow signals to be received on expansion card components such as a network interface controller.

[0004] The opposite end of the edge connector has a faceplate with different mechanisms to pull out the card such as a pull tab version, an ejector latch version, and an internal lock version. The faceplate includes the opening for the pluggable modules and various apertures for connectors and ventilation. However, the slot of the server chassis is generally larger in area to allow for insertion of the card without any physical interference. The gaps between the slot and the card may allow external electromagnetic interference (EMI) to effect internal components on the card or in the server chassis.

[0005] In order to protect the card, various mechanisms may protect the components of the card from Electromagnetic Interference (EMI). Such mechanisms are based on a principle known as a Faraday cage, which Michael Faraday introduced. A Faraday cage is an enclosed conductive housing having a zero electrical field and forms the basis of known shielding technology. As it is not practical to build an all-welded enclosure around structures such as a card faceplate, most enclosures require various openings for controls, access panels, ventilation, and the like. These gaps/discontinuities account for most of the leakage in a shielding enclosure. Discontinuities should be minimized and designed to maintain shielding effectiveness by proper seam treatment, and use of EMI shielding gaskets. Such gaskets are generally conformed to block openings in the faceplate of a card.

[0006] The function of an EMI gasket is to preserve continuity in the gap or slot of a shield. These gaskets are made from conductive materials and are strategically placed to block interfering signals from entering or exiting electronic devices. In other words, shielding not only reduces internal EMI radiation, but it also uses to limit external electrostatic discharge (ESD). Using a highly conductive material for the enclosure, gaskets have apparent advantages to seal discontinuity and help increase shielding effectiveness. Thus, EMI seals frequently are used to seal removable panels, covers, doors and removable parts such as OCP (Open Compute Project) 3.0 compliant adapter cards. Currently, OCP 3.0 compliant adapter cards are key parts of server systems for providing network interface functionality.

[0007] FIG. 1A shows a perspective view of an expansion device card **10** compliant with the OCP

3.0 form factor specification. FIG. 1B shows a side view of the card **10**. The expansion device card **10** includes a faceplate **12** that has a front plate **14**, a top flange **16**, and a bottom flange **18**. The top flange **16** and the bottom flange **18** are perpendicularly oriented to the front plate **14**. The front plate **14** includes side tabs **20** and **22** that extend perpendicularly from the sides of the front plate **14**. The faceplate **12** is attached perpendicularly to a rectangular circuit board **30**. The front plate **14** includes various air holes for air cooling and an aperture **32** that allows modular operational components mounted on the circuit board **30** to extend outward. The top flange **16** has a series of slots **34** that allow a gasket **36** to be inserted to provide protection against EMI.

[0008] The circuit board **30** has a top surface that supports operational components such as a Quad Small Form-Factor Pluggable (QSFP) connector module **40** that includes a controller chip **42**. The circuit board **30** has a heat sink **44** that is mounted over the controller **42** to assist in heat transfer away from the controller **42** and other components. The pluggable module **40** has a QSFP socket connector **46** that faces out from the respective aperture **32** of the front plate **14**. A distal edge of the circuit board **30** opposite the faceplate **12** includes golden finger connectors that define an edge connector **48**. The edge connector **48** is insertable into a straddle mount or right-angle connector socket on a motherboard of a computer system.

[0009] FIG. 1C is a perspective view of the OCP 3.0 expansion device card **10** in FIG. 1A installed in a server system chassis **50**. In this example, the server system chassis **50** has a panel **52** that includes a slot **54** that allows the expansion card **10** to be inserted into the server system chassis **50**. The socket connector **46** of the small form factor pluggable module **40** extends through the aperture **32** in the front plate **14** of the expansion card **10** and thus is accessible from outside the server system chassis **50**. When the expansion card **10** is inserted fully into the slot **54**, the edge connector **48** is connected to a straddle mount connector socket in the chassis **50**. The slot **54** must have a sufficient cross section area to allow the card **10** to be easily inserted. Thus, even when the card **10** is attached through in the slot **54**, gaps exist between the faceplate **12** and the sides of the slot **54**. This may risk EMI to the internal components.

[0010] The known electro-magnetic interference (EMI) gasket **36** is fabricated from high strength metal alloys such as beryllium (CuBe). The gasket **36** includes a support structure that joins one end of a series of fingers **60** that are mounted on the top flange **16**. The fingers **60** have a “C” shape to block the gap between the slot **54** and the top flange **16**. Thus, the gasket **36** extends over the width of the expansion card **10**. The free end of some of the fingers **60** are inserted in the slots **34** to allow the gasket **36** to be fixed to the top flange **16**. A similar bottom EMI finger gasket extends over the width of the expansion card **10** and is mounted on the bottom of the front plate **14** to plug any bottom gap between the bottom flange **18** and the slot **54**. The known finger strip based (finger stock) gaskets such as the gasket **36** withstand lateral shearing forces as well as perpendicular forces, for direct-compression applications. However, the disadvantage of the metal gasket **36** is that the width of the gasket **36** is defined by the number of fingers of the gasket and the overall width is a multiple of the width of the individual fingers **60**. The widths available are therefore a manufacturing limitation that prevents correct sizing of the gasket **36** to plug the entire gap as the number of fingers can only approximately match the width of a slot. Thus, gaps **70** and **72** are created at both ends of the card relative to the slot **54** when the gasket **36** is attached. The gaps **70** and **72** create the possibility of unwanted EMI for the components in the server chassis.

[0011] Another alternative for device cards is a fabric-over-foam (FOF) EMI gasket. These types of gaskets provide a wide range of excellent EMI shielding performance for expansion cards. FOF gaskets are composed of electrically conductive fabric wrapped around a soft foam core and include with a conductive pressure sensitive adhesive (PSA). Such a gasket is simply joined to the top flange **16** by the pressure sensitive adhesive and serves to block off gaps in the slot **54**.

Compared to metal-based finger strip gaskets, which are manufactured from high strength and high conductive alloys, a FOF gasket has the advantages of low cost and ease of installation.

[0012] As shown in U.S. Pat. No. 7,763,810 B2, entitled “Fabric-Over-Foam EMI Gaskets Having

Transverse Slits and Related Methods,” an undesirable side effect for such gasket may be discontinuities and gaps of the gasket that reduce the conductivity of gasket. For applications where space is limited, grooves and wide flanges may not be feasible as such features may interfere with the space required for the components on the card. When shear forces on the FOF gasket are created from contact with the slot when inserting or removing the card, the adhesion of the FOF gasket to the top plate of the front plate may fail, causing movement of the EMI gasket or a decrease in the electrical contact between the EMI gasket and the front panel.

[0013] Thus, there is a need for a gasket assembly that may use existing mechanisms to protect a device card from EMI in gaps between the device card and a slot. There is also a need for a gasket assembly that may employ the flexibility of a fabric-over-foam gasket with necessary strength to withstand shear forces. There is also a need for a gasket assembly that may be attached to existing device card form factors without modifying the form factor.

SUMMARY

[0014] One disclosed example is an electro-magnetic interference (EMI) gasket assembly for attachment to a front plate of a device card. The EMI gasket assembly includes a fabric-over-foam gasket extending the width of the front plate. A plurality of finger gaskets are attachable to the front plate. The finger gaskets are positioned to hold the fabric-over-foam gasket on the front plate.

[0015] In another implementation of the disclosed example gasket assembly, the fabric-over-foam gasket is configured to contact a top planar flange of the front plate. In another implementation, the top planar flange includes a plurality of slots. An edge of each of the plurality of finger gaskets is configured to be inserted in one of the plurality of slots of the top planar flange. In another implementation, the assembly includes a bottom fabric-over-foam gasket and a bottom plurality of gaskets attachable to a bottom edge of the front plate. The fabric-over-foam gasket and plurality of finger gaskets are attached at a top edge of the front plate. In another implementation, the finger gaskets are fabricated from a metal alloy. In another implementation, the fabric-over-foam gasket includes an outer conductive fabric of metal fibers enclosing a foam core. In another implementation, the fabric-over-foam gasket includes an adhesive for adhering the fabric-over-foam gasket to the front plate.

[0016] Another disclosed example is device card including a circuit board having a connector edge and an opposite front edge. A front plate is coupled to front edge of the circuit board. The front plate and circuit board are insertable into a slot on a panel of a chassis. A fabric-over-foam gasket extends the width of the front plate. A plurality of finger gaskets are attached to the front plate. The finger gaskets are positioned to hold the fabric-over-foam gasket on the front plate. The fabric-over-foam gasket and finger gaskets block gaps between the front plate and the slot.

[0017] In another implementation of the disclosed example device card, the device card and front plate are compliant with the OCP 3.0 Specification. In another implementation, the front plate includes a top planar flange in contact with the fabric-over-foam gasket. In another implementation, the top planar flange includes a plurality of slots. An edge of each of the plurality of finger gaskets is inserted in one of the plurality of slots of the top planar flange. In another implementation, a bottom fabric-over-foam gasket and a bottom plurality of gaskets are attached to a bottom edge of the front plate. The fabric-over-foam gasket and plurality of finger gaskets are attached at a top edge of the front plate. In another implementation, the finger gaskets are fabricated from a metal alloy. In another implementation, the fabric-over-foam gasket includes an outer conductive fabric of metal fibers enclosing a foam core. In another implementation, the fabric-over-foam gasket includes an adhesive adhering the fabric-over-foam gasket to the front plate.

[0018] Another disclosed example is a computing system including a chassis having an internal connector and a panel with a slot. A device card has a circuit board, a front plate, an operating component and a connector. The device card is insertable in the slot such that the connector is connected to the internal connector. A gasket assembly is connected to the device card to shield

gaps between the slot and the device card. The gasket assembly includes a fabric-over-foam gasket extending the width of the front plate. A plurality of finger gaskets are attached to the front plate. The finger gaskets are positioned to hold the fabric-over-foam gasket on the front plate.

[0019] The above summary is not intended to represent each embodiment or every aspect of the present disclosure. Rather, the foregoing summary merely provides an example of some of the novel aspects and features set forth herein. The above features and advantages, and other features and advantages of the present disclosure, will be readily apparent from the following detailed description of representative embodiments and modes for carrying out the present invention, when taken in connection with the accompanying drawings and the appended claims.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0020] The disclosure will be better understood from the following description of exemplary embodiments together with reference to the accompanying drawings, in which:

[0021] FIG. 1A is a view of a device card having a prior art finger type gasket installed;

[0022] FIG. 1B is a side perspective view of the device card and prior art finger type gasket;

[0023] FIG. 1C is a perspective view of the device card and prior art finger type gasket in FIG. 1A inserted in a computer device;

[0024] FIG. 2A is a top view of a card prior to the attachment of the example EMI protection gasket assembly;

[0025] FIG. 2B is a top view of the card in FIG. 2A with an example foam on fabric gasket placed on the front plate, according to certain aspects of the present disclosure;

[0026] FIG. 2C is a top view of the card in FIG. 2A showing the installation of individual finger gaskets over the fabric gasket, according to certain aspects of the present disclosure;

[0027] FIG. 3A is a top view of the card in FIG. 2A with the example combined finger and foam on fabric gasket assembly, according to certain aspects of the present disclosure;

[0028] FIG. 3B is a perspective view of the card in FIG. 2A with the example combined finger and foam on fabric gasket assembly, according to certain aspects of the present disclosure;

[0029] FIG. 4 is a bottom view of the card in FIG. 2A with another example combined finger and foam on fabric gasket assembly, according to certain aspects of the present disclosure;

[0030] FIG. 5 is a cross-section view of the foam on fabric gasket in FIG. 2B, according to certain aspects of the present disclosure; and

[0031] FIG. 6 is a cross-section view of one of the finger gaskets installed over the foam on fabric gasket on the top bracket of the card in FIG. 2A, according to certain aspects of the present disclosure.

[0032] The present disclosure is susceptible to various modifications and alternative forms. Some representative embodiments have been shown by way of example in the drawings and will be described in detail herein. It should be understood, however, that the invention is not intended to be limited to the particular forms disclosed. Rather, the disclosure is to cover all modifications, equivalents, and alternatives falling within the spirit and scope of the invention as defined by the appended claims.

DETAILED DESCRIPTION

[0033] The present inventions can be embodied in many different forms. Representative embodiments are shown in the drawings, and will herein be described in detail. The present disclosure is an example or illustration of the principles of the present disclosure, and is not intended to limit the broad aspects of the disclosure to the embodiments illustrated. To that extent, elements, and limitations that are disclosed, for example, in the Abstract, Summary, and Detailed Description sections, but not explicitly set forth in the claims, should not be incorporated into the

claims, singly or collectively, by implication, inference, or otherwise. For purposes of the present detailed description, unless specifically disclaimed, the singular includes the plural and vice versa; and the word “including” means “including without limitation.” Moreover, words of approximation, such as “about,” “almost,” “substantially,” “approximately,” and the like, can be used herein to mean “at,” “near,” or “nearly at,” or “within 3-5% of,” or “within acceptable manufacturing tolerances,” or any logical combination thereof, for example.

[0034] The present disclosure is directed toward gasket assembly that includes a fabric-over-foam gasket in combination with metal finger gaskets that minimizes the gap/discontinuity between a device card and a panel slot. The assembly maintains shielding effectiveness by proper seam treatment, and use of EMI shielding gaskets. The assembly has the advantage of the flexibility of a fabric-over-foam gasket while leveraging the shear resistance of a metal finger gasket.

[0035] FIG. 2A shows a view of the card **10** in FIG. 1A with the faceplate **12** without protection from EMI between the faceplate **12** and a slot where the card is inserted. Like elements in FIG. 1A are labeled with identical reference numbers in FIG. 2A. Although the example card **10** is compliant with the form factor requirements in the OCP 3.0 specification, the principles herein relating to a gasket assembly may be applied to protect any component that is inserted in a slot or aperture of a panel from EMI.

[0036] The card **10** has a OCP 3.0 compliant form factor in FIG. 2A and is shown before installation into a computer system such as the computer system shown in FIG. 1C. As may be seen in FIG. 2A, the exterior surface of the top flange **16** of the front plate **14** extends the width of the card **10**. As explained above the top flange **16** has a planar surface with the series of parallel slots **34**.

[0037] As shown in FIG. 2B, an example fabric-over-foam gasket **200** may be inserted over the top flange **16** in proximity to the slots **34**. The fabric-over-foam gasket **200** has a length that is sufficient to match the width of the card **10**. In this example, the fabric-over-foam gasket **200** has a roughly rectangular shape that may be tailored to the width of the card **10**. For example, the gasket **200** may be supplied in strips that may be cut to approximately match the width of the card **10**. The height of the fabric-over-foam gasket **200** is selected so the gasket **200** can fill any gap between a slot in a chassis such as the slot **54** in FIG. 1C and the top flange **16** of the front plate **14**.

[0038] The fabric-over-foam gasket **200** can be compressed to fill slightly smaller gaps between the card and the slot of the computing system. Thus, the height of the fabric-over-foam gasket **200** may be slightly larger than the gap between the top flange **16** and the top of a slot in a chassis panel. In this example, the fabric-over-foam gasket **200** may have an adhesive strip that allows it to be attached to the planar surface of the top flange **16** in this example. Alternatively, the fabric-over-foam gasket **200** may be held in place by the conventional finger gaskets as will be explained that are combined with the gasket **200**.

[0039] FIG. 2C shows the installation of separate finger gaskets **210** that engage the slots **34** in the top flange **16** of the card **10**. As may be seen in FIG. 2C, each of the finger gaskets **210** has opposing side edges that have a curved shape. One of the side edges is inserted in a corresponding one of the slots **34** in the top flange **16**. An opposite end of the finger gasket **210** is attached to the underside of a leading edge **212** of the top flange **16**. The gasket **210** has a semi-circular shape and thus may be compressed to block the gap between the top flange **16** and the top of the slot. The gasket **210** may utilize compressive force hold the fabric-over-foam gasket **200** in place. Multiple gaskets such as the gaskets **210** may be used in conduction with the slots **34**.

[0040] FIG. 3A shows a top view of the card **10** with the installation of all of the finger gaskets **210** in the respective slots **34** in the top flange **16**. FIG. 3B shows a perspective view of the finger gaskets **210** and the fabric-over-foam gasket **200** on the card **10**. As shown in FIG. 3A-3B, the finger gaskets **210** are located over the FOF gasket **200** that extends the width of the top flange **16**. The assembly of the fabric on foam gasket **200** and the finger gaskets **210** plug any gaps that may allow EMI, while have shear resistance due to the strength of the finger gaskets **210**. In this

example, individual finger gaskets **210** are attached to the top flange **16**. However, a conventional gasket having a support member attached to one end of the finger gaskets may also be used, saving the need for individual finger gaskets.

[0041] FIG. **4** shows a bottom view of the card **10** with the installation of another gasket assembly to shield EMI from gaps in the space between the bottom of the front plate **14** and the bottom of the slot through which the card **10** is inserted. In this example, a mylar cover **410** is positioned over the bottom side of the circuit board **30** to protect against EMI and dirt and debris. The bottom flange **18** has a flat surface with slots **412**. The bottom flange includes two edge indentations **414** that allow screws to be inserted to attach the bottom flange **18** to the circuit board **30**. An open edge **416** of the bottom flange **18** is positioned over one end of the bottom side of the circuit board **30**. One edge **420** of the mylar cover **410** is attached to the underside of the open edge **416** of the bottom flange **18**. The mylar cover **410** has an opposite edge **422** that rests on the opposite end of the circuit board **30** near the edge connector **48**. Labels **424** may be affixed to the mylar cover **410** to provide useful card device information.

[0042] In this example, the EMI gasket assembly in FIG. **4** includes a fabric-over-foam gasket **430** that is positioned over the width of the bottom flange **18**. A series of finger gaskets **440** similar to the gaskets **210** shown in FIGS. **3A-3B** have one edge inserted in the respective slots **412**. The other edge is inserted around the open edge **416** to hold the respective finger gaskets **440** in place. The compressive force applied by each finger gasket **440** also serves to fix the fabric-over-foam gasket **430** in place.

[0043] FIG. **5** shows a cross-section of the example fabric-over-foam gasket **200**. The fabric-over-foam gasket **200** has a conductive fabric layer **510** that encloses a foam core **512**. In this example the gasket **200** has a rectangular cross-section and thus the conductive fabric layer **510** forms a top, a bottom, and side panels. The conductive fabric layer **510** is electrically conductive and wrapped around the foam core **512**. The conductive fabric layer **510** provides shielding attenuation and high conductivity. In this example, conductive fabric layer **510** may be Nickel/copper (Ni/Cu) woven metal fibers that ensures effective conductivity and shielding effectiveness across a spectrum of frequencies. Alternatively, the conductive fabric layer **510** may be Tin/copper (Sn/Cu) fibers for versatile galvanic compatibility and shielding. In this example, the foam core **512** structure and resilience for the gasket **200**. Thus, materials for the core are those that ensure that the gasket **200** maintains its shape while exerting minimal pressure. An example material may be Polyurethane (PU) foam with low compression force. Another example of a foam material may be a soft silicone foam core, which offers good EMI shielding and grounding properties over a wide temperature range (from -40°C . to 125°C .). In this example, an adhesive strip **514** of PSA tape is attached to on the bottom of the conductive fabric layer **510**. The adhesive strip **514** may be used to attach the fabric-over-foam gasket **200** to a planar surface.

[0044] FIG. **6** shows a cross-section of the engagement of one of the finger gaskets **210**. In this example, the finger gasket **210** has a curved main body **610** having opposite ends **612** and **614**. One of the ends such as end **612** is inserted in the slot **34** formed in the top flange **16**. The end **614** is inserted under the edge of the top flange **16**. As shown in FIG. **6**, the compression from the finger gasket **210** partially compresses the fabric-over-foam gasket **200**.

[0045] In the example gasket assembly in FIG. **3A**, the EMI fabric-over-foam gasket **200** and metal alloy finger gaskets **210** constitute a gasket assembly that functions to block EMI. The gasket assembly is joined to the top flange **16** of the front plate **14** to retain and provide strength and rigidity for the gasket assembly. The flange surface geometry could be flat such as the top flange **16**, or differently shaped to completely enclose the gasket.

[0046] Thus, the EMI gasket assembly includes the FOF gasket **200** and the finger gaskets **210** that can be jointly attached in the top flange **16** of any card requiring EMI shielding such as an OCP 3.0 complaint adapter card. By retrofitting a card with an existing flange with the FOF gasket **200** and finger gaskets **210**, a performance advantage comes from dual functional properties of low cost and

ease of installation through simple retrofit of the existing flange. Further, the assembly minimizes the gaps/discontinuities and to reduce lateral shearing forces for shielding improvement. The improvement in shielding from the example gasket assembly not only reduces EMI radiations, but also improves immunity to electro-static discharge (ESD).

[0047] The terminology used herein is for the purpose of describing particular embodiments only, and is not intended to be limiting of the invention. As used herein, the singular forms “a,” “an,” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise. Furthermore, to the extent that the terms “including,” “includes,” “having,” “has,” “with,” or variants thereof, are used in either the detailed description and/or the claims, such terms are intended to be inclusive in a manner similar to the term “comprising.”

[0048] Unless otherwise defined, all terms (including technical and scientific terms) used herein have the same meaning as commonly understood by one of ordinary skill in the art. Furthermore, terms, such as those defined in commonly used dictionaries, should be interpreted as having a meaning that is consistent with their meaning in the context of the relevant art, and will not be interpreted in an idealized or overly formal sense unless expressly so defined herein.

[0049] While various embodiments of the present invention have been described above, it should be understood that they have been presented by way of example only, and not limitation. Numerous changes to the disclosed embodiments can be made in accordance with the disclosure herein, without departing from the spirit or scope of the invention. Thus, the breadth and scope of the present invention should not be limited by any of the above described embodiments. Rather, the scope of the invention should be defined in accordance with the following claims and their equivalents.

[0050] Although the invention has been illustrated and described with respect to one or more implementations, equivalent alterations, and modifications will occur or be known to others skilled in the art upon the reading and understanding of this specification and the annexed drawings. In addition, while a particular feature of the invention may have been disclosed with respect to only one of several implementations, such feature may be combined with one or more other features of the other implementations as may be desired and advantageous for any given or particular application.

Claims

1. An electro-magnetic interference (EMI) gasket assembly for attachment to a front plate of a device card, the EMI gasket assembly comprising: a fabric-over-foam gasket extending over a width of the front plate; and a plurality of finger gaskets attachable to the front plate, wherein the finger gaskets are positioned to hold the fabric-over-foam gasket on the front plate and wherein the finger gaskets each include a curved main body with opposite ends, wherein an angled end segment extends under the curved main body from each of the opposite ends, and wherein the end segments are insertable under an edge of the front plate.
2. The assembly of claim 1, wherein the fabric-over-foam gasket is configured to contact a top planar flange of the front plate.
3. The assembly of claim 2, wherein the top planar flange includes a plurality of slots, and wherein each of the end segments each of the plurality of finger gaskets is configured to be inserted into one of the plurality of slots of the top planar flange.
4. The assembly of claim 1, further comprising a bottom fabric-over-foam gasket; and a bottom plurality of finger gaskets attachable to a bottom edge of the front plate, wherein the fabric-over-foam gasket and plurality of finger gaskets are attachable at a top edge of the front plate.
5. The assembly of claim 1, wherein the finger gaskets are fabricated from a metal alloy.
6. The assembly of claim 1, wherein the fabric-over-foam gasket includes an outer conductive fabric of metal fibers enclosing a foam core.

7. The assembly of claim 6, wherein the foam core is one of polyurethane or silicone.
 8. The assembly of claim 6, wherein the fabric-over-foam gasket includes an adhesive for adhering the fabric-over-foam gasket to the front plate.
 9. A device card comprising: a circuit board having a connector edge and an opposite front edge; a front plate coupled to front edge of the circuit board, wherein the front plate and circuit board are insertable into a slot on a panel of a chassis; a fabric-over-foam gasket extending a width of the front plate; and a plurality of finger gaskets are attached to the front plate, wherein the finger gaskets are positioned to hold the fabric-over-foam gasket on the front plate, and wherein the finger gaskets each include a curved main body with opposite ends, wherein an angled end segment extends under the curved main body from each of the opposite ends, and wherein the end segments are insertable under an edge of the front plate, and wherein the fabric-over-foam gasket and finger gaskets block gaps between the front plate and the slot.
 10. The device card of claim 9, wherein the device card and the front plate are compliant with the OCP 3.0 Specification.
 11. The device card of claim 9, wherein the front plate includes a top planar flange in contact with the fabric-over-foam gasket.
 12. The device card of claim 11, wherein the top planar flange includes a plurality of slots, wherein each of the end segments of each of the plurality of finger gaskets is inserted in one of the plurality of slots of the top planar flange.
 13. The device card of claim 9, further comprising a bottom fabric-over-foam gasket and a bottom plurality of gaskets are attached to a bottom edge of the front plate, wherein the fabric-over-foam gasket and plurality of finger gaskets are attached at a top edge of the front plate.
 14. The device card of claim 9, wherein the finger gaskets are fabricated from a metal alloy.
 15. The device card of claim 9, wherein the fabric-over-foam gasket includes an outer conductive fabric of metal fibers enclosing a foam core.
 16. The device card of claim 15, wherein the foam core is one of polyurethane or silicone.
 17. The device card of claim 15, wherein the fabric-over-foam gasket includes an adhesive adhering the fabric-over-foam gasket to the front plate.
 18. A computer system comprising: a chassis having an internal connector and a panel with a slot; a device card including a circuit board, a front plate, an operating component and a connector, the device card insertable in the slot such that the connector is connected to the internal connector; and a gasket assembly connected to the device card to shield gaps between the slot and the device card, the gasket assembly including: a fabric-over-foam gasket extending a width of the front plate; and a plurality of finger gaskets are attached to the front plate, wherein the finger gaskets each include a curved main body with opposite ends, wherein an angled end segment extends under the curved main body from each of the opposite ends, and wherein the end segments are insertable under an edge of the front plate, and wherein the finger gaskets are positioned to hold the fabric-over-foam gasket on the front plate.
 19. The computer system of claim 18, wherein the fabric-over-foam gasket includes an outer conductive fabric of metal fibers enclosing a foam core.
 20. The computer system of claim 19, wherein the foam core is one of polyurethane or silicone.
-