

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250270964

Kind Code

A1

Publication Date

August 28, 2025

Inventor(s)

UCHIDA; Akito

VEHICLE WITH ENGINE

Abstract

A vehicle, with an engine, includes an engine control unit. The engine control unit is configured to control the engine in a circuit mode in which a traveling performance of the vehicle is improved, on a basis of a request transmitted from a portable terminal, when the portable terminal operated by a user of the vehicle determines that a current position of the vehicle equipped with the engine is in a circuit.

Inventors: UCHIDA; Akito (Toyota-shi, JP)

Applicant: TOYOTA JIDOSHA KABUSHIKI KAISHA (Toyota-shi, JP)

Family ID: 1000008377054

Assignee: TOYOTA JIDOSHA KABUSHIKI KAISHA (Toyota-shi, JP)

Appl. No.: 19/005191

Filed: December 30, 2024

Foreign Application Priority Data

JP 2024-027621

Feb. 27, 2024

Publication Classification

Int. Cl.: F02D31/00 (20060101); B60K35/28 (20240101)

U.S. Cl.:

CPC F02D31/001 (20130101); B60K35/28 (20240101); B60K2360/168 (20240101)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION

[0001] This application is based upon and claims the benefit of priority of the prior Japanese Patent Application No. 2024-027621, filed on Feb. 27, 2024, the entire contents of which are incorporated herein by reference.

TECHNICAL FIELD

[0002] The present disclosure relates to a vehicle with an engine.

BACKGROUND

[0003] A limiter is known to limit various functions for safety setting, fuel saving, and the like of a vehicle. As the various functions for safety setting, for example, a sideslip prevention function such as an anti-lock brake system is known. As a function for saving fuel, for example, a variable cylinder management system is known in which “one third or half” of an engine is automatically stopped depending on the traveling state to save fuel.

[0004] Further, a technique is known in which a current position of the vehicle is identified from data acquired by a global positioning system (GPS) and map information, and the amount of steering force assist is changed if a road is a circuit road. In addition, a technique is known in which the above-described limiter is released when it is determined that a vehicle is positioned in a circuit (see, for example, Japanese Unexamined Patent Application Publication No. 2015-199382).

[0005] Depending on the traveling state of the vehicle, the engine speed might increase beyond the maximum engine speed assumed at the time of design, that is, so-called over-revving might occur. In this case, engine components might be subjected to a stress greater than expected, which might reduce the durability of the components. For example, when the stress greater than expected is applied to the components such as a connecting rod, a piston, a cylinder head, or a camshaft of the engine, the durability of the components might be reduced. In order to suppress a decrease in durability of the components, the occurrence of over-revving may be limited by the limiter.

[0006] On the other hand, in a circuit mode for improving the traveling performance of the vehicle on the circuit road, it is also assumed that the limiter for limiting the occurrence of over-revving is released to increase the maximum engine speed. In this case, the deterioration of the durability of the components is not caused by the occurrence of over-revving, but is caused by the switching to the circuit mode based on the intention of a driver of the vehicle.

[0007] If the criterion for determining the occurrence of over-revving differs depending on whether or not the mode is switched to the circuit mode, it might be difficult to find a decrease in the durability of the components. For example, it is also assumed that the maximum engine speed is increased as described above in accordance with the switching to the circuit mode. However, when an initial first threshold for determining the occurrence of over-revving is changed to another second threshold at the same timing as the increase in the maximum engine speed, it might be difficult to determine the occurrence of over-revving.

SUMMARY

[0008] It is therefore an object of the present disclosure to provide a vehicle, with an engine, which uniquely determines occurrence of over-revving regardless of whether or not a circuit mode is switched.

[0009] The above object is achieved by a vehicle with an engine, the vehicle including an engine control unit configured to control the engine in a circuit mode in which a traveling performance of the vehicle is improved, on a basis of a request transmitted from a portable terminal, when the portable terminal operated by a user of the vehicle determines that a current position of the vehicle equipped with the engine is in a circuit, wherein, when a first maximum rotation speed of the engine is changed to a second maximum rotation speed higher than the first maximum rotation speed on a basis of the circuit mode, the engine control unit is configured to use a threshold associated with the first maximum rotation speed and used for determination of over-revving of the engine, regardless of a change from the first maximum rotation speed to the second maximum

rotation speed.

[0010] The engine control unit may be configured to count a number of times that the circuit mode is switched each time switching to the circuit mode occurs, and to record first information associated with second information in any of storage devices provided in the vehicle, the first information may include a total number of times that the circuit mode is switched, the first information may be used for failure diagnosis of engine components of the engine, and the second information may include dates when the circuit mode is switched.

[0011] The vehicle may further include a display control unit configured to control display of a display device provided in a vehicle cabin of the vehicle, wherein the display control unit may be configured to change a boundary rotation speed from a first boundary rotation speed to a second boundary rotation speed higher than the first boundary rotation speed, on a basis of the change from the first maximum rotation speed to the second maximum rotation speed, the boundary rotation speed may be a speed between a first meter display region and a second meter display region on a high rotation speed side adjacent to the first meter display region, and the first and second meter display regions may indicate a rotation speed of the engine.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0012] FIG. 1 illustrates an example of a vehicle control system;

[0013] FIG. 2A is an example of a correspondence table held by a mobile device, and FIG. 2B illustrates an example of a hardware configuration of an engine ECU;

[0014] FIG. 3 is a processing sequence diagram illustrating an example of an operation of the vehicle control system;

[0015] FIG. 4 is a flowchart illustrating an example of a determination process;

[0016] FIG. 5 illustrates an example of a switching information table; and

[0017] FIG. 6A illustrates an example of a tachometer in a normal traveling mode, and FIG. 6B illustrates an example of a tachometer in a circuit mode.

DETAILED DESCRIPTION

[0018] Hereinafter, embodiments of the present disclosure will be described with reference to the drawings.

[0019] As illustrated in FIG. 1, a vehicle control system ST includes a vehicle 10, a server 20, and a portable terminal 30. Although a smartphone is illustrated as an example of the portable terminal 30 in FIG. 1, a tablet terminal may be used instead of the smartphone. The vehicle 10, the server 20, and the portable terminal 30 cooperate with one another, whereby the vehicle control system ST provides a service limited to a circuit C1 to a driver 10D who is a user of the vehicle 10.

[0020] For example, when the vehicle 10 enters the circuit C1 and the driver 10D operates the portable terminal 30 in an office C2 of the circuit C1 to activate a circuit application, the portable terminal 30 acquires GPS information including a current position of the vehicle 10 via the server 20. The circuit application is application software installed in the portable terminal 30 and is associated with the vehicle 10. The circuit application is used when the vehicle 10 is controlled in a circuit mode for improving the traveling performance of the vehicle 10.

[0021] The vehicle 10 includes a data communication module (DCM) 11 as a wireless communication device to which an antenna ATN is connected, a DCM-electronic control unit (ECU) 12, and a GPS 13. The DCM-ECU 12 controls communication between the portable terminal 30 and the engine ECU 15 described later. The GPS 13 measures positions of the vehicle 10 and holds GPS information including the measured positions. The DCM-ECU 12 acquires the GPS information from the GPS 13, and transmits the GPS information to the server 20 by radio wave WL via the GPS and the antenna ATN. Therefore, when the server 20 requests the vehicle 10

to transmit the GPS information, the server **20** acquires the GPS information from the vehicle **10**.

[0022] The GPS information reaches the server **20** via a base station BS and a communication network NW. The communication network NW includes one or both of the Internet and a local area network (LAN). When the portable terminal **30** requests the server **20** to transmit the GPS information, the server **20** transmits the GPS information to the portable terminal **30** by the radio wave WL via the communication network NW and the base station BS. Thus, the portable terminal **30** acquires the GPS information of the vehicle **10**.

[0023] The server **20** also holds map information (hereinafter referred to as circuit information) including the position or area of the circuit C1. When the portable terminal **30** requests the server **20** to transmit the circuit information, the server **20** transmits the circuit information to the portable terminal **30** by the radio wave WL via the communication network NW and the portable base station BS. Thus, the portable terminal **30** acquires the circuit information.

[0024] When the portable terminal **30** acquires the GPS information and the circuit information, the portable terminal **30** determines whether a current position of the vehicle **10** is within the circuit C1 or not on the basis of the circuit information and the GPS information. When the vehicle **10** is not located in the circuit C1, the portable terminal **30** rejects the switching to the circuit mode and presents the rejection to the driver **10D** on the screen.

[0025] On the other hand, when the vehicle **10** is located in the circuit C1, the portable terminal **30** presents a notice about the switching to the circuit mode to the driver **10D**, and requests the driver **10D** to accept the switching. In this way, in the circuit mode, it is determined whether or not the position of the vehicle **10** is within the circuit C1. Therefore, the circuit mode is different from a sport mode (or a sport traveling mode) in which the traveling performance is improved only by switching of a switch provided in the vehicle cabin of the vehicle **10** without performing such determination.

[0026] When the portable terminal **30** receives the acceptance of the switching from the driver **10D**, the portable terminal **30** transmits circuit-mode request information (hereinafter, referred to as request ID (Identifier)) including the acceptance of the switching to the server **20**. The request ID is identification information for requesting the vehicle **10** to switch to the circuit mode. The request ID is prepared and defined for each version of the circuit application. Therefore, when the version of the circuit application is updated by version upgrade, different independent request ID is transmitted based on the update of the version.

[0027] When the request ID is transmitted from the portable terminal **30**, the server **20** generates switching information including the request ID and transmits the switching information to the vehicle **10**. The switching information is information for switching the traveling performance of the vehicle **10** to traveling performance specialized for traveling in the circuit C1, which will be described in detail later. For example, the server **20** transmits the switching information to the vehicle **10** by a short message service (SMS).

[0028] In the vehicle **10**, the DCM-ECU **12** receives the switching information from the server **20** via the DCM **11** and the antenna ATN. The vehicle **10** includes an engine **14**, an engine ECU **15**, a display device **16**, and a meter ECU **17**. The engine ECU **15** is an example of an engine control unit. The meter ECU **17** is an example of a display control unit. An engine speed sensor **14B** is provided in the vicinity of a crankshaft **14A** of the engine **14**. The engine speed sensor **14B** detects the rotation speed of the crankshaft **14A** as the engine rotation speed. The display device **16** is provided in the vehicle cabin of the vehicle **10**. The DCM-ECU **12**, the engine ECU **15**, and the meter ECU **17** achieves a control device of the vehicle **10**.

[0029] When the DCM-ECU **12** receives the switching information, the DCM-ECU **12** transmits the switching information to the engine ECU **15** by using a controller area network (CAN) signal. Thus, the engine ECU **15** receives the switching information. When receiving the switching information, the engine ECU **15** determines whether or not both of a first condition and a second condition, which are a part of all of at least three or more conditions for stably burning fuel

supplied to the engine **14** in the circuit mode, are unsatisfied.

[0030] For example, the at least three conditions include the first condition related to a temperature of a coolant that cools the engine **14**, the second condition related to an atmospheric pressure, and a third condition related to an injection amount of the fuel supplied to the engine **14**. The at least three conditions may include, for example, a fourth condition related to a rotation speed of the engine **14**, a fifth condition related to a temperature of an outside air, and a sixth condition related to communication between the DCM-ECU **12** and the engine ECU **15**. The engine ECU **15** determines whether or not, for example, both of the first condition and the second condition are unsatisfied among the first to sixth conditions. In this way, the engine ECU **15** determines whether both the first and second conditions are satisfied or not. Therefore, the engine ECU **15** reduces the number of adaptation steps as compared with the case where it is determined whether or not all the conditions from the first to sixth conditions are adapted.

[0031] Here, when either one of the first condition and the second condition is satisfied, the engine ECU **15** permits the switching to the circuit mode. Thus, the engine ECU **15** changes the control of the engine **14** based on the request ID included in the switching information. That is, the engine ECU **15** controls the engine **14** in the circuit mode. For example, the engine ECU **15** changes a first maximum rotation speed for preventing the occurrence of over-revving to a second maximum rotation speed higher than the first maximum rotation speed. Thus, the engine **14** is operated in, for example, the circuit mode in which the engine speed is increased.

[0032] The engine ECU **15** changes a torque upper limit map (hereinafter, simply referred to as torque map) that defines an upper limit of the torque of the engine **14**. Thus, the engine **14** is operated in the circuit mode in which high torque is output. The circuit mode improves the traveling performance of the vehicle **10** as compared to the normal traveling mode. In this way, the use of the circuit mode is accepted, and thus the service of conveying the enjoyment of the motor sports to the driver **10D** is provided.

[0033] On the other hand, when both the first condition and the second condition are unsatisfied, the engine ECU **15** rejects the switching to the circuit mode. In this case, the engine ECU **15** notifies the portable terminal **30** of the switching error via the DCM-ECU **12**, the server **20**, or the like. Thus, the driver **10D** confirms that the switching to the circuit mode is rejected.

[0034] When the engine ECU **15** changes the control of the engine **14**, the engine ECU **15** transmits meter display control information to the meter ECU **17**. The meter display control information is information for controlling a display of a tachometer provided in the display device **16**. For example, when the engine ECU **15** changes the torque map, the engine ECU **15** generates meter display control information and transmits the meter display control information to the meter ECU **17**. The meter ECU **17** controls the display of the tachometer based on the meter display control information. When the use of the circuit mode is selected, a boundary rotation speed between a first meter display region and a second meter display region on the high rotation speed side adjacent to the first meter display region is increased to the high rotation speed side. The first and second meter display regions indicate the rotation speed of the engine **14**.

[0035] Thus, the meter display is shifted from the normal traveling mode to the circuit mode. As a result, the driver **10D** recognizes that the circuit mode is selected. Thus, by selecting the use of the circuit mode, the vehicle control system ST provides a service that conveys the fun of motor sports to the driver **10D**.

[0036] Next, the portable terminal **30** will be described in detail with reference to FIG. 2A.

[0037] As illustrated in FIG. 2A, the portable terminal **30** includes a non-volatile memory (NVM) **31**. The NVM **31** stores a correspondence table of version IDs for identifying the versions of the circuit applications and request IDs. For example, the request ID “#1” is associated with the version ID “Ver1”. The request ID “#2” is associated with the version ID “Ver2”. Thus, when the version of the application is updated from, for example, “Ver1” to “Ver2”, the portable terminal **30** transmits the request ID “#2”.

[0038] Next, the engine ECU **15** will be described in detail with reference to FIG. **2B**. Hardware configurations of the DCM-ECU **12** and the meter ECU **17** are basically the same as the hardware configuration of the engine ECU **15**, and thus detailed description thereof will be omitted. The engine ECU **15** indirectly communicates with the portable terminal **30** via the DCM-ECU **12**, the server **20**, or the like.

[0039] The engine ECU **15** is a hardware circuit including a central processing unit (CPU) **15A**, a random access memory (RAM) **15B**, a read only memory (ROM) **15C**, an input and output interface (I/F) **15D**, and a NVM **15E**. The NVM **15E** includes, for example, a Nanotube RAM (NRAM). The CPU **15A** is an example of a processor and indirectly communicates with the portable terminal **30**. The CPU **15A**, the RAM **15B**, the ROM **15C**, the input and output I/F **15D**, and the NVM **15E** are connected to one another via an internal bus **15F**. Although omitted in FIG. **2B**, the input and output I/F **15D** is connected to the DCM-ECU **12**, the engine **14**, and the meter ECU **17**. At least the CPU **15A** and the RAM **15B** cooperate with each other to achieve a computer. [0040] In the RAM **15B** mentioned above, the software pre-stored in the ROM **15C** is stored by the CPU **15A**. The CPU **15A** executes the stored software, and thus the CPU **15A** executes a series of processes described later. The software may be in accordance with a processing sequence diagram described later.

[0041] The ROM **15C** stores a plurality of torque maps for the respective request IDs. Each of the torque maps defines the upper limit of the torque of the engine **14**. The request IDs are prepared and defined for respective versions of the circuit application. That is, the plurality of torque maps are stored in the ROM **15C** for respective versions of the circuit application.

[0042] On the other hand, the NVM **15E** stores a switching information table. The switching information table stores switching information including the number of times that the circuit mode is switched, dates when the circuit mode is switched, and the like. For example, in a repair shop of the vehicle **10**, a service person operates a device for diagnosing a failure or a malfunction of the engine **14** to acquire the switching information from the NVM **15E**. In this way, the switching information is used for diagnosing a decrease in durability of components of the engine **14** and a failure of the components. The switching information may improve the accuracy of identifying a decrease in the durability of the component and the accuracy of diagnosing a failure, as compared with a case where the presence or absence of switching remains as a history.

[0043] Next, the operation of the vehicle control system ST will be described with reference to FIG. **3**.

[0044] First, the portable terminal **30** waits until the circuit application is activated (step **S1**: NO). For example, the portable terminal **30** waits until the driver **10D** performs a predetermined operation to instruct activation of the circuit application on the icon of the circuit application displayed on the portable terminal **30**. When a predetermined operation is performed on the icon of the circuit application and the circuit application is activated (step **S1**: YES), the portable terminal **30** requests the server **20** and the DCM-ECU **12** for determination information (step **S2**). The determination information is information for determining whether or not the position of the vehicle **10** is within the circuit **C1**.

[0045] For example, the portable terminal **30** directly requests the server **20** to transmit the determination information. On the other hand, the portable terminal **30** indirectly requests the DCM-ECU **12** for the determination information. That is, the portable terminal **30** requests the DCM-ECU **12** for the determination information via the server **20**. When the determination information is requested from the portable terminal **30**, the server **20** transmits the circuit information as the determination information to the portable terminal **30** (step **S3**). When the determination information is requested from the portable terminal **30** via the server **20**, the DCM-ECU **12** transmits the GPS information as the determination information to the portable terminal **30** via the server **20** (step **S4**).

[0046] When the portable terminal **30** acquires the GPS information and the circuit information, the

portable terminal **30** determines whether the current position of the vehicle **10** is within the circuit **C1** (step **S5**). If the current position is not within the circuit **C1** (step **S5**: NO), the portable terminal **30** skips the subsequent processing. In this case, the portable terminal **30** rejects the switching to the circuit mode, and thus the control of the vehicle **10** in the circuit mode is stopped.

[0047] On the other hand, when the current position is within the circuit **C1** (step **S5**: YES), the portable terminal **30** determines whether or not there is an approval for switching to the circuit mode (step **S6**). For example, the portable terminal **30** presents a notice about the switching to the circuit mode to the driver **10D** on the screen of the portable terminal **30**, and requests the driver **10D** to accept the switching. The notice includes, for example, an explanation about a decrease in durability of a component of the engine **14**, an explanation about deterioration of the engine **14**, and the like. When the driver **10D** performs an operation to reject the switching to the circuit mode, the portable terminal **30** determines that the driver **10D** does not accept the switching to the circuit mode (step **S6**: NO). In this case, the portable terminal **30** rejects the switching to the circuit mode, and thus the control of the vehicle **10** in the circuit mode is stopped.

[0048] On the other hand, when the driver **10D** performs an operation of accepting the switching to the circuit mode (for example, pressing of a “YES” button as illustrated in FIG. **1**), the portable terminal **30** determines that the acceptance of the switching to the circuit mode is made (step **S6**: YES). In this case, the portable terminal **30** transmits the request ID to the server **20** (step **S7**). Specifically, the portable terminal **30** checks the version ID for identifying the version of the current circuit application installed in the portable terminal **30**, and specifies and transmits the request ID corresponding to the version ID. For example, if the version of the circuit application identified by the version ID “Ver2” is installed in the portable terminal **30**, the portable terminal **30** transmits the request ID “#2”.

[0049] When the server **20** receives the request ID, the server **20** transmits the switching information to the DCM-ECU **12** (step **S8**). Specifically, when the server **20** receives the request ID, the server **20** generates the switching information including the received request ID and transmits the switching information to the DCM-ECU **12**. When the DCM-ECU **12** receives the switching information, the DCM ECU **12** transfers the switching information to the engine ECU **15** (step **S9**).

[0050] When the engine ECU **15** receives the switching information, the engine ECU **15** performs a determination process (step **S10**). The determination process is a process of determining whether both of the first condition and the second condition among the at least three conditions are unsatisfied. The determination process will be described in detail later. When one of the first condition and the second condition is satisfied, the engine ECU **15** changes the torque map and immediately uses the changed torque map (step **S11**). Specifically, when one of the first condition and the second condition is satisfied, the engine ECU **15** extracts the request ID from the switching information, and specifies and selects the torque map corresponding to the extracted request ID. For example, when the request ID “#2” is extracted, the engine ECU **15** specifies and selects one of the plurality of torque maps associated with the request ID “#2”.

[0051] If the torque map associated with the request ID “#1” is used before the switching information is received, the engine ECU **15** changes the torque map to the torque map associated with the request ID “#2”. When the engine ECU **15** changes the torque map, the engine ECU **15** uses the changed torque map for controlling the vehicle **10**.

[0052] The details of the determination process will be described with reference to FIG. **4**.

[0053] As described above, when the engine ECU **15** receives the switching information, the engine ECU **15** determines whether or not the first condition is satisfied (step **S21**). For example, the engine ECU **15** determines whether the temperature of the coolant that cools the engine **14** is equal to or higher than a temperature threshold as the first condition. The temperature threshold is set to a temperature at which the fuel supplied to the engine **14** is stably combusted, based on design, experiments, and the like.

[0054] When the first condition is not satisfied because the coolant temperature is lower than the temperature threshold (step S21: NO), the engine ECU 15 then determines whether or not a second condition is satisfied (step S22). For example, the engine ECU 15 determines whether or not an atmospheric pressure is equal to or higher than a pressure threshold as the second condition. The pressure threshold is set to a pressure at which the fuel supplied to the engine 14 is stably combusted, based on design, experiments, and the like.

[0055] If the second condition is not satisfied because the atmospheric pressure is lower than the pressure threshold (step S22: NO), the engine ECU 15 rejects the switching to the circuit mode (step S23). That is, when both the first condition and the second condition are unsatisfied, the engine ECU 15 might not be able to stably burn the fuel supplied to the engine 14. In such a case, the engine ECU 15 rejects the switching to the circuit mode because the control of the engine 14 in the circuit mode might not be suitable.

[0056] If the switching to the circuit mode is rejected, the engine ECU 15 notifies a switching error (step S24), and the determination process ends. Specifically, the engine ECU 15 notifies the portable terminal 30 of the switching error. The switching error reaches the portable terminal 30 via the DCM-ECU 12, the server 20, and the like. Thus, the driver 10D confirms that the switching to the circuit mode is rejected. When the switching to the circuit mode is rejected, the engine ECU 15 skips the process of step S11 described above.

[0057] On the other hand, when either the first condition or the second condition is satisfied (step S21: YES, step S22: YES), the engine ECU 15 permits the switching to the circuit mode (step S25). That is, when the first condition is satisfied because the coolant temperature is equal to or higher than the temperature threshold, the engine ECU 15 permits the switching to the circuit mode. When the second condition is satisfied because the atmospheric pressure is equal to or higher than the pressure threshold, the engine ECU 15 permits the switching to the circuit-mode.

[0058] When the switching to the circuit mode is permitted, the engine ECU 15 records the switching information (step S26). Specifically, the engine ECU 15 counts the number of times that the circuit mode is switched each time switching to the circuit mode occurs. When counting the number of times of switching, the engine ECU 15 records first information including the total number of times of switching and second information including a switching date in association with each other as switching information. The CPU 15A stores the switching information in the NVM 15E, so that the engine ECU 15 records the switching information.

[0059] As a result, as illustrated in FIG. 5, the engine ECU 15 holds the total number of times of switching and the dates of switching as a history each time switching to the circuit mode occurs. The engine ECU 15 may record the switching information in any of the plurality of storage devices provided in the vehicle 10. For example, the CPU 15A of the engine ECU 15 may record the switching information in an NVM included in the DCM-ECU 12 or the meter ECU 17.

[0060] When the switching information is recorded, the engine ECU 15 increases the maximum rotation speed of the engine 14 (step S27). That is, the engine ECU 15 changes the first maximum rotation speed to a second maximum rotation speed higher than the first maximum rotation speed. When the maximum engine speed is increased, the engine ECU 15 stops an increase in an over-revving determination threshold used for a determination of the over-revving (step S28). That is, the engine ECU 15 maintains and uses the original over-revving determination threshold set at the time of design. An original over-revving determination threshold is set to, for example, the same value as the first maximum rotation speed. On the other hand, a value close to the first maximum rotation speed may be set as the over-revving determination threshold as long as the over-revving determination threshold is within a range in which the over-revving is determined. In this way, the original over-revving determination threshold is associated with the first maximum rotation speed.

[0061] Even if the engine ECU 15 increases the over-revving determination threshold at the same timing of increasing the maximum rotation speed of the engine 14, the over-revving determination threshold is maintained at the original value at the time of design and used by the process in step

S28. Thus, the occurrence of over-revving is uniquely determined regardless of the presence or absence of switching to the circuit mode. When the engine ECU **15** stops increasing the over-revving determination threshold, the engine ECU **15** executes the process of step **S11** described above, and the determination process ends.

[0062] In this way, when the switching to the circuit mode is permitted, the engine ECU **15** changes the first maximum rotation speed of the engine **14** to the second maximum rotation speed higher than the first maximum rotation speed. In this case, the engine ECU **15** maintains the over-revving determination threshold used for the over-revving determination of the engine **14** and associated with the first maximum rotation speed, regardless of a change from the first maximum rotation speed to the second maximum rotation speed. Thus, the engine ECU **15** uniquely determines the occurrence of the over-revving regardless of the presence or absence of the switching to the circuit mode.

[0063] The engine ECU **15** counts the number of times of the switching each time switching to the circuit mode occurs. When the engine ECU **15** counts the number of times of switching, the engine ECU **15** associates the total number of times of switching used for failure diagnosis of the components of the engine with the switching date, and records the total number of times of switching as switching information in the engine ECU **15** itself. By acquiring and analyzing the switching information, a decrease in the durability of the components of the engine **14** is found early. In addition, by acquiring and analyzing the switching information, a failure of a component is found early.

[0064] The meter ECU **17** controls the display of the tachometer displayed on the display device **16** on the basis of a change from the first maximum rotation speed to the second rotation speed. For example, as illustrated in FIG. **6A**, in the normal traveling mode, a boundary rotation speed between a non-red zone **NRD** and a red zone **RD** of a tachometer **18** may be set to a first maximum rotation speed **Ne1**.

[0065] In this case, when the switching to the circuit mode is permitted, the boundary rotation speed between the non-red zone **NRD** and the red zone **RD** of the tachometer **18** is set to the second maximum rotation speed **Ne2** as illustrated in FIG. **6B**. That is, the meter ECU **17** changes the boundary rotation speed between the non-red zone **NRD** and the red zone **RD** to the high rotation speed side. Thus, the driver **10D** instantly confirms that the circuit mode is switched. In other words, the driver **10D** does not misunderstand that the circuit mode is not switched.

[0066] Although some embodiments of the present disclosure have been described in detail, [0067] the present disclosure is not limited to the specific embodiments but may be varied or changed within the scope of the present disclosure as claimed.

Claims

1. A vehicle with an engine, the vehicle comprising an engine control unit configured to control the engine in a circuit mode in which a traveling performance of the vehicle is improved, on a basis of a request transmitted from a portable terminal, when the portable terminal operated by a user of the vehicle determines that a current position of the vehicle equipped with the engine is in a circuit, wherein, when a first maximum rotation speed of the engine is changed to a second maximum rotation speed higher than the first maximum rotation speed on a basis of the circuit mode, the engine control unit is configured to use a threshold associated with the first maximum rotation speed and used for determination of over-revving of the engine, regardless of a change from the first maximum rotation speed to the second maximum rotation speed.

2. The vehicle with the engine according to claim 1, wherein the engine control unit is configured to count a number of times that the circuit mode is switched each time switching to the circuit mode occurs, and to record first information associated with second information in any of storage devices provided in the vehicle, the first information includes a total number of times that the

circuit mode is switched, the first information is used for failure diagnosis of engine components of the engine, and the second information includes dates when the circuit mode is switched.

3. The vehicle with the engine according to claim 1, further comprising a display control unit configured to control display of a display device provided in a vehicle cabin of the vehicle, wherein the display control unit is configured to change a boundary rotation speed from a first boundary rotation speed to a second boundary rotation speed higher than the first boundary rotation speed, on a basis of the change from the first maximum rotation speed to the second maximum rotation speed, the boundary rotation speed is a speed between a first meter display region and a second meter display region on a high rotation speed side adjacent to the first meter display region, and the first and second meter display regions indicate a rotation speed of the engine.

4. The vehicle with the engine according to claim 2, further comprising a display control unit configured to control display of a display device provided in a vehicle cabin of the vehicle, wherein the display control unit is configured to change a boundary rotation speed from a first boundary rotation speed to a second boundary rotation speed higher than the first boundary rotation speed, on a basis of the change from the first maximum rotation speed to the second maximum rotation speed, the boundary rotation speed is a speed between a first meter display region and a second meter display region on a high rotation speed side adjacent to the first meter display region, and the first and second meter display regions indicate a rotation speed of the engine.
