

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250273238

Kind Code

A1

Publication Date

August 28, 2025

Inventor(s)

KURIHARA; Kosuke et al.

MAGNETIC RECORDING DEVICE AND A METHOD FOR MANUFACTURING THE SAME

Abstract

According to one embodiment, a magnetic recording device includes a magnetic recording medium, a magnetic head configured to record information on the magnetic recording medium, and a controller configured to control the magnetic recording medium and the magnetic head. The magnetic head includes a coil, a first magnetic pole configured to generate a magnetic field according to a recording current supplied to the coil, and a light emitting section configured to irradiate the magnetic recording medium with a light to locally increase a temperature of the magnetic recording medium. The controller is configured to perform a first operation and a second operation. In the first operation, the controller is configured to record a first servo position information in a first region of the magnetic recording medium. In the second operation, the controller is configured to perform a repair operation if a first condition is not satisfied.

Inventors: KURIHARA; Kosuke (Yokohama Kanagawa, JP), ISOWAKI; Yousuke (Yokohama Kanagawa, JP)

Applicant: KABUSHIKI KAISHA TOSHIBA (Tokyo, JP); TOSHIBA ELECTRONIC DEVICES & STORAGE CORPORATION (Tokyo, JP)

Family ID: 1000008341068

Appl. No.: 18/983016

Filed: December 16, 2024

Foreign Application Priority Data

JP	2024-026755	Feb. 26, 2024
----	-------------	---------------

Publication Classification

Int. Cl.: G11B5/596 (20060101); G11B5/00 (20060101); G11B5/024 (20060101)

U.S. Cl.:

CPC **G11B5/59672** (20130101); **G11B5/024** (20130101); **G11B5/59638** (20130101);
G11B2005/0021 (20130101); G11B5/59661 (20130101)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application is based upon and claims the benefit of priority from Japanese Patent Application No. 2024-026755, filed on Feb. 26, 2024; the entire contents of which are incorporated herein by reference.

FIELD

[0002] Embodiments described herein relate generally to a magnetic recording device and a method for manufacturing the same.

BACKGROUND

[0003] In a magnetic recording device, information is recorded on a magnetic recording medium such as an HDD (Hard Disk Drive) using a magnetic head. In magnetic recording devices, it is desired to improve productivity.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0004] FIG. 1 is a schematic view illustrating a magnetic recording device according to a first embodiment;

[0005] FIG. 2 is a flowchart illustrating an operation of the magnetic recording device according to the first embodiment;

[0006] FIGS. 3A to 3C are schematic plan views illustrating the magnetic recording device according to the first embodiment;

[0007] FIG. 4 is a schematic cross-sectional view illustrating a part of the magnetic recording device according to the first embodiment;

[0008] FIG. 5 is a schematic diagram illustrating a magnetic recording device according to the first embodiment; and

[0009] FIG. 6 is a schematic diagram illustrating a magnetic recording device according to the first embodiment.

DETAILED DESCRIPTION

[0010] According to one embodiment, a magnetic recording device includes a magnetic recording medium, a magnetic head, and a controller. The magnetic head is configured to record information on the magnetic recording medium. The controller is configured to control the magnetic recording medium and the magnetic head. The magnetic head includes a coil, a first magnetic pole, and a light emitting section. The first magnetic pole is configured to generate a magnetic field according to a recording current supplied to the coil. The light emitting section is configured to irradiate the magnetic recording medium with a light to locally increase a temperature of the magnetic recording medium. The controller is configured to perform a first operation and a second operation. In the first operation, the controller is configured to record a first servo position information in a first region of the magnetic recording medium. In the second operation, the controller is configured to perform a repair operation if a first condition is not satisfied. The first condition includes a condition that a recording condition of the first servo position information is within a first range being determined. In the repair operation, the controller is configured to perform an erasing

operation of irradiating the first region with the light from the light emitting section to perform a re-recording operation of re-recording the first servo position information in the first region after the erasing operation.

[0011] Various embodiments are described below with reference to the accompanying drawings.

[0012] The drawings are schematic and conceptual; and the relationships between the thickness and width of portions, the proportions of sizes among portions, etc., are not necessarily the same as the actual values. The dimensions and proportions may be illustrated differently among drawings, even for identical portions.

[0013] In the specification and drawings, components similar to those described previously or illustrated in an antecedent drawing are marked with like reference numerals, and a detailed description is omitted as appropriate.

First Embodiment

[0014] FIG. 1 is a schematic view illustrating a magnetic recording device according to a first embodiment.

[0015] As shown in FIG. 1, a magnetic recording device **210** according to the embodiment includes a magnetic recording medium **80**, a magnetic head **110**, and a controller **75**. The magnetic head **110** is configured to record information on the magnetic recording medium **80**. The controller **75** is configured to control the magnetic recording medium **80** and the magnetic head **110**.

[0016] The magnetic head **110** includes a coil **30c** and a first magnetic pole **31**. The first magnetic pole **31** generates a magnetic field (recording magnetic field) according to a recording current I_w supplied to the coil **30c**. The generated magnetic field is applied to the magnetic recording medium **80**. Thereby, the direction of magnetization **83** of magnetic recording medium **80** is controlled. The state of magnetization **83** corresponds to the information to be recorded. In this example, the magnetic head **110** further includes a second magnetic pole **32**. The first magnetic pole **31** is, for example, a main magnetic pole. The second magnetic pole **32** is, for example, a trailing shield.

[0017] The magnetic head **110** further includes a light emitting section **77**. The light emitting section **77** is configured to irradiate the magnetic recording medium **80** with light **77L** to locally increase the temperature of the magnetic recording medium **80**.

[0018] For example, the light emitting section **77** includes a light source **77S** and a light guide **77G**. The light **77L** emitted from the light source **77S** is guided by the light guide **77G**. The light **77L** emitted from the light guide **77G** is emitted to the magnetic recording medium **80** via, for example, an optical element. The light source **77S** is, for example, a laser.

[0019] Hereinafter, an example of the operation of the controller **75** will be described.

[0020] FIG. 2 is a flowchart illustrating an operation of the magnetic recording device according to the first embodiment.

[0021] FIGS. 3A to 3C are schematic plan views illustrating the magnetic recording device according to the first embodiment.

[0022] As shown in FIG. 2, the controller **75** is configured to perform a first operation OP1 and a second operation OP2.

[0023] FIG. 3A corresponds to the first operation OP1. In the first operation OP1, the controller **75** records a first servo position information **81s** in a first region **81r** of the magnetic recording medium **80** (step S10 in FIG. 2). For example, the recording current I_w corresponding to the first servo position information **81s** is supplied to the coil **30c**. A recording magnetic field based on the recording current I_w is applied to the magnetic recording medium **80**, and the first servo position information **81s** is recorded in the first region **81r** being target.

[0024] In the second operation OP2, the controller **75** performs a repair operation RO if the following first condition is not satisfied (step S20 in FIG. 2). The first condition includes that the recording condition of the first servo position information **81s** is within a first range being determined. If the first condition is satisfied, the recording condition of the first servo position information **81s** is within the first range being appropriate. On the other hand, if the first condition

is not satisfied, the recording conditions for the first servo position information **81s** are inappropriate.

[0025] The controller **75** determines whether such a first condition is satisfied (step **S21**). In step **S21**, if the first condition is not satisfied, the repair operation **RO** is performed. In the repair operation **RO**, the controller **75** performs an erasing operation **ER** and a re-recording operation **RW**.

[0026] FIG. **3B** illustrates the erasing operation **ER**. In the erasing operation **ER**, the controller **75** irradiates the first region **81r** with the light **77L** from the light emitting section **77** (step **S22** in FIG. **2**). For example, the temperature of the first region **81r** irradiated with the light **77L** increases, and the magnetization state of the first region **81r** returns to the initial state.

[0027] FIG. **3C** illustrates the re-recording operation **RW**. The re-recording operation **RW** is performed after the erasing operation **ER**. In the re-recording operation **RW**, the controller **75** re-records the first servo position information **81s** in the first region **81r** after the erasing operation **ER** (step **S23** in FIG. **2**).

[0028] Thereby, the first servo position information **81s** can be correctly recorded in the event of an error in which the first condition is not satisfied. Thereby, the magnetic recording medium **80** being defective can be repaired. According to the embodiment, it is possible to provide a magnetic recording device that can improve productivity.

[0029] As shown in FIG. **2**, in step **S21**, the controller **75** may determine that the first condition is satisfied. In this case, it is estimated that the first servo position information **81s** is appropriately recorded in the first operation **OP1**. In this case, the repair operation **RO** is not performed. In this manner, the controller **75** does not perform the repair operation **RO** in the second operation **OP2** if the first condition is satisfied.

[0030] In the erasing operation **ER** described above, the recording current **I_w** is not supplied to the coil **30c**. Alternatively, the current supplied to the coil **30c** in the erasing operation **ER** is smaller than the current supplied to the coil in the first operation **OP1**. As a result, the first servo position information **81s** being erroneously recorded on the magnetic recording medium **80** is stably and effectively erased.

[0031] For example, in the first operation **OP1**, the controller **75** may record the first servo position information **81s** in the first region **81r** while irradiating the magnetic recording medium **80** with the light **77L**. For example, the first servo position information **81s** may be recorded by thermally assisted recording.

[0032] As described above, the first condition includes that the recording condition of the first servo position information **81s** is within the first range being determined. When the thermally assisted recording is performed, the recording condition of the first servo position information **81s** may include power supplied to the light source **77S** in the first operation **OP1**. For example, the value of the current supplied to the light source **77S** of laser is recorded. When the value of the recorded current is within the determined range (first range), the first condition is satisfied. It is estimated that the first servo position information **81s** was normally recorded.

[0033] The recording conditions for the first servo position information **81s** may further include the recording current **I_w** supplied to the coil **30c** in the first operation **OP1**. For example, the first condition is satisfied when the recording current **I_w** is normal. It is estimated that the first servo position information **81s** was recorded normally.

[0034] The recording conditions of the first servo position information **81s** may further include the temperature of the magnetic head **110** in the first operation **OP1**. The temperature of the magnetic head **110** is detected. The first condition is satisfied when the detected temperature is within normal range. It is estimated that the first servo position information **81s** was recorded normally.

[0035] The above first condition may further include that the result of detecting the first servo position information **81s** recorded in the first region **81r** by the first operation **OP1** is within a second range being determined. For example, after the first operation **OP1**, the first servo position information **81s** being recorded is detected (reproduced). The first condition is satisfied when the

detected condition is within the second range being determined. It is detected that the first servo position information **81s** was recorded normally.

[0036] In one example, the intensity of the light **77L** in the erasing operation ER (intensity during erasing) is higher than the intensity (intensity during recording) of the light **77L** in the first operation OP1. Stable erasing can be performed. For example, the intensity in the erasing may be not less than 1.1 times and not more than 3 times the intensity in the recording. The intensity in the erasing may be the same as the intensity in the recording.

[0037] For example, the power (for example, current) supplied to the light source **77S** in the erasing operation ER may be greater than the power (for example, current) supplied to the light source **77S** in the first operation OP1.

[0038] As shown in FIG. 3A, the first servo position information **81s** may be recorded in each of the plurality of first regions **81r**. For example, the first operation OP1 may be repeatedly performed until a desired number of pieces of first servo position information **81s** are recorded.

[0039] For example, as shown in FIG. 2, after step S23 and when it is determined in step S21 that the first condition is satisfied, the controller 75 performs step S30. In step S30, the controller 75 determines whether the first servo position information **81s** has been recorded a determined number of times. If the number of recordings has not reached the determined number, for example, the process returns to step S10. For example, when the number of recordings reaches a determined number, the recording ends.

[0040] In the embodiment, the controller 75 may be configured to repeatedly perform the first operation OP1 and the second operation OP2.

[0041] The controller 75 may be configured to continuously perform the plurality of second operations OP2 after continuously performing the plurality of first operations OP1.

[0042] As shown in FIG. 3A, the first region **81r** may have a spiral shape. In the embodiment, the first servo position information **81s** may be included in an intermediate pattern for self-servo writing.

[0043] FIG. 4 is a schematic cross-sectional view illustrating a part of the magnetic recording device according to the first embodiment.

[0044] As shown in FIG. 4, a plurality of magnetic recording media **80** and a plurality of magnetic heads **110** may be provided. The controller 75 may be configured to perform the first operation OP1 and the second operation OP2 for the plurality of magnetic recording media **80** and the plurality of magnetic heads **110**.

[0045] FIGS. 5 and 6 are schematic diagrams illustrating magnetic recording devices according to the first embodiment.

[0046] As shown in FIG. 5, a magnetic head **111** included in the magnetic recording device **210** according to the embodiment further includes the second magnetic pole **32** and a magnetic element **20**. The configuration of the magnetic head **111** except for this may be the same as the configuration of the magnetic head **110**.

[0047] The magnetic element **20** is provided between the first magnetic pole **31** and the second magnetic pole **32**. The controller 75 may be configured to supply an element current i_c to the magnetic element **20** when the magnetic head **111** records information on the magnetic recording medium **80**. As shown in FIG. 5, the magnetic element **20** may include a first magnetic layer **21**. The magnetization of the first magnetic layer **21** is controlled by the element current i_c . For example, the direction of the recording magnetic field emitted from the first magnetic pole **31** is controlled by the first magnetic layer **21**. The recording magnetic field is efficiently applied to the magnetic recording medium **80**. High-density recording becomes possible.

[0048] As shown in FIG. 6, in a magnetic head **112** included in the magnetic recording device **210** according to the embodiment, the magnetic element **20** further includes a second magnetic layer **22**. The configuration of the magnetic head **112** except for this may be the same as the configuration of the magnetic head **111**.

[0049] The controller **75** may be configured to supply the element current i_c to the magnetic element **20** when the magnetic head **112** records information on the magnetic recording medium **80**. The magnetization of the magnetic layer included in the magnetic element **20** oscillates by the element current i_c . An alternating magnetic field is generated from the magnetic element **20**, and the alternating magnetic field is applied to the magnetic recording medium **80**. High-density recording becomes possible.

Second Embodiment

[0050] The second embodiment relates to a method of manufacturing the magnetic recording device **210**. As already explained, the magnetic recording device **210** includes any magnetic head (hereinafter referred to as the magnetic head **110**) according to the embodiment. The magnetic recording device **210** includes the magnetic recording medium **80**, the magnetic head **110** configured to record information on the magnetic recording medium **80**, and the controller **75** configured to control the magnetic recording medium **80** and the magnetic head **110**. The magnetic head **110** includes the coil **30c**, the first magnetic pole **31**, and the light emitting section **77**. The first magnetic pole **31** generates the magnetic field according to the recording current I_w supplied to the coil **30c**. The light emitting section **77** is configured to irradiate the magnetic recording medium **80** with the light **77L** to locally increase the temperature of the magnetic recording medium **80**.

[0051] In the second embodiment, the controller **75** is configured to perform the first operation **OP1** and the second operation **OP2**. In the first operation **OP1**, the controller **75** records the first servo position information **81s** in the first region **81r** of the magnetic recording medium **80**. In the second operation **OP2**, the controller **75** performs the repair operation **RO** when the first condition is not satisfied. The first condition includes that the recording condition of the first servo position information **81s** is within the first range being determined. In the repair operation **RO**, the controller **75** performs the erasing operation **ER** of irradiating the first region **81r** with the light **77L** from the light emitting section **77**, and performs the re-recording operation **RW** of re-recording the first servo position information **81s** in the first region **81r** after the erasing operation **ER**.

[0052] According to the method for manufacturing the magnetic recording device **210** according to the second embodiment, it is possible to provide a method for manufacturing a magnetic recording device that can improve productivity.

[0053] In the second embodiment, the first condition further may include that the result of detecting the first servo position information **81s** recorded in the first region **81r** by the first operation **OP1** is within the second range being determined.

[0054] In the second embodiment, in the first operation **OP1**, the controller **75** may record the first servo position information **81s** in the first region **81r** while irradiating the magnetic recording medium **80** with the light **77L**. The erasing intensity of the light **77L** in the erasing operation **ER** may be higher than the recording intensity of the light **77L** in the first operation **OP1**.

[0055] As already explained, the light emitting section **77** may include the light source **77S**. The recording conditions for the first servo position information **81s** may include the power supplied to the light source **77S** in the first operation **OP1**.

[0056] The embodiments may include the following Technical proposals:

(Technical proposal 1)

[0057] A magnetic recording device, comprising: [0058] a magnetic recording medium; [0059] a magnetic head configured to record information on the magnetic recording medium; and [0060] a controller configured to control the magnetic recording medium and the magnetic head, [0061] the magnetic head including: [0062] a coil; [0063] a first magnetic pole configured to generate a magnetic field according to a recording current supplied to the coil; and [0064] a light emitting section configured to irradiate the magnetic recording medium with a light to locally increase a temperature of the magnetic recording medium, [0065] the controller being configured to perform a first operation and a second operation, [0066] in the first operation, the controller being configured

to record a first servo position information in a first region of the magnetic recording medium, [0067] in the second operation, the controller being configured to perform a repair operation if a first condition is not satisfied, [0068] the first condition including a condition that a recording condition of the first servo position information is within a first range being determined, and [0069] in the repair operation, the controller being configured to perform an erasing operation of irradiating the first region with the light from the light emitting section to perform a re-recording operation of re-recording the first servo position information in the first region after the erasing operation.

(Technical Proposal 2)

[0070] The magnetic recording device according to Technical proposal 1, wherein [0071] the controller does not perform the repair operation when the first condition is satisfied in the second operation.

(Technical Proposal 3)

[0072] The magnetic recording device according to Technical proposal 1 or 2, wherein [0073] the first condition further includes that a result of detecting the first servo position information recorded in the first region by the first operation is within a second range being determined.

(Technical Proposal 4)

[0074] The magnetic recording device according to any one of Technical proposals 1-3, wherein [0075] in the first operation, the controller records the first servo position information in the first region while irradiating the magnetic recording medium with the light, and [0076] an erasing intensity of the light in the erasing operation is higher than a recording intensity of the light in the first operation.

(Technical proposal 5)

[0077] The magnetic recording device according to Technical proposal 4, wherein [0078] the erasing intensity is not less than 1.1 times and not more than 3 times the recording intensity.

(Technical Proposal 6) The magnetic recording device according to Technical proposal 4 or 5, wherein [0079] the light emitting section includes a light source, and [0080] the recording condition for the first servo position information includes a power supplied to the light source in the first operation.

(Technical Proposal 7)

[0081] The magnetic recording device according to Technical proposal 6, wherein [0082] the recording condition for the first servo position information further includes the recording current supplied to the coil in the first operation.

(Technical Proposal 8)

[0083] The magnetic recording device according to Technical proposal 6 or 7, wherein [0084] the recording conditions for the first servo position information further includes a temperature of the magnetic head in the first operation.

(Technical Proposal 9)

[0085] The magnetic recording device according to any one of Technical proposals 1-8, wherein [0086] in the erasing operation, the recording current is not supplied to the coil.

(Technical Proposal 10)

[0087] The magnetic recording device according to any one of Technical proposals 1-8, wherein [0088] a current supplied to the coil in the erasing operation is smaller than a current supplied to the coil in the first operation.

(Technical Proposal 11)

[0089] The magnetic recording device according to any one of Technical proposals 1-10, wherein [0090] the controller is configured to repeatedly perform the first operation and the second operation.

(Technical Proposal 12)

[0091] The magnetic recording device according to any one of Technical proposals 1-10, wherein

[0092] the controller is configured to continuously perform a plurality of the second operations after continuously performing a plurality of the first operations.

(Technical Proposal 13)

[0093] The magnetic recording device according to any one of Technical proposals 1-12, wherein [0094] the first region has a spiral shape.

(Technical Proposal 14)

[0095] The magnetic recording device according to any one of Technical proposals 1-13, wherein [0096] the first servo position information is included in an intermediate pattern for self-servo writing.

(Technical Proposal 15)

[0097] The magnetic recording device according to any one of Technical proposals 1-14, wherein [0098] a plurality of the magnetic recording media and a plurality of the magnetic heads are provided, and [0099] the controller is configured to perform the first operation and the second operation for the plurality of magnetic recording media and the plurality of magnetic heads.

(Technical Proposal 16)

[0100] The magnetic recording device according to Technical proposal 1, wherein [0101] the magnetic head includes a second magnetic pole and a magnetic element provided between the first magnetic pole and the second magnetic pole, and [0102] the controller is configured to supply an element current to the magnetic element when the magnetic head records the information on the magnetic recording medium.

(Technical Proposal 17)

[0103] A method for manufacturing a magnetic recording device, the method comprising: [0104] manufacturing a magnetic recording device, [0105] the magnetic recording device including: [0106] a magnetic recording medium, [0107] a magnetic head configured to record information on the magnetic recording medium, and [0108] a controller configured to control the magnetic recording medium and the magnetic head, [0109] the magnetic head including: [0110] a coil, [0111] a first magnetic pole configured to generate a magnetic field according to a recording current supplied to the coil, and [0112] a light emitting section configured to irradiate the magnetic recording medium with a light to locally increase a temperature of the magnetic recording medium, [0113] the controller being configured to perform a first operation and a second operation, [0114] in the first operation, the controller being configured to record a first servo position information in a first region of the magnetic recording medium, [0115] in the second operation, the controller being configured to perform a repair operation if a first condition is not satisfied, [0116] the first condition including that a recording condition of the first servo position information is within a first range being determined, and [0117] in the repair operation, the controller being configured to perform an erasing operation of irradiating the first region with the light from the light emitting section to perform a re-recording operation of re-recording the first servo position information in the first region after the erasing operation.

(Technical Proposal 18)

[0118] The method for manufacturing the magnetic recording device according to Technical proposal 17, wherein [0119] the first condition further includes that a result of detecting the first servo position information recorded in the first region by the first operation is within a second range being determined.

(Technical Proposal 19)

[0120] The method for manufacturing the magnetic recording device according to Technical proposal 17 or 18, wherein [0121] in the first operation, the controller is configured to record the first servo position information in the first region while irradiating the magnetic recording medium with the light, and [0122] an erasing intensity of the light in the erasing operation is higher than a recording intensity of the light in the first operation.

(Technical Proposal 20)

[0123] The method for manufacturing the magnetic recording device according to Technical proposal 19, wherein [0124] the light emitting section includes a light source, and [0125] the recording conditions for the first servo position information include a power supplied to the light source in the first operation.

[0126] According to the embodiment, it is possible to provide a magnetic recording device and a method for manufacturing the same that can improve productivity.

[0127] In the specification of the application, “perpendicular” and “parallel” refer to not only strictly perpendicular and strictly parallel but also include, for example, the fluctuation due to manufacturing processes, etc. It is sufficient to be substantially perpendicular and substantially parallel.

[0128] Hereinabove, exemplary embodiments of the invention are described with reference to specific examples. However, the embodiments of the invention are not limited to these specific examples. For example, one skilled in the art may similarly practice the invention by appropriately selecting specific configurations of components included in magnetic recording devices such as magnetic recording medium, magnetic heads, controllers, etc., from known art. Such practice is included in the scope of the invention to the extent that similar effects thereto are obtained.

[0129] Further, any two or more components of the specific examples may be combined within the extent of technical feasibility and are included in the scope of the invention to the extent that the purport of the invention is included.

[0130] Moreover, all magnetic recording devices and all method for manufacturing the same practicable by an appropriate design modification by one skilled in the art based on the magnetic recording devices and the methods for manufacturing the same described above as embodiments of the invention also are within the scope of the invention to the extent that the purport of the invention is included.

[0131] Various other variations and modifications can be conceived by those skilled in the art within the spirit of the invention, and it is understood that such variations and modifications are also encompassed within the scope of the invention.

[0132] While certain embodiments have been described, these embodiments have been presented by way of example only, and are not intended to limit the scope of the inventions. Indeed, the novel embodiments described herein may be embodied in a variety of other forms; furthermore, various omissions, substitutions and changes in the form of the embodiments described herein may be made without departing from the spirit of the inventions. The accompanying claims and their equivalents are intended to cover such forms or modifications as would fall within the scope and spirit of the invention.

Claims

1. A magnetic recording device, comprising: a magnetic recording medium; a magnetic head configured to record information on the magnetic recording medium; and a controller configured to control the magnetic recording medium and the magnetic head, the magnetic head including: a coil; a first magnetic pole configured to generate a magnetic field according to a recording current supplied to the coil; and a light emitting section configured to irradiate the magnetic recording medium with a light to locally increase a temperature of the magnetic recording medium, the controller being configured to perform a first operation and a second operation, in the first operation, the controller being configured to record a first servo position information in a first region of the magnetic recording medium, in the second operation, the controller being configured to perform a repair operation if a first condition is not satisfied, the first condition including a condition that a recording condition of the first servo position information is within a first range being determined, and in the repair operation, the controller being configured to perform an erasing operation of irradiating the first region with the light from the light emitting section to perform a

re-recording operation of re-recording the first servo position information in the first region after the erasing operation.

2. The device according to claim 1, wherein the controller does not perform the repair operation when the first condition is satisfied in the second operation.

3. The device according to claim 1, wherein the first condition further includes that a result of detecting the first servo position information recorded in the first region by the first operation is within a second range being determined.

4. The device according to claim 1, wherein in the first operation, the controller records the first servo position information in the first region while irradiating the magnetic recording medium with the light, and an erasing intensity of the light in the erasing operation is higher than a recording intensity of the light in the first operation.

5. The device according to claim 4, wherein the erasing intensity is not less than 1.1 times and not more than 3 times the recording intensity.

6. The device according to claim 4, wherein the light emitting section includes a light source, and the recording condition for the first servo position information includes a power supplied to the light source in the first operation.

7. The device according to claim 6, wherein the recording condition for the first servo position information further includes the recording current supplied to the coil in the first operation.

8. The device according to claim 6, wherein the recording conditions for the first servo position information further includes a temperature of the magnetic head in the first operation.

9. The device according to claim 1, wherein in the erasing operation, the recording current is not supplied to the coil.

10. The device according to claim 1, wherein a current supplied to the coil in the erasing operation is smaller than a current supplied to the coil in the first operation.

11. The device according to claim 1, wherein the controller is configured to repeatedly perform the first operation and the second operation.

12. The device according to claim 1, wherein the controller is configured to continuously perform a plurality of the second operations after continuously performing a plurality of the first operations.

13. The device according to claim 1, wherein the first region has a spiral shape.

14. The device according to claim 1, wherein the first servo position information is included in an intermediate pattern for self-servo writing.

15. The device according to claim 1, wherein a plurality of the magnetic recording media and a plurality of the magnetic heads are provided, and the controller is configured to perform the first operation and the second operation for the plurality of magnetic recording media and the plurality of magnetic heads.

16. The device according to claim 1, wherein the magnetic head includes a second magnetic pole and a magnetic element provided between the first magnetic pole and the second magnetic pole, and the controller is configured to supply an element current to the magnetic element when the magnetic head records the information on the magnetic recording medium.

17. A method for manufacturing a magnetic recording device, the method comprising:
manufacturing a magnetic recording device, the magnetic recording device including: a magnetic recording medium, a magnetic head configured to record information on the magnetic recording medium, and a controller configured to control the magnetic recording medium and the magnetic head, the magnetic head including: a coil, a first magnetic pole configured to generate a magnetic field according to a recording current supplied to the coil, and a light emitting section configured to irradiate the magnetic recording medium with a light to locally increase a temperature of the magnetic recording medium, the controller being configured to perform a first operation and a second operation, in the first operation, the controller being configured to record a first servo position information in a first region of the magnetic recording medium, in the second operation, the controller being configured to perform a repair operation if a first condition is not satisfied, the

first condition including that a recording condition of the first servo position information is within a first range being determined, and in the repair operation, the controller being configured to perform an erasing operation of irradiating the first region with the light from the light emitting section to perform a re-recording operation of re-recording the first servo position information in the first region after the erasing operation.

18. The method according to claim 17, wherein the first condition further includes that a result of detecting the first servo position information recorded in the first region by the first operation is within a second range being determined.

19. The method according to claim 17, wherein in the first operation, the controller is configured to record the first servo position information in the first region while irradiating the magnetic recording medium with the light, and an erasing intensity of the light in the erasing operation is higher than a recording intensity of the light in the first operation.

20. The method according to claim 19, wherein the light emitting section includes a light source, and the recording conditions for the first servo position information include a power supplied to the light source in the first operation.
