

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent Application Publication

20250275083

Kind Code

A1

Publication Date

August 28, 2025

Inventor(s)

HIDALGO ARDANA; Pablo et al.

---

### DUAL OUTLET BLOWER TECHNOLOGY FOR ENHANCED HEAT TRANSFER IN THIN FORM FACTOR DEVICES

---

#### Abstract

Disclosed herein are blower fans, a computing device having blower fans, and a method for operating a computing device having blower fans. The blower fans described herein include blower fans having one air outlet and blower fans having two (e.g., dual) air outlets. In one example, the blower fan includes at least one outlet that is configured to direct air between an electronic device and a housing of the computing device, thus mitigating hot spots direct adjacent the electronic device.

---

**Inventors:** HIDALGO ARDANA; Pablo (Austin, TX), NISHI; Yoshifumi (Austin, TX)

**Applicant:** Advanced Micro Devices, Inc. (Santa Clara, CA)

**Family ID:** 1000008374410

**Appl. No.:** 18/984878

**Filed:** December 17, 2024

#### Related U.S. Application Data

us-provisional-application US 63559013 20240228

---

#### Publication Classification

**Int. Cl.:** H05K7/20 (20060101); G06F1/20 (20060101)

**U.S. Cl.:**

**CPC** H05K7/20172 (20130101); G06F1/206 (20130101); H05K7/20145 (20130101); G06F2200/201 (20130101); H05K7/20154 (20130101)

---

## Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS [0001] This application claims benefit of U.S. Provisional Application Ser. No. 63/559,013, filed Feb. 28, 2024, which is incorporated by reference in its entirety.

### TECHNICAL FIELD

[0002] Embodiments of the disclosure generally relate to blower fans suitable for use in computing devices, and computing devices having the same. More particularly, some embodiments of the disclosure relate to dual outlet blower fans and computing devices having the same.

### BACKGROUND

[0003] Today's mobile devices must meet strict skin temperature limit for safety, ergonomics and user experience (UX). Adding to these challenges, end users have also come to expect lower temperature ergonomics over the years despite the increased heat flux from the processor and increased power support to allow novel experiences like AI to be run locally in local computing device (such as Edge computing) in mobile computing devices, such as laptops, tablets, mobile phones and the like. Almost all OEMs are implementing mechanisms for steady-state power reduction control in their mobile computing devices to meet such skin temperature limits. Furthermore, with ever shrinking thickness of mobile computing devices, it is becoming increasingly more difficult to assure mechanical reliability of the cooling fans used in these devices.

[0004] Some known techniques for improved cooling include the use of high conductivity heat spreaders (copper foil, graphite sheet) bonded to the bottom skin of the mobile computing device. Auxiliary system cooling fans for active internal cooling have also been utilized, along with pressurized airflow inside the chassis of the mobile computing device and heat pipes. However, these techniques have not completely quenched the need for improved cooling.

[0005] Thus, there remains a need for improved cooling for computing devices.

### SUMMARY

[0006] Disclosed herein are blower fans, a computing device having blower fans, and a method for operating a computing device having blower fans. The blower fans described herein include blower fans having one air outlet and blower fans having two (e.g., dual) air outlets. In one example, the blower fan includes at least one outlet that is configured to direct air between an electronic device and a housing of the computing device, thus mitigating hot spots direct adjacent the electronic device.

[0007] In one example, a blower fan is provided. The blower fan includes a fan blade disposed in an interior volume of a housing. The housing includes a first cover, a second cover, a first side and a second side. The first and second covers and the first and second sides partially bound the interior volume of the housing in which the fan blade is disposed. The first cover has an air inlet formed therethrough. The housing has a first air outlet defined through the first side. The housing has a second air outlet defined through one or both of the second side and the first cover. The first air outlet is configured to predominantly direct air in a direction substantially parallel with a plane of the first cover, while the second air outlet is configured to direct air in a direction forming an obtuse angle with the plane of the first cover.

[0008] In another example, computing device is provided. The computing device includes a housing having an interior volume in which an electronic device and blower fan are disposed. The electronic device includes at least one integrated circuit (IC) die. The blower fan includes first cover, a second cover, a first side and a second side. The first and second covers and the first and second sides partially bound an interior volume of the blower fan. The first cover is disposed parallel with and adjacent to a side of the housing. The blower fan has an air inlet is formed

through one of the first and second covers, a first air outlet defined through the first side, and a second air outlet defined through one or both of the second side and the one of the first and second covers closest to the side of the housing. The first air outlet is configured to direct air in a direction substantially parallel with a plane of the first cover, while the second air outlet configured to direct air in a direction more directed toward the side of the housing relative to the direction of the air exiting the first air outlet.

[0009] In still another example, a method for operating a computing device is provided. The method includes operating one or more integrated circuit (IC) dies of an electronic device disposed in an interior volume of a housing of the computing device; directing air exiting a first air outlet of a blower fan in a direction substantially parallel to a side of the housing; and directing air exiting a second air outlet of a blower fan in a direction more toward the side of the housing relative to the direction of the air exiting the first air outlet, the air exiting the second air outlet directed between the electronic device and the side of the housing.

---

## Description

### BRIEF DESCRIPTION OF DRAWINGS

[0010] FIG. 1 is a simplified schematic diagram of a computing device having a dual outlet blower fan.

[0011] FIG. 2 depicts an exploded view of a portion of the computing device illustrating the dual outlet blower fan, a heat generating electronic device, and a thermal module.

[0012] FIGS. 3 and 4 depict top and bottom views of the dual outlet blower fan illustrated in FIG. 1.

[0013] FIG. 5 depicts a side view of the dual outlet blower fan illustrated in FIG. 1.

[0014] FIGS. 6 and 7 depict partial sectional views through the sidewalls of the dual outlet blower fan illustrated in FIG. 1.

[0015] FIG. 8 depicts a partial sectional view of the computing device illustrating air flow being directed from one outlet of the dual outlet blower fan along a housing of the computing device, according to a first example.

[0016] FIG. 9 depicts a partial sectional view of the computing device illustrating air flow being directed from one outlet of the dual outlet blower fan along a housing of the computing device, according to a second example.

[0017] FIG. 10 depicts a partial sectional view of the computing device illustrating air flow being directed from one outlet of the dual outlet blower fan along a housing of the computing device, according to a third example.

[0018] FIG. 11 depicts a partial sectional view of the computing device illustrating air flow being directed from one outlet of the dual outlet blower fan along a housing of the computing device, according to a fourth example.

[0019] FIG. 12 is a block diagram of a method for operating a computing device having a dual outlet blower fan.

[0020] FIGS. 13 and 14 depict top and bottom views of a single outlet blower fan.

[0021] FIG. 15 depicts a partial sectional view of the computing device illustrating air flow being directed from one outlet of a single outlet blower fan along a housing of the computing device, according to a first example.

[0022] FIG. 16 is a top view of a thermally conductive sheet of the single outlet blower fan depicted in FIGS. 13 and 14.

[0023] FIG. 17 is a block diagram of a method for operating a computing device having a single outlet blower fan.

[0024] To facilitate understanding, identical reference numerals have been used, where possible, to

designate identical elements that are common to the figures. It is contemplated that elements of one embodiment may be beneficially incorporated in other embodiments.

#### DETAILED DESCRIPTION

[0025] Described herein is a unique geometry of blower fans that enable better cooling of the outside surfaces (skin) of a chassis (e.g., case or housing) of computing devices, improved mechanical reliability of the fans, and lower cost of the fan assembly. Both single and dual outlet blower fans are disclosed herein. The unique geometry of the dual outlet blower fan enable mobile and other computing devices to achieve enhanced chassis surface cooling for improved ergonomics and mechanical reliability. In one example, a computing device includes a housing, a thermal module, and a dual outlet blower fan. The thermal module and the dual outlet blower fan are disposed in an interior volume of the housing. The thermal module has a surface disposed in a parallel spaced apart relationship with a skin of the housing. The dual outlet blower fan is oriented to direct flow from a first outlet into the interior volume of the housing while a secondary outlet of the dual outlet blower fan between the thermal module and the skin.

[0026] The secondary outlet opening on the blower fan fan's cover faces and/or is over one of the sidewalls such that the flow exiting such opening forms a wall jet that is directed against the system chassis and flow along it. The wall jet has significantly faster velocity as compared to conventional fans, and does not sacrifice significant amount of flow being diverted from the primary outlet of the blower fan, therefore cooling the skin of the computing device more efficiently.

[0027] Retaining the sidewall structure of the blower fan (as compared to conventional dual blower fans that have one sidewall removed to accommodate the second outlet) also enables additional mechanical structure for support and can prevent the system chassis from mechanical contact the fan rotor when under a compressive load. Thus, the blower fan disclosed herein has enhanced reliability. Moreover, the reliability improvement is not limited to the blower fans, but rather the disclosed technology improves product level mechanical reliability (since many modern devices consider fans as structural parts).

[0028] With the conventional dual outlet blower fan, a part of the frame (i.e., sidewall) needs to be cut to create an opening. This creates structurally weak point and additional reinforcement on the fan covers is typically required. With the present innovation, the frame remains intact therefore structure of the fan is not compromised.

[0029] Cut frame of the conventional dual outlet blower fan requires a separate sub-frame to support the covers, thus requiring an additional part and tooling cost. In contrast, the novel dual outlet blower fan eliminates the need for additional parts and lowers the overall cost of the blower fan.

[0030] The unique geometry of novel dual outlet blower fan enables better cooling of the outside surfaces (skin or chassis) of computing devices (such as laptops, desktops, servers, controllers, vehicle computing devices, mobile computing devices, smart phones, and the like), improved mechanical reliability of the fans, and lower cost of the fan assembly. Novel features include outlet opening(s) on fan cover(s) or sidewall to introduce a directed wall jet (over the sidewall) that flows along the chassis of the computing device. With conventional dual outlet blower fan pressurizing the system, flow is quickly dispersed and diffused. With the novel dual outlet blower fan, flow “attaches” to the bottom surface of cover wall (i.e., the skin) of the computing device, and retains higher velocity without losing significant portion of airflow to the primary heatsink, (i.e., thermal module). This result in significantly more efficient cooling of the chassis and of the electronic device.

[0031] In one example, a computing device includes a housing, a thermal module, and a dual outlet blower fan. The thermal module and the dual outlet blower fan are disposed in an interior volume of the housing. The thermal module has a surface disposed in a parallel spaced apart relationship with a skin of the housing. The dual outlet blower fan is oriented to direct flow from a first outlet of the dual outlet blower fan between the thermal module and the skin.

[0032] In another example, the dual outlet blower fan of the computing device includes a thermally conductive sheet extending from the housing in the same direction in which air exiting the second air outlet is directed. A single outlet blower fan is disclosed that also beneficially includes a thermally conductive sheet extending from the housing.

[0033] In another example, the dual outlet blower fan of the computing device includes a top cover disposed in a parallel spaced apart relationship with the skin of the housing.

[0034] In another example, the top cover further comprises an inlet and a notch, the notch forming the first outlet of the dual outlet blower fan.

[0035] In another example, the dual outlet blower fan of the computing device has a first sidewall coupled to the top cover, at least a portion of the sidewall spaced apart from the cover to form the first outlet of the dual outlet blower fan.

[0036] In another example, the dual outlet blower fan of the computing device preferentially directs a greater amount of flow from the first outlet of the dual outlet blower fan between a first surface of the thermal module and the skin relative to flow between a second surface of the thermal module that faces away from the second surface and a chip package.

[0037] Turning now to FIG. 1, a simplified schematic diagram of a computing device **100** having a dual outlet blower fan **122** is illustrated. The computing device **100** may be embodied a laptop, desktop, server, controller, vehicle computing device, mobile computing device, or a smart phone, among others. The computing device **100** includes a chassis **102** that encloses an interior volume **106**. The chassis **102** may also be referred to as an enclosure or housing. The computing device **100** also includes at least one electronic device **116** disposed in the interior volume **106** that is cooled, at least in part, by the dual outlet blower fan **122**. Optionally, a thermal module **108** may also be disposed in the interior volume **106** that is utilized to enhance the cooling of the electronic device **116**.

[0038] The dual outlet blower fan **122** is generally disposed adjacent the skin **104** (i.e., outer surface) of the chassis **102**. The skin **104** also includes a plurality of apertures **124** that allow air flow, depicted by arrow **126** in FIG. 1, to enter the interior volume **106** of the computing device **100**, where the air is directed by the dual outlet blower fan **122** to facilitate cooling of the electronic device **116**. The apertures **124** may be holes, slots or other passage that facilitates air movement into the interior volume **106** of the chassis **102**. In FIG. 1, the dual outlet blower fan **122** is disposed immediately adjacent the plurality of apertures **124** formed through the skin **104** of the chassis **102**. Although not shown in FIG. 1, standoffs may be utilized to space the dual outlet blower fan **122** from the skin **104** of the chassis **102**.

[0039] The dual outlet blower fan **122** generally includes a first (i.e., top) cover **130** and a second (i.e., bottom) cover **132** that are coupled by sidewalls **134**. The top and bottom covers **130**, **132** define the major surfaces of the dual outlet blower fan **122**. The top cover **130** includes the inlet of the dual outlet blower fan **122**, and is generally spaced below the air inlet apertures **124** of the chassis **102**. The top cover **130** may also include one of the outlets of the dual outlet blower fan **122**, with the other outlet formed through one of the sidewalls **134**, as further illustrated below with respect to FIG. 2.

[0040] Continuing to refer to FIG. 1, the electronic device **116** generally includes at least one integrated circuit (IC) die **114**. The IC die **114** may be part of a chip package **112** that includes a package substrate and optionally one or more other IC dies. The IC die **114** includes functional circuitry. The functional circuitry of the IC die **114** may be configured to function as a programmable logic device, such as field programmable gate array (FPGA), a memory device, an optical device, a logic device, a processor, a math engine, or other IC logic structures. Optical devices include photo-detectors, lasers, optical sources, and the like.

[0041] In one example, the functional circuitry of the IC die **114** may include central processing unit (CPU) cores. As such, the IC die **114** containing CPU cores may be referred to as a CPU die or CPU chiplet. The functional circuitry of the IC die **114** may also include System Management Unit

(SMU). The SMU is circuitry configured to monitor thermal and power conditions and adjust power and cooling to keep the IC die **114** functioning as within specifications. The functional circuitry of the IC die **114** may also include Dynamic Function exchange (DFX) Controller IP circuitry. The DFX circuitry provides management of hardware or software trigger events. For example, the DFX circuitry may pull partial bitstreams from memory and delivers them to an internal configuration access port (ICAP). The DFX circuitry also assists with logical decoupling and startup events, customizable per Reconfigurable Partition.

[0042] In another example, the functional circuitry of IC die **114** includes accelerated compute cores. As such, the IC die **114** containing accelerated compute cores may be referred to as an accelerator die or accelerator chiplet. The IC die **114** containing accelerated compute cores may also be referred to as a graphic processing unit (GPU) die or GPU chiplet. The accelerated compute cores contained in the functional circuitry of the IC die **114** generally includes math engine circuitry. The math engine circuitry is generally designed for task specific computing, such as used data center computing, high performance computing and AI/ML computing. Along with the accelerated compute cores, functional circuitry of the IC die **114** may also include SMU circuitry and DFX circuitry.

[0043] The IC die **114** (and/or chip package **112**) is mounted to a printed circuit board **110**. The printed circuit board **110** may be part of a motherboard, daughter board, expansion card and the like. The printed circuit board **110** and IC die **114** mounted thereon are generally spaced laterally from, and below, the dual outlet blower fan **122** (utilizing the skin **104** that contains the apertures **124** as a point of reference).

[0044] The thermal module **108**, when present, is disposed between the electronic device **116** and side of the chassis **102** that contains the apertures **124**. The thermal module **108** is spaced from the skin **104**, thus forming a first air passage **118** defined between the thermal module **108** and the skin **104**. The thermal module **108** is also spaced from the IC die **114** of the electronic device **116**, thus forming a second air passage **120** defined between the thermal module **108** and the electronic device **116** (i.e., the IC die **114**). As later detailed below, air exiting one outlet of the dual outlet blower fan **122** preferentially directs air through the first air passage **118** relative to the second air passages **120**, which enhances heat transfer between the thermal module **108** and skin **104** of the chassis **102**, which effectively increases the heat transfer from the electronic device **116** to the chassis **102**. The enhanced heat transfer from the IC die **114** of the electronic device **116** to the chassis **102** results in improved performance, reliability and service life of the IC die **114**, and consequently, improved performance, reliability and service life of the computing device **100**.

[0045] FIG. 2 depicts an exploded view of a portion of the computing device **100** illustrating the dual outlet blower fan **122**, the electronic device **116**, and the thermal module **108**. The thermal module **108** generally includes a body **212** formed from a metal or other material having high thermal conductivity. The body **212** has a first side **202** that faces the skin **104** of the chassis **102** that includes the air inlet apertures **124**. The body **212** has a second side **204** that faces away from the side **202** and toward the electronic device **116**. The first side **202** bounds one side of the first air passage **118**, while the second side **204** bounds one side of the second air passage **120**. In some examples, the body **212** may also include an extension **222** that, with the main portion body **212**, forms a notch **214** for receiving the dual outlet blower fan **122**.

[0046] The thermal module **108** generally functions as a heat sink and or heat exchanger for removing heat generated by the electronic device **116** so that the IC die **114** may be maintained at or below maximum operating temperature. The thermal module **108** also provides the electronic device **116** from creating hot spots in the adjacent portions of the skin **104** of the chassis **102**. The thermal module **108** may be at least one or both of an active or passive heat transfer device. Examples of active heat transfer devices includes thermoelectric coolers, forced air heat exchangers, forced liquid heat exchangers, and the like. Examples of passive heat transfer devices includes vapor chambers, heat pipes, phase change materials, fins, and the like. In the example

depicted in FIG. 1, the thermal module **108** includes fins **206** and one or more internal passages (not shown) coupled to a coolant inlet **208** and coolant outlet **210** for circulating a coolant within the body **212** of the thermal module **108**.

[0047] As briefly described above, the dual outlet blower fan **122** includes top and bottom covers **130**, **132** coupled by sidewalls **134**. The top and bottom covers **130**, **132** are, in one example, parallel to a plane defined by the skin **104** of the chassis **102** that contains the air inlet apertures **124**. The dual outlet blower fan **122** is generally rectangular in shape, having first, second, third and fourth sides **230**, **232**, **234**, **236**.

[0048] The dual outlet blower fan **122** generally has a first air outlet **240** formed in one of the sides **230**, **232**, **234**, **236** of the dual outlet blower fan **122**. The first side **230** of the dual outlet blower fan **122** is oriented to generally face in the direction of the electronic device **116**. In FIG. 2, the first air outlet **240** formed in the fourth side **236** of the dual outlet blower fan **122**. Air (illustrated by arrow **254**) exiting the first air outlet **240** of the dual outlet blower fan **122** is predominantly directed in a direction parallel to the plane defined by the skin **104** of the chassis **102** that contains the air inlet apertures **124**. The first air outlet **240** is oriented facing the extension **222** of the body **212** of the thermal module **108** such that air exiting the first air outlet **240** of the dual outlet blower fan **122** is directed across the fins **206** extending from the thermal module **108**. The first air outlet **240** may optionally also have an orientation not direct facing the electronic device **116**, such that air exiting the first air outlet **240** of the dual outlet blower fan **122** is directed away from (i.e., not in direct contact with) the electronic device **116**.

[0049] A second air outlet **242** of the dual outlet blower fan **122** is generally formed another one of the sides **230**, **232**, **234**, **236** and/or the top cover **130** of the dual outlet blower fan **122**. In FIG. 2, the first air outlet **240** formed through the top cover **130** generally adjacent to the first side **230** of the dual outlet blower fan **122**. As the first dies **130** of the dual outlet blower fan **122** is adjacent the fourth side **236** of the dual outlet blower fan **122**, the direction of air (illustrated by arrow **252**) exiting the second air outlet **242** is substantially perpendicular to the direction of the air (illustrated by arrow **254**) exiting the first air outlet **240** of the dual outlet blower fan **122** when viewed in a direction perpendicular to the plane of the top cover **130**. The air exiting the second air outlet **240** of the dual outlet blower fan **122** also is directed at an angle more towards the skin **104** of the chassis **102** that contains the air inlet apertures **124** relative to the air exiting the first air outlet **240** of the dual outlet blower fan **122**. Thus, air exiting the second air outlet **240** of the dual outlet blower fan **122** is directed at an obtuse angle relative to the plane of the top cover **130**, and predominantly directed through the first air passage **118** relative to the second air passage **120** such that that transfer between the thermal module **108** and skin **104** of the chassis **102** is enhanced, ultimately improving thermal management of the temperature of the IC die **114**.

[0050] FIGS. 3 and 4 depict top and bottom views of the dual outlet blower fan **122** illustrated in FIGS. 1 and 2. The dual outlet blower fan **122** generally includes a motor **304** that rotates a rotor **302**. The motor **304** may be a brushless DC or other suitable electric motor. Fan blades **306** are coupled to the rotor **302** such that as the rotor **302** and fan blades **306** are spun by the motor **304**, air is drawn into the dual outlet blower fan **122** through the air inlet **238** formed through the top cover **130**, and forced out of the dual outlet blower fan **122** through the two air outlets **240**, **242** as described above. In one example and as additionally illustrated in FIG. 5, the first air inlet **240** is formed on the fourth side **236** of the dual outlet blower fan **122**. In the example illustrated in FIG. 5, the first air inlet **240** spans the entire fourth side **236** of the dual outlet blower fan **122**, being bounded by the sidewalls **134** present on the first and third sides **130**, **134**.

[0051] Referring now to FIG. 3, the second air outlet **242** is formed along the first side **230** of the dual outlet blower fan **122**. The second air outlet **242** may span the entire first side **230** of the dual outlet blower fan **122** or only a portion of the first side **230** of the dual outlet blower fan **122**. In FIG. 3, the first side **230** of the dual outlet blower fan **122** extends from the second side **232** of the dual outlet blower fan **122** and terminates a distance further from the fourth side **236** of dual outlet

blower fan **122** than a distance that the air inlet **238** is spaced from the fourth side **236**. Stated differently, the second air outlet **242** may span a distance less than half or more than half of a distance defined between the first side **230** and an opposite side (e.g., the third side **234**) of the housing (e.g., chassis **102**).

[0052] As illustrated in FIG. 3, the second air outlet **242** is formed entirely in the top cover **130**. In one example, the second air outlet **242** may be formed as a slot **310** formed in the top cover **130**, wherein a web **312** of material of the top cover **130** separates the second air outlet **242** from the first side **230** of the dual outlet blower fan **122**. In another example, the second air outlet **242** may be formed as a notch **314** formed in the top cover **130** that is open to the sidewall **134** extending across the first side **230** of the dual outlet blower fan **122**. Alternatively, the second air outlet **242** may be formed in one or both of the sidewall **134** and top cover **130** in a manner that directs air towards the skin **104** of the chassis **102**.

[0053] FIGS. 6 and 7 depict partial sectional views through the sidewalls of the dual outlet blower fan **122** illustrated in FIGS. 4 and 5. In FIG. 6, the second air outlet **242** is shown formed at least partially through the top cover **130**. Optionally, a portion of the second air outlet **242** may be formed at least partially through the sidewall **134** spanning the first side **230** of the dual outlet blower fan **122**. The top cover **130** may optionally have a projection **606**, such as a ridge, extending between the second air outlet **242** and the air inlet **238** to help direct the air flow (**252**) in a direction away from the air inlet **238** and into the passage **118** between the thermal module **108** and skin **104** of the chassis **102**.

[0054] FIG. 7 generally depicts that the sidewall **134** spanning the second and third sides **232**, **234** of the dual outlet blower fan **122** connects the top and bottom covers **130**, **132**.

[0055] FIG. 8 depicts a partial sectional view of the computing device **100** illustrating air flow **242** being directed from one outlet **242** of the dual outlet blower fan **122** between the skin **104** of the chassis **102** of the computing device **100**, according to a first example as initially discussed above. As the air flow **242** exiting the second outlet **242** of the dual outlet blower fan **122** has a directional vector towards the skin **104**, the air flow **242** is predominantly directed through the first passage **118** defined between the chassis **102** and top surface **202** of the thermal module **108** relative to the second passage **120** defined between the bottom surface **204** of the thermal module **108** and the electronic device **116**.

[0056] FIG. 9 depicts a partial sectional view of the computing device **100** illustrating air flow **242** being directed from the second outlet **242** of the dual outlet blower fan **122** between the skin **104** of the chassis **102** of the computing device **100**, in an example where the second outlet **242** is at least partially formed in the sidewall **134** spanning the first side **230** of the dual outlet blower fan **122**. The second outlet **242** may optionally be also formed in a portion of the top cover **130**.

[0057] In the example depicted in FIG. 9, the sidewall **134** spanning the first side **230** of the dual outlet blower fan **122** includes a flared portion **902**. The flared portion **902** extends from a portion **910** of the sidewall **134** connected to the bottom cover **132**. The flared portion **902** extends to a distal end **904**. The distal end **904** of the flared portion **902** is spaced from an edge **906** of the top cover **130**, creating an aperture therebetween that forms the second outlet **242** of the dual outlet blower fan **122**. The upwardly and outwardly orientation of the flared portion **902** helps direct the air **252** exiting the second outlet **242** in a direction towards the skin **104** of the chassis **102** and away from the dual outlet blower fan **122**, and consequently predominantly into the first air passage **118** relative to the second air passage **120**.

[0058] FIG. 10 depicts a partial sectional view of the computing device **100** illustrating air flow **242** being directed from one outlet **242** of the dual outlet blower fan **122** between the skin **104** of the chassis **102** of the computing device **100**, according to another example. In the example depicted in FIG. 10, the dual outlet blower fan **122** includes a thermally conductive sheet **1110**. The thermally conductive sheet **1110** may be fabricated from graphite, metal sheet, metal foil, or other suitable highly thermally conductive material. The thermally conductive sheet **1110** includes a first

portion **1112** that is outside of the dual outlet blower fan **122** and a second portion **1114** that is disposed within the dual outlet blower fan **122**. The first portion **1112** extends from the first side **230** of the dual outlet blower fan **122** into the region between the thermal module **108** and skin **104** of the chassis **102**. The first portion **1112** of the thermally conductive sheet **1110** may bound the first air passage **118** with the skin **104** of the chassis **102**. The first portion **1112** of the thermally conductive sheet **1110** may be freely disposed adjacent the thermal module **108**, or may be connected to the thermal module **108** via a thermal interface **1120**. The thermal interface **1120** may be comprises of one or more of thermal interface materials (TIM), heat pipe, solder, brazing material or other material and/or device that enhances the transfer of heat between the thermal module **108** and the conductive sheet **1110**.

[0059] The conductive sheet **1110** functions to increase the heat transfer across the passage **118** to the skin **104** of the chassis **102**. The conductive sheet **1110** also functions to conduct heat from first portion **1112** outside of the dual outlet blower fan **122** to second portion **1114** of the conductive sheet **1110** disposed within the dual outlet blower fan **122**. As the second portion **1114** of the conductive sheet **1110** disposed within the dual outlet blower fan **122** is exposed to higher air velocities, heat is more readily transferred from the second portion **1114** of the conductive sheet **1110** to the air within the dual outlet blower fan **122**, where the heat transferred to the air is rapidly expelled with the air exiting the dual outlet blower fan **122** through the two outlets **240**, **242**.

[0060] The first and second portions **1112**, **1114** of the conductive sheet **1110** may in one example be coplanar. In another example first and second portions **1112**, **1114** of the conductive sheet **1110** reside in parallel planes. The conductive sheet **1110** may, but is not required, to extend through the second outlet **242**.

[0061] In the example depicted in FIG. **10**, the first and second portions **1112**, **1114** of the conductive sheet **1110** are connected by an intermediate portion **1116**. The intermediate portion **1116** may form a step connecting the first and second portions **1112**, **1114**. The intermediate portion **1116** may have an orientation that is perpendicular to at least one of the first and second portions **1112**, **1114** of the conductive sheet **1110** and/or the top cover **130**. Optionally, the intermediate portion **1116** may have an orientation that is flared upward and outward from the second portion **1114** to the first portion **1112** such that air **252** exiting the second outlet **242** is directed towards the skin **104** of the chassis **102**, and predominantly through the first air passage **118** relative to the second air passage **120**.

[0062] FIG. **11** depicts a partial sectional view of the computing device **100** illustrating air flow being directed from one outlet **242** of the dual outlet blower fan **122** along a chassis **102** of the computing device **100**, according to a fourth example. Similar to the dual outlet blower fan **122** described with reference to FIG. **10**, the dual outlet blower fan **122** depicted in FIG. **11** includes a thermally conductive sheet **1110**, except in that the second outlet **242** through which the thermally conductive sheet **1110** extends includes some or all of the first side **230** of the dual outlet blower fan **122**. Although the intermediate portion **1116** of the thermally conductive sheet **1110** illustrated in FIG. **11** has an orientation that is perpendicular to at least one of the first and second portions **1112**, **1114**, the intermediate portion **1116** may optionally have an orientation that is flared upward and outward from the second portion **1114** to the first portion **1112** such that air **252** exiting the second outlet **242** is directed towards the skin **104** of the chassis **102**, and predominantly through the first air passage **118** relative to the second air passage **120**.

[0063] FIG. **12** is a block diagram of a method **1200** for operating a computing device, such as but not limited to the computing device **100** described above. The method **1200** begins a operation **1202** by operating one or more integrated circuit (IC) dies **114** of an electronic device **116** disposed in an interior volume **106** of a housing (e.g., chassis **102**) of a computing device **100**. Operating the IC dies **114** may include performing logic processing, training models, performing computations, reading from memory, writing to memory, or other operation generally able to be performed by the functional circuitry of an integrated circuit die.

[0064] At operation **1204**, air exiting a first air outlet **240** of the dual outlet blower fan **122** is directed in a direction substantially parallel to a side of the housing (e.g., the chassis **102**). For example, air exiting the first air outlet **240** of the dual outlet blower fan **122** is directed in a direction substantially parallel to the skin **104** of a chassis **102** of the computing device **100** that includes the air inlet apertures **124**. Air exiting the first air outlet **240** of the dual outlet blower fan **122** may also be directed across fins of a thermal module **108** disposed next to the dual outlet blower fan **122**.

[0065] At operation **1206**, air exiting a second air outlet **242** of the dual outlet blower fan **122** is directed in a direction more toward the side of the housing relative to the direction of the air exiting the first air outlet **240**, the air exiting the second air outlet **242** directed between the electronic device and the side of the housing. At operation **1206**, air exiting the second air outlet **242** is predominantly directed through a passage defined between the skin of the chassis and a thermal device relative to a passage defined between the thermal device and the electronic device.

[0066] The method **1200** may also include directing air out an opening disposed in a first cover of the dual outlet blower fan facing the housing and facing away from the electronic device.

[0067] The method **1200** may also include directing air between a conductive sheet extending from the dual outlet blower fan and the side of the housing.

[0068] The method **1200** may also include flowing air within the dual outlet blower fan across a portion of the conductive sheet disposed with the dual outlet blower fan.

[0069] FIGS. **13** and **14** depict top and bottom views of a single outlet blower fan **1322**. The single outlet blower fan **1322** may replace the dual outlet blower fan **122** in the computing device **100** described above. The single outlet blower fan **1322** is generally configured the same as any of the dual outlet blower fans **122** described above that include a thermally conductive sheet, except that the second outlet **242** is not present in the single outlet blower fan **1322**. The air outlet **240** of the single outlet blower fan **1322** is generally formed through one of the sides of the single outlet blower fan **1322**, with the other sides enclosed by the sidewalls **134**. In the example depicted in FIGS. **13** and **14**, the air outlet **240** is formed through the fourth side **236** of the single outlet blower fan **1322**, with the other sides **230**, **232**, **234** of the single outlet blower fan **1322** are enclosed by the sidewalls **134**.

[0070] The single outlet blower fan **1322** includes a thermally conductive sheet **1310** that extends outward from one of the sides of the single outlet blower fan **1322**. In the example depicted in FIGS. **13** and **14**, the thermally conductive sheet **1310** extends from the first side **230** of the single outlet blower fan **1322**.

[0071] FIG. **15** depicts a partial sectional view of the computing device **100** illustrating air flow being directed from the outlet **240** of the single outlet blower fan **1322** along a skin **104** of the computing device **100**, according to a first example. The thermally conductive sheet **1310** may be fabricated from graphite, metal sheet, metal foil, or other suitable highly thermally conductive material.

[0072] The thermally conductive sheet **1310** includes a first portion **1312** that is outside of the single outlet blower fan **1322** and a second portion **1314** that is disposed within the single outlet blower fan **1322**. The first portion **1312** extends from the first side **230** of the single outlet blower fan **1322** into the region between the thermal module **108** and skin **104** of the chassis **102**. The first portion **1312** of the thermally conductive sheet **1310** may bound the first air passage **118** with the skin **104** of the chassis **102**. The first portion **1312** of the thermally conductive sheet **1310** may be freely disposed adjacent the thermal module **108**, or may be connected to the thermal module **108** via a thermal interface **1120**. The thermal interface **1120** may be comprises of one or more of thermal interface materials (TIM), heat pipe, solder, brazing material or other material and/or device that enhances the transfer of heat between the thermal module **108** and the conductive sheet **1310**.

[0073] The conductive sheet **1310** functions to increase the heat transfer across the passage **118** to

the skin **104** of the chassis **102**. The conductive sheet **1310** also functions to conduct heat from first portion **1312** outside of the single outlet blower fan **1322** to second portion **1314** of the conductive sheet **1310** disposed within the single outlet blower fan **1322**. Since the first portion **1312** resides over the portion of the thermal module **108** closest to the IC die **114**, heat readily moves from the IC die **114** through the thermal module **108** to first portion **1312** of the conductive sheet **1310** and then to the second portion **1314** of the conductive sheet **1310**. As the second portion **1314** of the conductive sheet **1310** disposed within the single outlet blower fan **1322** is exposed to higher air velocities, heat is more readily transferred from the second portion **1314** of the conductive sheet **1310** to the air within the single outlet blower fan **1322**, where the heat transferred to the air is rapidly expelled with the air exiting the single outlet blower fan **1322** through the outlet **240** way from the electronic device **116**. Thus, the conductive sheet **1310** prevents hot spots from forming in the skin **104** of the chassis **102** that is closely adjacent the electronic device **116**.

[0074] The first and second portions **1312**, **1314** of the conductive sheet **1310** may, in one example, be coplanar. In another example, the first and second portions **1312**, **1314** of the conductive sheet **1310** reside in parallel planes. The conductive sheet **1310** may, but is not required to, extend through the second outlet **242**.

[0075] In the example depicted in FIG. **10**, the first and second portions **1312**, **1314** of the conductive sheet **1310** are connected by an intermediate portion **1316**. The intermediate portion **1316** may form a step connecting the first and second portions **1312**, **1314**. The intermediate portion **1316** may have an orientation that is perpendicular to at least one of the first and second portions **1312**, **1314** of the conductive sheet **1310** and/or the top cover **130**. Optionally, the intermediate portion **1316** may have an orientation that is flared upward and outward from the second portion **1314** to the first portion **1312**.

[0076] The second portion **1314** of the conductive sheet **1310** may be secured to the bottom surface of the top cover **130** above the blades **306** of the single outlet blower fan **1322**. The second portion **1314** of the conductive sheet **1310** may be secured to the bottom surface of the top cover **130** using adhesives, fasteners, staking or other suitable technique. When second portion **1314** is disposed between the fan blades **306** and the air inlet **238** formed through the top cover **130**, the second portion **1314** includes an aperture **1502** to facilitate the flow of air from the air inlet **238** to the fan blades **306**, and ultimately out of the outlet **240**. The aperture **1502** in the second portion **1314** of the conductive sheet **1310** is more clearly depicted in the top view of the thermally conductive sheet **1310** illustrated in FIG. **16**.

[0077] FIG. **17** is a block diagram of a method **1700** for operating for operating a computing device, such as but not limited to the computing device **100** described above. The method **1200** begins a operation **1702** by operating one or more integrated circuit (IC) dies **114** of an electronic device **116** disposed in an interior volume **106** of a housing (e.g., chassis **102**) of a computing device **100**. Operating the IC dies **114** may include performing logic processing, training models, performing computations, reading from memory, writing to memory, or other operation generally able to be performed by the functional circuitry of an integrated circuit die.

[0078] At operation **1704**, air entering the single outlet blower fan **1322** is directed across a thermally conductive sheet **1310** disposed in the interior of the single outlet blower fan **1322**. The thermally conductive sheet **1310** extend out of the single outlet blower fan **1322** in a direction different than a direction that air exits the single outlet blower fan **1322**. The thermally conductive sheet **1310** extends over the electronic device **116**. The thermally conductive sheet **1310** also extends over the thermal module **108**.

[0079] At operation **1706**, air is directed out of an air outlet **240** of the single outlet blower fan **1322** in a direction away from the electronic device **116**. In one example, the direction that the thermally conductive sheet **1310** extends away from single outlet blower fan **1322** is substantially perpendicular or opposite to a direction that air is directed out of the outlet **240** of the single outlet blower fan **1322**.

[0080] Thus, the blower fans and computing devices described herein provide a beneficial alternative to conventional blower fans. The dual outlet blower fans disclosed herein have fewer parts and thus are more cost effective to fabricate, and also have increased structural integrity advantageously suitable for today's higher aspect ratio (shorter but wider) fan designs. The increase rigidity of the cooling fans described herein also results in improved system level mechanical reliability, and allows re-use of a chassis designed for most other cooling technologies without modifications.

[0081] While the foregoing is directed to embodiments of the present disclosure, other and further embodiments may be devised without departing from the basic scope thereof, and the scope thereof is determined by the claims that follow.

## Claims

1. A blower fan comprising: a plurality of fan blades operably coupled to a motor; and a housing having a first cover, a second cover, a first side and a second side, the first and second covers and the first and second sides partially bounding an interior volume of the housing, the first cover having an air inlet formed therethrough, the housing having a first air outlet defined through the first side, the housing having a second air outlet defined through one or both of the second side and the first cover, the first air outlet configured to direct air in a direction substantially parallel with a plane of the first cover, and the second air outlet configured to direct air in a direction forming an obtuse angle with the plane of the first cover.
2. The blower fan of claim 1, wherein the second side includes a sidewall extending from the second cover towards the first cover, the second air outlet defined between an edge of the sidewall and the first cover.
3. The blower fan of claim 2, wherein a portion of the sidewall meets the first cover, the second air outlet defined in a notch formed in the sidewall.
4. The blower fan of claim 1, wherein first cover includes an opening that defines the second air outlet.
5. The blower fan of claim 4, wherein opening extends half or less than a distance defined between the first side and an opposite side of the housing.
6. The blower fan of claim 4, wherein opening extends half or more than a distance defined between the first side and an opposite side of the housing.
7. The blower fan of claim 1, wherein the first and second sides are adjacent to one another.
8. The blower fan of claim 1 further comprising: a thermally conductive sheet extending from the housing in a common direction that the second air outlet is oriented to direct air exiting the second air outlet.
9. The blower fan of claim 8, wherein the thermally conductive sheet is exposed to and extends at least partially across the interior volume of the housing.
10. A computing device comprising: a housing; an electronic device comprising at least one integrated circuit (IC) die disposed in an interior volume of the housing; and a blower fan disposed in the interior volume of the housing, the blower fan comprising: a first cover, a second cover, a first side and a second side, the first and second covers and the first and second sides partially bounding an interior volume of the blower fan, the first cover disposed parallel with and adjacent to a side of the housing; an air inlet formed through one of the first and second covers; a first air outlet defined through the first side; and a second air outlet defined through one or both of the second side and the one of the first and second covers closest to the side of the housing, the first air outlet configured to direct air in a direction substantially parallel with a plane of the first cover, and the second air outlet configured to direct air in a direction more toward the side of the housing relative to the direction of air exiting the first air outlet.
11. The computing device of claim 10, wherein the second side includes a sidewall extending from

the second cover towards the first cover, the second air outlet defined between an edge of the sidewall and the first cover.

**12.** The computing device of claim 11, wherein a portion of the sidewall meets the first cover, the second air outlet defined in a notch formed in the sidewall.

**13.** The computing device of claim 10, wherein first cover includes an opening that defines the second air outlet.

**14.** The computing device of claim 10 further comprising: a thermal management device disposed between the electronic device and a sidewall of the housing, wherein the second air outlet directs air between the side of the housing and the thermal management device.

**15.** The computing device of claim 14 further comprising: a thermally conductive sheet extending from the blower fan between the side of the housing and the thermal management device, wherein the second air outlet directs air between the side of the housing and the thermally conductive sheet.

**16.** The computing device of claim 15, wherein the thermally conductive sheet is exposed to and extends at least partially across the interior volume of the blower fan.

**17.** A method for operating a computing device having a dual outlet blower fan, the method comprising: operating one or more integrated circuit (IC) dies of an electronic device disposed in an interior volume of a housing of the computing device; directing air exiting a first air outlet of the dual outlet blower fan in a direction substantially parallel to a side of the housing; and directing air exiting a second air outlet of the dual outlet blower fan in a direction more toward the side of the housing relative to the direction of the air exiting the first air outlet, the air exiting the second air outlet directed between the electronic device and the side of the housing.

**18.** The method of claim 17, wherein directing air exiting the second air outlet further comprises: directing air out an opening disposed in a first cover of the dual outlet blower fan facing the housing and facing away from the electronic device.

**19.** The method of claim 17, wherein directing air exiting the second air outlet further comprises: directing air between a conductive sheet extending from the dual outlet blower fan and the side of the housing.

**20.** The method of claim 19 further comprising flowing air within the dual outlet blower fan across a portion of the conductive sheet disposed with the dual outlet blower fan.

---