

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250275399

Kind Code

A1

Publication Date

August 28, 2025

Inventor(s)

SONG; Ki Woong et al.

DISPLAY APPARATUS HAVING PIXEL AREAS

Abstract

A display apparatus including pixel areas is provided. Each of the pixel areas can include a first sub-pixel and a second sub-pixel. Each of the first sub-pixel and the second sub-pixel can be disposed between a gate line, a data line, a power voltage supply line and a referenced voltage supply line. Each of the first sub-pixel and the second sub-pixel can include a driving circuit electrically connected to a light-emitting device. At least one of the power voltage supply line and the reference voltage supply line can include an auxiliary wiring disposed parallel to a main wiring and a connection wiring electrically connecting the auxiliary wiring to the main wiring. The driving circuit can be electrically connected to the main wiring. A first electrode of the light-emitting device can include a portion overlapping with the auxiliary wiring. Thus, in the display apparatus, a repair process can be simplified.

Inventors: SONG; Ki Woong (Paju-si, KR), JEONG; Yun Sik (Paju-si, KR), JANG; Gyu Bum (Paju-si, KR), KIM; Dong Kyu (Paju-si, KR)

Applicant: LG Display Co., Ltd. (Seoul, KR)

Family ID: 1000008365316

Appl. No.: 19/000114

Filed: December 23, 2024

Foreign Application Priority Data

KR 10-2024-0028815

Feb. 28, 2024

Publication Classification

Int. Cl.: H10K59/131 (20230101)

U.S. Cl.:

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application claims the benefit of Korean Patent Application No. 10-2024-0028815, filed on Feb. 28, 2024, which is hereby incorporated by reference as if fully set forth herein.

BACKGROUND

Technical Field

[0002] The present disclosure relates to a display apparatus in which each of pixel areas includes a plurality of sub-pixels.

Description of the Related Art

[0003] Generally, a display apparatus provides an image to a user. For example, the display apparatus can include a plurality of pixel areas. Each of the pixel areas can realize various colors. For example, each of the pixel areas can include a plurality of sub-pixels. The sub-pixels in each pixel area can display different colors. For example, a driving circuit electrically connected to a light-emitting device can be disposed in each sub-pixel.

BRIEF SUMMARY

[0004] In the display apparatus, the distance between pixel areas may increase due to the driving circuit of each sub-pixel. For example, the distance between sub-pixels displaying the same color may be increased. As a result, the process of forming repair wirings that connect sub-pixels of the same color during a repair process can become more complex. Additionally, the emission area defined within each sub-pixel may be reduced by the presence of the repair wirings. Accordingly, the present disclosure is directed to a display apparatus that substantially obviates one or more problems due to limitations and disadvantages of the related art.

[0005] Various embodiments of the present disclosure provide a display apparatus in which the decrease in the area of the emission area defined in each sub-pixel is minimized, and the process of forming the repair wirings is simplified.

[0006] Additional advantages, technical benefits, and features of the disclosure will be set forth in part in the description which follows and in part will become apparent to those having ordinary skill in the art upon examination of the following or can be learned from practice of the disclosure. The objectives and other advantages of the disclosure can be realized and attained by the structure particularly pointed out in the written description and claims hereof as well as the appended drawings.

[0007] As embodied and broadly described herein, a display apparatus is provided, comprising a first gate line. A first data line crosses the first gate line. A second data line is disposed parallel to the first data line. The second data line crosses the first gate line. A first sub-pixel includes a first driving circuit. The first driving circuit is electrically connected to the first gate line and the first data line. A second sub-pixel includes a second driving circuit. The second driving circuit is electrically connected to the first gate line and the second data line. A first power line is disposed parallel to the first data line and the second data line. The first power line includes a main wiring, an auxiliary wiring and a connection wiring. The auxiliary wiring extends parallel to the main wiring. The connection wiring connects the auxiliary wiring to the main wiring. The first driving circuit and the second driving circuit are electrically connected to the main wiring. A first light-emitting device is disposed in the first sub-pixel. A second light-emitting device is disposed in the second sub-pixel. A first electrode of the first light-emitting device and a first electrode of the second light-emitting device include a portion overlapping with the auxiliary wiring.

[0008] The second driving circuit can have a symmetrical arrangement to the first driving circuit

with respect to the first power line.

[0009] The first power line can cross between the first sub-pixel and the second sub-pixel.

[0010] A second power line can be disposed between the first data line and the second data line. A signal applied through the second power line can be different from a signal applied through the first power line.

[0011] Each of the first driving circuit and the second driving circuit can include a driving thin film transistor. A gate electrode of the driving thin film transistor can be disposed parallel to the first gate line.

[0012] A semiconductor pattern of the driving thin film transistor can be disposed parallel to the first data line and the second data line.

[0013] A second gate line can be disposed parallel to the first gate line. The second gate line can cross the first data line and the second data line. A third sub-pixel can include a third driving circuit. The third driving circuit can be electrically connected to the second gate line and the first data line. A fourth sub-pixel can include a fourth driving circuit. The fourth driving circuit can be electrically connected to the second gate line and the second data line. The third driving circuit and the fourth driving circuit can be electrically connected to the main wiring. A third light-emitting device can be disposed in the third sub-pixel. A fourth light-emitting device can be disposed in the fourth sub-pixel. A first electrode of the third light-emitting device and a first electrode of the fourth light-emitting device can include a portion overlapping with the auxiliary wiring.

[0014] The fourth driving circuit can have a symmetrical arrangement to the third driving circuit with respect to the first power line.

[0015] The first driving circuit and the second driving circuit can be disposed close to the first gate line. The third driving circuit and the fourth driving circuit can be disposed close to the second gate line.

[0016] The first gate line and the second gate line can extend in a first direction. The third driving circuit can have a symmetrical arrangement to the first driving circuit with respect to the first direction. The fourth driving circuit can have a symmetrical arrangement to the second driving circuit with respect to the first direction.

[0017] The auxiliary wiring can be disposed on a same layer as the main wiring.

[0018] The auxiliary wiring can include a same material as the main wiring.

[0019] The connection wiring can be disposed on a same layer as the main wiring and the auxiliary wiring.

[0020] The connection wiring can include a same material as the main wiring and the auxiliary wiring.

Description

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

[0021] The accompanying drawings, which are included to provide a further understanding of the present disclosure and are incorporated in and constitute a part of this application, illustrate embodiment(s) of the present disclosure and together with the description serve to explain the principle of the present disclosure. In the drawings:

[0022] FIG. 1 is a view schematically showing a display apparatus according to an embodiment of the present disclosure;

[0023] FIG. 2 is a view showing a circuit of a pixel area in the display apparatus according to the embodiment of the present disclosure;

[0024] FIG. 3 is an enlarged view of K1 region in FIG. 1;

[0025] FIG. 4 is an enlarged view of K2 region in FIG. 3;

[0026] FIG. 5 is an enlarged view of K3 region in FIG. 4;

[0027] FIG. 6 is an enlarged view of K4 region in FIG. 4;

[0028] FIG. 7 is a view taken along I-I' of FIG. 5;

[0029] FIG. 8 is a view taken along II-II' of FIG. 5;

[0030] FIG. 9 is a view showing a plane view of some sub-pixel by a repair process in the display apparatus according to the embodiment of the present disclosure; and

[0031] FIG. 10 is a view showing the display apparatus according to another embodiment of the present disclosure.

DETAILED DESCRIPTION

[0032] Hereinafter, details related to the above objects, technical configurations, and operational effects of the embodiments of the present disclosure will be clearly understood by the following detailed description with reference to the drawings, which illustrate some embodiments of the present disclosure. Here, the embodiments of the present disclosure are provided in order to allow the technical spirit of the present disclosure to be satisfactorily transferred to those skilled in the art, and thus the present disclosure can be embodied in other forms and is not limited to the embodiments described below.

[0033] In addition, the same or extremely similar elements can be designated by the same reference numerals throughout the specification.

[0034] The shapes, sizes, dimensions (e.g., length, width, height, thickness, radius, diameter, area, etc.), ratios, angles, number of elements, and the like illustrated in the accompanying drawings for describing the embodiments of the present disclosure are merely examples, and the present disclosure is not limited thereto.

[0035] A dimension including size and a thickness of each component illustrated in the drawing are illustrated for convenience of description, and the present disclosure is not limited to the size and the thickness of the component illustrated, but it is to be noted that the relative dimensions including the relative size, location, and thickness of the components illustrated in various drawings submitted herewith are part of the present disclosure.

[0036] It will be understood that, when a first element is referred to as being “on” a second element, although the first element can be disposed on the second element so as to come into contact with the second element, a third element can be interposed between the first element and the second element.

[0037] Here, terms such as, for example, “first” and “second” can be used to distinguish any one element with another element. However, the first element and the second element can be arbitrary named according to the convenience of those skilled in the art without departing the technical spirit of the present disclosure.

[0038] The terms used in the specification of the present disclosure are merely used in order to describe particular embodiments, and are not intended to limit the scope of the present disclosure. For example, an element described in the singular form is intended to include a plurality of elements unless the context clearly indicates otherwise. In addition, in the specification of the present disclosure, it will be further understood that the terms “comprises” and “includes” specify the presence of stated features, integers, steps, operations, elements, components, and/or combinations thereof, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or combinations.

[0039] And, unless ‘directly’ is used, the terms “connected” and “coupled” can include that two components are “connected” or “coupled” through one or more other components located between the two components.

[0040] Unless otherwise defined, all terms (including technical and scientific terms) used herein have the same meaning as commonly understood by one of ordinary skill in the art to which example embodiments belong. It will be further understood that terms, such as those defined in commonly used dictionaries, should be interpreted as having a meaning that is consistent with their meaning in the context of the relevant art and should not be interpreted in an idealized or overly

formal sense unless expressly so defined herein.

Embodiments

[0041] FIG. 1 is a view schematically showing a display apparatus according to an embodiment of the present disclosure. FIG. 2 is a view showing a circuit of a pixel area in the display apparatus according to the embodiment of the present disclosure.

[0042] Referring to FIGS. 1 and 2, the display apparatus according to the embodiment of the present disclosure can include a display panel DP. The display panel DP can generate an image provided to a user. For example, pixel areas PA and signal wirings GL, GL1, GL2, DL, DL1, DL2, PL and RL can be disposed in the display panel DP. Various signals can be provided in each pixel area PA through the signal wirings GL, GL1, GL2, DL, DL1, DL2, PL and RL. For example, the signal wirings GL, GL1, GL2, DL, DL1, DL2, PL and RL can include gate lines GL, GL1 and GL2 applying a gate signal, data lines DL, DL1 and DL2 applying a data signal, power voltage supply lines PL supplying a power voltage and reference voltage supply lines RL supplying a reference voltage. The data lines DL, DL1 and DL2 can extend in a direction crossing the gate lines GL, GL1 and GL2. The power voltage supply lines PL and the reference voltage supply lines RL can extend parallel to the data lines DL, DL1 and DL2.

[0043] The gate lines GL, GL1 and GL2 can be electrically connected to a gate driver GD. The data lines DL, DL1 and DL2 can be electrically connected to a data driver. The gate driver GD and the data driver can be electrically connected to a timing controller. The gate driver GD and the data driver can be controlled by the timing controller. For example, the gate driver GD can receive clock signals, reset signals and a start signal from the timing controller, and the data driver can receive digital video data and a source timing signal from the timing controller. The power voltage supply lines PL and the reference voltage supply lines RL can be electrically connected to a power unit.

[0044] The display panel DP can include an active area AA in which the pixel areas PA are disposed, and a bezel area BZ being disposed outside the active area AA. The bezel area BZ can be disposed outside the pixel areas PA. For example, the active area AA can be surrounded by the bezel area BZ. The gate driver GD, the data driver, the timing controller and the power unit can be disposed outside the active area AA. For example, each of the signal wirings GL, GL1, GL2, DL, DL1, DL2, PL and RL can include a region disposed on the bezel area BZ. At least one of the gate driver GD, the data driver, the timing controller and the power unit can be disposed on the bezel area BZ. For example, the display apparatus according to the embodiment of the present disclosure can be a GIP (Gate In Panel) type display apparatus in which the gate driver GD is formed on the bezel area BZ of the display panel DP.

[0045] The pixel areas PA can be disposed side by side in a first direction and a second direction. The second direction can be a direction perpendicular to the first direction. Each of the pixel areas PA can realize various colors. For example, each of the pixel areas PA can include a plurality of sub-pixels R-SP, G-SP, W-SP and B-SP. The sub-pixels R-SP, G-SP, W-SP and B-SP in each pixel area PA can display different colors. For example, each of the pixel area PA can include a red sub-pixel R-SP displaying red color, a green sub-pixel G-SP displaying green color, a white sub-pixel W-SP displaying white color, and a blue sub-pixel B-SP displaying blue color.

[0046] The sub-pixels R-SP, G-SP, W-SP and B-SP of each pixel area PA can be controlled by signals applied through the signal wirings GL, GL1, GL2, DL, DL1, DL2, PL and RL. For example, a driving circuit R-DC, G-DC, W-DC and B-DC electrically connected to a light-emitting device **300R**, **300G**, **300W** and **300B** can be disposed in each sub-pixel R-SP, G-SP and B-SP of each pixel area PA.

[0047] The driving circuit R-DC, G-DC, W-DC and B-DC of each sub-pixel R-SP, G-SP, W-SP and B-SP can control the light-emitting device **300R**, **300G**, **300W** and **300B** of the corresponding sub-pixel R-SP, G-SP, W-SP and B-SP by a signal applied through the signal wirings GL, GL1, GL2, DL, DL1, DL2, PL and RL. The driving circuit R-DC, G-DC, W-DC and B-DC of each sub-pixel R-SP, G-SP, W-SP and B-SP can be electrically connected to one of the gate lines GL, GL1 and

GL2, one of the data lines DL, DL1 and DL2, one of the power voltage supply lines PL, and one of the reference voltage supply lines RL. For example, the driving circuit R-DC, G-DC, W-DC and B-DC of each sub-pixel R-SP, G-SP, W-SP and B-SP can supply a driving current corresponding to the data signal to the light-emitting device **300R**, **300G**, **300W** and **300B** of the corresponding sub-pixel R-SP, G-SP, W-SP and B-SP according to the gate signal. The driving current supplied by the driving circuit R-DC, G-DC, W-DC and B-DC of each sub-pixel R-SP, G-SP, W-SP and B-SP can be maintained for one frame. The driving circuit R-DC, G-DC, W-DC and B-DC of each sub-pixel R-SP, G-SP, W-SP and B-SP can have a same structure. For example, the driving circuit R-DC, G-DC, W-DC and B-DC of each sub-pixel R-SP, G-SP, W-SP and B-SP can include a first thin film transistor TR1, a second thin film transistor TR2, a third thin film transistor TR3 and a storage capacitor Cst.

[0048] FIG. 3 is an enlarged view of K1 region in FIG. 1. FIG. 4 is an enlarged view of K2 region in FIG. 3. FIG. 5 is an enlarged view of K3 region in FIG. 4. FIG. 6 is an enlarged view of K4 region in FIG. 4. FIG. 7 is a view taken along I-I' of FIG. 5. FIG. 8 is a view taken along II-II' of FIG. 5.

[0049] Referring to FIGS. 2 to 8, the first thin film transistor TR1 of each sub-pixel R-SP, G-SP, W-SP and B-SP can transmit the data signal to the second thin film transistor TR2 of the corresponding sub-pixel R-SP, G-SP, W-SP and B-SP according to the gate signal. For example, the first thin film transistor TR1 of each sub-pixel R-SP, G-SP, W-SP and B-SP can function as a switching thin film transistor. The first thin film transistor TR1 of each sub-pixel R-SP, G-SP, W-SP and B-SP can include a first semiconductor pattern and a first gate electrode. The first semiconductor pattern of each sub-pixel R-SP, G-SP, W-SP and B-SP can include a first drain region, a first channel region and a first source region. The first channel region can be disposed between the first drain region and the first source region. The first drain region and the first source region can have a smaller resistance than the first channel region. The first gate electrode of each sub-pixel R-SP, G-SP, W-SP and B-SP can be disposed on the first channel region of the corresponding sub-pixel R-SP, G-SP, W-SP and B-SP. For example, the first gate electrode of each sub-pixel R-SP, G-SP, W-SP and B-SP can be electrically connected to the corresponding gate line GL1 and GL2, and the first drain region of each sub-pixel R-SP, G-SP, W-SP and B-SP can be electrically connected to the corresponding data line DL1 and DL2.

[0050] The second thin film transistor TR2 of each sub-pixel R-SP, G-SP, W-SP and B-SP can generate the driving current corresponding to the data signal. For example, the second thin film transistor TR2 of each sub-pixel R-SP, G-SP, W-SP and B-SP can function as a driving thin film transistor. The second thin film transistor TR2 of each sub-pixel R-SP, G-SP, W-SP and B-SP can have a same structure as the first thin film transistor TR1 of the corresponding sub-pixel R-SP, G-SP, W-SP and B-SP. For example, the second thin film transistor TR2 of each sub-pixel R-SP, G-SP, W-SP and B-SP can include a second semiconductor pattern **221** and a second gate electrode **223**.

[0051] The second semiconductor pattern **221** of each sub-pixel R-SP, G-SP, W-SP and B-SP can include a semiconductor material. For example, the second semiconductor pattern **221** of each sub-pixel R-SP, G-SP, W-SP and B-SP can include low-temperature poly-Si (LPTS) or an oxide semiconductor, such as IGZO. The second semiconductor pattern **221** of each sub-pixel R-SP, G-SP, W-SP and B-SP can include a second drain region **221d**, a second channel region **221c** and a second source region **221s**. The second channel region **221c** can be disposed between the second drain region **221d** and the second source region **221s**. The second drain region **221d** and the second source region **221s** can have a resistance smaller than the second channel region **221c**. For example, the second drain region **221d** and the second source region **221s** can include a conductive region of an oxide semiconductor. The second channel region **221c** can be a region of an oxide semiconductor, which is not conductorized.

[0052] The first semiconductor pattern of each sub-pixel R-SP, G-SP, W-SP and B-SP can include a same material as the second semiconductor pattern **221** of the corresponding sub-pixel R-SP, G-SP,

W-SP and B-SP. The first semiconductor pattern of each sub-pixel R-SP, G-SP, W-SP and B-SP can be disposed on a same layer as the second semiconductor pattern **221** of the corresponding sub-pixel R-SP, G-SP, W-SP and B-SP. The first semiconductor pattern of each sub-pixel R-SP, G-SP, W-SP and B-SP can be formed by a same process as the second semiconductor pattern **221** of the corresponding sub-pixel R-SP, G-SP, W-SP and B-SP. The first semiconductor pattern of each sub-pixel R-SP, G-SP, W-SP and B-SP can be formed simultaneously with the second semiconductor pattern **221** of the corresponding sub-pixel R-SP, G-SP, W-SP and B-SP. The second drain region **221d** of each sub-pixel R-SP, G-SP, W-SP and B-SP can be electrically connected to one of the power voltage supply lines PL.

[0053] The second gate electrode **223** of each sub-pixel R-SP, G-SP, W-SP and B-SP can be disposed on the second semiconductor pattern **221** of the corresponding sub-pixel R-SP, G-SP, W-SP and B-SP. For example, the second gate electrode **223** of each sub-pixel R-SP, G-SP, W-SP and B-SP can overlap the second channel region **221c** of the corresponding sub-pixel R-SP, G-SP, W-SP and B-SP. The second drain region **221d** and the second source region **221s** of each sub-pixel R-SP, G-SP, W-SP and B-SP can be disposed outside the second gate electrode **223** of the corresponding sub-pixel R-SP, G-SP, W-SP and B-SP. The second gate electrode **223** of each sub-pixel R-SP, G-SP, W-SP and B-SP can include a conductive material. For example, the second gate electrode **223** of each sub-pixel R-SP, G-SP, W-SP and B-SP can include a metal, such as aluminum (Al), chrome (Cr), copper (Cu), molybdenum (Mo), titanium (Ti) and tungsten (W). The second gate electrode **223** of each sub-pixel R-SP, G-SP, W-SP and B-SP can be spaced apart from the second semiconductor pattern **221** of the corresponding sub-pixel R-SP, G-SP, W-SP and B-SP. The second gate electrode **223** of each sub-pixel R-SP, G-SP, W-SP and B-SP can be insulated from the second semiconductor pattern **221** of the corresponding sub-pixel R-SP, G-SP, W-SP and B-SP. For example, the second channel region **221c** of each sub-pixel R-SP, G-SP, W-SP and B-SP can have an electrical conductivity corresponding to a voltage applied to the second gate electrode **223** of the corresponding sub-pixel R-SP, G-SP, W-SP and B-SP. The second gate electrode **223** of each sub-pixel R-SP, G-SP, W-SP and B-SP can be electrically connected to the first source region of the corresponding sub-pixel R-SP, G-SP, W-SP and B-SP.

[0054] The first gate electrode of each sub-pixel R-SP, G-SP, W-SP and B-SP can include a same material as the second gate electrode **223** of the corresponding sub-pixel R-SP, G-SP, W-SP and B-SP. The first gate electrode and the second gate electrode **223** of each sub-pixel R-SP, G-SP, W-SP and B-SP can be disposed on a same layer. The first gate electrode of each sub-pixel R-SP, G-SP, W-SP and B-SP can be formed by a same process as the second gate electrode **223** of the corresponding sub-pixel R-SP, G-SP, W-SP and B-SP. For example, the first gate electrode and the second gate electrode **223** of each sub-pixel R-SP, G-SP, W-SP and B-SP can be formed simultaneously.

[0055] The storage capacitor Cst of each sub-pixel R-SP, G-SP, W-SP and B-SP can maintain a voltage applied to the second gate electrode **223** of the corresponding sub-pixel R-SP, G-SP, W-SP and B-SP for one frame. For example, the storage capacitor Cst of each sub-pixel R-SP, G-SP, W-SP and B-SP can be electrically connected to the second source region **221s** and the second gate electrode **223** of the corresponding sub-pixel R-SP, G-SP, W-SP and B-SP. The storage capacitor Cst of each sub-pixel R-SP, G-SP, W-SP and B-SP can have a stacked structure of capacitor electrodes. For example, the storage capacitor Cst of each sub-pixel R-SP, G-SP, W-SP and B-SP include a first capacitor electrode electrically connected to the second source region **221s** of the corresponding sub-pixel R-SP, G-SP, W-SP and B-SP and a second capacitor electrode electrically connected to the second gate electrode **223** of the corresponding sub-pixel R-SP, G-SP, W-SP and B-SP. At least one of the first capacitor electrode and the second capacitor electrode in each sub-pixel R-SP, G-SP, W-SP and B-SP can be formed by using a process of forming the second thin film transistor TR2 of the corresponding sub-pixel R-SP, G-SP, W-SP and B-SP. Thus, in the display apparatus according to the embodiment of the present disclosure, a process of forming the

driving circuit R-DC, G-DC, W-DC and B-DC in each sub-pixel R-SP, G-SP, W-SP and B-SP can be simplified.

[0056] The third thin film transistor TR3 of each sub-pixel R-SP, G-SP, W-SP and B-SP can initialize the storage capacitor Cst of the corresponding sub-pixel R-SP, G-SP, W-SP and B-SP according to the gate signal. For example, the reference voltage can be applied to the storage capacitor Cst of each sub-pixel R-SP, G-SP, W-SP and B-SP by the third thin film transistor TR3 of the corresponding sub-pixel R-SP, G-SP, W-SP and B-SP according to the gate signal. The third thin film transistor TR3 of each sub-pixel R-SP, G-SP, W-SP and B-SP can function as a switching thin film transistor. The third thin film transistor TR3 of each sub-pixel R-SP, G-SP, W-SP and B-SP can have a same structure as the first thin film transistor TR1 of the corresponding sub-pixel R-SP, G-SP, W-SP and B-SP. For example, the third thin film transistor TR3 of each sub-pixel R-SP, G-SP, W-SP and B-SP can include a third semiconductor pattern and a third gate electrode. The third gate electrode of each sub-pixel R-SP, G-SP, W-SP and B-SP can include a third drain region, a third channel region and a third source region. The third gate electrode of each sub-pixel R-SP, G-SP, W-SP and B-SP can be electrically connected to the corresponding gate line GL1 and GL2, the third drain region of each sub-pixel R-SP, G-SP, W-SP and B-SP can be electrically connected to the corresponding reference voltage supply line RL. The gate line GL1 and GL2 electrically connected to the third gate electrode of each sub-pixel R-SP, G-SP, W-SP and B-SP can be the same as the gate line GL1 and GL2 electrically connected to the first gate electrode of the corresponding sub-pixel R-SP, G-SP, W-SP and B-SP. For example, the first thin film transistor TR1 and the third thin film transistor TR3 of each sub-pixel R-SP, G-SP, W-SP and B-SP can be turned on/off simultaneously.

[0057] The light-emitting device 300R, 300G, 300W and 300B of each sub-pixel R-SP, G-SP, W-SP and B-SP can emit light displaying a specific color according to the driving current applied by the driving circuit R-DC, G-DC, W-DC and B-DC of the corresponding sub-pixel R-SP, G-SP, W-SP and B-SP. The light-emitting device 300R, 300G, 300W and 300B of each sub-pixel R-SP, G-SP, W-SP and B-SP can have a same structure. For example, the light-emitting device 300R, 300G, 300W and 300B of each sub-pixel R-SP, G-SP, W-SP and B-SP can include a first electrode 310, a light-emitting layer 320 and a second electrode 330, which are sequentially stacked.

[0058] The first electrode 310 can include a conductive material. The first electrode 310 can include a material having a high transmittance. For example, the first electrode 310 can be a transparent electrode made of a transparent conductive material, such as ITO and IZO.

[0059] The light-emitting layer 320 can generate light having luminance corresponding to a voltage difference between the first electrode 310 and the second electrode 330. For example, the light-emitting layer 320 can include at least one emission material layer (EML). The emission material layer can include an organic emission material, an inorganic emission material or a hybrid emission material. For example, the display apparatus according to the embodiment of the present disclosure can be an organic light-emitting display apparatus including an organic emission material. The light-emitting layer 320 can have a multi-layer structure. For example, the light-emitting layer 320 can at least one of a hole injection layer (HIL), a hole transport layer (HTL), an electron transport layer (ETL) and an electron injection layer (EIL). Thus, in the display apparatus according to the embodiment of the present disclosure, the efficiency of the light-emitting layer 320 can be improved.

[0060] The second electrode 330 can include a conductive material. The second electrode 330 can include a different material from the first electrode 310. A reflection of the second electrode 330 can be greater than a reflection of the first electrode 310. For example, the second electrode 330 can include a metal, such as aluminum (Al) and silver (Ag). Thus, in the display apparatus according to the embodiment of the present disclosure, the light generated by the light-emitting layer 320 can be emitted outside through the first electrode 310. The second electrode 330 can have a lower work-function than the first electrode 310. For example, the first electrode 310 can function

as anode, and the second electrode **330** can function as cathode.

[0061] The light-emitting device **300R**, **300G**, **300W** and **300B** and the driving circuit R-DC, G-DC, W-DC and B-DC of each sub-pixel R-SP, G-SP, W-SP and B-SP can be disposed on a device substrate **100**. The device substrate **100** can include an insulating material. For example, the device substrate **100** can include glass or plastic.

[0062] A plurality of insulating layers **110**, **120**, **130**, **140** and **150** for preventing unnecessary electrical connection can be disposed on the device substrate **100**. For example, a buffer insulating layer **110**, a gate insulating layer **120**, a device passivation layer **130**, a planarization layer **140** and a bank insulating layer **150** can be disposed on the device substrate **100**.

[0063] The buffer insulating layer **110** can be disposed on the device substrate **100**. The buffer insulating layer **110** can prevent the pollution due to the device substrate **100** in a process of forming the driving circuit R-DC, G-DC, W-DC and B-DC of each sub-pixel R-SP, G-SP, W-SP and B-SP. For example, an upper surface of the device substrate **100** toward the driving circuit R-DC, G-DC, W-DC and B-DC of each sub-pixel R-SP, G-SP, W-SP and B-SP can be completely covered by the buffer insulating layer **110**. The driving circuit R-DC, G-DC, W-DC and B-DC of each sub-pixel R-SP, G-SP, W-SP and B-SP can be disposed on the buffer insulating layer **110**. The buffer insulating layer **110** can include an insulating material. For example, the buffer insulating layer **110** can include an inorganic insulating material, such as silicon oxide (SiOx) and silicon nitride (SiNx). The buffer insulating layer **110** can have a multi-layer structure. For example, the buffer insulating layer **110** can have a structure in which an inorganic insulating layer made of silicon oxide (SiOx) and an inorganic insulating layer made of silicon nitride (SiNx) are stacked.

[0064] A light-blocking pattern **105** can be disposed between the device substrate **100** and the buffer insulating layer **110** of each sub-pixel R-SP, G-SP, W-SP and B-SP. The light-blocking pattern **105** of each sub-pixel R-SP, G-SP, W-SP and B-SP can include a material capable of blocking light. For example, the light-blocking pattern **105** of each sub-pixel R-SP, G-SP, W-SP and B-SP can include a metal, such as aluminum (Al), chrome (Cr), copper (Cu), molybdenum (Mo), titanium (Ti) and tungsten (W). The light-blocking pattern **105** of each sub-pixel R-SP, G-SP, W-SP and B-SP can overlap the second semiconductor pattern **221** of the corresponding sub-pixel R-SP, G-SP, W-SP and B-SP. Thus, in the display apparatus according to the embodiment of the present disclosure, the light travelling toward the second semiconductor pattern **221** of each sub-pixel R-SP, G-SP, W-SP and B-SP passing through the device substrate **100** can be blocked by the light-blocking pattern **105** of the corresponding sub-pixel R-SP, G-SP, W-SP and B-SP. Therefore, in the display apparatus according to the embodiment of the present disclosure, the change in the characteristics of the second thin film transistor TR2 in each sub-pixel R-SP, G-SP, W-SP and B-SP due to an external light can be prevented.

[0065] A specific voltage can be applied to the light-blocking pattern **105** of each sub-pixel R-SP, G-SP, W-SP and B-SP. For example, a source connection electrode **240** for electrically connecting the light-blocking pattern **105** to the second source region **221s** can be disposed in sub-pixel R-SP, G-SP, W-SP and B-SP. The source connection electrode **240** of sub-pixel R-SP, G-SP, W-SP and B-SP can include a conductive material. The source connection electrode **240** of each sub-pixel R-SP, G-SP, W-SP and B-SP can include a material having a relative low resistance. For example, the source connection electrode **240** of each sub-pixel R-SP, G-SP, W-SP and B-SP can include a metal, such as aluminum (Al), chrome (Cr), copper (Cu), molybdenum (Mo), titanium (Ti) and tungsten (W). The source connection electrode **240** of each sub-pixel R-SP, G-SP, W-SP and B-SP can be disposed on a same layer as the second gate electrode **223** of the corresponding sub-pixel R-SP, G-SP, W-SP and B-SP. The second gate electrode **223** and the source connection electrode **240** of each sub-pixel R-SP, G-SP, W-SP and B-SP can include a same material. The source connection electrode **240** of each sub-pixel R-SP, G-SP, W-SP and B-SP can be formed by a same process as the second gate electrode **223** of the corresponding sub-pixel R-SP, G-SP, W-SP and B-SP. For example, the second gate electrode **223** and the source connection electrode **240** of each sub-pixel

R-SP, G-SP, W-SP and B-SP can be formed simultaneously. Thus, in the display apparatus according to the embodiment of the present disclosure, the change in the characteristics of the second thin film transistor TR2 in each sub-pixel R-SP, G-SP, W-SP and B-SP can be effectively prevented.

[0066] The gate insulating layer **120** can be disposed on the buffer insulating layer **110**. The first gate electrode of each sub-pixel R-SP, G-SP, W-SP and B-SP can be insulated from the first semiconductor pattern of the corresponding sub-pixel R-SP, G-SP, W-SP and B-SP by the gate insulating layer **120**. The second gate electrode **223** of each sub-pixel R-SP, G-SP, W-SP and B-SP can be insulated from the second semiconductor pattern **221** of the corresponding sub-pixel R-SP, G-SP, W-SP and B-SP by the gate insulating layer **120**. The third gate electrode of each sub-pixel R-SP, G-SP, W-SP and B-SP can be insulated from the third semiconductor pattern of the corresponding sub-pixel R-SP, G-SP, W-SP and B-SP by the gate insulating layer **120**. For example, the gate insulating layer **120** can cover the first semiconductor pattern, the second semiconductor pattern **221** and the third semiconductor pattern of each sub-pixel R-SP, G-SP, W-SP and B-SP. The first gate electrode, the second gate electrode **223** and the third gate electrode of each sub-pixel R-SP, G-SP, W-SP and B-SP can be disposed on the gate insulating layer **120**. The source connection electrode **240** of each sub-pixel R-SP, G-SP, W-SP and B-SP can be disposed on the gate insulating layer **120**. The gate insulating layer **120** can include an insulating material. For example, the gate insulating layer **120** can include an inorganic insulating material, such as silicon oxide (SiOx) and silicon nitride (SiNx).

[0067] The device passivation layer **130** can be disposed on the gate insulating layer **120**. The device passivation layer **130** can prevent the damage of the driving circuit R-DC, G-DC, W-DC and B-DC in each sub-pixel R-SP, G-SP, W-SP and B-SP due to the external impact and moisture. For example, the first gate electrode, the second gate electrode **223** and the third gate electrode of each sub-pixel R-SP, G-SP, W-SP and B-SP can be covered by the device passivation layer **130**. The device passivation layer **130** can include an insulating material. For example, the device passivation layer **130** can be a linear insulating layer made of inorganic insulating material.

[0068] The planarization layer **140** can be disposed on the device passivation layer **130**. The planarization layer **140** can remove a thickness difference due to the driving circuit R-DC, G-DC, W-DC and B-DC of each sub-pixel R-SP, G-SP, W-SP and B-SP. For example, an upper surface of the planarization layer **140** opposite to the device substrate **100** can be flat. The upper surface of the planarization layer **140** can be parallel to the upper surface of the device substrate **100**. The planarization layer **140** can include an insulating material. The planarization layer **140** can include a different material from the device passivation layer **130**. The planarization layer **140** can include a material having a relatively high fluidity. For example, the planarization layer **140** can include an organic insulating material.

[0069] The bank insulating layer **150** can be disposed on the planarization layer **140**. The bank insulating layer **150** can include an insulating material. For example, the bank insulating layer **150** can be an organic insulating material. The bank insulating layer **150** can include a different material from the planarization layer **140**.

[0070] The light-emitting device **300R**, **300G**, **300W** and **300B** of each sub-pixel R-SP, G-SP, W-SP and B-SP can be disposed on the planarization layer **140**. The first electrode **310** of each sub-pixel R-SP, G-SP, W-SP and B-SP can be insulated from the first electrode **310** of adjacent sub-pixel R-SP, G-SP, W-SP and B-SP by the bank insulating layer **150**. For example, an edge of the first electrode **310** in each sub-pixel R-SP, G-SP, W-SP and B-SP can be covered by the bank insulating layer **150**. The first electrode **310** of each sub-pixel R-SP, G-SP, W-SP and B-SP can be partially exposed by the bank insulating layer **150**. For example, the bank insulating layer **150** can define an emission area R-EA, G-EA, W-EA and B-EA in each sub-pixel R-SP, G-SP, W-SP and B-SP. The light-emitting layer **320** and the second electrode **330** of each sub-pixel R-SP, G-SP, W-SP and B-SP can be stacked on a portion of the first electrode **310** overlapping with the emission area

R-EA, G-EA, W-EA and B-EA of the corresponding sub-pixel R-SP, G-SP, W-SP and B-SP. For example, the light-emitting layer **320** can be in direct contact with the first electrode **310** and the second electrode **330** in the emission area R-EA, G-EA, W-EA and B-EA of each sub-pixel R-SP, G-SP, W-SP and B-SP.

[0071] The first electrode **310** of each sub-pixel R-SP, G-SP, W-SP and B-SP can be electrically connected to the driving circuit R-DC, G-DC, W-DC and B-DC of the corresponding sub-pixel R-SP, G-SP, W-SP and B-SP. For example, the first electrode **310** of each sub-pixel R-SP, G-SP, W-SP and B-SP can be in direct contact with the source connection electrode of the corresponding sub-pixel R-SP, G-SP, W-SP and B-SP by penetrating the device passivation layer **130** and the planarization layer **140**. The device passivation layer **130** and the planarization layer **140** can include pixel contact holes exposing a portion of the source connection electrode **240** in each sub-pixel R-SP, G-SP, W-SP and B-SP. The first electrode **310** of each sub-pixel R-SP, G-SP, W-SP and B-SP can be electrically connected to the source connection electrode **240** of the corresponding sub-pixel R-SP, G-SP, W-SP and B-SP through one of the pixel contact holes. The pixel contact holes can be disposed outside the emission area R-EA, G-EA, W-EA and B-EA defined in each sub-pixel R-SP, G-SP, W-SP and B-SP. For example, the pixel contact holes can overlap the bank insulating layer **150**. Thus, in the display apparatus according to the embodiment of the present disclosure, the change in the location of the first electrode **310** within the emission area R-EA, G-EA, W-EA and B-EA of each sub-pixel R-SP, G-SP, W-SP and B-SP can be minimized. For example, a portion of the first electrode **310** overlapping with the emission area R-EA, G-EA, W-EA and B-EA of each sub-pixel R-SP, G-SP, W-SP and B-SP can be in direct contact with the upper surface of the planarization layer **140**. Therefore, in the display apparatus according to the embodiment of the present disclosure, the luminance deviation according to the generating location of the light emitted from the emission area R-EA, G-EA, W-EA and B-EA of each sub-pixel R-SP, G-SP, W-SP and B-SP can be prevented.

[0072] The light emitted from the light-emitting device **300R**, **300G**, **300W** and **300B** of each sub-pixel R-SP, G-SP, W-SP and B-SP can display a different color from the light emitted from the light-emitting device **300R**, **300G**, **300W** and **300B** of adjacent sub-pixel R-SP, G-SP, W-SP and B-SP. The light-emitting layer **320** of the light-emitting device **300R**, **300G**, **300W** and **300B** in each sub-pixel R-SP, G-SP, W-SP and B-SP can be spaced apart from the light-emitting layer **320** of the light-emitting device **300R**, **300G**, **300W** and **300B** in adjacent sub-pixel R-SP, G-SP, W-SP and B-SP. For example, the light-emitting layer **320** of the light-emitting device **300R**, **300G**, **300W** and **300B** in each sub-pixel R-SP, G-SP, W-SP and B-SP can include different materials. The light-emitting layer **320** of the light-emitting device **300R**, **300G**, **300W** and **300B** in each sub-pixel R-SP, G-SP, W-SP and B-SP can have a stacked structure different from the light-emitting layer **320** of the light-emitting device **300R**, **300G**, **300W** and **300B** in adjacent sub-pixel R-SP, G-SP, W-SP and B-SP. The light-emitting layer **320** of the light-emitting device **300R**, **300G**, **300W** and **300B** in each sub-pixel R-SP, G-SP, W-SP and B-SP can include an end disposed on the bank insulating layer **150**.

[0073] A voltage applied to the second electrode **330** of each sub-pixel R-SP, G-SP, W-SP and B-SP can be a same as a voltage applied to the second electrode **330** of adjacent sub-pixel R-SP, G-SP, W-SP and B-SP. For example, the second electrode **330** of each sub-pixel R-SP, G-SP, W-SP and B-SP can be electrically connected to the second electrode **330** of adjacent sub-pixel R-SP, G-SP, W-SP and B-SP. The second electrode **330** of each sub-pixel R-SP, G-SP, W-SP and B-SP can include a same material as the second electrode **330** of adjacent sub-pixel R-SP, G-SP, W-SP and B-SP. The second electrode **330** of each sub-pixel R-SP, G-SP, W-SP and B-SP can be formed by a same process as the second electrode of adjacent sub-pixel R-SP, G-SP, W-SP and B-SP. For example, the second electrode **330** of each sub-pixel R-SP, G-SP, W-SP and B-SP can be formed simultaneously with the second electrode **330** of adjacent sub-pixel R-SP, G-SP, W-SP and B-SP. The second electrode **330** of each sub-pixel R-SP, G-SP, W-SP and B-SP can be in direct contact with the

second electrode **330** of adjacent sub-pixel R-SP, G-SP, W-SP and B-SP. Thus, in the display apparatus according to the embodiment of the present disclosure, a process of forming the second electrode **330** in each sub-pixel R-SP, G-SP, W-SP and B-SP can be simplified.

[0074] A color filter **400** can be disposed on a path of the light emitted from the light-emitting device **300R**, **300G**, **300W** and **300B** in each sub-pixel R-SP, G-SP, W-SP and B-SP. For example, the color filter **400** of each sub-pixel R-SP, G-SP, W-SP and B-SP can be disposed between the device passivation layer **130** and the planarization layer **140**. A thickness difference due to the color filter **400** of each sub-pixel R-SP, G-SP, W-SP and B-SP can be removed by the planarization layer **140**. The light passing through the color filter **400** of each sub-pixel R-SP, G-SP, W-SP and B-SP can display a same color as the light generated by the light-emitting device **300R**, **300G**, **300W** and **300B** of the corresponding sub-pixel R-SP, G-SP, W-SP and B-SP. Thus, in the display apparatus according to the embodiment of the present disclosure, the color reproduction of the light emitted from each sub-pixel R-SP, G-SP, W-SP and B-SP can be improved.

[0075] A capping layer **160** can be disposed on the light-emitting device **300R**, **300G**, **300W** and **300B** of each sub-pixel R-SP, G-SP, W-SP and B-SP. The capping layer **160** can prevent the damage of the light-emitting device **300R**, **300G**, **300W** and **300B** in each sub-pixel R-SP, G-SP, W-SP and B-SP. For example, the light-emitting device **300R**, **300G**, **300W** and **300B** of each sub-pixel R-SP, G-SP, W-SP and B-SP can be covered by the capping layer **160**. The capping layer **160** can include an insulating material. For example, the capping layer **160** can include an inorganic insulating material and/or an organic insulating material. The capping layer **160** can have a multi-layer structure. For example, the capping layer **160** can have a structure in which an inorganic insulating layer made of an inorganic insulating material and an organic insulating layer made of an organic insulating material are stacked. Thus, in the display apparatus according to the embodiment of the present disclosure, the damage of the light-emitting device **300R**, **300G**, **300W** and **300B** in each sub-pixel R-SP, G-SP, W-SP and B-SP can be effectively prevented by the capping layer **160**.

[0076] An encapsulating layer **500** and an encapsulation substrate **600** can be stacked on the capping layer **160**. The encapsulation substrate **600** can include a different material from the device substrate **100**. The encapsulation substrate **600** can include a material having relatively high heat dissipation characteristics. For example, the encapsulation substrate **600** can include a metal, such as aluminum (Al) and nickel (Ni).

[0077] The encapsulating layer **500** can include an insulating material. The encapsulating layer **500** can include an adhesive material. For example, the encapsulation substrate **600** can be coupled to the device substrate **100** in which the capping layer **160** is disposed by the encapsulating layer **500**. The encapsulating layer **500** can block or delay the movement of the external moisture. For example, the encapsulating layer **500** can include absorbing particles. The encapsulating layer **500** can have a multi-layer structure. For example, the encapsulating layer **500** can include a lower encapsulating layer **510** and an upper encapsulating layer **520** disposed on the lower encapsulating layer **510**. The lower encapsulating layer **510** can be disposed between the capping layer **160** and the upper encapsulating layer **520**. The absorbing particles can be dispersed in the upper encapsulating layer **520**. Thus, in the display apparatus according to the embodiment of the present disclosure, the stress applied in a direction of the device substrate **100** due to the expansion of the absorbing particles can be alleviated by the lower encapsulating layer **510**. The upper encapsulating layer **520** can include a different material from the lower encapsulating layer **510**. Therefore, in the display apparatus according to the embodiment of the present disclosure, the damage of the light-emitting device **300R**, **300G**, **300W** and **300B** in each sub-pixel R-SP, G-SP, W-SP and B-SP due to the penetrating of the external moisture and the external impact can be effectively prevented.

[0078] The sub-pixels R-SP, G-SP, W-SP and B-SP of each pixel area PA can be disposed side by side in a direction. For example, the red sub-pixel R-SP, the green sub-pixel G-SP, the white sub-pixel W-SP and the blue sub-pixel B-SP of each pixel area PA can be disposed side by side in the first direction X. The light-emitting device **300R**, **300G**, **300W** and **300B** of each sub-pixel R-SP,

G-SP, W-SP and B-SP can be controlled independently. For example, the gate lines GL1 and GL2 can include first gate lines GL1 extending in the first direction X and second gate lines GL2 extending parallel to the first gate lines GL1. The second gate lines GL2 can be disposed between the first gate lines GL1. For example, the emission area R-EA, G-EA, W-EA and B-EA of each sub-pixel R-SP, G-SP, W-SP and B-SP can be disposed between one of the first gate lines GL1 and one of the second gate lines GL2. The data lines DL1 and DL2 can include first data lines DL1 extending in the second direction Y and second data lines DL2 extending parallel to the first data lines DL1. One of the first data lines DL1 and one of the second data lines DL2 can be disposed between the pixel areas PA. The power voltage supply lines PL and the reference voltage supply lines RL can extend in the second direction Y. For example, each of the data lines DL1 and DL2, the power voltage supply lines PL and the reference voltage supply lines RL can cross the first gate lines GL1 and the second gate lines GL2.

[0079] Each of the sub-pixels R-SP, G-SP, W-SP and B-SP in each pixel area PA can share the data lines DL1 and DL2 with one of the sub-pixels R-SP, G-SP, W-SP and B-SP in adjacent pixel area PA. For example, one of the first data lines DL1 and one of the second data lines DL2 can cross between the pixel areas PA, a red driving circuit R-DC of the red sub-pixel R-SP in each pixel area PA can be electrically connected to the first data line DL1 disposed on a side of the corresponding pixel area PA, and a green driving circuit G-DC of the green sub-pixel G-SP in each pixel area PA can be electrically connected to the first data line DL1 disposed on an opposite side of the corresponding pixel area PA. A white driving circuit W-DC of the white sub-pixel W-SP in each pixel area PA can be electrically connected to the second data line DL2 disposed on a side of the corresponding pixel area PA, and a blue driving circuit B-DC of the blue sub-pixel B-SP in each pixel area PA can be electrically connected to the second data line DL2 disposed on an opposite side of the corresponding pixel area PA. That is, in the display apparatus according to the embodiment of the present disclosure, the red sub-pixel R-SP of each pixel area PA can share one of the first data lines DL1 with the green sub-pixel G-SP of adjacent pixel area PA, and the white sub-pixel W-SP of each pixel area PA can share one of the second data lines DL2 with the blue sub-pixel B-SP of adjacent pixel area PA. Thus, in the display apparatus according to the embodiment of the present disclosure, the number of the data lines DL1 and DL2 can be reduced. Therefore, in the display apparatus according to the embodiment of the present disclosure, an area of each sub-pixel R-SP, G-SP, W-SP and B-SP can be increased. For example, in the display apparatus according to the embodiment of the present disclosure, a size of the emission area R-EA, G-EA, W-EA and B-EA defined in each sub-pixel R-SP, G-SP, W-SP and B-SP can be increased.

[0080] Each of the sub-pixels R-SP, G-SP, W-SP and B-SP can be electrically connected to the gate line GL1 and GL2 different than that to which a sub-pixel of the sub-pixels R-SP, G-SP, W-SP and B-SP sharing the data line DL1 and DL2 with the corresponding sub-pixel R-SP, G-SP, W-SP and B-SP is electrically connected. For example, the red sub-pixel R-SP and the white sub-pixel W-SP of each pixel area PA can be electrically connected to one of the first gate lines GL1, and the green sub-pixel G-SP and the blue sub-pixel B-SP of each pixel area PA can be electrically connected to the one of the second gate lines GL2. Thus, in the display apparatus according to the embodiment of the present disclosure, the data signal can be applied simultaneously to the sub-pixels R-SP, G-SP, W-SP and B-SP of each pixel area PA through the data lines DL1 and DL2. That is, in the display apparatus according to the embodiment of the present disclosure, the sub-pixels R-SP, G-SP, W-SP and B-SP of each pixel area PA can operate simultaneously. Therefore, in the display apparatus according to the embodiment of the present disclosure, the decrease in the driving speed due to the operation delay of each pixel area PA can be prevented.

[0081] The driving circuit R-DC, G-DC, W-DC and B-DC and the emission area R-EA, G-EA, W-EA and B-EA of each sub-pixel R-SP, G-SP, W-SP and B-SP can be disposed side by side in the second direction Y. The driving circuit R-DC, G-DC, W-DC and B-DC of each sub-pixel R-SP, G-SP, W-SP and B-SP can be disposed close to the corresponding gate line GL1 and GL2. For

example, the red driving circuit R-DC and the white driving circuit W-DC of each pixel area PA can be disposed close to the corresponding first gate line GL1, and the green driving circuit G-DC and the blue driving circuit B-DC of each pixel area PA can be disposed close to the corresponding second gate line GL2. A red emission area R-EA defined in the red sub-pixel R-SP of each pixel area PA can be disposed between the red driving circuit R-DC of the corresponding pixel area PA and the corresponding second gate line GL2, and a white emission area W-EA defined in the white sub-pixel W-SP of each pixel area PA can be disposed between the white driving circuit W-DC of the corresponding pixel area PA and the corresponding second gate line GL2. A green emission area G-EA defined in the green sub-pixel G-SP of each pixel area PA can be disposed between the corresponding first gate line GL1 and the green driving circuit G-DC of the corresponding pixel area PA, and a blue emission area B-EA defined in the blue sub-pixel B-SP of each pixel area PA can be disposed between the corresponding first gate line GL1 and the blue driving circuit B-DC of the corresponding pixel area PA.

[0082] The sub-pixels R-SP, G-SP, W-SP and B-SP electrically connected to the first gate lines GL1 and the sub-pixels R-SP, G-SP, W-SP and B-SP electrically connected to the second gate lines GL2 can be alternately arranged in each pixel area PA. For example, the green sub-pixel G-SP of each pixel area PA can be disposed between the red sub-pixel R-SP and the white sub-pixel W-SP of the corresponding pixel area PA, and the white sub-pixel W-SP of each pixel area PA can be disposed between the green sub-pixel G-SP and the blue sub-pixel B-SP of the corresponding pixel area PA. Thus, in the display apparatus according to the embodiment of the present disclosure, a space for the driving circuit R-DC, G-DC, W-DC and B-DC of each sub-pixel R-SP, G-SP, W-SP and B-SP can be sufficiently secured. Therefore, in the display apparatus according to the embodiment of the present disclosure, the decrease in the area of the emission areas R-EA, G-EA, W-EA and B-EA defined in each pixel area PA due to the driving circuits R-DC, G-DC, W-DC and B-DC of the corresponding pixel area PA can be minimized.

[0083] The driving circuits R-DC, G-DC, W-DC and B-DC of each pixel area PA can be arranged to be symmetrical to each other. For example, the green driving circuit G-DC of each pixel area PA can be arranged to be symmetrical to the red driving circuit R-DC of the corresponding pixel area PA with respect to the first direction X, and the white driving circuit W-DC of each pixel area PA can be arranged to be symmetrical to the blue driving circuit B-DC of the corresponding pixel area PA with respect to the first direction X. Thus, in the display apparatus according to the embodiment of the present disclosure, the coupling capacitance of the green sub-pixel G-SP in each pixel area PA can be substantially the same as the coupling capacitance of the red sub-pixel R-SP in the corresponding pixel area PA, and the coupling capacitance of the blue sub-pixel B-SP in each pixel area PA can be substantially the same as the coupling capacitance of the white sub-pixel W-SP in the corresponding pixel area PA. The white driving circuit W-DC of each pixel area PA can be arranged to be symmetrical to the red driving circuit R-DC of the corresponding pixel area PA with respect to the second direction Y, and the blue driving circuit B-DC of each pixel area PA can be arranged to be symmetrical to the green driving circuit G-DC of the corresponding pixel area PA with respect to the second direction Y. That is, in the display apparatus according to the embodiment of the present disclosure, the coupling capacitance of the white sub-pixel W-SP in each pixel area PA can be substantially the same as the coupling capacitance of the red sub-pixel R-SP in the corresponding pixel area PA, and the coupling capacitance of the blue sub-pixel B-SP in each pixel area PA can be substantially the same as the coupling capacitance of the green sub-pixel G-SP in the corresponding pixel area PA. Therefore, in the display apparatus according to the embodiment of the present disclosure, the deviation in the luminance of the light emitted from each sub-pixel R-SP, G-SP, W-SP and B-SP due to the difference in the coupling capacitance can be prevented.

[0084] The second thin film transistor TR2 of each sub-pixel R-SP, G-SP, W-SP and B-SP can be disposed far from the emission area R-EA, G-EA, W-EA and B-EA of the corresponding sub-pixel

R-SP, G-SP, W-SP and B-SP. For example, the first gate lines GL1 and the second gate lines GL2 can be disposed between the emission area R-EA, G-EA, W-EA and B-EA and the second thin film transistor TR2 of each sub-pixel R-SP, G-SP, W-SP and B-SP. Thus, in the display apparatus according to the embodiment of the present disclosure, the coupling capacitance of each sub-pixel R-SP, G-SP, W-SP and B-SP can be minimized.

[0085] The first semiconductor pattern of each sub-pixel R-SP, G-SP, W-SP and B-SP can have a shape extending in the second direction Y. For example, the first semiconductor pattern of each sub-pixel R-SP, G-SP, W-SP and B-SP can cross one of the first gate lines GL1 and the second gate lines GL2. The first gate lines GL1 and the second gate lines GL2 can be disposed on a same layer as the first gate electrode of each sub-pixel R-SP, G-SP, W-SP and B-SP. For example, the first gate lines GL1 and the second gate lines GL2 can be disposed between the gate insulating layer 120 and the device passivation layer 130. The first gate lines GL1 and the second gate lines GL2 can include a same material as the first gate electrode of each sub-pixel R-SP, G-SP, W-SP and B-SP. The first gate lines GL1 and the second gate lines GL2 can be formed by a same process as the first gate electrode of each sub-pixel R-SP, G-SP, W-SP and B-SP. For example, the first gate lines GL1 and the second gate lines GL2 can be formed simultaneously with the first gate electrode of each sub-pixel R-SP, G-SP, W-SP and B-SP. The first gate electrode of each sub-pixel R-SP, G-SP, W-SP and B-SP can be in direct contact with one of the first gate lines GL1 and the second gate lines GL2. For example, the first gate electrode of each sub-pixel R-SP, G-SP, W-SP and B-SP can be a portion of the corresponding gate line GL1 and GL2. Thus, in the display apparatus according to the embodiment of the present disclosure, a process of forming the first gate electrode in each sub-pixel R-SP, G-SP, W-SP and B-SP can be simplified.

[0086] The second gate electrode 223 of each sub-pixel R-SP, G-SP, W-SP and B-SP can be disposed parallel to the first gate lines GL1 and the second gate lines GL2. The second semiconductor pattern 221 of each sub-pixel R-SP, G-SP, W-SP and B-SP can have a shape extending in the second direction Y. For example, the second semiconductor pattern 221 of each sub-pixel R-SP, G-SP, W-SP and B-SP can be disposed parallel to the data lines DL1 and DL2. Power connection lines 250 extending in the first direction X can be electrically connected to at least one of the power voltage supply lines PL and the second semiconductor pattern 221 of each sub-pixel R-SP, G-SP, W-SP and B-SP can be electrically connected to one of the power connection lines 250. Thus, in the display apparatus according to the embodiment of the present disclosure, the configuration of the driving circuit R-DC, G-DC, W-DC and B-DC in each sub-pixel R-SP, G-SP, W-SP and B-SP can be simplified. That is, in the display apparatus according to the embodiment of the present disclosure, an area occupied by the driving circuit R-DC, G-DC, W-DC and B-DC of each sub-pixel R-SP, G-SP, W-SP and B-SP can be minimized. Therefore, in the display apparatus according to the embodiment of the present disclosure, a size of each sub-pixel R-SP, G-SP, W-SP and B-SP can be reduced. And, in the display apparatus according to the embodiment of the present disclosure, an area of the emission area R-EA, G-EA, W-EA and B-EA defined in each sub-pixel R-SP, G-SP, W-SP and B-SP can be maximized.

[0087] The power connection lines 250 can be disposed on a different layer from the power voltage supply lines PL. The power connection lines 250 can be disposed on a same layer as the source connection electrode 240 of each sub-pixel R-SP, G-SP, W-SP and B-SP. For example, the power connection lines 250 can be disposed between the gate insulating layer 120 and the device passivation layer 130. The power connection lines 250 can include a same material as the source connection electrode 240 of each sub-pixel R-SP, G-SP, W-SP and B-SP. The power connection lines 250 can be formed by a same process as the source connection electrode 240 of each sub-pixel R-SP, G-SP, W-SP and B-SP. For example, the power connection lines 250 can be formed simultaneously with the source connection electrode 240 of each sub-pixel R-SP, G-SP, W-SP and B-SP. Thus, in the display apparatus according to the embodiment of the present disclosure, the decrease in the process efficiency due to the formation of the power connection lines 250 can be

prevented.

[0088] The power voltage supply lines PL can be disposed closer to the device substrate **100** than the power connection lines **250**. For example, the power voltage supply lines PL can be disposed on a same layer as the light-blocking pattern **105** of each sub-pixel R-SP, G-SP, W-SP and B-SP. The power voltage supply lines PL can include a same material as the light-blocking pattern **105** of each sub-pixel R-SP, G-SP, W-SP and B-SP. The power voltage supply lines PL can be formed by a same process as the light-blocking pattern **105** of each sub-pixel R-SP, G-SP, W-SP and B-SP. For example, the power voltage supply lines PL can be formed simultaneously with the light-blocking pattern **105** of each sub-pixel R-SP, G-SP, W-SP and B-SP. Thus, in the display apparatus according to the embodiment of the present disclosure, a process of forming the power voltage supply lines PL can be simplified.

[0089] The data lines DL1 and DL2 can be disposed on a same layer as the power voltage supply lines PL. For example, the data lines DL1 and DL2 can be disposed between the device substrate **100** and the buffer insulating layer **110**. The data lines DL1 and DL2 can include a same material as the power voltage supply lines PL. The data lines DL1 and DL2 can be formed by a same process as the power voltage supply lines PL. For example, the data lines DL1 and DL2 can be formed simultaneously with the power voltage supply lines PL. Thus, in the display apparatus according to the embodiment of the present disclosure, a process of forming the data lines DL1 and DL2 can be simplified.

[0090] The third thin film transistor TR3 of each sub-pixel R-SP, G-SP, W-SP and B-SP can be spaced apart from the first thin film transistor TR1 and the second thin film transistor TR2 of the corresponding sub-pixel R-SP, G-SP, W-SP and B-SP. The third semiconductor pattern of each sub-pixel R-SP, G-SP, W-SP and B-SP can have a shape extending in a direction different from the first semiconductor pattern and the second semiconductor pattern **221** of the corresponding sub-pixel R-SP, G-SP, W-SP and B-SP. For example, the third semiconductor pattern of each sub-pixel R-SP, G-SP, W-SP and B-SP can have a shape extending in the first direction X. The third semiconductor pattern of each sub-pixel R-SP, G-SP, W-SP and B-SP can be disposed parallel to the first gate lines GL1 and the second gate lines GL2. The third gate electrode of each sub-pixel R-SP, G-SP, W-SP and B-SP can extend in the second direction Y. The third gate electrode of each sub-pixel R-SP, G-SP, W-SP and B-SP can extend in a direction perpendicular to the first gate lines GL1 and the second gate lines GL2. For example, the third gate electrode of each sub-pixel R-SP, G-SP, W-SP and B-SP can have a shape protruding from one of the first gate lines GL1 and the second gate lines GL2. Thus, in the display apparatus according to the embodiment of the present disclosure, a width of each first gate line GL1 and a width of each second gate line GL2 can be increased. For example, in the display apparatus according to the embodiment of the present disclosure, a resistance of each first gate line GL1 and a resistance of each second gate lines GL2 can be reduced. Therefore, in the display apparatus according to the embodiment of the present disclosure, the delay of the signal applied through the first gate lines GL1 and the second gate lines GL2 can be prevented.

[0091] The reference voltage supply lines RL can be disposed parallel to the power voltage supply lines PL. For example, the reference voltage supply lines RL can extend in the second direction Y. each of the reference voltage supply lines RL can cross one of the pixel areas PA. For example, the red sub-pixel R-SP and the green sub-pixel G-SP of each pixel area PA can be disposed between one of the second data lines DL2 and one of the reference voltage supply lines RL, and the white sub-pixel W-SP and the blue sub-pixel B-SP of each pixel area PA can be disposed between one of the reference voltage supply lines RL and one of the first data lines DL1. Thus, in the display apparatus according to the embodiment of the present disclosure, a process of connecting the third drain region of the third thin film transistor TR3 in each sub-pixel R-SP, G-SP, W-SP and B-SP to the corresponding reference voltage supply line RL can be simplified.

[0092] The reference voltage supply lines RL can be disposed on a same layer as the power voltage

supply lines PL. For example, the reference voltage supply lines RL can be disposed between the device substrate **100** and the buffer insulating layer **110**. The reference voltage supply lines RL can include a same material as the power voltage supply lines PL. The reference voltage supply lines RL can be formed by a same process as the power voltage supply lines PL. For example, the reference voltage supply lines RL can be formed simultaneously with the power voltage supply lines PL. Thus, in the display apparatus according to the embodiment of the present disclosure, a process of forming the reference voltage supply lines RL can be simplified.

[0093] Each of the reference voltage supply lines RL can include a main wiring R1, an auxiliary wiring R2 and a connection wiring Rc. The auxiliary wiring R2 can extend parallel to the main wiring R1. For example, the auxiliary wiring R2 can extend in the second direction Y. The auxiliary wiring R2 can be spaced apart from the main wiring R1 in the first direction X. The auxiliary wiring R2 can be disposed on a same layer as the main wiring R1. The auxiliary wiring R2 can include a same material as the main wiring R1. The auxiliary wiring R2 can be formed by a same process as the main wiring R1. For example, the auxiliary wiring R2 can be formed simultaneously with the main wiring R1.

[0094] The connection wiring Rc can be disposed between the main wiring R1 and the auxiliary wiring R2. The auxiliary wiring can be electrically connected to the main wiring R1 through the connection wiring Rc. For example, the connection wiring Rc can be in direct contact with a portion of the main wiring R1 and a portion of the auxiliary wiring R2. The connection wiring Rc can be disposed on a same layer as the main wiring R1 and the auxiliary wiring R2. The connection wiring Rc can include a same material as the main wiring R1 and the auxiliary wiring R2. The connection wiring Rc can be formed by a same process as the main wiring R1 and the auxiliary wiring R2. For example, the connection wiring Rc can be formed simultaneously with the main wiring R1 and the auxiliary wiring R2.

[0095] The third drain region of each sub-pixel R-SP, G-SP, W-SP and B-SP can be electrically connected to the main wiring R1 of the corresponding reference voltage supply line RL. The third drain region of each sub-pixel R-SP, G-SP, W-SP and B-SP can be insulated from the auxiliary wiring R2 of the corresponding reference voltage supply line RL. Thus, in the display apparatus according to the embodiment of the present disclosure, when the connection wiring Rc of each reference voltage supply line RL disposed on some of the pixel areas PA can be removed, a portion of the auxiliary wiring R2 of each reference voltage supply line RL can be separated from another portion of the auxiliary wiring R2 of the corresponding reference voltage supply line RL, such that a portion of the auxiliary wiring R2 overlapping with the corresponding pixel area PA can be a wiring in a floating state where not signal is applied.

[0096] The auxiliary wiring R2 of each reference voltage supply line RL can have a smaller width than the main wiring R1 of the corresponding reference voltage supply line RL. Thus, in the display apparatus according to the embodiment of the present disclosure, even when a portion of the auxiliary wiring R2 of each reference voltage supply line RL is separated, the change in the resistance of the corresponding reference voltage supply line RL can be minimized.

[0097] The first electrode **310** of each sub-pixel R-SP, G-SP, W-SP and B-SP can include a portion overlapping with the auxiliary R2 of the corresponding reference voltage supply line RL. Thus, in the display apparatus according to the embodiment of the present disclosure, the first electrode **310** of each sub-pixel R-SP, G-SP, W-SP and B-SP can be connected selectively to the auxiliary wiring R2 of the corresponding reference voltage supply line RL. For example, in the display apparatus according to the embodiment of the present disclosure, the first electrode **310** disposed on one of the sub-pixels R-SP, G-SP, W-SP and B-SP in each pixel area PA can be electrically connected to the auxiliary wiring R2 of the reference voltage supply line RL crossing the corresponding pixel area PA. That is, in the display apparatus according to the embodiment of the present disclosure, a portion of the auxiliary wiring R2 of each reference voltage supply line RL can be used as a repair wiring.

[0098] FIG. 9 is a view showing a plane view of some sub-pixel by a repair process in the display apparatus according to the embodiment of the present disclosure.

[0099] Referring to FIGS. 3 to 9, in the display apparatus according to the embodiment of the present disclosure, the repair process can include a process of electrically connecting the first electrode 310 of the red sub-pixel R-SP in each pixel area PA and a portion WA1 of the first electrode 310 of the red sub-pixel R-SP in the pixel area PA adjacent to the corresponding pixel area PA in the second direction Y to the auxiliary wiring R2 of the reference voltage supply line RL, a process of separating portions CT1 of the auxiliary wiring R2 electrically connected to the first electrodes 310 of the red sub-pixels R-SP adjacent in the second direction Y from another portion of the corresponding auxiliary wiring R2, and a process of removing a portion CT2 of the connection wiring Rc connected to the separated auxiliary wiring R2. Thus, in the display apparatus according to the embodiment of the present disclosure, the first electrodes 310 of two red sub-pixels R-SP adjacent in the second direction Y can be electrically connected to each other by the separated auxiliary wiring R2. For example, in the display apparatus according to the embodiment of the present disclosure, the red driving circuit R-DC of the red sub-pixel R-SP in which the red light-emitting device 300R is damaged can be electrically connected to the light-emitting device 300R of the red sub-pixel R-SP adjacent in the second direction Y by the repair process. Therefore, in the display apparatus according to the embodiment of the present disclosure, the repair process can be simplified.

[0100] Accordingly, the display apparatus according to the embodiment of the present disclosure can include the pixel areas PA disposed between the gate lines GL1 and GL2, the data lines DL1 and DL2, the power voltage supply lines PL, and the reference voltage supply lines RL, wherein each of the pixel areas PA can include the sub-pixels R-SP, G-SP, W-SP and B-SP disposed side by side in the first direction X, wherein each of the reference voltage supply lines RL extending in the second direction Y can include the main wiring R1 electrically connected to the driving circuit R-DC, G-DC, W-DC and B-DC of each sub-pixel R-SP, G-SP, W-SP and B-SP and the auxiliary wiring R2 connected to the main wiring R1 by the connection wiring Rc, and wherein the first electrode 310 of each sub-pixel R-SP, G-SP, W-SP and B-SP can include a portion overlapping with the auxiliary wiring R2 of one of the reference voltage supply lines RL. Thus, in the display apparatus according to the embodiment of the present disclosure, the auxiliary wiring R2 of each reference voltage supply line RL can be used as a repair wiring in the repair process. Therefore, in the display apparatus according to the embodiment of the present disclosure, the repair process can be simplified.

[0101] And, in the display apparatus according to the embodiment of the present disclosure, a portion of the reference voltage supply lines RL can be used as the repair wiring. Thus, in the display apparatus according to the embodiment of the present disclosure, the decrease in the process efficiency due to a process of forming the repair wiring can be prevented. Therefore, in the display apparatus according to the embodiment of the present disclosure, the production energy can be reduced by process optimization.

[0102] The display apparatus according to the embodiment of the present disclosure is described that the driving circuit R-DC, G-DC, W-DC and B-DC of each sub-pixel R-SP, G-SP, W-SP and B-SP can include the first thin film transistor TR1, the second thin film transistor TR2, the third thin film transistor TR3 and the storage capacitor Cst. However, in the display apparatus according to another embodiment of the present disclosure, the driving circuit R-DC, G-DC, W-DC and B-DC of each sub-pixel R-SP, G-SP, W-SP and B-SP can include a driving thin film transistor and at least one switching thin film transistor. For example, in the display apparatus according to another embodiment of the present disclosure, the driving circuit R-DC, G-DC, W-DC and B-DC of each sub-pixel R-SP, G-SP, W-SP and B-SP can include only the first thin film transistor TR1 functioning as a switching thin film transistor, the second thin film transistor TR2 functioning as a driving thin film transistor, and the storage capacitor Cst. Thus, in the display apparatus according

to another embodiment of the present disclosure, the degree of freedom in configuring the driving circuit R-DC, G-DC, W-DC and B-DC in each sub-pixel R-SP, G-SP, W-SP and B-SP can be improved.

[0103] In the display apparatus according to the embodiment of the present disclosure, the location and the electric connection of the first drain region, the first source region, the second drain region **221d**, the second source region **221s**, the third drain region and the third source region in each driving circuit R-DC, G-DC, W-DC and B-DC can vary depending on the configuration of the corresponding driving circuit R-DC, G-DC, W-DC and B-DC and/or the type of the corresponding thin film transistors **TR1**, **TR2** and **TR3**. For example, in the display apparatus according to another embodiment of the present disclosure, the second gate electrode **223** of each driving circuit R-DC, G-DC, W-DC and B-DC can be electrically connected to the first drain region of the corresponding driving circuit R-DC, G-DC, W-DC and B-DC. Thus, in the display apparatus according to another embodiment of the present disclosure, the degree of freedom in the configuration of each driving circuit R-DC, G-DC, W-DC and B-DC and the type of each thin film transistor **TR1**, **TR2** and **TR3** can be improved.

[0104] The display apparatus according to the embodiment of the present disclosure is described that the first drain region, the first source region, the second drain region **221d**, the second source region **221s**, the third drain region and the third source region of each pixel area PA can be used as wiring. However, in the display apparatus according to another embodiment of the present disclosure, the first thin film transistor **TR1**, the second thin film transistor **TR2** and the third thin film transistor **TR3** of each sub-pixel R-SP, G-SP, W-SP and B-SP can have various structures. For example, in the display apparatus according to the embodiment of the present disclosure, the driving circuit R-DC, G-DC, W-DC and B-DC of each sub-pixel R-SP, G-SP, W-SP and B-SP can include a second drain electrode electrically connected to the second drain region **221d** and a second source electrode electrically connected to the second source region **221s**. The second drain electrode and the second source electrode of each sub-pixel R-SP, G-SP, W-SP and B-SP can be disposed on a different layer from the second gate electrode **223** of the corresponding sub-pixel R-SP, G-SP, W-SP and B-SP. For example, the second drain electrode and the second source electrode of each sub-pixel R-SP, G-SP, W-SP and B-SP can be disposed between an interlayer insulating layer covering the second gate electrode **223** of the corresponding sub-pixel R-SP, G-SP, W-SP and B-SP and the device passivation layer **130**. Thus, in the display apparatus according to another embodiment of the present disclosure, the degree of freedom for the configuration of the driving circuit R-DC, G-DC, W-DC and B-DC in each sub-pixel R-SP, G-SP, W-SP and B-SP can be improved.

[0105] The display apparatus according to the embodiment of the present disclosure is described that the repair process can use the auxiliary wiring **R2** of each reference voltage supply line **RL**. However, in the display apparatus according to another embodiment of the present disclosure, one of the signal wirings **DL1**, **DL2**, **RL** and **PL** extending in the second direction Y can be used as a repair wiring. For example, in the display apparatus according to another embodiment of the present disclosure, some of the power voltage supply lines **PL** can include a main wiring **P1**, an auxiliary wiring **P2** and a connection wiring **Pc**, as shown in FIG. **10**. The auxiliary wiring **P2** of some of the power voltage supply lines **PL** can be disposed between the main wiring **P1** of the corresponding power voltage supply line **PL** and one of the second data lines **DL2**. The first electrode **310** of each sub-pixel R-SP, G-SP, W-SP and B-SP can include a portion of the auxiliary wiring **P2** of one of the power voltage supply lines **PL**. Thus, in the display apparatus according to another embodiment of the present disclosure, various repair wirings can be used in the repair process, without the decrease of the process efficiency. For example, in the display apparatus according to another embodiment of the present disclosure, the repair process can be performed by using at least one of power lines **PL** and **RL** supplying the power voltage or the reference voltage in the second direction Y. Therefore, in the display apparatus according to another embodiment of the

present disclosure, the degree of freedom for the configuration and the arrangement of the power lines PL and RL can be improved. And, in the display apparatus according to another embodiment of the present disclosure, the reliability of the repair process can be improved.

[0106] In the result, the display apparatus according to the embodiments of the present disclosure can comprise the second data line disposed parallel to the first data line, the first gate line crossing the first data line and the second data line, the first sub-pixel including the first driving circuit that is electrically connected to the first data line and the first gate line, and the second sub-pixel including the second driving circuit that is electrically connected to the first gate line and the second data line, wherein the power line disposed parallel to the first data line and the second data line can include the auxiliary wiring disposed parallel to the main wiring and the connection wiring connecting the auxiliary wiring to the main wiring, wherein the first driving circuit and the second driving circuit can be electrically connected to the main wiring, and wherein the first electrode of the first light-emitting device disposed in the first sub-pixel and the first electrode of the second light-emitting device disposed in the second sub-pixel can include a portion overlapping with the auxiliary wiring. Thus, in the display apparatus according to the embodiments of the present disclosure, the auxiliary wiring can function as the repair wiring in the repair process. Thereby, in the display apparatus according to the embodiments of the present disclosure, the decrease in an area of the emission area defined in each sub-pixel can be reduced. And, in the display apparatus according to the embodiments of the present disclosure, the production energy can be reduced by process optimization.

[0107] The various embodiments described above can be combined to provide further embodiments. All of the U.S. patents, U.S. patent application publications, U.S. patent applications, foreign patents, foreign patent applications and non-patent publications referred to in this specification and/or listed in the Application Data Sheet are incorporated herein by reference, in their entirety. Aspects of the embodiments can be modified, if necessary to employ concepts of the various patents, applications and publications to provide yet further embodiments.

[0108] These and other changes can be made to the embodiments in light of the above-detailed description. In general, in the following claims, the terms used should not be construed to limit the claims to the specific embodiments disclosed in the specification and the claims, but should be construed to include all possible embodiments along with the full scope of equivalents to which such claims are entitled. Accordingly, the claims are not limited by the disclosure.

Claims

1. A display apparatus comprising: a first data line crossing a first gate line from a plan view; a second data line disposed parallel to the first data line, the second data line crossing the first gate line from a plan view; a first sub-pixel including a first driving circuit, the first driving circuit electrically connected to the first gate line and the first data line; a second sub-pixel including a second driving circuit, the second driving circuit electrically connected to the first gate line and the second data line; and a first power line disposed parallel to the first data line and the second data line, wherein the first power line includes an auxiliary wiring extending parallel to a main wiring and a connection wiring connecting the auxiliary wiring to the main wiring, wherein the first driving circuit and the second driving circuit are electrically connected to the main wiring, and wherein a first electrode of a first light-emitting device disposed in the first sub-pixel and a first electrode of a second light-emitting device disposed in the second sub-pixel include a portion overlapping with the auxiliary wiring.
2. The display apparatus according to the claim 1, wherein the second driving circuit has a symmetrical arrangement to the first driving circuit with respect to the first power line.
3. The display apparatus according to claim 1, wherein the first power line crosses between the first sub-pixel and the second sub-pixel.

- 4.** The display apparatus according to claim 3, further comprising a second power line disposed between the first data line and the second data line, wherein a signal applied through the second power line is different from a signal applied through the first power line.
 - 5.** The display apparatus according to claim 1, wherein each of the first driving circuit and the second driving circuit includes a driving thin film transistor, wherein a gate electrode of the driving thin film transistor is disposed parallel to the first gate line.
 - 6.** The display apparatus according to claim 5, wherein a semiconductor pattern of the driving thin film transistor is disposed parallel to the first data line and the second data line.
 - 7.** The display apparatus according to claim 1, further comprising: a second gate line disposed parallel to the first gate line, the second gate line crossing the first data line and the second data line; a third sub-pixel including a third driving circuit, the third driving circuit electrically connected to the second gate line and the first data line; and a fourth sub-pixel including a fourth driving circuit, the fourth driving circuit electrically connected to the second gate line and the second data line, wherein the third driving circuit and the fourth driving circuit are electrically connected to the main wiring, and wherein a first electrode of a third light-emitting device disposed in the third sub-pixel and a first electrode of a fourth light-emitting device disposed in the fourth sub-pixel include a portion overlapping with the auxiliary wiring.
 - 8.** The display apparatus according to claim 7, wherein the fourth driving circuit has a symmetrical arrangement to the third driving circuit with respect to the first power line.
 - 9.** The display apparatus according to claim 7, wherein the first driving circuit and the second driving circuit are disposed close to the first gate line, and the third driving circuit and the fourth driving circuit are disposed close to the second gate line.
 - 10.** The display apparatus according to claim 9, wherein the first gate line and the second gate line extend in a first direction, wherein the third driving circuit has a symmetrical arrangement to the first driving circuit with respect to the first direction, and wherein the fourth driving circuit has a symmetrical arrangement to the second driving circuit with respect to the first direction.
 - 11.** The display apparatus according to claim 1, wherein the auxiliary wiring is disposed on a same layer as the main wiring.
 - 12.** The display apparatus according to claim 11, wherein the auxiliary wiring includes a same material as the main wiring.
 - 13.** The display apparatus according to claim 11, wherein the connection wiring is disposed on a same layer as the main wiring and the auxiliary wiring.
 - 14.** The display apparatus according to claim 13, wherein the connection wiring includes a same material as the main wiring and the auxiliary wiring.
-