

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250287540

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

YANAGIBASHI; NAGISA

ELECTRONIC APPARATUS

Abstract

An electronic apparatus includes a heat generator, a heat radiating member configured to radiate heat from the heat generator, and a thermally conductive member disposed between the heat generator and the heat radiating member. The thermally conductive member has a first area, a second area, and a third area having a curved shape and disposed between the first area and the second area. The first area and the second area of the thermally conductive member are attached to one of the heat generator and the heat radiating member.

Inventors: YANAGIBASHI; NAGISA (Kanagawa, JP)

Applicant: CANON KABUSHIKI KAISHA (Tokyo, JP)

Family ID: 96949876

Appl. No.: 19/043907

Filed: February 03, 2025

Foreign Application Priority Data

JP 2024-037311

Mar. 11, 2024

Publication Classification

Int. Cl.: H05K7/20 (20060101); H04N23/52 (20230101)

U.S. Cl.:

CPC H05K7/2039 (20130101); H04N23/52 (20230101)

Background/Summary

BACKGROUND

Technical Field

[0001] The present disclosure relates to an electronic apparatus.

Description of Related Art

[0002] Conventionally, there is known an image pickup apparatus that includes an image stabilizing mechanism configured to displacing an image sensor in a two-dimensional direction orthogonal to the optical axis in order to suppress image blur caused by a user's hand shake. Such an image pickup apparatus is to exhibit sufficient heat radiating performance because the heat generated in the image sensor and circuit board constituting the image stabilizing mechanism affects image quality. However, if a heat radiating member with high rigidity is attached for heat radiation, a reaction force is generated when the image sensor is displaced in a two-dimensional direction and places a load on the image stabilizing mechanism.

[0003] Japanese Patent Laid-Open No. 2009-284414 discloses a structure that includes a ring-shaped heat radiation sheet between a support plate mounted with an image sensor and a heat radiating plate fixed at a position opposite to the support plate. The ring-shaped heat radiation sheet is flexible and thus can perform heat radiation without placing a load on the image stabilizing mechanism.

[0004] However, in the structure disclosed in Japanese Patent Laid-Open No. 2009-284414, a contact surface of the heat radiation sheet that is to contact the support plate mounted with the image sensor changes due to the two-dimensional displacement amount of the image sensor and gravity, and may reduce the heat radiating effect.

SUMMARY

[0005] An electronic apparatus according to one aspect of the disclosure includes a heat generator, a heat radiating member configured to radiate heat from the heat generator, and a thermally conductive member disposed between the heat generator and the heat radiating member. The thermally conductive member has a first area, a second area, and a third area having a curved shape and disposed between the first area and the second area. The first area and the second area of the thermally conductive member are attached to one of the heat generator and the heat radiating member.

[0006] Further features of various embodiments of the disclosure will become apparent from the following description of embodiments with reference to the attached drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0007] FIGS. 1A and 1B are external perspective views of an electronic apparatus according to a first embodiment.

[0008] FIG. 2 is a block diagram of the electronic apparatus according to the first embodiment.

[0009] FIG. 3 is an exploded perspective view of the electronic apparatus according to the first embodiment.

[0010] FIGS. 4A and 4B are exploded perspective views of an imaging unit according to the first embodiment.

[0011] FIGS. 5A to 5D are schematic diagrams of the thermally conductive sheet according to the first embodiment.

[0012] FIG. 6 is an internal configuration diagram of an electronic apparatus according to a second embodiment.

[0013] FIG. 7 is an exploded perspective view of an electronic apparatus according to a third embodiment.

[0014] FIG. 8 is a sectional view of a thermally conductive sheet according to the third

embodiment.

DETAILED DESCRIPTION

[0015] Referring now to the accompanying drawings, a detailed description will be given of embodiments according to the disclosure.

First Embodiment

[0016] Referring now to FIGS. **1A** and **1B**, a description will be given of a camera body (image pickup apparatus, electronic apparatus) **10** according to this embodiment. FIG. **1A** is an external perspective view of the camera body **10** viewed from the front side, and FIG. **1B** is an external perspective view of the camera body **10** when viewed the rear side.

[0017] In FIG. **1A**, the camera body **10** includes a mount **103** for detachably mounting a lens apparatus (interchangeable lens) **20** (see FIG. **2**). A grip portion **112** for a user to hold the camera body **10** is provided on the right side of the mount **103**. Each embodiment describes a lens interchangeable type camera in which a lens apparatus (interchangeable lens) is attachable to and detachable from the image pickup apparatus as the camera body **10** (camera body **10a**), but is not limited to this example. Each embodiment is also applicable to an image pickup apparatus in which the camera body and the lens apparatus are integrated.

[0018] In FIG. **1B**, a plurality of operation members **113**, a liquid crystal display (LCD) monitor **114**, and an electronic viewfinder (EVF) unit **400** are attached to a rear cover **104**. The LCD monitor **114** displays various setting screens, captured images, live-view images, etc. of the camera body **10**. The EVF unit **400** is an eye approachable viewfinder, and displays various setting screens, captured images, live-view images, etc. of the camera body **10**. The plurality of operation members **113** are attached to a top cover **106**. The operation members **113** can be used to power on and off the camera body **10**, start imaging, and change various settings.

[0019] Referring now to FIG. **2**, a description will be given of the electrical configuration and operation of the camera body **10**. FIG. **2** is a block diagram that illustrates a schematic diagram of the main electrical configuration of the camera body **10**.

[0020] The lens apparatus **20** includes an optical system (imaging optical system) that includes a lens **154** and an aperture stop (diaphragm) **152**. The position of the lens **154** in a direction along the optical axis OA (optical axis direction) is controlled by a focus detection control unit **155**. An aperture control unit **153** controls an aperture amount of the aperture stop **152**. Light incident on the lens **154** passes through the aperture stop **152** and a shutter **116** and is focused as an optical image on the imaging surface of an image sensor **231**. The shutter **116** is a light shielding member. The opening and closing operation of the shutter **116** is controlled by a shutter (SH) control unit **165**, and thereby an exposure amount to the image sensor **231** is controlled.

[0021] The imaging unit **200** includes an image sensor unit **230** and an image stabilizing mechanism **240**. The image sensor unit **230** includes the image sensor (electronic component, heat generator) **231**. The image sensor **231** includes a complementary metal oxide semiconductor (CMOS) image sensor or a charge coupled device (CCD) image sensor, photoelectrically converts an optical image formed by the imaging optical system, and outputs image data. The image stabilizing mechanism **240** corrects image blur by driving the image sensor **231** in a two-dimensional direction orthogonal to the optical axis OA according to a shake amount of the camera body **10** detected by a gyro (sensor) **159**.

[0022] A system control circuit **150** is a control unit configured to control the entire camera body **10**. A memory **156** is a storage unit storing constants and programs for the operation of the system control circuit **150**. A timer **157** measures the time for various operations. The system control circuit **150** is used as a determining unit and a control unit in various operations of the camera body **10**. The system control circuit **150** also controls the shutter **116**, the lens **154**, and the aperture stop **152** based on the results of calculations by an image processing circuit **151** on image data captured by the image sensor **231**, to perform autofocus (AF) processing and auto-exposure (AE) processing. The memory **156** further stores a holding state of the image sensor unit **230** by the

image stabilizing mechanism **240**. An external terminal **163** is a terminal for electrically connecting to an external device, and information can be sent and received between the system control circuit **150** and the external device via the external terminal **163**.

[0023] The LCD monitor **114** and the electronic viewfinder (EVF) panel **401** display image data captured by the image sensor **231**, as well as settings and information regarding imaging. A thermometer **158** measures the temperature of the heat generator such as the image sensor **231**, the LCD monitor **114**, and the EVF panel **401**. The operation members **113** include various buttons and switches that are operable by the user, and used to select and set various functions in performing imaging, playback, communication, and the like, and to give instructions regarding imaging and playback. A power switch **162** can switch between the power-on state and the power-off state of the camera body **10**.

[0024] A power supply control unit **161** includes a battery detection circuit, a DC/DC converter, and a switch circuit that switches between blocks to which electricity is applied. It detects the type and remaining charge of the battery **160** that serves as the power source for the camera body **10**, and supplies the required voltage to each unit, including a recording medium **164**, for a necessary period based on the detection results and instructions from the system control circuit **150**.

[0025] Referring now to FIG. **3**, the internal structure of the camera body **10** will be described. FIG. **3** is an exploded perspective view of the camera body **10**. The camera body **10** is covered by a front base **102**, a top cover **106**, a rear cover **104**, and a bottom cover **108**. These parts constitute the exterior member of the camera body **10**.

[0026] Provided inside the exterior member, the shutter **116** are the imaging unit **200**, a heat radiating sheet metal (heat radiating member) **300**, a main board **120**, and the EVF unit **400**. The heat radiating sheet metal **300** is disposed at a position opposite to the imaging unit **200**, which is a heat generator (opposite surface), and radiates heat from the imaging unit **200**. The front base **102** is formed, for example, of magnesium die casting or resin. Various electronic components such as electronic elements constituting the system control circuit **150** or an image processing circuit **151**, and a connector for mounting the recording medium **164** are mounted on the main board **120**. The main board **120** is fixed to the front base **102** and the heat radiating sheet metal **300** with screws.

[0027] A flexible printed circuit (FPC) board **270** electrically connects the imaging unit **200** and the main board **120**. An image signal from the imaging unit **200** is transmitted to the main board **120** via the FPC board **270**.

[0028] The imaging unit **200** consumes a large amount of power, particularly in the camera body **10**. Thus, the imaging unit **200** generates a large amount of heat and is prone to temperature rise. However, if the temperature of the imaging unit **200** exceeds a predetermined temperature, it will affect the captured image, so the temperature of the imaging unit **200** is to be kept below the predetermined temperature. The imaging unit **200** is fixed to the front base **102** with screws. In addition, by connecting a thermally conductive sheet **501** (described later) to the heat radiating sheet metal **300**, the heat from the imaging unit **200** can be radiated to the front base **102** and the heat radiating sheet metal **300**.

[0029] The FPC board **405** electrically connects the EVF unit **400** and the main board **120**. The EVF unit **400** displays captured image data, as well as settings and information regarding imaging, from the main board **120** via the FPC board **405**.

[0030] The EVF unit **400** has a large amount of self-heat generation because it includes a display device. In addition, the EVF unit **400** is susceptible to heat generation from electronic components mounted on the main board **120** via the FPC board **405**, and so its temperature is likely to rise. By connecting a thermally conductive sheet **410** (described later) to the heat radiating sheet metal **300**, the heat from the EVF unit **400** can be radiated to the heat radiating sheet metal **300**.

[0031] Referring now to FIGS. **4A**, **4B**, and **5A** to **5D**, a description will be given of the heat radiating structure for the image stabilizing mechanism **240** and image sensor **231** of the imaging unit **200**. FIG. **4A** is an exploded perspective view of the imaging unit **200** viewed from the front

side, and FIG. 4B is an exploded perspective view of the imaging unit **200** viewed from the rear side. FIG. 5A is a perspective view of the thermally conductive sheet **501**, FIG. 5B is a sectional view of the thermally conductive sheet **501**, FIG. 5C is a sectional view of the thermally conductive sheet **501** in a pressed state, and FIG. 5D is a perspective view of a state in which a plurality of thermally conductive sheets **501** are stacked.

[0032] The imaging unit **200** includes a front plate **210**, a rear plate **220**, and an image sensor unit **230** disposed between the front plate **210** and the rear plate **220**. Each of the front plate **210** and the rear plate **220** includes a metal plate. The imaging unit **200** is fixed to the front base **102** with three screws **247**, and three coil springs **245** are disposed between the imaging unit **200** and the front base **102**. The imaging unit **200** is supported displaceably (movably) in the optical axis direction by the tightening amounts of the three screws **247** and the three coil springs **245**, and the tilt of the image sensor **231** relative to the front base **102** can be adjusted.

[0033] The image sensor unit **230** includes the image sensor **231** and an image sensor holder **232** configured to hold the image sensor **231**. Between the image sensor holder **232** and the rear plate **220**, three balls **242** are disposed around the image sensor **231** so as to surround the optical axis OA. These three balls **242** roll freely, so that the image sensor unit **230** is held between the front plate **210** and the rear plate **220** swingably in a direction orthogonal to the optical axis direction (within a plane orthogonal to the optical axis OA).

[0034] A plurality of magnets **244** are disposed on the front plate **210** and the rear plate **220**. On the other hand, a plurality of coils **246** are disposed opposite to the magnets **244** on the image sensor holder **232**.

[0035] The FPC board **270** supplies power to the magnets **244**. This power supply controls the swing of the image sensor unit **230** by utilizing the repulsive and attractive forces between the magnetic field generated in the coils **246** and the magnets **244**. In general, the image stabilizing mechanism **240** controls the image sensor unit **230** so as to maintain it at the imaging center position, and also controls the image sensor unit **230** to move in a direction that cancels image shake of the camera body **10** caused by the user.

[0036] The image sensor **231** is mounted on the imaging board **280**, and the imaging board **280** and the main board **120** are electrically connected by imaging FPC boards **271** and **272**. The imaging FPC boards **271** and **272** have wirings that transmit the imaging signal output from the image sensor **231** and the control signal required to drive the image sensor **231**, and each signal is sent to the main board **120**. The imaging FPC boards **271** and **272** also supply power to drive the image sensor **231**.

[0037] The thermally conductive sheets **500** and **501** are, for example, graphite sheets with high heat radiating performance. A thermally conductive sheet fixing unit **221** is fixed to the rear plate **220** with screws. The thermally conductive sheet **500** connects the imaging board **280** mounted with the image sensor **231** and the thermally conductive sheet fixing unit **221**. In the thermally conductive sheet **500**, contact portions **500a** and **500b** are adhered to attachment surfaces **221a** and **221b**, respectively, and a contact portion **500c** is adhered to the imaging board **280**, via an adhesive such as double-sided tape. A distance between the contact portions **500a** and **500b** and a distance between the contact portions **500b** and **500c** are set to a sufficient length so that the thermally conductive sheet **500** follows the displacement of the image sensor unit **230**.

[0038] The thermally conductive sheet **501** is a thermally conductive member disposed between the imaging unit **200** and the heat radiating sheet metal **300**, and is disposed so that the imaging unit **200** and the heat radiating sheet metal **300** are in thermal contact with each other. In this embodiment, the thermally conductive sheet **501** connects the thermally conductive sheet fixing unit **221** and the heat radiating sheet metal **300**.

[0039] The thermally conductive sheet **501** has an attachment area (first area) **501a** and an attachment area (second area) **501b** at both ends, and a curved area (third area having a curved shape) **501c** between them. The curved area **501c** includes cylindrically shaped areas **501c1** and an

area **501c2** in contact with the imaging unit **200** (thermally conductive sheet fixing unit **221**).
[0040] The thermally conductive sheet **501** is attached to a surface (surface of the heat radiating sheet metal **300**) orthogonal to the optical axis OA in each of the attachment areas **501a** and **501b**. The attachment areas **501a** and **501b** of the thermally conductive sheet **501** are folded back at folding back portions **501f** relative to the curved area **501c**. The attachment areas **501a** and **501b** are attached to the heat radiating sheet metal **300** with an adhesive such as double-sided tape. At this time, the thermally conductive sheet **501** is positioned by aligning holes **501d** and **501.sub.e** in the thermally conductive sheet **501** with holes **301a** and **301b** in the heat radiating sheet metal **300**. The curved area **501c** has a sufficient length to contact the thermally conductive sheet fixing unit **221**.

[0041] The thermally conductive sheet **501** may be disposed in the opposite manner to the above, with the attachment areas **501a** and **501b** adhered to the thermally conductive sheet fixing unit **221** and the curved area **501c** in contact with the heat radiating sheet metal **300** (other related members may also be configured in the opposite manner). That is, the attachment areas **501a** and **501b** of the thermally conductive sheet **501** may be attached to one of the imaging unit **200** (thermally conductive sheet fixing unit **221**) and the heat radiating sheet metal **300**, and the curved area **501c** may be in contact with the other of the imaging unit **200** and the heat radiating sheet metal **300**.

[0042] As illustrated in FIG. 5D, the thermally conductive sheet **501** has an Ω shape (curved shape) when viewed from a direction orthogonal to the optical axis direction (X-axis direction). Thereby, the thermally conductive sheet **501** becomes flexible, follows the displacement amount of the imaging unit **200** in the optical axis direction, and maintains a contact state with the thermally conductive sheet fixing unit **221**. In addition, the imaging unit **200** can be adjusted in the optical axis direction without applying a load to the three coil springs **245**.

[0043] At least a portion of the area between the curved area **501c** and the attachment areas **501a** and **501b** is adhered by a double-sided tape (adhesive member) **502**. In the thermally conductive sheet **501**, the curved area **501c** has a cylindrical shape that is uniform in the Y-axis direction relative to the attachment areas **501a** and **501b**. Thereby, the thermally conductive sheet **501** can maintain the Ω shape (curved shape) against the displacement of the imaging unit **200** or gravity, and the contact surface of the thermally conductive sheet fixing unit **221** can be stable.

[0044] The heat radiating sheet metal **300** has clearance grooves (openings) **302a** and **302b** for allowing at least a portion of the thermally conductive sheet **501** to escape. Therefore, even if the heat radiating sheet metal **300** and the thermally conductive sheet fixing unit **221** are close to each other and the thermally conductive sheet **501** is pressed (crushed), the thermally conductive sheet **501** can escape in the clearance grooves **302a** and **302b**, and does not develop a crease, allowing it to return to its Ω shape.

[0045] To further enhance the heat radiating effect, the thermally conductive sheet **501** may be configured by stacking multiple thermally conductive sheets or by providing them at multiple locations. As illustrated in FIG. 5D, multiple conductive sheets may be arranged in a cross-like manner to increase the contact area.

[0046] The above structure according to this embodiment can radiate the heat generated by the image sensor **231** to the heat radiating sheet metal **300** through the thermally conductive sheets **500** and **501** without applying a load to the swing control of the imaging unit **200**.

Second Embodiment

[0047] Next, a second embodiment of the present disclosure will be described. The first embodiment has discussed an example heat radiation configuration from the image sensor **231** to the heat radiating sheet metal **300**. On the other hand, this embodiment will discuss an example heat radiation configuration from the image sensor **231** to an exterior member. Those elements in this embodiment, which are corresponding elements in the first embodiment, will be designated by the same reference numerals, and a detailed description thereof will be omitted.

[0048] Referring now to FIG. 6, a description will be given of the configuration of the thermally

conductive sheet **600** according to this embodiment. FIG. **6** is an internal configuration diagram of a camera body (image pickup apparatus, electronic apparatus) **10a** having a thermally conductive sheet **600** according to this embodiment. The thermally conductive sheet **600** is a thermally conductive member having an attachment area (first area) **600a**, an attachment area (second area) **600b**, and a curved area (curved third area) **600c** between the attachment areas **600a** and **600b**. The attachment areas **600a** and **600b** are attached to the periphery of the image sensor unit **230** by an adhesive such as double-sided tape. The number, the position in the XY direction, or the length of the curved area **600c** of the thermally conductive sheet **600** may be changed as appropriate according to the load of the swing control of the image sensor unit **230**.

[0049] A side plate **111** constituting an exterior member is attached to a side surface of the front base **102** constituting the exterior member (housing). Similarly, a bottom plate **109** constituting the exterior member is attached to a bottom surface of the front base **102**. Thereby, the camera body **10a** can withstand impacts from the outside of the camera body **10a**.

[0050] The thermally conductive sheet **600** attached to the upper side of the image sensor unit **230** contacts the front base **102**. The thermally conductive sheet **600** attached to the lower side of the image sensor unit **230** contacts the bottom plate **109**. The thermally conductive sheet **600** attached to the left side of the image sensor unit **230** contacts the side plate **111**. Thus, this embodiment can effectively radiate the heat generated by the image sensor unit **230**, by bringing the thermally conductive sheet **600** into contact with each exterior member (housing) as a heat radiating member.

[0051] The thermally conductive sheet **600** has flexibility due to its Ω shape (curved shape). Therefore, according to this embodiment, the thermally conductive sheet **600** can follow the XY-directional swing control of the image sensor unit **230** without applying a load and maintain a contact state with each exterior member.

Third Embodiment

[0052] Next, a third embodiment of the present disclosure will be described. The first and second embodiments have discussed examples of the heat radiation configuration of the image sensor **231** as a heat generator (electronic component). On the other hand, this embodiment will discuss an example heat radiation configuration of the EVF panel **401** as a heat generator (electronic component). Those elements in this embodiment, which are corresponding elements in the above embodiments, will be designated by the same reference numerals, and a detailed description thereof will be omitted.

[0053] The heat radiating structure of the EVF panel **401** according to this embodiment will be described with reference to FIGS. **7** and **8**. FIG. **7** is an exploded perspective view of the EVF unit (electronic apparatus) **400** according to this embodiment. FIG. **8** is a sectional view of the thermally conductive sheet **410**.

[0054] The EVF unit **400** includes an EVF panel unit **402** and a lens unit **404**. The EVF panel unit **402** has a diopter adjusting mechanism (not illustrated) and is displaceable in the Z-axis direction (optical axis direction) relative to the lens unit **404**. The EVF panel unit **402** includes an EVF panel **401** and a panel holder **403** that holds the EVF panel **401**. The EVF panel **401** is adhered and fixed to the panel holder **403**.

[0055] The thermally conductive sheet **410** is a thermally conductive member that connects the EVF panel **401** and the contact surface **303** of the heat radiating sheet metal **300**. The thermally conductive sheet **410** has an Ω shape (curved shape) when viewed from the X-axis direction. The thermally conductive sheet **410** is adhered to the EVF panel **401** with an adhesive agent (adhesive member) such as double-sided tape. The curved area **410c** of the thermally conductive sheet **410** has a sufficient length so that it can contact a contact surface **303** of the heat radiating sheet metal **300** following the displacement amount of the EVF panel unit **402** in the Z-axis direction.

[0056] The heat radiating sheet metal **300** has inclined surfaces **304** and **305** configured to support the thermally conductive sheet **410**. As a result, even if the thermally conductive sheet **410** is inclined in the Y-axis direction, it contacts the inclined surfaces **304** and **305** to maintain its Ω

shape, and the thermally conductive sheet **410** is supported so that it is always in contact with the contact surface **303**. The thermally conductive sheet **410** is likely to tilt in the $-Y$ -axis direction, which is the gravity direction, when the image pickup apparatus is in the normal position state (when the upper side of the image pickup apparatus is disposed on the $+Y$ -axis side (opposite the direction of the gravity direction)). Therefore, the heat radiating sheet metal **300** may have the inclined surface **304** on the $-Y$ -axis side (gravity direction side), and may not have the inclined surface **305** on the $+Y$ -axis side.

[0057] This embodiment using the thermally conductive sheet **410** applies no load to the adjustment in the Z -axis direction, and can effectively radiate the heat generated from the EVF panel **401** as a heat radiator to the heat radiating sheet metal **300**.

[0058] The electronic apparatus according to each embodiment can secure a sufficient heat radiating path from the heat generator by stabilizing the contact surface between the heat generator and the thermally conductive sheet without impeding the displacement of the heat generator. Therefore, each embodiment can provide an electronic apparatus that can stably radiate heat from a displaceable heat generator.

[0059] While the disclosure has described example embodiments, it is to be understood that the disclosure is not limited to the example embodiments. The scope of the following claims is to be accorded the broadest interpretation so as to encompass all such modifications and equivalent structures and functions.

[0060] Each embodiment can provide an electronic apparatus that can stably radiate heat from a displaceable heat generator.

[0061] This application claims priority to Japanese Patent Application No. 2024-037311, which was filed on Mar. 11, 2024, and which is hereby incorporated by reference herein in its entirety.

Claims

1. An electronic apparatus comprising: a heat generator; a heat radiating member configured to radiate heat from the heat generator; and a thermally conductive member disposed between the heat generator and the heat radiating member, wherein the thermally conductive member has a first area, a second area, and a third area having a curved shape and disposed between the first area and the second area, and wherein the first area and the second area of the thermally conductive member are attached to one of the heat generator and the heat radiating member.
2. The electronic apparatus according to claim 1, wherein the thermally conductive member is disposed so that the heat generator and the heat radiating member are in thermal contact.
3. The electronic apparatus according to claim 1, wherein the third area of the thermally conductive member includes an area having a cylindrical shape.
4. The electronic apparatus according to claim 1, wherein the third area of the thermally conductive member includes an area that contacts another of the heat generator and the heat radiating member.
5. The electronic apparatus according to claim 1, wherein the first area and the second area of the thermally conductive member are folded back relative to the third area.
6. The electronic apparatus according to claim 1, further comprising an adhesive member for adhering each of the first area and the second area to a part of the third area of the thermally conductive member.
7. The electronic apparatus according to claim 1, wherein one of the heat generator and the heat radiating member has an opening that allows at least a part of the thermally conductive member to escape in a case where the thermally conductive member is pressed in a direction in which the heat generator and the heat radiating member approach each other.
8. The electronic apparatus according to claim 1, wherein the thermally conductive member is a thermally conductive sheet attached to a surface orthogonal to an optical axis in each of the first area and the second area.

- 9.** The electronic apparatus according to claim 1, wherein the heat generator is an imaging unit displaceable in an optical axis direction.
- 10.** The electronic apparatus according to claim 1, wherein the heat radiating member includes a heat radiating sheet metal disposed at a position opposite to the heat generator.
- 11.** The electronic apparatus according to claim 1, wherein the heat radiating member is an exterior member of the electronic apparatus.
- 12.** The electronic apparatus according to claim 1, wherein the heat generator is an electronic viewfinder panel displaceable in an optical axis direction.
- 13.** The electronic apparatus according to claim 12, wherein the heat radiating member has an inclined surface configured to support the thermally conductive member.
- 14.** The electronic apparatus according to claim 13, wherein the inclined surface is formed on a gravity direction side of the thermally conductive member in a case where the electronic apparatus is in a normal position state.
-