

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12409663
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Yraceburu; Robert et al.

Composite electrode fluid level sensing

Abstract

A fluid level sensing system includes: a sensor electrode to extend into a fluid reservoir, the sensor electrode including (i) a first segment of a first material having a first conductivity, and (ii) a second segment of a second material having a second conductivity; and a controller connected to the sensor electrode, to: detect a response from the sensor electrode to an input applied to the fluid reservoir; and determine, based on the response, which of the first and second segments are in contact with fluid in the fluid reservoir.

Inventors:	Yraceburu; Robert (Vancouver, WA), Downing; Elliott Michael (Vancouver, WA), Clayburn; Jody Lee (Vancouver, WA)
Applicant:	HEWLETT-PACKARD DEVELOPMENT COMPANY, L.P. (Spring, TX)
Family ID:	77079239
Assignee:	Hewlett-Packard Development Company, L.P. (Spring, TX)
Appl. No.:	17/792260
Filed (or PCT Filed):	January 28, 2020
PCT No.:	PCT/US2020/015471
PCT Pub. No.:	WO2021/154217
PCT Pub. Date:	August 05, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20230052524 A1	Feb. 16, 2023

Publication Classification

Int. Cl.: G01F23/24 (20060101); B41J2/175 (20060101)

U.S. Cl.:

CPC B41J2/17566 (20130101); B41J2002/17579 (20130101)

Field of Classification Search

CPC: G01F (23/0007); G01F (23/24-244); G01F (23/26-268)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5408223	12/1994	Guillemot	73/304R	G01F 23/241
6431670	12/2001	Schantz et al.	N/A	N/A
6874861	12/2004	Farr et al.	N/A	N/A
7775105	12/2009	Khadkikar et al.	N/A	N/A
7802471	12/2009	Sieh et al.	N/A	N/A
9789697	12/2016	Knierim et al.	N/A	N/A
10323972	12/2018	van Dijk	N/A	G01F 23/242
2005/0280424	12/2004	Qu	324/663	G01F 23/265
2007/0076023	12/2006	Knierim et al.	N/A	N/A
2007/0240506	12/2006	Lin	73/304R	G01F 23/266
2009/0019930	12/2008	Larocque	702/155	G01F 23/265
2012/0184932	12/2011	Giezendanner	73/304R	G01F 23/268
2012/0306974	12/2011	Nicholson et al.	N/A	N/A
2013/0276533	12/2012	Wilder	73/304C	G01F 23/263
2016/0202103	12/2015	Heinonen	73/304C	G01F 23/242
2018/0080808	12/2017	Naydenov	N/A	G01F 23/265
2020/0064176	12/2019	Souques	N/A	G01F 23/265
2021/0088499	12/2020	Stewart	N/A	G01N 11/14

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
------------	------------------	---------	-----

208148820	12/2017	CN	N/A
2657663	12/2012	EP	G01F 23/265
WO-2017131761	12/2016	WO	N/A

OTHER PUBLICATIONS

Anne Marie Helmenstine, Ph. D. (May 12, 2024). A table of electrical conductivity and resistivity of common materials. ThoughtCo. <https://www.thoughtco.com/table-of-electrical-resistivity-conductivity-608499> (Year: 2024). cited by examiner

Primary Examiner: Mercado; Alexander A

Attorney, Agent or Firm: Brooks, Cameron & Huebsch

Background/Summary

BACKGROUND

(1) Fluid dispensing devices, such as ink cartridges for printers, may include reservoirs holding fluid (e.g. ink) to be dispensed. The devices may also include mechanisms to determine a volume of fluid contained in the reservoir. Such mechanisms may be subject to constraints on available space, manufacturing cost, or the like.

Description

BRIEF DESCRIPTIONS OF THE DRAWINGS

- (1) FIG. 1 is a diagram of an example fluid dispenser with a level sensing system.
- (2) FIG. 2 is a diagram of an example fluid dispenser with a level sensing system.
- (3) FIG. 3 is a diagram of an example fluid dispenser with a level sensing system.
- (4) FIG. 4 is a diagram of an example fluid dispenser with a level sensing system.
- (5) FIG. 5A is a cross section of an example sensor electrode.
- (6) FIG. 5B is a cross section of an example sensor electrode.
- (7) FIG. 6 is an example method of fluid level sensing.
- (8) FIG. 7 is an example method of fluid level sensing.

DETAILED DESCRIPTION

- (9) To provide level sensing for a fluid reservoir of a fluid dispensing device, a conductive sensor electrode may be provided within the reservoir. For example, the reservoir may hold printing fluid for application by a printing system. The sensor electrode may extend to a predetermined level within the reservoir, such that when the fluid is below the predetermined level the sensor electrode is not in contact with the fluid, and when the fluid is at or above the predetermined level, the sensor electrode is in contact with the fluid. A drive electrode may also be provided within the reservoir, to apply a drive signal to the fluid. When the sensor electrode is in contact with the fluid, the drive signal is detected by the sensor electrode, and a controller connected with the sensor electrode can determine that the fluid is at least at the predetermined level mentioned above.
- (10) The arrangement mentioned above thus provides a binary indication of whether the fluid in the reservoir is above or below the predetermined level to which the sensor electrode extends. To provide indications of whether the fluid is above or below additional levels, additional sensor electrodes may be installed in the reservoir. Such additional sensor electrodes, however, may increase the manufacturing cost of the fluid dispensing device. In addition, additional sensor electrodes may be difficult to accommodate physically within the reservoir.

(11) To provide multi-level sensing for fluid dispensing devices, while reducing manufacturing costs and the physical footprint of the sensing mechanism, described herein is a fluid level sensing system includes a composite sensor electrode, including segments with different conductivities.

(12) FIG. 1 shows a cross sectional view of a fluid dispenser **100**. The fluid dispenser **100** includes a housing **104** that defines a fluid reservoir **108** therein. The fluid reservoir **108** is to contain a fluid, such as printer ink, liquid printer toner, feed fluid for a 3D printer, or the like. The fluid dispenser **100** can be a printer cartridge that stores ink or toner and dispenses the ink or toner to a print head for application to print media. The fluid dispenser **100** may also be used by a 3D printer to apply the above-mentioned feed fluid to a bed of material such as a substrate plate. The fluid dispenser **100** therefore also includes at least one outlet **112**, to dispense fluid e.g. towards the print head, and at least one inlet **116** to receive fluid to replenish the reservoir **108**. In some examples, multiple outlets **112** may be provided. In some examples, multiple inlets **116** may also be provided.

(13) The fluid dispenser **100** also includes a sensing system to provide multi-level sensing within the reservoir **108**. That is, the sensing system can determine, for each of at least two levels within the reservoir, whether the fluid is at or above the respective level. The sensing system includes a sensor electrode **120** that extends into the reservoir **108** to terminate at a first fluid level **124**. The sensor electrode **120** includes at least a first segment **128** and a second segment **132**. As seen in FIG. 1, the first segment **128** terminates at the level **124**, while the second segment terminates at a level **134**.

(14) The first segment **128** includes a first material with a first conductivity, and the second segment **132** includes a second material with a second conductivity. That is, the first and second segments **128** and **132** have different conductivities as a result of the different materials used in the first and second segments **128** and **132**. The first material and the second material can include metals with different conductivities. The first material and the second material can also include conductive powders, fibers or the like embedded in a carrier material such as a plastic, a thermoset epoxy, silicon, or the like. Examples of such powders and fibers include metal powders and carbon fiber. For example, the first material can include a greater concentration of the above-mentioned conductive components in the carrier material than the second material.

(15) The fluid dispenser **100** also includes a controller **136** connected with the sensor electrode **120**. The controller **136** can be implemented as at least one microcontroller, sensing circuit, field-programmable gate array (FPGA), or the like. The fluid dispenser **100** further includes a drive electrode **140** that extends into the reservoir **108** and terminates at least at the level **124**, or below the level **124**. As illustrated in FIG. 1 the sensor electrode **120** and the drive electrode **140** extend into the reservoir from an upper wall of the housing **104**. In other examples, the sensor electrode **120** and the drive electrode **140** can extend into the reservoir from a side wall or a lower wall of the housing **104**.

(16) The drive electrode **140**, as well as the sensor electrode **120**, are connected with the controller **136**. For example, the sensor electrode **120** and the drive electrode **140** can be supported by a sensor mount **144** containing electrical connections between the controller **136** and the electrodes **120** and **140**. The segment **128** is distal to the sensor mount **144**, while the segment **132** is proximal to the sensor mount **144**.

(17) The controller **136** applies an input, also referred to as a drive signal, to the fluid in the reservoir **108** via the drive electrode **140**. If the sensor electrode **120** is in contact with the fluid, the drive signal is received by the sensor electrode **120** and detected by the controller **136**. Because of the differing conductivities of the segments **128** and **132**, the response detected by the controller **136** via the sensor electrode **120** varies depending on whether the segment **128** alone is in contact with the fluid, or whether the segments **128** and **132** are both in contact with the fluid. The controller **136** can determine, based on step-like variations in the response from the sensor electrode **120**, which of the segments **128** and **132** are in contact with the fluid.

(18) In particular, when the fluid in the reservoir **108** rises from below the level **134** to above the

level **134**, the change in conductivity caused by the segment **132** coming into contact with the fluid leads to a step-like change in the response detected at the controller **136**. The first segment **128** can have a lower conductivity than the second segment **132**, and the step-like change can therefore be an increase in the magnitude of the response, the frequency of the response, or the like. The controller **136** can store, for each segment of the sensor electrode **120**, a range of response values corresponding to that segment. Thus, when the response detected at the controller falls within the range that corresponds to the segment **132**, the controller **136** can determine that the segment **132** and the segment **128** are in contact with the fluid. In other words, the controller **136** can determine whether the fluid is below the level **124** (when the drive signal is not detected by the sensor electrode **120**), whether the fluid is between the level **124** and the level **134**, or whether the fluid is above the level **134**.

(19) In some examples, the sensor electrode **120** includes at least one additional segment. Referring to FIG. 2, the fluid dispenser **100** is shown with another example sensing system that includes a sensor electrode **220**. The sensor electrode **220** includes a first segment **224**, a second segment **228**, and a third segment **232**, each including different materials with distinct conductivities. The first segment **224** can have a lower conductivity than the second segment **228**, and the second segment **228** can have a lower conductivity than the third segment **232**. The sensor electrode **220** enables the controller **136** to determine whether a level of the fluid in the reservoir **108** is below the level **124**, between the level **124** and a level **236**, between the level **236** and a level **240**, or above the level **240**.

(20) In other examples, sensor electrodes with greater numbers of segments may be implemented. While the segments **128** and **132** illustrated in FIG. 1 have equal lengths, and the segments **224**, **228** and **232** illustrated in FIG. 2 have equal lengths, in other examples, the lengths of the segments of the sensor electrode can have different lengths.

(21) Turning to FIG. 3, the fluid dispenser **100** is shown with another example sensing system that includes two sensor electrodes **300** and **304**. The sensor electrode **300** includes a first segment **308** and a second segment **312**, with the first segment **308** having a lower conductivity than the second segment **312**. The sensor electrode **304** includes a third segment **316** and a fourth segment **320**, with the third segment **316** have a lower conductivity than the fourth segment **320**. As seen in FIG. 3, the first segment **308** and the third segment **316** include the same materials and thus have the same conductivities, while the second segment **312** and the fourth segment **320** also include the same materials and thus have the same conductivities. In other examples each of the four segments may employ different materials and therefore have different conductivities.

(22) The boundary between the third and fourth segments **316** and **320**, which defines a level **324**, is offset from a boundary between the first and second segments **308** and **312**, which defines a level **328**. The controller **136** is connected to both the sensor electrodes **300** and **304**, and therefore detects responses from each sensor electrode. The controller **136**, based on the responses, determines which segments of each sensor electrode **300** and **304** are in contact with the fluid in the reservoir **108**. Based on such a determination, the controller **136** can determine whether the fluid is below the lever **124**, between the level **124** and the level **328**, between the level **328** and **324**, or above the level **324**.

(23) The ability to distinguish between the above-mentioned four regions of fluid level may also be implemented by a single sensor electrode with three segments, such as the sensor electrode **220** shown in FIG. 2. However, in some implementations the use of two distinct sensor electrodes with offset segment boundaries may provide more reliable fluid sensing, as the differences in conductivity between two segments may be greater than differences in conductivity between adjacent ones of larger numbers of segments.

(24) Turning to FIG. 4, the fluid dispenser **100** is shown with another example sensing system that includes two sensor electrodes **400** and **404**. The sensor electrode **400** includes three segments **408**, **412** and **416** with increasing conductivities, with the segment **408** having the lowest conductivity.

The sensor electrode **404** includes three segments **420**, **424** and **428** with increasing conductivities, with the segment **420** having the lowest conductivity. The segments of the sensor electrode **404** define levels **124**, **432** and **436** detectable in a lower portion of the reservoir **108**, while the segments of the sensor electrode **400** define levels **440**, **444** and **448** in an upper portion of the reservoir **108**. In addition, the segments **408** and **412**, as well as the segments **420** and **424**, are identically sized and use the same materials. Therefore, manufacturing of the sensing system may be streamlined by producing multiple pairs of such segments, which may then be attached to the segments **428** and **416** that are manufactured with variable lengths.

(25) The segments of the sensor electrodes discussed above may have various internal structures. In some examples, turning to FIG. 5A, a cross section of a sensor electrode **500** is shown. The sensor electrode **500** includes a conductive core **504** of a conductive core material. Surrounding the conductive core are a first sleeve **506** of a first material, and a second sleeve **508** of a second material. The sleeves **506** and **508** form respective segments of the sensor electrode **500**.

(26) Referring to FIG. 5B, a cross section of another sensor electrode **510** is shown. The sensor electrode **510** includes a first segment **512** of a first material, and a second segment **514** of a second material. Rather than being implemented as sleeves about a conductive core, the segments **512** and **514** are joined by way of a protrusion **516** of the second segment **514** that extends from an end of the second segment **514** into a complementary opening at an end of the first segment **512**.

(27) Turning to FIG. 6, and as will also be apparent from the discussion above, the controller **136** can implement a method for monitoring fluid levels via the sensing systems of FIGS. 1-5.

(28) FIG. 6 illustrates a flowchart of a method **600**. The method **600** can be performed, for example, by the controller **136**. At block **605**, the controller **136** applies a drive signal to the reservoir via the drive pin **140**. At block **610**, the controller **136** detects a response from each sensor electrode of the sensing system. At block **615**, based on the response(s) detected at block **610**, the controller **136** determines which segments of each sensor electrode are in contact with fluid in the fluid reservoir. At block **620**, the controller **136** generates a fluid level indication for transmission, display or the like. The fluid level indication can be, for example, expressed as a fraction corresponding to the nearest level in the reservoir indicated by the response(s) of the sensor electrode(s).

(29) For example, with reference to the sensing system as shown in FIG. 2, the fluid level indication can be selected from values of 0% (empty) when none of the segments of the sensor electrode **220** are in contact with the fluid, 33% when the segment **224** is in contact with the fluid, 66% when the segments **224** and **228** are in contact with the fluid, and 100% when all three segments **224**, **228** and **232** are in contact with the fluid.

(30) FIG. 7 illustrates a flowchart of another method **700** that may be implemented at the controller **136** when the sensing system of the fluid dispenser **100** includes at least two sensor electrodes. At blocks **705** and **710**, the controller **136** applies an input and detects responses from each sensor electrode as described above in connection with blocks **605** and **610**. At block **715**, the controller **136** determines, based on the responses, which segments of each sensor electrode are in contact with the fluid, as at block **615** of the method **600**.

(31) At block **717**, the controller **136** determines whether the responses detected at block **710** conflict. For example, in the system of FIG. 4, if a response is detected indicating that only the segment **420** of the sensor electrode **404** is in contact with the fluid, and simultaneously a further response is detected indicating that the segment **408** of the sensor electrode **400** is in contact with the fluid, the determination at block **717** is affirmative. The response noted above conflict because they indicate two distinct fluid levels within the reservoir **108**, which may indicate a malfunction of a sensor electrode, the controller **136** or the like.

(32) In response to an affirmative determination at block **717**, the controller **136** generates an error message, for display and/or transmission to another controller, at block **718**. When the determination at block **717** is negative, the controller **136** proceeds to block **720** to generate the

fluid level indication as noted above in connection with block 620.

(33) It should be recognized that features and aspects of the various examples provided above can be combined into further examples that also fall within the scope of the present disclosure. In addition, the figures are not to scale and may have size and shape exaggerated for illustrative purposes.

Claims

1. A fluid level sensing system, comprising: a sensor electrode to extend into a fluid reservoir, the sensor electrode including a first segment of a first material having a first conductivity, a second segment of a second material having a second conductivity, and a third segment of a third material having a third conductivity, wherein each segment of the first, second, and third segments define a fluid level within the fluid reservoir, and wherein the second segment is in direct electrical contact with the first and third segment; and a controller connected to the sensor electrode, to: detect a response from the sensor electrode to an input applied to the fluid reservoir by the controller; determine, based on the response, which of the first, second, and third segments are in contact with fluid in the fluid reservoir; and generate a fluid level indication corresponding to a nearest fluid level in the fluid reservoir indicated by the response of the sensor electrode.
2. The fluid level sensing system of claim 1, further comprising a drive electrode to extend into the fluid reservoir; wherein the controller is to apply the input to the fluid reservoir via the drive electrode.
3. The fluid level sensing system of claim 1, wherein the sensor electrode includes at least one additional segment of an additional material having an additional conductivity different from the first and second conductivities.
4. The fluid level sensing system of claim 1, further comprising: a sensor mount to support the sensor electrode on a housing defining the fluid reservoir; wherein the second segment is proximal to the sensor mount, and the first segment is distal to the sensor mount.
5. The fluid level sensing system of claim 4, wherein the first conductivity is lower than second conductivity.
6. The fluid level sensing system of claim 1, wherein the sensor electrode includes a core of a conductive core material; and wherein the first segment includes a first sleeve of the first material about the core, and the second segment includes a second sleeve of the second material about the core.
7. The fluid level sensing system of claim 1, further comprising an additional sensor electrode having a fourth segment of the first material, and a fifth segment of the second material.
8. The fluid level sensing system of claim 7, wherein a boundary between the fourth and fifth segments is offset from a boundary between the first and second segments.
9. The fluid level sensing system of claim 7, wherein a length of the additional sensor electrode is different from a length of the sensor electrode.
10. The fluid level sensing system of claim 1, wherein the first segment includes a protrusion extending from an end of the first segment and the second segment includes an opening at an end of the second segment to receive the protrusion for joining the first segment and the second segment.
11. A fluid dispenser, comprising: a reservoir for holding a fluid; a sensor electrode to extend into the reservoir, the sensor electrode including: a first segment of a first material having a first conductivity, a second segment of a second material having a second conductivity; a third segment of a third material having a third conductivity; and wherein each segment of the first, second, and third segments define a fluid level within the fluid reservoir, and wherein the second segment is in direct electrical contact with the first and third segment; a controller connected to the sensor electrode, to: apply an input to the fluid reservoir; detect a response from the sensor electrode based

on the applied input; determine, based on the response, which of the first, second, and third segments are in contact with the fluid in the fluid reservoir; and generate a fluid level indication corresponding to a nearest fluid level in the fluid reservoir indicated by the response of the sensor electrode.

12. A method, comprising: applying an input to a fluid reservoir by a controller; detecting a response to the input from a sensor electrode in the fluid reservoir, the sensor electrode having a first segment with a first conductivity, a second segment with a second conductivity, and a third segment of a third material having a third conductivity, wherein each segment of the first, second, and third segments define a fluid level within the fluid reservoir, and wherein the second segment is in direct electrical contact with the first and third segment; determining, based on the response, which of the first segment, the second segment, and the third segment are in contact with fluid in the fluid reservoir; and based on which of the first segment and the second segment are in contact with fluid in the fluid reservoir, generating a fluid level indication corresponding to a nearest fluid level in the fluid reservoir indicated by the response of the sensor electrode.

13. The method of claim 12, further comprising: detecting an additional response to the input from an additional sensor electrode in the fluid reservoir, the additional sensor electrode having a fourth segment and a fifth segment; determining, based on the additional response, which of the fourth segment and the fifth segment are in contact with the fluid; and determining whether the response and the additional response conflict.

14. The method of claim 13, further comprising: generating an error message when the response and the additional response conflict.
