

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12409849
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Wang; Yanyan et al.

Method and apparatus for passing through barrier gate crossbar by vehicle

Abstract

A vehicle collects data of a plurality of to-be-detected barrier gate crossbars around the vehicle by using a sensor mounted on the vehicle, and transmits the data of the plurality of to-be-detected barrier gate crossbars to a processor; the processor determines data of a target barrier gate crossbar from the data of the plurality of to-be-detected barrier gate crossbars based on a pose of the target barrier gate crossbar, where the target barrier gate crossbar is a barrier gate crossbar of a lane on which the vehicle is located; and the processor determines a status of the target barrier gate crossbar based on the data of the target barrier gate crossbar, and controls, based on the status of the target barrier gate crossbar, the autonomous driving vehicle to pass through the target barrier gate crossbar.

Inventors: Wang; Yanyan (Shenzhen, CN), Wu; Zuguang (Hangzhou, CN), Yang; Yue (Shanghai, CN), Zheng; Jia (Hangzhou, CN)

Applicant: Shenzhen Yinwang Intelligent Technologies Co., Ltd. (Guangdong, CN)

Family ID: 76879304

Assignee: SHENZHEN YINWANG INTELLIGENT TECHNOLOGIES CO., LTD.
(Shenzhen, CN)

Appl. No.: 17/975392

Filed: October 27, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230048680 A1	Feb. 16, 2023

Related U.S. Application Data

Publication Classification**Int. Cl.:** **B60W60/00** (20200101); **B60W30/18** (20120101)**U.S. Cl.:****CPC** **B60W60/001** (20200201); **B60W30/18009** (20130101); B60W2420/403 (20130101); B60W2552/50 (20200201)**Field of Classification Search****USPC:** None

References Cited**U.S. PATENT DOCUMENTS**

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6212825	12/2000	Hopkins, Jr.	49/358	E01F 13/06
2002/0090259	12/2001	Crowley	404/6	E01F 15/003
2006/0228177	12/2005	Allain et al.	N/A	N/A
2013/0261950	12/2012	Sasabuchi	342/70	B61L 23/041
2019/0111919	12/2018	Matsunaga	N/A	B60W 10/18
2019/0347496	12/2018	Takahashi	N/A	G01B 11/24
2020/0062243	12/2019	Perez Barrera et al.	N/A	N/A
2020/0070823	12/2019	Zhang et al.	N/A	N/A
2022/0324480	12/2021	Tsunekazu	N/A	B60W 60/001

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
103359034	12/2012	CN	N/A
208421926	12/2018	CN	N/A
109345647	12/2018	CN	N/A
109664878	12/2018	CN	N/A
109774714	12/2018	CN	N/A
110503823	12/2018	CN	N/A
102013226599	12/2014	DE	N/A
102015209671	12/2015	DE	N/A
2645126	12/2012	EP	N/A
2014137611	12/2013	JP	N/A
19980073039	12/1997	KR	N/A

OTHER PUBLICATIONS

Machine translation of DE102013226599A1, a FOR document provided in the IDS (Year: 2024).
cited by examiner

Primary Examiner: Chad; Aniss

Assistant Examiner: Anda; Jennifer M

Attorney, Agent or Firm: WOMBLE BOND DICKINSON (US) LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of International Application No. PCT/CN2020/087578, filed on Apr. 28, 2020, which is hereby incorporated by reference in its entirety.

TECHNICAL FIELD

(1) Embodiments of this application relate to the field of autonomous driving, furthermore, to a method and an apparatus for passing through a barrier gate crossbar by a vehicle.

BACKGROUND

(2) Artificial intelligence (AI) is a theory, method, technology, and application system that simulates, extends, and expands human intelligence, perceives an environment, obtains knowledge, and uses the knowledge to obtain an optimal result by using a digital computer or a digital computer-controlled machine. In other words, artificial intelligence is a branch of computer science, and seeks to learn essence of intelligence and produce a new intelligent machine that can react in a way similar to artificial intelligence. Artificial intelligence is to study design principles and implementation methods of various intelligent machines, so that the machines have functions of perception, inference, and decision-making. Researches in the field of artificial intelligence include robotics, natural language processing, computer vision, decision-making and inference, human-computer interaction, recommendation and search, basic theories of AI, and the like.

(3) Autonomous driving is a mainstream application in the field of artificial intelligence. An autonomous driving technology relies on collaboration of computer vision, a radar, a monitoring apparatus, a global positioning system, and the like, to enable a motor vehicle to implement autonomous driving without active human operations. An autonomous driving vehicle uses various computing systems to help transport a passenger from one position to another position. Some autonomous driving vehicles may require some initial inputs or continuous inputs from an operator (such as a navigator, a driver, or a passenger). The autonomous driving vehicle allows the operator to switch from a manual operation mode to an autonomous driving mode or a mode between the manual operation mode and the autonomous driving mode. Because the autonomous driving technology does not require a human to drive a motor vehicle, a driving error of a human can be effectively avoided theoretically, occurrence of traffic accidents can be reduced, and highway transportation efficiency can be improved. Therefore, the autonomous driving technology has received increasing attention.

(4) However, there is no definite solution for how an autonomous driving vehicle passes through a barrier gate crossbar.

SUMMARY

(5) This application provides a method and an apparatus for passing through a barrier gate crossbar by a vehicle, and resolves a problem of how a vehicle passes through a barrier gate crossbar in an autonomous driving mode.

(6) To achieve the foregoing objective, this application uses the following technical solutions.

(7) According to a first aspect, this application provides a method for passing through a barrier gate crossbar by a vehicle. The method may be applied to a processor. For example, the processor includes a chip system. The method includes: The processor obtains data that is of N to-be-detected

barrier gate crossbars around a vehicle and that is collected by one or more sensors mounted on the vehicle, and the processor determines data of a target barrier gate crossbar from the data of the N to-be-detected barrier gate crossbars based on a pose of the target barrier gate crossbar, where the target barrier gate crossbar is a barrier gate crossbar of a lane on which the vehicle is located. Further, the processor determines a status of the target barrier gate crossbar based on the data of the target barrier gate crossbar, and controls, based on the status of the target barrier gate crossbar, the vehicle to pass through the target barrier gate crossbar. N is an integer greater than or equal to 1.

(8) In an autonomous driving mode, the vehicle may travel based on a road map. The road map may be a high-precision map, and records information about a static object around a lane. For example, the road map records information about a preplanned barrier gate crossbar in a lane. Therefore, in a traveling process, the vehicle may obtain the pose of the barrier gate crossbar of the lane on which the vehicle is located based on the road map. It may be understood that, the barrier gate crossbar of the lane on which the vehicle is located is the target barrier gate crossbar. The target barrier gate crossbar is a barrier gate crossbar that the vehicle is to pass through. The pose includes a position and an orientation. However, the vehicle does not know a state of the barrier gate crossbar that the vehicle is to pass through.

(9) Further, the vehicle senses the N to-be-detected barrier gate crossbars in a surrounding environment of the vehicle by using the one or more sensors, to obtain the data of the N to-be-detected barrier gate crossbars. However, the vehicle does not know data of which barrier gate crossbar in the data of the N to-be-detected barrier gate crossbars is the data of the barrier gate crossbar of the lane on which the vehicle is located. Therefore, the vehicle determines the data of the target barrier gate crossbar from the data of the N to-be-detected barrier gate crossbars. In this way, the status of the target barrier gate crossbar is determined based on the data of the target barrier gate crossbar, and the vehicle is controlled to pass through the target barrier gate crossbar.

(10) In one embodiment, the status of the target barrier gate crossbar includes an open/close state, and the open/close state of the target barrier gate crossbar includes open and close. The controlling, based on the status of the target barrier gate crossbar, the vehicle to pass through the target barrier gate crossbar includes: controlling, based on the open/close state of the target barrier gate crossbar, the vehicle to pass through the target barrier gate crossbar.

(11) For example, when the open/close state of the target barrier gate crossbar is open, the vehicle is controlled to travel, to smoothly pass through the target barrier gate crossbar.

(12) In another example, when the open/close state of the target barrier gate crossbar is close, the vehicle is controlled to stop, to avoid running into the target barrier gate crossbar.

(13) In another possible design, the status of the target barrier gate crossbar further includes a motion state, and the motion state of the target barrier gate crossbar includes ascending, descending, and static. The controlling, based on the status of the target barrier gate crossbar, the vehicle to pass through the target barrier gate crossbar includes: controlling, based on the open/close state and the motion state of the target barrier gate crossbar, the vehicle to pass through the target barrier gate crossbar.

(14) Vehicle traveling states in various possible cases of the open/close state and the motion state of the target barrier gate crossbar are described below.

(15) In a first case, when the open/close state of the target barrier gate crossbar is open, and the motion state of the target barrier gate crossbar is ascending, the vehicle is controlled to travel.

(16) In a second case, when the open/close state of the target barrier gate crossbar is open, and the motion state of the target barrier gate crossbar is static, the vehicle is controlled to travel.

(17) In a third case, when the open/close state of the target barrier gate crossbar is open, and the motion state of the target barrier gate crossbar is descending, the vehicle is controlled to stop.

(18) In a fourth case, when the open/close state of the target barrier gate crossbar is close, and the motion state of the target barrier gate crossbar is descending, the vehicle is controlled to stop.

(19) In a fifth case, when the open/close state of the target barrier gate crossbar is close, and the

motion state of the target barrier gate crossbar is static, the vehicle is controlled to stop.

(20) In a sixth case, when the open/close state of the target barrier gate crossbar is close, and the motion state of the target barrier gate crossbar is ascending, the vehicle is controlled to stop.

(21) In one embodiment, the determining an open/close state and a motion state of the target barrier gate crossbar based on the data of the target barrier gate crossbar includes: determining an angle of the target barrier gate crossbar based on the data of the target barrier gate crossbar, where the angle of the target barrier gate crossbar is an included angle between the target barrier gate crossbar and a reference straight line; and determining the open/close state and the motion state of the target barrier gate crossbar based on the angle of the target barrier gate crossbar.

(22) In some embodiments, determining the open/close state of the target barrier gate crossbar based on the angle of the target barrier gate crossbar includes: if the angle of the target barrier gate crossbar is greater than a first preset angle, determining that the open/close state of the target barrier gate crossbar is open; if the angle of the target barrier gate crossbar is less than a second preset angle, determining that the open/close state of the target barrier gate crossbar is close, where the second preset angle is less than the first preset angle; and if the angle of the target barrier gate crossbar is less than or equal to the first preset angle, and the angle of the target barrier gate crossbar is greater than or equal to the second preset angle, determining that the open/close state of the target barrier gate crossbar is an open/close state that is of the target barrier gate crossbar and that is determined at a previous moment.

(23) In some embodiments, determining the motion state of the target barrier gate crossbar based on the angle of the target barrier gate crossbar includes: if an i .sup.th angle of the target barrier gate crossbar is greater than an $(i-1)$.sup.th angle of the target barrier gate crossbar, determining that the motion state of the target barrier gate crossbar is ascending; and if the i .sup.th angle of the target barrier gate crossbar is less than the $(i-1)$.sup.th angle of the target barrier gate crossbar, determining that the motion state of the target barrier gate crossbar is descending, where the i .sup.th angle of the target barrier gate crossbar is determined based on the target barrier gate crossbar in an i .sup.th frame of image, the $(i-1)$.sup.th angle of the target barrier gate crossbar is determined based on the target barrier gate crossbar in an $(i-1)$.sup.th frame of image, and the i .sup.th frame of image is adjacent to the $(i-1)$.sup.th frame of image.

(24) In another embodiment, the method further includes: obtaining the pose of the target barrier gate crossbar based on a pre-configured road map by using the processor.

(25) In another embodiment, determining the target barrier gate crossbar included in the N to-be-detected barrier gate crossbars based on the data of the N to-be-detected barrier gate crossbars and the pose of the target barrier gate crossbar includes: determining first coordinates of the N to-be-detected barrier gate crossbars based on the data of the N to-be-detected barrier gate crossbars; determining coordinates of the target barrier gate crossbar based on the pose of the target barrier gate crossbar, where the first coordinates of the N to-be-detected barrier gate crossbars and the coordinates of the target barrier gate crossbar are coordinates in a two-dimensional coordinate system, or the first coordinates of the N to-be-detected barrier gate crossbars and the coordinates of the target barrier gate crossbar are coordinates in a three-dimensional coordinate system; determining N Euclidean distances based on the first coordinates of the N to-be-detected barrier gate crossbars and the coordinates of the target barrier gate crossbar; and determining data of a barrier gate crossbar corresponding to a smallest Euclidean distance in the N Euclidean distances as the data of the target barrier gate crossbar.

(26) For different sensors, types of obtained data of barrier gate crossbars may be different. For example, a sensor may be a camera or a LiDAR.

(27) In one embodiment, the first coordinates of the N to-be-detected barrier gate crossbars are the coordinates in the two-dimensional coordinate system, and the determining first coordinates of the N to-be-detected barrier gate crossbars based on the data of the N to-be-detected barrier gate crossbars includes: determining the first coordinates of the N to-be-detected barrier gate crossbars

based on the data of the N to-be-detected barrier gate crossbars and a target position detection model.

(28) In some embodiments, the coordinates of the target barrier gate crossbar are the coordinates in the two-dimensional coordinate system, and the determining coordinates of the target barrier gate crossbar based on the pose of the target barrier gate crossbar includes: determining a pose of the sensor based on a pose of the vehicle and an extrinsic parameter of the sensor; and determining the coordinates of the target barrier gate crossbar based on the pose of the target barrier gate crossbar, the pose of the sensor, and an intrinsic parameter of the sensor.

(29) In some embodiments, the method further includes: training sample data to generate the target position detection model.

(30) In another embodiment, the first coordinates of the N to-be-detected barrier gate crossbars are the coordinates in the three-dimensional coordinate system, and the determining first coordinates of the N to-be-detected barrier gate crossbars based on the data of the N to-be-detected barrier gate crossbars includes: determining three-dimensional models of the N to-be-detected barrier gate crossbars based on point cloud data of the N to-be-detected barrier gate crossbars, and determining the first coordinates of the N to-be-detected barrier gate crossbars based on the three-dimensional models of the N to-be-detected barrier gate crossbars.

(31) According to a second aspect, this application provides an apparatus for passing through a barrier gate crossbar by a vehicle. The apparatus includes: a processing unit, configured to obtain data that is of N to-be-detected barrier gate crossbars and that is collected by one or more sensors, where N is an integer greater than or equal to 1, the processing unit is further configured to determine data of a target barrier gate crossbar from the data of the N to-be-detected barrier gate crossbars based on a pose of the target barrier gate crossbar, the target barrier gate crossbar is a barrier gate crossbar of a lane on which the vehicle is located, and the processing unit is further configured to determine a status of the target barrier gate crossbar based on the data of the target barrier gate crossbar; and a control unit, configured to control, based on the status of the target barrier gate crossbar, the vehicle to pass through the target barrier gate crossbar.

(32) In one embodiment, the status of the target barrier gate crossbar includes an open/close state, and the open/close state of the target barrier gate crossbar includes an open state and a close state. The control unit is configured to control, based on the open/close state of the target barrier gate crossbar, the vehicle to pass through the target barrier gate crossbar.

(33) For example, when the open/close state of the target barrier gate crossbar is open, the vehicle is controlled to travel, to smoothly pass through the target barrier gate crossbar.

(34) In another example, when the open/close state of the target barrier gate crossbar is close, the vehicle is controlled to stop, to avoid running into the target barrier gate crossbar.

(35) In another embodiment, the status of the target barrier gate crossbar further includes a motion state, and the motion state of the target barrier gate crossbar includes ascending, descending, and static. The control unit is configured to control, based on the open/close state and the motion state of the target barrier gate crossbar, the vehicle to pass through the target barrier gate crossbar.

(36) Vehicle traveling states in various possible cases of the open/close state and the motion state of the target barrier gate crossbar are described below.

(37) In a first case, when the open/close state of the target barrier gate crossbar is open, and the motion state of the target barrier gate crossbar is ascending, the vehicle is controlled to travel.

(38) In a second case, when the open/close state of the target barrier gate crossbar is open, and the motion state of the target barrier gate crossbar is static, the vehicle is controlled to travel.

(39) In a third case, when the open/close state of the target barrier gate crossbar is open, and the motion state of the target barrier gate crossbar is descending, the vehicle is controlled to stop.

(40) In a fourth case, when the open/close state of the target barrier gate crossbar is close, and the motion state of the target barrier gate crossbar is descending, the vehicle is controlled to stop.

(41) In a fifth case, when the open/close state of the target barrier gate crossbar is close, and the

motion state of the target barrier gate crossbar is static, the vehicle is controlled to stop.

(42) In a sixth case, when the open/close state of the target barrier gate crossbar is close, and the motion state of the target barrier gate crossbar is ascending, the vehicle is controlled to stop.

(43) In an embodiment, the processing unit is configured to: determine an angle of the target barrier gate crossbar based on the data of the target barrier gate crossbar, where the angle of the target barrier gate crossbar is an included angle between the target barrier gate crossbar and a reference straight line; and determine the open/close state and the motion state of the target barrier gate crossbar based on the angle of the target barrier gate crossbar.

(44) In some embodiments, the processing unit is configured to: if the angle of the target barrier gate crossbar is greater than a first preset angle, determine that the open/close state of the target barrier gate crossbar is open; if the angle of the target barrier gate crossbar is less than a second preset angle, determine that the open/close state of the target barrier gate crossbar is close, where the second preset angle is less than the first preset angle; and if the angle of the target barrier gate crossbar is less than or equal to the first preset angle, and the angle of the target barrier gate crossbar is greater than or equal to the second preset angle, determine that the open/close state of the target barrier gate crossbar is an open/close state that is of the target barrier gate crossbar and that is determined at a previous moment.

(45) In some embodiments, the processing unit is configured to: if an i .sup.th angle of the target barrier gate crossbar is greater than an $(i-1)$.sup.th angle of the target barrier gate crossbar, determine that the motion state of the target barrier gate crossbar is ascending; and if the i .sup.th angle of the target barrier gate crossbar is less than the $(i-1)$.sup.th angle of the target barrier gate crossbar, determine that the motion state of the target barrier gate crossbar is descending, where the i .sup.th angle of the target barrier gate crossbar is determined based on the target barrier gate crossbar in an i .sup.th frame of image, the $(i-1)$.sup.th angle of the target barrier gate crossbar is determined based on the target barrier gate crossbar in an $(i-1)$.sup.th frame of image, and the i .sup.th frame of image is adjacent to the $(i-1)$.sup.th frame of image.

(46) In another embodiment, the processing unit is further configured to obtain the pose of the target barrier gate crossbar based on a pre-configured road map.

(47) In another embodiment, the processing unit is configured to: determine first coordinates of the N to-be-detected barrier gate crossbars based on the data of the N to-be-detected barrier gate crossbars; determine coordinates of the target barrier gate crossbar based on the pose of the target barrier gate crossbar, where the first coordinates of the N to-be-detected barrier gate crossbars and the coordinates of the target barrier gate crossbar are coordinates in a two-dimensional coordinate system, or the first coordinates of the N to-be-detected barrier gate crossbars and the coordinates of the target barrier gate crossbar are coordinates in a three-dimensional coordinate system; determine N Euclidean distances based on the first coordinates of the N to-be-detected barrier gate crossbars and the coordinates of the target barrier gate crossbar; and determine data of a barrier gate crossbar corresponding to a smallest Euclidean distance in the N Euclidean distances as the data of the target barrier gate crossbar.

(48) For different sensors, types of obtained data of barrier gate crossbars may be different. For example, a sensor may be a camera or a LiDAR.

(49) In one embodiment, the first coordinates of the N to-be-detected barrier gate crossbars are the coordinates in the two-dimensional coordinate system, and the processing unit is configured to determine the first coordinates of the N to-be-detected barrier gate crossbars based on the data of the N to-be-detected barrier gate crossbars and a target position detection model.

(50) In some embodiments, the coordinates of the target barrier gate crossbar are the coordinates in the two-dimensional coordinate system, and the processing unit is configured to: determine a pose of the sensor based on a pose of the vehicle and an extrinsic parameter of the sensor; and determine the coordinates of the target barrier gate crossbar based on the pose of the target barrier gate crossbar, the pose of the sensor, and an intrinsic parameter of the sensor.

(51) In some embodiments, the processing unit is further configured to train sample data to generate the target position detection model.

(52) In another embodiment, the first coordinates of the N to-be-detected barrier gate crossbars are the coordinates in the three-dimensional coordinate system, and the processing unit is configured to: determine three-dimensional models of the N to-be-detected barrier gate crossbars based on point cloud data of the N to-be-detected barrier gate crossbars, and determine the first coordinates of the N to-be-detected barrier gate crossbars based on the three-dimensional models of the N to-be-detected barrier gate crossbars.

(53) According to a third aspect, an apparatus for passing through a barrier gate crossbar by a vehicle is provided. The apparatus includes a processor and a memory. The memory is configured to store computer programs and instructions. The processor receives data that is of N to-be-detected barrier gate crossbars and that is collected by one or more sensors. The processor is configured to execute the computer programs and instructions to implement the method for passing through a barrier gate crossbar by a vehicle according to the first aspect, where N is an integer greater than or equal to 1.

(54) According to a fourth aspect, a computer program product is provided. The computer program product includes: computer program code, where when the computer program code is run, the method for passing through a barrier gate crossbar by a vehicle according to the first aspect is implemented.

(55) According to a fifth aspect, this application provides a chip system. The chip system includes a processor, configured to implement functions of the processor in the method according to the first aspect. In one embodiment, the chip system further includes a memory, configured to store program instructions and/or data. The chip system may include a chip, or include a chip and other discrete devices.

(56) According to a sixth aspect, this application provides a computer-readable storage medium. The computer-readable storage medium stores computer programs, where when the computer programs are run, the method for passing through a barrier gate crossbar by a vehicle according to the first aspect is implemented.

(57) According to a seventh aspect, this application provides a vehicle, including one or more sensors and the apparatus for passing through a barrier gate crossbar by a vehicle according to the third aspect. The one or more sensors are configured to obtain data of a plurality of to-be-detected barrier gate crossbars. The apparatus is configured to implement the method for passing through a barrier gate crossbar by a vehicle according to the first aspect with auxiliary execution by the one or more sensors.

(58) In this application, names of the apparatus for passing through a barrier gate crossbar by a vehicle, the vehicle, and the processor do not limit the devices themselves. During actual implementation, the devices may appear with other names. Provided that functions of the devices are similar to those of this application, the devices fall within the scope of the claims of this application and equivalent technologies thereof.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) FIG. 1 is a schematic structural diagram of a vehicle according to an embodiment of this application;

(2) FIG. 2 is a schematic structural diagram of a computer system according to an embodiment of this application;

(3) FIG. 3 is a schematic diagram of application of a cloud-side instruction automobile according to an embodiment of this application;

- (4) FIG. 4 is a flowchart of a method for passing through a barrier gate crossbar by a vehicle according to an embodiment of this application;
- (5) FIG. 5 is a schematic diagram of barrier gate crossbars in a surrounding environment of a vehicle according to an embodiment of this application;
- (6) FIG. 6 is a flowchart of a method for passing through a first barrier gate crossbar by a vehicle according to an embodiment of this application;
- (7) FIG. 7 is a schematic diagram of a first barrier gate crossbar in a surrounding environment of a vehicle according to an embodiment of this application;
- (8) FIG. 8 is a flowchart of a method for passing through a first barrier gate crossbar by a vehicle according to an embodiment of this application;
- (9) FIG. 9 is a schematic diagram of an angle of a first barrier gate crossbar according to an embodiment of this application;
- (10) FIG. 10(a) to FIG. 10(c) are a schematic diagram of an open/close state of a first barrier gate crossbar according to an embodiment of this application;
- (11) FIG. 11(a) and FIG. 11(b) are a schematic diagram of a motion state of a first barrier gate crossbar according to an embodiment of this application;
- (12) FIG. 12 is a schematic diagram of a sequence queue of angles of a barrier gate crossbar according to an embodiment of this application;
- (13) FIG. 13(a) to FIG. 15(d) are schematic diagrams of passing through a first barrier gate crossbar by a vehicle according to an embodiment of this application; and
- (14) FIG. 16 is a schematic diagram of composition of an apparatus for passing through a barrier gate crossbar by a vehicle according to an embodiment of this application.

DESCRIPTION OF EMBODIMENTS

- (15) In the specification, claims, and accompanying drawings of this application, the terms “first”, “second”, “third” and the like are intended to distinguish between different objects but do not limit a particular order.
- (16) In addition, in the embodiments of this application, the word “example” or “for example” is used to represent giving an example, an illustration, or a description. Any embodiment or design scheme described as the word “example” or “for example” in the embodiments of this application should not be explained as being more preferred or having more advantages than another embodiment or design scheme. Exactly, use of the word “example” or “for example” or the like is intended to present a relative concept in a specific manner.
- (17) The following describes the technical solutions in the embodiments of this application with reference to the accompanying drawings in the embodiments of this application. Apparently, the described embodiments are merely a part rather than all of the embodiments of this application. All other embodiments obtained by a person of ordinary skill in the art based on the embodiments of this application without creative efforts shall fall within the protection scope of this application.
- (18) For clear and concise description of the following embodiments, a brief description of related technologies is first provided.
- (19) FIG. 1 is a functional block diagram of a vehicle **100** according to an embodiment of this application. In an embodiment, the vehicle **100** is configured into a complete or partial autonomous driving mode. For example, the vehicle **100** may control itself in an autonomous driving mode, and through human operations, may determine current states of the vehicle and a surrounding environment of the vehicle, determine a possible behavior of at least one another vehicle in the surrounding environment, and determine a confidence level corresponding to a possibility that the another vehicle executes the possible behavior, and control the vehicle **100** based on determined information. When the vehicle **100** is in the autonomous driving mode, the vehicle **100** may be set to operate when there is no interaction with a human.
- (20) The vehicle **100** may include various subsystems, for example, a travel system **102**, a sensor system **104**, a control system **106**, one or more peripheral devices **108** and a power supply **110**, a

computer system **112**, and a user interface **116**. In some embodiments, the vehicle **100** may include more or fewer subsystems, and each subsystem may include a plurality of elements. In addition, each subsystem and element of the vehicle **100** may be connected to each other in a wired or wireless manner.

(21) The travel system **102** may include a component providing power motion to the vehicle **100**. In an embodiment, the travel system **102** may include an engine **118**, an energy source **119**, a transmission device **120**, and a wheel/tire **121**. The engine **118** may be an internal combustion engine, an electric motor, an air compression engine, or a combination of other types of engines, such as a hybrid engine including a gasoline engine and an electric motor. Another example is a hybrid engine including an internal combustion engine and an air compression engine. The engine **118** converts the energy source **119** into mechanical energy.

(22) Examples of the energy source **119** include gasoline, diesel, other petroleum-based fuels, propane, other compressed gas-based fuels, ethanol, a solar panel, a battery, and other power sources. The energy source **119** may also provide energy to other systems of the vehicle **100**.

(23) The transmission device **120** may transmit mechanical power from the engine **118** to the wheel/tire **121**. The transmission device **120** may include a gear box, a differential, and a drive shaft. In an embodiment, the transmission device **120** may further include other devices, such as a clutch. For example, the drive shaft may include one or more shafts that may be coupled to one or more wheels/tires **121**.

(24) The sensor system **104** may include several sensors that sense information about a surrounding environment of the vehicle **100**. For example, the sensor system **104** may include a positioning system **122** (the positioning system may be a global positioning system (GPS), or may be a Beidou system or another positioning system), an inertial measurement unit (IMU) **124**, a radar **126**, a laser rangefinder **128**, and a camera **130**. The sensor system **104** may also include sensors of internal systems of the monitored vehicle **100** (for example, an in-vehicle air quality monitor, a fuel gauge, and an oil temperature gauge). Sensor data from one or more of these sensors may be used for detecting an object and corresponding characteristics (a position, a shape, a direction, a speed, and the like) of the object. Such detection and recognition are key functions of safe operation of the vehicle **100**.

(25) The positioning system **122** may be configured to estimate a geographic location of the vehicle **100**. The inertial measurement unit **124** is configured to sense a pose (a position and an orientation) change of the vehicle **100** based on an inertial acceleration. In an embodiment, the inertial measurement unit **124** may be a combination of an accelerometer and a gyroscope.

(26) The radar **126** may sense an object in the surrounding environment of the vehicle **100** by using a radio signal. In some embodiments, in addition to sensing an object, the radar **126** may also be configured to sense a speed and/or an advancing direction of the object. For example, the radar **126** may be a LiDAR.

(27) The laser rangefinder **128** may sense an object in an environment in which the vehicle **100** is located by using laser. In some embodiments, the laser rangefinder **128** may include one or more laser sources, a laser scanner, one or more detectors, and other system components.

(28) The camera **130** may be configured to capture a plurality of images of the surrounding environment of the vehicle **100**. The camera **130** may be a still camera or a video camera.

(29) The control system **106** controls operations of the vehicle **100** and components of the vehicle **100**. The control system **106** may include various elements, including a steering system **132**, a throttle **134**, a brake unit **136**, a sensor fusion algorithm **138**, a computer vision system **140**, a route control system **142**, and an obstacle avoidance system **144**.

(30) The steering system **132** is operable to adjust an advancing direction of the vehicle **100**. For example, in an embodiment, the steering system **132** may be a steering wheel system.

(31) The throttle **134** is configured to: control an operating speed of the engine **118** and further control a speed of the vehicle **100**.

(32) The brake unit **136** is configured to control the vehicle **100** to decelerate. The brake unit **136** may slow down the wheel/tire **121** by using a friction force. In other embodiments, the brake unit **136** may convert kinetic energy of the wheel/tire **121** into a current. The brake unit **136** may also slow down a rotation speed of the wheel/tire **121** by using other forms, to control the speed of the vehicle **100**.

(33) The computer vision system **140** is operable to process and analyze the images captured by the camera **130**, to recognize objects and/or features in the surrounding environment of the vehicle **100**. The objects and/or features may include traffic signals, road boundaries, and obstacles. The computer vision system **140** may use an object recognition algorithm, a structure from motion (Structure from Motion, SFM) algorithm, video tracking, and other computer vision technologies. In some embodiments, the computer vision system **140** may be configured to: map an environment, track an object, estimate a speed of the object, and the like.

(34) The route control system **142** is configured to determine a travel route of the vehicle **100**. In some embodiments, the route control system **142** may determine the travel route for the vehicle **100** with reference to data from the sensor fusion algorithm **138**, the positioning system **122**, and one or more predetermined maps.

(35) The obstacle avoidance system **144** is configured to recognize, evaluate, and avoid or surmount, in other manners, potential obstacles in the environment of the vehicle **100**.

(36) Certainly, in an example, the control system **106** may additionally or alternatively include components other than those shown and described. Alternatively, some of the components shown above may be reduced.

(37) The vehicle **100** interacts with an external sensor, another vehicle, another computer system, or a user by using the peripheral device **108**. The peripheral device **108** may include a wireless communications system **146**, a vehicle-mounted computer **148**, a microphone **150**, and/or a speaker **152**.

(38) In some embodiments, the peripheral device **108** provides a means for a user of the vehicle **100** to interact with the user interface **116**. For example, the vehicle-mounted computer **148** may provide information to the user of the vehicle **100**. The user interface **116** may also operate the vehicle-mounted computer **148** to receive a user input. The vehicle-mounted computer **148** may be operated by using a touchscreen. In other cases, the peripheral device **108** may provide a means for the vehicle **100** to communicate with other devices located in the vehicle. For example, the microphone **150** may receive audio (for example, a voice command or another audio input) from the user of vehicle **100**. Similarly, the speaker **152** may output audio to the user of the vehicle **100**.

(39) The wireless communications system **146** may wirelessly communicate with one or more devices directly or by using a communications network. For example, the wireless communications system **146** may use 3G cellular communication, such as code division multiple access (CDMA), EVDO, global system for mobile communications (GSM)/general packet radio service (GPRS), or 4G cellular communication, such as LTE, or 5G cellular communication. The wireless communications system **146** may communicate with a wireless local area network (WLAN) by using Wi-Fi. In some embodiments, the wireless communications system **146** may communicate directly with a device by using an infrared link, Bluetooth, or ZigBee. Other wireless protocols, such as various vehicle communications systems, for example, the wireless communication system **146** may include one or more dedicated short range communications (DSRC) devices, which may include public and/or private data communication between vehicles and/or roadside stations.

(40) The power supply **110** may provide power to various components of the vehicle **100**. In an embodiment, the power supply **110** may be a rechargeable lithium-ion or lead-acid battery. One or more battery packs of such batteries may be configured to provide power to various components of the vehicle **100**. In some embodiments, the power supply **110** and the energy source **119** may be implemented together, such as in some all-electric vehicles.

(41) Some or all of the functions of the vehicle **100** are controlled by the computer system **112**. The

computer system **112** may include at least one processor **113** that executes instructions **115** stored in a non-transitory computer-readable medium such as a data storage apparatus **114**. The computer system **112** may alternatively be a plurality of computing devices that control individual components or subsystems of the vehicle **100** in a distributed manner. The data storage apparatus **114** may be a memory.

(42) The processor **113** may be any conventional processor, such as a commercially available central processing unit (CPU). Alternatively, the processor may be a dedicated device such as an application-specific integrated circuit (ASIC) or another hardware-based processor. Although FIG. **1** functionally illustrates the processor, the memory, and other elements of the computer system **112** in a same block, a person of ordinary skill in the art should understand that the processor, the computer, or the memory may actually include a plurality of processors, computers, or memories that may not be stored in a same physical housing. For example, the memory may be a hard disk drive or another storage medium located in a housing different from that of the computer system **112**. Therefore, reference to a processor or a computer will be understood as reference to a set including processors or computers or memories that may or may not operate in parallel. Different from using a single processor to perform the operations described herein, some components, such as a steering component and a deceleration component, may each have its own processor that performs only calculation related to component-specific functions.

(43) In various aspects described herein, the processor may be located far away from the vehicle **100** and perform wireless communication with the vehicle **100**. In other aspects, some of the processes described herein are performed by a processor disposed in the vehicle **100**, and others are performed by a remote processor, including taking operations necessary for single manipulation.

(44) In some embodiments, the data storage apparatus **114** may include instructions **115** (for example, program logics), and the instructions **115** may be executed by the processor **113**, to perform various functions of the vehicle **100**, including those described above. The data storage apparatus **114** may also include additional instructions, including instructions to send data to, receive data from, interact with, and/or control one or more of the travel system **102**, the sensor system **104**, the control system **106**, and the peripheral device **108**.

(45) In addition to the instructions **115**, the data storage apparatus **114** may also store data, such as a road map, route information, a position, a direction, and a speed of the vehicle, other such vehicle data, and other information. Such information may be used by the vehicle **100** and the computer system **112** during operation of the vehicle **100** in autonomous, semi-autonomous, and/or manual modes.

(46) The user interface **116** is configured to provide information to or receive information from the user of the vehicle **100**. In some embodiments, the user interface **116** may include one or more input/output devices in a set of peripheral devices **108**, such as the wireless communications system **146**, the vehicle-mounted computer **148**, the microphone **150**, and the speaker **152**.

(47) The computer system **112** may control the functions of the vehicle **100** based on inputs received from various subsystems (for example, the travel system **102**, the sensor system **104**, and the control system **106**) and the user interface **116**. For example, the computer system **112** may control, by using an input from the control system **106**, the steering system **132** to avoid obstacles detected by the sensor system **104** and the obstacle avoidance system **144**. In some embodiments, the computer system **112** is operable to provide control over many aspects of the vehicle **100** and the subsystems of the vehicle **100**.

(48) For example, when the vehicle **100** is in an autonomous driving mode, the processor **113** may obtain a road map from the data storage apparatus **114**, and learn, based on the road map, a pose of a barrier gate crossbar of a lane on which the vehicle **100** is located. For ease of description, in the following, the barrier gate crossbar of the lane on which the vehicle **100** is located is referred to as a target barrier gate crossbar. The processor **113** may also receive data that is of a plurality of to-be-detected barrier gate crossbars in a surrounding environment and that is obtained by the sensor

system **104**, determine data of the target barrier gate crossbar from the data of the plurality of to-be-detected barrier gate crossbars in the surrounding environment based on a pose of the target barrier gate crossbar, and determine a status of the target barrier gate crossbar by using the data of the target barrier gate crossbar, and control, based on the status of the target barrier gate crossbar, the vehicle **100** to pass through the target barrier gate crossbar.

(49) In this specification, the status of the target barrier gate crossbar includes an open/close state and a motion state. The open/close state includes open and close. It may be understood that, that the target barrier gate crossbar is in an open state may mean that an angle of the target barrier gate crossbar is greater than a particular angle. That the target barrier gate crossbar is in a close state may mean that the angle of the target barrier gate crossbar is less than a particular angle. In some embodiments, that the target barrier gate crossbar is in a close state may mean that the target barrier gate crossbar is completely closed. In other words, the target barrier gate crossbar is parallel to the ground.

(50) The motion state is a state of a motion speed of an object relative to a reference system when the object performs mechanical motion. Content of the motion state includes the motion speed of the object (a variation of a position vector of the object per unit time, namely, displacement of the object per unit time) and a motion direction of the object. Static or motion also falls within a range of the motion state.

(51) Physically, when the speed of the object changes and/or the motion direction of the object changes, the motion state of the object changes. Changes in the speed of the object include that the object changes from fast to slow, changes from slow to fast, changes from static to motion, and changes from motion to static. Changes in the motion direction of the object include upward rotation and downward rotation of the object.

(52) In this specification, the motion state of the target barrier gate crossbar includes ascending, descending, and static.

(53) In some embodiments, one or more of these components may be mounted separate from the vehicle **100** or may be associated with the vehicle **100**. For example, the data storage apparatus **114** may exist partially or completely separate from the vehicle **100**. The components may be communicatively coupled together in a wired and/or wireless manner.

(54) In some embodiments, the foregoing components are merely an example. During actual application, components in the foregoing modules may be added or deleted based on an actual requirement. FIG. **1** should not be construed as a limitation on the embodiments of this application.

(55) An autonomous driving automobile traveling on a road, such as the foregoing vehicle **100**, may recognize an object in the surrounding environment of the vehicle **100**, to determine adjustment on a current speed. The object may be another vehicle, a traffic control device, or another type of object. In some examples, each recognized object may be considered independently, and based on respective characteristics of the object, such as a current speed of the object, an acceleration of the object, a distance from the vehicle, a speed to be obtained after adjustment by the autonomous driving automobile may be determined.

(56) In some embodiments, the vehicle **100** or a computing device (such as the computer system **112**, the computer vision system **140**, or the data storage apparatus **114** in FIG. **1**) associated with the vehicle **100** may predict a behavior of the recognized object based on the characteristics of the recognized object and a state of the surrounding environment (such as traffic, rain, and ice on a road). In some embodiments, each recognized object depends on the behavior of each other. Therefore, the behavior of a single recognized object may alternatively be predicted by considering all the recognized objects together. The vehicle **100** can adjust the speed of the vehicle **100** based on the predicted behavior of the recognized object. In other words, the vehicle **100** can determine what steady state the vehicle **100** needs to adjust to (for example, accelerate, decelerate, or stop) based on the predicted behavior of the object. In this process, other factors such as a lateral position of the vehicle **100** on a road on which the vehicle **100** travels, a curvature of the road, and a

proximity between static and dynamic objects may also be considered, to determine the speed of the vehicle **100**.

(57) In addition to providing instructions to adjust the speed of the vehicle **100**, the computing device may also provide instructions to modify a steering angle of the vehicle **100**, so that the vehicle **100** follows a given trajectory and/or maintains safe lateral and longitudinal distances from an object (such as a car in an adjacent lane on the road) near the vehicle **100**.

(58) The vehicle **100** may be a car, a truck, a motorcycle, a bus, a boat, an airplane, a helicopter, a lawn mower, a recreational vehicle, a playground vehicle, a construction device, a tram, a golf cart, a train, a cart, or the like. This is not particularly limited in the embodiments of this application.

(59) In an embodiment, as shown in FIG. 2, a computer **101** includes a processor **103**, and the processor **103** is coupled to a system bus **105**. The processor **103** may be one or more processors, and each processor may include one or more processor cores. A display adapter (video adapter) **107**, where the display adapter **107** may drive a display **109**, and the display **109** is coupled to the system bus **105**. The system bus **105** is coupled to an input/output bus (I/O BUS or I/O bus) by using a bus bridge **111**. An I/O interface **115** is coupled to the I/O bus. The I/O interface **115** communicates with a plurality of I/O devices, such as an input device **117** (for example, a keyboard, a mouse, or a touchscreen), a media tray **121** (for example, a CD-ROM or a multimedia interface), a transceiver **123** (which can send and/or receive a radio communications signal), a camera **155** (which can capture static and dynamic digital video images), and an external USB port **125**. In some embodiments, an interface connected to the I/O interface **115** may be a USB port.

(60) The processor **103** may be any conventional processor, including a reduced instruction set computing (“RISC”) processor, a complex instruction set computing (“CISC”) processor, or a combination thereof. In some embodiments, the processor may be a dedicated apparatus such as an application-specific integrated circuit (“ASIC”). In some embodiments, the processor **103** may be a neural network processor or a combination of the neural network processor and the foregoing conventional processor.

(61) In some embodiments, in various embodiments described herein, the computer **101** may be located far away from the vehicle **100** and may wirelessly communicate with the vehicle **100**. In other aspects, some of the processes described herein are performed by the processor disposed in the vehicle **100**, and others are performed by the remote processor, including taking actions necessary for single manipulation.

(62) The computer **101** may communicate with a software deployment server **149** by using a network interface **129**. The network interface **129** is a hardware network interface, such as a network adapter. The network **127** may be an external network, such as the Internet, or an internal network, such as the Ethernet or a virtual private network (for example, a virtual private network (VPN)). In some embodiments, the network **127** may alternatively be a wireless network, for example, a Wi-Fi network or a cellular network.

(63) A hard disk drive interface is coupled to the system bus **105**. The hardware drive interface is connected to a hard disk drive. A system memory **135** is coupled to the system bus **105**. Data run in the system memory **135** may include an operating system (OS) **137** and an application **143** of the computer **101**.

(64) The operating system includes a shell **139** and a kernel **141**. The shell **139** is an interface between a user and the kernel of the operating system. The shell is an outermost layer of the operating system. The shell manages interaction between the user and the operating system, waits for an input of the user, explains the input of the user to the operating system, and processes various output results of the operating system.

(65) The kernel **141** includes those parts of the operating system that are used for managing memories, files, peripherals, and system resources. The kernel directly interacts with hardware. The kernel of the operating system usually runs processes and provides inter-process communication, CPU time slice management, interruption, memory management, I/O management, and the like.

(66) The application **143** includes a related program **147** controlling autonomous driving of an automobile, for example, a program managing interaction between an autonomous driving automobile and an obstacle on a road, a program controlling a route or a speed of the autonomous driving automobile, or a program controlling interaction between the autonomous driving automobile and another autonomous driving automobile on the road. The application **143** also exists on a system of the software deployment server **149**. In an embodiment, when the application **143** needs to be executed, the computer **101** may download the application **143** from the software deployment server **149**.

(67) For example, the application **143** may include a related program for the vehicle **100** to pass through a barrier gate crossbar. The processor **103** receives the data that is of the plurality of to-be-detected barrier gate crossbars and that is obtained by the sensor system **104**, obtains the pose of the target barrier gate crossbar based on a road map, determines the data of the target barrier gate crossbar from the data of the plurality of to-be-detected barrier gate crossbars by using the pose of the target barrier gate crossbar, and determines the status of the target barrier gate crossbar by using the data of the target barrier gate crossbar. If the processor **103** is located in the vehicle **100**, the processor **103** may control, based on the status of the target barrier gate crossbar, the vehicle **100** to pass through the target barrier gate crossbar. If the processor **103** is located far away from the vehicle **100**, the processor **103** may send a control instruction to the processor **113**, and the processor **113** controls the travel system **102** of the vehicle **100** to pass through the target barrier gate crossbar.

(68) A sensor **153** is associated with the computer **101**. The sensor **153** is configured to detect an environment around the computer **101**. For example, the sensor **153** may detect an animal, an automobile, an obstacle, a crosswalk, and the like. Further, the sensor **153** may also detect an environment around an object such as the foregoing animal, automobile, obstacle, or crosswalk, for example, an environment around an animal, for example, another animal that appears around the animal, weather conditions, or brightness of a surrounding environment. In some embodiments, if the computer **101** is located in an autonomous driving automobile, the sensor **153** may be a camera, an infrared sensor, a chemical detector, a microphone, or the like.

(69) For example, the processor **153** may detect the data of the plurality of to-be-detected barrier gate crossbars in the surrounding environment of the vehicle **100**, the processor **103** determines two-dimensional coordinates of the plurality of to-be-detected barrier gate crossbars by using a target position detection model and the data of the plurality of to-be-detected barrier gate crossbars, to determine the target barrier gate crossbar from the plurality of to-be-detected barrier gate crossbars based on the two-dimensional coordinates of the plurality of to-be-detected barrier gate crossbars, and determine the state of the target position detection model, and control the vehicle **100** to pass through the target barrier gate crossbar. The target position detection model may be obtained by training based on sample data.

(70) In some embodiments, an artificial intelligence (AI) chip is disposed in the computer **101**, and the AI chip periodically trains the received sample data to generate the target position detection model. The AI chip may also be referred to as a neural network processor (NPU). For example, the AI chip may be the processor **103**. The processor **103** stores target position detection models, or, these target position detection models are stored in the memory by using the system bus **105**. A form of the AI chip may be a chip or another physical component, for example, may be a training chip used for constructing a neural network model, or may be an inference chip that performs inference by using a neural network model. The neural network model may also be referred to as an artificial neural network, a neural network (NNs), or a connection model. The so-called “artificial neural network” is an algorithmic mathematical model that performs distributed parallel information processing by using a structure similar to brain synaptic connections. The artificial neural network relies on complexity of the system and adjusts connections between a large quantity of internal nodes to process information. The AI chip periodically trains the sample data, to

generate the target position detection model, to better adapt to a change of the target position detection model.

(71) In some embodiments, the computer system **112** may also receive information from or transfer information to other computer systems. Alternatively, the sensor data collected by the sensor system **104** of the vehicle **100** may be transferred to another computer for processing. For example, data from the computer system **112** may be transmitted via a network to a cloud service center for further processing. For example, FIG. 3 is a schematic diagram of composition of a vehicle **100** and a cloud service center according to an embodiment of this application. The vehicle **100** may exchange data with the cloud service center **320** by using a network **310**.

(72) The network **310** and intermediate nodes may include various configurations and protocols, including the Internet, the World Wide Web, an intranet, a virtual private network, a wide area network, a local area network, a private network using proprietary communication protocols of one or more companies, the Ethernet, Wi-Fi, and HTTP, and various combinations thereof. Such communication may be performed by any device that can transmit data to and from other computers, such as a modem or a wireless interface.

(73) In an example, the cloud service center **320** may include a server including a plurality of computers, such as a load balance server farm, which exchanges information with different nodes of the network **310** for the purpose of receiving data from the computer system **112**, processing the data, and transmitting the data. The cloud service center **320** may be configured in a way similar to a way in which the computer system **112** is configured, and has a processor **330**, a memory **340**, an instruction **350**, and data **360**.

(74) The cloud service center **320** runs, based on received data, a related program controlling autonomous driving of an automobile stored in the cloud service center **320**, to control the vehicle **100**. The related program controlling autonomous driving of an automobile may be a program managing interaction between an autonomous driving automobile and an obstacle on a road, a program controlling a route or a speed of the autonomous driving automobile, or a program controlling interaction between the autonomous driving automobile and another autonomous driving automobile on the road.

(75) In some examples, the cloud service center **320** sends a suggested solution for possible driving conditions in the environment (for example, telling an obstacle ahead and how to get around it) to the vehicle **100**. For example, the cloud service center **320** may assist the vehicle **100** in determining how to travel when facing a particular obstacle in the environment. The cloud service center **320** sends, to the vehicle **100**, a response indicating how the vehicle **100** should travel in a given scene. For example, the cloud service center **320** may confirm, based on the collected sensor data, that there is a temporary stop sign on a road ahead, and further determine, based on a “lane closed” sign and sensor data of a construction vehicle on the lane, that the lane is closed due to construction. Correspondingly, the cloud service center **320** sends a suggested operation mode (for example, indicating the vehicle to change lanes onto another road) for the vehicle **100** to pass through the obstacle. When the cloud service center **320** observes a video stream in an operating environment of the cloud service center **320** and has confirmed that the vehicle **100** can safely and successfully pass through the obstacle, the operations used for the vehicle **100** may be added to a driving information map. Correspondingly, this information may be sent to other vehicles that may encounter a same obstacle in the region, to assist the other vehicles not only in recognizing the closed lane but also in knowing how to pass. In another example, the cloud service center **320** may determine, based on the collected sensor data, that there is a barrier gate crossbar ahead of the road on which the vehicle **100** is located. Correspondingly, the cloud service center **320** sends a suggested operation mode for the vehicle **100** to pass through the barrier gate crossbar of the road on which the vehicle **100** is located.

(76) Next, the following describes in detail, with reference to the accompanying drawings, that the vehicle **100** passes through the barrier gate crossbar of the road on which the vehicle **100** is located

in an autonomous driving mode.

(77) FIG. 4 is a flowchart of a method for passing through a barrier gate crossbar by a vehicle according to an embodiment of this application. Description is provided herein by using an example in which a processor **113** in a vehicle **100** controls, based on data obtained by a sensor system **104**, the vehicle **100** to pass through a barrier gate crossbar of a road on which the vehicle **100** is located.

(78) **S401**: One or more sensors in the vehicle **100** collect data of N to-be-detected barrier gate crossbars.

(79) The sensor system **104** includes one or more sensors. The one or more sensors may be mounted at positions such as front, rear, and side positions of the vehicle **100**. In a traveling process, the vehicle **100** may sense an object in a surrounding environment of the vehicle **100** by using the one or more sensors, to avoid the object, so that the vehicle **100** can normally travel, thereby avoiding traffic accidents. For example, when the vehicle **100** enters or exits from a place such as a park or a parking lot, the data of the N to-be-detected barrier gate crossbars in the surrounding environment of the vehicle **100** may be sensed by using the one or more sensors. N is an integer greater than or equal to 1. It may be understood that, the N to-be-detected barrier gate crossbars include a barrier gate crossbar of a lane on which the vehicle **100** is located and a barrier gate crossbar of a lane opposite to the vehicle **100**.

(80) For example, FIG. 5 is a schematic diagram of barrier gate crossbars in the surrounding environment of the vehicle **100**. As shown in FIG. 5, the vehicle **100** may sense the barrier gate crossbars in the surrounding environment of the vehicle **10** by using the one or more sensors. In some embodiments, the barrier gate crossbars in the surrounding environment of the vehicle **100** include the barrier gate crossbar of the lane on which the vehicle **100** is located and the barrier gate crossbar of the lane opposite to the vehicle **100**. For example, a first barrier gate crossbar **501** shown in FIG. 5 is the barrier gate crossbar of the lane on which the vehicle **100** is located, and a second barrier gate crossbar **502** is the barrier gate crossbar of the lane opposite to the vehicle **100**.

(81) Types of data of barrier gate crossbars obtained by different sensors may be different.

(82) For example, if the sensor is a camera **130**, the data of the barrier gate crossbars is image data. The image data is a set of grayscale values (pixel) that are of pixels and that are represented by values. It may be understood that, the image data is two-dimensional data, such as an image of the first barrier gate crossbar and an image of the second barrier gate crossbar shown in FIG. 5.

(83) In another example, if the sensor is a radar **126**, the data of the barrier gate crossbars is point cloud data. The point cloud data is a set of points for representing a shape of an object. It may be understood that, the point cloud data is three-dimensional data, and each point includes three-dimensional coordinates. Some points may further include color information (RGB) or reflection intensity information.

(84) In an autonomous driving mode, the vehicle **100** may travel based on a road map. The road map may be a high-precision map, and records information about a static object around a lane. For example, the road map records information about a preplanned barrier gate crossbar in a lane. Therefore, in a process in which the vehicle **100** travels based on the road map, the vehicle **100** may obtain a pose of the barrier gate crossbar of the lane on which the vehicle **100** is located. It may be understood that, the barrier gate crossbar of the lane on which the vehicle **100** is located is a target barrier gate crossbar. The target barrier gate crossbar is a barrier gate crossbar that the vehicle **100** is to pass through. However, the vehicle **100** does not know a state of the barrier gate crossbar that the vehicle **100** is to pass through.

(85) Further, the vehicle **100** may sense the N to-be-detected barrier gate crossbars in the surrounding environment of the vehicle **100** by using the one or more sensors, to obtain the data of the N to-be-detected barrier gate crossbars. However, the vehicle **100** does not know data of which barrier gate crossbar in the data of the N to-be-detected barrier gate crossbars is the data of the barrier gate crossbar of the lane on which the vehicle **100** is located. Therefore, the vehicle **100**

determines the data of the target barrier gate crossbar from the data of the N to-be-detected barrier gate crossbars based on the pose of the target barrier gate crossbar, and determines the status of the target barrier gate crossbar by using the data of the target barrier gate crossbar. In this way, the vehicle **100** passes through the target barrier gate crossbar based on the status of the target barrier gate crossbar. Refer to descriptions of the following **S402** to **S404** for detailed explanations of passing through the target barrier gate crossbar.

(86) **S402**: The processor **113** determines the data of the target barrier gate crossbar from the data of the N to-be-detected barrier gate crossbars based on the pose of the target barrier gate crossbar.

(87) In the autonomous driving mode, the vehicle **100** travels based on a planned road. For example, the vehicle **100** travels based on a pre-configured road map. The road map not only includes lane information, but also includes object information in the surrounding environment of a lane, for example, poses of the barrier gate crossbars in the surrounding environment of the vehicle **100**. Therefore, the vehicle **100** may determine the data of the barrier gate crossbar of the lane on which the vehicle **100** is located from the detected data of the barrier gate crossbars by using the poses of the barrier gate crossbars in the surrounding environment. The processor **113** may receive the data detected by the one or more sensors.

(88) The processor **113** determines first coordinates of each of the N to-be-detected barrier gate crossbars based on data of the to-be-detected barrier gate crossbar; determines coordinates of the target barrier gate crossbar based on the pose of the target barrier gate crossbar; determines N Euclidean distances based on the first coordinates of the N to-be-detected barrier gate crossbars and the coordinates of the target barrier gate crossbar; and determines data of a barrier gate crossbar corresponding to a smallest Euclidean distance in the N Euclidean distances as the data of the target barrier gate crossbar.

(89) **S403**: The processor **113** determines the status of the target barrier gate crossbar based on the data of the target barrier gate crossbar.

(90) **S404**: The processor **113** controls, based on the status of the target barrier gate crossbar, the vehicle **100** to pass through the target barrier gate crossbar.

(91) The status of the target barrier gate crossbar includes an open/close state, and the open/close state of the target barrier gate crossbar includes open and close. The processor **113** controls, based on the open/close state of the target barrier gate crossbar, the vehicle **100** to pass through the target barrier gate crossbar. For example, when the open/close state of the target barrier gate crossbar is open, the vehicle **100** is controlled to travel. In another example, when the open/close state of the target barrier gate crossbar is close, the vehicle **100** is controlled to stop.

(92) In some embodiments, the status of the target barrier gate crossbar further includes a motion state, and the motion state of the target barrier gate crossbar includes ascending, descending, and static. The processor **113** controls, based on the open/close state and the motion state of the target barrier gate crossbar, the vehicle **100** to pass through the target barrier gate crossbar.

(93) In one embodiment, when the open/close state of the target barrier gate crossbar is open, and the motion state of the target barrier gate crossbar is ascending, the vehicle **100** is controlled to travel.

(94) In another embodiment, when the open/close state of the target barrier gate crossbar is open, and the motion state of the target barrier gate crossbar is static, the vehicle **100** is controlled to travel. It may be understood that, that the open/close state of the target barrier gate crossbar is open and the motion state of the target barrier gate crossbar is static means that the target barrier gate crossbar is perpendicular to the ground, and is in a completely open state.

(95) In another embodiment, when the open/close state of the target barrier gate crossbar is open, and the motion state of the target barrier gate crossbar is descending, the vehicle **100** is controlled to stop.

(96) In another embodiment, when the open/close state of the target barrier gate crossbar is close, and the motion state of the target barrier gate crossbar is descending, the vehicle **100** is controlled

to stop.

(97) In another embodiment, when the open/close state of the target barrier gate crossbar is close, and the motion state of the target barrier gate crossbar is static, the vehicle **100** is controlled to stop. It may be understood that, that the open/close state of the target barrier gate crossbar is close and the motion state of the target barrier gate crossbar is static means that the target barrier gate crossbar is parallel to the ground, and is in a completely close state.

(98) In another embodiment, when the open/close state of the target barrier gate crossbar is close, and the motion state of the target barrier gate crossbar is ascending, the vehicle **100** is controlled to stop.

(99) A method for determining the open/close state and the motion state of the target barrier gate crossbar will be described below.

(100) According to the method for passing through a barrier gate crossbar by a vehicle provided in this application, the vehicle **100** obtains the data of the plurality of to-be-detected barrier gate crossbars in the surrounding environment of the vehicle **100** by using the one or more sensors, determines the data of the target barrier gate crossbar from the data of the plurality of to-be-detected barrier gate crossbars based on the pose of the target barrier gate crossbar, to determine the status of the target barrier gate crossbar based on the data of the target barrier gate crossbar, so that the vehicle **100** controls, by using the status of the target barrier gate crossbar, the vehicle **100** to pass through the target barrier gate crossbar.

(101) Description is provided below by using an example in which data of two to-be-detected barrier gate crossbars around the vehicle **100** is obtained. For example, the vehicle **100** may obtain data of the first barrier gate crossbar and data of the second barrier gate crossbar around the vehicle **100** by using the one or more sensors. As shown in FIG. 6, the method includes the following operations.

(102) **S601**: One or more sensors in a vehicle **100** collect data of a first barrier gate crossbar and data of a second barrier gate crossbar.

(103) In this specification, it is assumed that a barrier gate crossbar that the vehicle **100** is to pass through is the first barrier gate crossbar. In other words, the first barrier gate crossbar is a target barrier gate crossbar (a barrier gate crossbar of a lane on which the vehicle **100** is located).

(104) After obtaining the data of the first barrier gate crossbar and the data of the second barrier gate crossbar, the vehicle **100** determines, by using a processor **113**, data of the target barrier gate crossbar from the data of the first barrier gate crossbar and the data of the second barrier gate crossbar based on a pose of the target barrier gate crossbar, to be specific, determines the data of the first barrier gate crossbar as the data of the target barrier gate crossbar. Refer to descriptions of the following **S602** to **S605** for details.

(105) **S602**: The processor **113** determines first coordinates of the first barrier gate crossbar based on the data of the first barrier gate crossbar, and determines first coordinates of the second barrier gate crossbar based on the data of the second barrier gate crossbar.

(106) The processor **113** receives the data that are of the first barrier gate crossbar and the second barrier gate crossbar and that are collected by the one or more sensors.

(107) If the sensor is a camera **130**, images shot by the camera **130** include an image of the first barrier gate crossbar and an image of the second barrier gate crossbar. It may be understood that the data of the first barrier gate crossbar is image data. The data of the second barrier gate crossbar is image data. The first coordinates of the first barrier gate crossbar and the first coordinates of the second barrier gate crossbar are both coordinates in a two-dimensional coordinate system.

(108) First, the processor **113** determines the first coordinates of the first barrier gate crossbar based on the data of the first barrier gate crossbar and a target position detection model, and determines the first coordinates of the second barrier gate crossbar based on the data of the second barrier gate crossbar and the target position detection model.

(109) Before the first coordinates of the first barrier gate crossbar and the first coordinates of the

second barrier gate crossbar are determined, a large amount of sample data may be trained by using machine learning or artificial neural networks (Artificial Neural Networks, ANNs), to obtain the target position detection model. For example, an AI chip trains the sample data to obtain the target position detection model. The target position detection model is used for outputting coordinates of a barrier gate crossbar based on image data of the barrier gate crossbar.

(110) In some embodiments, a processor training the sample data is not limited. For example, if the processor **113** is the AI chip, the processor **113** may train the sample data to obtain the target position detection model. In another example, the sample data may alternatively be trained by another neural network processor outside the vehicle **100**, to obtain the target position detection model.

(111) Further, the processor **113** may input the image data of the first barrier gate crossbar into the target position detection model, the target position detection model performs inference operation, and outputs a 2D detection box and key points of the first barrier gate crossbar. The 2D detection box is a compact bounding rectangular box of the first barrier gate crossbar on the image. The key points are two points with semantic information, and are respectively a rotation center point and a rising point. For example, FIG. 7 shows the first barrier gate crossbar **501** compactly bounded by the 2D detection box. The first barrier gate crossbar **501** includes a rotation center point **501a** and a rising point **501b**. It may be understood that, the first coordinates of the first barrier gate crossbar **501** include two endpoints of the first barrier gate crossbar **501**: the rotation center point **501a** of the first barrier gate crossbar **501** and the rising point **501b** of the first barrier gate crossbar **501**.

(112) Similarly, the processor **113** may input the image data of the second barrier gate crossbar into the target position detection model, the target position detection model performs inference operation, and outputs a 2D detection box and key points of the second barrier gate crossbar. The key points include a rotation center point of the second barrier gate crossbar and a rising point of the second barrier gate crossbar.

(113) In some other embodiments, if the sensor is a radar **126**, point cloud data scanned by the radar **126** includes point cloud data of the first barrier gate crossbar and point cloud data of the second barrier gate crossbar. The first coordinates of the first barrier gate crossbar and the first coordinates of the second barrier gate crossbar are both coordinates in a three-dimensional coordinate system.

(114) The processor **113** determines a three-dimensional model of the first barrier gate crossbar based on the point cloud data of the first barrier gate crossbar, determines the first coordinates of the first barrier gate crossbar based on the three-dimensional model of the first barrier gate crossbar, determines a three-dimensional model of the second barrier gate crossbar based on the point cloud data of the second barrier gate crossbar, and determines the first coordinates of the second barrier gate crossbar based on the three-dimensional model of the second barrier gate crossbar.

(115) For example, the radar **126** may be a LiDAR. The LiDAR obtains, in real time, the point cloud data of the first barrier gate crossbar, and sends the point cloud data of the first barrier gate crossbar to the processor **113**. The processor **113** obtains a pose of the first barrier gate crossbar based on a road map, and filters out irrelevant point cloud data by using the pose of the first barrier gate crossbar. For remaining point cloud, impact of outliers is eliminated by using a random sampling consistent (Random sampling consistent, RANSAC) algorithm, to obtain processed point cloud data, and the processed point cloud data is fitted with a straight line, to obtain the three-dimensional model of the first barrier gate crossbar.

(116) Similarly, the LiDAR obtains, in real time, the point cloud data of the second barrier gate crossbar, and sends the point cloud data of the second barrier gate crossbar to the processor **113**. The processor **113** obtains a pose of the second barrier gate crossbar based on the road map, and filters out irrelevant point cloud data by using the pose of the second barrier gate crossbar. For remaining point cloud, impact of outliers is eliminated by using the RANSAC algorithm, to obtain

processed point cloud data, and the processed point cloud data is fitted with a straight line, to obtain the three-dimensional model of the second barrier gate crossbar.

(117) **S603:** The processor **113** determines coordinates of the target barrier gate crossbar based on the pose of the target barrier gate crossbar.

(118) In some embodiments, the processor **113** determines a pose of the camera **130** based on a pose of the vehicle **100** and an extrinsic parameter of the camera **130**.

(119) The processor **113** may obtain the pose of the vehicle **100**, namely, pose information of a rear axle center point of the vehicle **100** in a world coordinate system, by using a GPS or an IMU mounted on the vehicle **100**.

(120) It may be understood that, the extrinsic parameter of the camera **130** is pose information of the camera **130** relative to another reference object in the world coordinate system. The extrinsic parameter of the camera **130** includes a rotation matrix and a translation matrix. The rotation matrix and the translation matrix together describe a conversion relationship of a point between the world coordinate system and a camera coordinate system. The rotation matrix describes a direction of a coordinate axis of the world coordinate system relative to a coordinate axis of the camera coordinate system. The translation matrix describes a position of a spatial origin in the camera coordinate system.

(121) The camera **130** mounted on the vehicle **100** is provided with the extrinsic parameter of the camera **130**. In this specification, the extrinsic parameter of the camera **130** may be pose information relative to the rear axle center point of the vehicle **100**.

(122) The processor **113** performs matrix operation based on the pose of the vehicle **100** and the extrinsic parameter of the camera **130**, to determine the pose of the camera **130**, namely, the pose of the camera **130** in the world coordinate system. The pose of the camera **130** indicates a conversion relationship between three-dimensional coordinates of an object in the world coordinate system and three-dimensional coordinates of the object in the camera coordinate system.

(123) Further, the processor **113** determines the coordinates of the target barrier gate crossbar based on the pose of the target barrier gate crossbar, the pose of the camera **130**, and an intrinsic parameter of the camera **130**.

(124) The pose of the target barrier gate crossbar includes three-dimensional coordinates of the target barrier gate crossbar in the world coordinate system. The processor **113** may obtain the pose of the target barrier gate crossbar by using the road map.

(125) The intrinsic parameter of the camera **130** is a parameter related to characteristics of the camera itself, for example, a focal length or a pixel size of the camera **130**. The intrinsic parameter of the camera **130** indicates a conversion relationship between three-dimensional coordinates of an object in the camera coordinate system and two-dimensional coordinates of the object in an image coordinate system on a shot image.

(126) In some embodiments, the processor **113** converts the pose of the target barrier gate crossbar from the world coordinate system to the camera coordinate system by using the pose of the camera **130**, to obtain the pose of the target barrier gate crossbar in the camera coordinate system.

(127) The processor **113** converts the pose of the target barrier gate crossbar in the camera coordinate system to the coordinates of the target barrier gate crossbar in the image coordinate system by using the intrinsic parameter of the camera **130**, to obtain the coordinates of the target barrier gate crossbar.

(128) **S604:** The processor **113** determines a first Euclidean distance based on the first coordinates of the first barrier gate crossbar and the coordinates of the target barrier gate crossbar and determines a second Euclidean distance based on the first coordinates of the second barrier gate crossbar and the coordinates of the target barrier gate crossbar.

(129) The Euclidean distance is a distance definition that is usually used. The Euclidean distance is also referred to as euclidean metric. The Euclidean distance is an actual distance between two points in an m-dimensional space, or a natural length (namely, a distance from the point to an

origin) of a vector. The Euclidean distance in a two-dimensional space is an actual distance between two points. The Euclidean distance in the two-dimensional space satisfies the following formula (1).

$$\rho = \sqrt{(x_{\text{sub.2}} - x_{\text{sub.1}})^2 + (y_{\text{sub.2}} - y_{\text{sub.1}})^2} \quad (1)$$
 where ρ represents a Euclidean distance between a point $(x_{\text{sub.2}}, y_{\text{sub.2}})$ and a point $(x_{\text{sub.1}}, y_{\text{sub.1}})$.
(130) For example, $(x_{\text{sub.1}}, y_{\text{sub.1}})$ may be the first coordinates of the first barrier gate crossbar. $(x_{\text{sub.2}}, y_{\text{sub.2}})$ may be the coordinates of the target barrier gate crossbar. In this case, the coordinates of the target barrier gate crossbar are coordinates in the two-dimensional coordinate system.

(131) In another example, $(x_{\text{sub.1}}, y_{\text{sub.1}})$ may be the first coordinates of the second barrier gate crossbar. $(x_{\text{sub.2}}, y_{\text{sub.2}})$ may be the coordinates of the target barrier gate crossbar.

(132) The Euclidean distance in the three-dimensional space satisfies the following formula (2).

$$\rho = \sqrt{(x_{\text{sub.2}} - x_{\text{sub.1}})^2 + (y_{\text{sub.2}} - y_{\text{sub.1}})^2 + (z_{\text{sub.2}} - z_{\text{sub.1}})^2} \quad (1)$$
 where ρ represents a Euclidean distance between a point $(x_{\text{sub.2}}, y_{\text{sub.2}}, z_{\text{sub.2}})$ and a point $(x_{\text{sub.1}}, y_{\text{sub.1}}, z_{\text{sub.1}})$.

(133) For example, $(x_{\text{sub.1}}, y_{\text{sub.1}}, z_{\text{sub.1}})$ may be the first coordinates of the first barrier gate crossbar. $(x_{\text{sub.2}}, y_{\text{sub.2}}, z_{\text{sub.2}})$ may be the coordinates of the target barrier gate crossbar. In this case, the coordinates of the target barrier gate crossbar are coordinates in the three-dimensional coordinate system.

(134) In another example, $(x_{\text{sub.1}}, y_{\text{sub.1}}, z_{\text{sub.1}})$ may be the first coordinates of the second barrier gate crossbar. $(x_{\text{sub.2}}, y_{\text{sub.2}}, z_{\text{sub.2}})$ may be the coordinates of the target barrier gate crossbar.

(135) A smaller Euclidean distance indicates a higher probability that a detected barrier gate crossbar is the target barrier gate crossbar. A larger Euclidean distance indicates a lower probability that a detected barrier gate crossbar is the target barrier gate crossbar. Therefore, the processor **113** may compare the first Euclidean distance with the second Euclidean distance, and determines a barrier gate crossbar corresponding to the smaller one in the first Euclidean distance and the second Euclidean distance as the target barrier gate crossbar. In this specification, assuming that the first Euclidean distance is less than the second Euclidean distance, the data of the target barrier gate crossbar corresponding to the first Euclidean distance is determined as the data of the target barrier gate crossbar. **S605** is performed.

(136) **S605**: The processor **113** determines the data of the first barrier gate crossbar corresponding to the first Euclidean distance as the data of the target barrier gate crossbar.

(137) **S606**: The processor **113** determines an open/close state and a motion state of the first barrier gate crossbar based on the data of the first barrier gate crossbar.

(138) The open/close state of the first barrier gate crossbar includes open and close. The motion state of the first barrier gate crossbar includes ascending, descending, and static. It may be understood that the data of the first barrier gate crossbar is the data of the target barrier gate crossbar.

(139) In some embodiments, as shown in FIG. 8, determining the open/close state and the motion state of the first barrier gate crossbar based on the data of the first barrier gate crossbar includes the following detailed operations.

(140) **S6061**: The processor **113** determines an angle of the first barrier gate crossbar based on the data of the first barrier gate crossbar.

(141) The angle of the first barrier gate crossbar is an included angle between the first barrier gate crossbar and a reference straight line.

(142) If the sensor is the camera **130**, the processor **113** may determine the angle of the first barrier gate crossbar based on the first coordinates of the first barrier gate crossbar and the reference straight line. The first coordinates of the first barrier gate crossbar include first coordinates of two endpoints of the first barrier gate crossbar.

(143) It should be understood that, the first coordinates of the first barrier gate crossbar are coordinates in the image coordinate system, namely, two-dimensional coordinates. In the two-dimensional coordinate system, the first barrier gate crossbar may be simulated into a straight line based on the two-dimensional coordinates of the two endpoints of the first barrier gate crossbar. An included angle between the straight line and the X-axis may be the angle of the first barrier gate crossbar. It may be understood that, the angle of the first barrier gate crossbar may be an included angle between the first barrier gate crossbar and the ground.

(144) If the sensor is the radar **126**, the three-dimensional model of the first barrier gate crossbar is projected onto a reference plane to obtain second coordinates of the first barrier gate crossbar. The second coordinates of the first barrier gate crossbar include second coordinates of the two endpoints of the first barrier gate crossbar. The second coordinates are coordinates in the two-dimensional coordinate system. The angle of the first barrier gate crossbar is determined based on the second coordinates of the first barrier gate crossbar and the reference straight line. The two-dimensional coordinate system may be the image coordinate system.

(145) For example, as shown in FIG. **9**, coordinates of the rotation center point **501a** are (x.sub.1, y.sub.1), and coordinates of the rising point **501b** are (x.sub.2, y.sub.2). A line connecting two coordinate points: the rotation center point **501a** and the rising point **501b** may represent a straight line simulating the first barrier gate crossbar. α represents the angle of the first barrier gate crossbar.

(146) **S6062**: The processor **113** determines the open/close state and the motion state of the first barrier gate crossbar based on the angle of the first barrier gate crossbar.

(147) In some embodiments, if the angle of the first barrier gate crossbar is greater than a first preset angle, the processor **113** determines that the open/close state of the first barrier gate crossbar is open.

(148) If the angle of the first barrier gate crossbar is less than a second preset angle, the processor **113** determines that the open/close state of the first barrier gate crossbar is close. The second preset angle is less than the first preset angle.

(149) If the angle of the first barrier gate crossbar is less than or equal to the first preset angle, and the angle of the first barrier gate crossbar is greater than or equal to the second preset angle, the processor **113** determines that the open/close state of the first barrier gate crossbar is an open/close state that is of the first barrier gate crossbar and that is determined at a previous moment. It may be understood that, the open/close state of the first barrier gate crossbar determined at the previous moment may be the open/close state of the first barrier gate crossbar mostly recently determined by the processor **113**.

(150) For example, it is assumed that ϕ represents the first preset angle, and v represents the second preset angle. FIG. **10(a)** is a schematic diagram showing that the angle of the first barrier gate crossbar is greater than the first preset angle. In this case, it indicates that the open/close state of the first barrier gate crossbar is open. FIG. **10(b)** is a schematic diagram showing that the angle of the first barrier gate crossbar is less than the second preset angle. In this case, it indicates that the open/close state of the first barrier gate crossbar is close. FIG. **10(c)** is a schematic diagram showing that the angle of the first barrier gate crossbar is less than or equal to the first preset angle, and the angle of the first preset angle is greater than or equal to the second preset angle. In this case, it indicates that the open/close state of the first barrier gate crossbar is close or open.

(151) In some embodiments, if an i.sup.th angle of the first barrier gate crossbar is greater than an (i-1).sup.th angle of the first barrier gate crossbar, it is determined that the motion state of the first barrier gate crossbar is ascending.

(152) If the i.sup.th angle of the first barrier gate crossbar is less than the (i-1).sup.th angle of the first barrier gate crossbar, it is determined that the motion state of the first barrier gate crossbar is descending.

(153) The i.sup.th angle of the first barrier gate crossbar is determined based on the first barrier gate crossbar in an i.sup.th frame of image, the (i-1).sup.th angle of the first barrier gate crossbar is

determined based on the first barrier gate crossbar in an (i-1).sup.th frame of image, and the i.sup.th frame of image is adjacent to the (i-1).sup.th frame of image.

(154) In some embodiments, the i.sup.th angle of the first barrier gate crossbar and the (i-1).sup.th angle of the first barrier gate crossbar are assumed. FIG. 11(a) is a schematic diagram of ascending of the first barrier gate crossbar. In this case, $\alpha_1 > \alpha_2$. FIG. 11(b) is a schematic diagram of descending of the first barrier gate crossbar. In this case, $\alpha_1 < \alpha_2$.

(155) S607: The processor 113 controls, based on the open/close state and the motion state of the first barrier gate crossbar, the vehicle 100 to pass through the first barrier gate crossbar.

(156) In some embodiments, in a traveling process, the vehicle 100 continuously obtains data of a plurality of barrier gate crossbars in a surrounding environment of the vehicle by using the one or more sensors, and determines the open/close state and the motion state of the barrier gate crossbar of the lane on which the vehicle 100 is located by using a plurality of frames of images of the barrier gate crossbars.

(157) In some embodiments, after obtaining the data of the barrier gate crossbar, the sensor feeds back a detection result to the processor 113. The detection result includes the data of the barrier gate crossbar, and a time stamp of the data of the barrier gate crossbar. After determining the angle of the barrier gate crossbar based on the data of the barrier gate crossbar, the processor 113 sorts angles of the barrier gate crossbar in a sequence based on time stamps, to form a sequence historical queue that is updated in real time.

(158) The processor 113 performs data smoothing on the sequence historical queue by using an average value and a covariance of the angles of the barrier gate crossbar in a local window range in a manner of mobile filtering, to effectively correct a problem of a detection result jitter.

(159) The processor 113 may further establish a first-order motion model by using the angles of the barrier gate crossbar as an observation amount based on historical frame information in the smoothed sequence queue, perform angle prediction on a frame that misses detection, and adds a supplementary point to the smoothed sequence queue. For example, FIG. 12 is a schematic diagram of the sequence queue of the angles of the barrier gate crossbar.

(160) In addition, after determining the barrier gate crossbar of the lane on which the vehicle 100 is located, the processor 113 does not need to match the barrier gate crossbar of the lane on which the vehicle 100 is located, and only needs to determine the open/close state and the motion state of the barrier gate crossbar of the lane on which the vehicle 100 is located, and control the vehicle 100 to pass through the barrier gate crossbar of the lane on which the vehicle 100 is located.

(161) The following describes a process in which the vehicle 100 passes through the first barrier gate crossbar by using examples with reference to FIG. 13(a) to FIG. 15(d). For ease of understanding, dashed lines in the figures represent the open/close state and the motion state of the first barrier gate crossbar at historical moments. Solid lines in the figures represent the open/close state and the motion state of the first barrier gate crossbar at a current moment.

(162) FIG. 13(a) and FIG. 13(b) show a process in which the first barrier gate crossbar rises slowly, and a vehicle 200 in front of the vehicle 100 passes through the first barrier gate crossbar. In this case, the open/close state of the first barrier gate crossbar is open, and the motion state of the first barrier gate crossbar is ascending. The vehicle 100 obtains the data that are of the first barrier gate crossbar and the second barrier gate crossbar and that are collected by the one or more sensors, determines the data of the target barrier gate crossbar, namely, the data of the first barrier gate crossbar, from the data of the first barrier gate crossbar and the data of the second barrier gate crossbar based on the pose of the first barrier gate crossbar, and determines, based on the data of the first barrier gate crossbar, that the open/close state of the first barrier gate crossbar is open and the motion state of the first barrier gate crossbar is ascending, and controls the vehicle 100 to travel.

(163) As shown in FIG. 13(c), the first barrier gate crossbar is perpendicular to the ground, and is in a completely open state. In this case, the vehicle 100 obtains the data that is of the first barrier

gate crossbar and that is collected by the one or more sensors, and determines that the open/close state of the first barrier gate crossbar is open and the motion state of the first barrier gate crossbar is static, and controls the vehicle **100** to travel.

(164) As shown in FIG. **13(d)**, the vehicle **200** has passed through the first barrier gate crossbar, and the first barrier gate crossbar starts to descend. The vehicle **100** obtains the data that is of the first barrier gate crossbar and that is collected by the one or more sensors, determines, based on the data of the first barrier gate crossbar, that the open/close state of the first barrier gate crossbar is open and the motion state of the first barrier gate crossbar is descending, and controls the vehicle **100** to stop and wait.

(165) As shown in FIG. **14(a)**, the first barrier gate crossbar continuously descends. The vehicle **100** obtains the data that is of the first barrier gate crossbar and that is collected by the one or more sensors. In this case, the angle of the first barrier gate crossbar is less than or equal to the first preset angle, and the angle of the first barrier gate crossbar is greater than or equal to the second preset angle, and the vehicle **100** may determine the open/close state and the motion state of the first barrier gate crossbar based on an angle of the first barrier gate crossbar at a previous moment. For example, the open/close state and the motion state of the first barrier gate crossbar are determined based on the angle of the first barrier gate crossbar shown in FIG. **13(d)**. To be specific, the open/close state of the first barrier gate crossbar is open and the motion state of the first barrier gate crossbar is descending. The vehicle **100** is controlled to stop and wait.

(166) As shown in FIG. **14(b)**, the first barrier gate crossbar continuously descends. The vehicle **100** obtains the data that is of the first barrier gate crossbar and that is collected by the one or more sensors, determines, based on the data of the first barrier gate crossbar, that the open/close state of the first barrier gate crossbar is close and the motion state of the first barrier gate crossbar is descending, and controls the vehicle **100** to stop and wait.

(167) As shown in FIG. **14(c)**, the first barrier gate crossbar is parallel to the ground, and is in a completely close state. In this case, the open/close state of the first barrier gate crossbar is close and the motion state of the first barrier gate crossbar is static. The vehicle **100** is controlled to stop and wait.

(168) As shown in FIG. **14(d)**, the first barrier gate crossbar starts to ascend. The vehicle **100** obtains the data that is of the first barrier gate crossbar and that is collected by the one or more sensors, determines, based on the data of the first barrier gate crossbar, that the open/close state of the first barrier gate crossbar is close and the motion state of the first barrier gate crossbar is ascending, and controls the vehicle **100** to stop and wait.

(169) As shown in FIG. **15(a)**, the first barrier gate crossbar continuously ascends. The vehicle **100** obtains the data that is of the first barrier gate crossbar and that is collected by the one or more sensors. In this case, the angle of the first barrier gate crossbar is less than or equal to the first preset angle, and the angle of the first barrier gate crossbar is greater than or equal to the second preset angle, and the vehicle **100** may determine the open/close state and the motion state of the first barrier gate crossbar based on the angle of the first barrier gate crossbar at a previous moment. For example, the open/close state and the motion state of the first barrier gate crossbar are determined based on the angle of the first barrier gate crossbar shown in FIG. **14(d)**. To be specific, the open/close state of the first barrier gate crossbar is close and the motion state of the first barrier gate crossbar is ascending. The vehicle **100** is controlled to stop and wait.

(170) As shown in FIG. **15(b)** and FIG. **15(c)**, the first barrier gate crossbar continuously ascends. The vehicle **100** obtains the data that is of the first barrier gate crossbar and that is collected by the one or more sensors, determines, based on the data of the first barrier gate crossbar, that the open/close state of the first barrier gate crossbar is open and the motion state of the first barrier gate crossbar is ascending, and controls the vehicle **100** to travel.

(171) In some embodiments, when the vehicle **100** is in a traveling process, a head of the vehicle is excessively close to the first barrier gate crossbar, the first barrier gate crossbar is not in a field of

view (field of view, FoV) range of the sensor, and the sensor cannot obtain the data of the first barrier gate crossbar. Therefore, the vehicle **100** may determine the open/close state and the motion state of the first barrier gate crossbar by using the data of the first barrier gate crossbar of historical frames. In this scenario, because the first barrier gate crossbar continuously ascends, the vehicle **100** determines, based on the data of the first barrier gate crossbar of the historical frames, that the open/close state of the first barrier gate crossbar is open and the motion state of the first barrier gate crossbar is ascending, and controls the vehicle **100** to slowly pass through the first barrier gate crossbar.

(172) As shown in FIG. **15(d)**, the vehicle **200** has passed through the first barrier gate crossbar, and the first barrier gate crossbar starts to descend.

(173) It should be noted that, a method for recognizing a vehicle by a barrier gate crossbar is not limited in this application. Refer to the prior art for details.

(174) It may be understood that, to implement functions in the foregoing embodiments, the vehicle includes corresponding hardware structures and/or software modules for performing the functions. A person skilled in the art should easily be aware that, in combination with the examples described in the embodiments disclosed in this application, units, method operations may be implemented by hardware or a combination of hardware and computer software. Whether a function is performed by hardware or hardware driven by computer software depends on particular application scenarios and design constraints of the technical solutions.

(175) FIG. **16** is a schematic structural diagram of a possible apparatus for passing through a barrier gate crossbar by a vehicle according to an embodiment of this application. These apparatuses for passing through a barrier gate crossbar by a vehicle may be configured to implement functions of the processor in the foregoing method embodiments, and therefore beneficial effects of the foregoing method embodiments can also be achieved. In this embodiment of this application, the apparatus for passing through a barrier gate crossbar by a vehicle may be the processor **113** shown in FIG. **1**.

(176) As shown in FIG. **16**, the apparatus **1600** for passing through a barrier gate crossbar by a vehicle includes a processing unit **1610** and a control unit **1620**. The apparatus **1600** for passing through a barrier gate crossbar by a vehicle is configured to implement the functions of the processor in the method embodiment shown in FIG. **4**, FIG. **6**, or FIG. **8**.

(177) When the apparatus **1600** for passing through a barrier gate crossbar by a vehicle is configured to implement the functions of the processor in the method embodiment shown in FIG. **4**, the processing unit **1610** is configured to perform **S402** and **S403**, and the control unit **1620** is configured to perform **S404**.

(178) When the apparatus **1600** for passing through a barrier gate crossbar by a vehicle is configured to implement the functions of the processor in the method embodiment shown in FIG. **6**, the processing unit **1610** is configured to perform **S602** to **S606**, and the control unit **1620** is configured to perform **S607**.

(179) When the apparatus **1600** for passing through a barrier gate crossbar by a vehicle is configured to implement the functions of the processor in the method embodiment shown in FIG. **8**, the processing unit **1610** is configured to perform **S602** to **S606**, and the control unit **1620** is configured to perform **S607**.

(180) For more detailed descriptions of the processing unit **1610** and the control unit **1620**, directly refer to related descriptions in the method embodiment shown in FIG. **4**, FIG. **6**, or FIG. **8**, and details are not described herein.

(181) It should be noted that the processor in the embodiments of this application may be a central processing unit (CPU), may be another general-purpose processor, a digital signal processor (DSP), an application-specific integrated circuit (ASIC), a field programmable gate array (FPGA), or another programmable logical device, a transistor logical device, a hardware component, or any combination thereof. The general-purpose processor may be a microprocessor or any conventional

processor.

(182) The method operations in the embodiments of this application may be implemented by hardware, or may be implemented by a processor executing a software instruction. The software instruction may include a corresponding software module. The software module may be stored in a random access memory (RAM), a flash memory, a read-only memory (ROM), a programmable read-only memory (PROM), an erasable programmable read-only memory (EPROM), an electrically erasable programmable read-only memory (EEPROM), a register, a hard disk, a mobile hard disk, a compact disc read-only memory (CD-ROM), or any other form of storage medium well-known in the art. For example, a storage medium is coupled to a processor, so that the processor can read information from the storage medium or write information into the storage medium. Certainly, the storage medium may be a component of the processor. The processor and the storage medium may be located in the ASIC. In addition, the ASIC may be located in a network device or a terminal device. Certainly, the processor and the storage medium may exist in the network device or the terminal device as discrete components.

(183) All or some of the foregoing embodiments may be implemented by using software, hardware, firmware, or any combination thereof. When software is used to implement the embodiments, the embodiments may be implemented completely or partially in a form of a computer program product. The computer program product includes one or more computer programs or instructions. When the computer programs or instructions are loaded and executed on the computer, the procedure or functions described in the embodiments of this application are all or partially performed. The computer may be a general-purpose computer, a dedicated computer, a computer network, a network device, user equipment, or another programmable apparatus. The computer programs or instructions may be stored in a computer-readable storage medium or may be transmitted from a computer-readable storage medium to another computer-readable storage medium. For example, the computer programs or instructions may be transmitted from a website, computer, server, or data center to another website, computer, server, or data center in a wired or wireless manner. The computer-readable storage medium may be any usable medium that can be accessed by a computer, or a data storage device, for example, a server or data center integrating one or more usable media. The usable medium may be a magnetic medium, for example, a floppy disk, a hard disk, or a magnetic tape, or may be an optical medium, for example, a digital video disc (DVD), or may be a semiconductor medium, for example, a solid state drive (SSD).

(184) In the embodiments of this application, if there is no special description or logical conflict, and terms and/or descriptions in different embodiments are consistent and may be mutually referenced, technical features in the different embodiments may be combined to form a new embodiment based on an internal logical relationship.

(185) In this application, “at least one” means one or more, and “a plurality of” means two or more. The term “and/or” describes an association relationship for describing associated objects and represents that three relationships may exist. For example, A and/or B may represent the following three cases: Only A exists, both A and B exist, and only B exists, where A and B may be singular or plural. In the text description of this application, the character “/” generally indicates that associated objects are in an “or” relationship. In the formula of this application, the character “/” indicates that the associated objects are in a “division” relationship.

(186) It may be understood that various numeric numbers in the embodiments of this application are merely distinguishing for ease of description, and are not intended to limit the scope of the embodiments of this application. Sequence numbers of the foregoing processes do not mean execution sequences. The execution sequences of the processes should be determined based on functions and internal logic of the processes.

Claims

1. A method for passing through a barrier gate crossbar by an autonomous driving vehicle, comprising: obtaining data of a plurality of barrier gate crossbars collected by one or more sensors; determining information of a target barrier gate crossbar of the plurality of barrier gate crossbars from the data of the plurality of barrier gate crossbars based on a pose of the target barrier gate crossbar, the pose including a position and an orientation of the target barrier gate crossbar, wherein the target barrier gate crossbar is a barrier gate crossbar of a lane on which the autonomous driving vehicle is located; determining a status of the target barrier gate crossbar based on the information of the target barrier gate crossbar, the status of the target barrier gate crossbar comprising one of an open state or a close state, wherein the status of the target barrier gate crossbar further comprises a motion state comprising an ascending state, a descending state, or a static state; and controlling, based on the status of the target barrier gate crossbar, the autonomous driving vehicle to pass through the target barrier gate crossbar, comprising: controlling the autonomous driving vehicle to pass through the target barrier gate crossbar, when the one of the open state or the close state of the target barrier gate crossbar is the open state, and the motion state of the target barrier gate crossbar is the ascending state or the static state.
2. The method according to claim 1, wherein the controlling, based on the status of the target barrier gate crossbar, the autonomous driving vehicle to pass through the target barrier gate crossbar comprises: controlling, based on the one of the open state or the close state of the target barrier gate crossbar, the autonomous driving vehicle to pass through the target barrier gate crossbar.
3. The method according to claim 2, wherein the controlling, based on the one of the open state or the close state of the target barrier gate crossbar, the autonomous driving vehicle to pass through the target barrier gate crossbar comprises: when the one of the open state or the close state of the target barrier gate crossbar is the open state, controlling the autonomous driving vehicle to travel; and when the one of the open state or the close state of the target barrier gate crossbar is the close state, controlling the autonomous driving vehicle to stop.
4. The method according to claim 1, wherein the controlling, based on the one of the open state or the close state and the motion state of the target barrier gate crossbar, the autonomous driving vehicle to pass through the target barrier gate crossbar comprises: when the one of the open state or the close state of the target barrier gate crossbar is the open state, and the motion state of the target barrier gate crossbar is the descending state, controlling the autonomous driving vehicle to stop.
5. The method according to claim 1, wherein the controlling, based on the one of the open state or the close state and the motion state of the target barrier gate crossbar, the autonomous driving vehicle to pass through the target barrier gate crossbar comprises: when the one of the open state or the close state of the target barrier gate crossbar is the close state, and the motion state of the target barrier gate crossbar is the descending state, the static state, or the ascending state, controlling the autonomous driving vehicle to stop.
6. The method according to claim 1, wherein the determining the status of the target barrier gate crossbar based on the data of the target barrier gate crossbar comprises: determining an angle of the target barrier gate crossbar based on the data of the target barrier gate crossbar, wherein the angle of the target barrier gate crossbar is an included angle between the target barrier gate crossbar and a reference straight line; and determining the one of the open state or the close state and the motion state of the target barrier gate crossbar based on the angle of the target barrier gate crossbar.
7. The method according to claim 6, wherein the determining the one of the open state or the close state of the target barrier gate crossbar and the motion state of the target barrier gate crossbar based on the angle of the target barrier gate crossbar comprises: when the angle of the target barrier gate crossbar is greater than a first preset angle, determining that the one of the open state or the close state of the target barrier gate crossbar is the open state; when the angle of the target barrier gate crossbar is less than a second preset angle, determining that the one of the open state or the close

state of the target barrier gate crossbar is the close state, wherein the second preset angle is less than the first preset angle; and when the angle of the target barrier gate crossbar is less than or equal to the first preset angle and greater than or equal to the second preset angle, determining that the one of the open state or the close state of the target barrier gate crossbar is an open state or close state of the target barrier gate crossbar determined at an immediate previous moment when a last determination was made.

8. The method according to claim 6, wherein the determining the one of the open state or the close state and the motion state of the target barrier gate crossbar based on the angle of the target barrier gate crossbar comprises: when an i .sup.th angle of the target barrier gate crossbar is greater than an $(i-1)$.sup.th angle of the target barrier gate crossbar, determining that the motion state of the target barrier gate crossbar is ascending; and when the i .sup.th angle of the target barrier gate crossbar is less than the $(i-1)$.sup.th angle of the target barrier gate crossbar, determining that the motion state of the target barrier gate crossbar is descending, wherein the i .sup.th angle of the target barrier gate crossbar is determined based on the target barrier gate crossbar in an i .sup.th frame of image, the $(i-1)$.sup.th angle of the target barrier gate crossbar is determined based on the target barrier gate crossbar in an $(i-1)$.sup.th frame of image, and the i .sup.th frame of image is adjacent to the $(i-1)$.sup.th frame of image.

9. An apparatus for passing through a barrier gate crossbar by an autonomous driving vehicle, comprising: at least one processor; and a memory coupled to the at least one processor and storing programming instructions, which when executed by the at least one processor, cause the at least one processor to: obtain data of a plurality of barrier gate crossbars collected by one or more sensors, determine information of a target barrier gate crossbar of the plurality of barrier gate crossbars from the data of the plurality of barrier gate crossbars based on a pose of the target barrier gate crossbar, the pose including a position and an orientation of the target barrier gate crossbar, wherein the target barrier gate crossbar is a barrier gate crossbar of a lane on which the autonomous driving vehicle is located, and determine a status of the target barrier gate crossbar based on the information of the target barrier gate crossbar, the status of the target barrier gate crossbar comprising one of an open state or a close state, wherein the status of the target barrier gate crossbar further comprises a motion state comprising an ascending state, a descending state, or a static state; and control, based on the status of the target barrier gate crossbar, the autonomous driving vehicle to pass through the target barrier gate crossbar, wherein the at least one processor is caused to: control the autonomous driving vehicle to pass through the target barrier gate crossbar, when the one of the open state or the close state of the target barrier gate crossbar is the open state, and the motion state of the target barrier gate crossbar is the ascending state or the static state.

10. The apparatus according to claim 9, wherein the at least one processor storing programming instructions, which when executed by the at least one processor further cause the at least one processor to: control, based on the one of the open state or the close state of the target barrier gate crossbar, the autonomous driving vehicle to pass through the target barrier gate crossbar.

11. The apparatus according to claim 10, wherein the at least one processor storing programming instructions, which when executed by the at least one processor further cause the at least one processor to: when the one of the open state or the close state of the target barrier gate crossbar is the open state, control the autonomous driving vehicle to travel; and when the one of the open state or the close state of the target barrier gate crossbar is the close state, controlling the autonomous driving vehicle to stop.

12. The apparatus according to claim 9, wherein the at least one processor storing programming instructions, which when executed by the at least one processor further cause the at least one processor to: when the one of the open state or the close state of the target barrier gate crossbar is the open state, and the motion state of the target barrier gate crossbar is the descending state, control the autonomous driving vehicle to stop.

13. The apparatus according to claim 12, wherein the at least one processor storing programming

instructions, which when executed by the at least one processor further cause the at least one processor to: when the one of the open state or the close state of the target barrier gate crossbar is the close state, and the motion state of the target barrier gate crossbar is the descending state, the static state, or the ascending state, control the autonomous driving vehicle to stop.

14. The apparatus according to claim 13, wherein the at least one processor storing programming instructions, which when executed by the at least one processor further cause the at least one processor to: determine an angle of the target barrier gate crossbar based on the data of the target barrier gate crossbar, wherein the angle of the target barrier gate crossbar is an included angle between the target barrier gate crossbar and a reference straight line; and determining the one of the open state or the close state and the motion state of the target barrier gate crossbar based on the angle of the target barrier gate crossbar.

15. The apparatus according to claim 14, wherein the at least one processor storing programming instructions, which when executed by the at least one processor further cause the at least one processor to: when the angle of the target barrier gate crossbar is greater than a first preset angle, determining that the one of the open state or the close state of the target barrier gate crossbar is the open state; when the angle of the target barrier gate crossbar is less than a second preset angle, determining that the one of the open state or the close state of the target barrier gate crossbar is the close state, wherein the second preset angle is less than the first preset angle; and when the angle of the target barrier gate crossbar is less than or equal to the first preset angle and greater than or equal to the second preset angle, determining that the one of the open state or the close state of the target barrier gate crossbar is an open state or a close state of the target barrier gate crossbar determined at an immediate previous moment when a last determination was made.

16. A computer program product comprising computer-executable instructions stored on a non-transitory computer-readable storage medium which, when executed by a processor, cause an apparatus to: obtain data of a plurality of barrier gate crossbars collected by one or more sensors; determine information of a target barrier gate crossbar of the plurality of barrier gate crossbars from the data of the plurality of barrier gate crossbars based on a pose of the target barrier gate crossbar, the pose including a position and an orientation of the target barrier gate crossbar, wherein the target barrier gate crossbar is a barrier gate crossbar of a lane on which an autonomous driving vehicle is located; determine a status of the target barrier gate crossbar based on the information of the target barrier gate crossbar, the status of the target barrier gate crossbar comprising one of an open state or a close state, wherein the status of the target barrier gate crossbar further comprises a motion state comprising an ascending state, a descending state, or a static state; and control, based on the status of the target barrier gate crossbar, the autonomous driving vehicle to pass through the target barrier gate crossbar, wherein the apparatus is caused to: control the autonomous driving vehicle to pass through the target barrier gate crossbar, when the one of the open state or the close state of the target barrier gate crossbar is the open state, and the motion state of the target barrier gate crossbar is the ascending state or the static state.

17. The computer program product according to claim 16, wherein the computer-executable instructions stored on the non-transitory computer-readable storage medium which, when executed by the processor, further cause the apparatus to: control, based on the one of the open state or the close state of the target barrier gate crossbar, the autonomous driving vehicle to pass through the target barrier gate crossbar.

18. The computer program product according to claim 17, wherein the computer-executable instructions stored on the non-transitory computer-readable storage medium which, when executed by the processor, further cause the apparatus to: when the one of the open state or the close state of the target barrier gate crossbar is the open state, control the autonomous driving vehicle to travel; and when the one of the open state or the close state of the target barrier gate crossbar is the close state, controlling the autonomous driving vehicle to stop.

19. The computer program product according to claim 16, wherein the computer-executable

instructions stored on the non-transitory computer-readable storage medium which, when executed by the processor, further cause the apparatus to: when the one of the open state or the close state of the target barrier gate crossbar is the open state, and the motion state of the target barrier gate crossbar is the descending state, control the autonomous driving vehicle to stop.

20. The computer program product according to claim 19, wherein the computer-executable instructions stored on the non-transitory computer-readable storage medium which, when executed by the processor, further cause the apparatus to: when the one of the open state or the close state of the target barrier gate crossbar is the close state, and the motion state of the target barrier gate crossbar is the descending state, the static state, or the ascending state, control the autonomous driving vehicle to stop.
