

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12411626
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Cao; Kaiyao et al.

File system and host performance booster for flash memory

Abstract

In an aspect, a method for managing a logic to physical (L2P) mapping table of a memory device is disclosed. A first configuration corresponding to a file is received from a host device with the memory device. Transmitting an L2P dirty entry notification associated with the file to the host device is refrained from. The L2P dirty entry notification indicates that an L2P entry of an L2P mapping table stored in the host device has become dirty. In response to the refraining, a first confirmation is transmitted to the host device.

Inventors: Cao; Kaiyao (Wuhan, CN), Zhang; Yaping (Wuhan, CN), Sun; Xiuli (Wuhan, CN)

Applicant: YANGTZE MEMORY TECHNOLOGIES CO., LTD. (Wuhan, CN)

Family ID: 77081257

Assignee: YANGTZE MEMORY TECHNOLOGIES CO., LTD. (Wuhan, CN)

Appl. No.: 18/378524

Filed: October 10, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240036750 A1	Feb. 01, 2024

Related U.S. Application Data

continuation parent-doc US 17307083 20210504 US 11829621 child-doc US 18378524
continuation parent-doc WO PCT/CN2021/084657 20210331 PENDING child-doc US 17307083

Publication Classification

Int. Cl.: G06F3/06 (20060101)

U.S. Cl.:

CPC **G06F3/0638** (20130101); **G06F3/0604** (20130101); **G06F3/0655** (20130101);
G06F3/0679 (20130101);

Field of Classification Search

CPC: G05B (13/00-048); G05B (15/00-02); G05B (17/00-02); G06F (1/00-3296); G06F (3/00);
G06F (3/06-0689); G06F (5/00-16); G06F (8/00-78); G06F (9/00-548); G06F (11/00-
3696); G06F (12/00-16); G06F (13/00-4295); G06F (15/00-825); G06F (16/00-986);
G06F (18/00-41); G06F (17/00-40); G06F (21/00-88); G06F (2009/3883); G06F
(2009/45562-45595); G06F (2015/761-768); G06F (2201/00-885); G06F (2206/00-20);
G06F (2209/00-549); G06F (2211/00-902); G06F (2212/00-7211); G06F (2213/00-4004);
G06F (2216/00-17); G06F (2221/00-2153); G06N (3/00-126); G06N (5/00-048); G06N
(7/00-08); G06N (10/00); G06N (20/00-20); G06N (99/00-007); G06T (1/00-60); G06V
(30/00-43); G11B (20/00-24); G11B (33/00-1493); G11C (11/00-5692); G11C (13/00-
06); G11C (14/00-009); G11C (15/00-06); G11C (16/00-3495); G11C (17/00-18); G11C
(2207/00-229); G11C (2216/00-30); H01L (25/00-50); H01L (2225/00-1094); H03M
(7/00-707); H04L (9/00-38); H04L (12/00-66); H04L (41/00-5096); H04L (49/00-9094);
H04L (61/00-59); H04L (67/00-75)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
9747202	12/2016	Shaharabany	N/A	G06F 12/0246
10430117	12/2018	Jean	N/A	N/A
10983918	12/2020	Manganelli et al.	N/A	N/A
11126562	12/2020	Lee	N/A	N/A
11169744	12/2020	Brief et al.	N/A	N/A
11262938	12/2021	Lin	N/A	N/A
11409651	12/2021	Jean et al.	N/A	N/A
11614885	12/2022	Chen	N/A	N/A
11829621	12/2022	Cao	N/A	G06F 12/0246
2018/0024745	12/2017	Lee	711/103	G06F 12/0246
2020/0327063	12/2019	Kang	N/A	G06F 12/0871
2020/0364148	12/2019	Lv et al.	N/A	N/A
2020/0394139	12/2019	Lee	N/A	G06F 12/10
2021/0026748	12/2020	Kim	N/A	N/A
2021/0089470	12/2020	Hao	N/A	G06F 12/1027
2021/0133095	12/2020	Kim	N/A	G11C 8/04
2021/0365569	12/2020	Chen	N/A	N/A
2021/0397370	12/2020	Chen	N/A	G06F 3/0638
2022/0113877	12/2021	Kim et al.	N/A	N/A
2022/0253388	12/2021	Zhang	N/A	G06F 12/0868

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
------------	------------------	---------	-----

111538682	12/2019	CN	N/A
111581121	12/2019	CN	N/A
111831581	12/2019	CN	N/A
112286445	12/2020	CN	N/A

OTHER PUBLICATIONS

J. Hong, S. Han and E.-Y. Chung, "A RAM cache approach using host memory buffer of the NVMe interface," 2016 International SoC Design Conference (ISOCC), Jeju, Korea (South), 2016, pp. 109-110, doi: 10.1109/ISOCC.2016.7799757. (Year: 2016). cited by examiner

Y. Peng, L. Peng, S. Sun, L. Yin, Q. Li and J. Zhang, "FlexHMB: A Flexible HMB Design Towards Bufferless Mobile Flash," in IEEE Transactions on Computer-Aided Design of Integrated Circuits and Systems, doi: 10.1109/TCAD.2025.3568773. (Year: 2025). cited by examiner

International Search Report of the International Searching Authority directed to related International Patent Application No. PCT/CN2021/084657, mailed Jan. 4, 2022; 4 pages. cited by applicant

J. Hong, S. Han and E.-Y. Chung, "A RAM cache approach using host memory buffer of the NVMe interface," 2016 International SoC Design Conference (ISOCC), Jeju, Korea (South), 2016, pp. 109-110, doi: 10.1109/ISOCC.2016.7799757. (Year: 2016). cited by applicant

J. Koo, C. Chung, Arvind and S. Lee, "A Case for Application-Managed Flash," in IEEE Transactions on Computers, vol. 70, No. 2, pp. 240-254, Feb. 1, 2021, doi: 10.1109/TC.2020.2987569. (Year: 2021). cited by applicant

K. Han, H. Kim and D. Shin, "WAL-SSD: Address Remapping-Based Write-Ahead-Logging Solid-State Disks," in IEEE Transactions on Computers, vol. 69, No. 2, pp. 260-273, Feb. 1, 2020, doi: 10.1109/TC.2019.2947897. (Year: 2020). cited by applicant

Jesung Kim, Jong Min Kim, S.H. Noh, Sang Lyul Min and Yookun Cho, "A space-efficient flash translation layer for CompactFlash systems," in IEEE Transactions on Consumer Electronics, vol. 48, No. 2, pp. 366-375, May 2002, doi: 10.1109/TCE.2002.1010143. cited by applicant

Primary Examiner: Chappell; Daniel C.

Attorney, Agent or Firm: BAYES PLLC

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. application Ser. No. 17/307,083, filed on May 4, 2021, entitled "FILE SYSTEM AND HOST PERFORMANCE BOOSTER FOR FLASH MEMORY," issued as U.S. Pat. No. 11,829,621, which is a continuation of International Application No. PCT/CN2021/084657, filed on Mar. 31, 2021, entitled "FILE SYSTEM AND HOST PERFORMANCE BOOSTER FOR FLASH MEMORY," both of which are hereby incorporated by reference in their entireties.

BACKGROUND

(1) In order to read or write a file in an operating system, the data storage system determines a logic address and a physical address of the file. The management and retrieval of the logic address and the physical address may be cumbersome for the data storage system and may limit the speed of file reading and writing processes.

SUMMARY

(2) Some aspects of this disclosure relate to apparatuses and methods for an enhancement on a data storage system. For example, systems and methods are provided for improving read and write

efficiencies of the data storage system.

(3) Some aspects of this disclosure provide a host device comprising a memory and a processor coupled to the memory. The memory is used to store a logic-to-physical (L2P) mapping table that includes an entry mapping logical addresses of a file to physical addresses of a file. The processor is configured to generate a first configuration corresponding to a file and transmit the first configuration to a memory device. The first configuration instructs the memory device to refrain from transmitting a L2P dirty entry notification to the host device. The L2P dirty entry notification corresponds to the file.

(4) Some aspects of this disclosure provide a memory device comprising a memory and a processor coupled to the memory. The memory controller is configured to receive, from a host device, a first configuration corresponding to a file; refrain from transmitting a logic to physical (L2P) dirty entry notification corresponding to the file to the host device; and transmit a first confirmation to the host device, wherein the first confirmation indicates refraining from transmitting the L2P dirty entry notification to the host device.

(5) Some aspects of this disclosure provide a system comprising a host device and a memory device. The host device is configured to generate a first configuration corresponding to a file; and transmit the first configuration to a memory device. The memory device is configured to receive, from the host device, the first configuration; and refrain from transmitting a logic-to-physical (L2P) dirty entry notification corresponding to the file to the host device.

(6) Some aspects of this disclosure relate to the system, wherein the host device is further configured to generate a second configuration corresponding to the file; and transmit the second configuration to the memory device, wherein the second configuration instructs the memory device to resume transmitting the L2P dirty entry notification corresponding to the file to the host device.

(7) Some aspects of this disclosure provide a system, comprising a host device and a memory device. The host device comprises a first memory for storing a logic-to-physical (L2P) mapping table that includes an entry mapping logical addresses of a file to physical addresses of a file; the host device further comprises a processor coupled to the first memory, and the processor is configured to: generate a first configuration corresponding to the file; and transmit the first configuration to a memory device, wherein the first configuration instructs the memory device to refrain from transmitting a L2P dirty entry notification to the host device, and wherein the L2P dirty entry notification corresponds to the file. The memory device comprises a second memory and a memory controller coupled to the second memory; the memory controller is configured to: receive, from a host device, a first configuration corresponding to a file; refrain from transmitting a logic to physical (L2P) dirty entry notification corresponding to the file to the host device; and transmit a first confirmation to the host device, wherein the first confirmation indicates refraining from transmitting the L2P dirty entry notification to the host device.

(8) Some aspects of this disclosure provide a method for managing a L2P mapping table of a memory device. The method comprises: receiving, from a host device coupled with the memory device, a first configuration corresponding to a file; refraining from transmitting a logic to physical (L2P) dirty entry notification corresponding to the file to the host device; and transmitting a first confirmation to the host device, wherein the first confirmation indicates refraining from transmitting the L2P dirty entry notification to the host device,

(9) This Summary is provided merely for the purpose of illustrating some aspects to provide an understanding of the subject matter described herein. Accordingly, the above-described features are merely examples and should not be construed to narrow the scope or spirit of the subject matter in this disclosure. Other features, aspects, and advantages of this disclosure will become apparent from the following Detailed Description, Figures, and Claims.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The accompanying drawings are incorporated herein and form a part of the specification.
- (2) FIG. 1 illustrates an example system implementing an enhancement on a data storage system, according to some aspects of the disclosure.
- (3) FIG. 2 illustrates an example method for reading from a memory device, according to aspects of the disclosure.
- (4) FIG. 3 illustrates an example method for writing in the memory device, according to aspects of the disclosure.
- (5) FIG. 4 illustrates an example method for managing a logical-to-physical (L2P) mapping table with a set-hot configuration.
- (6) FIG. 5 illustrates an example method for managing an L2P mapping table with a clear-hot configuration.
- (7) FIG. 6 illustrates an example method for generating set-hot and clear-hot configurations.
- (8) FIG. 7 is an example computer system for implementing some aspects of the disclosure or portion(s) thereof.
- (9) In the drawings, like reference numbers generally indicate identical or similar elements. Additionally, generally, the left-most digit(s) of a reference number identifies the drawing in which the reference number first appears.

DETAILED DESCRIPTION

- (10) Provided herein are system, apparatus, device, method and/or computer program product embodiments, and/or combinations and sub-combinations thereof, for managing a data storage system. The embodiments disclosed herein may improve write and read efficiencies of the storage system.
- (11) According to some aspects, a file in an operating system may correspond to a logical address or a physical address. The operating system may identify the file by the logical address, which may also be referred to as a virtual address. In some aspects, one or more processors of a device generate the logical address of the file and identify the file by the logical address. For example, when executing an application or a program to read a file, the one of more processors determines the logic address of the file. Subsequently, the logic address is mapped to the physical address, where data of the file is actually stored in a memory of the device. The one or more processors then retrieve the data from the memory based on the physical address.
- (12) According to some aspects, a component of the device, such as a flash translation layer (FTL), maps logical addresses to physical addresses. For example, the FTL may maintain a logical-to-physical (L2P) mapping table. Each entry of the L2P mapping table may represent a mapping relationship between a logical address and a physical address. When mapping relationship changes, the FTL updates the L2P mapping table. For example, when the physical address of the file changes, the FTL updates an entry of the L2P mapping table accordingly to map the logical address to an updated physical address. The FTL may reside in devices, including but not limited to wireless communication devices, home entertainment devices, smartphones, laptops, desktops, tablets, personal assistants, monitors, televisions, wearable devices, Internet of Things (IoT) devices, vehicle onboard devices, memory devices (i.e., eMMC NAND flash memory device, UFS NAND flash memory device), and the like.
- (13) According to some aspects, memory devices, such as a NAND flash memory device (i.e., eMMC or UFS) may utilize the L2P mapping table for reading and writing data of the file. For example, the L2P mapping table may be stored in a flash memory of the memory device. When the NAND flash memory device receives a reading request of the file, the FTL may retrieve one or more L2P entries of the L2P mapping table and translate a logical address of the file to a physical address. A processor of the NAND flash memory device may subsequently retrieve data of the file based on the physical address. When the NAND flash memory device receives a writing request of

the file, the processor may perform an erase-and-write operation to write the data of the file in a physical address. For example, the processor may erase data stored in the physical address of the file and write the data of the file in the physical address. In some aspects, the processor may write the data of the file in a different physical address. For example, the processor may determine that the physical address of the file is not suitable for storing the data and locate an updated physical address. The processor, coupled to the FTL, updates the L2P mapping table to reflect such change so that the logical address maps to the updated physical address.

(14) In some aspects, reading and writing operations described above may limit the efficiency of the NAND flash memory device. For example, in the reading operation, retrieving the one or more L2P entries of the L2P mapping table may be time-consuming. Especially when the data to be read is small and frequencies of reading are high, L2P mapping table retrieving becomes cumbersome due to the limitation of flash memory reading speed. In some aspects, the NAND flash memory device may also include a random-access memory (RAM) memory. However, the L2P mapping table may not fit in the RAM memory due to the limited size of the RAM memory. Furthermore, in the writing operation, the processor and the FTL may update the L2P mapping table every time when the physical address changes. This may likewise limit the efficiency of the NAND flash memory device similarly to the reading operation.

(15) According to some aspects, the memory devices may connect with a host device. The host device may include a flash-friendly file System (F2FS), but is not limited to, wireless communication devices, home entertainment devices, smartphones, laptops, desktops, tablets, personal assistants, monitors, televisions, wearable devices, Internet of Things (IoT) devices, vehicle onboard devices, memory devices, and the like. The host device may include a RAM that has a larger capacity than the RAM of the memory device. In some aspects, the memory device may store the L2P mapping table in the RAM of the host device. In some aspects, a speed of the memory device reading from the RAM of the host device may be higher than a speed of the memory device reading from its own flash memory. In other words, a speed of retrieving the L2P mapping table from the RAM of the host device may be higher than a speed of retrieving the L2P mapping table from the flash memory of the memory device. Such cooperation between the memory device and the host device may also be referred to as a host performance booster (HPB) system.

(16) In some aspects, storing the L2P mapping table in the host device improves efficiencies of the reading and writing operations. For example, as discussed above, the memory device may retrieve the one or more L2P entries of the L2P mapping table at a higher speed from the host device. In some aspects, the host device sends reading and/or writing requests to the memory device. The host device may combine the reading and/or writing requests with corresponding entries of the L2P mapping table to form a combined message and send it to the memory device. In such a case, there is no delay caused by retrieving the one or more L2P entries of the L2P mapping table.

(17) According to some aspects, when the processor of the memory device writes data of the file in a new physical address, the one or more L2P entries of the L2P mapping table need to be updated because the logical address maps to the new physical address after the writing operation. When the host device stores the L2P mapping table, the host device needs to update the L2P mapping table stored in its RAM.

(18) In some aspects, the memory device may mark the one or more L2P entries as dirty entries when their corresponding physical addresses change. The memory device notifies the host device that the one or more L2P entries are dirty entries. The host device may request updates of the dirty entries from the memory device to update the L2P mapping table stored in the RAM of the host device. The dirty entries become clean after the update.

(19) According to some aspects, some entries of the L2P mapping table may become dirty entries more frequently than other entries. For example, files containing direct node blocks of directories or directory entry (“dentry”) blocks may subject to change frequently. In other words, the processor

of the memory device may perform writing operations frequently to change data of the files. Therefore, the entries of the L2P mapping table corresponding to the files need to be updated frequently. Consequently, to update the entries, the host device may perform writing operations to the RAM of the host device frequently for the files. Thus, the files that change frequently may have a negative impact on the performance of the HPB system.

(20) In some aspects, the files that change frequently affect the host device because writing operations affect the performance of the host device. As shown in the Table 1 below, for example, when 70% of the operations are writing operations, the input/output operations per second (IOPS) is 13.4 k. When there are only reading operations, the IOPS is 56.1 k. Therefore, decreasing a number of writing operations may improve the performance of the host device.

(21) TABLE-US-00001 TABLE 1 Writing Operation Impact Read/Write 30%:70% 50%:50% 70%:30% 80%:20% 90%:10% 100%:0% IOPS 13.4k 15.8k 21.3k 26.8k 36.8k 56.1k

(22) In some aspects, the files that change frequently also affect the memory device as well. For example, the memory device may send dirty entry notifications and entry updates to the host device to report such changes of the files, which put burdens on the memory device and decrease reading and/or writing efficiencies of the memory device.

(23) According to some aspects, the host device may identify the files that change frequently as hot files. The host device may notify the memory device to disable HPB functions on the hot files. For example, the memory device may refrain from transmitting dirty entry notifications to the host device and rely on the L2P mapping table stored in the flash memory of the memory device for the writing and reading operations. In some aspects, when the memory device determines that entries of the L2P mapping table corresponding to the hot files becomes dirty, the memory device may refrain from sending a notification to the host device. In such a case, frequent entry updates in the host device is avoided. The memory device may update the entries of the L2P mapping table in the memory device when corresponding physical addresses change. In some aspects, the memory device may ignore the entries of the hot files received from the host device in reading and/or writing requests. Instead, the FTL maps logical addresses to physical addresses based on the L2P mapping table stored in the memory device. In some aspects, the host device may refrain from sending entries of the hot files to the memory device.

(24) According to some aspects, the host device identifies hot files based on the properties of the files. For example, the host device may determine that files containing direct node blocks of directories or dentry blocks are hot files. The host device may also identify hot files based on user requests. For example, the user may send requests to the host device identifying hot files.

(25) According to some aspects, the host device may change statuses of hot files. For example, the host device may send a clear-hot notification to the memory device indicating that some hot files are no longer hot files. In such a case, the memory device resumes HPB operations. For example, the memory device resume sending dirty entry notifications to the host device when entries corresponding to the files become dirty.

(26) Various embodiments of these features will now be discussed with respect to the corresponding figures.

(27) FIG. 1 illustrates an example system **100** implementing an enhancement on a data storage system, according to some aspects of the disclosure. The system **100** can include a host device **102** and a memory device **110**. The memory device **110** can be a NAND flash memory device provided in a wireless communication device, a home entertainment device, a smartphone, a laptop, a desktop, a tablet, a personal assistant, a monitor, a television, a wearable device, an Internet of Things (IoT) devices, a vehicle onboard device, and the like. The memory device **110** can include a memory controller **112** and a memory **114**. The memory **114** can include a RAM memory and/or flash memory. The host device **102** can include a processor **104**, a memory **106**, and a controller **108**. In some aspects, the host device **102** communicates with the memory device **110** via the controller **108**.

(28) According to some aspects, the host device **102** stores an L2P mapping table in the memory **106**, wherein the memory **106** can be a RAM memory. The L2P mapping table may include entries that map logical addresses to physical addresses. For example, the processor **104** can receive a reading request of a file. The reading request may include one or more logical addresses of the file. In some aspects, the processor **104** can receive the reading request from an application. The processor **104** can retrieve one or more L2P entries of the L2P mapping table from the memory **106**. The processor **104** can combine the reading request and the one or more L2P entries and send it to the controller **108**. The controller **108** can transmit the combined reading request and the one or more L2P entries to the memory device **110**. The memory controller **112** of the memory device **110** can retrieve the one or more logical addresses from the reading request and map the one or more logical addresses to one or more physical addresses based on the one or more L2P entries. The memory controller **112** can retrieve data from the memory **114** based on the one or more physical addresses. Upon retrieving the data, the memory device **110** can send the data to the host device **102**.

(29) In some aspects, the controller **108** can retrieve the one or more L2P entries of the L2P mapping table from the memory **106** directly. For example, the controller **108** retrieves the one or more logical addresses from the reading request received from the processor **104**. Based on the one or more logical addresses, the controller **108** retrieves the one or more L2P entries of the L2P mapping table from the memory **106**.

(30) According to some aspects, the processor **104** receives a writing request of the file. The writing request may include one or more logical addresses of the file and data to be written to the file. In some aspects, the processor **104** can receive the writing request from an application. Similar to above, the controller **108** can send a combination of the writing request and the one or more L2P entries of the L2P mapping table to the memory device **110**. The memory controller **112** can determine the one or more physical addresses based on the writing request and the one or more L2P entries as similarly discussed above. The memory controller **112** can determine that the one or more physical addresses are not available for writing the data. For example, the one or more physical addresses may not have enough space to store the data. The memory controller **112** can determine one or more updated physical addresses and store the data in the one or more updated physical addresses. Thus, the one or more L2P entries become dirty because the one or more logical addresses no longer map to the one or more physical addresses. The memory controller **112** generates a dirty entry notification indicating that the one or more L2P entries are dirty. The memory device **110** transmits the dirty entry notification to the host device **102**. The host device **102** can request an update of the one or more L2P entries from the memory device **110** and update the one or more L2P entries in the memory **106**. In some aspects, the host device **102** can request the one or more updated physical addresses and update the one or more L2P entries in the memory **106** based on the one or more updated physical addresses.

(31) According to some aspects, the processor **104** can determine a file to be a hot file by such as F2FS (Flash Friendly File System) deposited in the host device **102**. The processor **104** can determine based on the file type. For example, the processor **104** can determine that files containing direct node blocks of directories or dentry blocks are hot files. This is because these files are subject to change frequently. The processor **104** can determine that files are hot files based on user requests. Upon determining that the files are hot files, the processor **104** can notify the memory device **110** via the controller **108**. For example, the processor **104** can generate a set-hot configuration and send to the controller **108**, which forwards the set-hot configuration to the memory device **110**. The memory device **110** can mark the files to be hot. When one or more physical addresses of the files change, the memory device **110** refrains from notifying the host device **102**. Instead, the memory device **110** updates one or more L2P entries of an L2P mapping table stored in the memory **114** based on changes of the one or more physical addresses of the file.

(32) According to some aspects, the processor **104** can determine that a file is no longer a hot file.

The processor **104** can determine based on a change of file type. For example, the processor **104** can determine that the files no longer contain direct node blocks of directories or dentry blocks. The processor **104** can also determine based on user requests. For example, the processor **104** can receive a user request indicating that a file is no longer a hot file. Upon determining that the file is no longer a hot file, the processor **104** can notify the memory device **110** via the controller **108**. For example, the processor **104** can generate a clear-hot configuration and send it to the controller **108**, which forwards the clear-hot configuration to the memory device **110**. The memory device **110** can mark that the file is no longer a hot file. When physical addresses of the file change, the memory device **110** resumes notifying the host device **102**.

(33) FIG. 2 illustrates an example method for reading from a memory device, according aspects of the disclosure. As a convenience and not a limitation, FIG. 2 may be described with regard to elements of FIGS. 1 and 7. Method **200** can represent the operation of an electronic device (for example, the host devices **102** of FIG. 1) implementing the reading operation. Method **200** can also be performed by computer system **700** of FIG. 7. But method **200** is not limited to the specific aspects depicted in those figures and other systems may be used to perform the method, as will be understood by those skilled in the art. It is to be appreciated that not all operations may be needed, and the operations may not be performed in the same order as shown in FIG. 2.

(34) At **202**, the electronic device may generate a read request. For example, the electronic device generates the read request for reading a group of data of a file. The read request may include one or more logical addresses of the file.

(35) At **204**, the electronic device may retrieve an L2P entry corresponding to the file or the one or more logical addresses. For example, the electronic device may retrieve the L2P entry from an L2P mapping table stored in the electronic device.

(36) At **206**, the electronic device may combine the read request and the L2P entry. For example, the electronic device may generate a combined request including the read request and the L2P entry. The electronic device may also encrypt the combined request.

(37) At **208**, the electronic device may transmit the combined request to a memory device, such as the memory device **110** of FIG. 1.

(38) At **210**, the electronic device may receive a group of data from the memory device, wherein the group of data corresponds to the file.

(39) FIG. 3 illustrates an example method for writing to a memory device, according to aspects of the disclosure. As a convenience and not a limitation, FIG. 3 may be described with regard to elements of FIGS. 1 and 7. Method **300** can represent the operation of an electronic device (for example, the host devices **102** of FIG. 1) implementing the writing operation. Method **300** can also be performed by computer system **700** of FIG. 7. But method **300** is not limited to the specific aspects depicted in those figures and other systems may be used to perform the method, as will be understood by those skilled in the art. It is to be appreciated that not all operations may be needed, and the operations may not be performed in the same order as shown in FIG. 3.

(40) At **302**, the electronic device may generate a write request. For example, the electronic device generates the write request for writing a group of data of a file. The write request may include one or more logical addresses of the file and the group of data.

(41) At **304**, the electronic device may retrieve an L2P entry corresponding to the file or the one or more logical addresses. For example, the electronic device may retrieve the L2P entry from an L2P mapping table stored in the electronic device.

(42) At **306**, the electronic device may combine the write request and the L2P entry. For example, the electronic device may generate a combined request including the write request and the L2P entry. The electronic device may also encrypt the combined request.

(43) At **308**, the electronic device may transmit the combined request to a memory device, such as the memory device **110** of FIG. 1.

(44) At **310**, the electronic device may receive an L2P dirty entry notification from the memory

device, wherein the L2P dirty entry notification corresponds to the L2P entry of the L2P mapping table.

(45) FIG. 4 illustrates an example method for managing an L2P mapping table with a set-hot configuration. As a convenience and not a limitation, FIG. 4 may be described with regard to elements of FIGS. 1 and 7. Method 400 can represent the operation of electronic devices (for example, the host devices 102 and the memory device 110 of FIG. 1) managing the L2P mapping table with a set-hot configuration. Method 400 can also be performed by computer system 700 of FIG. 7. But method 400 is not limited to the specific aspects depicted in those figures and other systems may be used to perform the method, as will be understood by those skilled in the art. It is to be appreciated that not all operations may be needed, and the operations may not be performed in the same order as shown in FIG. 4.

(46) At 402, the processor 104 of the host device 102 generates a set-hot configuration corresponding to a file. The processor 104 can determine the file to be a hot file. The processor 104 can determine based on a file type. For example, the processor 104 can determine that files containing direct node blocks of directories or dentry blocks are hot files. This is because these files are subject to change frequently. The processor 104 can also determine that files are hot files based on user requests.

(47) At 404, the processor 104 transmits the set-hot configuration to the controller 108.

(48) At 406, the controller 108 transmits the set-hot configuration to the memory device 110. In some aspects, the controller 108 can forward the set-hot configuration generated by the processor 104. The controller 108 can also generate and transmit a new set-hot configuration that is compatible with the memory device 110 based on the set-hot configuration received. In some aspects, the controller 108 can encrypt the set-hot configuration before transmitting.

(49) At 408, the memory device 110 disables dirty entry notifications. For example, the memory device 110 can refrain from notifying the host device 102 when an L2P entry of an L2P mapping table corresponding to the file becomes dirty. In some aspects, the memory device may ignore L2P entries of the file received from the host device 102. In some aspects, upon receiving the set-hot configuration from the controller 108, the memory device 110 can decrypt the set-hot configuration.

(50) At 410, the memory device 110 transmits a confirmation for the set-hot configuration to the controller 108 of the host device 102. The confirmation indicates that the memory device 110 no longer transmits dirty entry notification corresponding to the file to the host device 102.

(51) At 412, the controller 108 transmits the confirmation for the set-hot configuration to the processor 104.

(52) At 414, the processor 104 generates a combined write request similarly as described in 306 of FIG. 3. The combined request may include one or more logical addresses of a file, one or more L2P entries of the L2P mapping table, and a group of data to be written in the file.

(53) At 416, the processor 104 transmits the combined write request to the controller 108.

(54) At 418, the controller 108 transmits the combined write request to the memory device 110. In some aspects, the controller 108 can also encrypt the combined write request.

(55) At 420, the memory device 110 writes the group of data in a memory, such as the memory 114 of the memory device 110 in FIG. 1. In some aspects, the memory device 110 determines one or more physical addresses of the memory 114 based on the write request. For example, the memory device 110 retrieves the one or more logical addresses and the one or more L2P entries of the L2P mapping table from the write request. The memory device 110 maps the one or more logical addresses to the one or more physical addresses based on the one or more L2P entries of the L2P mapping table. The memory device 110 can determine that the one or more physical addresses are not suitable for storing the group of data contained in the write request based on available spaces in the one or more physical addresses. The memory device 110 can determine one or more updated physical addresses and store the group of data in the one or more updated physical addresses. In

such a case, the one or more L2P entries of the L2P mapping table in the host device **102** becomes dirty entries because the one or more logical addresses map to the one or more updated physical addresses.

(56) In some aspects, upon receiving the combined write request, the memory device **110** decrypt the combined write request.

(57) At **422**, the memory device **110** updates one or more L2P entries of an L2P mapping table stored in the memory **114** of the memory device **110** based on the one or more updated physical addresses.

(58) In some aspects, because the memory device **110** disabled the dirty entry notification in step **408** as described above, the memory device **110** refrains from transmitting a notification regarding the dirty entries of the L2P mapping table in the host device **102**.

(59) At **424**, the processor **104** generates a combined read request similarly as described in **206** of FIG. **2**. The combined read request includes the one or more logical addresses of the file and the one or more L2P entries of the L2P mapping table stored in the host device **102**.

(60) At **426**, the processor **104** transmits the combined read request to the controller **108**.

(61) At **428**, the controller **108** transmits the combined read request to the memory device **110**. In some aspects, the controller **108** can also encrypt the combined read request.

(62) At **430**, the memory device **110** retrieve the one or more updated L2P entries stored in the memory device **110**. For example, the memory device **110** retrieves the one or more logical addresses of the file from the combined read request received. The memory device **110** retrieves the one or more updated L2P entries from the memory **114** of the memory device **110** based on the one or more logical addresses. In some aspects, the memory device may ignore the one or more L2P entries received in the combined read request.

(63) At **432**, the memory device **110** retrieves the group of data based on the one or more updated physical addresses. For example, the memory device **110** determines the one or more updated physical addresses based on the one or more logical addresses and the one or more updated L2P entries. The memory device retrieves the group of data, based on the one or more updated physical addresses, stored in the memory **114** of the memory device **110**.

(64) At **434**, the memory device **110** transmits the group of data to the controller **108**.

(65) At **436**, the controller **108** transmits the group of data to the processor **104**.

(66) FIG. **5** illustrates an example method for managing an L2P mapping table with a clear-hot configuration. As a convenience and not a limitation, FIG. **5** may be described with regard to elements of FIGS. **1** and **7**. Method **500** can represent the operation of electronic devices (for example, the host devices **102** and the memory device **110** of FIG. **1**) managing the L2P mapping table with a clear-hot configuration. Method **500** can also be performed by computer system **700** of FIG. **7**. But method **500** is not limited to the specific aspects depicted in those figures and other systems may be used to perform the method, as will be understood by those skilled in the art. It is to be appreciated that not all operations may be needed, and the operations may not be performed in the same order as shown in FIG. **5**.

(67) At **502**, the processor **104** of the host device **102** generates a clear-hot configuration corresponding to a file. The processor **104** can determine that the file is no longer a hot file. The processor **104** can determine based on a change of a file type. For example, the processor **104** can determine that the file no longer contains direct node blocks of directories or dentry blocks are hot files. The processor **104** can determine that the file is no longer a hot file based on user requests.

(68) At **504**, the processor **104** transmits the clear-hot configuration to the controller **108**.

(69) At **506**, the controller **108** transmits the clear-hot configuration to the memory device **110**. In some aspects, the controller **108** can forward the clear-hot configuration generated by the processor **104**. The controller **108** can also generate and transmit a new clear-hot configuration that is compatible with the memory device **110** based on the clear-hot configuration received. In some aspects, the controller **108** can encrypt the clear-hot configuration before transmitting.

(70) At **508**, the memory device **110** enables dirty entry notifications based on the clear-hot configuration received. For example, the memory device **110** can resume notifying the host device **102** when an L2P entry of an L2P mapping table corresponding to the file becomes dirty. In some aspects, the memory device may resume using L2P entries of the file received from the host device **102**. In some aspects, upon receiving the clear-hot configuration from the controller **108**, the memory device **110** can decrypt the clear-hot configuration.

(71) In some implementation, at **508**, the updated L2P entries obtained at **422** could be uploaded to the memory **106** in the host device **102**. Thus, the updated L2P entries can be resumed to using.

(72) At **510**, the memory device **110** transmits a confirmation for the clear-hot configuration to the controller **108** of the host device **102**. The confirmation indicates that the memory device **110** resumed transmitting dirty entry notifications corresponding to the file to the host device **102**.

(73) At **512**, the controller **108** transmits the confirmation for the clear-hot configuration to the processor **104**.

(74) At **514**, the processor **104** generates a combined write request similarly as described in **306** of FIG. **3**. The combined request may include one or more logical addresses of a file, one or more L2P entries of the L2P mapping table, and a group of data to be written in the file.

(75) At **516**, the processor **104** transmits the combined write request to the controller **108**.

(76) At **518**, the controller **108** transmits the combined write request to the memory device **110**. In some aspects, the controller **108** can also encrypt the combined write request.

(77) At **520**, the memory device **110** writes the group of data in a memory, such as the memory **114** of the memory device **110** in FIG. **1**. In some aspects, the memory device **110** determines one or more physical addresses of the memory **114** based on the write request. For example, the memory device **110** retrieves the one or more logical addresses and the one or more L2P entries of the L2P mapping table from the write request. The memory device **110** maps the one or more logical addresses to the one or more physical addresses based on the one or more L2P entries of the L2P mapping table. The memory device **110** can determine that the one or more physical addresses are not suitable for storing the group of data contained in the write request based on available spaces in the one or more physical addresses. The memory device **110** can determine one or more updated physical addresses and store the group of data in the one or more updated physical addresses. In such a case, the one or more L2P entries of the L2P mapping table in the host device **102** becomes dirty entries because the one or more logical addresses map to the one or more updated physical addresses.

(78) In some aspects, upon receiving the combined write request, the memory device **110** decrypt the combined write request.

(79) At **522**, the memory device **110** updates one or more L2P entries of an L2P mapping table stored in the memory **114** of the memory device **110** based on the one or more updated physical addresses.

(80) At **524**, the memory device generates a dirty entry notification. In some aspects, the dirty entry notification indicates that the one or more L2P entries of the L2P mapping table stored in the memory **106** of the host device **102** became dirty. According to some aspects, the memory device may include the one or more updated L2P entries in the dirty entry notification.

(81) At **526**, the memory device transmits the dirty entry notification to the controller **108** of the host device **102**.

(82) At **528**, the controller **108** transmits the dirty entry notification to the processor **104**.

(83) At **530**, the processor **104** transmits an L2P update request to the controller **108**. The L2P update request may include identifications of the one or more L2P entries indicated in the dirty entry notification. In some aspects, the L2P update request may include an identification of the dirty entry notification received from the memory device **110**.

(84) At **532**, the controller **108** transmits the L2P update request to the memory device **110**.

(85) At **534**, the memory device **110** transmits the one or more updated L2P entries to the controller

108. In some aspects, the memory device **110** can retrieve the one or more updated L2P entries based on the identifications of the one or more updated L2P entries received from the host device **102**. The memory device **110** can also retrieve the one or more updated L2P entries based on the identification of the dirty entry notification.

(86) At **536**, the controller **108** transmits the one or more updated L2P entries to the processor **104**.

(87) At **538**, the processor **104** updates the L2P mapping table stored in the memory **106** based on the one or more updated L2P entries received from the memory device **110**.

(88) FIG. **6** illustrates an example method for generating set-hot and clear-hot configurations. As a convenience and not a limitation, FIG. **6** may be described with regard to elements of FIGS. **1** and **7**. Method **600** can represent the operation of an electronic device (for example, the host devices **102** of FIG. **1**) generating set-hot and clear-hot configurations. Method **600** can also be performed by computer system **700** of FIG. **7**. But method **600** is not limited to the specific aspects depicted in those figures and other systems may be used to perform the method, as will be understood by those skilled in the art. It is to be appreciated that not all operations may be needed, and the operations may not be performed in the same order as shown in FIG. **6**.

(89) At **602**, the electronic device determines whether a user request corresponding to a file is received. The user request indicates whether the file is a hot file. If the electronic device determines that the user request is received, the control moves to **604**.

(90) At **604**, the electronic device determines whether the user request instructs to set the file as a hot file. If yes, the control moves to **606**.

(91) At **606**, the electronic device generates a set-hot configuration corresponding to the file as discussed in **402** of FIG. **4** above.

(92) Referring back to **604**, if the user request instructs not to set the file as a hot file, the control moves to **608**.

(93) At **608**, the electronic device generates a clear-hot configuration corresponding to the file as discussed in **502** of FIG. **5** above.

(94) Referring back to **602**, if the electronic device determines that no user request is received, the control moves to **610**.

(95) At **610**, the electronic device determines a file type of the file by such as F2FS (Flash Friendly File System).

(96) At **612**, the electronic device determines whether the file type is one of the hot file types. For example, a hot file type may indicate that the file includes direct node blocks of directories or dentry blocks. If the electronic device determines that the file type is one of the hot file types, the control moves to **606** to set the file as a hot file.

(97) If the electronic device determines that the file type is no one of the hot file types, the control moves to **608** to set the file as a code file by generating a clear-hot configuration as described above.

(98) Various aspects may be implemented, for example, using one or more computer systems, such as computer system **700** shown in FIG. **7**. Computer system **700** can be any well-known computer capable of performing the functions described herein such as the host device **102** and the memory device **110** of FIG. **1**. Computer system **700** includes one or more processors (also called central processing units, or CPUs), such as a processor **704**. Processor **704** is connected to a communication infrastructure **706** (e.g., a bus.) Computer system **700** also includes user input/output device(s) **703**, such as monitors, keyboards, pointing devices, etc., that communicate with communication infrastructure **706** through user input/output interface(s) **702**. Computer system **700** also includes a main or primary memory **708**, such as random access memory (RAM). Main memory **708** can include one or more levels of cache. Main memory **708** has stored therein control logic (e.g., computer software) and/or data.

(99) Computer system **700** can also include one or more secondary storage devices or memory **710**. Secondary memory **710** can include, for example, a hard disk drive **712** and/or a removable storage

device or drive **714**. Removable storage drive **714** can be a floppy disk drive, a magnetic tape drive, a compact disk drive, an optical storage device, tape backup device, and/or any other storage device/drive.

(100) Removable storage drive **714** can interact with a removable storage unit **718**. Removable storage unit **718** includes a computer usable or readable storage device having stored thereon computer software (control logic) and/or data. Removable storage unit **718** can be a floppy disk, magnetic tape, compact disk, DVD, optical storage disk, and/or any other computer data storage device. Removable storage drive **714** reads from and/or writes to removable storage unit **718** in a well-known manner.

(101) According to some aspects, secondary memory **710** can include other means, instrumentalities or other approaches for allowing computer programs and/or other instructions and/or data to be accessed by computer system **700**. Such means, instrumentalities or other approaches may include, for example, a removable storage unit **722** and an interface **720**. Examples of the removable storage unit **722** and the interface **720** can include a program cartridge and cartridge interface (such as that found in video game devices), a removable memory chip (such as an EPROM or PROM) and associated socket, a memory stick and USB port, a memory card and associated memory card slot, and/or any other removable storage unit and associated interface.

(102) Computer system **700** can further include a communication or network interface **724**. Communication interface **724** enables computer system **700** to communicate and interact with any combination of remote devices, remote networks, remote entities, etc. (individually and collectively referenced by reference number **728**). For example, communication interface **724** can allow computer system **700** to communicate with remote devices **728** over communications path **726**, which may be wired and/or wireless, and which may include any combination of LANs, WANs, the Internet, etc. Control logic and/or data may be transmitted to and from computer system **700** via communication path **726**.

(103) The operations in the preceding aspects may be implemented in a wide variety of configurations and architectures. Therefore, some or all of the operations in the preceding aspects may be performed in hardware, in software or both. In some aspects, a tangible, non-transitory apparatus or article of manufacture includes a tangible, non-transitory computer useable or readable medium having control logic (software) stored thereon is also referred to herein as a computer program product or program storage device. This includes, but is not limited to, computer system **700**, main memory **708**, secondary memory **710** and removable storage units **718** and **722**, as well as tangible articles of manufacture embodying any combination of the foregoing. Such control logic, when executed by one or more data processing devices (such as computer system **700**), causes such data processing devices to operate as described herein.

(104) Based on the teachings contained in this disclosure, it will be apparent to persons skilled in the relevant art(s) how to make and use aspects of the disclosure using data processing devices, computer systems and/or computer architectures other than that shown in FIG. 7. In particular, aspects may operate with software, hardware, and/or operating system implementations other than those described herein.

(105) In summary, the present disclosure describes various embodiments of a memory storage system and methods of making the same.

(106) Some aspects of this disclosure provide a host device comprising a memory and a processor coupled to the memory. The memory is used to store a logic-to-physical (L2P) mapping table that includes an entry mapping logical addresses of a file to physical addresses of a file. The processor is configured to generate a first configuration corresponding to a file and transmit the first configuration to a memory device. The first configuration instructs the memory device to refrain from transmitting a L2P dirty entry notification to the host device. The L2P dirty entry notification corresponds to the file.

(107) Some aspects of this disclosure relate to the host device, wherein the host device further

comprises a controller. The controller is coupled to the memory and the process, and is configured to drive the memory device.

(108) Some aspects of this disclosure relate to the host device, wherein the processor is further configured to generate a read request to retrieve a group of data from the memory device, wherein the group of data corresponds to the file; generate a combined request by combining the read request with the L2P entry; and transmit the combined request to the memory device.

(109) Some aspects of this disclosure relate to the host device, wherein the processor is further configured to generate a write request to write a group of data into the memory device, wherein the group of data corresponds to the file; generate a combined request by combining the write request with the L2P entry; and transmit the combined request to the memory device.

(110) Some aspects of this disclosure relate to the host device, wherein the processor is further configured to generate the first configuration corresponding to the file by determining that the file includes direct node blocks of directories or directory entry blocks, or receiving a user request corresponding to the file.

(111) Some aspects of this disclosure relate to the host device, wherein the least one processor is further configured to generate the first configuration corresponding to the file by determining the file to be a hot file through a flash-friendly file System (F2FS) deposited in the host device.

(112) Some aspects of this disclosure relate to the host device, wherein the processor is further configured to generate a second configuration corresponding to the file and transmit the second configuration to the memory device. The second configuration instructs the memory device to resume transmitting the L2P dirty entry notification corresponding to the file to the host device.

(113) Some aspects of this disclosure relate to the host device, wherein the processor is further configured to receive the L2P dirty entry notification from the memory device; transmit an L2P mapping update request to the memory device; receive an L2P mapping update from the memory device; and update the L2P entry of the file in the L2P mapping table based on the L2P mapping update.

(114) Some aspects of this disclosure relate to the host device, wherein the first configuration includes a set-hot configuration corresponding to the file, and the second configuration includes a clear-hot configuration corresponding to the file.

(115) Some aspects of this disclosure relate to the host device, wherein the memory includes a RAM memory.

(116) Some aspects of this disclosure relate to the host device, wherein the host device is provided with a host performance booster (HPB) system, and the processor is further configured to, in response to refraining from transmitting a L2P dirty entry notification to the host device, disable HPB functions of the HPB system on the file.

(117) Some aspects of this disclosure relate to the host device, wherein the processor is further configured to, in response to resuming transmitting the L2P dirty entry notification, enable HPB functions of the HPB system on the file.

(118) Some aspects of this disclosure provide a memory device comprising a memory and a processor coupled to the memory. The memory controller is configured to receive, from a host device, a first configuration corresponding to a file; refrain from transmitting a logic to physical (L2P) dirty entry notification corresponding to the file to the host device; and transmit a first confirmation to the host device, wherein the first confirmation indicates refraining from transmitting the L2P dirty entry notification to the host device.

(119) Some aspects of this disclosure relate to the memory device, wherein the memory controller is further configured to receive a combined request from the host device, wherein the combined request includes a read request and an L2P entry of the file; determine a logic address of the file based on the read request; determine a physical address of the file based on the logic address and the L2P entry; retrieve, from the memory, a group of data based on the physical address; and transmit the group of data to the host device.

(120) Some aspects of this disclosure relate to the memory device, wherein the memory controller is further configured to decrypt the combined request.

(121) Some aspects of this disclosure relate to the memory device, wherein the memory controller is further configured to receive a combined request from the host device, wherein the combined request includes a write request and an L2P entry of the file; determine a logic address of the file based on the write request; determine a physical address of the file based on the logic address and the L2P entry; determine a second physical address; and write a group of data in the second physical address.

(122) Some aspects of this disclosure relate to the memory device, wherein the memory controller is further configured to update the L2P entry based on the second physical address; and store the updated L2P entry in the memory.

(123) Some aspects of this disclosure relate to the memory device, wherein the memory controller is further configured to receive a second configuration corresponding to the file from the host device; resume transmitting the L2P dirty entry notification corresponding to the file to the host device based on the second configuration; and transmit a second confirmation to the host device, wherein the second confirmation indicates resuming transmitting the L2P dirty entry notification to the host device.

(124) Some aspects of this disclosure relate to the memory device, wherein the memory controller is further configured to receive a combined request from the host device, wherein the combined request includes a write request and an L2P entry of the file; determine a logic address of the file based on the write request; determine a physical address of the file based on the logic address and the L2P entry; determine a second physical address; update the L2P entry based on the second physical address; and transmit the L2P dirty entry notification corresponding to the updated L2P entry to the host device based on the second configuration.

(125) Some aspects of this disclosure relate to the memory device, wherein the memory controller is further configured to receive an L2P mapping update request from the host device; and transmit the update L2P entry to the host device.

(126) Some aspects of this disclosure relate to the memory device, wherein the memory includes a RAM memory for storing a logic-to-physical (L2P) mapping table that includes an entry mapping logical addresses of the file to physical addresses of the file, and a NAND flash memory.

(127) Some aspects of this disclosure relate to the memory device, wherein the first configuration includes a set-hot configuration corresponding to the file, and the second configuration includes a clear-hot configuration corresponding to the file.

(128) Some aspects of this disclosure provide a system comprising a host device and a memory device. The host device is configured to generate a first configuration corresponding to a file; and transmit the first configuration to a memory device. The memory device is configured to receive, from the host device, the first configuration; and refrain from transmitting a logic-to-physical (L2P) dirty entry notification corresponding to the file to the host device.

(129) Some aspects of this disclosure relate to the system, wherein the host device is further configured to generate a second configuration corresponding to the file; and transmit the second configuration to the memory device, wherein the second configuration instructs the memory device to resume transmitting the L2P dirty entry notification corresponding to the file to the host device.

(130) Some aspects of this disclosure relate to the system, wherein the memory device is further configured to receive a second configuration from the host device; resume transmitting the L2P dirty entry notification corresponding to the file to the host device based on the second configuration; and transmit a confirmation to the host device, wherein the confirmation indicates resuming transmitting the L2P dirty entry notification to the host device.

(131) Some aspects of this disclosure relate to the system, wherein the memory device is further configured to receive an L2P entry from the host device; update the L2P entry; and transmit the updated L2P entry to the host device based on the second configuration.

(132) Some aspects of this disclosure relate to the system, wherein the host device is provided with a host performance booster (HPB) system, and a processor of host device is configured to, in response to refraining from transmitting a L2P dirty entry notification to the host device, disable HPB functions of the HPB system on the file.

(133) Some aspects of this disclosure relate to the system, wherein the processor is further configured to, in response to resuming transmitting the L2P dirty entry notification, enable HPB functions of the HPB system on the file.

(134) Some aspects of this disclosure provide a system, comprising a host device and a memory device. The host device comprises a first memory for storing a logic-to-physical (L2P) mapping table that includes an entry mapping logical addresses of a file to physical addresses of a file; the host device further comprises a processor coupled to the first memory, and the processor is configured to: generate a first configuration corresponding to the file; and transmit the first configuration to a memory device, wherein the first configuration instructs the memory device to refrain from transmitting a L2P dirty entry notification to the host device, and wherein the L2P dirty entry notification corresponds to the file. The memory device comprises a second memory and a memory controller coupled to the second memory; the memory controller is configured to: receive, from a host device, a first configuration corresponding to a file; refrain from transmitting a logic to physical (L2P) dirty entry notification corresponding to the file to the host device; and transmit a first confirmation to the host device, wherein the first confirmation indicates refraining from transmitting the L2P dirty entry notification to the host device.

(135) Some aspects of this disclosure provide a method for managing a L2P mapping table of a memory device. The method comprises: receiving, from a host device coupled with the memory device, a first configuration corresponding to a file; refraining from transmitting a logic to physical (L2P) dirty entry notification corresponding to the file to the host device; and transmitting a first confirmation to the host device, wherein the first confirmation indicates refraining from transmitting the L2P dirty entry notification to the host device,

(136) Some aspects of this disclosure relate to the method, wherein the method further comprises: decrypting the combined request.

(137) Some aspects of this disclosure relate to the method, wherein the method further comprises: receiving a combined request from the host device, wherein the combined request includes a write request and an L2P entry of the file; determining a logic address of the file based on the write request; determining a physical address of the file based on the logic address and the L2P entry; determining a second physical address; and writing a group of data in the second physical address.

(138) Some aspects of this disclosure relate to the method, wherein the method further comprises: updating the L2P entry based on the second physical address; and storing the updated L2P entry in the memory.

(139) Some aspects of this disclosure relate to the method, wherein the first configuration includes a set-hot configuration corresponding to the file, and the second configuration includes a clear-hot configuration corresponding to the file.

(140) The Summary and Abstract sections can set forth one or more but not all exemplary embodiments of the present disclosure as contemplated by the inventor(s), and thus, are not intended to limit the present disclosure and the appended claims in any way.

(141) While the disclosure has been described herein with reference to exemplary aspects for exemplary fields and applications, it should be understood that the disclosure is not limited thereto. Other aspects and modifications thereto are possible, and are within the scope and spirit of the disclosure. For example, and without limiting the generality of this paragraph, aspects are not limited to the software, hardware, firmware, and/or entities illustrated in the figures and/or described herein. Further, aspects (whether or not explicitly described herein) have significant utility to fields and applications beyond the examples described herein.

(142) Aspects have been described herein with the aid of functional building blocks illustrating the

implementation of specified functions and relationships thereof. The boundaries of these functional building blocks have been arbitrarily defined herein for the convenience of the description. Alternate boundaries can be defined as long as the specified functions and relationships (or equivalents thereof) are appropriately performed. In addition, alternative aspects may perform functional blocks, steps, operations, methods, etc. using orderings different from those described herein.

(143) References herein to “one aspect,” “an aspect,” “an example aspect,” or similar phrases, indicate that the aspect described may include a particular feature, structure, or characteristic, but every aspect may not necessarily include the particular feature, structure, or characteristic. Moreover, such phrases are not necessarily referring to the same aspect. Further, when a particular feature, structure, or characteristic is described in connection with an aspect, it would be within the knowledge of persons skilled in the relevant art(s) to incorporate such feature, structure, or characteristic into other aspects whether or not explicitly mentioned or described herein.

(144) The breadth and scope of the disclosure should not be limited by any of the above-described exemplary aspects, but should be defined only in accordance with the following claims and their equivalents.

(145) It is well understood that the use of personally identifiable information should follow privacy policies and practices that are generally recognized as meeting or exceeding industry or governmental requirements for maintaining the privacy of users. In particular, personally identifiable information data should be managed and handled so as to minimize risks of unintentional or unauthorized access or use, and the nature of authorized use should be clearly indicated to users.

Claims

1. A method for managing a logic to physical (L2P) mapping table of a memory device, comprising: receiving, from a host device coupled with the memory device, a first configuration indicating that a first file is designated as a hot file; in response to receiving the first configuration, transmitting a first confirmation to the host device without transmitting a L2P dirty entry notification associated with the first file; receiving a second configuration corresponding to a second file from the host device; transmitting the L2P dirty entry notification associated with the second file to the host device based on the second configuration, wherein the L2P dirty entry notification indicates that a L2P entry of the L2P mapping table stored in the host device has become dirty; and in response to receiving the second configuration, transmitting a second confirmation to the host device.
2. The method of claim 1, further comprising: receiving a combined request from the host device, wherein the combined request includes a read request and the L2P entry of the second file; determining a logic address of the second file based on the read request; determining a physical address of the second file based on the logic address and the L2P entry; retrieving, from a memory of the memory device, a group of data based on the physical address; and transmitting the group of data to the host device.
3. The method of claim 2, further comprising: decrypting the combined request.
4. The method of claim 1, further comprising: receiving a combined request from the host device, wherein the combined request includes a write request and the L2P entry of the second file; determining a logic address of the second file based on the write request; determining a physical address of the second file based on the logic address and the L2P entry; determining a second physical address; and writing a group of data in the second physical address.
5. The method of claim 4, further comprising: updating the L2P entry based on the second physical address; and storing the updated L2P entry in the memory.
6. The method of claim 1, wherein the first configuration includes a set-hot configuration

corresponding to the first file, and the set-hot configuration indicates that the first file is designated as the hot file in case that the first file comprises direct node blocks of directories or dentry blocks.

7. The method of claim 1, further comprising: receiving a combined request from the host device, wherein the combined request includes a write request and the L2P entry of the second file; determining a logic address of the second file based on the write request; determining a physical address of the second file based on the logic address and the L2P entry; determining a second physical address; updating the L2P entry based on the second physical address; and transmitting the L2P dirty entry notification corresponding to the updated L2P entry to the host device based on the second configuration.

8. The method of claim 7, further comprising: receiving an L2P mapping update request from the host device; and transmitting the updated L2P entry to the host device.

9. The method of claim 1, wherein the second configuration includes a clear-hot configuration corresponding to the second file.

10. A method for managing a logic to physical (L2P) mapping table of a host device, comprising: designating a first file as a hot file; transmitting, from the host device, a first configuration for instructing a memory device to not to transmit a L2P dirty entry notification associated with the first file to the host device, transmitting a second configuration corresponding to a second file to the memory device; and receiving the L2P dirty entry notification associated with the second file from the memory device based on the second configuration, wherein the L2P dirty entry notification associated with the second file indicates that a L2P entry of the L2P mapping table has become dirty.

11. The method of claim 10, further comprising: generating a combined request comprising the L2P entry and a read request to retrieve a group of data from the memory device; and transmitting the combined request to the memory device.

12. The method of claim 10, further comprising: generating a combined request comprising the L2P entry and a write request to write a group of data into the memory device, and transmitting the combined request to the memory device.

13. The method of claim 10, wherein the first configuration includes a set-hot configuration corresponding to the first file, the set-hot configuration indicates that the first file is designated as the hot file in case that the first file comprises direct node blocks of directories or dentry blocks.

14. The method of claim 10, further comprising: transmitting an L2P mapping update request to the memory device; receiving an L2P mapping update from the memory device; and updating the L2P entry of the second file in the L2P mapping table based on the L2P mapping update.

15. The method of claim 10, wherein the second configuration includes a clear-hot configuration corresponding to the second file.

16. A system, comprising: a host device comprising: a first memory for storing a logic-to-physical (L2P) mapping table that includes L2P entry mapping logical addresses to physical addresses; and a processor coupled to the first memory and configured to: transmit, to a memory device, a first configuration indicating that a first file is designated as a hot file, transmit, to the memory device, a second configuration indicates a second file is designated as a cold file, receive a logic to physical (L2P) dirty entry notification associated with the second file based on the second configuration, wherein the L2P dirty entry notification indicates that a L2P entry of the L2P mapping table stored in the host device has become dirty, and receive an updated L2P entry from the memory device; and the memory device comprising: a second memory; and a memory controller coupled to the second memory and configured to: receive, from the host device, the first configuration; in response to receiving the first configuration, transmit a first confirmation to the host device without transmitting the L2P dirty entry notification associated with the first file, receive, from the host device, the second configuration; transmit the L2P dirty entry notification associated with the second file to the host device based on the second configuration; and in response to receiving the second configuration, transmit a second confirmation to the host device.

17. The system of claim 16, wherein the first configuration includes a set-hot configuration corresponding to the first file, and the set-hot configuration indicates that the first file is designated as the hot file in case that the first file comprises direct node blocks of directories or dentry blocks.
18. The system of claim 16, wherein the memory controller is further configured to: receive a combined request from the host device, wherein the combined request includes a read request and the L2P entry of the second file; determine a logic address of the second file based on the read request; determine a physical address of the second file based on the logic address and the L2P entry; retrieve a group of data based on the physical address; and transmit the group of data to the host device.
19. The system of claim 18, wherein the memory controller is further configured to decrypt the combined request.
20. The system of claim 16, wherein the memory controller is further configured to: receive a combined request from the host device, wherein the combined request includes a write request and the L2P entry of the second file; determine a logic address of the second file based on the write request; determine a physical address of the second file based on the logic address and the L2P entry; determine a second physical address; and write a group of data in the second physical address.
-