

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12412268
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Matsuki; Kenji et al.

Treatment system, control device, and control method

Abstract

A treatment system that includes a treatment instrument to apply a treatment energy to a living tissue from an end effector according to a supplied electric power to incise the living tissue, an imaging device to generate a captured image capturing a state in which the treatment energy is applied from the end effector to the living tissue, and a control device that includes a processor to control operation of the imaging device. The processor acquires the captured image, calculates a temporal change amount based on any one of a predetermined point and a predetermined area in the captured image as a determination value, determines whether incision of the living tissue has been completed based on the determination value, and in response to determining that incision of the living tissue has been completed, execute an instruction to stop supply of the electric power to the treatment instrument.

Inventors: Matsuki; Kenji (Hachioji, JP), Hirabayashi; Yuto (Suwa, JP), Matsui; Shunsuke (Hachioji, JP)

Applicant: OLYMPUS CORPORATION (Hachioji, JP)

Family ID: 76787782

Assignee: OLYMPUS CORPORATION (Tokyo, JP)

Appl. No.: 17/859824

Filed: July 07, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20220343503 A1	Oct. 27, 2022

Related U.S. Application Data

continuation parent-doc WO PCT/JP2020/000470 20200109 PENDING child-doc US 17859824

Publication Classification

Int. Cl.: **G06T7/00** (20170101); **A61B1/00** (20060101); **G06T7/90** (20170101); A61B18/00 (20060101)

U.S. Cl.:

CPC **G06T7/0012** (20130101); **A61B1/00009** (20130101); **G06T7/90** (20170101); A61B2018/00601 (20130101); A61B2018/00708 (20130101); A61B2018/00982 (20130101); G06T2207/10068 (20130101); G06T2207/20081 (20130101); G06T2207/30004 (20130101)

Field of Classification Search

CPC: G06T (7/0012); G06T (7/90); G06T (2207/10068); G06T (2207/20081); G06T (2207/30004); A61B (1/00009); A61B (2018/00601); A61B (2018/00708); A61B (2018/00982); A61B (2017/320093); A61B (17/320092); A61B (18/1445); A61B (2018/00678); A61B (2018/00988); A61B (2034/2065); A61B (2090/309); A61B (2090/3612)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2012/0157890	12/2011	Govari et al.	N/A	N/A
2014/0343416	12/2013	Panescu et al.	N/A	N/A
2017/0280983	12/2016	Kawano	N/A	A61B 1/00158
2019/0046262	12/2018	Hayashida et al.	N/A	N/A
2020/0275824	12/2019	Tata	N/A	A61B 1/0052

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
4112762	12/2007	JP	N/A
4960112	12/2011	JP	N/A
2012-125584	12/2011	JP	N/A
2015-000093	12/2014	JP	N/A
2016-523592	12/2015	JP	N/A
2017/187523	12/2016	WO	N/A
WO 2019/008629	12/2018	WO	N/A

OTHER PUBLICATIONS

Machine translation for JP JP 2015-000093 (Year: 2015). cited by examiner

Machine translation for JP 4112762 (Year: 2008). cited by examiner

Machine translation for WO 2019/008629 (Year: 2019). cited by examiner

Mar. 17, 2020 International Search Report issued in International Patent Application No. PCT/JP2020/000470. cited by applicant

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION (1) This application is a continuation of International Application No. PCT/JP2020/000470, filed on Jan. 9, 2020, the entire contents of which are incorporated herein by reference.

BACKGROUND

1. Technical Field

(1) The present disclosure relates to a treatment system, a control device, and a control method.

2. Related Art

(2) In the related art, a treatment instrument to incise a living tissue by applying a treatment energy to the living tissue from an end effector according to a supplied electric power has been known.

(3) To treat a living tissue by using the treatment instrument, an operator causes a control device to supply an electric power to a treatment instrument by operating a foot switch or the like, to apply a treatment energy to a living tissue from an end effector. Moreover, the operator sees a captured image that is captured by an endoscope and displayed on a display device, and thereby recognizes whether incision of the living tissue has been completed. The operator then stops the supply of the electric power to the treatment instrument from the control device by operating the footswitch or the like.

SUMMARY

(4) In some embodiments, a treatment system includes a treatment instrument configured to apply a treatment energy to a living tissue from an end effector according to a supplied electric power to incise the living tissue, an imaging device configured to generate a captured image capturing the living tissue during a state in which the treatment energy is applied from the end effector to the living tissue, and a control device including a processor configured to control operation of the imaging device, the processor being configured to: acquire the captured image from the imaging device, calculate a temporal change amount of the living tissue based on movement of the treatment instrument relative to any one of a predetermined point and a predetermined area in the captured image as a determination value, determine whether incision of the living tissue has been completed based on the determination value, and in response to determining that the incision of the living tissue has been completed, execute an instruction to stop supply of the electric power to the treatment instrument.

(5) In some embodiments, a control device includes a processor configured to control operation of an imaging device when applying treatment energy by a treatment instrument to a living tissue from an end effector according to a supplied electric power to incise the living tissue. The processor is configured to acquire a captured image capturing the living tissue during a state in which the treatment energy is applied from the end effector to the living tissue, determine whether incision of the living tissue has been completed based on the captured image by calculating a temporal change amount of the living tissue based on movement of the treatment instrument relative to any one of a predetermined point and a predetermined area in the captured image, and execute an instruction to stop supply of the electric power to the treatment instrument in response to determining that the incision of the living tissue has been completed.

(6) In some embodiments, provided is a control method that is performed by a processor of a control device. The method includes acquiring a captured image capturing a living tissue during a state in which a treatment energy is applied from an end effector to the living tissue, determining

whether incision of the living tissue has been completed based on the captured image by calculating a temporal change amount of the living tissue based on movement of a treatment instrument relative to any one of a predetermined point and a predetermined area in the captured image, and executing an instruction to stop supply of an electric power to the treatment instrument in response to determining that the incision of the living tissue has been completed.

(7) The above and other features, advantages and technical and industrial significance of this disclosure will be better understood by reading the following detailed description of presently preferred embodiments of the disclosure, when considered in connection with the accompanying drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a diagram illustrating a treatment system according to a first embodiment;
- (2) FIG. 2 is a flowchart illustrating a control method performed by a first processor;
- (3) FIG. 3 is a diagram explaining device recognition processing (step S2);
- (4) FIG. 4 is a diagram explaining first determination processing (step S4);
- (5) FIG. 5 is a diagram further explaining the first determination processing (step S4);
- (6) FIG. 6 is a diagram further explaining the first determination processing (step S4);
- (7) FIG. 7 is a flowchart illustrating a control method according to a second embodiment;
- (8) FIG. 8 is a diagram explaining second determination processing (step S4A);
- (9) FIG. 9 is a diagram further explaining the second determination processing (step S4A);
- (10) FIG. 10 is a flowchart illustrating a control method according to a third embodiment;
- (11) FIG. 11 is a diagram explaining third determination processing (step S4B);
- (12) FIG. 12 is a diagram further explaining the third determination processing (step S4B);
- (13) FIG. 13 is a diagram further explaining third determination processing (step S4B);
- (14) FIG. 14 is a flowchart illustrating a control method according to a fourth embodiment;
- (15) FIG. 15 is a diagram explaining fourth determination processing (step S4C);
- (16) FIG. 16 is a diagram further explaining the fourth determination processing (step S4C);
- (17) FIG. 17 is a flowchart illustrating a control method according to a fifth embodiment;
- (18) FIG. 18 is a flowchart illustrating a control method according to a sixth embodiment; and
- (19) FIG. 19 is a diagram illustrating a modification of the third embodiment.

DETAILED DESCRIPTION

(20) Hereinafter, modes to implement the disclosure (hereinafter, embodiments) will be explained with reference to the drawings. The embodiments explained below are not intended to limit the disclosure. Furthermore, like reference symbols are given to like parts throughout the description of the drawings.

First Embodiment

(21) Schematic Configuration of Treatment System

(22) FIG. 1 is a diagram illustrating a treatment system according to a first embodiment.

(23) A treatment system 1 is a system that treats a living tissue to be treated (hereinafter, described as target site) in a living body while observing the inside of the living body. This treatment system includes an endoscope device 2, a display device 3, and a treatment device 4 as illustrated in FIG. 1.

(24) Hereinafter, configurations of the endoscope device 2 and the treatment device 4 will be explained sequentially.

(25) Configuration of Endoscope Device

(26) The endoscope device 2 is a device to observe the inside of a living body. This endoscope device 2 includes a scope 21 and a control device 22 as illustrated in FIG. 1.

(27) The scope **21** corresponds to an imaging device. This scope **21** is inserted into the living body, and captures an image of the inside of the living body. In the first embodiment, the scope **21** is flexible, and has a long thin shape, and is constituted of so-called flexible endoscope inserted into a living body. The scope **21** is detachably connected to the control device **22** by a connector (not illustrated). The scope **21** includes an illumination lens **211**, an objective lens **212**, an imaging unit **213**, and an operating unit **214** as illustrated in FIG. 1.

(28) The illumination lens **211** is arranged at a distal end of the scope **21**, facing an emitting end of a light guide **23** (FIG. 1). Light emitted from the light guide **23** passes through the illumination lens **211**, and then irradiated to the inside of a living body.

(29) The objective lens **212** is arranged at a distal end of the scope **21**. The objective lens **212** takes in light that has been irradiated to the inside of the living body from the illumination lens **211** and then reflected from the inside of the living body (subject image), to form an image on an acceptance surface of the imaging unit **213**.

(30) The imaging unit **213** generates a captured image by capturing the subject image formed by the objective lens **212** under control of the control device **22**. The imaging unit **213** outputs the generated captured image to the control device **22**.

(31) The operating unit **214** has various kinds of switches (not illustrated) arranged therein to accept a user operation made by a user, such as a doctor. The operating unit **214** then outputs an operating signal according to the operation to the control device **22**.

(32) The control device **22** is constituted of a central processing unit (CPU), a field-programmable gate array (FPGA), and the like, and overall controls operation of the scope **21** and the display device **3**. This control device **22** includes an analog processing unit **221**, an A/D converter **222**, an image processing unit **223**, a video-output I/F unit **224**, a first processor **225**, a memory **226**, and a light source device **227** as illustrated in FIG. 1.

(33) The analog processing unit receives a captured image (analog signal) from the scope **21**, and performs analog processing, such as clamp processing and noise removal processing (correlated double sampling (CDS)) with respect to the captured image.

(34) The A/D converter **222** A/D converts the captured image (analog signal) subjected to the analog processing, and outputs the converted captured image (digital signal).

(35) The image processing unit **223** performs various kinds of image processing with respect to a captured image input thereto, using various kinds of parameters for image processing that are stored in the memory **226**, under control of the first processor **225**. Examples of the various kinds of image processing include optical black subtraction processing, white balance (WB) adjustment processing, demosaicing processing, color matrix arithmetic processing, gamma correction processing, color reproduction processing, edge enhancement processing, and the like.

(36) The video-output I/F unit **224** is constituted of a digital analog converter (DAC) encoder, or the like, and generates a video signal for display based on the captured image (digital signal) subjected to various kinds of image processing by the image processing unit **223**. The video-output I/F unit **224** outputs the video signal for display to the display device **3**.

(37) The display device **3** is constituted of a display using liquid crystal, organic electroluminescence (EL), or the like. The display device **3** receives a video signal for display input therein from the video-output I/F unit **224**, and displays a captured image based on the video signal for display.

(38) The light source device **227** includes a light source **228** and a light source driver **229** as illustrated in FIG. 1. In the first embodiment, the light source device **227** is configured to be integrated in the control device **22**, but not limited thereto, it may be configured to be independent from the control device **22**.

(39) The light source **228** is constituted of, for example, a white light emitting diode (LED) or the like, and emits light according to a supplied electric power. The light emitted from the light source **228** passes through the light guide **23** and the illumination lens **211**, and then irradiated to the

inside of a living body.

(40) The light source driver **229** supplies an electric power to the light source **228** under control of the first processor **225**.

(41) The first processor **225** corresponds to a processor. The first processor **225** is constituted of, for example, a CPU, an FPGA, or the like and controls operation of the scope **21**, operation of the display device **3**, and overall operation of the control device **22**. Moreover, the control device **22** and a generator **43** (FIG. **1**) that constitutes the treatment device **4** are detachably connected to each other by a third electric cable C3 (FIG. **1**). The first processor **225** controls operation of the generator **43** through the third electric cable C3. Detailed functions of the first processor **225** will be explained in “Control Method Performed by First Processor” described later.

(42) The memory **226** stores a program executed by the first processor **225**, information necessary for processing by the first processor **225**, various kinds of parameters for the image processing described above, and the like.

(43) [Configuration of Treatment Device]

(44) The treatment device **4** treats a target site by applying a treatment energy to the target site. A treatment that can be performed by the treatment device **4** according to the first embodiment is a treatment for performing coagulation and incision of a target site, or a treatment for performing only incision of a target site. Hereinafter, for convenience of explanation, the treatment will be described as incision. Moreover, at least any one of an ultrasonic energy, a high frequency energy, and a thermal energy can be an example of the treatment energy. Applying an ultrasonic energy to a target site means applying an ultrasonic vibration to the target site. Moreover, applying a high frequency energy to a target site means applying a high frequency electric current to the target site. Furthermore, to apply a thermal energy to a target site means propagating heat generated by a heater or the like to the target site. This treatment device **4** includes a first treatment device **41** and a second treatment device **42**, and the generator **43** as illustrated in FIG. **1**.

(45) The treatment device **4** is selectable to be used in a state in which the first treatment device **41** and the generator **43** are connected through the first electric cable C1 (FIG. **1**) or a state in which the second treatment device **42** and the generator **43** are connected through the second electric cable C2 (FIG. **1**) depending on a treatment method, a type of target site, and the like.

(46) The first treatment device **41** corresponds to the treatment instrument, and is a clamp type treatment device that incises a target site while gripping the target site. The first treatment device **41** includes, as illustrated in FIG. **1**, a first holding case **411**, an operating knob **412**, a first switch **413**, a shaft **414**, and a gripping portion **415**.

(47) The first holding case **411** supports the entire first treatment device **41**. This first holding case **411** includes, as illustrated in FIG. **1**, a holding-case main unit **416** that is positioned on a center axis Ax1 (FIG. **1**) of the shaft **414**, and a fixing handle **417** that extends downward from the holding-case main unit **416** in FIG. **1** and that is held by an operator.

(48) The operating knob **412** is pivotably supported about the first holding case **411**, and accepts an opening/closing operation by an operator.

(49) The first switch **413** is arranged, being exposed to the outside from the first holding case **411**, and accepts depression by the operator (hereinafter, described as first treatment-start operation). The first switch **413** outputs an operation signal according to the first treatment-start operation to the generator **43** through the first electric cable C1.

(50) The shaft **414** has a cylindrical shape, and its end portion on a proximal end side (right side in FIG. **1**) is connected to the holding case main unit **416**. Moreover, to an end portion on a distal end side (left side in FIG. **1**) of the shaft **414**, the gripping portion **415** is attached. Inside the shaft **414**, an opening closing mechanism (not illustrated) that causes a first and a second grippers **418**, **419** constituting the gripping portion **415** to open and close according to an opening/closing operation made by an operator with respect to the operating knob **412** is arranged.

(51) The gripping portion **415** corresponds to the end effector. This gripping portion **415** is a

portion that incise a target site while gripping the target site. This gripping portion **415** includes the first and the second grippers **418**, **419** as illustrated in FIG. 1.

(52) The first and the second grippers **418**, **419** correspond to a pair of grippers, and can grip a target site by opening and closing in a direction of an arrow R1 (FIG. 1) according to the opening closing operation by the operator made with respect to the operating knob **412**. At least one of the first and the second grippers **418**, **419** applies a treatment energy to a gripped target site under control of the generator **43**. Thus, the target site is incised.

(53) The second treatment device **42** corresponds to the treatment instrument, and is a non-clamp type device that incise a target site in a state in which it is in contact with the target site, being incapable of gripping a target site. This second treatment device **42** includes, as illustrated in FIG. 1, a second holding case **421**, a second switch **422**, and an end effector **423**.

(54) The second holding case **421** has a substantially cylindrical shape extending along a center axis Ax2, and supports the end effector **423**.

(55) The second switch **422** is arranged being exposed to the outside of the second holding case **421**, and accepts depression by an operator (hereinafter, described as second treatment-start operation). The second switch **422** outputs an operation signal according to the second treatment-start operation to the generator **43** through the second electric cable C2.

(56) The end effector **423** has a long shape extending along the center axis Ax2, and is attached inside the second holding case **421** in a state in which an end portion on a distal end side (left side in FIG. 1) is exposed to the outside. The end effector **423** applies a treatment energy to a target site from an end portion in a state in which the end portion on the distal end side is in contact with the target site under control of the generator **43**. Thus, the target site is incised.

(57) The generator **43** is constituted of a CPU, an FPGA, and the like, and overall controls operation of the first treatment device **41** connected through the first electric cable C1, or operation of the second treatment device **42** connected through the electric cable C2. This generator **43** includes a treatment-energy output unit **431** and a second processor **432** as illustrated in FIG. 1.

(58) The treatment-energy output unit **431** supplies an electric power necessary for applying a treatment energy to a target site to the first treatment device **41** that is connected through the first electric cable C1, or to the second treatment device **42** that is connected through the second electric cable C2 under control of the second processor **432**.

(59) For example, when the first treatment device **41** is configured to apply an ultrasonic energy to a target site, the first treatment device **41** has an ultrasound transducer that generates an ultrasonic vibration according to an electric power supplied from the treatment-energy output unit **431**. One of the first and the second grippers **418**, **419** is constituted of a vibration transmission member that transmits the ultrasonic vibration, and applies the transmitted ultrasonic vibration to a target site gripped between the first and the second grippers **418**, **419**.

(60) When the second treatment device **42** is configured to apply an ultrasonic energy to a target site, the second treatment device **42** has an ultrasound transducer that generates an ultrasonic vibration according to an electric power supplied from the treatment-energy output unit. The end effector **423** is constituted of a vibration transmission member that transmits the ultrasonic vibration, and applies the transmitted ultrasonic vibration to a target site.

(61) Moreover, for example, when the first treatment device **41** is configured to apply a high frequency energy to a target site, the first and the second grippers **418**, **419** respectively include an electrode to which an electric power is supplied from the treatment-energy output unit **431**. As the electric power is supplied to the pair of electrodes, a high frequency current flows through a target site gripped between the pair of electrodes.

(62) When the second treatment device **42** is configured to apply a high frequency energy to a target site, the end effector **423** includes an electrode that is supplied with an electric power from the treatment-energy output unit **431** to a portion between itself and a return electrode attached on a surface of a subject. As the electric power is supplied to the portion between the electrode and the

return electrode, a high frequency current flows through a target site positioned between the end effector **423** and the return electrode.

(63) Furthermore, for example, when the first treatment device **41** is configured to apply a thermal energy to a target site, at least one of the first and the second grippers **418**, **419** has a heater that generates heat according to an electric power supplied from the treatment-energy output unit **431**. At least one of the first and the second grippers **418**, **419** transmits heat of the heater to a target site gripped between the first and the second grippers **418** and **419** according to the supply of the electric power.

(64) When the second treatment device **42** is configured to apply a thermal energy to a target site, the end effector **423** has a heater that generates heat according to an electric power supplied from the treatment-energy output unit **431**. The end effector **423** transmits heat of the heater to the target site according to the supply of the electric power.

(65) The second processor **432** is constituted of, for example, a CPU, an FPGA, or the like. The second processor **432** performs incision control according to the first treatment-start operation by an operator with respect to the first switch **413**, or the second treatment-start operation with respect to the second switch **422**. The incision control is a control to incise a target site by causing the treatment-energy output unit **431** to supply an electric power to the first treatment device **41** or the second treatment device **42**, and by applying a treatment energy to the target site.

(66) [Control Method Performed by First Processor]

(67) Next, a control method performed by the first processor **225** will be explained.

(68) FIG. **2** is a flowchart illustrating the control method performed by the first processor **225**.

(69) In the following, the first and the second treatment devices **41**, **42** are collectively described as treatment device **40** for convenience of explanation.

(70) First, the first processor **225** sequentially acquires captured images (digital signals) that capture the inside of a living body taken by the imaging unit **213**, and that have passed through the analog processing unit **221**, the A/D converter **222**, and the image processing unit **223** in a frame unit (step **S1**).

(71) In the first embodiment, at step **S1**, the first processor **225** acquires a captured image that captures the inside of a living body taken by the imaging unit **213**, and that has passed through the analog processing unit **221**, the A/D converter **222**, and the image processing unit **223**, but it is not limited thereto. For example, at step **S1**, the first processor **225** may acquire a captured image that captures the inside of a living body taken by the imaging unit **213**, and that has passed through the analog processing unit **221** and the A/D converter **222** (captured image before subjected to various kinds of image processing by the image processing unit **223**).

(72) After step **S1**, the first processor **225** performs device recognition processing described below (step **S2**).

(73) FIG. **3** is a diagram explaining the device recognition processing (step **S2**). Specifically, FIG. **3** illustrates a captured image **F1** acquired at step **S1**. In FIG. **3**, a case in which the first treatment device **41** out of the first and the second treatment devices **41**, **42** is used is illustrated.

(74) First, the first processor **225** extracts, as illustrated in FIG. **3**, an area **Ar1** constituted of pixels having a pixel value of a specific color (for example, silver) unique to the treatment device **40** in the captured image **F1**.

(75) Next, the first processor **225** determines whether the extracted area **Ar1** extends linearly from an edge of the captured image **F1**.

(76) When it is determined that it extends linearly from the edge of the captured image **F1**, the first processor **225** recognizes that the area **Ar1** is the treatment device **40** (the first treatment device **41** in the case of FIG. **3**) shown in the captured image **F1**.

(77) The first processor **225** performs the device recognition processing (step **S2**) described above sequentially in a frame unit with respect to the captured image acquired sequentially at step **S1**.

(78) After step **S2**, the first processor **225** monitors all the time whether the processing start

operation (in the first embodiment, the first processing-start operation or the second processing-start operation) has been performed (step S3). When the first processing-start operation or the second processing-start operation has been performed, the second processor 432 starts incision control. That is, application of a treatment energy with respect to a target site LT (FIG. 3) from the gripping portion 415 or the end effector 423 is started. Moreover, the second processor 432 outputs a signal indicating that the treatment start operation has been performed to the first processor 225 through the third electric cable C3. The first processor 225 determines that the processing start operation has been performed based on the signal.

(79) When it is determined that the treatment start operation has been performed (step S3: YES), the first processor 225 performs first determination processing described below (step S4).

(80) FIG. 4 to FIG. 6 are diagrams explaining the first determination processing (step S4).

Specifically, FIG. 4 and FIG. 5 illustrate captured images F2, F3 that are acquired at step S1.

Moreover, the captured image F2 illustrated in FIG. 4 is an image capturing a state before the target site LT is incised. The captured image F3 is an image capturing a state soon after the target site LT is incised. In FIG. 4 and FIG. 5, similarly to FIG. 3, a case in which the first treatment device 41 is used out of the first and the second treatment devices 41, 42 is illustrated. Furthermore, in FIG. 5, a position of the first treatment device 41 in the state illustrated in FIG. 4 is indicated by a broken line. FIG. 6 is a diagram illustrating a behavior of a moving speed of the treatment device 40 (the first treatment device 41 in the case of FIG. 4 and FIG. 5) after the treatment energy is started to be applied to the target site LT.

(81) First, the first processor 225 identifies a feature point P1 (FIG. 4, FIG. 5) having a feature in pixel value or shape in the area Ar1 (the treatment device 40) extracted at step S2. The first processor 225 sequentially identifies the feature point P1 in a frame unit from the captured images acquired sequentially at step S1. The respective feature points P1 in the respective captured images (for example, the captured images F2, F3) are an identical portion on a subject (the treatment device 40).

(82) Next, the first processor 225 calculates a moving speed of the treatment device 40 by dividing a difference (the number of pixels) D1 (FIG. 5) in coordinate value between the feature point P1 of a captured image (for example, the captured image F3) of the present frame (hereinafter, described as current frame) and the feature point P1 of a captured image next previous to the current frame (for example, the captured image F2) by time between the frames. The first processor 225 sequentially calculates the moving speed of the treatment device 40 for the captured images acquired sequentially at step S1 in a frame unit. The moving speed of the treatment device 40 corresponds to a determination value.

(83) The moving speed of the treatment device described above is calculated based on the captured image of the current frame and the captured image of the next previous frame, but it is not limited thereto, and it may be calculated based on a captured image of the current frame and a captured image several frames before the current frame.

(84) Next, the first processor 225 compares the calculated moving speed of the treatment device 40 with a first threshold Th (FIG. 6) sequentially. When the moving speed of the treatment device 40 becomes equal to or higher than the threshold Th1, the first processor 225 determines that incision of the target site LT has been completed (detects completion of incision of the target site LT). The first threshold Th1 is stored in the memory 226 as information necessary for processing of the first processor 225.

(85) When the target site LT is to be incised by using the clamp type first treatment device 41, an operator first makes the target site LT be under tension, while gripping the target site LT with the first and the second grippers 418, 419 (state illustrated in FIG. 4). After setting this condition, the operator performs the first processing-start operation with respect to the first switch 413. Therefore, as it is found when FIG. 4 and FIG. 5 are compared, the first and the second grippers 418, 419 move at a high speed by reaction when the target site LT is incised as they have been pulling the

target site LT. In other words, when the target site LT is incised, the moving speed of the treatment device **40** described above momentarily becomes equal to or higher than the first threshold Th1 as illustrated in FIG. 6.

(86) When completion of incision of the target site LT is detected (step S5: YES), the first processor **225** instructs the generator **43** (the second processor **432**) to stop the output to through the third electric cable C3 (step S6). Thus, the second processor **432** stops supply of an electric power to the treatment device **40** (stops the operation of the treatment-energy output unit **431**).

(87) According to the first embodiment explained above, following effects are obtained.

(88) The control device **22** according to the first embodiment determines whether incision of the target site LT has been completed based on a captured image (for example, the captured images F1 to F3) capturing a state in which the treatment energy is applied to the target site LT by the gripping portion **415** or the end effector **423**, and stops the supply of the electric power to the treatment device **40** when it is determined that incision of the target site LT has been completed. That is, determination whether incision of the target site LT has been completed is not performed by visual confirmation by an operator, but is performed by the control device **22** and, furthermore, stop of supply of an electric power to the treatment device **40** is not performed by an operation by the operator, but is performed by the control device **22**.

(89) Therefore, a time lag from completion of incision of the target site LT to stop of supply of an electric power to the treatment device **40** can be resolved. Accordingly, it is possible to avoid supply of unnecessary power to the treatment device **40**, and to reduce a load on the treatment device **40**.

(90) Moreover, in the control device **22** according to the first embodiment, the moving speed of the treatment device **40** described above is adopted as a determination value.

(91) Therefore, by using a typical phenomenon that occurs at the time of incision of the target site LT in the treatment device **40**, completion of incision of the target site LT can be favorably determined. The typical phenomenon is, as described above, a phenomenon that “the first and the second grippers **418**, **419** move at a high speed by reaction when the target site LT is incised as they have been pulling the target site LT”.

(92) Moreover, in the control device **22** according to the first embodiment, out of subjects taken in the captured images (for example, the captured images F1 to F3), an object extending linearly from an edge of the captured image is detected as the first and the second grippers **418**, **419** (the device recognition processing (step S2)).

(93) Therefore, by using a typical way of appearance of the treatment device **40** shown in the captured image, the treatment device **40** can be favorably recognized.

Second Embodiment

(94) Next, a second embodiment will be explained.

(95) In the following explanation, identical reference symbols are given to components similar to those of the first embodiment described above, and their detailed explanation will be omitted or simplified.

(96) FIG. 7 is a flowchart illustrating a control method according to the second embodiment.

(97) In the second embodiment, as illustrated in FIG. 7, a control method performed by the first processor **225** is different from the first embodiment described above.

(98) In the control method according to the second embodiment, as illustrated in FIG. 7, steps S4A, S5A are adopted instead of steps S4, S5 in the control method (FIG. 2) explained in the first embodiment described above. In the following, steps S4A, S5A will be explained mainly.

(99) Step S4A is performed when it is determined that the processing start operation has been performed (step S3: YES).

(100) Specifically, the first processor **225** performs second determination processing described below at step S4A.

(101) FIG. 8 and FIG. 9 are diagrams explaining the second determination processing (step S4A).

Specifically, FIG. 8 and FIG. 9 illustrate captured images F4, F5 acquired at step S1. Moreover, the captured image F4 illustrated in FIG. 8 is an image capturing a state similar to that of the captured image F2 illustrated in FIG. 4. The captured image F5 illustrated in FIG. 9 is an image capturing a state similar to that of the captured image F3 illustrated in FIG. 5.

(102) First, the first processor 225 identifies a feature point P2 (FIG. 8, FIG. 9) having a feature in pixel value and shape in the area Ar1 (the treatment device 40) extracted at step S2. The first processor 225 sequentially identifies the feature point P2 in a frame unit from the captured images sequentially acquired at step S1. The respective feature points P2 in the respective captured images (for example, the captured images F4, F5) are an identical portion on a subject (the treatment device 40).

(103) Next, the first processor 225 identifies feature points P3, P4 (FIG. 8, FIG. 9) having a feature in pixel value and shape in the target site LT adjacent to the area Ar1 (the treatment device 40) extracted at step S2. The first processor 225 sequentially identifies the feature points P3, P4 (FIG. 8, FIG. 9) in a frame unit from the captured images sequentially acquired at step S2. The first processor 225 sequentially identifies the feature points P3, P4 in a frame unit from the captured images sequentially acquired at step S1. The respective feature points P3 identified in the respective captured images (for example, the captured images F4, F5) are an identical portion on a subject (the target site LT). Similarly, the respective feature points P4 identified in the respective captured images (for example, the captured images F4, F5) are an identical portion on the subject (the target site LT).

(104) Next, the first processor 225 calculates a distance (the number of pixels) D2 between the feature points P2 and P3, and a distance (the number of pixels) D3 between the feature points P2 and P4, respectively in the captured images of the same frame (for example, the captured image F4 or the captured image F5). The first processor 225 sequentially performs calculation of the distances D2, D3 in a frame unit in the captured images sequentially acquired at step S1.

(105) Next, the first processor 225 calculates a first moving speed of the treatment device 40 by dividing a difference (the number of pixels) between the difference D2 in the captured image of the current frame (for example, the captured image F5) and the distance D2 in the captured image of the next previous frame (for example, the captured image F4) by time between the frames. The first moving speed of the treatment device 40 means a moving speed of the treatment device 40 (the feature point P2) relative to the feature point P3 as a reference point. The first processor 225 sequentially performs calculation of the first moving speed of the treatment device 40 in a frame unit for the captured images sequentially acquired at step S1.

(106) The treatment device 40 explained above corresponds to a determination value.

(107) The first and the second moving speeds of the treatment device 40 described above are respectively calculated based on the captured image of the current frame and the captured image of the next previous frame, but not limited thereto, they may respectively be calculated based on the captured image of the current frame and a captured image several frames before the current frame.

(108) Next, the first processor 225 sequentially compares the calculated first and second moving speeds of the treatment device 40 with the first threshold Th1. The first processor 225 detects completion of incision of the target site LT when both the first and the second moving speeds of the treatment device 40 become equal to or higher than the first threshold Th1.

(109) When completion of incision of the target site LT is detected (step S5A: YES), the first processor 225 shifts to step S6.

(110) According to the second embodiment explained above, besides effects similar to those of the first embodiment described above, following effects are obtained.

(111) In the control device 22 according to the second embodiment, the first and the second moving speeds of the treatment device 40 relative to the feature points P3, P4 in the target site LT are adopted as the determination value.

(112) Therefore, an influence of hand shake of a scopist holding the scope 21 with hands can be

cancelled, and completion of incision of the target site LT can be accurately determined.

(113) Particularly, the first and the second moving speeds of the treatment device **40** are adopted as the determination value. Therefore, for example, compared to when only one of the first and the second moving speeds is adopted as the determination value, as more than one value is used as the determination value, erroneous determination is suppressed, and completion of incision of the target site LT can be more accurately determined.

Third Embodiment

(114) Next, a third embodiment will be explained.

(115) In the following explanation, identical reference symbols are given to components similar to those of the first embodiment described above, and their detailed explanation will be omitted or simplified.

(116) FIG. **10** is a flowchart illustrating a control method according to a third embodiment.

(117) In the third embodiment, as illustrated in FIG. **10**, the control method performed by the first processor **225** is different from that of the first embodiment described above.

(118) In the control method according to the third embodiment, as illustrated in FIG. **10**, steps **S4B**, **S5B** are adopted instead of steps **S4**, **S5** in the control method (FIG. **2**) explained in the first embodiment described above. In the following, steps **S4B**, **S5B** will be explained mainly.

(119) Step **S4B** is performed when it is determined that the processing start operation has been performed (step **S3**: YES).

(120) Specifically, the first processor **225** performs third determination processing described below at step **S4B**.

(121) FIG. **11** to FIG. **13** are diagrams explaining the third determination processing (step **S4B**). Specifically, FIG. **11** and FIG. **12** illustrate captured images **F6**, **F7** acquired at step **S1**. Moreover, the captured image **F6** illustrated in FIG. **11** is an image capturing a state similar to that of the captured image **F2** illustrated in FIG. **4**. The captured image **F7** illustrated in FIG. **12** is an image capturing a state similar to that of the captured image **F3** illustrated in FIG. **5**. FIG. **13** is a diagram illustrating a behavior of fluctuation speed of pixel level in an area **Ar2** (FIG. **11**, FIG. **12**) after application of a treatment energy to the target site LT.

(122) First, the first processor **225** identifies the area **Ar2** (FIG. **11**, FIG. **12**) adjacent to the area **Ar1** (the treatment device **40**) extracted at step **S2**. The first processor **225** sequentially identifies the area **Ar2** in a frame unit from the captured images sequentially acquired at step **S1**. The respective areas **Ar2** identified in the respective captured images (for example, the captured images **F6**, **F7**) are areas having an identical positional relationship with respect to the respective areas **Ar1** (the treatment device **40**) extracted in the respective captured images.

(123) Next, the first processor **225** calculates a mean value of pixel level of respective pixels in the area **Ar2** in the captured image (for example, the captured image **F6** or the captured image **F7**) of the same frame. Examples of the pixel level include a pixel value (RGB value) of a pixel, a brightness value according to a Y signal (brightness signal). The first processor **225** sequentially performs calculation of a mean value of the pixel level of the respective pixels in the area **Ar2** in a frame unit for the captured images sequentially acquired at step **S1**.

(124) Next, the first processor **225** calculates a fluctuation speed of pixel level by dividing a difference between the mean value of pixel level of the respective pixels in the area **Ar2** in the captured image of the current frame (for example, the captured image **F7**) and the mean value of pixel level of the respective pixels in the area **Ar2** in the captured image of the next previous frame (for example, the captured image **F6**) by time between the frames. The fluctuation speed of pixel value corresponds to the determination value.

(125) The fluctuation speeds of pixel level described above is calculated based on a captured image of the current frame and a captured image of the next previous frame, but not limited thereto, they may respectively be calculated based on a captured image of the current frame and a captured image several frames before the current frame.

(126) Next, the first processor **225** sequentially compares the calculated fluctuation speeds of pixel level with a second threshold Th2 (FIG. **13**). The first processor **225** detects completion of incision of the target site LT when the fluctuation speed of pixel level becomes equal to or higher than the second threshold Th2. The second threshold Th2 is stored in the memory **226** as information necessary for the processing of the first processor **225**.

(127) When the target site LT is incised, as it is found when FIG. **11** and FIG. **12** are compared, the target site LT adjacent to the gripping portion **415** is incised to be separated, and respectively moves apart from the gripping portion **415** quickly. In other words, because the target site LT that has been present in the area Ar2 rapidly moves away and disappears therefrom when the target site LT is incised, the fluctuation speed of pixel level described above momentarily becomes equal to or higher than the second threshold Th2 as illustrated in FIG. **13**.

(128) When completion of incision of the target site LT is detected (step S5B: YES), the first processor **225** shifts to step S6.

(129) According to the third embodiment explained above, besides effects similar to those of the first embodiment described above, following effects are obtained.

(130) In the control device **22** according to the third embodiment, the fluctuation speed of pixel level is adopted as the determination value.

(131) Therefore, also when the non-clamp type second treatment device **42** other than the clamp type first treatment device **41** that incise the target site LT in a state in which the target site LT is pulled while gripping the target site LT is used, completion of incision of the target site LT can be favorably detected.

Fourth Embodiment

(132) Next, a fourth embodiment will be explained.

(133) In the following explanation, identical reference symbols are given to components similar to those of the first embodiment described above, and their detailed explanation will be omitted or simplified.

(134) FIG. **14** is a flowchart illustrating a control method according to the fourth embodiment.

(135) In the fourth embodiment, as illustrated in FIG. **14**, the control method performed by the first processor **225** is different from the first embodiment described above.

(136) In the control method according to the fourth embodiment, as illustrated in FIG. **14**, steps S4C, S5C are adopted instead of steps S4, S5 in the control method (FIG. **2**) explained in the first embodiment described above. In the following, steps S4C, S5C will be explained mainly.

(137) Step S4C is performed when it is determined that the processing start operation has been performed (step S3: YES).

(138) Specifically, the first processor **225** performs fourth determination processing described below at step S4C.

(139) FIG. **15** and FIG. **16** are diagrams explaining the fourth determination processing (step S4C). Specifically, FIG. **15** and FIG. **16** illustrate captured images F8, F9 acquired at step S1. Moreover, the captured image F8 illustrated in FIG. **15** is an image capturing a state similar to that of the captured image F2 illustrated in FIG. **4**. The captured image F9 illustrated in FIG. **16** is an image capturing a state similar to that of the captured image F3 illustrated in FIG. **5**.

(140) First, the first processor **225** identifies a feature points P5, P6 (FIG. **15**, FIG. **16**) having a feature in pixel value and shape in the target site LT adjacent to the area Ar1 (the treatment device **40**) extracted at step S2. The first processor **225** sequentially identifies the feature points P5, P6 in a frame unit from the captured images sequentially acquired at step S1. The respective feature points P5 identified in the respective captured images (for example, the captured images F8, F9) are an identical portion on a subject (the target site LT). Similarly, the respective feature points P6 identified in the respective captured images (for example, the captured images F8, F9) are an identical portion on a subject (the target site LT).

(141) Next, the first processor **225** calculates a distance (the number of pixels) D4 between the

feature points P5 and P6 in the captured image of the same frame (for example, the captured image F8 or the captured image F9). The first processor 225 sequentially performs calculation of the distance D4 in a frame unit in the captured images sequentially acquired at step S1.

(142) Next, the first processor 225 calculates a moving speed of the target site LT by dividing a difference (the number of pixels) between the distance D4 in the captured image of the current frame (for example, the captured image F9) and the distance D4 in the captured image of the next previous frame (for example, the captured image F8) by time between the frames. The first processor 225 sequentially calculates the moving speed of the target site LT for the captured images acquired sequentially at step S1 in a frame unit. The moving speed of the target site LT corresponds to the determination value.

(143) The moving speed of the target site LT described above is calculated based on the captured image of the current frame and the captured image of the next previous frame, but not limited thereto, it may be calculated based on the captured image of the current frame and a captured image several frames before the current frame.

(144) Next, the first processor 225 sequentially compares the calculated moving speed of the target site LT with a third threshold Th3. The first processor 225 detects completion of incision of the target site LT when the moving speed of the target site LT becomes equal to or higher than the third threshold Th3. The third threshold is stored in the memory 226 as information necessary for the processing of the first processor 225.

(145) When the target site LT is incised, as it is found when FIG. 15 and FIG. 16 are compared, the target site LT adjacent to the gripping portion 415 is incised to be separated, and respectively moves apart from the gripping portion 415 at a high speed. In other words, when the target site LT is incised, the moving speed of the target site LT described above momentarily becomes equal to or higher than the third threshold Th3.

(146) When completion of incision of the target site LT is detected (step S5C: YES), the first processor 225 shifts to step S6.

(147) Also when the moving speed of the target site LT described above is adopted as the determination value as in the fourth embodiment explained above, effects similar to those of the first and the third embodiments can be obtained.

Fifth Embodiment

(148) Next, a fifth embodiment will be explained.

(149) In the following explanation, identical reference symbols are given to components similar to those of the first embodiment described above, and their detailed explanation will be omitted or simplified.

(150) FIG. 17 is a flowchart illustrating a control method according to the fifth embodiment.

(151) In the fifth embodiment, as illustrated in FIG. 17, the control method performed by the first processor 225 is different from the first embodiment described above.

(152) In the control method according to the fifth embodiment, as illustrated in FIG. 17, steps S7D, S8D and steps S4B, S5B explained in the third embodiment described above are added to the control method (FIG. 2) explained in the first embodiment described above. In the following, steps S7D, S8D will be explained mainly.

(153) In the fifth embodiment, a training model described below is stored in the memory 226 as information necessary for processing of the first processor 225.

(154) The training model is provided for each type of the treatment device 40 (type of the first treatment device 41: clamp type, type of the second treatment device 42: non-clamp type), and is a model that is trained by machine learning (for example, deep learning, or the like) to learn a feature of the treatment device 40 based on captured image (training image) capturing the treatment device 40. The first processor 225 is enabled to determine the type of the treatment device 40 (type of the first treatment device 41: clamp type, type of the second treatment device 42: non-clamp type) shown in a captured image by image recognition n (artificial intelligence (AI)) using the training

model.

(155) Step S7D is performed after the device recognition processing (step S2).

(156) Specifically, the first processor **225** performs type determination processing to determine the type of the treatment device **40** (type of the first treatment device **41**: clamp type, type of the second treatment device **42**: non-clamp type) shown in a captured image acquired at step S1, by the image recognition using the training model stored in the memory **226** (step S7D).

(157) Thereafter, the first processor **225** shifts to step S3.

(158) Step S8D is performed when the processing start operation has been performed (step S3: YES).

(159) Specifically, the first processor **225** determines whether the type of the treatment device **40** shown in the captured image is determined by the type determination processing (step S7D) as the clamp type (step S8D).

(160) When the type of the treatment device **40** is determined as the clamp type (step S8D: YES), the first processor **225** shifts to step S4.

(161) On the other hand, when the treatment device **40** is determined as the non-clamp type (step S8D: NO), the first processor **225** shifts to step S4B. When completion of incision of the target site LT is detected at step S4B (step S5B: YES), the first processor **225** shifts to step S6.

(162) According to the fifth embodiment explained above, besides effects similar to those of the first embodiment described above, following effects are obtained.

(163) According to the control device **22** according to the fifth embodiment, because the type determination processing (step S7D) described above is performed, appropriate determination processing (processing of determining whether incision of the target site LT has been completed) according to the type of the treatment device **40** can be performed.

Sixth Embodiment

(164) Next, a sixth embodiment will be explained.

(165) In the following explanation, identical reference symbols are given to components similar to those of the first embodiment described above, and their detailed explanation will be omitted or simplified.

(166) FIG. **18** is a flowchart illustrating a control method according to the sixth embodiment. In the sixth embodiment, as illustrated in FIG. **18**, the control method performed by the first processor **225** is different from that of the first embodiment described above.

(167) In the control method according to the sixth embodiment, as illustrated in FIG. **18**, steps S4E, S5E1, and S5E2 are adopted instead of steps S4, S5 in the control method (FIG. **2**) explained in the first embodiment described above, and step S9E is added. In the following, steps S4E, S5E1, S5E2, S9E will be explained mainly.

(168) Step S4E is performed when it is determined that the processing start operation has been performed (step S3: YES).

(169) Specifically, the first processor **225** performs the first determination processing (step S4) explained in the first embodiment described above, and the third determination processing (step S4B) explained in the third embodiment described above in parallel (step S4E).

(170) When completion of incision of the target site LT is detected as a result of the first determination processing (step S5E1: YES), the first processor **225** shifts to step S6.

(171) On the other hand, even when completion of incision of the target site LT cannot be detected as a result of the first determination processing (step S5E1: NO), if completion of incision of the target site LT is detected as a result of the third determination processing (step S5E2: YES), the first processor **225** shifts to step S6.

(172) When completion of incision of the target site LT cannot be detected as a result of the first and the third determination processing (steps S5E1, S5E2: NO), the first processor **225** controls operation of the display device **3**, and causes the display device **3** to display an alert (image) indicating that completion of incision of the target site LT cannot be detected (step S9E).

(173) As for the alert, in addition to displaying on the display device **3**, it may be configured to output the alert from a speaker, or to output the alert by lighting or flashing an LED or the like arranged on the control device **22**.

(174) According to the sixth embodiment explained above, besides effects similar to those of the first and the third embodiments described above, following effects are obtained.

(175) When the typical phenomenon that occurs at the time of incision of the target site LT is a phenomenon that the scope **21** moves in a direction of the optical axis, completion of incision of the target site LT cannot be detected by the first determination processing even though the target site has been incised.

(176) In the control device **22** according to the sixth embodiment, the first and the third determination processing is performed in parallel (step **S4E**), and even when completion of incision of the target site LT cannot be detected as a result of the first determination processing (step **S5E1**: NO), if completion of incision of the target site LT is detected as a result of the third determination processing (step **S5E2**: YES), supply of an electric power to the treatment device **40** is stopped (step **S6**). Therefore, even when the typical phenomenon that occurs at the time of incision of the target site LT in the treatment device **40** is a phenomenon that the scope **21** moves in the direction of optical axis, completion of incision of the target site LT can be detected, and the supply of an electric power to the treatment device **40** can be stopped.

Other Embodiments

(177) The embodiments to implement the disclosure have so far been explained, but the disclosure is not to be limited to the first to the sixth embodiments.

(178) In the first to the sixth embodiments, as the determination value, the moving speed of the treatment device **40**, the first and the second moving speed of the treatment device **40**, the fluctuation speed of pixel level, and the moving speed of the target site LT have been adopted, but it is not limited thereto. For example, a moving amount of the feature point **P1** (corresponding to a moving amount of the treatment device **40**), the distance **D2** between the feature points **P2** and **P3** (corresponding to a moving amount of the treatment device **40**), the distance **D3** between the feature points **P2** and **P4** (corresponding to a moving amount of the treatment device **40**), a mean value of pixel level of respective pixels in the area **Ar2**, and the distance **D4** between the feature points **P5** and **P6** (corresponding to a moving amount of the target site LT) after the treatment energy is started to be applied to the target site LT may be adopted as the determination value. Moreover, as the determination value, the moving speed of the treatment device **40**, the first and the second moving speeds of the treatment device **40**, the fluctuation speed of pixel level, and the moving speed of the target site LT, and the moving amount of the feature point **P1**, the distance **D** between the feature points **P2** and **P3**, the distance **D3** between the feature points **P2**, and **P4**, the mean value of pixel level of the respective pixels in the area **Ar2**, and the distance **D4** between the feature points **P5** and **P6** after the start of application of a treatment energy to the target site LT may be combined.

(179) FIG. **19** is a diagram illustrating a modification of the third embodiment. Specifically, FIG. **19** is a diagram illustrating a behavior of the mean value of pixel level (brightness value) of respective pixels in the area **Ar2** after the start of application of the treatment energy to the target site LT.

(180) For example, if the mean value of pixel level (brightness value) of the respective pixels in the area **Ar2** is adopted as the determination value, when the target site LT is incised, the target site LT moves from the area **Ar2** and disappears therefrom, and a portion less likely to be illuminated by the illumination light then enters the area **Ar2**. Therefore, when the target site LT is incised, the mean value decreases to be equal to or lower than the second threshold **Th2** as illustrated in FIG. **19**. That is, the first processor **225** detects completion of incision of the target site LT when the mean value becomes equal to or lower than the second threshold **Th2**.

(181) In the second embodiment described above, as the determination value, the first and the

second moving speeds based on the distances D2, D3 from the feature points P3, P4 in the target site LT to the feature point P2 in the treatment device **40** are adopted, but it is not limited thereto. Three or more moving speeds based on three or more distances from three or more feature points in the target site LT to one feature point in the treatment device **40** may be adopted as the determination value. Moreover, conversely, plural moving speeds based on plural distances from one feature point in the target site LT to plural feature points in the treatment device **40** may be adopted as the determination value. Furthermore, plural moving speeds based on plural distances from plural feature points in the target site LT to plural feature points in the treatment device **40** may be adopted as the determination value.

(182) In the fifth embodiment described above, a configuration in which instead of the first determination processing (steps S4, S5), the second determination processing (steps S4A, S5A) is performed may be adopted. Moreover, in the fifth embodiment described above, a configuration in which instead of the third determination processing (steps S4B, S5B), the fourth determination processing (steps S4C, S5C) is performed may be adopted.

(183) Similarly, in the sixth embodiment, a configuration in which the second determination processing is performed instead of the first determination processing may be adopted. Furthermore, in the sixth embodiment, a configuration in which the fourth determination processing is performed instead of the third determination processing may be adopted.

(184) In the first to the sixth embodiments, the common generator **43** is used for the first and the second treatment devices **41**, **42**, but it is not limited thereto, and generators may be provided respectively to the first treatment device **41** and the second treatment device **42**.

(185) In the first to the sixth embodiments described above, the scope **21** is constituted of a flexible endoscope, but it is not limited thereto. Instead of the scope **21**, a component combining a rigid endoscope and a camera head may be adopted.

(186) In the first to the sixth embodiments described above, as the treatment instrument, a robotics treatment instrument (for example, refer to Japanese Patent No. 4960112) that includes plural arms, a joint portion that connects the arms in a relatively movable manner, and a driving mechanism that drives the arms by actuating the joint portion may be adopted.

(187) In the first to the sixth embodiments described above, the device recognition processing (step S2) may be performed, similarly to the type determination processing (step S7D), by image recognition using a training model (image recognition using AI).

(188) In the first to the sixth embodiments described above, the control method illustrated in FIG. 2, FIG. 7, FIG. 10, FIG. 14, FIG. 17, and FIG. 18 may be performed by the second processor **432**. That is, it may be configured to make the second processor **432**, not the first processor **225**, function as the processor.

(189) In the first to the sixth embodiments described above, the control method illustrated in FIG. 2, FIG. 7, FIG. 10, FIG. 14, FIG. 17, and FIG. 18 may be performed by plural processors. That is, the processor according to the disclosure may be constituted of plural processors, not limited to one.

(190) According to the treatment system, the control device, and the control method according to the disclosure, it is possible to avoid supply of unnecessary power to a treatment instrument, and to reduce a load on the treatment instrument.

(191) Additional advantages and modifications will readily occur to those skilled in the art. Therefore, the disclosure in its broader aspects is not limited to the specific details and representative embodiments shown and described herein. Accordingly, various modifications may be made without departing from the spirit or scope of the general inventive concept as defined by the appended claims and their equivalents.

Claims

1. A treatment system comprising: a treatment instrument having an end effector configured to apply a treatment energy to a living tissue; an imaging device configured to generate an image of the living tissue; and a processor configured to control the imaging device that is also configured to: acquire the image, set, based on the image, a reference point on the living tissue adjacent to the end effector, calculate, based on the image, at least one of a moving amount or a moving speed of a specific point on the end effector after the treatment energy is started to be applied to the living tissue, relative to the reference point, determine that incision of the living tissue has been completed based on the at least one of the moving amount or the moving speed, the moving amount or the moving speed indicating that the end effector moved away from the reference point, and in response to determining that the incision of the living tissue has been completed, execute an instruction to stop supply of an electric power to the treatment instrument.
2. The treatment system according to claim 1, further comprising a memory configured to store a first threshold, wherein: the end effector includes a gripper configured to grip the living tissue, the end effector configured to apply the treatment energy to the living tissue through the gripper, the specific point comprises the gripper, and the processor is configured to: determine that the incision of the living tissue has been completed when the at least one of the moving amount or the moving speed becomes equal to or higher than the first threshold.
3. The treatment system according to claim 2, wherein the processor is configured to detect an object that extends linearly from an edge of the image out of a plurality of objects shown in the image.
4. The treatment system according to claim 2, wherein the processor is configured to detect the gripper from a plurality of objects shown in the image, based on a color in the image.
5. The treatment system according to claim 1, further comprising a memory configured to store a second threshold, wherein: the processor is configured to: calculate, based on the image, at least one of a pixel level of an area adjacent to the end effector or a fluctuation speed of the pixel level, and determine whether the incision of the living tissue has been completed by comparing the at least one of the pixel level or the fluctuation speed to the second threshold.
6. The treatment system according to claim 1, further comprising a memory configured to store a third threshold, wherein: the processor is configured to: calculate, based on the image, at least one of a moving amount or a moving speed of the living tissue adjacent to the end effector after the treatment energy is started to be applied to the living tissue, and determine that the incision of the living tissue has been completed when the at least one of the moving amount or the moving speed of the living tissue adjacent to the end effector becomes equal to or larger than the third threshold value.
7. The treatment system according to claim 6, wherein the processor is configured to calculate at least one of a moving amount or a moving speed among a plurality of feature points of the living tissue adjacent to the end effector to determine whether the incision of the living tissue has been completed.
8. The treatment system according to claim 1, wherein the processor is configured to: determine a type of the treatment instrument based on the image, and perform determination processing according to the determined type of the treatment instrument from a plurality of kinds of determination processing to determine whether the incision of the living tissue has been completed.
9. The treatment system according to claim 1, wherein the treatment energy is at least one of an ultrasonic vibration, a high-frequency electric current, or heat.
10. The treatment system according to claim 1, wherein the end effector is configured to apply the treatment energy to the living tissue while gripping the living tissue to be under tension such that a moving amount of the living tissue immediately changes when the incision of the living tissue has been completed.
11. The treatment system according to claim 1, wherein the processor is configured to recognize a

type of the treatment instrument by performing image recognition that has been trained to learn a shape of the treatment instrument on objects shown in the image.

12. The treatment system according to claim 1, wherein the moving speed is calculated based on the moving amount of the specific point on the end effector.

13. The treatment system according to claim 1, wherein the moving amount is calculated based on the moving speed of the specific point on the end effector.

14. A control device comprising: a processor configured to: acquire an image, set, based on the image, a reference point on a living tissue in the image adjacent to an end effector, calculate, based on the image, at least one of a moving amount or a moving speed of a specific point on the end effector after a treatment energy is started to be applied to a living tissue, relative to the reference point, determine that incision of the living tissue has been completed, based on the at least one of the moving amount or the moving speed, the moving amount or the moving speed indicating that the end effector moved away from the reference point; and execute an instruction to stop supply of an electric power to a treatment instrument in response to determining that the incision of the living tissue has been completed.

15. The control device according to claim 14, wherein the processor is configured to detect an object that extends linearly from an edge of the image out of a plurality of objects shown in the image.

16. A control method, comprising: acquiring an image; setting, based on the image, a reference point on a living tissue in the image adjacent to an end effector; calculating, based on the image, at least one of a moving amount or a moving speed of a specific point on the end effector after a treatment energy is started to be applied to a living tissue, relative to the reference point; determining whether incision of the living tissue has been completed, based on the at least one of the moving amount or the moving speed, the moving amount or the moving speed indicating that the end effector moved away from the reference point; and executing an instruction to stop supply of an electric power to a treatment instrument in response to determining that the incision of the living tissue has been completed.

17. The control method according to claim 16, further comprising detecting an object that extends linearly from an edge of the image out of a plurality of objects shown in the image.
