

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12412708
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Unterreiner; Nikolaus et al.

On-load tap changer module

Abstract

An on-load tap changer module for an on-load tap changer, including a carrier, a diverter switch with a vacuum interrupter and a bridge switch, a selector, a change-over selector, and a drive module, wherein the diverter switch, the selector, and the change-over selector are arranged on the carrier and are activated centrally by the drive module.

Inventors:	Unterreiner; Nikolaus (Regensburg, DE), Hiltner; Robert (Bernhardswald, DE), Feldmeier; Stefan (Bernhardswald, DE), Muenzberg; Christian (Biburg, DE), Meyer; Markus (Hemau, DE)
Applicant:	Maschinenfabrik Reinhausen GmbH (Regensburg, DE)
Family ID:	77126825
Assignee:	MASCHINENFABRIK REINHAUSEN GMBH (Regensburg, DE)
Appl. No.:	18/042221
Filed (or PCT Filed):	July 21, 2021
PCT No.:	PCT/EP2021/070380
PCT Pub. No.:	WO2022/042954
PCT Pub. Date:	March 03, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230317382 A1	Oct. 05, 2023

Foreign Application Priority Data

DE	10 2020 122 453.2	Aug. 27, 2020
----	-------------------	---------------

Publication Classification

Int. Cl.: H01H9/00 (20060101)

U.S. Cl.:

CPC H01H9/0044 (20130101); H01H9/0016 (20130101);

Field of Classification Search

CPC: H01H (9/00); H01H (9/16); H01H (9/44); H01H (9/0005); H01H (9/0027); H01H (9/02); H01H (9/0271); H01H (15/00); H01H (15/08); H01H (19/12); H01H (2009/00); H01H (2009/0005); H01H (2009/0016); H01H (2009/0022); H01H (2009/0044); H01H (2009/0088); H01H (2009/02)

USPC: 200/52R

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
9455658	12/2015	Kammerl	N/A	H02P 13/06
2015/0091684	12/2014	Pankofer et al.	N/A	N/A
2019/0066940	12/2018	Meyer et al.	N/A	N/A
2019/0228922	12/2018	Stocker	N/A	H01F 29/04
2022/0392717	12/2021	Hiltner et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
109411254	12/2018	CN	N/A
209418349	12/2018	CN	N/A
102016104500	12/2016	DE	N/A
102016117526	12/2017	DE	N/A
102019131169	12/2020	DE	N/A
2621070	12/2016	RU	N/A

Primary Examiner: Jimenez; Anthony R

Attorney, Agent or Firm: LEYDIG, VOIT & MAYER, LTD.

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS

(1) This application is a U.S. National Phase application under 35 U.S.C. § 371 of International Application No. PCT/EP2021/070380, filed on Jul. 21, 2021, and claims benefit to German Patent Application No. DE 10 2020 122 453.2, filed on Aug. 27, 2020. The International Application was published in German on Mar. 3, 2022 as WO 2022/042954 A1 under PCT Article 21(2).

FIELD

(2) The invention relates to an on-load tap changer module for an on-load tap changer.

BACKGROUND

(3) On-load tap-changers usually have a diverter switch and a selector. The diverter switch with the vacuum interrupters and the transition resistors is arranged in a cylindrical vessel. The selector is made up of a multiplicity of bars arranged in a circle. Contacts which serve as connections for a tap winding are arranged at different levels on said bars. Two selector arms are secured to a switching pillar within the selector. They make contact with the contacts on the bars. The diverter switch and selector are connected to each other via a gear unit. The motor drive is arranged on the outside of the tap transformer and is connected to the on-load tap changer via a drive shaft. This structure requires a lot of structural space and is complex and expensive.

SUMMARY

(4) In an embodiment, the present disclosure provides an on-load tap changer module for an on-load tap changer, comprising a carrier, a diverter switch with a vacuum interrupter and a bridge switch, a selector, a change-over selector, and a drive module, wherein the diverter switch, the selector, and the change-over selector are arranged on the carrier and are activated centrally by the drive module.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) Subject matter of the present disclosure will be described in even greater detail below based on the exemplary figures. All features described and/or illustrated herein can be used alone or combined in different combinations. The features and advantages of various embodiments will become apparent by reading the following detailed description with reference to the attached drawings, which illustrate the following:

(2) The invention and its advantages are described in more detail below with reference to the attached drawings. In the drawings:

(3) FIG. 1 illustrates a first side of an on-load tap changer module;

(4) FIG. 2 illustrates a drive module for an on-load tap changer module;

(5) FIG. 3 illustrates a second side of an on-load tap changer module;

(6) FIG. 4 illustrates a detailed view of a change-over selector; and

(7) FIG. 5 illustrates an on-load tap changer with three on-load tap changer modules.

DETAILED DESCRIPTION

(8) In an embodiment, the present invention provides an on-load tap changer module for an on-load tap changer which has a simple and compact structure and nevertheless thus ensures secure operation.

(9) In an embodiment, an on-load tap changer module is provided for an on-load tap changer, comprising: a carrier, a diverter switch with a vacuum interrupter and a bridge switch, a selector, a change-over selector, a drive module, wherein: the diverter switch, the selector, and the change-over selector are arranged on the carrier and are activated centrally by the drive module.

(10) Because all the parts of the diverter switch, the selector, and the change-over selector are arranged on a single carrier, the on-load tap changer module is particularly compact. An on-load tap changer with the on-load tap changer module is thus also particularly small and takes up a small amount of structural space inside a tap transformer. The design of the on-load tap changer module furthermore enables central activation of all the parts via a common drive module. The drive module is here arranged centrally, i.e. in the middle between the diverter switch, the selector, and the change-over selector. In other words, the drive module is encircled by the diverter switch, the selector, and the change-over selector. In spite of the central arrangement of the drive module and

the compact structure, the potential-conducting parts are still safely spaced apart from one another. The central activation furthermore makes it possible, by virtue of the drive module, to carry out all the change-overs precisely.

(11) The carrier can be designed in any desired fashion and be produced, for example, as a plate or plate-like injection-molded part. The carrier can be made from plastic, fiberglass-reinforced plastic, or any other electrically insulating material.

(12) The diverter switch can be designed in any desired fashion and have, for example, one or more vacuum interrupters and one or more bridge switches. The bridge switch can be activated by a linear or rotational movement.

(13) The selector can be designed in any desired fashion and have, for example, one or more selector arms. A selector arm can be designed in any desired fashion and be configured, for example, as a Geneva wheel or a toothed wheel. The selector furthermore has a plurality of selector contacts which can, for example, have a T-shaped or L-shaped design such that, on the one hand, they extend from one side of the carrier to a second side of the carrier and, on the other hand, they project to a side wall of the carrier, where they are connected to the winding taps of a tap winding. The first side of the carrier is arranged opposite the second side of the carrier.

(14) The drive module can be designed in any desired fashion and consist, for example, of a drive shaft and at least one activating element. The drive shaft and the activating element can be configured as a single piece or multiple pieces. The activating element can be configured as a toothed wheel, cam contour, partially toothed wheel, driver, or dual driver.

(15) According to an embodiment, a plurality of activating elements can be arranged on or at the drive shaft. The plurality of activating elements can be configured as a single piece or multiple pieces. The activating elements can be connected to one another, for example, by an adhesive, screwed, or plugged-together connection.

(16) Each activating element can be designed in any desired fashion and directly or indirectly activate or drive selectors or change-over selectors, diverter switches, or parts thereof.

Alternatively, an activating element can activate a plurality of elements such as, for example, selectors and change-over selectors. Furthermore, a plurality of activating elements can activate a selector, in particular a first selector arm and a second selector arm.

(17) The drive module can be designed in any desired fashion and be arranged essentially centrally in the middle of the carrier, encircled or surrounded by selectors, change-over selectors, and diverter switches. The drive module can be arranged centrally, i.e. in the geometrical center of the carrier or approximately in the geometrical center of the carrier.

(18) It can be provided that three on-load tap changer modules are connected to one another via, for example, bars, a plurality of plates, or a frame and are activated by means of a motor and consequently form an on-load tap changer.

(19) The on-load tap changer can as required be designed in any desired fashion and be designed, for example, as a resistor-type high-speed tap changer or a reactor-type tap changer.

(20) FIG. 1 shows an on-load tap changer module 1 according to an embodiment of the invention for an on-load tap changer 9. The on-load tap changer module 1 has a carrier 2 which is made from a plastic, fiberglass-reinforced plastic, or another electrically insulating material. This carrier 2 is either designed as a milled part or is produced by means of an injection-molding process. A first selector arm 11 of a selector 10, and a bridge switch 25 of a diverter switch 20, are arranged on a first side 2.1 of the carrier 2. The first selector arm 11 is configured as a Geneva wheel. The first selector arm 11 is mounted rotatably and performs a rotational movement about a selector axis 19. Furthermore, the first selector arm 11 carries at least one first sliding contact 12. Selector contacts 18 are arranged in a circle about the selector 10, i.e. the first selector arm 11. The selector contacts 18 are configured in such a way that they, on the one hand, extend from the first side 2.1 of the carrier 2 to the second side 2.2 of the carrier and, on the other hand, are routed to a first side wall 5 of the carrier 2. Specifically, the selector contacts 18 have a T-shaped or L-shaped design.

- (21) The bridge switch **25** has a housing with contacts fastened thereon. Furthermore, the bridge switch **25** has a plurality of fixed contacts. The fixed contacts are fastened to the carrier **2** and also project from the first side **2.1** of the carrier **2** to the second side **2.2** of the carrier **2**. The housing is connected to a toothed wheel via a connecting rod. The contacts on the housing of the bridge switch **25** are connected to a load take-off lead.
- (22) A drive module **30** is furthermore arranged on the carrier **2**. It has, inter alia, a drive shaft **31** which is configured as a hollow or solid plastic square shaft. The drive shaft **31** also extends from a first side **2.1** of the carrier **2** to a second side **2.2** of the carrier **2**. The drive module **30** is arranged essentially between the selector **10** and the diverter switch **20**. A plurality of activating elements are arranged on the drive shaft **31**, as illustrated in FIG. 2, in particular a first driver **32**, a cam driver **34**, and a drive toothed wheel **35**. The first activating element, i.e. the first driver **32**, activates the first selector arm **11** of the selector **10**. The fourth activating element, i.e. the drive toothed wheel **35**, activates the bridge switch **25** of the diverter switch **20**. The third activating element, i.e. the cam driver **34**, activates a vacuum interrupter **21** of the diverter switch **20**.
- (23) FIG. 3 shows the second side **2.2** of the carrier **2**. The second selector arm **15** of the selector **10** is arranged here. The second selector arm **15** is also configured as a Geneva wheel. The second selector arm **15** is mounted rotatably and also performs a rotational movement about the selector axis **19**. The second selector arm **15** furthermore carries at least one second sliding contact **12**. Selector contacts **18** are arranged in a circle around the selector **10**, i.e. the second selector arm **15**. The selector contacts **18** are configured in such a way that, on the one hand, they extend from the second side **2.2** of the carrier **2** to the first side **2.1** of the carrier and, on the other hand, are routed to a first side wall **5** of the carrier **2**. As already described, the selector contacts **18** have a T-shaped or L-shaped design.
- (24) Furthermore, the vacuum interrupter **21** of the diverter switch **20** is arranged on the second side **2.2** of the carrier **2**. It is fixed on the carrier **2**, inter alia, by means of a bearing block. A transition resistor **4** is arranged on the second side **2.2** of the carrier **2** and is connected to the on-load tap changer module **1** via a connecting element **3**.
- (25) As can be seen in FIG. 4, a change-over selector **40** is moreover arranged on the second side **2.2** of the carrier **2**. It has a change-over selector arm **41** which is also configured as a Geneva wheel. The first change-over selector arm **41** is rotatably mounted and also performs a rotational movement about the change-over selector axis **44**. Additionally, the change-over selector **40** has a change-over selector swing arm **42** which can switch between two change-over selector contacts **43** by means of a pivoting movement.
- (26) Furthermore, a further part of the drive module **30** is arranged on the carrier **2**. It has the already mentioned drive shaft **31**. The drive module **30** is arranged essentially between the selector **10**, the diverter switch **20**, and the change-over selector **40**. A second activating element, i.e. the second driver **33**, is arranged here on the drive shaft **31**. The second driver **33** has a first catch and a second catch by means of which the second selector arm **15** of the selector **10**, and the change-over selector swing arm **42**, are activated via the change-over selector arm **41** of the change-over selector **40**.
- (27) FIG. 5 shows an on-load tap changer **9** with three on-load tap changer modules **1** which are activated via a motor by means of a common drive module **30** and its drive shaft **31**.
- (28) While subject matter of the present disclosure has been illustrated and described in detail in the drawings and foregoing description, such illustration and description are to be considered illustrative or exemplary and not restrictive. Any statement made herein characterizing the invention is also to be considered illustrative or exemplary and not restrictive as the invention is defined by the claims. It will be understood that changes and modifications may be made, by those of ordinary skill in the art, within the scope of the following claims, which may include any combination of features from different embodiments described above.
- (29) The terms used in the claims should be construed to have the broadest reasonable

interpretation consistent with the foregoing description. For example, the use of the article “a” or “the” in introducing an element should not be interpreted as being exclusive of a plurality of elements. Likewise, the recitation of “or” should be interpreted as being inclusive, such that the recitation of “A or B” is not exclusive of “A and B,” unless it is clear from the context or the foregoing description that only one of A and B is intended. Further, the recitation of “at least one of A, B and C” should be interpreted as one or more of a group of elements consisting of A, B and C, and should not be interpreted as requiring at least one of each of the listed elements A, B and C, regardless of whether A, B and C are related as categories or otherwise. Moreover, the recitation of “A, B and/or C” or “at least one of A, B or C” should be interpreted as including any singular entity from the listed elements, e.g., A, any subset from the listed elements, e.g., A and B, or the entire list of elements A, B and C.P

LIST OF REFERENCE SIGNS

(30) **1** on-load tap changer module **2** carrier **2.1** first side of **2** **2.2** second side of **2** **3** connecting element **4** transition resistor **5** first side wall of **3** **9** on-load tap changer **10** selector **11** first selector arm **12** first sliding contact **15** second selector arm **16** second sliding contact **18** selector contacts **19** selector axis **20** diverter switch **21** vacuum interrupter **25** bridge switch **30** drive module **31** drive shaft **32** first driver/first activating element **33** second driver/second activating element **34** cam driver for vacuum interrupter/third activating element **35** drive toothed wheel for bridge switch/fourth activating element **40** change-over selector **41** change-over selector arm **42** change-over selector swing arm **43** change-over selector contact **44** change-over selector axis

Claims

1. An on-load tap changer module for an on-load tap changer, the on-load tap changer module comprising: a single carrier, which is a single plate; a diverter switch comprising a vacuum interrupter and a bridge switch; a selector; a change-over selector; and a drive module, wherein the diverter switch, the selector, and the change-over selector are arranged on the carrier and are configured to be centrally activated by the drive module.
2. The on-load tap changer module as claimed in claim 1, wherein the drive module comprises a drive shaft with at least one activating element.
3. The on-load tap changer module as claimed in claim 1, wherein the selector, the change-over selector, and the diverter switch are distributed evenly on the carrier and are arranged around the drive module.
4. The on-load tap changer module as claimed in claim 1, wherein: the selector has a plurality of selector contacts, the selector contacts are arranged in a circle and extend from a first side of the carrier to a second side of the carrier, and the selector contacts are routed to a first side wall of the carrier.
5. The on-load tap changer module as claimed in claim 1, wherein the carrier has a connecting element for a transition resistor or a reactor.
6. The on-load tap changer module as claimed in claim 1, wherein the drive module is arranged on the carrier centrally between the diverter switch, the selector, and the change-over selector, wherein the drive module comprises at least one activating element arranged on a drive shaft, the at least one activating element being configured as a toothed wheel, cam contour, partially toothed wheel, driver, or dual driver, and wherein the at least one activating element is configured to directly or in directly activate the diverter switch, the selector, and the change-over selector.
7. The on-load tap changer module as claimed in claim 1, wherein the drive module comprises: a first activating element that is configured to activate a first selector arm of the selector, a second activating element that is configured to activate a second selector arm of the selector, a third activating element that is configured to activate the vacuum interrupter of the diverter switch, and a fourth activating element that is configured to activate the bridge switch of the diverter switch.

8. The on-load tap changer module as claimed in claim 7, wherein the second activating element is configured to activate the change-over selector.
 9. The on-load tap changer module as claimed in claim 7, wherein the first, second, third, and fourth activating elements are designed as a single piece or multiple pieces.
 10. An on-load tap changer module for an on-load tap changer, the on-load tap changer module comprising: a carrier; a diverter switch comprising a vacuum interrupter and a bridge switch; a selector; a change-over selector; and a drive module, wherein the diverter switch, the selector, and the change-over selector are arranged on the carrier and are configured to be centrally activated by the drive module, wherein the drive module comprises: a first activating element that is configured to activate a first selector arm of the selector, a second activating element that is configured to activate a second selector arm of the selector, a third activating element that is configured to activate the vacuum interrupter of the diverter switch, and a fourth activating element that is configured to activate the bridge switch of the diverter switch.
 11. The on-load tap changer module as claimed in claim 10, wherein the second activating element is configured to activate the change-over selector.
 12. An on-load tap changer module for an on-load tap changer, the on-load tap changer module comprising: a single carrier, which is a single plate; a diverter switch comprising a vacuum interrupter and a bridge switch; a selector; a change-over selector; and a drive module, wherein the diverter switch, the selector, and the change-over selector are arranged on the carrier and are configured to be centrally activated by the drive module, wherein the drive module is arranged on the carrier centrally between the diverter switch, the selector, and the change-over selector, wherein the drive module comprises at least one activating element arranged on a drive shaft, the at least one activating element being configured as a toothed wheel, cam contour, partially toothed wheel, driver, or dual driver, and wherein the at least one activating element is configured to directly or in directly activate the diverter switch, the selector, and the change-over selector.
-