

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12412961
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Kamiyama; Yuma et al.

Square secondary battery

Abstract

A secondary battery includes a battery case housing a flat electrode body and a sealing plate. The electrode body is housed in the battery case such that a winding axis thereof is parallel with a longitudinal direction of the sealing plate. At an end portion of the electrode body in a winding axis direction thereof, an edge of a positive or negative electrode plate is connected to an external terminal fixed to the sealing plate through a current collector. An insulating pressing member is arranged between the sealing plate and the electrode body. The pressing member presses the electrode body in a direction perpendicular to the winding axis such that a distance between a portion of the electrode body contacting the pressing member and the sealing plate is longer than a distance between the end portion of the electrode body in the winding axis direction thereof and the sealing plate.

Inventors:	Kamiyama; Yuma (Osaka, JP), Wakimoto; Ryoichi (Hyogo, JP)
Applicant:	SANYO Electric Co., Ltd. (Kadoma, JP)
Family ID:	77291893
Assignee:	SANYO Electric Co., Ltd. (Osaka, JP)
Appl. No.:	17/791328
Filed (or PCT Filed):	January 19, 2021
PCT No.:	PCT/JP2021/001683
PCT Pub. No.:	WO2021/161738
PCT Pub. Date:	August 19, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20230352799 A1	Nov. 02, 2023

Foreign Application Priority Data

JP	2020-022465	Feb. 13, 2020
----	-------------	---------------

Publication Classification

Int. Cl.: **H01M50/474** (20210101); **H01M50/103** (20210101); **H01M50/15** (20210101); **H01M50/486** (20210101); **H01M50/538** (20210101); H01M10/04 (20060101); H01M50/477 (20210101)

U.S. Cl.:

CPC **H01M50/474** (20210101); **H01M50/103** (20210101); **H01M50/15** (20210101); **H01M50/486** (20210101); **H01M50/538** (20210101); H01M10/0431 (20130101); H01M10/0468 (20130101); H01M50/477 (20210101); Y02E60/10 (20130101); Y02P70/50 (20151101)

Field of Classification Search

CPC: H01M (10/0431); H01M (10/0468); H01M (50/103); H01M (50/15); H01M (50/474); H01M (50/477); H01M (50/486); H01M (50/538); Y02E (60/10); Y02P (70/50)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2013/0052500	12/2012	Nonaka et al.	N/A	N/A
2015/0287966	12/2014	Jeong	N/A	N/A
2015/0357670	12/2014	Yamafuku	429/94	H01M 50/477
2018/0097207	12/2017	Unno et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
107534115	12/2017	CN	N/A
2013-54821	12/2012	JP	N/A
2015-49959	12/2014	JP	N/A
2015-049959	12/2014	JP	N/A
2015-232941	12/2014	JP	N/A
2016/185867	12/2015	WO	N/A

OTHER PUBLICATIONS

International Search Report dated Apr. 6, 2021, issued in counterpart International Application No. PCT/JP2021/001683, w/English translation (5 pages). cited by applicant

Office Action dated Oct. 18, 2022, issued in counterpart IN Application No. 202247035579, with English Translation. (5 pages). cited by applicant

Extended Supplementary European Search Report dated Sep. 27, 2024, issued in counterpart Application No. 21754346.1. (9 pages). cited by applicant

Chinese Search Report dated Mar. 29, 2025, issued in counterpart CN Application No. 202180012124.X, with English Translation. (5 pages). cited by applicant

Primary Examiner: Zeng; Lingwen R

Attorney, Agent or Firm: WHDA, LLP

Background/Summary

TECHNICAL FIELD

(1) The present disclosure relates to a rectangular secondary battery configured such that a flat electrode body is housed in a rectangular battery case.

BACKGROUND ART

(2) A secondary battery such as a lithium ion secondary battery has a structure in which an electrode body configured such that a positive electrode plate and a negative electrode plate are wound with a separator interposed therebetween is housed in a battery case together with an electrolytic solution.

(3) Patent Document 1 discloses a rectangular secondary battery configured such that a flat electrode body is housed in a rectangular battery case with a winding axis of the electrode body being parallel with a longitudinal direction of a sealing plate. Edges of positive and negative electrode plates extending from both end portions (hereinafter merely referred to as “end portions”) of the electrode body in a winding axis direction thereof are each connected to external terminals

fixed to the sealing plate through current collectors. The sealing plate is provided with a gas discharge valve, and when the pressure of gas generated in the battery exceeds a predetermined value, the gas discharge valve is operated to release the gas to the outside of the battery.

CITATION LIST

Patent Document

(4) PATENT DOCUMENT 1: Japanese Unexamined Patent Publication No. 2013-54821

SUMMARY OF THE INVENTION

(5) In the rectangular secondary battery disclosed in Patent Document 1, the electrode body is housed in the battery case such that the winding axis thereof is parallel with the longitudinal direction of the sealing plate. Thus, gas generated by reaction with an electrolytic solution in the electrode body moves along the winding axis, and is discharged from the end portions of the electrode body to a space in the battery case.

(6) Since both end portions of the electrode body are connected to the current collectors fixed to the sealing plate, these end portions are fixed by the current collectors. Thus, even when the volume of the negative electrode plate forming the electrode body expands due to charging and discharging, the positions of both end portions of the electrode body do not move. On the other hand, a center portion (hereinafter merely referred to as a “center portion”) of the electrode body in a winding axis direction thereof is not fixed by the current collectors. For this reason, when the volume of the negative electrode plate expands, the center portion of the electrode body expands in a direction perpendicular to the winding axis. Thus, as a result of repeated charging and discharging of the secondary battery in a state in which the secondary battery is placed with the sealing plate positioned on the upper side, the center portion of the electrode body is positioned higher than both end portions of the electrode body.

(7) Normally, gas generated by reaction with the electrolytic solution in the electrode body is lighter than the electrolytic solution. For this reason, gas generated at the center portion of the electrode body is less likely to be discharged from both end portions of the electrode body. As a result, gas which cannot be discharged from both end portions of the electrode body tends to be accumulated on the center portion of the electrode body.

(8) Active materials are covered with the gas accumulated in the electrode body, and such active materials cannot be utilized. This leads to, e.g., capacity/power decline and lithium deposition. Particularly, in a battery increased in size, the length of an electrode body in the winding axis direction thereof is longer, and therefore, a gas discharge path is longer. Accordingly, the amount of gas accumulated in the electrode body is greater, and as a result, e.g., capacity/power decline and lithium deposition become more prominent.

(9) A rectangular secondary battery according to the present disclosure includes a flat electrode body configured such that a positive electrode plate and a negative electrode plate are wound with a separator interposed therebetween, a rectangular battery case having an opening and housing the electrode body, and a sealing plate sealing the opening. The electrode body is housed in the battery case such that a winding axis of the electrode body is parallel with a longitudinal direction of the sealing plate. At an end portion of the electrode body in a winding axis direction thereof, an edge of the positive or negative electrode plate is connected to an external terminal fixed to the sealing plate through a current collector. An insulating pressing member contacting the sealing plate and the electrode body is arranged between the sealing plate and the electrode body. The pressing member presses the electrode body in a direction perpendicular to the winding axis of the electrode body such that a distance between a portion of the electrode body contacting the pressing member and the sealing plate is longer than a distance between the end portion of the electrode body in the winding axis direction thereof and the sealing plate.

(10) According to the present disclosure, the rectangular secondary battery can be provided, which is configured so that capacity/power decline and lithium deposition due to deformation of the electrode body caused by expansion of the volume of the negative electrode plate can be reduced.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIGS. **1A** to **1C** are views schematically showing the configuration of a rectangular secondary battery in one embodiment of the present disclosure, FIG. **1A** is a plan view, FIG. **1B** is a sectional view along an Ib-Ib line of FIG. **1A**, and FIG. **1C** is a sectional view along an Ic-Ic line of FIG. **1B**.

(2) FIGS. **2A** and **2B** are views for describing features and advantageous effects in the present embodiment.

(3) FIGS. **3A** and **3B** are views for describing the steps of assembling the rectangular secondary battery.

(4) FIGS. **4A** and **4B** are views for describing the steps of assembling the rectangular secondary battery.

(5) FIG. **5A** is a perspective view showing a specific example of the shape of a pressing member.

(6) FIG. **5B** is a perspective view showing a specific example of the shape of the pressing member.

(7) FIG. **5C** is a perspective view showing a specific example of the shape of the pressing member.

(8) FIGS. **6A** to **6D** are views showing a variation of the present embodiment. FIG. **6A** is a plan view of a rectangular secondary battery, FIG. **6B** is a sectional view along a VIb-VIb line of FIG. **6A**, FIG. **6C** is a sectional view along a VIc-VIc line of FIG. **6B**, and FIG. **6D** is a perspective view of a pressing member.

(9) FIGS. **7A** and **7B** are views showing another variation of the present embodiment, FIG. **7A** is a plan view of a rectangular secondary battery, and FIG. **7B** is a sectional view along a VIb-VIIb line of FIG. **7A**.

(10) FIG. **8** is a view showing the dimensions of an electrode body and a pressing member in examples.

DESCRIPTION OF EMBODIMENTS

(11) Hereinafter, an embodiment of the present disclosure will be described in detail based on the drawings. Note that the present invention is not limited to the following embodiment. Moreover, changes can be made as necessary without departing from a scope in which the advantageous effects of the present invention are provided.

(12) FIGS. **1A** to **1C** are views schematically showing the configuration of a rectangular secondary battery in one embodiment of the present disclosure. FIG. **1A** is a plan view, FIG. **1B** is a sectional view along an Ib-Ib line of FIG. **1A**, and FIG. **1C** is a sectional view along an Ic-Ic line of FIG. **1B**. The rectangular secondary battery in the present embodiment is a battery using a “non-aqueous” electrolyte such as an organic electrolyte/solvent, and the type thereof is not particularly limited. Representative examples of the non-aqueous electrolyte secondary battery include a lithium ion secondary battery.

(13) As shown in FIGS. **1A** to **1C**, the rectangular secondary battery **10** in the present embodiment includes an electrode body **11**, a rectangular battery case **20** housing the electrode body **11**, and a sealing plate **21** sealing an opening of the battery case **20**. The electrode body **11** has a flat structure in which a positive electrode plate and a negative electrode plate are wound with a separator interposed therebetween. The electrode body **11** is housed in the battery case **20** such that a winding axis (the right-left direction as viewed in the figure) of the electrode body **11** is parallel with a longitudinal direction A of the sealing plate **21**.

(14) At end portions (hereinafter merely referred to as “end portions”) **12**, **13** of the electrode body **11** in a winding axis direction thereof, edges of the positive and negative electrode plates are each connected to positive and negative electrode external terminals **14**, **15** fixed to the sealing plate **21** through positive and negative electrode current collectors **16**, **17**. The edges of the positive and negative electrode plates are regions to which no positive and negative electrode active materials are applied.

(15) The positive and negative electrode external terminals **14**, **15** are fixed to the sealing plate **21** through insulating plates **18**, **19**. With this configuration, the positive and negative electrode external terminals **14**, **15** are electrically insulated from the sealing plate **21**. The sealing plate **21** is provided with a gas discharge valve **22**. The gas discharge valve **22** releases gas from the battery when the internal pressure of the battery case **20** has increased to a predetermined value or more. The sealing plate **21** is provided with a solution injection hole, and the solution injection hole is sealed with a plug **23** after the electrolytic solution has been injected into the battery case **20** through the solution injection hole.

(16) In the present embodiment, an insulating pressing member **30** contacting the sealing plate **21** and the electrode body **11** is arranged between the sealing plate **21** and the electrode body **11**. The pressing member **30** is arranged at a center portion (hereinafter merely referred to as a “center portion”) of the electrode body **11** in the winding axis direction thereof.

(17) The pressing member **30** presses the center portion of the electrode body **11** in a direction (a downward direction as viewed in the figure) perpendicular to the winding axis of the electrode body **11**. With this configuration, a distance between a portion **11a** of the electrode body **11** contacting the pressing member **30** and the sealing plate **21** is longer than a distance between the end portion **12**, **13** of the electrode body **11** and the sealing plate **21**. That is, when the rectangular secondary battery **10** is placed in a state in which the sealing plate **21** provided with the gas discharge valve **22** is positioned on the upper side, the sealing-plate-**21**-side (the upper side as viewed in the figure) end portion **11a** of the electrode body **11** at the center portion thereof is positioned lower than sealing-plate-**21**-side end portions of the end portions **12**, **13** of the electrode body **11**. Since the end portion **11a** of the electrode body **11** is pressed by the pressing member **30** and is maintained in a bent state, the position of the end portion **11a** does not change even when the volume of the negative electrode plate expands.

(18) Next, features and advantages effects in the present embodiment will be described with reference to FIGS. 2A and 2B. FIGS. 2A and 2B do not show the battery case **20**, the sealing plate **21**, etc., and show only the electrode body **11** and the current collectors **16**, **17**. FIG. 2A shows a case where no pressing member **30** is arranged between the sealing plate **21** and the electrode body **11**, and FIG. 2B shows a case where the pressing member **30** is arranged between the sealing plate **21** and the electrode body **11**.

(19) In the case where no pressing member **30** is arranged between the sealing plate **21** and the electrode body **11** as shown in FIG. 2A, the positions of both end portions **12**, **13** of the electrode body **11** do not move even when the volume of the negative electrode plate forming the electrode body **11** expands because both end portions **12**, **13** of the electrode body **11** are fixed by the current collectors **16**, **17** fixed to the sealing plate **21**.

(20) On the other hand, since the center portion of the electrode body **11** is not fixed by the current collectors **16**, **17**, the center portion of the electrode body **11** expands in the direction (the up-down direction as viewed in the figure) perpendicular to the winding axis when the volume of the negative electrode plate expands. For this reason, as a result of repeated charging and discharging in a state in which the rectangular secondary battery **10** is placed with the sealing plate **21** positioned on the upper side, the sealing-plate-**21**-side (the upper side as viewed in the figure) end portion **11a** of the electrode body **11** at the center portion thereof is positioned higher than the sealing-plate-**21**-side end portions of the end portions **12**, **13** of the electrode body **11**.

(21) Normally, gas generated by reaction with the electrolytic solution in the electrode body **11** is lighter than the electrolytic solution. For this reason, gas generated at the sealing-plate-**21**-side (the upper side as viewed in the figure) end portion **11a** of the electrode body **11** at the center portion thereof is less likely to be discharged from the end portions **12**, **13** of the electrode body **11**. As a result, gas which cannot be discharged from the end portions **12**, **13** of the electrode body **11** tends to be accumulated on the center portion of the electrode body **11**.

(22) The active materials are covered with the gas accumulated in the electrode body **11**, and such

active materials cannot be utilized. This leads to, e.g., capacity/power decline and lithium deposition. Particularly, in a battery increased in size, the length of an electrode body **11** in the winding axis direction thereof is longer, and therefore, a gas discharge path is longer. Accordingly, the amount of gas accumulated in the electrode body **11** is greater, and as a result, e.g., capacity/power decline and lithium deposition become more prominent.

(23) On the other hand, in the case where the pressing member **30** is arranged between the sealing plate **21** and the electrode body **11** as shown in FIG. 2B, the sealing-plate-2I-side (the upper side as viewed in the figure) end portion **11a** of the electrode body **11** at the center portion thereof is, as described above, positioned lower than the sealing-plate-2I-side end portions of the end portions **12**, **13** of the electrode body **11** when the rectangular secondary battery **10** is placed with the sealing plate **21** positioned on the upper side.

(24) Thus, gas generated at the sealing-plate-2I-side end portion **11a** of the electrode body **11** at the center portion thereof is forcibly discharged toward the end portions **12**, **13** of the electrode body **11** at the positions higher than the end portion **1a**. With this configuration, gas accumulation on the center portion of the electrode body **11** can be reduced. As a result, capacity/power decline and lithium deposition due to deformation of the electrode body **11** caused by expansion of the volume of the negative electrode plate can be reduced.

(25) Next, the steps of assembling the rectangular secondary battery in the present embodiment will be described with reference to FIGS. 3A, 3B, 4A, and 4B.

(26) First, as shown in FIG. 3A, the sealing plate **21** to which the external terminals **14**, **15** and the current collectors **16**, **17** are attached, the pressing member **30**, and the electrode body **11** are prepared.

(27) Next, as shown in FIG. 3B, the electrode body **11** is arranged such that the winding axis of the electrode body **11** is parallel with the longitudinal direction of the sealing plate **21**, and thereafter, the pressing member **30** is sandwiched between the sealing plate **21** and the electrode body **11**. Note that the pressing member **30** is arranged at the center portion of the electrode body **11**. Thereafter, a center portion of the sealing plate **21** and both end portions **12**, **13** of the electrode body **11** are pressed from the opposite directions, and accordingly, the portion of the electrode body **11** contacting the pressing member **30** is bent.

(28) Next, as shown in FIG. 4A, while the bent state of the electrode body **11** is maintained, the current collectors **16**, **17** are each welded to the end portions **12**, **13** of the electrode body **11** at welding locations **40**, **41**.

(29) Next, as shown in FIG. 4B, the electrode body **11** attached to the sealing plate **21** is housed in the rectangular battery case **20**, and thereafter, the sealing plate **21** is welded at the peripheral edge of the opening of the battery case **20**. Note that the force of bending the sealing plate **21** acts from the electrode body **11** through the pressing member **30**, and therefore, for avoiding bending of the sealing plate **21**, the sealing plate **21** is preferably welded while the center portion of the sealing plate **21** is pressed.

(30) The pressing member **30** arranged between the sealing plate **21** and the electrode body **11** receives reactive force from the pressed electrode body **11**. Thus, the position of the pressing member **30** can be maintained without the need for fixing the pressing member **30** by the sealing plate **21**, for example. The pressing member **30** may be fixed by the sealing plate **21**, for example.

(31) In the present embodiment, the material of the pressing member **30** is not particularly limited as long as the material has heat resistance even in the battery **10**. Examples of the material to be used for the pressing member **30** may include resins such as polypropylene (PP) and polyethylene (PE) and rubbers such as polyvinylidene fluoride (PVDF) and styrene-butadiene copolymer (SBR).

(32) In the present embodiment, the shape of the pressing member **30** is not particularly limited. FIGS. 5A to 5C are perspective views showing, as examples, the shape of the pressing member **30**. In these figures, an arrow A indicates the longitudinal direction of the sealing plate **21**.

(33) As shown in FIG. 1C, the electrode body **11** is configured such that the end portions **11a**, **11b**

of the electrode body **11** in the direction perpendicular to the winding axis direction are in a curved shape. Thus, as shown in FIG. 5A, a surface **30a**, which is to contact the electrode body **11**, of the pressing member **30** is preferably in a curved shape along the curved shape of the end portion **11a** of the electrode body **11**. With this configuration, the electrode body **11** can be stably pressed without extra stress applied to the electrode body **11**.

(34) Alternatively, as shown in FIG. 5B, the portion, which is to contact the electrode body **11**, of the pressing member **30** may include an elastic body **31**. With this configuration, stress applied to the electrode body **11** when the electrode body **11** is pressed by the pressing member can be reduced. As a result, e.g., cracking of the electrode plate forming the electrode body **11** can be reduced or prevented.

(35) Of surfaces, which are to contact the electrode body **11**, of the pressing member **30**, surfaces **30b** parallel with the longitudinal direction A of the sealing plate **21** may be in a curved shape protruding toward the electrode body **11**, as shown in FIG. 5C. With this configuration, the electrode body **11** can be smoothly bent along the longitudinal direction A. As a result, e.g., cracking of the electrode plate forming the electrode body **11** can be reduced or prevented.

Variations of Present Embodiment

(36) In the above-described embodiment, the gas discharge valve **22** provided at the sealing plate **21** is at the position apart from the center portion of the sealing plate **21** for avoiding contact with the pressing member **30** arranged at the center portion of the electrode body **11**, as shown in FIGS. 1A and 1B.

(37) However, for quickly discharging gas from the battery case **20** to the outside of the battery, the gas discharge valve **22** is preferably provided at the position at which the gas discharge path is shortest, i.e., the center portion of the sealing plate **21**.

(38) FIGS. 6A to 6D are views showing a variation of a rectangular secondary battery configured such that a gas discharge valve **22** is provided at a center portion of a sealing plate **21**. FIG. 6A is a plan view of the rectangular secondary battery, FIG. 6B is a sectional view along a VIb-VIb line of FIG. 6A, FIG. 6C is a sectional view along a VIc-VIc line of FIG. 6B, and FIG. 6D is a perspective view of a pressing member **30**.

(39) As shown in FIGS. 6A and 6B, the gas discharge valve **22** is provided at the center portion of the sealing plate **21**. Moreover, the pressing member **30** is arranged at a center portion of an electrode body **11** as in that shown in FIGS. 1A and 1B. As shown in FIGS. 6C and 6D, the pressing member **30** is, on the side contacting the sealing plate **21**, formed with a groove **30c** along the longitudinal direction of the sealing plate **21** such that the groove **30c** overlaps with the gas discharge valve **22** as viewed in plane. That is, the pressing member **30** is arranged at such a position that the pressing member **30** does not contact the gas discharge valve **22**. With this configuration, gas accumulated in a battery case **20** is quickly discharged to the outside of the battery through the gas discharge valve **22** by way of the groove **30c**.

(40) FIGS. 7A and 7B are views showing another variation of the rectangular secondary battery configured such that the gas discharge valve **22** is provided at the center portion of the sealing plate **21**. FIG. 7A is a plan view of the rectangular secondary battery, and FIG. 7B is a sectional view along a VIIb-VIb line of FIG. 7A.

(41) As shown in FIGS. 7A and 7B, the gas discharge valve **22** is provided at the center portion of the sealing plate **21**. Moreover, a pair of pressing members **30a**, **30b** is, as viewed in plane, arranged between the sealing plate **21** and the electrode body **11** through the gas discharge valve **22**. That is, the pressing members **30a**, **30b** are arranged at such positions that the pressing members **30a**, **30b** do not contact the gas discharge valve **22**. With this configuration, gas accumulated in the battery case **20** is quickly discharged to the outside of the battery through the gas discharge valve **22**.

(42) Note that the pressing members **30a**, **30b** are not arranged at the center portion of the electrode body **11** in the present variation, but the electrode body **11** pressed by the pair of pressing members

30a, **30b** is, as shown in FIG. 7B, bent in a manner substantially similar to that in the case shown in FIG. 1B. That is, the pair of pressing members **30a**, **30b** provides features and advantageous effects similar to those in the case where the single pressing member **30** is arranged at the center portion of the electrode body **11**.

Examples

(43) Hereinafter, examples of the present disclosure will be described. The present invention is not limited to the following examples.

(44) (Production of Lithium Ion Secondary Battery)

(45) A lithium ion secondary battery having the structure shown in FIGS. 1A to 1C was produced by the following steps.

(46) A positive electrode material mixture including a positive electrode active material containing lithium-nickel-cobalt-manganese composite oxide was applied to both surfaces of a positive electrode core made of aluminum foil, and in this manner, a strip-shaped positive electrode plate was produced. A negative electrode material mixture including a negative electrode active material containing black lead was applied to both surfaces of a negative electrode core made of copper foil, and in this manner, a strip-shaped negative electrode plate was produced. The produced strip-shaped positive and negative electrode plates were wound with a polyolefin separator interposed therebetween, and in this manner, a flat electrode body **11** was produced.

(47) As shown in FIG. 8, the length L of the electrode body **11** in a winding axis direction thereof was 280 mm. The length L was the length of a region to which the active materials were applied.

(48) A positive electrode current collector **16** made of aluminum alloy and a negative electrode current collector **17** made of copper alloy were attached to a sealing plate **21**, and thereafter, the electrode body **11** was pressed and bent by a pressing member **30** by the steps shown in FIG. 3B. Thereafter, by the steps shown in FIG. 4A, the positive electrode current collector **16** and the negative electrode current collector **17** were each welded to the positive and negative electrode cores extending from end portions **12**, **13** of the electrode body **11**.

(49) As shown in FIG. 8, pressing members **30** whose ratios (D/L) of the length D of the pressing member **30** to the length L of the electrode body **11** in the winding axis direction are 10%, 30%, 50%, and 70% were used as the pressing member **30**. Moreover, a pressing distance S by which the electrode body **11** is pressed by the pressing member **30** was 0 mm, 0.5 mm, 1.0 mm, and 1.5 mm.

(50) The electrode body **11** attached to the sealing plate **21** was housed in a battery case **20**, and thereafter, the sealing plate **21** was welded to an edge of an opening of the battery case to seal the battery case **20**. A non-aqueous electrolytic solution was injected into the battery case **20** through a solution injection hole, and thereafter, the solution injection hole was sealed with a plug. In this manner, a lithium ion secondary battery was produced. The designed capacity of the produced lithium ion secondary battery was 60 Ah.

(51) Note that a small lithium ion battery that the length L of an electrode body **11** is 120 mm and a designed capacity is 28 Ah was also produced as a reference by a similar method.

(52) (Evaluation of Li Deposition)

(53) It has been known that as a result of repeated charging and discharging in a state in which gas is accumulated in the electrode body **11**, excessive current concentration is caused around bubbles caused due to the gas and Li is deposited on a negative electrode plate surface due to concentration of Li ions, which can be occluded in the negative electrode active material, or more. For this reason, gas accumulation in the electrode body **11** was evaluated based on whether or not Li is deposited on the negative electrode plate surface after the charged and discharged lithium ion battery had been disassembled. A test was conducted by the following method.

(54) The produced battery was charged with a constant current at 1.0 C until reaching 4.2 V, and subsequently, was discharged at 1.0 C until a battery voltage reaches 2.5 V. After charging and discharging, the battery was disassembled, the negative electrode plate was taken out, and the presence or absence of Li deposition was visually checked.

(55) Table 1 shows evaluation results. Note that the same test was also conducted for the small lithium ion battery produced as a reference.

(56) TABLE-US-00001 TABLE 1 Electrode Body Pressing Length Distance Pressing Member Length Ratio (D/L) (L) (S) 10% 30% 50% 70% 280 mm 0 mm Deposited 0.5 mm Deposited Deposited Deposited Deposited 1.0 mm Not Not Not Deposited Deposited Deposited Deposited 1.5 mm Not Not Not Deposited Deposited Deposited Deposited 120 mm 0 mm Not Deposited

(57) As shown in Table 1, Li deposition was observed on the negative electrode plate surface in the battery (the pressing distance S is 0 mm) in which the electrode body **11** is not pressed by the pressing member **30**. Moreover, Li deposition was also observed in the battery with a pressing distance S of 0.5 mm.

(58) On the other hand, in the batteries with a pressing distance S of 1.0 mm and 1.5 mm, Li deposition was observed in the case where the ratio (D/L) of the length of the pressing member **30** is 70%, but no Li deposition was observed in the case where the ratio (D/L) of the length of the pressing member **30** is 50% or less.

(59) In the small lithium ion battery produced as a reference, no Li deposition was observed even without pressing of the electrode body **11** by the pressing member **30**.

(60) The above-described results show that the small lithium ion battery having a short length of the electrode body **11** and a small capacity does not show the phenomenon that Li is deposited on the negative electrode plate surface, but gas tends to be accumulated in the electrode body **11** in the size-increased lithium ion battery having a long length of the electrode body **11** and a great capacity and such a lithium ion battery prominently shows the phenomenon that Li is deposited on the negative electrode plate surface.

(61) The results also show that in such a size-increased lithium ion battery, the electrode body **11** is bent by the pressing member **30** so that gas accumulation in the electrode body **11** can be reduced and Li deposition on the negative electrode plate can be reduced accordingly.

(62) Note that in a case where the ratio (D/L) of the length of the pressing member **30** is 70% or more, bending of the electrode body **11** is insufficient and the feature and advantageous effect of forcibly discharging gas generated in the electrode body **11** toward the end portions of the electrode body **11** are not provided. Thus, for providing these feature and advantageous effect, the ratio (D/L) of the length of the pressing member **30** is preferably equal to or less than 50% (equal to or less than $\frac{1}{2}$) and more preferably equal to or less than 30%.

(63) In a case where the pressing distance S by which the electrode body **11** is pressed by the pressing member **30** is short, bending of the electrode body **11** is insufficient, and similar feature and advantageous effect are not provided. Thus, for providing these feature and advantageous effect, the pressing distance S of the electrode body **11** is preferably equal to or greater than 1.0 mm. Note that in the case of an extremely-long pressing distance S, e.g., cracking of the electrode plate forming the electrode body **11** might be caused. For this reason, the pressing distance S of the electrode body **11** is preferably equal to or less than 5 mm.

(64) The present disclosure has been described with reference to the preferred embodiments, but such description does not limit the present disclosure. Needless to say, various modifications can be made.

DESCRIPTION OF REFERENCE CHARACTERS

(65) **10** Rectangular Secondary Battery **11** Electrode Body **12** End Portion of Electrode Body (Positive Electrode Core) **13** End Portion of Electrode Body (Negative Electrode Core) **14, 15** External Terminal **16** Current Collector (Positive Electrode Current Collector) **17** Current Collector (Negative Electrode Current Collector) **20** Battery Case **21** Sealing Plate **22** Gas Discharge Valve **23** Plug **30** Pressing Member **31** Elastic Body

Claims

1. A rectangular secondary battery comprising: a flat electrode body configured such that a positive electrode plate and a negative electrode plate are wound with a separator interposed therebetween; a rectangular battery case having an opening and housing the electrode body; and a sealing plate sealing the opening, wherein the electrode body is housed in the battery case such that a winding axis of the electrode body is parallel with a longitudinal direction of the sealing plate, at an end portion of the electrode body in a winding axis direction thereof, an edge of the positive or negative electrode plate is connected to an external terminal fixed to the sealing plate through a current collector, an insulating pressing member contacting the sealing plate and the electrode body is arranged between the sealing plate and the electrode body, the pressing member is configured to press a portion of the electrode body in a direction perpendicular to the winding axis of the electrode body thereby maintaining said portion in a bent state such that a distance between said portion of the electrode body contacting the pressing member and the sealing plate is longer than a distance between the end portion of the electrode body in the winding axis direction thereof and the sealing plate, and wherein the pressing member is located only on an end portion of the electrode body facing the sealing plate and along an adjacent curved shape of the end portion of the electrode body.
 2. The rectangular secondary battery of claim 1, wherein the pressing member is made of resin.
 3. The rectangular secondary battery of claim 1, wherein a portion of the pressing member contacting the electrode body includes an elastic body.
 4. The rectangular secondary battery of claim 1, wherein the electrode body is configured such that an end portion of the electrode body in a direction perpendicular to the winding axis direction of the electrode body is in a curved shape, and a surface of the pressing member contacting the electrode body is in a curved shape along the curved shape of the end portion of the electrode body.
 5. The rectangular secondary battery of claim 1, wherein the sealing plate is provided with a gas discharge valve, and the pressing member is arranged at a position at which the pressing member does not contact with the gas discharge valve.
 6. The rectangular secondary battery of claim 1, wherein the pressing member is arranged at a center portion of the electrode body in the winding axis direction thereof, and a length of the pressing member in the winding axis direction of the electrode body is equal to or less than $\frac{1}{2}$ of a length of the electrode body in the winding axis direction thereof.
-