

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12403286
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Spataro; Joe et al.

Passive dilation in catheter insertion systems

Abstract

Disclosed herein is a catheter, which in some embodiments includes a distal section configured to enter a skin insertion site. The distal section can include a tapered junction having one or more dilation structures configured to dilate the skin insertion site. The distal section can further include a distal portion extending from a distal end of the tapered junction, the distal portion having a diameter smaller than a proximal portion of the catheter. In combination, the tapered junction, the one or more dilation structures, and the specific actions of the user urging the catheter into the insertion site can result in an improved fit of the catheter in the insertion site.

Inventors: Spataro; Joe (Cottonwood Heights, UT), Blanchard; Daniel B. (Bountiful, UT), Thornley; Kyle G. (Farmington, UT), Mckinnon; Austin J. (Herriman, UT)

Applicant: Bard Access Systems, Inc. (Salt Lake City, UT)

Family ID: 80035035

Assignee: Bard Access Systems, Inc. (Salt Lake City, UT)

Appl. No.: 17/542096

Filed: December 03, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20220176081 A1	Jun. 09, 2022

Related U.S. Application Data

us-provisional-application US 63121761 20201204

Publication Classification

Int. Cl.: A61M25/00 (20060101); **A61M25/06** (20060101)

U.S. Cl.:

CPC **A61M25/0662** (20130101); **A61M25/0068** (20130101); **A61M25/0082** (20130101);
A61M2025/0687 (20130101)

Field of Classification Search

CPC: A61M (25/0662); A61M (25/02); A61M (25/0023); A61M (25/0068); A61M (25/0082);
A61M (2025/0687); A61M (2025/0286); A61M (2025/0293); A61M (2025/0096); A61B
(17/32093); A61B (17/3415); A61B (17/3209); A61B (2017/3458); A61B (90/02)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2566499	12/1950	Richter	N/A	N/A
2842133	12/1957	Uhma	N/A	N/A
3921631	12/1974	Thompson	604/508	A61M 25/065
4601710	12/1985	Moll	N/A	N/A
4693250	12/1986	Coons	N/A	N/A
4889112	12/1988	Schachner et al.	N/A	N/A
4955890	12/1989	Yamamoto et al.	N/A	N/A
5279285	12/1993	Griggs	N/A	N/A
5334157	12/1993	Klein et al.	N/A	N/A
5509900	12/1995	Kirkman	606/198	A61M 25/04
5755697	12/1997	Jones et al.	N/A	N/A
5800450	12/1997	Lary et al.	N/A	N/A
5843115	12/1997	Morejon	N/A	N/A
6033388	12/1999	Nordstrom et al.	N/A	N/A
6517519	12/2002	Rosen et al.	N/A	N/A
6761725	12/2003	Grayzel et al.	N/A	N/A
9114227	12/2014	Blanchard	N/A	N/A
9480498	12/2015	Kessler	N/A	N/A
10028762	12/2017	Slupchynskyj	N/A	N/A
10376675	12/2018	Mitchell et al.	N/A	N/A
2002/0040231	12/2001	Wysoki	N/A	N/A
2004/0133227	12/2003	Shang et al.	N/A	N/A
2004/0181246	12/2003	Heppler	N/A	N/A
2004/0181273	12/2003	Brasington et al.	N/A	N/A
2005/0177183	12/2004	Thorne et al.	N/A	N/A
2009/0024089	12/2008	Levine et al.	N/A	N/A
2009/0076435	12/2008	Melsheimer et al.	N/A	N/A
2009/0125030	12/2008	Tebbe et al.	N/A	N/A
2010/0057056	12/2009	Gurtner et al.	N/A	N/A
2012/0130417	12/2011	Lepulu et al.	N/A	N/A
2012/0226299	12/2011	Heppler	N/A	N/A
2013/0197558	12/2012	Ingold, Jr. et al.	N/A	N/A

2016/0128713	12/2015	Rauchwerger et al.	N/A	N/A
2016/0346503	12/2015	Jackson	N/A	A61M 25/0021
2017/0128700	12/2016	Roche Rebollo	N/A	A61M 25/0105
2017/0296792	12/2016	Ornelas Vargas et al.	N/A	N/A
2019/0307485	12/2018	Kiev	N/A	A61B 17/3496
2019/0351183	12/2018	Ishida	N/A	N/A
2020/0061322	12/2019	De Rezende Neto	N/A	N/A
2020/0086095	12/2019	Kleinhaus	N/A	A61B 17/3478
2020/0155190	12/2019	Basadonna et al.	N/A	N/A
2020/0222077	12/2019	Takahashi	N/A	N/A
2020/0246597	12/2019	Broniec et al.	N/A	N/A
2021/0069471	12/2020	Howell	N/A	N/A
2021/0085927	12/2020	Howell	N/A	N/A
2021/0106351	12/2020	Hossack et al.	N/A	N/A
2021/0113809	12/2020	Howell	N/A	N/A
2021/0113810	12/2020	Howell	N/A	N/A
2021/0121661	12/2020	Howell	N/A	N/A
2021/0212722	12/2020	Kiev et al.	N/A	N/A
2022/0152368	12/2021	Thornley et al.	N/A	N/A
2023/0141739	12/2022	Doctor et al.	N/A	N/A
2023/0233227	12/2022	Lindekugel et al.	N/A	N/A
2023/0241353	12/2022	Howell et al.	N/A	N/A
2023/0241354	12/2022	Howell	N/A	N/A
2023/0255660	12/2022	Howell	N/A	N/A
2023/0255661	12/2022	Howell	N/A	N/A
2023/0277212	12/2022	Howell	N/A	N/A
2023/0277813	12/2022	Howell	N/A	N/A
2023/0277814	12/2022	Howell	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2456639	12/2000	CN	N/A
210844555	12/2019	CN	N/A
111481303	12/2019	CN	N/A
112155683	12/2020	CN	N/A
10100332	12/2001	DE	N/A
202004012605	12/2003	DE	N/A
9108709	12/1990	WO	N/A
9412091	12/1993	WO	N/A
02087666	12/2001	WO	N/A
03022129	12/2002	WO	N/A
2011024013	12/2010	WO	N/A
2011057282	12/2010	WO	N/A
2012087506	12/2011	WO	N/A
2016176065	12/2015	WO	N/A

2017006323	12/2016	WO	N/A
2020076691	12/2019	WO	N/A
2022104149	12/2021	WO	N/A
2022120201	12/2021	WO	N/A
2023081465	12/2022	WO	N/A
2023122313	12/2022	WO	N/A
2023141170	12/2022	WO	N/A
2023150263	12/2022	WO	N/A
2023150314	12/2022	WO	N/A
2023158643	12/2022	WO	N/A
2023158645	12/2022	WO	N/A
2023167943	12/2022	WO	N/A
2023168005	12/2022	WO	N/A
2023168097	12/2022	WO	N/A

OTHER PUBLICATIONS

PCT/US2021/059256 filed Nov. 12, 2021 International Search Report and Written Opinion dated Mar. 23, 2022. cited by applicant

Rauchwerger, Jacob Jeffrey, Michael Serle, and Jeffrey C. Astbury. "Novel Wire-Guided Scalpel to Facilitate Central Venous Catheter Insertion without a Skin Bridge." Vascular Specialist International 37 (2021). cited by applicant

PCT/US2021/061857 filed Dec. 3, 2021 International Search Report and Written Opinion dated Apr. 11, 2022. cited by applicant

PCT/US2022/049134 filed Nov. 7, 2022 International Search Report and Written Opinion dated Mar. 30, 2023. cited by applicant

PCT/US2022/053889 filed Dec. 22, 2022 International Search Report and Written Opinion dated Apr. 20, 2023. cited by applicant

PCT/US2023/011067 filed Jan. 18, 2023 International Search Report and Written Opinion dated May 11, 2023. cited by applicant

PCT/US2023/012270 filed Feb. 3, 2023 International Search Report and Written Opinion dated Jun. 21, 2023. cited by applicant

PCT/US2023/012345 filed Feb. 3, 2023 International Search Report and Written Opinion dated Jun. 27, 2023. cited by applicant

PCT/US2023/013056 filed Feb. 14, 2023 International Search Report and Written Opinion dated Jun. 12, 2023. cited by applicant

PCT/US2023/013058 filed Jun. 7, 2023 International Search Report and Written Opinion dated Jun. 7, 2023. cited by applicant

PCT/US2023/014298 filed Mar. 1, 2023 International Search Report and Written Opinion dated Jun. 1, 2023. cited by applicant

PCT/US2023/014384 filed Mar. 2, 2023 International Search Report and Written Opinion dated Jun. 16, 2023. cited by applicant

PCT/US2023/014532 filed Mar. 3, 2023 International Search Report and Written Opinion dated Jul. 10, 2023. cited by applicant

U.S. Appl. No. 17/525,774, filed Nov. 12, 2021 Non-Final Office Action dated Jan. 24, 2024. cited by applicant

U.S. Appl. No. 17/525,774, filed Nov. 12, 2021 Advisory Action dated Aug. 26, 2024. cited by applicant

U.S. Appl. No. 17/525,774, filed Nov. 12, 2021 Final Office Action dated Jun. 18, 2024. cited by applicant

U.S. Appl. No. 17/525,774, filed Nov. 12, 2021 Non-Final Office Action dated Jan. 28, 2025. cited

Primary Examiner: Bouchelle; Laura A

Assistant Examiner: Grasmeder; Sarah Dympna

Attorney, Agent or Firm: Rutan & Tucker LLP

Background/Summary

PRIORITY (1) This application claims the benefit of priority to U.S. Provisional Application No. 63/121,761, filed Dec. 4, 2020, which is incorporated by reference in its entirety into this application.

BACKGROUND

(1) In some catheter placement procedures, dilation of the tissue surrounding an insertion site is a core activity that occurs during catheter placement. Proper dilation of the tissue allows an improved fit of the catheter. Current dilation techniques are done by hand, using a separate hardened component and/or a skin nick to relieve the tension in the skin while dilating the tissue. These techniques require the insertion and removal of various instruments adding complexity, time and increasing the risk of infection. Furthermore, these techniques may lead to undesired tissue deflection and require increased pushing forces resulting in over dilation of the tissue surrounding the insertion site. It would be beneficial to be able to dilate only the tissue necessary for the fit of the catheter and reduce the necessity of the skin nick. Disclosed herein is a system and method of use that address the foregoing.

SUMMARY

(2) Disclosed herein is a distal section of a catheter configured to enter a skin insertion site including a tapered junction including one or more dilation structures configured to dilate the skin insertion site, and a distal portion extending from a distal end of the tapered junction, the distal portion having a diameter smaller than a proximal portion of the catheter.

(3) In some embodiments, the one or more dilation structures includes one or more protrusions or a helix extending from a side wall of the tapered junction.

(4) In some embodiments, the one or more dilation structures extend radially from the side wall of the tapered junction.

(5) In some embodiments, each protrusion includes a proximal edge and a distal edge.

(6) In some embodiments, each protrusion extends longitudinally from the proximal edge to the distal edge.

(7) In some embodiments, each protrusion extends laterally from the side wall to an apex.

(8) In some embodiments, the apex is located between a longitudinal mid-point and one of the proximal edge or the distal edge, including the proximal edge or the distal edge.

(9) In some embodiments, each protrusion defines a proximal face extending between the apex and the proximal edge.

(10) In some embodiments, each protrusion defines a distal face extending between the apex and the distal edge.

(11) In some embodiments, the proximal face defines a cutting edge extending longitudinally through a midline of the proximal face.

(12) In some embodiments, the distal face defines a cutting edge extending longitudinally through a

midline of the distal face.

(13) In some embodiments, the protrusions are longitudinally organized into a first line of two or more protrusions and a second line of two or more protrusions disposed on opposite sides of the tapered junction.

(14) In some embodiments, the proximal face and the distal face of each protrusion coordinate to define a rounded outer profile.

(15) In some embodiments, each protrusion of the first line is longitudinally aligned with each protrusion of the second line.

(16) In some embodiments, each protrusion of the first line is longitudinally offset from each protrusion of the second line.

(17) In some embodiments, the helix includes a right handed helix or a left handed helix.

(18) In some embodiments, the helix includes beveled or chamfered edges.

(19) Also disclosed herein is a method of inserting a catheter including inserting a distal section of a catheter into a skin insertion site, the distal section having a tapered junction including one or more dilation structures configured to dilate the skin insertion site and a distal portion extending from a distal end of the tapered junction, the distal portion having a diameter smaller than a proximal portion of the catheter, dilating the skin insertion site, and advancing the proximal portion of the catheter into the skin insertion site.

(20) In some embodiments, the one or more dilation structures include one or more protrusions or a helix extending from a side wall of the tapered junction.

(21) In some embodiments, each protrusion includes a proximal face and a distal face.

(22) In some embodiments, the proximal face defines a cutting edge extending longitudinally through a midline of the proximal face.

(23) In some embodiments, the distal face defines a cutting edge extending longitudinally through a midline of the distal face.

(24) In some embodiments, dilating the skin insertion site includes using the cutting edge to dilate the insertion site.

(25) In some embodiments, dilating the skin insertion site includes rotating a helical dilation structure about a longitudinal axis to dilate the insertion site.

(26) In some embodiments, wherein the helix includes a right handed helix or left handed helix.

(27) In some embodiments, the helix includes beveled or chamfered edges.

(28) In some embodiments, dilating the skin insertion site includes using the beveled or chamfered edges to dilate the insertion site.

(29) In some embodiments, dilating the skin insertion site includes twisting the distal section of the catheter around a longitudinal axis, clockwise or counterclockwise.

(30) In some embodiments, dilating the skin insertion site includes wiggling the distal section of the catheter about a transverse or lateral axis.

(31) These and other features of the concepts provided herein will become more apparent to those of skill in the art in view of the accompanying drawings and following description, which describe particular embodiments of such concepts in greater detail.

Description

DRAWINGS

(1) A more particular description of the present disclosure will be rendered by reference to specific embodiments thereof that are illustrated in the appended drawings. It is appreciated that these drawings depict only typical embodiments of the invention and are therefore not to be considered limiting of its scope. Example embodiments of the invention will be described and explained with additional specificity and detail through the use of the accompanying drawings in which:

(2) FIG. 1 illustrates a plan view of a catheter insertion system, in accordance with some embodiments.

(3) FIG. 2 illustrates a perspective view of components of a catheter insertion system including a tapered junction, in accordance with some embodiments.

(4) FIG. 3A illustrates a schematic view of an exemplary dilation structure, in accordance with some embodiments.

(5) FIGS. 3B-3I illustrates perspective views of various embodiments of the one or more dilation structures, in accordance with some embodiments.

(6) FIGS. 4A-4D illustrate cross sectional views of various embodiments of the dilation structures, in accordance with some embodiments.

(7) FIGS. 5A-5C illustrate an exemplary method of inserting a catheter into an insertion site, in accordance with some embodiments.

(8) FIG. 6 illustrates a flow chart of an exemplary method of inserting a catheter, in accordance with some embodiments.

DESCRIPTION

(9) Before some particular embodiments are disclosed in greater detail, it should be understood that the particular embodiments disclosed herein do not limit the scope of the concepts provided herein. It should also be understood that a particular embodiment disclosed herein can have features that can be readily separated from the particular embodiment and optionally combined with or substituted for features of any of a number of other embodiments disclosed herein.

(10) Regarding terms used herein, it should also be understood the terms are for the purpose of describing some particular embodiments, and the terms do not limit the scope of the concepts provided herein. Ordinal numbers (e.g., first, second, third, etc.) are generally used to distinguish or identify different features or steps in a group of features or steps, and do not supply a serial or numerical limitation. For example, “first,” “second,” and “third” features or steps need not necessarily appear in that order, and the particular embodiments including such features or steps need not necessarily be limited to the three features or steps. Labels such as “left,” “right,” “top,” “bottom,” “front,” “back,” and the like are used for convenience and are not intended to imply, for example, any particular fixed location, orientation, or direction. Instead, such labels are used to reflect, for example, relative location, orientation, or directions. Singular forms of “a,” “an,” and “the” include plural references unless the context clearly dictates otherwise.

(11) With respect to “proximal,” a “proximal portion” or a “proximal-end portion” of, for example, a catheter disclosed herein includes a portion of the catheter intended to be near a clinician when the catheter is used on a patient. Likewise, a “proximal length” of, for example, the catheter includes a length of the catheter intended to be near the clinician when the catheter is used on the patient. A “proximal end” of, for example, the catheter includes an end of the catheter intended to be near the clinician when the catheter is used on the patient. The proximal portion, the proximal-end portion, or the proximal length of the catheter can include the proximal end of the catheter; however, the proximal portion, the proximal-end portion, or the proximal length of the catheter need not include the proximal end of the catheter. That is, unless context suggests otherwise, the proximal portion, the proximal-end portion, or the proximal length of the catheter is not a terminal portion or terminal length of the catheter.

(12) With respect to “distal,” a “distal portion” or a “distal-end portion” of, for example, a catheter disclosed herein includes a portion of the catheter intended to be near or in a patient when the catheter is used on the patient. Likewise, a “distal length” of, for example, the catheter includes a length of the catheter intended to be near or in the patient when the catheter is used on the patient. A “distal end” of, for example, the catheter includes an end of the catheter intended to be near or in the patient when the catheter is used on the patient. The distal portion, the distal-end portion, or the distal length of the catheter can include the distal end of the catheter; however, the distal portion, the distal-end portion, or the distal length of the catheter need not include the distal end of the

catheter. That is, unless context suggests otherwise, the distal portion, the distal-end portion, or the distal length of the catheter is not a terminal portion or terminal length of the catheter.

(13) Unless defined otherwise, all technical and scientific terms used herein have the same meaning as commonly understood by those of ordinary skill in the art.

(14) FIG. 1 illustrates a plan view of a catheter insertion system **100**, in accordance with some embodiments. In some embodiments, the catheter insertion system **100** includes a catheter **110** having a hub **112** disposed at a proximal end and including one or more extension legs **114** extending proximally from the proximal end of the hub **112**. In some embodiments, the catheter **110** includes a catheter tube **116** distally extending from the distal end of the hub **112**. In some embodiments, the catheter tube **116** may be configured to slide over a guidewire **102**. The catheter tube **116** includes a proximal end **119** and a distal section **121** terminating in a distal tip **118** and can define one or more catheter lumens **120** therein. In some embodiments, the catheter **110** may include a Rapid Insertion Central Catheter (“RICC”), such as described, for example, in U.S. Pat. Nos. 10,376,675; 11,517,719; U.S. Publication No. 2021/0069471; U.S. Publication No. 2021/0113809; U.S. Publication No. 2021/0113810; and U.S. Publication No. 2021/0121661, each of which is incorporated by reference in its entirety into this application. As used herein, the catheter insertion system **100** can be used to place a RICC to access the vasculature of a patient. However, it will be appreciated that embodiments disclosed herein can be used to place various catheters, cannulas, single lumen catheters, multi-lumen catheters, intravenous (IV) catheters, peripheral intravenous line (PIV) catheters, peripherally inserted central catheters (PICC), central venous catheter (CVC), dialysis catheters, drainage catheters, and the like, without limitation.

(15) Placing a catheter **110** requires dilating the tissue surrounding an insertion site since typically the insertion site is smaller than the diameter of the catheter **110**. Current dilation techniques use a hardened component that can cause tissue deflection and excessive stretching of the skin tissue as the hardened component is forced through the insertion site. The less movement of the insertion site and the less tissue dilated around the insertion site can lead to a more accurate placement of the catheter **110** within the body and a better fit of the catheter **110** within the insertion site.

(16) In some embodiments, a cross-sectional shape of the catheter tube **116** may be cylindrical, a triangular prism, a rectangular prism, or the like, although other cross-sectional shapes are also contemplated. In some embodiments, the catheter tube **116** may be configured to have a tapered junction **122** between the proximal end **119** of the catheter tube **116** and the distal section **121** of the catheter tube **116**. In some embodiments, the tapered junction **122** may be configured to include one or more dilation structures **123** extending from a side wall **124** of the tapered junction **122** that will be described in more detail herein.

(17) FIG. 2 illustrates a perspective view of components of a catheter insertion system **100** including the tapered junction **122**, in accordance with some embodiments. In some embodiments, the catheter tube **116** includes a proximal portion **125**, the tapered junction **122** having the side wall **124** and a distal portion **127** distal the tapered junction **122**. In some embodiments, the catheter tube **116** defines a central longitudinal axis **117**. The proximal portion **125** has a second diameter **126** and the distal portion **127** has a first diameter **128**. In some embodiments, the second diameter **126** is larger than the first diameter **128**. The tapered junction **122** is a portion of the catheter tube **116** that is tapered from the proximal portion **125** to the distal portion **127** and from the second diameter **126** to the first diameter **128**. In some embodiments, the tapered junction **122** may be evenly tapered, or unevenly tapered from the proximal portion **125** to the distal portion **127**. In some embodiments, the first diameter **128** and the second diameter **126** may be associated with the French catheter scale. In some embodiments, the tapered junction **122** may be configured to include one or more dilation structures **123** that may be configured to have a specific shape to dilate the tissue surrounding an insertion site that will be described in more detail herein.

(18) FIG. 3A illustrates a schematic view of an exemplary dilation structure, in accordance with some embodiments. In some embodiments, the one or more dilation structures **123** may be

configured to include structures that extend from the tapered junction **122** that dilate tissues upon insertion of the catheter **110** into an insertion site. In some embodiments, the one or more dilation structures **123** include a protrusion **130** extending from the side wall **124**. In some embodiments, the one or more dilation structures extend radially from the side wall **124** or longitudinally from a proximal edge **135** to a distal edge **137**. In some embodiments, the protrusion **130** may be configured to extend from the side wall **124** to an apex **132**. In some embodiments, the apex **132** defines the furthest point of the protrusion **130** from the side wall **124**. In some embodiments, the protrusion **130** further defines a proximal face **134**, extending laterally between the apex **132** and the proximal edge **135** and a distal face **136** extending between the apex **132** and the distal edge **137**. In some embodiments, the protrusion **130** includes a length **138** and a width **140**. In some embodiments, as illustrated in FIGS. 3C-3D, the length **138** may remain the same while the apex **132** may be disposed anywhere along the length **138** including a longitudinal mid-point, towards and including the proximal edge **135** or the distal edge **137**.

(19) In some embodiments, the one or more dilation structures **123** may include one or more protrusions **130** or helices **160** that will be described in more detail herein. FIGS. 3B-3I illustrate perspective views of various embodiments of the protrusions **130** or helices **160**, in accordance with some embodiments. As will be appreciated, the protrusions **130** can extend radially from the side wall **124**. In some embodiments, the one or more protrusions **130** can extend from the side wall **124** at a same distance or at a different distance from the side wall **124** of the tapered junction **122**, as will be described in more detail herein. In some embodiments, as illustrated in FIGS. 3B-3C, the protrusion **130** can include various geometries. For example, as illustrated in FIG. 3B, the proximal face **134A** or distal face **136A** can define a cutting edge extending longitudinally through a midline **139** of the proximal face **134A** or the distal face **136A**. In some embodiments, the cutting edge may be configured to assist the user with dilating the tissue around the insertion site and avoid tissue deflection. As illustrated in FIG. 3D, the tapered junction **122** can include a plurality of protrusions **130A-C**, defining the longitudinally rounded distal face **136**, the midline **139** and the longitudinally rounded proximal face **134**. An apex **132A** of a first protrusion **130A** can be longitudinally offset from an apex **132B** of a second protrusion **130B**.

(20) FIG. 3E illustrates a perspective view of the one or more protrusions **130** wherein the one or more protrusions **130** include a plurality of ribs **150**, wherein the plurality of ribs **150** are repeated rounded protrusions. In some embodiments, each rib of the plurality of ribs **150** includes a rib face **155** extending from a proximal edge **156** to a distal edge **157**, a rib length **158** extending from the proximal edge **156** to the distal edge **157**, and a rib width **159**. In some embodiments, the rib face **155** defines the rounded outer profile of the protrusion **130**. In some embodiments, the rib length **158** of the plurality of ribs **150** may be the same or varied. In some embodiments, the rib width **159** of the plurality of ribs **150** may be the same or varied. In an embodiment, the rib width **159** tapers from a larger rib width **159** proximally to a smaller rib width **159** distally.

(21) In some embodiments, the plurality of ribs **150** may be randomly distributed or evenly distributed on the side wall **124** of the tapered junction **122**. In some embodiments, the plurality of ribs **150** may be longitudinally organized into a first line **152** of two or more ribs and a second line **154** of two or more ribs. In an embodiment, each rib in the first line **152** may be longitudinally aligned with each rib in the second line **154**. In an embodiment as illustrated in FIG. 3E, each rib in the first line **152** may be longitudinally offset from each rib in the second line **154**. Each rib in the first line **152** may be evenly spaced or unevenly spaced from the other ribs in the first line **152** and each rib in the second line may be evenly spaced or unevenly spaced from the other ribs in the second line. The first line **152** and the second line **154** can be disposed on opposite sides of the tapered junction **122**. In some embodiments, the first line **152** may be aligned along a lateral side and the second line **154** may be aligned along a transverse side, or at an angle therebetween.

(22) In an embodiment, the first line of ribs **152** can be arranged in a helical pattern about the longitudinal axis **117**, where each rib of the first line of ribs **152** are rotationally offset by an angle

about the longitudinal axis **117** and longitudinally offset by a distance. In an embodiment, each rib of the first line of ribs **152** can be rotationally offset by the same angle or by different angles. In an embodiment, each rib of the first line of ribs **152** can be longitudinally offset by the same distance or different distances.

(23) FIGS. **3F-3I** illustrates a perspective view of the one or more dilation structures **123** wherein the dilation structure **123** includes the helix **160** extending radially about longitudinal axis **117** from the side wall **124**. In some embodiments, the helix **160** may be a right handed helix or a left handed helix. In some embodiments, as illustrated in FIG. **3F**, the helix **160** may have a longitudinal length **161**. In some embodiments, e.g. FIG. **3F**, the dilation structure **123** can include a relatively high number of revolutions per longitudinal length **161**, providing a relatively “tighter” helical structure. In some embodiments, e.g. FIG. **3G**, the dilation structure **123** can include a relatively low number of revolutions per longitudinal length **161**, providing a relatively “looser” helical structure.

(24) In some embodiments, each revolution of the helix **160** may extend radially the same distance from the side wall **124**, as illustrated in FIG. **3G**, or each revolution may extend different distances from the side wall **124**. For example, as illustrated in FIG. **3H**, the helix **160** may extend a greater distance from the side wall **124** at a proximal end and may extend a lesser distance from the side wall **124** at a distal end. Advantageously, by rotating the tapered junction **122**, including the helical dilation structure **123**, the mechanical action of the helix **160** pulls the tapered junction **122** through the insertion site **104**, avoiding tissue deflection or distortion. In some embodiments, as illustrated in FIG. **3I**, the helix **160** may be configured to have beveled, chamfered, squared or rounded edges. The beveled or chamfered edges may be configured to partially cut or fully cut the tissue surrounding the insertion site **104** as the helix **160** is rotated, further dilating the tissue. Although FIGS. **3A-3I** illustrate various embodiments of the one or more dilation structures **123** of the tapered junction **122**, other shapes or protrusions are considered.

(25) FIGS. **4A-4D** illustrate cross sections of the one or more dilation structures **123** including the one or more protrusions **130** of the tapered junction **122**, in accordance with some embodiments. In some embodiments, the catheter tube **116** includes the one or more lumens **120** extending therethrough. In some embodiments, the protrusions **130** include a height **141**. As used herein, the “height” of the protrusion **130** is a distance of an outer most point of the protrusion **130** extending radially from the side wall **124**. In some embodiments, the protrusion **130** defines a width **140**. As used herein a “width” is a distance extending parallel to the side wall **124**. In some embodiments, the protrusions **130** may have the same width **140** and the same height **141** or different widths **140** and different heights **141**.

(26) As illustrated in FIG. **4A**, the tapered junction **122** may include four protrusions **130A-D** extending radially from the side wall **124** of the tapered junction **122**. In some embodiments, a first ridge **130A** may be equidistant from a second ridge **130B** and a fourth ridge **130D**. In some embodiments, the fourth ridge **130D** may be equidistant from the first ridge **130A** and a third ridge **130C**. Simply put, the four protrusions **130A-D** may be evenly spaced radially around the tapered junction **122**. As illustrated in FIG. **4B**, in some embodiments, the tapered junction **122** may include eight ridges **130A-H** extending from the side wall **124** of the tapered junction **122**. In some embodiments, the eight ridges **132A-H** may be even spaced, unevenly spaced or clustered together around the tapered junction **122**. Although eight ridges are illustrated, greater or lesser number of ridges are also contemplated.

(27) As illustrated in FIG. **4C**, in some embodiments, the tapered junction **122** may include two protrusions **130A**, **130B** extending from the side wall **124** of the catheter tube **116**. In some embodiments, the first protrusion **130A** and the second protrusion **130B** define a lateral axis **129**. In some embodiments, the first protrusion **130A** may be longitudinally aligned with the second protrusion **130B**, defining a lateral axis **129** on opposite sides of the tapered junction **122**. In some embodiments, the first protrusion **130A** may be longitudinally offset from the second protrusion **130B**. In some embodiments, the one or more protrusions **130** may include the plurality of ribs **150**.

In some embodiments, the plurality of ribs **150** may be organized in the first line **152** and the second line **154**. As illustrated in FIG. **4D**, in some embodiments, the first line **152** may longitudinally aligned with the second line **154**, on opposite sides of the catheter tube **116**. In some embodiments, the first line **152** may be longitudinally offset from the second line **154**. In some embodiments, the plurality of ribs **150** may radially extend evenly or unevenly from the side wall **124** to define different distances from the side wall **124** of the tapered junction **122**. In some embodiments, the plurality of ribs **150** located proximally may radially extend a greater distance from the side wall **124** than the ribs located distally. In some embodiments, the plurality of ribs **150** may be organized into a plurality of lines, evenly spaced around the tapered junction **122**. In some embodiments, the plurality of ribs **150** may be spaced in an organized configuration or a random configuration around the catheter tube **116**. In some embodiments the plurality of ribs may be arranged in a helical line about the longitudinal axis **117**.

(28) FIGS. **5A-5C** illustrate an exemplary method of using inserting a catheter **110** into an insertion site **104**. In some embodiments, the catheter insertion system **100** includes a guidewire **102**. As illustrated in FIG. **5A**, the guidewire **102** may be inserted into an insertion site **104** in a target area **106**. In some embodiments, the target area **106** may include a target vessel. In some embodiments, a user may confirm the guidewire **102** is in the correct target location. In some embodiments, as illustrated in FIG. **5B**, the catheter insertion system **100** further includes the catheter **110** having the hub **112** disposed at a proximal end and including one or more extension legs **114** extending proximally from the proximal end of the hub **112**. The catheter **110** includes the catheter tube **116** distally extending from the distal end of the hub **112**. The catheter tube **116** may be configured to slide over the guidewire **102**. The catheter tube **116** includes the proximal end **119** and a distal section **121**, terminating in the distal tip **118** and can define the one or more catheter lumens **120** therein. The catheter tube **116** further includes the proximal portion **125**, the tapered junction **122** having the side wall **124** and the distal portion **127**. The proximal portion **125** has the second diameter **126** and the distal portion **127** has the first diameter **128** with the second diameter **126** being larger than the first diameter **128**. The tapered junction **122** may be configured to include one or more dilation structures **123** radially extending from the side wall **124** and configured to have a specific shape to dilate the tissue surrounding the skin insertion site **104** while mitigating tissue deflection. The dilation structures **123** can include one or more protrusions **130** or helices **160**.

(29) Once the guidewire **102** is placed at the correct target location, the catheter **110** may be slid over the guidewire **102** and urged into the skin insertion site **104** as illustrated in FIG. **5B**. Since the distal portion **127** defines a smaller first diameter **128**, the distal portion **127** can enter the skin insertion site **104** more easily. The tapered junction **122** including the one or more dilation structures **123** can then dilate the skin insertion site **104** for the larger second diameter **126** and the proximal portion **125**. As the catheter **110** is urged into the skin insertion site **104**, the one or more dilation structures **123** facilitates dilating the tissue around the skin insertion site **104** by stretching the tissue around the skin insertion site **104** along a lateral axis. For example, a rotating helix **160** may be configured to use mechanical advantage to pull the tapered junction **122** through the skin insertion site **104**, minimizing tissue deflection. In some embodiments, the user may further twist the catheter **110** clockwise or counterclockwise about the longitudinal axis **117** while urging the catheter **110** into the skin insertion site **104** to further dilate the tissue surrounding the insertion site **104**.

(30) In some embodiments, the user may “wiggle” the catheter **110** back and forth along the lateral axis, transverse axis or a combination thereof, while urging the catheter **110** into the insertion site **104** to further dilate the tissue surrounding the insertion site **104**. In some embodiments, e.g. FIG. **3D**, the user may wiggle the catheter **110** back and forth along the lateral or a transverse axis. In some embodiments, e.g. FIGS. **3E-3I**, the user may wiggle and twist the catheter **110** while urging the catheter **110** into the insertion site **104**. In some embodiments, the user may continue to wiggle or twist the catheter **110** until the catheter **110** is completely inserted into the insertion site **104**, as

illustrated in FIG. 5C. Once the catheter **110** is fully inserted, the user may confirm proper target location placement of the catheter **110** through imaging. In some embodiments, using the catheter **110** to dilate the insertion site **104** leads to an increased fit of the catheter **110** into the insertion site **104**, while minimizing tissue deflection around the insertion site **104**.

(31) FIG. 6 illustrates a flow chart of an exemplary method **300** of inserting a catheter **110** into an insertion site **104** using a catheter insertion system **100**, in accordance with some embodiments. In some embodiments, the method **300** includes inserting a distal section **121** of the catheter **110** into the insertion site **104** (block **302**). In some embodiments, the distal section **121** includes the tapered junction **122** having one or more dilation structures **123** radially extending from the side wall **124** and a distal portion **127** extending from the distal end of the tapered junction, having the first diameter **128**.

(32) The method **300** includes dilating the skin insertion site **104**(block **304**). In some embodiments, dilating the insertion site **104** includes dilating from the smaller first diameter **128** to the larger second diameter **126**. In some embodiments, dilating the skin insertion site **104** includes urging the tapered junction **122** of the catheter **110** into the skin insertion site **104**, the tapered junction **122** includes the one or more dilation structures **123** radially extending from the side wall **124**. In some embodiments, the one or more dilation structures **123** include the one or more protrusions **130** or the helix **160**. In some embodiments, dilating the insertion site **104** includes twisting the catheter **110** clockwise or counterclockwise around the central longitudinal axis **117**. In some embodiments, dilating the insertion site **104** includes wiggling the catheter **110** along the transverse or lateral axis.

(33) The method **300** further includes advancing the proximal portion **125** of the catheter **110** into the insertion site **104** (block **306**). In some embodiments, the proximal portion **125** includes the second diameter **126**. In some embodiments, the second diameter **126** is greater than the first diameter **128**.

(34) While some particular embodiments have been disclosed herein, and while the particular embodiments have been disclosed in some detail, it is not the intention for the particular embodiments to limit the scope of the concepts provided herein. Additional adaptations and/or modifications can appear to those of ordinary skill in the art, and, in broader aspects, these adaptations and/or modifications are encompassed as well. Accordingly, departures may be made from the particular embodiments disclosed herein without departing from the scope of the concepts provided herein.

Claims

1. A catheter configured to enter a skin insertion site, comprising: a hub disposed proximally and including one or more extension legs extending proximally therefrom; a catheter tube extending distally from the hub and defining a first catheter lumen and a second catheter lumen, each of which are in fluid communication with an extension leg of the one or more extension legs; a tapered junction coupled to a distal end of the catheter tube and including a dilation structure configured to dilate the skin insertion site, the dilation structure comprising: a first protrusion extending along a longitudinal axis between a first distal edge and a first proximal edge and extending along a lateral axis to a first apex, the first apex disposed proximate a first mid-point between the first distal edge and the first proximal edge, the first protrusion including a first cutting edge; and a second protrusion extending along the longitudinal axis between a second distal edge and a second proximal edge and extending along the lateral axis to a second apex, the second apex disposed proximate a second mid-point between the second distal edge and the second proximal edge, the second protrusion including a second cutting edge; and a distal portion extending from a distal end of the tapered junction, the distal portion having a diameter smaller than a diameter of a proximal portion of the catheter tube and defining a distal part of the first catheter lumen, the

- second catheter lumen terminating at an aperture disposed in a side wall and disposed adjacent the distal end of the catheter tube.
2. The catheter according to claim 1, wherein an outermost lateral diameter extending between the first apex and the second apex, is greater than, the diameter of the catheter tube.
 3. The catheter according to claim 2, wherein an outermost transverse diameter of the dilation structure, extending perpendicular to the lateral axis is less than the diameter of the catheter tube.
 4. The catheter according to claim 1, wherein the first protrusion defines a first proximal face extending between the first apex and the first proximal edge, and the second protrusion defines a second proximal face extending between the second apex and the second proximal edge.
 5. The catheter according to claim 4, wherein the first protrusion defines a first distal face extending between the first apex and the first distal edge, and the second protrusion defines a second distal face extending between the second apex and the second distal edge.
 6. The catheter according to claim 4, wherein the first proximal face defines the first cutting edge extending longitudinally through a first midline of the first proximal face, and the second proximal face defines the second cutting edge extending longitudinally through a second midline of the second proximal face.
 7. The catheter according to claim 5, wherein the first distal face defines the first cutting edge extending longitudinally through a first midline of the first distal face, and the second distal face defines the second cutting edge extending longitudinally through a second midline of the second distal face.
 8. The catheter according to claim 1, wherein the tapered junction, the distal portion and the distal end of the catheter tube are configured to be placed subcutaneously through the skin insertion site.
-