

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12403499
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Enderle; Gerrit et al.

Apparatus for conveying viscous material

Abstract

An apparatus for conveying viscous material from a container having a base and an upwardly-extending shell includes: a follower plate movable towards and away from the base adjacent to the shell inner surface facing the interior and having an outlet and at least one deaeration and/or aeration opening; a deaerator for sucking air through the deaeration opening(s) and/or an aerator for introducing compressed air through the aeration opening(s); a lifting/lowering device for lifting/lowering the plate; a control for alternately controlling the lifting/lowering device in a movement mode and the deaerator or aerator in a deaeration or aeration mode, the lifting/lowering device having at least one vertical holding rod connected to a plate upper side, the plate being vertically movable in a limited manner relative to the rod; and a sensor for detecting and transmitting to the control upper and lower end plate positions relative to the rod.

Inventors:	Enderle; Gerrit (Knittlingen, DE), Hausner; Thomas (Bretten, DE), Knopf; Marco (Malschenberg, DE)
Applicant:	Atlas Copco IAS GmbH (Bretten, DE)
Family ID:	79686426
Assignee:	Atlas Copco IAS GmbH (Bretten, DE)
Appl. No.:	18/013080
Filed (or PCT Filed):	July 19, 2021
PCT No.:	PCT/EP2021/070111
PCT Pub. No.:	WO2022/028869
PCT Pub. Date:	February 10, 2022

Prior Publication Data

Document Identifier	Publication Date
----------------------------	-------------------------

Foreign Application Priority Data

DE	10 2020 120 748.4	Aug. 06, 2020
DE	10 2020 120 815.4	Aug. 06, 2020
DE	10 2020 127 440.8	Oct. 19, 2020

Publication Classification

Int. Cl.: B05C5/02 (20060101)

U.S. Cl.:

CPC B05C5/0225 (20130101);

Field of Classification Search

CPC: B05C (5/0225); F04B (15/02); F04B (23/028); B67D (7/645)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5957338	12/1998	Lehmann	N/A	N/A
9695034	12/2016	Sauer	N/A	N/A
11480164	12/2021	Mori et al.	N/A	N/A
2008/0023082	12/2007	Schucker	N/A	N/A
2008/0257915	12/2007	Wold	222/389	A61M 11/007
2013/0256062	12/2012	Kotyk et al.	N/A	N/A
2015/0375185	12/2014	Waizenauer et al.	N/A	N/A
2016/0016786	12/2015	Sauer	N/A	N/A
2016/0067735	12/2015	Bourbeau	222/173	B05B 7/26
2018/0193871	12/2017	Scholl	N/A	B05C 5/0225
2019/0184615	12/2018	Gerke et al.	N/A	N/A
2020/0063726	12/2019	Enderle et al.	N/A	N/A
2021/0046493	12/2020	Fippl et al.	N/A	N/A
2021/0238024	12/2020	Tasaka	N/A	B67D 7/645
2022/0299017	12/2021	Sinders	N/A	F04B 53/143
2024/0408639	12/2023	Gao	N/A	B05C 11/1034

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
512 536	12/2012	AT	N/A

107921466	12/2017	CN	N/A
110035836	12/2018	CN	N/A
10 2004 030 654	12/2005	DE	N/A
102007003972	12/2007	DE	B67D 7/0227
20 2011 108 222	12/2011	DE	N/A
10 2013 020932	12/2013	DE	N/A
11 2013 001 703	12/2013	DE	N/A
10 2014 011 395	12/2015	DE	N/A
10 2016 108 807	12/2015	DE	N/A
10 2017 000 047	12/2017	DE	N/A
10 2017 215706	12/2018	DE	N/A
10 2018 104 763	12/2018	DE	N/A
0 827 937	12/1997	EP	N/A
2 906 333	12/2016	EP	N/A
3 296 075	12/2017	EP	N/A
3 590 609	12/2019	EP	N/A
2 069 060	12/1980	GB	N/A
2018/192642	12/2017	NO	N/A
2018/054548	12/2017	WO	N/A
2019/166200	12/2018	WO	N/A

OTHER PUBLICATIONS

English translation of DE 10 2007 003972, Specification, Sep. 30, 2024 (Year: 2024). cited by examiner

English translation of DE 10 2004 030 645, Specification, Sep. 30, 2024 (Year: 2024). cited by examiner

Machine Translation of DE-102007003972-A1 (Year: N/A). cited by examiner

International Search Report in PCT/EP2021/070111, mailed Nov. 8, 2021. cited by applicant

English translation of the International Preliminary Report on Patentability and Written Opinion of the International Searching Authority in PCT/EP2021/070111, mailed Feb. 16, 2023. cited by applicant

European Office Action dated Nov. 10, 2023 in European Application No. 21 745 819.9, with English translation of relevant parts. cited by applicant

German Search Report in DE 10 2020 127 440.8, dated May 17, 2021, with English translation of relevant parts. cited by applicant

Chinese Office Action in Chinese Application No. 202180056991.3 dated Apr. 30, 2025 with English translation. cited by applicant

Primary Examiner: Carroll; Jeremy

Attorney, Agent or Firm: Collard & Roe, P.C.

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS

(1) This application is the National Stage of PCT/EP2021/070111 filed on Jul. 19, 2021, which claims priority under 35 U.S.C. § 119 of German Application Nos. 10 2020 120 748.4 filed on Aug.

6, 2020; 10 2020 120 815.4 filed on Aug. 6, 2020; and 10 2020 127 440.8 filed on Oct. 19, 2020, the disclosures of which are incorporated by reference. The international application under PCT article 21 (2) was not published in English.

(2) The invention relates to an apparatus for conveying viscous material out of a barrel-like container.

(3) Such apparatuses are used, for example, for applying adhesives, sealants, insulation materials or heat-conductive pastes onto workpieces, in particular onto car body parts in the production of motor vehicles. In this regard, the viscous material is conveyed out of the container by way of a material outlet opening, by means of a pump, wherein a follower plate that has the material outlet opening is constantly held in contact with a surface of the material in the container by means of a lifting and lowering device, and follows the decreasing material level in the container by being lowered by means of the lifting and lowering device. The follower plate is sealed off relative to the container mantle, so that on the one hand, no material can penetrate out of the container, and on the other hand, air from the surroundings cannot penetrate into the container. Once the container has been emptied, it is replaced with a new, full container, wherein first the follower plate is moved upward out of the emptied container, so that then it can be introduced into the full container that has been positioned below it, in the meantime, until it rests on the viscous material and the conveying process can begin. During introduction of the follower plate into the full container, however, it is unavoidable that air is enclosed between the follower plate and the viscous material, which air must be removed before the viscous material is pumped out of the container.

Furthermore, the follower plate lies against the inner surface of the container mantle that faces the container interior, with a seal around its circumference, so that a force must be exerted when it is lowered onto the surface of the viscous material. During manual introduction of a follower plate into a full container, pumping off the air situated in the container interior and lowering the follower plate onto the material surface requires great skill of the operator. It is furthermore known (cf. DE 10 2017 000 047 A1) to pump off material before starting to convey the viscous material and to reject it as waste until the conveyed material no longer has any air inclusions. However, this practice is particularly disadvantageous if the viscous material is very expensive.

(4) It is therefore the task of the invention to develop an apparatus of the type stated initially, which allows automated introduction of the follower plate into the container and/or automated removal of the follower plate from the container.

(5) This task is accomplished by means of an apparatus having the characteristics of claim 1. Advantageous further developments of the invention are the object of the dependent claims.

(6) The invention is based on the idea of alternately switching between a movement mode, in which the holding rod or the holding rods is/are lowered, in particular driven by a motor, and a de-aeration mode, in that air is drawn off from the container interior by means of the deaeration device, through the de-aeration opening(s). For this purpose, the follower plate is mounted to float with reference to the lifting and lowering device, and can be moved vertically, within limits, relative to this device. In this regard, it is possible that the floating mounting is arranged between the follower plate and the at least one holding rod so that the follower plate can be moved vertically, within limits, relative to the at least one holding rod, or that it is arranged between the at least one holding rod and a vertically movable support element of the lifting and lowering device that carries the holding rod(s), so that it can be moved vertically, within limits, with reference to the support element, so that the follower plate is drawn further into the container interior by means of the production of a partial vacuum in the container interior, and the at least one holding rod or the support element remains in its position, so that subsequently, when pumping off the air has been completed, it is moved to the correct position. These steps are alternately repeated until the follower plate is resting on the viscous material. Vice versa, during removal of a follower plate from an emptied container, it is possible to alternately switch between the movement mode, in which the at least one holding rod or the support element is lifted, and an aeration mode, in which

compressed air is introduced into the container interior. The excess pressure in the container interior presses the follower plate upward until it has reached the upper end position with reference to the at least one holding rod, whereupon the introduction of compressed air is stopped and the at least one holding rod or the support element is moved upward a certain distance, so as to advance the follower plate.

(7) It is practical if the follower plate is connected with every holding rod, or the at least one holding rod is connected with the support element, by means of at least one bolt guided in an oblong hole that extends vertically. This is a simple but nevertheless reliable structure of the floating mounting of the follower plate on the at least one holding rod, so as to fasten it in place with limited vertical mobility with reference to the at least one holding rod. In this regard, it is preferred that the sensor device has a path measurement device for detecting the position of the follower plate with reference to the at least one holding rod or with reference to the support element. The path measurement device measures the path traveled by the follower plate with reference to the at least one holding rod or with reference to the support element, and thereby can determine the position of the follower plate with reference to the at least one holding rod or with reference to the support element, and also can determine when the upper and lower end positions have been reached, with great precision. However, it is also possible that the sensor device has at least one first sensor for detecting the bolt or one of the bolts when the upper end position is reached by the follower plate, and at least one second sensor for detecting the bolt or one of the bolts when the lower end position is reached by the follower plate. The sensors are preferably proximity switches. They turn on when the bolt or one of the bolts reaches either the lower or the upper end position.

(8) It is possible that the at least one bolt is firmly connected with the follower plate and is guided in an oblong hole, in particular one that runs vertically, which hole also extends over the at least one holding rod or a component firmly connected with the latter. However, it is preferred that each holding rod, with its lower end, is held in a sleeve fixed in place on the top side of the follower plate, and that at least one bolt that is guided in an oblong hole of the sleeve projects radially away from the holding rod. The sleeve can be screwed onto the follower plate, for example. It is also possible and advantageous, in particular for smaller apparatuses, that every holding rod is held, with its upper end, in a sleeve that is fixed in place on a vertically movable component of the lifting and lowering device, in particular on the underside of a traverse. In this case, too, at least one bolt projects radially away from the at least one holding rod, which bolt is guided in an oblong hole of the sleeve. Furthermore, it is preferred that at least two bolts project radially away from each holding rod, at equal angular distances from one another, which bolts are each guided in an oblong hole of the related sleeve. In particular, two bolts can project radially away from each holding rod in opposite directions. This measure produces a symmetry that reduces stress on the bolts caused by torques that occur. Furthermore, it is preferred that the lifting and lowering device has multiple holding rods, which are preferably arranged concentrically and at equal distances from one another, around a center point of the follower plate. In other words, the holding rods run at equal distances from a center longitudinal axis of the follower plate, which is essentially structured to be cylindrical. In particular, two holding rods can be provided, which lie diametrically opposite one another with reference to the center point or the center axis.

(9) In order to recognize when the container has been emptied, the follower plate can have a sensor for detecting when the plate sits on the container bottom. This sensor has a pin that projects out of the underside of the follower plate and can move into the follower plate counter to a reset force. The pin triggers the sensor signal when the follower plate sits on the container bottom with its full weight and the pin is pressed into the follower plate.

(10) At least one aeration opening and at least one de-aeration opening arranged at a distance from the former can be provided. However, it is preferred that the aeration opening(s) and the deaeration opening(s) coincide, so that at least one opening is present in the follower plate for the introduction

and withdrawal of air. The deaeration device can be a compressor or a Venturi tube, for example. It is also possible to configure the deaeration device in such a manner that it can be operated in the opposite direction and introduces compressed air into the container interior. However, it is also possible to supply the compressed air by way of a separate compressed air line.

(11) In order to prevent viscous material from being drawn in from the container interior when air is drawn away, a cover layer composed of a material that is permeable for air and impermeable for liquid is arranged on the underside of the follower plate, according to a preferred exemplary embodiment, which layer covers the deaeration opening(s) and/or the aeration opening(s) and leaves the material outlet opening free. The cover layer can be adapted to the viscous material. It does not have to be impermeable for every liquid, but rather only for the viscous material in question, which is supposed to be conveyed out of the container. In particular, the cover layer can consist of a foldable material, for example of a thin felt layer or a commercially available weed control fabric. In order to facilitate laying the cover layer onto the material surface below the follower plate, the cover layer can be connected with a rigid ring on its circumferential edge. However, it is also possible that the cover layer is connected with a ring composed of elastically stretchable material on its circumferential edge. The latter configuration can also be implemented independent of the floating mounting of the follower plate on the at least one holding rod with limited vertical mobility of the follower plate with reference to the at least one holding rod or with reference to the support element. The cover layer preferably consists of polypropylene (PP), in particular of thermally bonded endless filaments. In this regard, a polypropylene layer that has a weight according to DIN EN 29073 T.1 of $60 \text{ g/m}^2 \pm 10\%$ is preferred, which has a maximum tensile strength according to DIN EN 29073 T.2 lengthwise of 130 N/5 cm and crosswise of 90 N/5 cm , $\pm 20\%$, in each instance, and an elongation of DIN 29073 T.3 lengthwise of 88% and crosswise of 87% , $\pm 20\%$, in each instance. Such a material is sold, for example, by the company p. glatzeder gmbh under the name PP spun-bonded 60 g/m^2 —LA. Other weights per surface area are also possible. During introduction of the follower plate, air is drawn off from the container interior through the cover layer, while the viscous material is retained in the container, so that the scrap rate of material is reduced. Before introducing the follower plate into the container, the elastically stretchable ring can be stretched and pulled over the circumferential edge of the container mantle, so that it is arranged circumferentially around the container mantle on an outer side facing away from the container interior. When the follower plate is introduced into the container, it impacts the cover layer, so that the ring is pulled off the container mantle and lays itself around an outer mantle surface of the follower plate. The ring can then form an additional seal between the follower plate and the container mantle. When the container has been emptied and the follower plate has been removed from it, the cover layer, together with the ring, can be pulled off the follower plate and thrown away. A new cover layer is then fastened onto the container, in that its ring is pulled over the circumferential edge of the container mantle.

Description

(1) In the following, the invention will be explained in greater detail using an exemplary embodiment shown schematically in the drawing. The figures show:

(2) FIG. 1 an apparatus for conveying viscous material, in a side view;

(3) FIG. 2 the apparatus according to FIG. 1 in a top view;

(4) FIG. 3 the lower region of the apparatus according to FIGS. 1, 2, in a section along the line A-A, and

(5) FIG. 4 an enlarged detail from FIG. 3.

(6) The apparatus 10 shown in the drawing serves for conveying viscous material out of a barrel-like container. It has a follower plate 12 that can be lifted and lowered by means of a lifting and

lowering device **14**. The lifting and lowering device **14** has a bottom plate **16** as well as hydraulic cylinders **18** mounted on the bottom plate **16**, the piston rods **20** of which are passed out toward the top and are connected with one another by means of a support element **22** in the form of a traverse. Two holding rods **24** extend downward from the traverse **22**, on which rods the follower plate **12** is suspended.

(7) The follower plate **12** has a material outlet opening **26** in its center, through which opening the viscous material can be conveyed out of the container by means of a chop-check pump **28** when the follower plate **12** lies on the viscous material with its underside. It furthermore has multiple aeration and de-aeration openings **30**, through which air can be pumped out of the container interior and compressed air can be introduced into the container interior. Optionally, a deaeration device or an aeration device, not shown in any detail, can be connected with the aeration and deaeration openings **30**.

(8) The follower plate **12** is connected with the holding rods **24**, not in a rigid manner, but rather mounted to float on them in the sense that it can move vertically, within limits, with reference to the holding rods **24**. For this purpose, two sleeves **34** are screwed onto the top side **32** of the follower plate **12**, which sleeves each hold the lower end of one of the two holding rods **24**. A bolt **36** projects radially away from each of the holding rods, which bolt passes through an oblong hole **38** in the related sleeve **34** that extends in the vertical direction, and is guided in this hole so as to be displaceable in the vertical direction. Toward the outside, the oblong hole **38** is covered by a cover cap **40**, in each instance. With regard to the holding rods **24**, the follower plate **12** can be displaced between an upper end position, shown in FIGS. **3**, **4**, in which the bolts **36** lie against the lower end of the corresponding oblong hole **38**, in each instance, and an upper end position, in which they lie against the upper end of the related oblong hole **38**, in each instance. A sensor device in the form of a path measurement device **42** on each sleeve **24** detects the position of the follower plate **12** with reference to the holding rods **24** and, in particular, when the upper end position has been reached and when the lower end position has been reached by the follower plate **12**. The path measurement device **42** emits signals to a control device, not shown in any detail, when the corresponding end position is reached by the follower plate **12**.

(9) In order to be able to convey viscous material out of a container, the follower plate **12** is lifted off the bottom plate **16** by means of the lifting and lowering device **14**, and the container, which is open toward the top, is set up under the follower plate **12** on the bottom plate **16**. A cover element **50** is then arranged on the container, which is open toward the top, so as to cover it. The cover element **50** has a cover layer **52** that is permeable for air but not for the viscous material. The cover layer **52** is thin and consists of a foldable material such as a commercially available weed control fabric, for example, or a thin felt layer. An elastically stretchable ring **54** runs in a circle around the cover layer **52**, which ring is pulled over the mantle surface of the container, so that it lies against the mantle surface, on the outside, in the stretched state. The follower plate **12** is then lowered, presses down on the cover layer **52**, and thereby pulls the elastic ring **54** off the mantle surface of the container, until it lies against the mantle surface **56** of the follower plate **12**, as shown in FIG. **4**. The cover layer **52** covers the aeration and deaeration opening **30**, but not the material outlet opening **26**. The follower plate **12** is lowered by means of the lifting and lowering device **14**, to such an extent that a wiping ring **58** that runs around its mantle surface **56** makes contact with the inner surface of the container mantle, so that its friction force inhibits further introduction of the follower plate **12**.

(10) Further lowering of the holding rods **24** brings the follower plate **12** into its upper end position, so that the path measurement device **42** is triggered and the control device activates the deaeration device and stops the lifting and lowering device **14**. By means of the partial vacuum that occurs in the container, the follower plate **12** is drawn downward until it reaches its lower end position, so that the path measurement device **42** is triggered, the control device deactivates the de-aeration device and turns on the lifting and lowering device **14**, which lowers the holding rods **24**.

The switch between a movement mode, in which the de-aeration device is deactivated and the lifting and lowering device **14** moves the holding rods **24**, and a de-aeration mode, in which the holding rods **24** are held in a fixed location and air is pumped out of the container interior through the aeration and de-aeration openings **30** by means of the de-aeration device, is continued until the follower plate **12** lies on the viscous material and the air has been pumped out of the container. Then the conveying process begins, during which the chop-check pump **28** pumps the viscous material out of the container. Due to the partial vacuum that occurs in the container, the follower plate **12** follows the material level until it reaches its bottom end position, whereupon once again the control device turns on the lifting and lowering device **14** on the basis of a signal of the path measurement device **42**, so that the holding rods **24** are lowered until the follower plate **12** reaches its upper end position and the path measurement device **42** transmits a corresponding signal to the control device. In order to prevent the container from being lifted off the bottom plate **16** when a partial vacuum prevails in it, at least one hold-down firmly connected with the bottom plate **16** can be provided, which engages into a lower and/or into an upper container edge.

(11) Once the container has been emptied, the follower plate **12** is removed from the container in accordance with the method of procedure during introduction of the follower plate **12** into the container. For this purpose, compressed air is introduced into the aeration and de-aeration opening **30** by means of the aeration device, and thereby the follower plate **12** is lifted up from the container bottom under the effect of pressure. It then gets into its upper end position, the path measurement device **42** is triggered, the control device interrupts the feed of compressed air and activates the lifting and lowering device **14**, which lifts the holding rods **24** until the follower plate **12** has reached its lower end position once again. Then the path measurement device **42** is triggered once again, the lifting and lowering device **14** is stopped, and compressed air is introduced into the container interior again, and so forth, until the follower plate **12** reaches the upper container edge and can be lifted off.

(12) In summary, the following should be stated: The invention, according to an exemplary embodiment, relates to an apparatus **10** for conveying viscous material out of a barrel-like container that has a container bottom and a container mantle that extends upward from the container bottom, having a follower plate **12** that can be moved toward the container bottom and away from the container bottom, lying against the inner surface of the container mantle, which faces the container interior, and that has a material outlet opening **26** and at least one de-aeration opening **30** and/or at least one aeration opening **30**, having a de-aeration device for drawing off air from the container interior through the de-aeration opening(s) **30** and/or having an aeration device for introducing compressed air into the container interior through the aeration opening(s) **30**, having a lifting and lowering device **14** for lifting and lowering the follower plate **12**, having a control device for alternately controlling the lifting and lowering device **14** in a movement mode and the de-aeration device or the aeration device in a de-aeration mode or in an aeration mode, wherein the lifting and lowering device **14** has at least one holding rod **24** that runs vertically, which is connected with a top side **32** of the follower plate **12**, wherein the follower plate **12** can be moved vertically, within limits, with reference to the at least one holding rod **24**, and having a sensor device **42** for detecting at least one upper end position and at least one lower end position of the follower plate **12** with reference to the at least one holding rod **24** and for transmitting the detected positions to the control device.

Claims

1. An apparatus for conveying viscous material out of a barrel-like container that has a container bottom and a container mantle that extends upward from the container bottom, the apparatus comprising: a follower plate that can be moved in the direction toward the container bottom and away from the container bottom, lying against the inner surface of the container mantle, which

faces the container interior, and that has a material outlet opening and at least one de-aeration opening and/or at least one aeration opening, a de-aeration device for drawing off air from the container interior through the de-aeration opening(s) and/or an aeration device for introducing compressed air into the container interior through the aeration opening(s), a lifting and lowering device for lifting and lowering the follower plate, a control device for alternately controlling the lifting and lowering device in a movement mode and the de-aeration device or the aeration device in a de-aeration mode or in an aeration mode, wherein the lifting and lowering device has at least one holding rod that runs vertically, which is connected with a top side of the follower plate and extends downward from a support element that can move in the vertical direction, wherein the follower plate can be moved vertically, within limits, with reference to the at least one holding rod and/or with reference to the support element, and a sensor device for detecting at least one upper end position and at least one lower end position of the follower plate with reference to the at least one holding rod or with reference to the support element and for transmitting the detected positions to the control device.

2. The apparatus according to claim 1, wherein the follower plate is connected with each holding rod or each holding rod is connected with the support element by means of at least one bolt that is guided in an oblong hole that extends vertically.
3. The apparatus according to claim 2, wherein the sensor device has at least one path measurement device for detecting the position of the follower plate with reference to the at least one holding rod or with reference to the support element.
4. The apparatus according to claim 2, wherein the sensor device has at least a first sensor for detecting the bolt or one of the bolts when the follower plate reaches the upper end position and at least a second sensor for detecting the bolt or one of the bolts when the follower plate reaches the lower end position.
5. The apparatus according to claim 4, wherein the sensors are proximity switches.
6. The apparatus according to claim 2, wherein each holding rod is held, with a respective lower end of each holding rod, in a sleeve fixed in place on the top side of the follower plate or, with a respective upper end of each holding rod, in a sleeve fixed in place on the support element, and wherein at least one bolt projects radially away from each holding rod, wherein the at least one bolt is guided in an oblong hole of the sleeve.
7. The apparatus according to claim 6, wherein at least two bolts project radially away from each holding rod, at equal angular distances from one another, which bolts are each guided in an oblong hole of the related sleeve.
8. The apparatus according to claim 1, wherein the lifting and lowering device has multiple holding rods.
9. The apparatus according to claim 1, wherein the follower plate has a sensor for recognizing that the plate sits on the container bottom, which sensor has a pin that projects out of the underside of the follower plate and can move into the follower plate counter to a reset force.
10. The apparatus according to claim 1, wherein the aeration opening(s) and the de-aeration opening(s) coincide.
11. The apparatus according to claim 1, wherein a cover layer composed of a material that is permeable for air and impermeable for liquids, which cover layer covers the de-aeration opening(s) and/or the aeration opening(s) and leaves the material outlet opening free is arranged on the underside of the follower plate.
12. The apparatus according to claim 11, wherein the cover layer comprises a foldable material.
13. The apparatus according to claim 12, wherein the cover layer is connected with a rigid ring on a circumferential edge of the cover layer.
14. The apparatus according to claim 12, wherein the cover layer is connected with a ring composed of elastically stretchable material on a circumferential edge of the cover layer.
15. An apparatus for conveying viscous material out of a barrel-like container that has a container

bottom and a container mantle that extends upward from the container bottom, the apparatus comprising: a follower plate that can be moved in the direction toward the container bottom and away from the container bottom, lying against the inner surface of the container mantle, which faces the container interior, and that has a material outlet opening and at least one deaeration opening and/or at least one aeration opening, a de-aeration device for drawing off air from the container interior through the de-aeration opening(s) and/or an aeration device for introducing compressed air into the container interior through the aeration opening(s), a lifting and lowering device for lifting and lowering the follower plate, and a control device for alternately controlling the lifting and lowering device in a movement mode and the de-aeration device or the aeration device in a de-aeration mode or in an aeration mode, wherein a cover layer composed of a material that is permeable for air and impermeable for liquids and covers the de-aeration opening(s) and/or the aeration opening(s) and leaves the material outlet opening free is arranged on the underside of the follower plate, which cover layer is connected with an elastically stretchable ring on a circumferential edge of the cover layer, wherein the elastically stretchable ring is configured to be stretched and pulled over a circumferential edge of the container mantle and, when the follower plate is introduced into the container and impacts the cover layer, to be pulled off the container mantle and laid around an outer mantle surface of the follower plate.

16. The apparatus according to claim 11, wherein the cover layer comprises polypropylene (PP).

17. A method for introducing the follower plate of the apparatus according to claim 1 into a barrel-like container that is open toward the top, has a container bottom and a container mantle that extends upward from the container bottom, wherein the follower plate is lowered onto the container by means of the lifting and lowering device, until the follower plate lies against the inner surface of the container mantle, forming a seal, wherein the follower plate is lowered by means of alternately switching between the movement mode and the de-aeration mode after the upper end position of the follower plate has been reached, by means of de-aeration of the container interior, and the at least one holding rod or the support element is lowered by means of the lifting and lowering device after the lower end position of the follower plate has been reached.

18. The method according to claim 17, wherein the cover layer of the apparatus used in the method is connected with a ring composed of elastically stretchable material on its circumferential edge, wherein before lowering the follower plate onto the container, the cover layer is affixed to the container, in that the ring is stretched and drawn over the circumferential edge of the container mantle, so that the ring is arranged circumferentially around the container mantle on an outer side that faces away from the container interior, and wherein the ring is drawn from the container mantle by means of impacting the cover layer by means of the follower plate during its introduction into the container, and lays itself around an outer mantle surface of the follower plate.

19. The method for removing the follower plate of the apparatus according to claim 1 from a barrel-like container that is open toward the top, has a container bottom and a container mantle that extends upward from the container bottom, wherein the at least one holding rod or the support element is lifted by means of alternately switching between the movement mode and the aeration mode after the upper end position has been reached by the follower plate, and the follower plate is lifted after the follower plate has reached its lower end position, by means of introducing compressed air into the container interior.
