

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12403574
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Kukucka; Paul et al.

Fastener extractor device

Abstract

A fastener extractor tool is an apparatus that is used to remove a seized or damaged fastener. The apparatus may include at least one shank body and at least one torque-tool body. The at least one shank body allows the apparatus to be attached to an external torque tool. The torque-tool body engages the seized fastener to apply torque to dislodge said seized fastener. The at least one torque-tool body may include a plurality of laterally-bracing sidewalls and at least one engagement feature. The plurality of laterally-bracing sidewalls engage with the seized fastener to efficiently transfer torque from the external torque tool to the seized fastener. The at least one engagement feature is an engagement cavity that forms at least one engagement tooth on the at least one torque-tool body. The at least one engagement tooth engages the seized fastener to ensure torque is transferred to the seized fastener.

Inventors:	Kukucka; Paul (Brandon, FL), Kukucka; Thomas Stefan (Brandon, FL)
Applicant:	GRIP HOLDINGS LLC (Brandon, FL)
Family ID:	80115443
Assignee:	GRIP HOLDINGS LLC (Brandon, FL)
Appl. No.:	17/509633
Filed:	October 25, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20220040834 A1	Feb. 10, 2022

Related U.S. Application Data

continuation-in-part parent-doc US 16255341 20190123 US 11154969 child-doc US 17509633
continuation-in-part parent-doc US 16107842 20180821 US 10780556 20200922 child-doc US 16255341

continuation-in-part parent-doc WO PCT/IB2017/054379 20170719 PENDING child-doc US 16255341
continuation-in-part parent-doc US 15601864 20170522 ABANDONED child-doc US 16255341
continuation-in-part parent-doc WO PCT/IB2017/052453 20170427 PENDING child-doc US 16255341
us-provisional-application US 62733507 20180919
us-provisional-application US 62328102 20160427

Publication Classification

Int. Cl.: B25B27/18 (20060101); B25B15/00 (20060101)

U.S. Cl.:

CPC B25B27/18 (20130101); B25B15/008 (20130101);

Field of Classification Search

CPC: B25B (13/04); B25B (13/063); B25B (15/001); B25B (15/008); B25B (23/08); B25B (27/18); B25B (13/065)

USPC: 81/53.2; 81/461

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
1549041	12/1924	Berg	N/A	N/A
1798944	12/1930	Jackman	N/A	N/A
1863045	12/1931	Randall	81/441	B25B 27/18
1875484	12/1931	Nigra	81/441	B25B 27/18
3405377	12/1967	Pierce	N/A	N/A
3495485	12/1969	Knudsen et al.	N/A	N/A
3902384	12/1974	Ehrler	N/A	N/A
3908489	12/1974	Yamamoto et al.	N/A	N/A
4074597	12/1977	Jansson	N/A	N/A
4598616	12/1985	Colvin	N/A	N/A
4607547	12/1985	Martus	N/A	N/A
4893530	12/1989	Warheit	N/A	N/A
4927020	12/1989	Randy	N/A	N/A
4930378	12/1989	Colvin	N/A	N/A
4970922	12/1989	Krivec	81/451	B25B 15/005
5019080	12/1990	Hemer	N/A	N/A
5031487	12/1990	Polonsky	N/A	N/A
5219392	12/1992	Ruzicka et al.	N/A	N/A
5228570	12/1992	Robinson	N/A	N/A
5251521	12/1992	Burda et al.	N/A	N/A
5398823	12/1994	Anders	N/A	N/A
5481948	12/1995	Zerkovitz	N/A	N/A

5501342	12/1995	Geibel	N/A	N/A
5519929	12/1995	Bleckman	N/A	N/A
5645177	12/1996	Lin	N/A	N/A
5669516	12/1996	Horn	N/A	N/A
5725107	12/1997	Dembicks	N/A	N/A
5743394	12/1997	Martin	N/A	N/A
5782148	12/1997	Kerkhoven	N/A	N/A
5829327	12/1997	Stanton	N/A	N/A
5832792	12/1997	Hsieh	N/A	N/A
5873290	12/1998	Chaconas	N/A	N/A
6009778	12/1999	Hsieh	N/A	N/A
6092279	12/1999	Shoup	N/A	N/A
6352011	12/2001	Fruhm	N/A	N/A
6431373	12/2001	Blick	N/A	N/A
6575057	12/2002	Ploeger	N/A	N/A
6698316	12/2003	Wright	N/A	N/A
6755098	12/2003	Huang	N/A	N/A
6761089	12/2003	Bergamo	N/A	N/A
6857340	12/2004	Wagner	N/A	N/A
6951156	12/2004	Garg	N/A	N/A
7000501	12/2005	Chen	N/A	N/A
D524615	12/2005	Albertson	N/A	N/A
7225710	12/2006	Pacheco, Jr.	N/A	N/A
7331260	12/2007	Cheng	N/A	N/A
D614931	12/2009	Su	N/A	N/A
7717278	12/2009	Kao	N/A	N/A
7788994	12/2009	Wright et al.	N/A	N/A
7841480	12/2009	Hsieh	N/A	N/A
7913593	12/2010	Dahar et al.	N/A	N/A
8166851	12/2011	Pchola	N/A	N/A
8302255	12/2011	Lin	N/A	N/A
8336709	12/2011	Geibel	N/A	N/A
D745814	12/2014	Hsieh	N/A	N/A
D776505	12/2016	Doroslovac	N/A	N/A
D784106	12/2016	Doroslovac	N/A	N/A
9687968	12/2016	Doroslovac et al.	N/A	N/A
D794405	12/2016	Doroslovac et al.	N/A	N/A
9718170	12/2016	Eggert et al.	N/A	N/A
D798682	12/2016	Doroslovac et al.	N/A	N/A
9873195	12/2017	Buxton	N/A	N/A
9878441	12/2017	Kao	N/A	N/A
D829069	12/2017	Doroslovac et al.	N/A	N/A
10081094	12/2017	Doroslovac et al.	N/A	N/A
D859944	12/2018	Kukucka et al.	N/A	N/A
D859945	12/2018	Kukucka et al.	N/A	N/A
D859946	12/2018	Kukucka et al.	N/A	N/A
D859947	12/2018	Kukucka et al.	N/A	N/A
D867841	12/2018	Kukucka et al.	N/A	N/A
D868553	12/2018	Kukucka et al.	N/A	N/A
D879577	12/2019	Kukucka et al.	N/A	N/A

D880968	12/2019	Kukucka et al.	N/A	N/A
D880977	12/2019	Kukucka et al.	N/A	N/A
D885149	12/2019	Kukucka et al.	N/A	N/A
D887233	12/2019	Kukucka et al.	N/A	N/A
D887711	12/2019	Kukucka et al.	N/A	N/A
D889224	12/2019	Kukucka et al.	N/A	N/A
D889257	12/2019	Kukucka et al.	N/A	N/A
D892578	12/2019	Kukucka et al.	N/A	N/A
10780556	12/2019	Kukucka et al.	N/A	N/A
10786890	12/2019	Kukucka et al.	N/A	N/A
D899091	12/2019	Kukucka et al.	N/A	N/A
10828766	12/2019	Kukucka et al.	N/A	N/A
D904152	12/2019	Kukucka et al.	N/A	N/A
D906781	12/2020	Kukucka et al.	N/A	N/A
10882162	12/2020	Kukucka et al.	N/A	N/A
D909842	12/2020	Kukucka et al.	N/A	N/A
D910490	12/2020	Lim et al.	N/A	N/A
10919133	12/2020	Kukucka et al.	N/A	N/A
10967488	12/2020	Kukucka et al.	N/A	N/A
11154969	12/2020	Kukucka	N/A	B25B 15/008
2003/0136228	12/2002	Liu	81/53.2	B25B 27/18
2003/0209111	12/2002	Huang	N/A	N/A
2004/0256263	12/2003	Shih	N/A	N/A
2005/0098459	12/2004	Gorman	N/A	N/A
2005/0103664	12/2004	Shih	N/A	N/A
2005/0257357	12/2004	Huang	N/A	N/A
2006/0130618	12/2005	Hsieh	N/A	N/A
2006/0156869	12/2005	Hsieh	N/A	N/A
2006/0266168	12/2005	Pacheco, Jr.	N/A	N/A
2007/0079674	12/2006	Rupp	81/53.2	B25B 23/108
2007/0261519	12/2006	Cheng	N/A	N/A
2008/0235930	12/2007	English	N/A	N/A
2009/0003967	12/2008	Luna	411/404	B25B 15/005
2009/0007732	12/2008	Hsieh	N/A	N/A
2009/0120885	12/2008	Kao	N/A	N/A
2009/0220321	12/2008	Sakamura	N/A	N/A
2009/0255384	12/2008	Whitehead	N/A	N/A
2010/0037734	12/2009	Kozak	81/53.2	B25B 27/18
2010/0064863	12/2009	Kozak	N/A	N/A
2011/0056339	12/2010	Su	N/A	N/A
2011/0252925	12/2010	Whitehead	81/53.2	B25B 15/005
2011/0303052	12/2010	Chen	N/A	N/A
2012/0060656	12/2011	Chang	N/A	N/A
2013/0047798	12/2012	Huang	N/A	N/A
2013/0213193	12/2012	Lukes	81/436	B25B 15/005
2014/0260832	12/2013	Hsiao	N/A	N/A
2014/0331826	12/2013	Campbell	N/A	N/A
2014/0360321	12/2013	Steinweg et al.	N/A	N/A
2015/0093212	12/2014	Pinheiro	411/403	F16B 23/003
2015/0135910	12/2014	Eggert et al.	N/A	N/A

2015/0266169	12/2014	Campbell, II	N/A	N/A
2015/0314429	12/2014	Doroslovac	N/A	N/A
2015/0335368	12/2014	Auger	606/319	B25B 15/004
2016/0046008	12/2015	Thomas	N/A	N/A
2016/0067853	12/2015	Neto	N/A	N/A
2016/0136792	12/2015	Harp	N/A	N/A
2016/0223005	12/2015	Rathmann	N/A	N/A
2016/0339564	12/2015	Chen	N/A	N/A
2017/0246733	12/2016	Shehab	N/A	N/A
2017/0252905	12/2016	Doroslovac	N/A	N/A
2017/0282337	12/2016	Johnson et al.	N/A	N/A
2017/0312839	12/2016	Moss et al.	N/A	N/A
2017/0312897	12/2016	Doroslovac et al.	N/A	N/A
2018/0001450	12/2017	Anderson	N/A	B25B 27/18
2018/0003241	12/2017	Goss	N/A	N/A
2018/0141192	12/2017	Chang	N/A	N/A
2018/0354022	12/2017	Ross et al.	N/A	N/A
2018/0354102	12/2017	Kukucka et al.	N/A	N/A
2019/0001469	12/2018	Cho et al.	N/A	N/A
2019/0015961	12/2018	Kukucka et al.	N/A	N/A
2019/0039216	12/2018	Ikada	N/A	B25B 13/488
2019/0152033	12/2018	Kukucka et al.	N/A	N/A
2019/0283233	12/2018	Kukucka et al.	N/A	N/A
2019/0337131	12/2018	Kukucka et al.	N/A	N/A
2019/0375077	12/2018	Kukucka et al.	N/A	N/A
2020/0070321	12/2019	Schulz	N/A	B25B 15/008
2020/0078908	12/2019	Wu et al.	N/A	N/A
2020/0298380	12/2019	Doroslovac et al.	N/A	N/A
2020/0376648	12/2019	Kukucka et al.	N/A	N/A
2020/0391360	12/2019	Kukucka et al.	N/A	N/A
2021/0039245	12/2020	Kukucka et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
201612229	12/2015	AU	N/A
201612720	12/2015	AU	N/A
201612721	12/2015	AU	N/A
2564093	12/2006	CA	N/A
168071	12/2015	CA	N/A
2898480	12/2016	CA	N/A
2767068	12/2005	CN	N/A
3630254	12/2005	CN	N/A
201046555	12/2007	CN	N/A
101208181	12/2007	CN	N/A
101973013	12/2010	CN	N/A
102395447	12/2011	CN	N/A
102554833	12/2011	CN	N/A
203197845	12/2012	CN	N/A
103639950	12/2013	CN	N/A
303924849	12/2015	CN	N/A

303956827	12/2015	CN	N/A
303984883	12/2015	CN	N/A
207824800	12/2017	CN	N/A
3911409	12/1989	DE	N/A
29613327	12/1995	DE	N/A
10321284	12/2003	DE	N/A
202010006146	12/2009	DE	N/A
102013021238	12/2014	DE	N/A
0930132	12/1998	EP	N/A
0930132	12/1999	EP	N/A
1371453	12/2002	EP	N/A
1731774	12/2005	EP	N/A
0930132	12/2006	EP	N/A
2363245	12/2010	EP	N/A
906839	12/1961	GB	N/A
1294764	12/1971	GB	N/A
H0615580	12/1993	JP	N/A
H0737805	12/1994	JP	N/A
2011143522	12/2010	JP	N/A
2012157913	12/2010	JP	N/A
2014100742	12/2013	JP	N/A
2017042898	12/2016	JP	N/A
2015180835	12/2016	JP	N/A
200149097	12/1998	KR	N/A
2152870	12/1999	RU	N/A
2225786	12/2000	RU	N/A
45671	12/2004	RU	N/A
58510	12/2005	RU	N/A
2387533	12/2009	RU	N/A
116398	12/2011	RU	N/A
180548	12/2017	RU	N/A
16616	12/1929	SU	N/A
542769	12/2002	TW	N/A
M442238	12/2011	TW	N/A
201341127	12/2012	TW	N/A
201829135	12/2017	TW	N/A
WO1994016862	12/1993	WO	N/A
WO1996010932	12/1995	WO	N/A
WO1996026870	12/1995	WO	N/A
WO1996027745	12/1995	WO	N/A
WO1997010926	12/1996	WO	N/A
WO9812982	12/1997	WO	N/A
WO1998012982	12/1997	WO	N/A
WO1999032264	12/1998	WO	N/A
WO2001066312	12/2000	WO	N/A
WO2004002687	12/2003	WO	N/A
WO2005070621	12/2004	WO	N/A
WO2006023374	12/2005	WO	N/A
WO2006130490	12/2005	WO	N/A
WO2010007402	12/2009	WO	N/A

WO2011109040	12/2010	WO	N/A
WO2015050942	12/2014	WO	N/A
WO2015082283	12/2014	WO	N/A
090809	12/2015	WO	N/A
WO2016051080	12/2015	WO	N/A
091188	12/2015	WO	N/A
091189	12/2015	WO	N/A
WO2016174615	12/2015	WO	N/A
WO2017069953	12/2016	WO	N/A
WO2017178997	12/2016	WO	N/A
WO2017187388	12/2016	WO	N/A
2018150360	12/2017	WO	N/A
WO2018172831	12/2017	WO	N/A
WO2018172831	12/2017	WO	N/A
WO2019012486	12/2018	WO	N/A
WO2019167032	12/2018	WO	N/A
WO2019175652	12/2018	WO	N/A
WO2020039281	12/2019	WO	N/A
WO2020039285	12/2019	WO	N/A
WO2020058777	12/2019	WO	N/A
WO2020152516	12/2019	WO	N/A
WO2020208608	12/2019	WO	N/A
WO2020225800	12/2019	WO	N/A
WO2021001696	12/2020	WO	N/A
WO2021019500	12/2020	WO	N/A
WO2021033152	12/2020	WO	N/A

Primary Examiner: Keller; Brian D

Assistant Examiner: Dion; Marcel T

Background/Summary

(1) The current application is a continuation-in-part (CIP) application of a U.S. non-provisional application Ser. No. 16/255,341 filed on Jan. 23, 2019. The U.S. non-provisional application Ser. No. 16/255,341 claims a priority to a U.S. Provisional Patent application Ser. No. 62/733,507 filed on Sep. 19, 2018.

FIELD OF THE INVENTION

(1) The present invention generally relates to tools designed for extracting or removing fasteners, in particular bolts and nuts. More specifically, the present invention discloses a combination of anti-slip threaded extractors, designed to remove damaged fasteners.

BACKGROUND OF THE INVENTION

(2) Hex bolts, nuts, screws, and other similar threaded devices are used to secure and hold multiple components together by being engaged to a complimentary thread, known as a female thread. The general structure of these types of fasteners is a cylindrical shaft with an external thread and a head at one end of the shaft. The external thread engages a complimentary female thread tapped into a hole or a nut and secures the fastener in place, thus fastening the associated components together. To engage the fastener, the head receives an external torque force from an external tool such as a

wrench or screwdriver which rotates the rest of the fastener, thus driving the fastener into the female threading. Further, the head is shaped specifically to allow the external tool to apply the torque to the fastener in order to rotate the fastener and engage the complimentary female threading to a certain degree. This type of fastener is simple, extremely effective, cheap, and highly popular in modern construction.

(3) One of the most common problems in using these types of fasteners, whether male or female, is the tool slipping in the head portion, or slipping on the head portion. This is generally caused by either a worn fastener or tool, corrosion, overtightening, or damage to the head portion of the fastener. Now, various methods may be used to remove a fastener, some more aggressive than others, as once a fastener head is damaged, a more aggressive method must be implemented to remove the seized fastener. Drilling out the fastener is a common method utilized by some users to dislodge the fastener. While this method can prove to be effective in some scenarios, there is a high risk of damaging the internal threads of the hole. So, an objective of the present invention is to provide an extractor removal system that virtually eliminates the chance of slippage. The design of the present invention uses a series of integrated splines that bite into the head of the fastener and allow for efficient torque transfer between the extractor bit and the head portion of the fastener. Another common issue when using traditional bolt extractors is that material from the fastener or the actual fastener remains attached to the extractor tool. The present invention allows users to dislodge any remaining material and or the fastener from the extracting tool.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a top front perspective view of a first embodiment of the present invention.
- (2) FIG. 2 is a magnified view of the torque-tool body of the first embodiment of the present invention shown in FIG. 1.
- (3) FIG. 3 is a side view of the first embodiment of the present invention.
- (4) FIG. 4 is an enlarged vertical cross-sectional view taken along line 4-4 in FIG. 3.
- (5) FIG. 5 is a top view of the first embodiment of the present invention.
- (6) FIG. 6 is a magnified view of the torque-tool body of the first embodiment of the present invention shown in FIG. 5.
- (7) FIG. 7 is a top front perspective view showing a second embodiment of the present invention, wherein the present invention is shown with two shank bodies and two torque-tool bodies.
- (8) FIG. 8 is a top front perspective view showing the tubular sleeve of the present invention.
- (9) FIG. 9 is a front view showing the tubular sleeve of the present invention.
- (10) FIG. 10 is a vertical cross-sectional view of the tubular sleeve of the present invention taken along line 10-10 in FIG. 9.
- (11) FIG. 11 is a top front perspective view showing the tubular sleeve engaged with the external thread of the first embodiment of the present invention.
- (12) FIG. 12 is a top front perspective view of a third embodiment of the present invention.
- (13) FIG. 13 is a magnified view of the torque-tool body of the third embodiment of the present invention shown in FIG. 12.
- (14) FIG. 14 is a side view of the third embodiment of the present invention.
- (15) FIG. 15 is an enlarged vertical cross-sectional view taken along line 15-15 in FIG. 14.
- (16) FIG. 16 is a magnified view of the torque-tool body of the third embodiment of the present invention shown in FIG. 14.
- (17) FIG. 17 is a top perspective view of a fourth embodiment of the present invention.
- (18) FIG. 18 is a top view of the fourth embodiment of the present invention.
- (19) FIG. 19 is a top perspective view of a fifth embodiment of the present invention.

(20) FIG. 20 is a top front perspective view showing a sixth embodiment of the present invention, wherein the present invention is shown with two shank bodies and two torque-tool bodies of the fourth embodiment.

DETAIL DESCRIPTIONS OF THE INVENTION

(21) All illustrations of the drawings are for the purpose of describing selected versions of the present invention and are not intended to limit the scope of the present invention.

(22) The present invention is generally related to extraction tools and extraction tool accessories. More specifically, the present invention discloses various extractor bits, including both male and female embodiments. In addition, removing damaged fasteners from an extractor tool can prove to be a difficult task. The present invention aims to solve this issue by disclosing a releasable sleeve coupled to an extractor tool, specifically designed to assist users with removing any pieces of broken fastener which may have been wedged onto the extractor tool.

(23) Referring to FIG. 1 through 6 and 12 through 16, the present invention comprises at least one shank body 1 and at least one torque-tool body 3. The at least one shank body 1 allows the present invention to be attached to an external torque tool and, thus, allow torque to be applied to the socket fastener through the at least one torque-tool body 3 for extraction, similar to traditional designs. External torque tools include, but are not limited to, electric drills, torque wrenches, pneumatic drills, socket screw drivers, and any other tools able to transmit torque. Further, the at least one shank body 1 preferably has a circular cross-sectional profile, but other polygonal profiles may be used if preferred and are considered part of the present invention.

(24) The torque-tool body 3 is preferably a shank-like structure which engages a seized socket fastener, such as a socket screw, a socket bolt, or a specific sized drilled hole within a broken stud, any threaded shank, pipe or threadably removable object in order to apply torque force to dislodge said seized fastener. Referring to FIG. 1 through 6 and 12 through 16, the at least one torque-tool body 3 comprises a plurality of laterally-bracing sidewalls 4 and at least one engagement feature 8. In general, the at least one torque-tool body 3 is preferably a prism composed of a strong metal that is terminally and concentrically connected to the shank body 1. The at least one torque-tool body 3 is terminally and concentrically connected to the at least one shank body 1. This arrangement forms an overall elongated and cylindrical structure. The plurality of laterally-bracing sidewalls 4 is radially positioned about a rotation axis 12 of the at least one torque-tool body 3 to yield a geometric profile complimentary to that of a socket fastener or aperture within any rationally removable object. The number within the plurality of laterally-bracing sidewalls 4 is subject to change to compliment the shape and profile of a variety of socket fasteners. Moreover, each of the plurality of laterally-bracing sidewalls 4 engage within and grip the socket fastener in order to efficiently transfer torque from the external torque tool to the socket fastener. In one embodiment, the number of the plurality of laterally-bracing sidewalls 4 is six and the resulting geometric profile of the at least one torque-tool body 3 is a hexagon. In an alternative embodiment, the number of the plurality of laterally-bracing sidewalls 4 is four and the resulting geometric profile of the at least one torque-tool body 3 is a square. In alternative embodiments, the shank body 1 and torque tool body 3 may be the same shape or comprise the same components. In other words, the engagement cavity 8, the bracing surface 7, and the engagement tooth 33 may continue along the length of the elongated tool.

(25) In one embodiment, the at least one engagement feature 8 is preferably an engagement cavity to create at least one recession on the at least one torque-tool body 3. So, the at least one engagement cavity 8 is integrated into specific sidewall from the plurality of sidewalls 4 to receive the drive features of the fastener's head. Referring to FIG. 1 through 6 and 12 through 16, each of the plurality of laterally-bracing sidewalls 4 comprises a first lateral edge 5, a second lateral edge 6, and a bracing surface 7. The bracing surface 7 physically presses against a socket fastener, specifically against a lateral sidewall of a head portion of a socket fastener or the lateral sidewalls of an aperture within a rotationally removable object. The first lateral edge 5 and the second lateral

edge **6** are positioned opposite to each other across the bracing surface **7** is preferably a flat surface but may be a convex or concave surface, or a combination thereof. When viewed from either the top perspective or the bottom perspective, the first lateral edge **5** and the second lateral edge **6** from each of the plurality of laterally-bracing sidewalls **4** make up the corners of the at least one torque-tool body **3**. Moreover, the engagement cavity **8** partially traverses normal and into the bracing surface **7** of the specific sidewall **20** such that at least one engagement tooth **33** is formed on the bracing surface **7** of the specific sidewall. The engagement tooth **33** is created by the engagement cavity **8** and the bracing surface **7** so that the engagement tooth **33** serves as a gripping point for the present invention. In addition, due to the way the at least one engagement tooth **33** is formed on the bracing surface **7**, a length of the at least one engagement tooth **33** is less than or equal to a length of the at least one engagement cavity **8**. Referring to FIGS. **4** and **15**, a width of the at least one engagement tooth **33** extending from the first base **13** and towards the second base **14** along the rotation axis **12** is also less than or equal to a width of the at least one engagement cavity **8** extending along the rotation axis **12** due to the various profiles that the engagement cavity **8** may have. In alternative embodiments, the engagement tooth **33** may be created by adding material to the bracing surface in the form of a protrusion rather than removing said material.

(26) In some embodiments, the bracing surface **7** of a specific sidewall **20** may be offset to the bracing surface **7** of the adjacent sidewall. In another embodiment, the first lateral edge **5** and the second lateral edge **6** may be positioned coplanar to each other. However, the first lateral edge **5** and the second lateral edge **6** may be positioned offset to each other as well. Referring to FIG. **12** through **16**, the bracing surface **7** width may also taper from the first base **13** towards the second base **14**. In other words, a width distance of the bracing surface **7** from first lateral edge **5** to the second lateral edge **6** adjacent to first base **13** may be less than a bracing surface **7** width distance from first lateral edge **5** to second lateral edge **6** adjacent to second base **14**.

(27) Referring to FIGS. **4** and **15**, in one embodiment, the entire cross-section **9** of the engagement cavity **8** comprises a curved portion **10** and a straight portion **11**. The resulting gripping point is uniquely shaped in order to form the sharp engagement tooth **33** that digs into at least one corner of the socket fastener, allowing material from the internal sides of the fastener socket into the engagement cavity **8**, and thus yielding a superior grip over traditional tools which are simply designed to push material away. This is especially true for worn or damaged fastener sockets. The engagement tooth **33** may be constructed of three surfaces, one being a face surface and two being side surfaces. The face surface may be a flat surface, while the side surfaces may include a concave surface, a convex surface, or a combination of both. Similarly, the bracing surface **7** may be a flat surface, a concave surface, or a convex surface, or a combination of the said surfaces.

(28) Moreover, the curved portion **10** may be a partially circular curve that is positioned adjacent to the first lateral edge **5** of the specific sidewall **20**. Referring to FIG. **1** through **6** and **12** through **16**, the straight portion **11** is positioned adjacent to the curved portion **10**, opposite to the first lateral edge **5** of the specific sidewall **20**. The straight portion **11** guides a portion of the socket fastener to press against the formed engagement tooth **33**. As such, the straight portion **11** extends from the curved portion **10** to the second lateral edge **6** of the specific sidewall **20**. Specifically, the straight portion **11** starts at the curved portion **10** and ends at the second lateral edge **6** of the specific sidewall **20**. This embodiment may be implemented in a clockwise configuration or a counterclockwise configuration by flipping the positioning of the curved portion **10** with the straight portion **11**. In other embodiments, the curved portion **10** and/or the straight portion **11** may be replaced with other shape profiles as in straight, concave, or convex shapes, or combination of said shapes or profiles that may result in different shape profiles of the engagement tooth **33**. Furthermore, the engagement cavity **8** may traverse normal and into a portion of the bracing surface **7** of the specific sidewall without traversing into a remaining portion of the bracing surface **7** of the specific sidewall. This increases the sharpness of the engagement tooth **33** without

affecting the strength of the torque-tool body **3**. The remaining portion of the bracing surface **7** of the specific sidewall is also preferably flat which, depending on the design, may result in an arc length of the curved portion **10** being larger than a length of the remaining portion of the bracing surface **7** of the specific sidewall and less than a length of the straight portion **11**.

(29) In one embodiment of the present invention, the entire cross-section **9** of the engagement cavity **8** is a partially-circular profile, as shown in FIGS. **4** and **15**. Additionally, the partially-circular profile is concave along a direction from the first lateral edge **5** of the specific sidewall **20** to the second lateral edge **6** of the specific sidewall **20**. The partially-circular profile ensures that there are little to no high stress points in the at least one torque-tool body **3**, thus increasing the overall longevity of the tool. In a separate embodiment of the present invention, the entire cross-section **9** of the engagement cavity is a triangular profile, as shown in FIG. **17** through **20**.

Additionally, the triangular profile is concave along a direction from the first lateral edge **5** of the specific sidewall **20** to the second lateral edge **6** of the specific sidewall **20**. Alternative profiles may be used for the engagement cavity **8** including, but not limited to, a semi-square profile, a semi-rectangular profile, and a semi-oval profile. It is preferred that the internal corners of triangular, square, semi square type profiles have a radius for additional structural strength. In another embodiment of the present invention, the engagement cavity **8** is centrally positioned on the bracing surface **7** of the specific sidewall **20**. In particular, the engagement cavity **8** is positioned offset from the first lateral edge **5** of the specific sidewall **20** by a first distance and offset from the second lateral edge **6** of the specific sidewall **20** by a second distance; wherein the first distance equals the second distance. In an alternative embodiment, the first distance may not be equal to the second distance. This positions the engagement cavity **8** to engage the internal lateral sidewall of the socket fastener for the most efficient transfer of torque with the least possibility of slippage. Additionally, this embodiment may be used to rotate the socket fastener in either the clockwise or the counterclockwise direction.

(30) In some embodiments, the present invention may further comprise a drive head **2** and at least one external thread **15**. Referring to FIG. **1** through **6** and **12** through **16**, like the at least one shank body **1**, the drive head **2** allows the present invention to be attached to an external torque tool and, thus, allow torque to be applied to the socket fastener through the at least one torque-tool body **3** for extraction. The drive head **2** acts as the engagement element for the external torque tool. Specifically, the drive head **2** is a nut-shaped element that is terminally and concentrically connected to the at least one shank body **1**. The preferred profile of the drive head **2** is a hexagonal profile although alternative geometries may also be utilized. For example, in one embodiment, the drive head **2** has a square profile. In another embodiment, the bottom portion of the drive head **2** is dome shaped. Specifically, the bottom portion is the portion of the drive head **2** that is located opposite the shank body **1**, across the drive head **2**. The dome-shaped design yields a striking surface where impact force is applied to forcibly insert the torque-tool body **3** into the object to be extracted. However, the striking surface is not limited to being dome shaped. Further, the at least one shank body **1** preferably has a circular cross-sectional profile, but other polygonal profiles may be used if preferred and are considered part of the present invention. In addition, the torque-tool body **3** is positioned opposite the drive head **2**, along the at least one shank body **1**. Moreover, the at least one external thread **15** extends along the shank body **1** in between the at least one torque-tool body **3** and the drive head **2**. Additionally, the at least one external thread **15** is laterally connected to the at least one shank body **1**. In other embodiments, the drive head can be replaced with other engagement means.

(31) In some embodiments, the present invention may further comprise a tubular sleeve **16**, an internal thread **17**, and a nut **18**. Referring to FIG. **8** through **11**, the tubular sleeve **16** is an elongated tubular structure with an internal diameter complimentary to the external diameter of the at least one shank body **1**. The tubular sleeve **16**, the internal thread **17**, the at least one external thread **15**, and the nut **18** act as a dislodging mechanism for removing any excess material and or a

socket fastener from the at least one torque-tool body **3**. The preferred tubular sleeve **16** design includes a diameter step-up along the tubular sleeve **16** at a first end of the tubular sleeve **16**, wherein the first end of the tubular sleeve **16** is positioned adjacent to the at least one torque-tool body **3**. This provides additional engagement surface in between the tubular sleeve **16** and the foreign object affixed to the at least one torque-tool body **3**. In general, the tubular sleeve **16** translates along the at least one shank body **1** in order to press against a socket fastener on the at least one torque-tool body **3** until said socket fastener, i.e., foreign object, is dislodged. The internal thread **17** is designed complimentary to the external thread **15** for an interlocking fit. The internal thread **17** is positioned within the tubular sleeve **16** and extends along the tubular sleeve **16**.

(32) Additionally, the internal thread **17** laterally traverses into the tubular sleeve **16**. Referring to FIG. **8** through **11**, for operation, the at least one shank body **1** is concentrically positioned within the tubular sleeve **16** with the internal thread **17** being mechanically engaged to the at least one external thread **15**. This allows the tubular sleeve **16** to slide along the at least one shank body **1** when the at least one shank body **1** and the tubular sleeve **16** are spun relative to each other. After the at least one torque-tool body **3** is used to remove a seized socket fastener, the user may need to remove the socket fastener from the at least one torque-tool body **3**. For this, the user simply spins the tubular sleeve **16** about the at least one shank body **1** to slide the tubular sleeve **16** towards the at least one torque-tool body **3** until the tubular sleeve **16** presses against the socket fastener to dislodge the socket fastener. Rotating the tubular sleeve **16** may be done with the user's hands, but in cases where additional leverage is necessary the user may use two external torque tools, such as wrenches. One wrench is mechanically engaged to shank body **1** through the drive head **2** and the other wrench is mechanically engaged to the tubular sleeve **16** through the nut **18**. For this, the nut **18** is terminally and concentrically connected to the tubular sleeve **16**. Similar to the tubular sleeve **16**, the at least one shank body **1** is also positioned within the nut **18**. The preferred shaped of the nut **18** is a hex, although alternative geometries may also be used. The size, length, and material composition of the tubular sleeve **16** and the nut **18** are subject to change to meet the needs and preferences of the user. The tubular sleeve **16** may further comprise any polygonal shape complementary to the nut **18** or otherwise. In some embodiments, the tubular sleeve **16** and the nut **18** may be constructed of a single polygonal shape and or a single piece.

(33) Furthermore, in some embodiments, referring to FIG. **1** through **6** and **12** through **16**, the at least one engagement feature **8** preferably comprises a plurality of engagement features **19**. For this, the plurality of engagement features **19** is radially positioned about the rotation axis **12** with each of the plurality of engagement features **19** being integrated into the corresponding laterally-bracing sidewall from the plurality of laterally-bracing sidewalls **4**. This configuration yields an additional gripping feature on each of the plurality of laterally-bracing sidewalls **4** that ensure that a significant grip is created in between the present invention and a socket fastener.

(34) In some embodiments, the at least one torque-tool body **3** may further comprise a first base **13** and a second base **14** corresponding to the bases of polygonal-shaped body, as shown in FIG. **1** through **6** and **12** through **20**. In one embodiment, the engagement feature **8** extends into the torque-tool body **3** from the first base **13** towards the second base **14**. This ensures that the engagement tooth **33** extends along the length of the at least one torque-tool body **3** for maximum grip engagement. Referring to FIG. **1** through **6**, the first base **13** and the second base **14** are positioned opposite and preferably parallel to each other along the plurality of laterally-bracing sidewalls **4**; wherein the at least one shank body **1** is adjacently connected to the second base **14**, opposite the first base **13**. In some embodiments, the first base **13** and second base **14** are oriented perpendicular to each of the plurality of laterally-bracing sidewalls **4** and thus enclose/complete the prism shape of the at least one torque-tool body **3**. More specifically, it is preferred that the first base **13** comprises a first base surface, wherein the first base surface is flat and is oriented perpendicular to the each of the plurality of laterally-bracing sidewalls **4**. Further, the first base **13** may be convex shaped to yield a point, similar to a tool punch. When impact force is applied to the

drive head **2**, the engagement tooth **33** cuts into the sidewall of the object to be removed. Further, the at least one torque-tool body **3** may taper from the second base **14** towards the first base **13** to allow the present invention to be used on socket fasteners of different sizes. The degree of taper is subject to change to meet the needs and preferences of the user. In one embodiment of the present invention, the torque-tool body **3** may be connected to various implements including, but not limited to, impact tools, hydraulic screws, wrench sockets, and screwdrivers. To further ensure maximum grip engagement, it is preferred that an entire cross-section **9** of the engagement cavity **8** is oriented parallel to the first base **13** and the second base **14**. The bracing surface **7** width may also taper from the first base **13** towards the second base **14**. In other words, a width distance of the bracing surface **7** from first lateral edge **5** to the second lateral edge **6** adjacent to first base **13** may be less than a bracing surface **7** width distance from first lateral edge **5** to second lateral edge **6** adjacent to second base **14**.

(35) In one embodiment, referring to FIGS. **7** and **20**, the present invention is implemented in a double-ended configuration. In this embodiment, the at least one shank body **1** comprises a first shank body **22** and a second shank body **23**; the at least one torque-tool body **3** comprises a first torque-tool body **24** and a second torque-tool body **25**; and the at least one external thread **15** comprises a first external thread **26** and a second external thread **27**. This embodiment provides a dual sided version for the present invention, wherein the two sides may be differently designed and or oriented for increased versatility; specifically, this allows the present invention to be utilized for clockwise rotation and counterclockwise rotation. The first shank body **22** and the second shank body **23** are positioned opposite to each other across the drive head **2**. The first torque-tool body **24** is terminally and concentrically connected to the first shank body **22**, opposite the drive head **2**. The first external thread **26** extends along the first shank body **22**, in between the first torque-tool body **24** and the drive head **2**; additionally, the first external thread **26** is laterally connected to the first shank body **22**. This outlines a single engagement side of the present invention. Mirroring this, the second torque-tool body **25** is terminally and concentrically connected to the second shank body **23**, opposite the drive head **2**. The second external thread **27** extends along the second shank body **23**, in between the second torque-tool body **25** and the drive head **2**; additionally, the second external thread **27** is laterally connected to the second shank body **23**. In this embodiment, the type of engagement cavities of the first torque-tool body **24** may vary from the type of engagement cavities of the second torque-tool body **25** to yield a two-in-one tool.

(36) In some embodiments, the present invention may further comprise at least one cavity-transition feature **28** and a plurality of wall-transition features **29**. Both the at least one cavity-transition feature **28** and the plurality of wall-transition features **29** provide a smoother shift from the at least one engagement cavity **8** and the plurality of laterally-bracing sidewalls **4** to the torque-tool body **3** and consequently to the shank body **1**. As previously discussed, the at least one engagement cavity **8** is integrated into specific sidewall from the plurality of sidewalls **4**. Referring to FIG. **1** through **6** and **12** through **16**, the at least one cavity-transition feature **28** is terminally integrated into the engagement cavity **8**, adjacent to the shank body **1**. This also facilitates the insertion of the at least one torque-tool body **3** into the drive features in the fastener's head. Moreover, each of the plurality of wall-transition features **29** is terminally integrated into a corresponding laterally-bracing sidewall from the plurality of laterally-bracing sidewalls **4**, adjacent to the shank body **1**. In addition, each of the plurality of wall-transition features **29** may be terminally integrated into the corresponding engagement tooth **33** to increase the overall width of the engagement tooth **33**. So, the number of wall-transition features **29** matches the number of laterally-bracing sidewalls **4** to form a symmetrical structure. Alternatively, the number of wall-transition features **29** may not match the number of laterally-bracing sidewalls **4** in an asymmetrical fashion.

(37) In one embodiment, the at least one cavity-transition feature **28** comprises a first feature end **30** and a second feature end **31** corresponding to the ends of the cavity-transition feature. Referring

to FIG. 1 through 6 and 12 through 16, the first feature end 30 is positioned offset from the shank body 1, while the second feature end 31 is positioned adjacent to the shank body 1. This results in the at least one cavity-transition feature 28 to extend a desired distance into the at least one shank body 1. Moreover, the at least one cavity-transition feature 28 tapers from the first feature end 30 to the second feature end 31, or from the second feature end 31 to the first feature end 30, resulting in a curved, smooth transition from the at least one engagement cavity 8 to the at least one shank body 1. In other embodiments, the at least one cavity-transition feature 28 can include other non-curved designs. Furthermore, the at least one cavity-transition feature 28 may also comprise a plurality of cavity-transition features 32, similar to how the at least one engagement cavity 8 may be a plurality of engagement cavities 19. Like the plurality of engagement cavities 19, each of the plurality of cavity-transition features 32 is terminally integrated into a corresponding engagement cavity form the plurality of engagement cavities 19, adjacent to the shank body 1.

(38) In other embodiments, the engagement cavity 8 may be replaced with an engagement protrusion. Referring to FIG. 17 through 20, the engagement protrusion is material extruding from the torque-tool body 3 that creates an additional gripping element to the specific sidewall.

Specifically, the engagement protrusion is laterally connected to the bracing surface 7 of the specific sidewall. Additionally, the engagement protrusion extends from the first base 13 to the second base 14 to ensure the additional gripping element extends along the length of the torque-tool body 3. This allows the present invention to engage the socket fastener at an increased depth, thus maximizing the torque applied to the socket fastener. Furthermore, it is preferred that the engagement protrusion is centrally positioned in between the first lateral edge 5 of the specific sidewall and the second lateral edge 6 of the specific sidewall to allow for this embodiment to be used as a clockwise and counterclockwise tool. To ensure consistent grip along the torque-tool body 3, an entire cross-section 19 of the engagement protrusion is parallel to the first base 13 and the second base 14. It is understood that all the embodiments described within the application of the present invention for use in a socket fastener, wherein the removed subject is not limited to a socket fastener. It is further understood that a socket fastener is merely used as an example and that the afore described torque tool body 3 embodiments are designed for use in any rotationally removable object. It is further understood that the afore described embodiments are designed to engage within the aperture of any rotationally removable objects wherein the torque tool body 3 may be forcibly driven into the aperture of the rotationally removable object by percussion blows to the drive head 2 and rotationally removed by applying rotational torque to the drive head 2 by an external torque tool.

(39) Although the invention has been explained in relation to its preferred embodiment, it is to be understood that many other possible modifications and variations can be made without departing from the spirit and scope of the invention as hereinafter claimed.

Claims

1. A fastener extractor device comprising: at least one shank body; at least one torque-tool body; a drive head; a first base; a second base; an external thread; a tubular sleeve; an internal thread; the drive head being terminally and concentrically connected to the shank body; the torque-tool body being terminally and concentrically connected to the shank body; the external thread extending along the shank body, in between the torque-tool body and the drive head; the shank body being adjacently connected to the second base, opposite to the first base; the torque-tool body comprising a plurality of laterally-bracing sidewalls and at least one engagement feature; the plurality of laterally-bracing sidewalls being radially positioned about a rotation axis of the torque-tool body; each of the plurality of laterally-bracing sidewalls comprising a first lateral edge, a second lateral edge, and a bracing surface; the first lateral edge and the second lateral edge being positioned opposite to each other across the bracing surface; the first lateral edge and the second lateral edge

each being oriented parallel with the rotation axis from the first base towards the second base; at least part of a cross-section of the torque-tool body being uniform and non-tapering from the first base towards the second base; the at least one engagement feature being integrated into a specific sidewall among the plurality of laterally-bracing sidewalls; the at least one engagement feature forming an engagement tooth; the engagement tooth being parallel with the rotation axis; and the drive head being configured to receive percussion blows, wherein the engagement tooth is configured to cut into an internal sidewall of a fastener.

2. The fastener extractor device as claimed in claim 1 comprising: an entire cross-section of the at least one engagement cavity comprising a curved portion and a straight portion; the curved portion being positioned adjacent to the first lateral edge of the specific sidewall; the straight portion being positioned adjacent to the curved portion, opposite the first lateral edge of the specific sidewall; and, the straight portion extending from the curved portion to the second lateral edge of an adjacent sidewall.

3. The fastener extractor device as claimed in claim 2 comprising: the engagement cavity traversing normal and into a portion of the bracing surface of the specific sidewall without traversing into a remaining portion of the bracing surface of the specific sidewall; the remaining portion of the bracing surface of the specific sidewall being flat; and, an arc length of the curved portion being larger than a length of the remaining portion of the bracing surface of the specific sidewall and less than a length of the straight portion.

4. The fastener extractor device as claimed in claim 1, wherein the bracing surface is a flat surface.

5. The fastener extractor device as claimed in claim 1, wherein the bracing surface is a concave surface.

6. The fastener extractor device as claimed in claim 1, wherein the bracing surface is a convex surface.

7. The fastener extractor device as claimed in claim 1 comprising: the external thread being laterally connected to the shank body.

8. The fastener extractor device as claimed in claim 7 comprising: the internal thread being positioned within the tubular sleeve; the internal thread extending along the tubular sleeve; the internal thread traversing into the tubular sleeve; the shank body being concentrically positioned within the tubular sleeve; and, the internal thread being mechanically engaged to the external thread.

9. The fastener extractor device as claimed in claim 8 comprising: a nut; the nut being terminally and concentrically connected to the tubular sleeve; and, the shank body being positioned within the nut.

10. The fastener extractor device as claimed in claim 1 comprising: the at least one engagement feature comprises a plurality of engagement features; the plurality of engagement features being radially positioned about the rotation axis of the torque-tool body; and, each of the plurality of engagement features being integrated into a corresponding sidewall from the plurality of laterally-bracing sidewalls.

11. The fastener extractor device as claimed in claim 1 comprising: the at least one shank body comprising a first shank body and a second shank body; the at least one torque-tool body comprises a first torque-tool body and a second torque-tool body; the drive head being terminally and concentrically connected to the at least one shank body; the first shank body and the second shank body being positioned opposite to each other across the drive head; the first torque-tool body being terminally and concentrically connected to the first shank body, opposite the drive head; and, the second torque-tool body being terminally and concentrically connected to the second shank body, opposite the drive head.

12. The fastener extractor device as claimed in claim 11 comprising: the at least one external thread comprises a first external thread and a second external thread; the first external thread extending along the first shank body, in between the first torque-tool body and the drive head; the first

external thread being laterally connected to the first shank body; the second torque-tool body being terminally and concentrically connected to the second shank body, opposite the drive head; the second external thread extending along the second shank body, in between the second torque-tool body and the drive head; and, the second external thread being laterally connected to the second shank body.

13. The fastener extractor device as claimed in claim 1 comprising: at least one cavity-transition feature; a plurality of wall-transition features; the cavity-transition feature being terminally integrated into the engagement cavity, adjacent to the shank body; and, each of the plurality of wall-transition features being terminally integrated into a corresponding laterally-bracing sidewall from the plurality of laterally-bracing sidewall, adjacent to the shank body.

14. The fastener extractor device as claimed in claim 13 comprising: the cavity-transition feature comprising a first feature end and a second feature end; the first feature end being positioned offset from the shank body; the second feature end being positioned adjacent to the shank body; and, the cavity-transition feature tapering from the first feature end to the second feature end.

15. The fastener extractor device as claimed in claim 13 comprising: the at least one engagement cavity comprising a plurality of engagement cavities; the at least one cavity-transition feature comprising a plurality of cavity-transition features; and, each of the plurality of cavity-transition features being terminally integrated into a corresponding engagement cavity from the plurality of engagement cavities, adjacent to the shank body.
