

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12403806
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Dillinger; Thomas

Head restraint for a vehicle seat, and vehicle seat

Abstract

A head restraint for a vehicle seat may have a head restraint support, a first loudspeaker unit, and at least one second loudspeaker unit. The head restraint may also have a lining element and a cover. The lining element covers the head restraint support, the first loudspeaker unit and the at least one second loudspeaker unit in the direction of a contact surface. The cover covers the head restraint support, the first loudspeaker unit and the at least one second loudspeaker unit in a direction opposite to the contact surface. The lining element, the head restraint support and the cover are designed in such a way that a sound generated by the first loudspeaker unit can be emitted from the head restraint to an external environment of the head restraint in a largely unattenuated manner. A vehicle seat having a backrest and the head restraint is also provided.

Inventors:	Dillinger; Thomas (Ratingen, DE)
Applicant:	Adient US LLC (Plymouth, MI)
Family ID:	80461234
Assignee:	Adient US LLC (Plymouth, MI)
Appl. No.:	18/264441
Filed (or PCT Filed):	February 15, 2022
PCT No.:	PCT/IB2022/051320
PCT Pub. No.:	WO2022/175806
PCT Pub. Date:	August 25, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20240101009 A1	Mar. 28, 2024

Foreign Application Priority Data

Publication Classification

Int. Cl.: H04R1/02 (20060101); B60N2/42 (20060101); B60N2/58 (20060101); B60N2/879 (20180101)

U.S. Cl.:

CPC B60N2/879 (20180201);

Field of Classification Search

CPC: H04R (1/025); H04R (5/023); B60N (2/879); B60R (11/0217); B60R (2011/0017)

USPC: 181/199; 181/287; 297/217.4; 381/333

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6324294	12/2000	Azima et al.	N/A	N/A
9088842	12/2014	Silverstein	N/A	H04R 1/02
9403454	12/2015	Subat	N/A	H04R 5/02
2007/0024097	12/2006	Shiraishi	N/A	N/A
2007/0169988	12/2006	Chang	181/199	H04R 1/023
2014/0270322	12/2013	Silverstein	381/391	B60N 2/4214
2016/0137106	12/2015	Subat	381/389	H04R 1/023
2016/0255430	12/2015	Fujita et al.	N/A	N/A
2016/0368403	12/2015	Kobayashi	N/A	B60N 2/80
2018/0312091	12/2017	Subat et al.	N/A	N/A
2019/0375324	12/2018	Subat et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
102005015292	12/2005	DE	N/A
102015212510	12/2016	DE	N/A
102019206715	12/2019	DE	N/A
3274215	12/2018	EP	N/A
2009247388	12/2008	JP	N/A
2015100026	12/2014	JP	N/A
2017005660	12/2016	WO	N/A
2019121266	12/2018	WO	N/A
2020224945	12/2019	WO	N/A

OTHER PUBLICATIONS

European Patent Office, International Search Report and Written Opinion in Application No. PCT/IB2022/051320 dated May 6, 2022, 12 pages, Rijswijk, Netherlands. cited by applicant

Background/Summary

FIELD

(1) The invention relates to a headrest for a vehicle seat, having a headrest carrier, a first loudspeaker unit and at least one second loudspeaker unit, wherein the first loudspeaker unit and the at least one second loudspeaker unit are carried by the headrest carrier, the headrest further having a trim element and a cover, wherein the trim element covers the headrest carrier, the first loudspeaker unit and the at least one second loudspeaker unit in the direction of an abutment face, and the cover covers the headrest carrier, the first loudspeaker unit and the at least one second loudspeaker unit in a direction counter to the abutment face. The invention further relates to a vehicle seat.

BACKGROUND

(2) There are generally known from the prior art headrests for vehicles, wherein a filling material in the form of a foam is arranged between an outer trim and an inner connection member for connecting the headrest to a headrest retention member. In known headrests, for example, there is provision in this instance for a preformed foam member to be used to fill the headrest member.

(3) DE 10 2005 015 292 B3 discloses such a headrest for a vehicle. The headrest comprises a headrest member and a headrest retention member, wherein a trim is provided at the outer side of the headrest member. Inside the headrest member, a connection member for connecting the headrest retention member to the headrest member is provided, wherein filling material which is made of foam is arranged between the connection member and the trim. The filling material is constructed to be liquid in the processing state thereof, wherein the connection member and the trim define a substantially fluid-tight spatial region with respect to the filling material in the processing state thereof. Furthermore, a method for producing the headrest is described.

(4) DE 10 2015 212 510 A1 discloses a headrest with a headrest member which has at least one frame with one or more internal, flexible support elements which form an abutment face, and which is produced by initially being formed from a plastics material, in particular a material which is free from foamed materials, or a composite material.

(5) EP 3 274 215 B1 discloses a headrest with an integrated functional module, wherein the functional module is a loudspeaker unit.

(6) WO 2019/121266 A1 discloses a headrest with a dipole loudspeaker. The dipole loudspeaker is suitable for producing sound at bass frequencies. The dipole loudspeaker has a diaphragm having a first radiation face and a second radiation face, wherein the first radiation face and the second radiation face are located at opposite sides of the diaphragm, and wherein the first and second radiation faces each have a surface-area of at least 100 cm^{sup.2}. The dipole loudspeaker further has a drive unit which is configured to move the diaphragm at bass frequencies so that the first and second radiation faces generate sound at bass frequencies, wherein the sound generated by the first radiation face is in phase opposition to the sound generated by the second radiation face.

SUMMARY

(7) An object of the invention is to improve a headrest of the type mentioned in the introduction, in particular a headrest with integrated loudspeakers with a reduced required structural space and at the same time to propose an expanded acoustic frequency range and to provide a corresponding vehicle seat.

(8) This object is achieved according to the invention by a headrest for a vehicle seat, having a

headrest carrier, a first loudspeaker unit and at least one second loudspeaker unit, wherein the first loudspeaker unit and the at least one second loudspeaker unit are carried by the headrest carrier, the headrest further having a trim element and a cover, wherein the trim element covers the headrest carrier, the first loudspeaker unit and the at least one second loudspeaker unit in the direction of an abutment face, and the cover covers the headrest carrier, the first loudspeaker unit and the at least one second loudspeaker unit in a direction counter to the abutment face.

(9) In that the trim element, the headrest carrier and the cover are configured in such a manner that a sound, which is generated by the first loudspeaker unit, in particular by a diaphragm of the first loudspeaker unit, can be output, in particular in a direction perpendicular to the diaphragm of the first loudspeaker unit, from the headrest to an external environment of the headrest in a substantially non-damped manner, it becomes possible to use the principle of so-called “open acoustic baffle”. The term “substantially non-damped” is intended to be understood to mean in this instance a specific air flow resistance of less than 200 Pa s/m. Values greater than 200 Pa s/m are not intended to be included by the term “substantially non-damped”. Preferably, the specific air flow resistance is less than 100 Pa s/m, extremely preferably less than 25 Pa s/m, in each case measured in accordance with ISO 9053, Method B.

(10) Advantageous embodiments which can be used individually or in conjunction with each other are set out in the dependent claims.

(11) The specific air flow resistance of the trim element may be less than 200 Pa s/m, in particular less than 100 Pa s/m, extremely preferably less than 25 Pa s/m. The specific air flow resistance of the trim element in a region which covers the first loudspeaker unit and/or the at least one second loudspeaker unit may be less than 200 Pa s/m, in particular less than 100 Pa s/m, extremely preferably less than 25 Pa s/m, in each case measured in accordance with ISO 9053, Method B.

(12) The specific air flow resistance of the cover may be less than 200 Pa s/m, in particular less than 100 Pa s/m, extremely preferably less than 25 Pa s/m. The specific air flow resistance of the cover in a region which covers the first loudspeaker unit and/or the at least one second loudspeaker unit may be less than 200 Pa s/m, in particular less than 100 Pa s/m, extremely preferably less than 25 Pa s/m, in each case measured in accordance with ISO 9053, Method B.

(13) The first loudspeaker unit may be an acoustic dipole loudspeaker. The at least one second loudspeaker unit may be an acoustic dipole loudspeaker.

(14) The first loudspeaker unit can be retained centrally in the headrest carrier. The at least one second loudspeaker unit can be retained in a laterally offset manner relative to the first loudspeaker unit in the headrest carrier. The headrest may have two second loudspeaker units. The two second loudspeaker units can be arranged opposite each other laterally with respect to the first loudspeaker unit. The first loudspeaker unit can be arranged between the two second loudspeaker units.

(15) The first loudspeaker unit may be a low-frequency loudspeaker. A low-frequency loudspeaker is also referred to as a bass loudspeaker or woofer. The low-frequency loudspeaker may be in the form of an open loudspeaker without speaker units, in particular diaphragm or wall-mounted loudspeakers. In particular, the low-frequency loudspeaker may be in the form of an acoustic dipole or an acoustic baffle loudspeaker. The first loudspeaker unit may be a loudspeaker unit which is known from WO 2019/121266 A1.

(16) The second loudspeaker unit may be a mid-range loudspeaker. A mid-range loudspeaker is also referred to as a mid-tone speaker. The second loudspeaker unit may be a treble loudspeaker. A treble loudspeaker is also referred to as a tweeter. The second loudspeaker unit may be a combined mid-range/treble loudspeaker. For example, the second loudspeaker unit may be in the form of an open loudspeaker without speaker units, in particular a diaphragm loudspeaker, or a wall-mounted loudspeaker. In particular, the second loudspeaker unit may be in the form of an acoustic dipole or an acoustic baffle loudspeaker.

(17) The headrest carrier may form an abutment face which is provided with a plurality of internal, flexible support elements. The abutment face can be formed by the support elements. The specific

air flow resistance of the abutment face, in particular in the region of the support elements, may be less than 200 Pa s/m, in particular less than 100 Pa s/m, extremely preferably less than 25 Pa s/m.

(18) The headrest carrier can be produced from a plastics material or a composite material. Such a headrest carrier can be produced in a cost-effective manner and also has good damping and support properties without using foamed materials (in a foam-free manner). In this case, the use of foamed materials can be dispensed with, particularly completely. For example, the headrest carrier is made from a shock-resistant elastoplastic or thermoplastic material, in particular a thermoplastic plastics material, polypropylene, urethane, polyurethane, polyethylene or polycarbonate acrylonitrile butadiene styrene (PC-ABS). Preferably, the headrest carrier is formed by injection-molding a material which is free from foamed plastics material or by multiple-component injection-molding from a plurality of plastics materials.

(19) The support elements may form an ergonomically configured abutment face of the headrest carrier (also referred to as a headrest face). In particular, the support elements form a concave-formed abutment face. In this instance, the abutment face may be formed in such a concave manner that it has an abutment face which is greater than conventional headrest members. In particular, the headrest carrier with a concave-formed abutment face allows a head, in particular the back of the head of an occupant, to abut the abutment face and to be laterally supported.

(20) The trim element can have a perforation in a region which covers the first loudspeaker unit and the at least one second loudspeaker unit and the abutment face. The headrest carrier and the trim element can have a perforation in a region which laterally covers the at least one second loudspeaker unit. The cover can have a perforation in a region which covers the first loudspeaker unit in a direction counter to the abutment face. The term “perforation” in the context of the present invention is generally intended to be understood to be a planar arrangement of holes, in particular for regularly configuring a hole pattern, with different or identical shapes and sizes of the holes.

(21) The trim element can have a trim material and a foam layer. The trim element can have a textile trim material and a foam layer. The foam layer can be stitched to the trim material. The foam layer can have a thickness of up to 20 mm. The foam layer preferably has a thickness of up to 15 mm. The foam layer extremely preferably has a thickness of up to 10 mm. The foam layer can be a layer of acoustic foam.

(22) At least one sound wave guide can be arranged between the first loudspeaker unit and the at least one second loudspeaker unit. Preferably, the first loudspeaker unit is arranged centrally between two second loudspeaker units, wherein a sound wave guide can be arranged in each case between the first loudspeaker unit and the second loudspeaker unit. The sound wave guide can be integrated in the headrest carrier. The sound wave guide preferably extends over the entire height of the first loudspeaker unit and/or over the entire height of the second loudspeaker unit. In a preferred embodiment, the sound wave guide allows the sound waves to be output forward and/or backward, preferably forward and backward.

(23) The object is further achieved according to the invention by a vehicle seat having a backrest having a headrest according to the preceding description.

Description

DESCRIPTION OF THE FIGURES

- (1) The invention is explained below with reference to an advantageous exemplary embodiment which is illustrated in the Figures and with reference to two variants of this exemplary embodiment. However, the invention is not limited to this exemplary embodiment. In the drawings:
- (2) FIG. 1: shows a vehicle seat according to the invention with a headrest according to the invention,
- (3) FIG. 2: shows an exploded illustration of the headrest,

- (4) FIG. 3: shows an additional exploded illustration of the headrest,
- (5) FIG. 4: shows a sectioned illustration of the headrest along the plane of section IV-IV from FIG. 8,
- (6) FIG. 5: shows a sectioned illustration of the headrest along the plane of section V-V from FIG. 8,
- (7) FIG. 6: shows a sectioned illustration of the headrest along the plane of section VI-VI from FIG. 8,
- (8) FIG. 6A: shows a cutout of FIG. 6, supplemented by an optional sound wave guide according to a first variant,
- (9) FIG. 6B: shows a cutout of FIG. 6, supplemented by an optional sound wave guide according to a second variant,
- (10) FIG. 7: shows a sectioned illustration of the headrest along the plane of section VII-VII from FIG. 6,
- (11) FIG. 8: shows a sectioned illustration of the headrest along the plane of section VIII-VIII from FIG. 6, and
- (12) FIG. 9: shows a sectioned illustration of the headrest along the plane of section IX-IX from FIG. 6.

DETAILED DESCRIPTION

- (13) FIG. 1 shows a vehicle seat **1** according to the invention with a headrest **10** according to the invention.
- (14) The vehicle seat **1** which is illustrated schematically in FIG. 1 has a seat member **2** and a backrest **4** and is described below using three spatial directions which extend perpendicularly to each other. A longitudinal direction *x* extends in a vehicle seat **1** which is fitted in the vehicle substantially horizontally and preferably parallel with a longitudinal vehicle direction which corresponds to the conventional travel direction of the vehicle. A transverse direction *y* which extends perpendicularly to the longitudinal direction *x* is also orientated horizontally in the vehicle and extends parallel with a transverse vehicle direction. A vertical direction *z* extends perpendicularly to the longitudinal direction *x* and perpendicularly to the transverse direction *y*. In a vehicle seat **1** which is fitted in the vehicle, the vertical direction *z* extends parallel with the vertical vehicle axis.
- (15) The position indications and direction indications used, such as, for example, front, rear, top, bottom and lateral, relate to a viewing direction of an occupant who is sitting in the vehicle seat **1** in the normal seating position, wherein the vehicle seat **1** is fitted in the vehicle, is in a position for use suitable for conveying persons with an upright backrest **4** and is orientated as usual in a travel direction. However, the vehicle seat **1** according to the invention can also be fitted in a different orientation, for example, transversely relative to the travel direction.
- (16) The headrest **10** is arranged at an upper edge of the backrest **4**. FIGS. 2 and 3 show the headrest **10** in an exploded illustration. FIGS. 4 to 6 show the headrest **10** along different planes of section from FIG. 8. FIGS. 7 to 9 show sectioned illustrations of the headrest **10** along different planes of section from FIG. 6.
- (17) FIGS. 2 to 9 are described together below.
- (18) The headrest **10** has a trim element **20**, a headrest carrier **30**, a first loudspeaker unit **40**, two second loudspeaker units **42** and a cover **50**. The headrest **10** has a headrest retention member **60**, by which the headrest **10** can be connected to a frame structure of the backrest **4** of the vehicle seat **1**. The headrest retention member **60** may be able to be fixed to the frame structure. The headrest **10** may be vertically adjustable.
- (19) The first loudspeaker unit **40** and the two second loudspeaker units **42** are carried by the headrest carrier **30**. To this end, the first loudspeaker unit **40** and the two second loudspeaker units **42** are retained in corresponding recesses of the headrest carrier **30** in a positive-locking and/or non-positive-locking manner. The first loudspeaker unit **40** and/or the two second loudspeaker units

42 can be clip-fitted in the headrest carrier **30**.

(20) The trim element **20** covers the headrest carrier **30**, the first loudspeaker unit **40** and the two second loudspeaker units **42** at a front side of the headrest **10**. The front side of the headrest **10** is used by the abutment face **32** to abut a head of an occupant of the vehicle seat **1**. The cover **50** covers the headrest carrier **30**, the first loudspeaker unit **40** and the two second loudspeaker units **42** in a backward direction. The cover **50** covers the headrest carrier **30**, the first loudspeaker unit **40** and the two second loudspeaker units **42** at a side, which faces away from the abutment face **32**, of the headrest **10**. The abutment face **32** of the headrest carrier **30** is formed by a plurality of internal, flexible support elements **34**.

(21) The trim material is preferably an expansible textile, but may also be a layer of leather or synthetic leather. If the trim element **20** is made, for example, from an extensible textile, the trim element **20** has, in a region which covers the first loudspeaker unit **40** and the at least one second loudspeaker unit **42**, a perforation **22** which is formed particularly by a changed mesh size or by holes. If the trim element **20** is made, for example, from leather or synthetic leather, the trim element **20** has in a region which covers the first loudspeaker unit **40** and the at least one second loudspeaker unit **42**, a perforation **22** which is formed in particular by an arrangement of holes. The trim element **20** has, in a region which laterally covers the second loudspeaker units **42**, an additional perforation **22** which is configured identically.

(22) The trim element **20** preferably has a trim material and a foam layer. The foam layer is stitched to the trim material. A point-like adhesive bonding, which is distributed over a face, of the foam layer to the trim material is also conceivable. The foam layer is preferably a layer of acoustic foam which is adapted to reduce inherent oscillations of the individual components of the headrest **10**.

(23) The cover **50** has, in a region which covers the first loudspeaker unit **40** at a side which faces away from the abutment face **32**, a perforation **52**. The headrest carrier **30** has, in a region which laterally covers the second loudspeaker units **42**, a perforation **36**.

(24) The perforations **22** of the trim element **20**, the perforation **36** of the headrest carrier **30** and the perforation **52** of the cover **50** are used to configure a propagation path of a sound pressure which is generated by the loudspeaker units **40**, **42** to be as open as possible so that the sound pressure can be discharged forward and backward out of the trim element **20** or the cover **50** in an approximately non-influenced state, in particular in a non-damped state.

(25) The headrest **10** can optionally have a sound wave guide **31A**; **31B**. FIG. **6a** shows a dot-dash illustration of a sound wave guide **31A** according to a first variant. FIG. **6B** shows a dotted/shaded illustration of a sound wave guide **31B** according to a second variant. The sound wave guides **31A**; **31B** are integrated in the headrest carrier **30** in this case. The sound wave guides **31A**; **31B** separate the first loudspeaker unit **40** acoustically from the second loudspeaker units **42** by the sound wave guides **31A**; **31B** each laterally separating a space for receiving the first loudspeaker unit **40** from a space for receiving the second loudspeaker unit **42**. The sound of the first loudspeaker unit **40** can consequently be output only forward through the trim element **20** and backward through the cover **50**. The sound waves of the first loudspeaker unit **40** can thereby interfere substantially only spatially in front of the trim element **20** and behind the cover **50** with sound waves of the second loudspeaker units **42**. It is thereby possible to significantly improve the sound quality and furthermore to better provide the headrest **10** with an active noise suppression, also known as Active Noise Cancellation.

(26) The features disclosed in the above description, claims and drawings may be significant both individually and together for carrying out the invention in its various embodiments as long as they are within the scope of protection of the independent patent claims.

LIST OF REFERENCE NUMERALS

(27) **1** Vehicle seat **2** Seat member **4** Backrest **10** Headrest **20** Trim element **22** Perforation **30** Headrest carrier **31a** Sound wave guide **31b** Sound wave guide **32** Abutment face **34** Support element **36** Perforation **40** First loudspeaker unit **42** Second loudspeaker unit **50** Cover **52**

Claims

1. A headrest for a vehicle seat, comprising: a headrest carrier, a first loudspeaker unit and at least one second loudspeaker unit, wherein the first loudspeaker unit and the at least one second loudspeaker unit are carried by the headrest carrier, the headrest further having a trim element and a cover, wherein the trim element covers the headrest carrier, the first loudspeaker unit and the at least one second loudspeaker unit in the direction of an abutment face, and the cover covers the headrest carrier, the first loudspeaker unit and the at least one second loudspeaker unit in a direction counter to the abutment face, wherein the trim element, the headrest carrier and the cover are configured in such a manner that a sound, which is generated by the first loudspeaker unit, can be output from the headrest to an external environment of the headrest in a substantially non-damped manner.
 2. The headrest as claimed in claim 1, wherein the specific air flow resistance of the trim element is less than 200 Pa s/m.
 3. The headrest as claimed in claim 1, wherein the specific air flow resistance of the cover is less than 200 Pa s/m.
 4. The headrest as claimed in claim 1, wherein the headrest carrier has the abutment face which is provided with a plurality of internal, flexible support elements formed thereby.
 5. The headrest as claimed in claim 4, wherein the specific air flow resistance of the abutment face is less than 200 Pa s/m.
 6. The headrest as claimed in claim 1, wherein the trim element has a perforation in a region which covers the first loudspeaker unit, the at least one second loudspeaker unit and the abutment face.
 7. The headrest as claimed in claim 1, wherein the headrest carrier and the trim element have a perforation in a region which laterally covers the at least one second loudspeaker unit.
 8. The headrest as claimed in claim 1, wherein the cover has a perforation in a region which covers the first loudspeaker unit in a direction counter to the abutment face.
 9. The headrest as claimed in claim 1, wherein the trim element has a trim material and a foam layer.
 10. The headrest as claimed in claim 9, wherein the foam layer is stitched to the trim material.
 11. The headrest as claimed in claim 9, wherein the foam layer has a thickness of up to 20 mm.
 12. The headrest as claimed in claim 9, wherein the foam layer is a layer of acoustic foam.
 13. The headrest as claimed in claim 1, wherein at least one sound wave guide is arranged between the first loudspeaker unit and the at least one second loudspeaker unit.
 14. The headrest as claimed in claim 13, wherein the sound wave guide is integrated in the headrest carrier.
 15. A vehicle seat having a backrest having the headrest as claimed in claim 1.
-