

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12405049
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Woo; Dongrim et al.

Refrigerator

Abstract

Provided is a refrigerator. The refrigerator includes a cabinet in which a storage space is defined and a door which is configured to open and close the storage space and into which an insulating material is filled. The door includes an outer plate which is configured to define a front surface of the door and in which an opening is defined, a panel assembly configured to shield the opening so that the inside of the door is seen therethrough, a supporter frame mounted on a rear surface of the outer plate and configured to support a circumference of the opening and a circumference of the panel assembly, and a display device which is mounted on the supporter frame in which a plurality of LEDs are continuously disposed on a substrate. A transmission portion through which light irradiated from the display is transmitted is provided in the display device.

Inventors:	Woo; Dongrim (Seoul, KR), Cheon; Sanghyun (Seoul, KR), Kang; Chanuk (Seoul, KR), Lee; Changjae (Seoul, KR)
Applicant:	LG ELECTRONICS INC. (Seoul, KR)
Family ID:	80491828
Assignee:	LG ELECTRONICS INC. (Seoul, KR)
Appl. No.:	18/023057
Filed (or PCT Filed):	September 02, 2021
PCT No.:	PCT/KR2021/011834
PCT Pub. No.:	WO2022/050714
PCT Pub. Date:	March 10, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230314062 A1	Oct. 05, 2023

Foreign Application Priority Data

KR

10-2020-0111935

Sep. 02, 2020

Publication Classification

Int. Cl.: F25D23/02 (20060101)

U.S. Cl.:

CPC F25D23/028 (20130101); F25D2400/36 (20130101)

Field of Classification Search

CPC: A47B (2096/208); A47B (96/20); F25D (23/02); F25D (23/028); F25D (2323/02); F25D (2400/18); F25D (2400/36); F25D (27/00); F25D (27/005)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
10285513	12/2018	Lee	N/A	N/A
10704826	12/2019	Lee et al.	N/A	N/A
11604023	12/2022	Kang	N/A	F25D 27/005
11859901	12/2023	Kang	N/A	F25D 23/028
12117237	12/2023	Kang	N/A	F25D 23/025
2016/0003519	12/2015	Kim	49/70	F25D 29/005
2017/0059875	12/2016	Seung	N/A	G02B 27/144
2017/0191745	12/2016	Choi	N/A	A47F 3/0434
2017/0191746	12/2016	Seo	N/A	F25D 27/005
2017/0370636	12/2016	Koo	N/A	F25D 23/02
2018/0038627	12/2017	Kim	N/A	F25D 11/02
2018/0164031	12/2017	Lee	N/A	F25D 11/00
2018/0335252	12/2017	Oh	N/A	F25D 23/028
2018/0363970	12/2017	Koo	N/A	F25D 17/04
2019/0017679	12/2018	Choi	N/A	F21V 7/06
2019/0249485	12/2018	Jeong	N/A	F25D 29/005
2019/0257571	12/2018	Park	N/A	E06B 3/70
2019/0271500	12/2018	Lee	N/A	F25D 29/00
2019/0307263	12/2018	Lee	N/A	F25D 23/025
2021/0055038	12/2020	Lee	N/A	F25C 5/22
2021/0318061	12/2020	Lee	N/A	F25D 23/028
2021/0325104	12/2020	Kang	N/A	F25D 29/005
2021/0325107	12/2020	Kang	N/A	F25D 23/025
2023/0266057	12/2022	Kang	62/264	H04R 1/028
2023/0332822	12/2022	Kang	N/A	G06Q 30/015

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
------------	------------------	---------	-----

2013-079805	12/2012	JP	N/A
5932630	12/2015	JP	N/A
2019-027759	12/2018	JP	N/A
10-2017-0031721	12/2016	KR	N/A
10-2018-0067360	12/2017	KR	N/A
10-2018-0067391	12/2017	KR	N/A
10-2019-0007891	12/2018	KR	N/A

OTHER PUBLICATIONS

Translation JP2019027759A (Year: 2019). cited by examiner

Translation KR20170031721A (Year: 2017). cited by examiner

International Search Report (with English Translation) and Written Opinion dated Dec. 1, 2021 issued in Application No. PCT/KR2021/011834. cited by applicant

Primary Examiner: Roersma; Andrew

Attorney, Agent or Firm: KED & ASSOCIATES, LLP

Background/Summary

CROSS-REFERENCE TO RELATED PATENT APPLICATIONS

(1) This application is a U.S. National Stage Application under 35 U.S.C. § 371 of PCT Application No. PCT/KR2021/011834, filed Sep. 2, 2021, which claims priority to Korean Patent Application No. 10-2020-0111935, filed Sep. 2, 2020, whose entire disclosures are hereby incorporated by reference.

TECHNICAL FIELD

(2) The present disclosure relates to a refrigerator.

BACKGROUND ART

(3) In general, a refrigerator is a home appliance for storing foods in an internal storage space, which is shielded by a door, at a low temperature by low temperature air. For this, the refrigerator is configured to accommodate the stored food in an optimum state by cooling the internal storage space using cold air generated through heat exchange with a refrigerant circulating in a refrigeration cycle.

(4) In recent years, refrigerators have become increasingly multi-functional with changes of dietary lives and gentrification of products, and refrigerators having various structures and convenience devices for convenience of users and for efficient use of internal spaces have been released.

(5) The storage space of the refrigerator may be opened/closed by the door. Also, refrigerators may be classified into various types according to an arranged configuration of the storage space and a structure of the door that opens and closes the storage space.

(6) In general, the refrigerator has a problem in that when the door is not opened, internal food may not be identified. That is, the door should be opened to identify whether desired food is received in a space in the refrigerator or in a separate storage space provided in the door. Further, when a user does not exactly know where the food is stored, an opening time of the door may increase or the number of times the door is opened may increase. At this time, unnecessary outflow of cold air may occur.

(7) In recent years, to solve such a limitation, a refrigerator has been developed while allows a portion of a door thereof to be transparent or allows the inside thereof to be visible from the outside.

(8) In Korean Patent Publication No. 10-2018-0067391, a panel assembly through which the inside of a refrigerator is visible and on which a screen is output is provided on a door of the refrigerator. Also, a structure in which a screen is output by an operation of the panel assembly to transmit information through a see-through portion disposed on a front surface is disclosed.

(9) However, in a refrigerator having the above-described structure, there are limitations in that an operation of a large-scale display is essential to transmit information, and the operation state is output, and the information is transmitted through only the output of the screen on the see-through area due to the operation of the display.

DISCLOSURE OF THE INVENTION

Technical Problem

(10) Embodiments provide a refrigerator in which insulation performance of a door, in which a transmission portion that displays information is disposed, is secured.

(11) Embodiments also provide a refrigerator in which a display device provided with a surface light-type transmission portion has a compact mounting structure inside a door.

(12) Embodiments also provide a refrigerator in which a see-through portion that displays bar-shaped surface light is disposed in a panel assembly that sees through the inside of a door.

Technical Solution

(13) In one embodiment, a refrigerator includes: a cabinet in which a storage space is defined; and a door which is configured to open and close the storage space and into which an insulating material is filled, wherein the door includes: an outer plate which is configured to define a front surface of the door and in which an opening is defined; a panel assembly configured to shield the opening so that the inside of the door is seen therethrough; a supporter frame mounted on a rear surface of the outer plate and configured to support a circumference of the opening and a circumference of the panel assembly; and a display device which is mounted on the supporter frame in which a plurality of LEDs are continuously disposed on a substrate, wherein a transmission portion through which light irradiated from the display is transmitted is provided in the display device.

(14) In another embodiment, a refrigerator includes: a cabinet in which a storage space is defined; and a door which is configured to open and close the storage space and into which an insulating material is filled, wherein the door includes: an outer plate which is configured to define a front surface of the door and in which an opening is defined; a panel assembly configured to shield the opening so that the inside of the door is seen therethrough; a supporter frame mounted on a rear surface of the outer plate and configured to support a circumference of the opening and a circumference of the panel assembly; and a display device which is mounted on the supporter frame in which a plurality of LEDs are continuously disposed on a substrate, wherein a transmission portion through which light irradiated from the display is transmitted is provided in the display device, and, in the display device, the LEDs are disposed to be spaced apart from the transmission portion in a vertical direction and disposed to be inclined with respect to a front surface of the panel assembly to irradiate light toward the transmission portion.

(15) In the display device, a normal line of a front surface of each of the LEDs may be mounted to pass through the transmission portion.

(16) The LEDs may be spaced about 3 mm upward from each other based on a center of the transmission portion.

(17) The base substrate may be arranged to have an angle of 15° with respect to the front surface of the panel assembly.

(18) A display mounting portion recessed to accommodate the display device may be provided in the supporter frame, and the display mounting portion may be shielded by the panel assembly.

(19) An inclined portion configured to protrude backward as the inclined portion extends downward may be disposed on the display mounting portion, and an inclination of the inclined portion may be greater than that of the substrate.

(20) A vertical portion configured to extend up to a lower end of the display mounting portion may be disposed on a lower end of the inclined portion, and the vertical portion may extend parallel to a front surface of the panel assembly.

(21) A support portion configured to support the substrate from a rear side may be disposed inside the display mounting portion, and the support portion may be provided in plurality at certain intervals.

(22) The support portion may include: a rear support portion configured to support a rear surface of the substrate and provided to have an inclination that is equal to that of the substrate; an upper support portion configured to protrude forward from an upper end of the rear support portion so as to restrict an upper end of the substrate; and a lower support portion configured to protrude forward from a lower end of the rear support portion so as to support a lower end of the substrate.

(23) A lower restriction portion, which protrudes upward and has a bent structure to be elastically deformed so as to press and fix a front surface of the substrate, may be disposed on the display mounting portion.

(24) An upper restriction portion configured to protrude downward so as to restrict an upper end of the substrate may be disposed on the display mounting portion.

(25) A coupling portion configured to protrude so as to support one end of the substrate from a rear side and configured to pass through a coupling hole of the substrate may be disposed on the display mounting portion.

(26) A side restriction portion configured to protrude from an opposite side of the coupling portion and configured to restrict the other end of the substrate may be provided.

(27) The front surface of the panel assembly may be made of a glass material, a bezel portion that is opaquely printed may be disposed on a rear surface of the front panel, and the transmission portion may be disposed on a partial area on which the bezel portion is not disposed.

(28) The transmission portion may be shielded by a diffusion sheet configured to diffuse the light irradiated from the LEDs.

(29) In further another embodiment, a refrigerator includes: a cabinet in which a storage space is defined; a main door which is configured to open and close the storage space and in which an opening is defined; and a sub door configured to open and close the opening at a front side of the main door, wherein the sub door includes: an outer plate which is configured to define a front surface of the door and in which an opening is defined; a panel assembly including a plurality of panels, which are configured to shield the opening and through which the inside of the door is seen therethrough, and a transparent display through which a screen is output; a supporter frame mounted on a rear surface of the outer plate and configured to support a circumference of the panel assembly; a display device which is mounted on the supporter frame in which a plurality of LEDs are continuously disposed on a substrate; and an insulating material configured to fill a space between the circumference of the panel assembly and the inside of the sub door, wherein a transmission portion through which light irradiated from the display is transmitted is provided in the display device, and, in the display device, the LEDs are disposed above the transmission portion and disposed to be inclined with respect to a front surface of the panel assembly to irradiate light toward the transmission portion.

(30) The panel assembly may include: a front panel configured to define a front surface of the panel assembly and shield the opening; a rear panel spaced apart from the front panel to provide a space in which the display is disposed and configured to define a rear surface of the front panel; and an outer frame configured to connect the front panel to the rear panel and define a circumferential surface of the panel assembly, wherein the front panel may be larger than the rear panel so that a portion of the front panel protruding to the outside of the outer frame shields the display device at a front side.

(31) A display mounting portion recessed to accommodate the display device may be provided in the supporter frame, and a rear surface of the front panel may be in contact with a front surface of

the supporter frame so as to define a closed space in the display mounting portion.

(32) The supporter frame may include a connector groove that is further recessed from the display mounting portion to accommodate a connector on the rear surface of the substrate, and a wire guide portion extending from the connector groove to the circumferential surface of the panel assembly and recessed to guide a wire connected to the connector, and the wire may extend up to an upper end of the door along a gap between the circumference of the panel assembly and the supporter frame.

(33) The substrate may be disposed to be inclined backward as the substrate goes downward and may be mounted so that a normal line of a front surface of each of the LEDs has an inclination passing through the transmission portion.

(34) The details of one or more embodiments are set forth in the accompanying drawings and the description below. Other features will be apparent from the description and drawings, and from the claims.

Advantageous Effects

(35) The refrigerator and the refrigerator door according to the embodiment may have the following effects.

(36) According to an embodiment, the display device may be disposed to be inclined toward the transmission portion at the position that is spaced vertically apart from the transmission portion. Thus, there may be the advantage in that the surface light having the sufficient brightness is realized without forming the spot-shaped light on the transmission portion while disposing the display device to be closer to the front panel.

(37) Particularly, there may be the advantage in that the display device is disposed closer to the front panel to secure the insulating thickness inside the door, thereby securing the insulating performance. In addition, there may be the advantage in that the dew condensation is prevented from occurring on the surface of the door corresponding to the display mounting portion having the relatively thin insulating thickness due to the securing of the insulating performance.

(38) In addition, there may be the advantage in that the more compact mounting structure is capable of being realized while realizing the surface light in the transmission portion due to the inclined arrangement structure of the display device.

(39) In addition, there may be the advantage in that the structure of the support portion, the upper fixing portion, the lower fixing portion, the side fixing portion, and coupling portion are provided to maintain the inclined state of the substrate, thereby maintaining the state in which the substrate is firmly fixed inside the display mounting portion, and thus, the display device is maintained in its position even when the door is repeatedly opened and closed and is impacted.

(40) In addition, there may be the advantage in that the transmission portion, which is displayed in the form of the surface light by the display device is disposed on the area adjacent to the see-through portion output on the screen by the display to transmit the information associated with the display or output the screen associated with the display, thereby enabling the more effective transmission.

(41) In addition, there may be the advantage in that the transmission portion enables the operation state of the refrigerator and the information transmission by the independent operation regardless of the state of the see-through portion, thereby improving the convenience of use.

(42) In addition, there may be the advantage in that the transmission portion is displayed in the form of the surface light having the high brightness to improve the visibility when the display device operates and also realizing the luxurious outer appearance.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a perspective view of a refrigerator according to an embodiment.
- (2) FIG. 2 is a perspective view illustrating a state in which a sub door of a door of the refrigerator is opened.
- (3) FIG. 3 is a perspective view illustrating a state in which a main door of the door of the refrigerator is opened.
- (4) FIG. 4 is a perspective view of the door when viewed from the front.
- (5) FIG. 5 is a perspective view of the door when viewed from the rear.
- (6) FIG. 6 is an exploded perspective view of the door.
- (7) FIG. 7 is a perspective view of a panel assembly that is one component of the door when viewed from the rear.
- (8) FIG. 8 is a cross-sectional view illustrating an upper end of the panel assembly.
- (9) FIG. 9 is a front view of a supporter frame that is one component of the door.
- (10) FIG. 10 is an exploded perspective view illustrating a coupling structure of the panel assembly, an auxiliary display, and a lower frame.
- (11) FIG. 11 is an enlarged view illustrating a portion A of FIG. 10.
- (12) FIG. 12 is a front view of the auxiliary display.
- (13) FIG. 13 is a view illustrating a state in which the auxiliary display is mounted.
- (14) FIG. 14 is a cutaway perspective view taken along line XIV-XIV' of FIG. 13.
- (15) FIG. 15 is a cross-sectional view illustrating a lower end of the door.
- (16) FIG. 16 is an enlarged view illustrating a portion B of FIG. 15.
- (17) FIG. 17 is a view illustrating an output state of a transmission portion in the door.
- (18) FIG. 18 is a view illustrating various example in state changes of the transmission portion.

BEST MODE FOR CARRYING OUT THE INVENTION

- (19) Hereinafter, detailed embodiments will be described in detail with reference to the accompanying drawings. However, the present disclosure is limited to the embodiments in which the spirit of the present invention is proposed, and other degenerate idea or other embodiments included in the scope of the present invention may be easily proposed by addition, changes, deletions, etc. of other elements.
- (20) Prior to a description, directions are defined. In an embodiment of the present disclosure, a direction facing a front surface of the door illustrated in FIG. 1 may be defined as a front direction, a direction facing a cabinet with respect to the front surface of the door will be defined as a rear direction, a direction facing a bottom surface on which the refrigerator is installed will be defined as a downward direction, and a direction that is away from the bottom surface will be defined as an upward direction.
- (21) FIG. 1 is a perspective view of a refrigerator according to an embodiment.
- (22) As illustrated in the drawings, an outer appearance of a refrigerator 1 according to an embodiment may be defined by a cabinet 10 defining a storage space and a door that opens and closes the storage space.
- (23) The inside of the cabinet 10 is partitioned into upper and lower portions by a barrier 11 (see FIG. 3). A refrigerating compartment 12 may be defined in the upper portion of the cabinet 10, and a freezing compartment 13 may be defined in the lower portion of the cabinet 10.
- (24) Also, a controller 14 for controlling an overall operation of the refrigerator 1 may be disposed on a top surface of the cabinet 10. The controller 14 may be configured to control a cooling operation of the refrigerator as well as electric components for selective viewing and screen output of a see-through portion 611.
- (25) The door may include a refrigerating compartment door 20 and a freezing compartment door 30. The refrigerating compartment door 20 may be opened and closed by rotating an opened front surface of the refrigerating compartment 12, and the freezing compartment door 30 may be opened

and closed by rotating an opened front surface of the freezing compartment **13**. Also, the refrigerating compartment door **20** may be provided at an upper side and thus called an upper door, and the freezing compartment door **30** may be provided at a lower side and thus called a lower door.

(26) Also, the refrigerating compartment door **20** may be provided in a pair of left and right doors. Thus, the refrigerating compartment **12** may be shielded by the pair of doors **20a** and **20b**. The freezing compartment door **30** may be provided in a pair of left and right doors. Thus, the freezing compartment **13** may be opened and closed by the pair of doors. Alternatively, the freezing compartment door **30** may be withdrawable in a draw type as necessary and provided as one or more doors.

(27) Although a refrigerator in which, a French type door in which a pair of doors rotate to open and close one space is applied to a bottom freezer type refrigerator in which the freezing compartment **13** is provided at a lower portion, is described as an example in this embodiment, the present invention may be applied to all types of refrigerators including door without being limited to shapes of the refrigerators.

(28) At least one door **20b** of the pair of refrigerating compartment doors **20a** and **20b** may be provided to allow the inside of the refrigerator to be seen therethrough. A see-through portion **611**, which is a storage space inside the refrigerating compartment door **20b** or a region through which the storage space and/or a space inside the refrigerator are seen, may be provided in the refrigerating compartment door **20b**. The see-through portion **611** may constitute at least a portion of a front surface of the refrigerating compartment door **20b**. The see-through portion **611** may be selectively transparent or opaque according to user's manipulation. Thus, foods accommodated in the refrigerator may be identified through the see-through portion **611**.

(29) In addition, a transmission portion **612** displaying information related to an operation of the refrigerator **1** may be disposed on the refrigerating compartment door **20b** by a display device **90** described below. Light irradiated from the display device **90** may pass through the transmission portion **612** and be expressed in the form of surface light, and the transmission portion **612** may be output in the form of a bar. The see-through portion **611** may be referred to as a main display portion, and the transmission portion **612** may be referred to as an auxiliary display portion.

(30) Also, although an example in which the see-through portion **611** and the transmission portion **612** are provided in the refrigerating compartment door **20b** is described in this embodiment, the see-through portion **611** and the transmission portion **612** may be provided in various different types of refrigerator doors.

(31) FIG. 2 is a perspective view illustrating a state in which a sub door of the door of the refrigerator is opened. In addition, FIG. 3 is a perspective view illustrating a state in which a main door of the door of the refrigerator is opened.

(32) As illustrated in drawings, the right refrigerating compartment door **20b** of the pair of refrigerating compartment doors **20** may be configured to be doubly opened and closed. In detail, the refrigerating compartment door **20b**, which is disposed at the right side, may include a main door **40** that opening and closing the refrigerating compartment **12** and a sub-door **50** rotatably disposed on a main door **40** to open and close an opening defined in the main door **40**.

(33) The main door **40** may have the same size as that of the left refrigerating compartment door **20a** of the pair of refrigerating compartment doors **20a** and **20b**. The main door **40** may be rotatably mounted on the cabinet **10** by an upper hinge **401** and a lower hinge **402** to open at least a portion of the refrigerating compartment **12**.

(34) Also, an opening **41** that is opened with a predetermined size is defined in the main door **40**. A door basket **431** may be mounted on the rear surface of the main door **40** as well as the inside of the opening **41**. Here, the opening **41** may have a size that occupies most of the front surface of the main door **40** except for a portion of a circumference of the main door **40**.

(35) A storage case **43** may be provided on the rear surface of the main door **40**. A plurality of door

baskets may be disposed in the storage case **43**. When the sub-door **50** is opened, the storage case **43** may have a structure that is accessible through the opening **41**. Also, the storage case **43** may be provided with a case door to access the inside of the storage case from the rear surface of the main door **40**.

(36) Also, a main gasket **45** may be disposed on a circumference of the rear surface of the main door **40** to prevent cool air within an internal space of the cabinet **10** from leaking when the main door **40** is opened.

(37) The sub-door **50** may be rotatably mounted on the front surface of the main door **40** to open and close the opening **41**. That is, a sub upper hinge **501** and a sub lower hinge **502** may be respectively provided on upper and lower ends of the sub-door **50** so that the sub-door **50** is rotatably mounted on the front surface of the main door **40**. Thus, the sub-door **50** may be opened to expose the opening **41**.

(38) The sub-door **50** may have the same size as the main door **40** to cover the entire front surface of the main door **40**. Also, when the sub-door **50** is closed, the main door **40** and the sub-door **50** may be coupled to each other to provide the same size and configuration as those of the left refrigerating compartment door **20a**. Also, a sub gasket **58** may be disposed on the rear surface of the sub-door **50** to seal a gap between the main door **40** and the sub-door **50**.

(39) A panel assembly **60** through which the inside of the refrigerator is selectively visible and on which a screen is capable of being output is provided at a center of the sub-door **50**. Therefore, even when the sub door **50** is closed, the inside of the opening **41** may be selectively seen through the see-through portion **611**, and an image may be output on an area of the see-through portion **611**.

(40) The panel assembly **60** may be configured to be selectively transparent or opaque according to user's manipulation. Thus, only when desired by the user, the see-through portion **611** may be transparent so that the inside of the refrigerator **1** is visible, otherwise, the see-through portion **611** is maintained in an opaque state. In addition, when the panel assembly **60** is in the transparent or opaque state, a screen may be output through the see-through portion **611** by an operation of a display **63** described below.

(41) In the embodiment, the panel assembly **60** is configured to shield an opened portion of the sub-door **50**. However, according to types of the door, even when one door is configured as in the right door **20b** of the refrigerating chamber **12**, an opening may be formed in the door **20**, and the transparent panel assembly may be mounted to shield the opening of the door **20**. That is, it is noted that the panel assembly **60** may be applied to all types of doors, through which an opening is formed, regardless of the shape of the refrigerator and the shape of the door.

(42) Therefore, for convenience of description and understanding, hereinafter, the sub door **50** will be referred to as a door **50**.

(43) Hereinafter, a structure of the door **50** will be described in more detail with reference to the accompanying drawings.

(44) FIG. **4** is a perspective view of the door when viewed from the front. Also, FIG. **5** is a perspective view of the door when viewed from the rear. Also, FIG. **6** is an exploded perspective view of the door.

(45) As illustrated in the drawings, the door **50** may include an outer plate **51** defining an outer appearance of the door **50**, a door liner **52** mounted to be spaced apart from the outer plate **51**, the panel assembly **60** mounted on an opening of the outer plate **51** and the door liner **52**, and upper and lower cap decorations **54** and **55** defining the top and bottom surfaces of the door **50**. The above-described constituents may be coupled to define the whole outer appearance of the door **50**.

(46) The outer plate **51** may constitute an outer appearance of the front surface of the door **50** and a portion of a peripheral surface of the door **50** and be made of a stainless steel material. The outer plate **51** may constitute a portion of the outer appearance of the door **50** as well as the front surface of the door **50**.

(47) Also, a plate opening **511** may be defined at a center of the outer plate **51**. Here, the plate

opening **511** may be shielded by the panel assembly **60**. Also, since the inside of the refrigerator **1** is visible through the panel assembly **60** that shields the plate opening **511**, an internal region of the plate opening **511** may be referred to as the see-through portion **611**.

(48) A bent plate portion **512** that is bent backward may be disposed on a peripheral surface of the plate opening **511**. The bent plate portion **512** may be disposed along a circumference of the plate opening **511** and be inserted into and fixed to a plate accommodation groove **703** defined in a front surface of a supporter frame **70** to be described below.

(49) Both surfaces of the outer plate **51** may be bent to define an outer appearance of a side surface of the door **50**. Both ends of the outer plate **51** may be coupled to the door liner **52**. Also, upper and lower ends of the outer plate **51** may be coupled to the upper cap decoration **54** and the lower cap decoration **55**, respectively. An insulating material **53** may be filled inside the door **40** except for the panel assembly **60**, i.e., inside the outer plate **51**, the door liner **52**, the upper cap decoration **54**, and the lower cap decoration **55**.

(50) The door liner **52** defines the rear surface of the door **50** and has a door liner opening **521** in the area on which the panel assembly **60** is disposed. Also, a sub gasket **58** for sealing a gap between the door **50** and the main door **40** may be mounted on the rear surface of the door liner **52**.

(51) Also, a door light **56** may be provided on each of both sides of the door liner opening **521**. The door light **56** may illuminate the rear surface of the door **50** and a rear side of the panel assembly **60**. The door light **56** may be mounted on a light mounting portion **523** protruding backward from a rear surface of the door **50**.

(52) Thus, when the door light **56** is turned on, the inside of the storage case **43** may be brightened, and thus, the inside of the refrigerator may be more brightened up than the outside of the refrigerator so that a rear space of the door **50** may be visible through the panel assembly **60**.

(53) Also, if the door light **56** is turned on when the panel assembly **60** outputs the screen, the panel assembly **60** may function as an auxiliary backlight to allow the screen to be more clear.

(54) The upper cap decoration **54** may define a top surface of the door **50** and be coupled to upper ends of the outer plate **51** and the door liner **52**. The top surface of the upper cap decoration **54** is opened so that a decoration opening **541** communicating with an upper space of the panel assembly **60** is formed, and is shielded by a decoration cover **57**.

(55) PCBs **573** and **574** for operating electrical components inside the panel assembly **60** and the door may be mounted on the decoration cover **57** inserted into the upper cap decoration **54**. The PCBs **573** and **574** may be configured in at least one module form and may be provided in the PCB accommodating space **710** above the door **50**.

(56) Here, an inner space of the door **50** except for the PCB accommodating space **710** communicating with the decoration opening **541** may be filled with an insulating material **53**.

(57) The lower cap decoration **55** may define a bottom surface of the door **50** and be coupled to lower ends of the outer plate **51** and the door liner **52**.

(58) The panel assembly **60** may be disposed between the outer plate **51** and the door liner **52**. Also, a front surface of the panel assembly **60** may shield the plate opening **511**, and a rear surface of the panel assembly **60** may shield the door liner opening **521**. Also, the panel assembly **60** may be selectively manipulated to one state of transparent, translucent, opaque, and screen output states by the user.

(59) Thus, the panel assembly **60** may define a portion of an outer appearance of each of the front surface and the rear surface of the door **50**. In addition, the user may selectively see through the inner space of the door **50** through the panel assembly **60** and also see the screen output through the panel assembly **60**.

(60) The supporter frame **70** configured to support the panel assembly **60** is mounted on a rear surface of the outer plate **51**. The panel assembly **60** may be maintained in the fixed and mounted state by the supporter frame **70**. Particularly, a front surface of the outer plate **51** and a front surface of the panel assembly **60** may be disposed on the same extension line so that a front surface of the

door **50** has a sense of unity.

(61) A frame opening **701** is defined at a center of the supporter frame **70**. The frame opening **701** has a size somewhat less than that of the plate opening **511** and has a structure in which the panel assembly **60** is seated thereon. In the state in which the panel assembly **60** is mounted on the supporter frame **70**, the front surface of the panel assembly **60** may shield the plate opening **511** and be exposed forward. A rear surface of the panel assembly **60** may shield the liner opening **521** and be exposed backward.

(62) The panel assembly **60** may have a size that is enough to cover the plate opening **511** and the liner opening **521** inside the door **50**. Also, the see-through portion **611** may be provided in the transparent panel assembly **60** so that the inner space of the refrigerator is selectively visible, and a screen is outputted.

(63) Also, the front surface of the panel assembly **60**, which is exposed forward through the outer plate **51**, may include the see-through portion **611** through which the inside of the panel assembly **60** is visible and on which a screen is output, a bezel **613** provided to be opaque along a circumference of the see-through portion **611**, and a transmission portion **612** through which light is transmitted from a lower side of the see-through portion **611**.

(64) In detail, the bezel **613** may be disposed on a circumference of a front panel **61** defining the front surface of the panel assembly **60**. The bezel **613** may be printed with an opaque color such as black, and components disposed behind the front panel **61** may be covered so as not to be exposed to the outside.

(65) Also, a central area on which the bezel **613** is not disposed may be the see-through portion **611**, and the see-through portion **611** may have a size corresponding to a position corresponding to the display **63**. Thus, the see-through portion **611** defines an area through which the inside of the refrigerator is visible and defines an area on which the screen is output when the display **63** operates. Thus, the see-through portion **611** may be referred to as an output portion, a visualization portion, and a main display portion.

(66) Also, the transmission portion **612**, which is narrowed in a vertical direction and extends lengthily in a horizontal direction, may be disposed below the see-through portion **611**. The transmission portion **612** may also be provided to allow light to be transmitted because the bezel **613** is not provided. Thus, information may be displayed, or an operation state of the refrigerator **1** may be displayed by the transmitted light.

(67) For example, the see-through portion **611** may display a voice recognition state, a touch or note operation input state, an internal temperature, a time setting state, and the like and may be displayed as a surface emission area such as a bar graph. In addition, while the surface emission area moves or is changed in length, the see-through portion **611** may be dynamically displayed. Since the transmission portion **612** is displayed in the form of a line, the transmission portion **612** may be referred to an auxiliary display portion.

(68) Also, the transmission portion **612** may be disposed on an area between a lower end of the see-through portion **611** and a lower end of the front panel **61**. Also, the transmission portion **612** may have a vertical width of approximately 2 mm to approximately 5 mm and may have a length corresponding to a horizontal length of the see-through portion **611**.

(69) The display device **90** that irradiates light toward the transmission portion **612** may be provided at a rear side corresponding to the transmission portion **612**. Also, the display device **90** may be accommodated inside the display mounting portion **74** disposed below the supporter frame **70**.

(70) Hereinafter, the structure of the panel assembly **60** will be described in more detail with reference to the drawings.

(71) FIG. **7** is a rear perspective view of the panel assembly that is one component of the door. In addition, FIG. **8** is a cross-sectional view illustrating an upper end of the panel assembly.

(72) As illustrated in the drawings, the panel assembly **60** may be constituted by a plurality of

plate-shaped panels, and each of the panels may be spaced a predetermined interval from each other by at least one spacer to constitute one assembly.

(73) In detail, the panel assembly **60** may have an outer appearance that is defined by the front panel **61** and the rear panel **651**, which define the front and rear surfaces of the transparent panel assembly **60**, and an outer frame **67** connecting the front panel **61** to the rear panel **651**.

(74) The front panel **61** may be made of a transparent material that defines an outer appearance of the front surface of the panel assembly **60**. The front panel **61** may have a size corresponding to that of the plate opening **511** and may have a size greater than that of the frame opening **701**. Thus, the rear surface of the front panel **61** may be supported by the supporter frame **70**. Also, in a state in which the panel assembly **60** is mounted, an end of the front panel **61** may be in contact with an end of the plate opening **511**, and the plate opening **511** and a circumference of the front panel **61** may be in contact with each other.

(75) In detail, the circumference of the front panel **61** may further protrude outward than the rear panel **651**. Thus, the circumference of the front panel **61** defining the front surface of the panel assembly **60** may further extend to the outside of the frame opening **701** and thus may be stably supported by the supporter frame **70**. The rear panel **651** as well as the outer frame **67** may be inserted into the frame opening **701**.

(76) Also, the supporter frame **70** may be coupled to the panel assembly **60** by coupling the outer frame **67** to a coupling member such as a screw. Thus, a circumference of the panel assembly **60** may be supported by the supporter frame **70** and be maintained in a state of being fixed to the door **50**.

(77) A touch screen bonding (TSB) **62** may be disposed on the rear surface of the front panel **61**. The touch screen **62** may have a transparent film shape and be attached to the rear surface of the front panel **61** to sense user's touch manipulation. The touch screen **62** may be referred to as a touch sensing device or a touch sensor.

(78) A touch cable **621** connected to the touch sensor **62** may be disposed on an outer end of the front panel **61**. The touch cable **621** may connect the touch screen **62** to the PCB **573** above the door **50**.

(79) In addition, each of the display cable **632** connected to the display **63** and the light cable **642** connected to the display light **641** may also be provided in the form of a flat cable, and all of the cables **621**, **632**, and **642** may extend up to the upper end of the panel assembly **60** and be connected to the PCBs **573** and **574**.

(80) The display **63** may be disposed on the rear surface of the front panel **61**. The display **63** may be configured to output a picture or an image through the see-through portion **611** and may have a size corresponding to that of the see-through portion **611**. The display **63** may be provided in the form of a module on which a screen is capable of being output. Also, the display **63** may be transparent so that the user sees the inside through the display **63** when the screen is not outputted. Thus, the display **63** may be referred to as a transparent display and may have various shapes.

(81) In addition, a source board **631** may be disposed on one end of both left and right sides of the display **63**. The source board **631** may be disposed inside the outer frame **67** so as not to be exposed through the see-through portion **611**.

(82) The source board **631** may be connected to the display cable **632**. The display cable **632** may extend along the circumferential surface of the panel assembly **60** and may be coupled with the PCB **573**.

(83) A first spacer **643** may be provided on each of both left and right sides of the display **63**. The first spacer **643** may allow the display **63** and the light guide plate **64** to be maintained at a set distance. Also, the first spacer **643** may have a rod shape extending from an upper end to a lower end of the display **63** and may be made of aluminum.

(84) The outer frame **67** may have a rectangular frame shape. The outer frame **67** may connect the rear surface of the front panel **61** to the front surface of the rear panel **651** and also define the

peripheral surface of the panel assembly **60**.

(85) In detail, the outer frame **67** may define a circumference of an outer portion of the panel assembly **60** and also have a connection structure that is capable of allowing the front panel **61** to be maintained at a certain distance. The outer frame **67** may be disposed along the circumference of the panel assembly **60**.

(86) That is, the overall outer appearance of the panel assembly **60** may be defined by the front panel **61**, the rear panel **651**, and the outer frame **67**, and all of the remaining constituents may be provided in the outer frame **67**.

(87) In detail, the light guide plate **64** is configured so that light irradiated from the display light **641** is diffused or scattered to illuminate the display **63** at the rear side. For this, the light guide plate **64** may have a plate shape. The display light **641** may be disposed at a position corresponding to each of upper and lower ends of the light guide plate **64**.

(88) The light guide plate **64** may be disposed behind the display **63** and may be supported by a first spacer (not shown) disposed on each of both left and right sides of the rear surface of the front panel **61** and a light guide plate support portion **672a** disposed on the outer frame **67**. Thus, the light guide plate **64** may be spaced a predetermined distance from the display **63**.

(89) A pair of second spacers **661**, **661** may be disposed between the rear panel **651** and the light guide plate **64**. An insulating panel **652** may be supported by the second spacers **661** and **662**, and the insulating panel **652** may maintain a state of being spaced apart from the light guide plate **64** and the rear panel **651**.

(90) The insulating panel **652** may be maintained to be spaced a set interval from each of the insulating panel **652** and the rear panel **651** by the pair of second spacers **661** and **662**. A double-layered insulating space may be defined by the pair of second spacers **661** and **662**, the insulating panel **652**, and the rear panel **651**. In addition, an insulating space may be defined to be vacuumed or be defined by injecting an insulating gas.

(91) The display light **641** may be mounted at positions corresponding to a top surface and a bottom surface of the circumference of the panel assembly **60** on an inner surfaces of the outer frame **67**. The LED **641a** of the display light **641** may emit light toward an end of the light guide plate **64**. Thus, the light emitted through the LED **641** may travel along the light guide plate **64** so that an entire surface of the light guide plate **64** emits light.

(92) A heater **673** may be disposed along an outer surface of the outer frame **67**. The heater **673** may be provided in the form of a wire and be mounted on the outer surface of the outer frame **67**. Heat generated by the heater **673** may heat the circumference of the front panel **61** along the outer frame **67** to prevent condensation from occurring.

(93) Also, a panel assembly fixing portion **672b** may be disposed on the outer surface of the outer frame **67**. A screw passing through the supporter frame **70** may be coupled to the panel assembly fixing portion **672b**. The panel assembly **60** may be maintained in a state of being mounted on the supporter frame **70** by the coupling of the screw.

(94) Hereinafter, the structure of the frame **70** will be described in more detail with reference to the drawings.

(95) FIG. **9** is a front view of the supporter frame that is one component of the door.

(96) As illustrated in the drawings, the supporter frame **70** may be injection-molded using a plastic material and may have a rectangular frame shape so that a frame opening **701** is defined at a center thereof. Also, the supporter frame **70** may have a predetermined width and be coupled to the outer plate **51**, and simultaneously, the panel assembly **60** may be fixedly mounted on the supporter frame **70**.

(97) The supporter frame **70** may include an upper frame **71** defining an upper portion, a lower frame **73** defining a lower portion, and a side frame **72** connecting both ends of each of the upper frame **71** and the lower frame **73** to each other.

(98) In detail, the supporter frame **70** may define the overall shape of the supporter frame **70** having

the rectangular frame shape by coupling the upper frame **71**, the lower frame **73**, and the pair of side frames **72** to each other.

(99) The upper frame **71** may support an upper portion of the outer plate **51** and an upper portion of the front panel **61**. The upper frame **71** may define a shape of the upper portion of the supporter frame **70** and may divide the upper space of the door **50** in a front and rear direction. That is, the upper frame **71** may be provided with an upper extension part **711** extending up to the top surface of the door **50**, and the space above the door **50** may be divided forward and backward by the upper extension part **711**.

(100) Thus, the upper side of the door **50** may be divided forward and backward by the upper frame **71**, and a PCB accommodating space **710** in which the PCB **573** is accommodated may be defined in a rear space.

(101) The lower frame **73** may be coupled to a lower end of the side frame **72** and may be configured to support a lower portion of the outer plate **51** and a lower portion of the panel assembly **60**.

(102) The side frame **72** may define both left and right sides of the supporter frame **70** and extend lengthily in a vertical direction to connect the upper frame **71** to the lower frame **73**. That is, the side frame **72** has a structure that is capable of being coupled to both ends of the upper frame **71** and the lower frame **73**.

(103) The overall structure of the supporter frame **70** may have the rectangular frame shape by coupling the upper frame **71**, the lower frame **73**, and the side frame **72** to each other. In a state in which the supporter frame **70** is assembled, a panel assembly support portion **702** extending backward may be disposed on a circumferential surface of the frame opening **701** defined at the center of the supporter frame **70**.

(104) The panel assembly support portion **702** may extend backward to have a predetermined width and may be disposed to be in contact with the circumferential surface of the panel assembly **60**, that is, the outer frame **67**. Also, the screw that is coupled to pass through the panel assembly support portion **702** may be coupled to the outer frame **67** so that the panel assembly **60** is stably fixed and mounted on the supporter frame **70**.

(105) Also, a plate accommodation groove **703** recessed along a circumference of the supporter frame **70** may be disposed on a front surface of the supporter frame **70**. The plate accommodation groove **703** may be recessed at a position corresponding to the bent plate portion **512** so that the bent plate portion **512** of the outer plate **51** is inserted and may be disposed along the bent plate portion **512**. In addition, the bent plate portion **512** may be disposed to be in contact with the circumference of the front panel **61** in the state of being inserted into the plate accommodation groove **703**.

(106) Inner and outer surfaces of the plate accommodation groove **703** may define a plane having the same height, and thus, the front circumference of the supporter frame **70** may stably support the rear surface of the outer plate **51** corresponding to the circumferential surface of the plate opening **511**. That is, each of the upper frame **71**, the lower frame **73**, and the pair of side frames **72** may support the outer plate **51**.

(107) In this embodiment, the supporter frame **70** may have a structure in which the supporter frame **70** is molded to be separated into four parts, but the supporter frame **70** may be provided by coupling two or more components to each other, as necessary.

(108) The display mounting portion **74**, on which the display device **90** is mounted, in addition to the structure of supporting and fixing each of the outer plate **51** and the lower portion of the panel assembly **60** may be disposed on the lower frame **73**.

(109) The display device **90** may be accommodated inside the display mounting portion **74**. In addition, in the state in which the display device **90** is mounted inside the display mounting portion **74**, a wire connected to the display device **90** may be guided to an inner surface of the frame opening **701** by passing through a connector groove **733** and a wire guide portion **732**, which are

provided in the lower frame **73** and then be connected to extend up to the PCB **573** mounted on the upper frame **71** along the inner surface of the frame opening **701**.

(110) Hereinafter, a structure in which the auxiliary display **340** is mounted will now be described in more detail with reference to the accompanying drawings.

(111) FIG. **10** is an exploded perspective view illustrating a coupling structure of the panel assembly, the auxiliary display, and the lower frame. In addition, FIG. **11** is an enlarged view illustrating a portion A of FIG. **10**. In addition, FIG. **12** is a front view illustrating the auxiliary assembly of FIG. **13**.

(112) As illustrated in the drawings, the lower frame **73** may define a lower portion of the supporter frame **70** and may support a bottom surface of the circumferential surface of the panel assembly **60**. In addition, the lower frame **73** may be mounted to be in contact with a rear surface of the front panel **61**. Here, most of a front surface **731** of the lower frame **73** may be in surface contact with the rear surface of the front panel **61**. Here, the rear surface of the front panel **61** and the front surface **731** of the lower frame **73** may be bonded to each other with an adhesive. Also, the lower frame **73** may be disposed at a position corresponding to the lower portion of the front panel **61** to shield the transmission portion **612** at a rear side.

(113) The transmission portion **612** may be disposed on an area of a bezel **613** under the front panel **61**. The transmission portion **612** may be disposed at a position corresponding to the display mounting portion **74** and may be disposed in front of the display device **90**. The transmission portion **612** may be provided by cutting a portion of the bezel **613** to define a slit-shaped area through which light is transmitted. Thus, the light irradiated from the display device **90** may pass through the transmission portion **612** and be displayed to the outside. Here, the transmission portion may shine in the form of surface light according to the position of the display device **90**.

(114) As illustrated in FIG. **12**, the display device **90** may include a substrate **91** and a plurality of LEDs **92** mounted on the substrate **91**. In addition, the plurality of the LEDs **92** may be continuously arranged at regular intervals along the substrate **91**. Thus, the display device **90** may be referred to as a line display LED bar.

(115) The substrate **91** may have a size that is capable of being accommodated in the display mounting portion **74** and may extend in a left and right direction. The substrate **91** as a whole may be provided to be larger than a transverse length of the transmission portion **612**. In addition, the LED **92** disposed at each of both ends among the LEDs **92** may be disposed at the same position as each of both ends of the transmission portion **612** or disposed inside the transmission portion **612**, and thus, when all the LEDs **92** is turned on, the entire surface of the transmission portion **612** may shine in the form of the surface light.

(116) The LEDs **92** may be continuously disposed on a front surface of the substrate **91**, and elements **931** for controlling the LED **92** may be mounted on a rear surface of the substrate **91**. Also, a substrate connector **932** to which the wire **941** for supplying power to the substrate **91** is connected may be provided at one side of the rear surface of the substrate **91**. The substrate connector **932** may be disposed at a position corresponding to the connector groove **733** to facilitate the connection to the wire **941** based on a center of the substrate **91**.

(117) Also, a screw hole **911** through which a screw **95** coupled to fix the substrate **91** pass may be defined in one end of the substrate **91**. When the screw **95** is coupled to pass through the screw hole **911**, the display device **90** may be fixed and mounted inside the display mounting portion **74**.

(118) The display mounting portion **74** may be recessed to accommodate the display device **90** therein. In addition, the opened front surface of the display mounting portion **74** may be shielded by the front panel **61**. The display device **90** may be accommodated inside the display mounting portion **74** and may not interfere with the front panel **61** when the front panel **61** and the lower frame **73** are coupled to each other.

(119) The display mounting portion **74** may be recessed in the front surface of the lower frame **73**. The display mounting portion **74** may have a size that is slightly greater than that of the substrate

91.

(120) The display device **90** may be mounted inside the display mounting portion **74** and may be disposed to be inclined with respect to the front panel **61** so that the transmission portion **612** shines in the form of the surface light.

(121) In addition, a support portion **741** supporting the display device **90** at the rear side may protrude inside the display mounting portion **74**. The support portion **741** may be provided in the form of a rib, and a plurality of support portions **741** may be arranged at regular intervals inside the display mounting portion **74**.

(122) In addition, the support portion **741** may include a rear support portion **741a** that supports a rear surface of the substrate **91**, an upper support portion **741b** that restricts an upper end of the substrate **91**, and a lower support portion **741c** that restricts a lower end of the substrate **91**.

(123) The rear support portion **741a** may extend vertically and be in contact with the rear surface of the substrate **91** to support the substrate **91** at the rear side. Particularly, the rear support portion **741a** may be disposed to be inclined so that the substrate **91** is inclined at a set angle with respect to the front panel **61**.

(124) In addition, the upper support portion **741b** and the lower support portion **741c** may protrude forward from the upper and lower ends of the rear support portion **741a**, respectively, and may be in contact with the upper and lower ends of the substrate **91**. Therefore, the substrate **91** may maintain the set inclination and the correct mounting position in the state of being mounted on the support portion **741**. Particularly, when the substrate **91** is mounted, the LED **92** may not be disposed on the same extension line as the transmission portion **612**, but may be disposed at a crossing position in the vertical direction to prevent the LED **92**, which emits light through the transmission portion **612**, from being directly exposed.

(125) In addition, a coupling portion **742** may be disposed at one end of both left and right ends of the display mounting portion **74**. For example, the coupling portion **742** may be disposed at the right side of the display mounting portion **74**. The coupling portion **742** may protrude forward from a position corresponding to the coupling hole **911** defined to pass through one end of the substrate **91**.

(126) In the state in which the substrate **91** is mounted on the support portion, the right end of the rear surface of the substrate **91** may be in contact with the coupling portion **742**. In addition, the right end of the substrate **91** may be restricted by coupling the screw **746** to sequentially pass through the coupling hole **911** and the coupling portion **742**.

(127) In addition, a side restriction portion **743** protruding inward may be disposed at one end opposite to the coupling portion **742** among both the left and right ends of the display mounting portion **74**. For example, the side restriction portion **743** may protrude inward from the left surface of the display mounting portion **74**. The side restriction portion **743** may be spaced apart from the rear surface of the display mounting portion **74** and may provide a space into which a side end of the substrate **91** is inserted. When the substrate **91** is mounted, the side restriction portion **743** may be restricted to be hooked with the left end of the front surface of the substrate **91**.

(128) The substrate **91** may be prevented from moving in the left and right direction by the coupling portion **742** and the side restriction portion **743** and then may be restricted in movement forward and backward.

(129) Also, a lower restriction portion **744** may protrude upward from a bottom surface of the display mounting portion **74**. The lower restriction portion **744** may be provided in the form of an elastic ring and protrude upward from a bottom surface to press and fix the lower end of the front surface of the substrate **91**. In addition, the lower restriction portion **744** may have a structure which is opened upward so that the substrate **91** is capable of being inserted downward from an upper side.

(130) An upper restriction portion **745** may protrude from an upper portion of the display mounting portion **74**. The upper restriction portion **745** may protrude downward from the inner surface of the

display mounting portion **74** and may be fixed by pressing the upper end of the substrate **91** when mounting the substrate **91** thereon.

(131) Thus, the upper and lower restriction portions **744** and **745** may further prevent the substrate **91** from moving vertically and moving the forward and backward.

(132) A connector groove **733** may be further recessed inside the display mounting portion **74**. The connector groove **733** may be defined at a position corresponding to a connector **932** protruding from the rear surface of the substrate **91**, and the connector **932** may be disposed in the connector groove **733**.

(133) In addition, the lower frame **73** may be provided with a wire guide portion **732** connecting the display mounting portion **733** to the frame opening **701**. The lower wire guide portion **732** may guide the wire **941** connected to the connector **932** from the display mounting portion **74** to the inside of the frame opening **701**.

(134) The lower frame **73** may be covered without being exposed forward by the bezel **613**, and thus, the display device **90** and the wire **941** may not be exposed to the outside. However, light irradiated from the display device **90** may be transmitted to the outside through the transmission portion **612**.

(135) Hereinafter, a state in which the display device **90** is mounted will be described in more detail with reference to the drawings.

(136) FIG. **13** is a view illustrating a state in which the auxiliary display is mounted. In addition, FIG. **14** is a cutaway perspective view taken along line XIV-XIV' of FIG. **13**.

(137) As illustrated in the drawings, in order to mount the display device **90** inside the display mounting portion **74**, first, while moving the substrate **91** downward from the upper side of the lower restriction portion **744**, the display device **90** may be inserted between the lower restriction portion **744** and the inner surface of the display mounting portion **74**.

(138) Here, the lower restriction portion **744** may include an elastic portion **744a** and a pressing portion **744b**. The elastic portion **744a** may extend upward from the bottom surface of the display mounting portion **74** and be bent at a predetermined curvature to be elastically deformable. In addition, the pressing portion **744b** protruding to be in contact with the front surface of the substrate **91** may be disposed on an end of the elastic portion **744a**, and when the substrate **91** is mounted, the pressing portion **744b** may press and fix the front surface of the substrate **91** by elastic force of the elastic portion **744a**. That is, the substrate **91** may be restricted in downward and forward movement by the lower restriction portion **744**.

(139) In the state in which the lower portion of the substrate **91** is restricted, the substrate **91** may be in close contact with the support portion **741**. When the substrate **91** is in close contact with the support portion **741**, the substrate **91** may be maintained in the inclined state, and also, the rear surface of the substrate **91** may be in contact with the rear support portion **741a**, and the upper and lower ends of the substrate **91** may be in contact with the upper support portion **741b** by the lower support portion **741c**, and thus, the substrate **91** may be disposed at an accurate position, and the substrate **91** may be maintained in the set inclination.

(140) Here, the substrate **91** may be inclined so that the upper end faces a front side of the lower end, i.e., the front panel **61** and also may be disposed at a set angle α . For example, the substrate **91** may be disposed to be inclined by an angle of approximately 15° with respect to the front panel **61**. Here, the set angle may vary according to the arrangement height of the LED **92** and the distance between the LED **92** and the rear surface of the front panel **61**, and the set angle may be determined so that a normal line of the front surface of the LED **92** passes through an area of the transmission portion **612**.

(141) When the substrate **91** is in in close contact with the display mounting portion **74** so as to be supported by the support portion **741**, the upper end of the substrate **91** may be restricted by the upper restriction portion **745**. The upper restriction portion **745** may protrude from the inclined portion **74c** of the display mounting portion **74** and may be disposed to face a lower side as the

upper restriction portion **745** protrudes so as to press the upper end of the substrate **91** from the upper side, thereby fixing the substrate without moving forward and upward.

(142) The recessed space of the display mounting portion **74** may be defined by the bottom surface **74a**, the rear surface **74b**, and the inclined portion **74c**. The bottom surface **74a** may define a bottom surface inside the display mounting portion **74** and may extend to be perpendicular to the front surface of the lower frame **73** from the lower end of the opened front surface of the display mounting portion **74**. The rear end of the bottom surface **74a** may extend more backward than the lower end of the substrate **91**.

(143) In addition, the rear surface **74b** extending upward may be disposed on a rear end of the bottom surface **74a**. The rear surface **74b** may extend to a height between the upper end and the lower end of the substrate **91**. In addition, the inclined portion **74c** may be disposed on an upper end of the rear surface **74b**. The inclined portion **74c** may obliquely extend from the upper end of the rear surface **74b** to an upper end of the opened front surface of the display mounting portion **74**.

(144) An angle β of the inclined portion **74c** with respect to the front panel **61** may be greater than that of the substrate **91** (approximately 15°). That is, an extension line **L1** of the substrate **91** and an extension line **L2** of the inclined portion **74c** may cross each other. Thus, the distance between the inclined portion **74c** and the upper end of the substrate **91** may be reduced due to a difference in inclination. Thus, the upper restriction portion **745** may protrude from the inclined part **74c** to restrict the upper end of the substrate **91**.

(145) Due to the structure of the inclined portion **74c**, an upper space of the inner space of the display mounting portion **74** may be reduced, and thus, a space in which the insulating material **53** is further disposed may be provided to secure insulation performance.

(146) In addition, since the angle of the inclined portion **74c** is greater than the angle of the substrate **91**, the upper restriction portion **745** protruding from the inclined portion **74c** may not protrude excessively, and thus, the upper restriction portion **745** may be easily molded, and also, the upper restriction portion **745** may be prevented from being easily damaged during the mounting process of the display mounting portion **74**.

(147) In the state in which the upper and lower ends of the substrate are restricted by the upper restriction portion **745** and the lower restriction portion **744**, respectively, the substrate **91** may be pushed to the left side so that a left end of the substrate **91** is in close contact with a left surface of the display mounting portion **74**. In this state, the left end of the substrate **91** may be inserted between the side restriction portion **743** and the rear surface **74b** of the display mounting portion **74**.

(148) When the left end of the substrate **91** is in close contact with the left surface of the display mounting portion **74**, the coupling hole **911** of the substrate **91** may be supported by the coupling portion **742** so as to be aligned with each other. In this state, an operator may fix the right end of the substrate **91** to the coupling portion **742** by coupling the screw **746** to pass through the coupling hole **911**.

(149) The movement of the substrate **91** in the front and rear direction may be restricted by the side restriction portion **743** and the coupling portion **742**.

(150) As described above, the substrate **91** may be mounted to be sequentially restricted by the lower restriction portion **744**, the upper restriction portion **745**, the side restriction portion **743**, and the coupling portion **742**. In addition, the substrate **91** may be firmly fixed to the inside of the display mounting portion **74** by coupling the screw **746**.

(151) Since the substrate **91** is firmly fixed inside the display mounting portion **74**, the substrate **91** may be maintained at its initial mounting position even when the door **50** is repeatedly opened and closed and is impacted during the opening and closing of the door **50**. In addition, the light may be accurately irradiated to the transmission portion **612** so that the transmission portion **612** shines with set brightness.

(152) Hereinafter, the operation of the display device **90** having the above structure will be

described in detail with reference to drawings.

(153) FIG. 15 is a cross-sectional view illustrating the lower end of the door. In addition, FIG. 16 is an enlarged view illustrating a portion B of FIG. 15. In addition, FIG. 17 is a view illustrating an output state of the transmission portion in the door. In addition, FIG. 18 is a view illustrating various example in state changes of the transmission portion.

(154) As illustrated in the drawings, in a state in which the sub door 50 is assembled, the display device 90 may be disposed inside the display mounting portion 74. When the LED 92 of the display device 90 is turned on, the light of the LED 92 may be irradiated toward the transmission portion 612, and the transmission portion 612 may shine by the light passing through the transmission portion 612 when viewed from the outside.

(155) In addition, the LED 92 may be disposed higher than the transmission portion 612. Here, an extension line passing through a center of the transmission portion 612 may be disposed at the same position as an extension line passing through a center of the LED 92. For example, a set distance D2 may be approximately 3 mm and may be disposed in a state of being inclined toward the transmission portion 612. That is, the LED 92 may be substantially disposed on an area of the bezel portion 611 out of the transmission portion 612, and thus, even if the LED 92 is disposed close to the front panel 61, a phenomenon of light condensation may not occur at the position corresponding to the LED 92.

(156) In addition, the substrate 91 may be disposed to be inclined at a set angle with respect to the front panel 61. Thus, even when the LED 92 is disposed higher than the transmission portion 612, the light may be effectively irradiated toward the transmission portion 612. That is, the substrate 91 may be disposed inclined at an angle so that a normal line L3 of the front surface of the LED 92 is directed toward the rear end of the transmission portion 612.

(157) For example, a vertical width D2 of the transmission portion 612 may be about 2 mm. In addition, the center of the LED 92 may be spaced apart from the center of the transmission portion 612 upward by a set distance D2 of 3 mm. In addition, the substrate 91 may be inclined at an angle of about 15°, which is a set angle α , to the front panel 61 so as to effectively radiate the light toward the transmission portion 612.

(158) Due to the vertically spaced structure of the LED 92 and the transmission portion 612 and the inclined arrangement of the substrate 91, the distance between the LED 92 and the panel assembly 60 may be reduced, and also, the light condensation may be prevented from occurring in the transmission part 612.

(159) For example, the distance between the transmission portion 612 and the LED 92 may be disposed very close to about 4 mm, which is a set distance D3, and thus, the brightness of the transmission portion 612 may be secured in the state in which the transmission portion 612 is LEDs 92 are vertically spaced apart from the transmission portion 612.

(160) In addition, since the position of the LED 92 is closer than the panel assembly 60, a recessed depth of the display mounting portion 74 may be shallower to ensure a sufficient insulation distance inside the door 50. That is, due to the inclined arrangement of the display device 90, a sufficient thickness at which the insulation of the door 50 is satisfied may be secured.

(161) Due to such an arrangement structure, the door 50 may satisfy the insulation, and at the same time, when the display device 90 operates so that information of the transmission portion 612 is displayed, the transmission portion 612 may shine in the form of the surface light without the light condensation phenomenon.

(162) A bezel layer 615 may be disposed on the rear surface of the front panel 61 to prevent the light irradiated from the LED 92 from being transmitted to a portion other than the transmitting portion 612. The bezel layer 615 may be configured to block transmission of light and prevent the rear side of the front panel 61 from being visible. For example, the bezel layer 615 may be printed with a black color or provided by attaching a film, and an area of the bezel 613 may be defined by the bezel layer 615. Thus, only the area of the transmission portion 612 on which the bezel layer

615 is not formed may transmit the light irradiated from the LED **92**.

(163) Also, a diffusion sheet **614** may be attached to the rear surface of the front panel **61** corresponding to the transmission portion **612**. The diffusion sheet **614** may be configured to shield the transmission portion **612** at the rear side. Thus, the light irradiated from the LED **92** may be transmitted through the diffusion sheet **614**, and thus, the transmission portion **612** may be illuminated in the form of an overall surface light. That is, even when the light is irradiated in the state in which the LED **92** is disposed relatively close to the transmission portion **612**, it is possible to prevent light from shining in the form of a spot due to the light condensation in the transmission portion **612**.

(164) The transmission portion **612** may be configured to be shined by the plurality of LEDs **92** and may be converted into various colors according to the operation of the LED **92**. Thus, a specific color may be expressed according to an operation state of the refrigerator **1**.

(165) Also, the transmission portion **612** may partially turn on and off the LED **92** so that only a portion of the entire light is illuminated, and the operation state of the refrigerator including a temperature and time may be displayed in various patterns such as a bar graph or a bar shape in which a length varies.

(166) Also, the transmission portion **612** may allow the LED **92** to be continuously turned on and off, thereby enabling a dynamic output. For example, the shining portion may be changed, or the length or color of the shining area may be continuously changed.

(167) Also, the display device **90** may operate in conjunction with other components constituting the refrigerator **1**. For example, when a specific screen is output from the display **63** in conjunction with the operation of the display **63**, a specific pattern may be output together. Of course, the transmission portion **612** may independently output information when the display **63** is turned off. For example, when a voice signal is input by a microphone, which is provided at one side of the cabinet or door to receives a user's voice, or a sound is output by a speaker for outputting operation conditions or information of the refrigerator, the transmission portion **612** may visualize the voice signal or the sound in response thereto to visualize the state of the voice input or sound output to the user.

(168) The variable light emission pattern of the display device **90** may indicate that at least one or more of the number of LEDs **92** that are turned on, the position of the LED **92** that are turned on, the light emission intensity and color of the LED **90** that are turned on vary.

(169) Looking at an example of a change in the light emitting pattern of the display device, as illustrated in FIG. **18**, the display device may display a different pattern according to the intensity or volume of the sound input through the microphone to accurately input the user's voice.

(170) For example, referring to FIG. **15**, a sound intensity may be divided into a plurality of levels.

(171) When the sound intensity corresponds to a first level, a first group **92a** constituted by some of the plurality of LEDs **92** may be turned on so that a first area **612a** of the see-through portion **611** shines in the form of the surface light.

(172) In addition, when the sound intensity corresponds to a second level greater than the first level, a second group **92b** constituted by more LEDs **92** than those of the first group **92a** may be turned on so that a second area **612b** of the see-through portion **611**, which is longer than the first area **612a**, shines in the form of the surface light.

(173) In addition, when the sound intensity corresponds to a third level greater than the second level, a third group **92c** constituted by more LEDs **92** than those of the second group **92b** may be turned on so that a third area **612c** of the see-through portion **611**, which is longer than the second area **612b**, shines in the form of the surface light. Here, the third area **612c** may be an entire area of the see-through portion **611**.

(174) In FIG. **18**, as an example, the variation of the emission pattern of the see-through portion **611** when divided into three levels has been described, but the level division of the sound intensity is not limited thereto.

(175) In addition, although the first group **92a** is set to, for example, the LEDs **92** disposed at the central portion among the plurality of LEDs **92**, the position of the LEDs that are turned on may vary. For example, when the intensity of the sound is the first level, N LEDs may be turned on from the LEDs **92** disposed at the left or right end. When the sound intensity is the second level, M LEDs may be turned on from the LEDs disposed at the left or right end.

(176) For another example, the same number of LEDs that are turned on may be maintained, and the color or intensity of each of the LEDs that are turned on may vary according to the sound intensity.

(177) Although the structure in which the panel assembly **60** and the display device **90** are provided in the sub door is described as the embodiments, this structure may be equally applied to a single type refrigerating or freezing compartment door.

INDUSTRIAL APPLICABILITY

(178) The refrigerator according to an embodiment has the improved convenience of use due to the arrangement of the see-through portion, and thus industrial applicability is high.

Claims

1. A refrigerator comprising: a cabinet having a storage space; and a door configured to open and close the storage space, and an insulating material is provided within the door, wherein the door comprises: an outer plate configured to define a front of the door, and the outer plate having an opening; a panel assembly configured to shield the opening and selectively allow inside of the door to be seen therethrough; a supporter frame mounted on a rear of the outer plate, and the supporter frame is configured to support a circumference of the opening and a circumference of the panel assembly; and a display device mounted on the supporter frame, the display device including a substrate and a plurality of light emitting devices (LEDs) disposed on the substrate, wherein the panel assembly includes a transmission portion through which light from the display device is irradiated, and wherein the LEDs are spaced apart from the transmission portion, and the LEDs are inclined with respect to a front surface of the panel assembly to irradiate light toward the transmission portion.
2. The refrigerator according to claim 1, wherein the LEDs are disposed above the transmission portion, and wherein the LEDs are mounted such that a normal line of a front surface of each of the LEDs is to pass through the transmission portion.
3. The refrigerator according to claim 1, wherein the supporter frame includes a display mount that is recessed to accommodate the display device, and the panel assembly is configured to shield the display mount.
4. The refrigerator according to claim 3, wherein the display mount includes an inclined mount portion configured to protrude backward as the inclined mount portion extends downward, and an inclination of the inclined mount portion is greater than an inclination of the substrate.
5. The refrigerator according to claim 4, wherein the display mount includes a vertical mount portion configured to extend up to a lower end of the inclined mount portion, and the vertical mount portion is parallel to a front surface of the panel assembly.
6. The refrigerator according to claim 3, wherein the display mount includes a substrate support configured to support the substrate, and wherein the substrate support comprises: a rear support configured to support a rear surface of the substrate such that an inclination of the rear support is equal to the inclination of the substrate; an upper support to protrude forward from an upper end of the rear support, and configured to restrict an upper end of the substrate; and a lower support to protrude forward from a lower end of the rear support, and configured to support a lower end of the substrate.
7. The refrigerator according to claim 3, wherein the display mount includes a lower restriction that protrudes from the substrate and is bent to press and fix to a front surface of the display mount.

8. The refrigerator according to claim 7, wherein the lower restriction is opened upward to receive a lower end of the substrate, and wherein the display mount includes an upper restriction that protrudes downward, and is configured to restrict an upper end of the substrate.

9. The refrigerator according to claim 3, wherein the display mount includes: a coupler configured to pass through a coupling hole of the substrate and support a first end of the substrate; and a side restriction configured to protrude from a second end of the substrate and configured to restrict the second end of the substrate.

10. The refrigerator according to claim 1, wherein the door comprises: a main door configured to open and close the storage space, and to define a main door opening; and a sub door configured to open and close the main door opening at a front of the main door, wherein the outer plate is configured to define a front of the sub door, and the panel assembly is provided on the sub door.

11. The refrigerator according to claim 1, wherein the panel assembly comprises: a front panel configured to define a front of the panel assembly and to shield the opening at the outer plate; a rear panel spaced apart from the front panel to provide a space for a display, and the rear panel is configured to define a rear of the front panel; and an outer frame to connect the front panel to the rear panel, and configured to define a circumference of the panel assembly, and wherein the front panel is larger than the rear panel such that a portion of the front panel protruding to outside of the outer frame is configured to shield a front of the display device.

12. The refrigerator according to claim 11, wherein the front panel is made of a glass material, a bezel disposed on a rear of the front panel, and the transmission portion is disposed on the front panel at an area on which the bezel is not disposed.

13. The refrigerator according to claim 11, wherein the supporter frame includes a display mount that is recessed to accommodate the display device, and a rear of the front panel is in contact with a front of the supporter frame and is configured to define a closed space in the display mount.

14. The refrigerator according to claim 11, wherein a diffusion sheet shields the transmission portion, and the diffusion sheet is configured to diffuse the light irradiated from the LEDs.

15. A refrigerator comprising: a cabinet having a storage space; and a main door configured to open and close the storage space, and to define a main door opening; a sub door configured to open and close the main door opening, wherein the sub door comprises: an outer plate configured to define a front of the sub door, and the outer plate having an opening; a panel assembly configured to selectively allow inside of the main door to be seen therethrough, and including a main display to selectively output an image; a supporter frame mounted on a rear of the outer plate, and the supporter frame is configured to support the opening of the outer plate and the panel assembly; and a display device mounted on the supporter frame, the display device including a substrate and a plurality of light emitting devices (LEDs) disposed on the substrate, wherein the panel assembly includes an auxiliary display through which light from the display device is irradiated, and the auxiliary display is spaced apart from the main display, and wherein the LEDs are spaced apart from the auxiliary display, and the LEDs are inclined with respect to a front surface of the panel assembly to irradiate light toward the auxiliary display.

16. The refrigerator according to claim 15, wherein the supporter frame includes a display mount that is recessed to accommodate the display device, wherein the display mount includes a substrate support configured to support the substrate, and wherein the substrate support includes: a rear support configured to support a rear surface of the substrate such that an inclination of the rear support is equal to the inclination of the substrate; an upper support to protrude forward from an upper end of the rear support, and configured to restrict an upper end of the substrate; and a lower support to protrude forward from a lower end of the rear support, and configured to support a lower end of the substrate.

17. The refrigerator according to claim 16, wherein the panel assembly comprises: a front panel configured to define a front of the panel assembly and to shield the opening of the outer plate; a rear panel spaced apart from the front panel to provide a space for the main display, and the rear

panel is configured to define a rear of the panel assembly; and an outer frame to connect the front panel to the rear panel, and configured to define a circumference of the panel assembly, wherein the front panel is made of a glass material, and a bezel disposed on a rear of the front panel, and the auxiliary display is disposed on the front panel at an area on which the bezel is not disposed.

18. A refrigerator comprising: a cabinet having a storage space; and a door configured to open and close the storage space, wherein the door comprises: an outer plate configured to define a front of the door, and the outer plate having an opening; a panel assembly having a transparent display to selectively be visible or display an image; a supporter frame mounted on a rear of the outer plate, and the supporter frame is configured to support the outer plate and the panel assembly; and a display device mounted on the supporter frame, the display device including a substrate and a plurality of light emitting devices (LEDs) disposed on the substrate, wherein a bar-shaped transmission portion is provided in the door and is configured such that light from the display device is irradiated from the door, wherein the supporter frame includes a display mount that is recessed to accommodate the display device, and wherein the LEDs are spaced apart from the transmission portion, and the LEDs are inclined with respect to a front surface of the panel assembly to irradiate light toward the transmission portion.

19. The refrigerator according to claim 18, wherein the display mount includes a substrate support configured to support the substrate, wherein the substrate support includes: a rear support configured to support a rear surface of the substrate such that an inclination of the rear support is equal to the inclination of the substrate; an upper support to protrude forward from an upper end of the rear support, and configured to restrict an upper end of the substrate; and a lower support to protrude forward from a lower end of the rear support, and configured to support a lower end of the substrate.
