

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12405205
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Pariseau; David et al.

Personal air quality monitoring system

Abstract

An airborne, gas, or liquid particle sensor with multiple particle sensor blocks in a single particle counter. Each sensor would sample a portion of the incoming airstream, or possibly a separate airstream. The various counters could be used separately or in concert.

Inventors: Pariseau; David (Los Altos, CA), Giandomenico; Adam (Walpole, MA)

Applicant: Particles Plus, Inc. (Stoughton, MA)

Family ID: 80224051

Assignee: Particles Plus, Inc. (Stoughton, MA)

Appl. No.: 18/438166

Filed: February 09, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240410814 A1	Dec. 12, 2024

Related U.S. Application Data

continuation parent-doc US 18102208 20230127 US 11913869 child-doc US 18438166
continuation parent-doc US 17512406 20211027 US 11579072 20230214 child-doc US 18102208
continuation parent-doc US 16537492 20190809 US 11169077 20211109 child-doc US 17512406
continuation parent-doc US 16443508 20190617 US 11519842 20221206 child-doc US 16537492
continuation parent-doc US 14214876 20140315 US 10352844 20190716 child-doc US 16443508
us-provisional-application US 61786658 20130315
us-provisional-application US 61786616 20130315
us-provisional-application US 61786667 20130315

Publication Classification

Int. Cl.: G01N15/14 (20240101); G01N15/00 (20240101)

U.S. Cl.:

CPC G01N15/1459 (20130101); G01N2015/0046 (20130101); G01N2015/1486 (20130101); G01N2015/1493 (20130101)

Field of Classification Search

CPC: G01N (15/1459); G01N (2015/0046); G01N (2015/1486); G01N (2015/1493); G01N (15/0205)

USPC: 356/343

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3361030	12/1967	Goldberg	N/A	N/A
3696399	12/1971	Klein et al.	N/A	N/A
3710933	12/1972	Fulwyler et al.	N/A	N/A
3919050	12/1974	Curby	N/A	N/A
3941982	12/1975	Knollenberg et al.	N/A	N/A
4011459	12/1976	Knollenberg et al.	N/A	N/A
4153541	12/1978	Rumpf et al.	N/A	N/A
4232967	12/1979	Grachev et al.	N/A	N/A
4276472	12/1980	Costantino et al.	N/A	N/A
4361403	12/1981	Loos	N/A	N/A
4383917	12/1982	Wells	N/A	N/A
4506678	12/1984	Russell et al.	N/A	N/A
4571079	12/1985	Knollenberg	N/A	N/A
4594715	12/1985	Knollenberg	N/A	N/A
4607228	12/1985	Reif	N/A	N/A
4636075	12/1986	Knollenberg	N/A	N/A
4728190	12/1987	Knollenberg	N/A	N/A
4740988	12/1987	Knollenberg et al.	N/A	N/A
4798465	12/1988	Knollenberg	N/A	N/A
4832011	12/1988	Busch	N/A	N/A
4872972	12/1988	Wakabayashi et al.	N/A	N/A
4893928	12/1989	Knollenberg	N/A	N/A
4893932	12/1989	Knollenberg	N/A	N/A
4928153	12/1989	Glass	N/A	N/A
4984889	12/1990	Sommer	N/A	N/A
4999498	12/1990	Hunt et al.	N/A	N/A

5000052	12/1990	Sipin	N/A	N/A
5001463	12/1990	Hamburger	N/A	N/A
5059395	12/1990	Brittenham et al.	N/A	N/A
5093571	12/1991	Inomata et al.	N/A	N/A
5096474	12/1991	Miller, Jr. et al.	N/A	N/A
5235625	12/1992	Stolz et al.	N/A	N/A
5257087	12/1992	Furuya	N/A	N/A
5269659	12/1992	Hampton et al.	N/A	N/A
5282151	12/1993	Knollenberg	N/A	N/A
5317930	12/1993	Wedding	N/A	N/A
5410403	12/1994	Wells	N/A	N/A
5426501	12/1994	Hokanson et al.	N/A	N/A
5428964	12/1994	Lobdell	N/A	N/A
5467189	12/1994	Kreikebaum et al.	N/A	N/A
5493123	12/1995	Knollenberg et al.	N/A	N/A
5498273	12/1995	Mann	N/A	N/A
5515164	12/1995	Kreikebaum et al.	N/A	N/A
5553507	12/1995	Basch et al.	N/A	N/A
5553795	12/1995	Tsai et al.	N/A	N/A
5600438	12/1996	Kreikebaum et al.	N/A	N/A
5671046	12/1996	Knowlton	N/A	N/A
5751422	12/1997	Mitchell	N/A	N/A
5805281	12/1997	Knowlton	N/A	N/A
5825487	12/1997	Felbinger et al.	N/A	N/A
5861950	12/1998	Knowlton	N/A	N/A
5903338	12/1998	Mavliev et al.	N/A	N/A
5946091	12/1998	Yufa	N/A	N/A
5961291	12/1998	Sakagami et al.	N/A	N/A
6016194	12/1999	Girvin et al.	N/A	N/A
6031610	12/1999	Adams	N/A	N/A
6035551	12/1999	Scheufler et al.	N/A	N/A
6061132	12/1999	Girvin et al.	N/A	N/A
6091502	12/1999	Weigl et al.	N/A	N/A
6111642	12/1999	DeFreez et al.	N/A	N/A
6137572	12/1999	DeFreez et al.	N/A	N/A
6167107	12/1999	Bates	N/A	N/A
6246474	12/2000	Cerni et al.	N/A	N/A
6275290	12/2000	Cerni et al.	N/A	N/A
6284025	12/2000	Kreisberg et al.	N/A	N/A
6327918	12/2000	Lawless	N/A	N/A
6386015	12/2001	Rader et al.	N/A	N/A
6398118	12/2001	Rosen et al.	N/A	N/A
6508631	12/2002	Smith et al.	N/A	N/A
6592822	12/2002	Chandler	N/A	N/A
6615679	12/2002	Knollenberg et al.	N/A	N/A
6705844	12/2003	Englander	N/A	N/A
6709311	12/2003	Cerni	N/A	N/A
6788152	12/2003	Nishizono	N/A	N/A
6859277	12/2004	Wagner et al.	N/A	N/A
6900439	12/2004	Komiyama et al.	N/A	N/A

6903818	12/2004	Cerni et al.	N/A	N/A
6945090	12/2004	Rodier	N/A	N/A
6988671	12/2005	DeLuca	N/A	N/A
7011491	12/2005	Englander	N/A	N/A
7030980	12/2005	Sehler et al.	N/A	N/A
7058477	12/2005	Rosen	N/A	N/A
7088446	12/2005	Cerni	N/A	N/A
7088447	12/2005	Bates et al.	N/A	N/A
7150408	12/2005	DeLuca	N/A	N/A
7208123	12/2006	Knollenberg et al.	N/A	N/A
7235214	12/2006	Rodier et al.	N/A	N/A
RE39783	12/2006	Cerni et al.	N/A	N/A
7343751	12/2007	Kates	N/A	N/A
7439855	12/2007	Yufa	N/A	N/A
7456960	12/2007	Cerni et al.	N/A	N/A
7457709	12/2007	Zhang et al.	N/A	N/A
7473216	12/2008	Lolachi et al.	N/A	N/A
7521682	12/2008	Holland et al.	N/A	N/A
7576857	12/2008	Wagner	N/A	N/A
7598878	12/2008	Goldreich	N/A	N/A
7604676	12/2008	Braziunas	N/A	N/A
7616126	12/2008	Kadwell et al.	N/A	N/A
7667839	12/2009	Bates	N/A	N/A
7724150	12/2009	Chandler et al.	N/A	N/A
7724368	12/2009	Ahn	N/A	N/A
7796255	12/2009	Miller	N/A	N/A
7799567	12/2009	Call	N/A	N/A
7831801	12/2009	Anderson	N/A	N/A
7867779	12/2010	McDermott et al.	N/A	N/A
7895000	12/2010	Chandler et al.	N/A	N/A
7916293	12/2010	Mitchell et al.	N/A	N/A
7932490	12/2010	Wang et al.	N/A	N/A
7973929	12/2010	Bates	N/A	N/A
7985949	12/2010	Rodier	N/A	N/A
8009290	12/2010	Unger	N/A	N/A
8027035	12/2010	Mitchell et al.	N/A	N/A
8047055	12/2010	Wang et al.	N/A	N/A
8146376	12/2011	Williams et al.	N/A	N/A
8154724	12/2011	Mitchell et al.	N/A	N/A
8174697	12/2011	Mitchell et al.	N/A	N/A
8219249	12/2011	Harrod et al.	N/A	N/A
8415635	12/2012	Marks et al.	N/A	N/A
8424397	12/2012	Fjerdingstad	N/A	N/A
8427642	12/2012	Mitchell et al.	N/A	N/A
8534116	12/2012	Wang et al.	N/A	N/A
8708708	12/2013	Carideo et al.	N/A	N/A
8800383	12/2013	Bates	N/A	N/A
9116121	12/2014	Kaye et al.	N/A	N/A
9170180	12/2014	Shinohara et al.	N/A	N/A
9261287	12/2015	Warren et al.	N/A	N/A

9335244	12/2015	Han	N/A	N/A
9470627	12/2015	Alexander et al.	N/A	N/A
9541475	12/2016	Chu et al.	N/A	N/A
2002/0082488	12/2001	Al-Ali et al.	N/A	N/A
2002/0083780	12/2001	Lutz et al.	N/A	N/A
2002/0135764	12/2001	Oka et al.	N/A	N/A
2003/0009334	12/2002	Printz et al.	N/A	N/A
2003/0051023	12/2002	Reichel et al.	N/A	N/A
2003/0078751	12/2002	Juhasz	N/A	N/A
2003/0105546	12/2002	Robinson et al.	N/A	N/A
2004/0028561	12/2003	Daugherty et al.	N/A	N/A
2004/0068359	12/2003	Neiss et al.	N/A	N/A
2004/0068389	12/2003	Kleefstra	N/A	N/A
2004/0222307	12/2003	DeLuca	N/A	N/A
2004/0260702	12/2003	Cragun et al.	N/A	N/A
2005/0028593	12/2004	Rodier	N/A	N/A
2005/0043926	12/2004	Hayzen et al.	N/A	N/A
2005/0100181	12/2004	Croft et al.	N/A	N/A
2005/0161517	12/2004	Helt et al.	N/A	N/A
2005/0270151	12/2004	Winick	N/A	N/A
2006/0038998	12/2005	Wagner	N/A	N/A
2006/0049815	12/2005	Ho et al.	N/A	N/A
2006/0071803	12/2005	Hamburger	702/29	G01N 21/53
2006/0234621	12/2005	Desrochers et al.	N/A	N/A
2007/0048863	12/2006	Rodgers et al.	N/A	N/A
2007/0092976	12/2006	Watson et al.	N/A	N/A
2007/0147702	12/2006	Scoullar et al.	N/A	N/A
2007/0159156	12/2006	Hu et al.	N/A	N/A
2007/0178529	12/2006	Breidford et al.	N/A	N/A
2007/0229825	12/2006	Bates	N/A	N/A
2008/0057931	12/2007	Nass et al.	N/A	N/A
2008/0146890	12/2007	LeBoeuf et al.	N/A	N/A
2008/0182506	12/2007	Jackson	454/354	F24F 11/64
2008/0215345	12/2007	Hollingsworth et al.	N/A	N/A
2008/0221812	12/2007	Pittaro et al.	N/A	N/A
2008/0246963	12/2007	Nakajima	N/A	N/A
2009/0050538	12/2008	Lean et al.	N/A	N/A
2009/0128810	12/2008	Bates	N/A	N/A
2009/0190128	12/2008	Cerni et al.	N/A	N/A
2009/0237659	12/2008	Miers	N/A	N/A
2009/0242799	12/2008	Bolotin et al.	N/A	N/A
2009/0259709	12/2008	Nikitin	N/A	N/A
2009/0268202	12/2008	Wagner	N/A	N/A
2009/0283456	12/2008	Le Vot et al.	N/A	N/A
2010/0212670	12/2009	Amighi et al.	N/A	N/A
2010/0225913	12/2009	Trainer	N/A	N/A
2010/0253509	12/2009	Fu et al.	N/A	N/A
2010/0264301	12/2009	Borosak	N/A	N/A
2010/0282260	12/2009	Sung	N/A	N/A
2011/0175661	12/2010	Quesada et al.	N/A	N/A

2011/0277679	12/2010	Good et al.	N/A	N/A
2011/0303859	12/2010	Lofstrom et al.	N/A	N/A
2012/0012744	12/2011	Wang et al.	N/A	N/A
2012/0085831	12/2011	Kopp	N/A	N/A
2012/0140231	12/2011	Knox et al.	N/A	N/A
2012/0277902	12/2011	Sharpe et al.	N/A	N/A
2012/0295301	12/2011	Miyashita et al.	N/A	N/A
2013/0040857	12/2012	Anderson	N/A	N/A
2013/0050698	12/2012	Muraki et al.	N/A	N/A
2013/0166251	12/2012	Latimer et al.	N/A	N/A
2013/0270287	12/2012	Guo et al.	N/A	N/A
2013/0286392	12/2012	Erdtmann	N/A	N/A
2013/0295588	12/2012	Watkins et al.	N/A	N/A
2014/0022547	12/2013	Knox et al.	N/A	N/A
2014/0053586	12/2013	Poecher et al.	N/A	N/A
2014/0134608	12/2013	Hanashi et al.	N/A	N/A
2014/0354976	12/2013	Evenstad et al.	N/A	N/A
2015/0200083	12/2014	Brown et al.	N/A	N/A
2015/0323941	12/2014	Pariseau et al.	N/A	N/A
2016/0000358	12/2015	Lundin et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
100478670	12/2008	CN	N/A
202720173	12/2012	CN	N/A
2145171	12/2017	EP	N/A
674265	12/1951	GB	N/A
2233462	12/1990	GB	N/A
2420616	12/2005	GB	N/A
2474235	12/2010	GB	N/A
56-39420	12/1980	JP	N/A
3-296622	12/1990	JP	N/A
2001-281128	12/2000	JP	N/A
5005704	12/2011	JP	N/A
1994/29716	12/1993	WO	N/A
1998/56426	12/1997	WO	N/A
1999/22219	12/1998	WO	N/A
1999/56106	12/1998	WO	N/A
2001/06333	12/2000	WO	N/A
2001/63250	12/2000	WO	N/A
2002/063294	12/2001	WO	N/A
2004/010113	12/2003	WO	N/A
2007/076188	12/2006	WO	N/A
2007/126681	12/2006	WO	N/A
2008/140816	12/2007	WO	N/A
2009/073649	12/2008	WO	N/A
2009/073652	12/2008	WO	N/A
2010/0147166	12/2009	WO	N/A
2011/025763	12/2010	WO	N/A
2012/055048	12/2011	WO	N/A

2012/064878	12/2011	WO	N/A
2013/017832	12/2012	WO	N/A
2014/043413	12/2013	WO	N/A

OTHER PUBLICATIONS

Bauer et al., Monitoring personal fine particle exposure with a particle counter. J Expo Anal Environ Epidemiol. May-Jun. 1999;9(3):228-36. cited by applicant

Bell et al., Reassessment of the lethal London fog of 1952: novel indicators of acute and chronic consequences of acute exposure to air pollution. Environ Health Perspect. Jun. 2001;109(Suppl 3):389-94. cited by applicant

Chua et al., Electrical Mobility Separation of Airborne Particles Using Integrated Microfabricated Corona ionizer and Separator Electrodes. Journal of Microelectromechanical Systems. Feb. 2009;18(1):4-13. cited by applicant

Chung et al., Comparison of real-time instruments used to monitor airborne particulate matter. J Air Waste Manag Assoc. Jan. 2001;51(1):109-20. cited by applicant

Dylos Corporation, DC1100 Air Quality Monitor. User Manual. 19 pages, (2008). cited by applicant

Dylos Corporation, DC1100-PRO Air Quality Monitor, User Manual. 19 pages, (2008). cited by applicant

Dylos Corporation, DC1700 Air Quality Monitor, User Manual. 27 pages, (2010). cited by applicant

Erickson et al., Design of a Small, Battery-Operated Nanoparticle Sizer. NSTI-Nanotech. 2012;1:34-37. cited by applicant

Esmen et al., Theoretical Investigation of the Interrelationship Between Stationary and Personal Sampling in Exposure Estimation. Applied Occupational and Environmental Hygiene. Nov. 30, 2010; 15(1):114-119. cited by applicant

Fluke, 985, Airborne Particle Counter, Users Manual, 32 pages, Mar. 2012. cited by applicant

Freescale Semiconductor, Inc., Data Sheet: Technical Data: High Temperature Accuracy Integrated Silicon Pressure Sensor for Measuring Absolute Pressure, On-Chip Signal Conditioned, Temperature Compensated and Calibrated. Document No. MP3H6115A, Rev 5.1, 13 pages, May 2012. cited by applicant

Freescale Semiconductor, Inc., Integrated Silicon Pressure Sensor On-Chip Conditioned Temperature Compensated and Calibrated. MPXV5004G, Rev 12, 22 pages, Sep. 2009. cited by applicant

Giorio et al., Field comparison of a personal cascade impactor sampler, an optical particle counter and CEN-EU standard methods for PM10, PM2.5 and PM1 measurement in urban environment. Journal of Aerosol Science. 2013;65:111-120. cited by applicant

Golczewski et al., Performance Modelling and Response of the Dual-wavelength Optical Particle Spectrometer (DWOPS). Abstracts of the European Aerosol Conference. 2004, pp. S839-S840. cited by applicant

Hach, Met One 7000: 7005, 7015, Doc026.53.80360, Edition 1. User Manual. 32 pages, Jul. 2013. cited by applicant

Hal Technology, HAL-HPC600 Handheld Particle Counter, Operational Manual. 30 pages, (2008). cited by applicant

Hal Technology, Six-Channel Hybrid Handheld Particle Counter. 2 pages. cited by applicant

Howard-Reed et al., Use of a continuous nephelometer to measure personal exposure to particles during the U.S. Environmental Protection Agency Baltimore and Fresno Panel studies. J Air Waste Manag Assoc. Jul. 2000;50(7):1125-32. cited by applicant

Li et al., On the Feasibility of a No. Concentration Calibration Using a Wafer Surface Scanner. Aerosol Science and Technology. 2014;48:747-57. cited by applicant

Pope et al., Lung cancer, cardiopulmonary mortality, and long-term exposure to fine particulate air pollution. JAMA. Mar. 6, 2002;287(9):1132-41. cited by applicant

RTI International, MicroPEM™ - PM2.5 Personal Exposure Monitor. www.rti.org, 2 pages. cited by applicant

SAS, Sentry Air Systems, Inc., Portable Particle Counter, Model #PPC-1. 1 page. cited by applicant

Schaap et al., Continuous Size-Separation of Airborne Particles in a Microchannel for Aerosol Monitoring. IEEE Sensors Journal. Nov. 2011;11(11):2790-7. cited by applicant

Schaap et al., Transport of airborne particles in straight and curved microchannels. Physics of Fluids. 2012;24 (8):083301, 14 pages. cited by applicant

Sharp, GP2Y1010AUOF, Compact Optical Dust Sensor. Sharp Corporation. Data Sheet, 9 pages, Dec. 1, 2006. cited by applicant

Thermo Electron Corporation, Models: PDR-1000AN & PDR-1200S, Personal Dataram Particulate Monitoring, Instruction Manual. www.thermo.com/ih. 54 pages, Jan. 2004. cited by applicant

Thermo Scientific, MIE pDR-1500. Instruction Manual, Active Personal Particulate Monitor, Part No. 105983-00. Thermo Fisher Scientific, Inc. 112 pages, Jan. 31, 2014. cited by applicant

Thermo Scientific, Model pDR-AN/1200, personalDATARAM Instruction Manual. Particulate Monitor, Part No. 100181-00. Thermo Fisher Scientific, Inc. 56 pages, May 15, 2013. cited by applicant

TSI Incorporated, TSI Aerotrak Portable Particle Counter Model 9110, Application Note CC-107. Retrieved online at: https://www.tsi.com/getmedia/f7a6a0a2-cb7d-4c25-9674-b920b77d5835/AeroTrak_Portable_Particle_Counter_9110_A4_CC-107?ext=.pdf. 9 pages, (2013). cited by applicant

Tsi, Aerosol Instrument Manager Software for Scanner Mobility Particle Sizer (SMPS) Spectrometer. User's Manual. P/N 1930038, Revision H. 119 pages, Apr. 2010. cited by applicant

Tsi, AeroTrak Handheld Airborne Particle Counter, Model 9306, Operation Manual. P/N 6004215, Revision C. 81 pages, Feb. 2011. cited by applicant

TSI, Aero Trak Portable Airborne Particle Counter, Model 9110, Operation Manual, P/N 6004345, Revision A. 93 pages, Jul. 2010. cited by applicant

TSI, Model 3330 Optical Particle Sizer Spectrometer, Operation and Service Manual. P/N 6004403, Revision C. 114 pages, Jan. 2011. cited by applicant

TSI, Optical Particle Sizer, Model 3330, Specifications. 4 pages, (2010). cited by applicant

TSI, Sidepak™ Personal Aerosol Monitor, Model AM510, User Guide. TSI Incorporated, 74 pages, (2012). cited by applicant

Walton et al., Aerosol Instrumentation in Occupational Hygiene: An Historical Perspective. Aerosol Science and Technology. 1998;28(5):417-38. cited by applicant

Primary Examiner: Rahman; Md M

Attorney, Agent or Firm: McCarter & English, LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of, and claims priority to U.S. Utility patent application Ser. No. 18/102,208, filed on Jan. 27, 2023, which is a continuation of, and claims priority to U.S. Utility patent application Ser. No. 17/512,406, filed on Oct. 27, 2021, which is a continuation of, and claims priority to, U.S. Utility patent application Ser. No. 16/537,492, filed on Aug. 9, 2019, which is a continuation of, and claims priority to, U.S. Utility patent application Ser. No. 16/443,508, filed on Jun. 17, 2019, which

is a continuation of, and claims priority to, U.S. Utility patent application Ser. No. 14/214,876, now U.S. Pat. No. 10,352,844, filed on Mar. 15, 2014, which claimed priority to U.S. Provisional Application Ser. No. 61/786,642 filed on Mar. 15, 2013, U.S. Provisional Application Ser. No. 61/786,616 filed on Mar. 15, 2013, U.S. Provisional Application Ser. No. 61/786,651 filed on Mar. 15, 2013, U.S. Provisional Application Ser. No. 61/786,658 filed on Mar. 15, 2013, and U.S. Provisional Application Ser. No. 61/786,667 filed on Mar. 15, 2013, the contents of all of the above-referenced applications hereby incorporated in their entirety. (2) This application is related to and incorporates by reference U.S. Non-Provisional application Ser. No. 14/214,899, filed herewith on Mar. 15, 2014, titled PARTICLE COUNTER WITH INTEGRATED BOOTLOADER by inventor David Pariseau; U.S. Non-Provisional application Ser. No. 14/214,870, filed herewith on Mar. 15, 2014, titled PERSONAL AIR QUALITY MONITORING SYSTEM by inventors David Pariseau and Adam Giandomenico; U.S. Non-Provisional application Ser. No. 14/214,903, filed herewith on Mar. 15, 2014, titled MIXED-MODE PHOTO-AMPLIFIER FOR PARTICLE COUNTER by inventors David Pariseau and Ivan Horban; U.S. Non-Provisional application Ser. No. 14/214,889, filed herewith on Mar. 15, 2014, titled INTELLIGENT MODULES IN A PARTICLE COUNTER by inventor David Pariseau; U.S. Non-Provisional application Ser. No. 14/214,895, filed herewith on Mar. 15, 2014, titled PULSE SCOPE FOR PARTICLE COUNTER by inventor David Pariseau; and U.S. Non-Provisional application Ser. No. 14/214,907, filed herewith on Mar. 15, 2014, titled PULSE DISCRIMINATOR FOR PARTICLE COUNTER by inventors David Pariseau and Ivan Horban.

BACKGROUND

(1) Particle counters have been used for decades in manufacturing or industrial applications to measure particulate quantities in air, gases or liquids. Typically such counters would also bin particulates by size. These size bins vary by application and often by instrument. A particle counter has at least one size channel and popular counters can have 6 or more channels. Typically these size channels discriminate pulses based on the pulse height of the incoming signal. The pulse height refers to the peak voltage of the signal. Sometimes there is also rudimentary discrimination of pulse width, often in hardware.

(2) These systems provide a go/no-go qualification for an incoming pulse, typically they are implemented in hardware and provide a simple gate function such that pulses below a minimum duration are excluded from counting. The intent is to reject noise, typically at the most sensitive resolution where the signal-to-noise ratio is the poorest. However such particle counters are limited in their scope of particle size they can detect, are difficult to calibrate and don't have a means for detecting equipment failure. Therefore, what is needed is a system and method that allows detection of a wide range of particle sizes that is easy to calibrate and determine failures.

SUMMARY

(3) In accordance with various aspects and teachings of the present invention, a system and method are provided that allow detection of a wide range of particle sizes. The foregoing is a summary and includes, by necessity, simplifications, generalizations and omissions of detail. Those skilled in the art will appreciate that the summary is illustrative only and is not intended to be in any way limiting.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The foregoing summary as well as the following detailed description is better understood when read in conjunction with the appended drawings. For the purpose of illustrating the invention, there is shown in the drawings exemplary constructions of the invention; however, the invention is not limited to the specific various aspects, embodiments, methods and instrumentalities disclosed in the

drawings.

(2) FIG. 1 shows a system in accordance with the various aspects of the present invention.

(3) FIG. 2 shows a system in accordance with the various aspects of the present invention.

(4) FIG. 3 shows a system in accordance with the various aspects of the present invention.

(5) FIG. 4 shows a graph for figures from the Center for Disease Control (CDC) regarding the current state of asthma.

(6) FIG. 5 shows a system in accordance with the various aspects of the present invention.

(7) FIG. 6 shows a clip-on device incorporating a system in accordance with the various aspects of the present invention.

(8) FIG. 7 shows a wrist watch incorporating a system in accordance with the various aspects of the present invention.

(9) FIG. 8 shows a pendant incorporating a system in accordance with the various aspects of the present invention.

(10) FIG. 9 shows a personal device incorporating a system in accordance with the various aspects of the present invention.

DETAILED DESCRIPTION

(11) It is noted that, as used in this description, the singular forms “a,” “an” and “the” include plural referents unless the context clearly dictates otherwise. Reference throughout this specification to “one aspect,” “another aspect,” “at least one aspect,” “various aspects,” “further aspect,” “one embodiment,” “an embodiment,” “certain embodiments,” or similar language means that a particular aspect, feature, structure, or characteristic described in connection with the embodiment or embodiments is included in at least one aspect or embodiment of the present invention. Thus, appearances of the phrases “in accordance with one aspect,” “in accordance with various aspects,” “in accordance another aspect,” “one embodiment,” “in at least one embodiment,” “in an embodiment,” “in certain embodiments,” and similar language throughout this specification may, but do not necessarily, all refer to the same embodiment.

(12) In accordance with the various aspects of the present invention, a device includes a computing device. As referred to herein, the devices may be part of a system or the system. It may be implemented to include a central processing unit (e.g., a processor), memory, input devices (e.g., keyboard and pointing devices), output devices (e.g., display devices), and storage device (e.g., disk drives). The memory and storage device are computer-readable media that may contain instructions or code that, when executed by the processor or the central processing unit, cause the device to perform certain tasks. In addition, data structures and message structures may be stored or transmitted via a data transmission medium, such as a signal on a communications link. Various communications channels may be used (e.g., the Internet, a local area network (LAN), a wide area network (WAN), or a point-to-point dial-up connection, or any other wireless channel or protocol) to create a link.

(13) In accordance with the various aspects of the present invention, the device or system may be use various computing systems or devices including personal computers, server computers, hand-held or laptop devices, multiprocessor systems, microprocessor based systems, programmable consumer electronics, network personal computers (PCs), minicomputers, mainframe computers, distributed computing environments that include any of the above systems or devices, and the like. In accordance with the various aspects of the present invention, the device or system may also provide its services to various computing systems such as personal computers, cell phones, personal digital assistants, consumer electronics, home automation devices, and so on.

(14) In accordance with the various aspects of the present invention, the device or system may be described in the general context of computer-executable instructions, such as program modules or code, which is executed by one or more computers or devices. Generally, program modules include routines, programs, objects, components, data structures, and so on that perform particular tasks or implement particular data types. Typically, the functionality of the program modules may be

combined or distributed as desired in various embodiments.

(15) Where a range of values is provided, it is understood that each intervening value, to the tenth of the unit of the lower limit unless the context clearly dictates otherwise, between the upper and lower limit of that range and any other stated or intervening value in that stated range, is encompassed within the aspects of the present invention. The upper and lower limits of these smaller ranges may independently be included in the smaller ranges and are also encompassed within the aspects of the present invention, subject to any specifically excluded limit in the stated range. Where the stated range includes one or both of the limits, ranges excluding either or both of those included limits are also included in the aspects of the present invention.

(16) Referring now to FIG. 1, an example of a four-channel particle counter front-end **150** is shown below. In this example a beam present between the laser diode (**101**) and the beam stop (**102**) scatters light (**103**) as particles cross that beam. Typically the scattered light (**103**) is focused by one or more reflectors (**112**) onto the face of a photo-diode (**104**) on a photo-amplifier board (**100**). The tiny current in the photo-diode is then pre-amplified, usually by a trans-impedance amplifier (**105**). The pre-amplified signal is usually available on a calibration channel (**106**) for use during calibration. The pre-amplifier (**105**) signal is also sent to one or more amplifiers. In this case there are two, a low-gain channel (**107**) and a high-gain channel (**108**).

(17) These amplifiers further increase the signal amplitude and transmit send it, often, to a separate particle counting board (**120**). On this board the incoming pulse signals are sorted into size bins. In this example there are four channels, two channels (**122, 123**) connected to the high-gain amplifier (**111**) and two channels (**124, 125**) connected to the low-gain amplifier (**110**). The threshold comparators (**122, 123, 124, 125**) are setup during the calibration phase so that they each channel counts pulses above some threshold. This can be a manual process with manual adjustment of a potentiometer, or a programmatic process where firmware would set a digital potentiometer or digital-to-analog converter. The counter outputs (**126, 127, 128, 129**) would then be read by microcontroller and displayed to the user.

(18) A similar system functions for gases other than air, and liquids. It also functions for counters that use a light-blocking rather than a light-scattering architecture, except that pulses in light-blocking systems see a decrease in light as the particles pass through the beam.

(19) Traditionally, only a single sensor block and photo-amplifier board (**100**) is used in an instrument. This is largely due to the cost, and complexity of these sub-assemblies which often make-up the bulk of the cost of an instrument. It is also due to the processing requirements on the counter board.

(20) With the advent of miniaturization, lower-cost components, increases in processing power the possibility of combining multiple particle sensor blocks into a single instrument becomes possible.

(21) In certain embodiments, a counter includes multiple sensor block/photo-amplifier sub-assemblies within a single counter instrument. Each of these blocks would be communicatively coupled, e.g. connected, to a common counter board, or alternatively each of these blocks could have individual counter interface boards which might then provide processed data to a common instrument board which would manage the display, and external interfaces.

(22) In certain embodiments, the airstream is split into multiple segments, each with a respective sensor block. Such an embodiment means that: the particle velocity is slowed for each sensor given a fixed sample volume, this means that the system gets more signal per particle and thus can develop a more sensitive instrument (on all channels); the system can use a count comparator to correlate counts between multiple sensors, which would allow for: failure notification, since one failed sensor will mean a loss of count uniformity, calibration notification, since count uniformity will degrade, and redundancy, ability for remaining sensors to estimate counts for a failed sensor; and the system can assign different sensors for different size ranges, and end-up with a sensor with a much larger dynamic range.

(23) In certain embodiments, separate sensor blocks sample different airstreams. For example,

instruments with multiple sensors can: check that filtration is working as expected. By sampling air from either side of the filter simultaneously, the system can check that particulate counts from two or more sensors reflect a functioning filter; check that manufacturing equipment is operating as expected. By sampling air from various areas around a particular piece of equipment, the system can ensure that particulate levels are what is expected. Doing so with a single instrument allows us to correlate these counts and make decisions that involve more than a single threshold; and allow for an upgrade path for manifold systems that currently share a sensor block and switch airstreams between samples, sharing a single block, which means that there is no continuous sampling of all channels. By replacing this with a counter multiple chambers, the manifold installation could be made continuous, at a lower cost than providing individual instruments for each channel.

(24) Referring now to FIG. 2, one such architecture, shown below as system 400, would provide two or more sensor blocks (200) having process the Gain Outputs (210, 211), the two or more sensor blocks (200) being communicatively coupled to a common counter board (220) which would implement the threshold comparators (221) and counters (222).

(25) Referring now to FIG. 3, an alternative architecture is shown as system 500, based on the figure below, system 500 provides two or more of these sensor blocks combined with integrated counters (300). These Output Gain channels (307, 308) would interface to on-board Threshold comparators (315) and then to on-board Counters (316). These would be managed and accessed via an external interface (318). This interface could be any number of things, from a microcontroller with some type of standard interface like UART, SPI, I2C, UNIO, PMP, etc. to a custom interface like a memory mapped I/O interface for an off-board controller.

(26) Regardless of the actual interface used, an off-board system would be used to setup and access the counter data for local processing, manipulation, display, etc. or to communicate this data to an external system.

(27) Another option would be to have the sensor block have local processing beyond the typical Threshold Comparator and Counter implementation, such that pulse-height was measured for each pulse, and perhaps other parameters like pulse-width, time-of-arrival, etc. With such local processing it would allow the creation of intelligent sensors that could have a configurable number of channels, each with configurable thresholds.

(28) And, going the other way, the sensors could simply consist of the sensor chamber, the light components, photo-detector and pre-amplifier with everything else being integrated into one or more printed circuit boards.

(29) In certain embodiments, a single block could be created with multiple chambers in it, each with its own light source (or they could use a shared light source split from one laser and routed to each chamber) and then a single printed circuit board with all the electronics for the entire instrument.

(30) In certain embodiments, more than one chamber is present in an instrument to provide enhanced or otherwise unavailable performance or functionality and that the information from these chambers is processed by one or more sub-systems within the instrument and/or forwarded to some external system for post-processing, analysis, reporting, etc.

(31) With the increase of miniaturization of portable electronic products like heart-rate monitors, sophisticated pedometers, glucose monitors, insulin pumps, electro-encephalographs integrated with smart-phones, etc. People are increasingly carrying sophisticated instrumentation on or about their persons. Couple this with the increase of people with respiratory problems, and the growing proliferation of medicines, filtration equipment, masks, etc., there is a compelling case for creating a product that would alert the user to conditions that might aggravate respiration or bring-on asthma or other such attacks.

(32) Referring now to FIG. 4, shown are recent figures from the Center for Disease Control (CDC) regarding the current state of asthma (a widespread respirator condition).

(33) The number of people with asthma continues to grow. One in 12 people (about 25 million, or

8% of the population) had asthma in 2009, compared with 1 in 14 (about 20 million, or 7%) in 2001.

(34) More than half (53%) of people with asthma had an asthma attack in 2008. More children (57%) than adults (51%) had an attack. 185 children and 3,262 adults died from asthma in 2007.

(35) About 1 in 10 children (10%) had asthma and 1 in 12 adults (8%) had asthma in 2009. Women were more likely than men and boys more likely than girls to have asthma.

(36) About 1 in 9 (11%) non-Hispanic blacks of all ages and about 1 in 6 (17%) of non-Hispanic black children had asthma in 2009, the highest rate among racial/ethnic groups.

(37) The greatest rise in asthma rates was among black children (almost a 50% increase) from 2001 through 2009.

(38) Therefore what is needed is a system and method that allows an individual to monitor particles that affect an individual.

(39) In accordance with the various aspects and embodiments of the present invention, a system and method are disclosed that allow an individual to monitor particles that affect an individual.

(40) Particles affect the performance of athletes and individuals that suffer from a medical condition. Particles affect everyone, since at some threshold an individual is susceptible. Thus, an early warning indication of particulates above some threshold would allow individuals to make informed decisions about changing their environment or circumstances and thereby perhaps avoid compromising their health or having to take medications to alleviate symptoms or conditions exacerbated by particulates. Particles may include pollutants as well as naturally occurring particles, such as like pollen etc., which pose health issues. It would be an advance in the art of particulate detection to provide data about particles in an individual's ambient environment to the individual.

(41) A device that a user carried on or about his or her person, that monitored the local air quality and provided early warning of worsening air quality would allow the user to take measures to avoid being exposed to the environment and thereby avoid episodes of compromised or aggravated respiration, and perhaps also eliminate the need to take medications to alleviate such.

(42) Particle counters are typically used in manufacturing or industrial applications to measure particulate quantities in air, gases or liquids. Typically such counters also bin particulates by size. These size bins vary by application and often by instrument. A particle counter has at least one size channel and popular counters can have 6 or more channels. Typically these size channels discriminate pulses based on the pulse height of the incoming signal. The pulse height referring to the peak voltage of the signal. Sometimes there is also rudimentary discrimination of pulse width, often in hardware.

(43) In certain embodiments, an air quality monitoring system, such as a portable particle detection system, is worn or carried by a user to provide real-time monitoring of the air quality in their local environment.

(44) Referring now to FIG. 5, illustrated is an embodiment of an air quality monitoring system (550), also referred to as "personal particle counter" or "personal counter" or "personal counter device." Here, air is passed through a light beam generated by a light source (501) where particles scatter light (504). The airstream is generated by a fan or blower (512) or some other air impeller where air is drawn or pushed into the enclosure and is routed in such a way as to pass through the beam. In certain embodiments, the light source is a laser diode, a light-emitting-diode, or the equivalent. The light is focused by a lens to create a ribbon of light through which the airstream passes, in order to provide controlled scattering of light by particle size. In another implementation, a light blocking system is utilized, in which a beam is presented to a photo-diode and particles obscure the beam as they pass through it, thereby providing the signal.

(45) In the case of a light-scattering system. Light scattered by particles in the stream (504) gets collected by a reflector (503) and presented to the photo-detector (505) and the resulting signal is amplified by the pre-amplifier stage (506), such as a trans-impedance amplifier. In some cases a

second amplification (507) is utilized and the resulting electrical signal is used to drive one or more threshold comparators (510, 511). The outputs of the threshold comparators (510, 511) is used as inputs to counter channels within the microcontroller (520). These counts are used to determine the quality of the air. In this case there are two separate channels, which could be setup to different counts for particles of different sizes.

(46) The air quality monitoring system (550) is powered locally by a battery (531), which is charged from some external power source. A large number of charging techniques are possible including, but not limited to: an external power connector, power from some external wired interface, wireless (inductive) charging, a solar cell, local charging from energy harvesting means. The battery power is managed locally via the Power Management circuit (530) that provided regulated power to the on-board circuitry (including the analog circuits (amplifiers, comparators, etc.)) and the digital circuitry (microcontroller, internal/external interfaces).

(47) Here, the Internal/External user interfaces (535) is communicatively coupled to the threshold comparator. In certain embodiments, the Internal/External user interfaces (635) comprise one or more of these non-limiting features: an on-board display, liquid-crystal-display (LCD) or other, to display current air quality status, air-quality over time, cumulative particulate mass, graphs, charts, etc. or other air quality, an on-board memory (volatile or non-volatile) to store or log historic air quality data (for display use or later retrieval and reporting or analysis), an on-board eccentric-rotating-mass (ERM) motor, to provide vibration to alert or interface with user, an on-board audio transducer, to provide sound to alert or interface with user, one or more push-buttons on-board, to interface with user, an on-board wired interface channel for communication with external devices, an on-board wired interface to allow the battery to be charged, and an on-board wireless communications interface channel for communication with external devices.

(48) The above gives a general overview of the invention with some of the interface options. In certain embodiments, the air quality monitoring system (550) is embodied in a carrying means that takes on the structure of any of a plurality of form-factors, not limited by the examples provided below:

(49) Referring to FIG. 6, a clip-on version (600) is shown. In this embodiment, the device has an integrated clip (603) which can be implemented a large number of ways: molded piece of deformable material, spring tensioned pivot, etc. In this example the air enters the unit on the right (601) and exits the device on the left (602). Though the example describes an integrated clip (where it is part of the enclosure), it could also just as easily be implemented with a clip mounted to an external holder that is used to capture and carry the device.

(50) Referring now to FIG. 7, a wrist-watch or armband version (710) is shown. In this embodiment, the device is housed in a wristwatch type form factor with mounts to attach standard watch-bands (714). The air quality monitoring system (600), shown here as personal counter device (711), is configured to be worn on a wrist or arm of the person. In one embodiment, the personal counter device 711 takes the place a wristwatch, for example. Alternatively, the personal counter device 711 is integrated with a wristwatch to also provide time-keeping functionality. The air in this example enters from the top (712) and exits from the bottom (713).

(51) Referring now to FIG. 8, a pendant or necklace version (820) is shown. In this embodiment, the device is housed in a pendant form factor. The air quality monitoring system (800), shown here as the personal counter device (821), is hung from a pendant loop (824), which could be a chain, cord, string, or some other string-like material. In some implementations, the personal counter device (821) is also decorative as in a fashionable necklace or some such. In this example the air enters from the top (822) and exits from the bottom (823).

(52) Referring now to FIG. 9, a personal device or Mobile-phone version (900) is shown. In this embodiment, the device is housed as an adjunct to or as a holder for a mobile or smart phone (902). In the example below, the personal counter device (904) is attached to the docking port of the Mobile Phone (902) in order to provide a wired interface. Alternatively or in combination, the

personal counter **904** is molded into a holder for the phone and communicates with the phone wirelessly (via Bluetooth or WiFi for example). In this example the air enters from the top (**910**) and exits from the bottom (**912**).

(53) In accordance with various aspects of the present invention, other possible embodiments include: a broach form-factor that could be pinned or clipped to a garment or purse or something similar, a carrier to allow it to be mounted in a vehicle, a carrier to allow it to be mounted to a bicycle or motorbike, a carrier for a golf-cart, an armband that can be worn, perhaps during sporting activities or training, and in a pair of glasses, perhaps with a heads-up display projected on one or more lenses.

(54) Again many embodiments are possible for such a personal device, and the above embodiments are meant only to provide a sense of this variety rather than to attempt to describe the entire scope of possible embodiments.

(55) While various embodiments have been described above, it should be understood that they have been presented by way of example only, not limitation, and various changes in form and details may be made. Any portion of the device, instrument, apparatus and/or methods described herein may be combined in any combination, except mutually exclusive combinations. The aspects and embodiments described herein can include various combinations and/or sub-combinations of the functions, components and/or features of the different embodiments described. For example, multiple, distributed processing systems can be configured to operate in parallel.

(56) Although the present invention has been described in detail with reference to certain embodiments, one skilled in the art will appreciate that the present invention can be practiced by other than the described embodiments, which have been presented for purposes of illustration and not of limitation. Therefore, the scope of the appended claims should not be limited to the description of the embodiments contained herein.

(57) It will be apparent that various aspects of the present invention as related to certain embodiments may be implemented in software, hardware, application logic, or a combination of software, hardware, and application logic. The software, application logic and/or hardware may reside on a server, an electronic device, or be a service. If desired, part of the software, application logic and/or hardware may reside on an electronic device and part of the software, application logic and/or hardware may reside on a remote location, such as server.

(58) In accordance with the aspects disclosed in the teachings of the present invention and certain embodiments, a program or code may be noted as running on a device, an instrument, a system, or a computing device, all of which are an article of manufacture. Additional examples of an article of manufacture include: a server, a mainframe computer, a mobile telephone, a multimedia-enabled smartphone, a tablet computer, a personal digital assistant, a personal computer, a laptop, or other special purpose computer each having one or more processors (e.g., a Central Processing Unit, a Graphical Processing Unit, or a microprocessor) that is configured to execute a computer readable program code (e.g., an algorithm, hardware, firmware, and/or software) to receive data, transmit data, store data, or perform tasks and methods. Furthermore, an article of manufacture (e.g., device) includes a non-transitory computer readable medium having a series of instructions, such as computer readable program steps or code, which is encoded therein. In certain aspects and embodiments, the non-transitory computer readable medium includes one or more data repositories, memory, and storage, including non-volatile memory. The non-transitory computer readable medium includes corresponding computer readable program or code and may include one or more data repositories. Processors access the computer readable program code encoded on the corresponding non-transitory computer readable mediums and execute one or more corresponding instructions. Other hardware and software components and structures are also contemplated.

(59) Unless defined otherwise, all technical and scientific terms used herein have the same meaning as commonly understood by one of ordinary skill in the art to which this invention belongs.

Although any methods and materials similar or equivalent to those described herein can also be

used in the practice of the present invention, representative illustrative methods and materials are described herein.

(60) All publications and patents cited in this specification are herein incorporated by reference as if each individual publication or patent were specifically and individually indicated to be incorporated by reference and are incorporated herein by reference to disclose and describe the methods and/or system in connection with which the publications are cited. The citation of any publication is for its disclosure prior to the filing date and should not be construed as an admission that the present invention is not entitled to antedate such publication by virtue of prior invention. Further, the dates of publication provided may be different from the actual publication dates which may need to be independently confirmed.

(61) All statements herein reciting principles, aspects, and embodiments of the invention as well as specific examples thereof, are intended to encompass both structural and functional equivalents thereof. Additionally, it is intended that such equivalents include both currently known equivalents and equivalents developed in the future, i.e., any elements developed that perform the same function, regardless of structure. The scope of the present invention, therefore, is not intended to be limited to the exemplary embodiments shown and described herein. Rather, the scope and spirit of present invention is embodied by the appended claims.

Claims

1. A portable particle counter apparatus, comprising: a device housing for an optical particle counter having a form factor enabling the device housing to be carried during operation by a user; an air intake and outlet fluidly connected to a chamber in the device housing wherein an airstream passes through the chamber; a light source in the device housing that emits a beam of light that passes through the airstream passing through the chamber; a light detector in the device housing that detects light that passes through the airstream in the chamber, the light detector configured to detect airborne particles passing through the beam of light in the airstream traversing from the air intake to the outlet; an analog circuit in the device housing connected to the light detector, the analog circuit including at least one amplifier in communication with the light detector, the at least one amplifier configured to convert signals from the light detector into amplified electrical pulses; a microcontroller configured to count particles from the user's local environment that are detected passing through the chamber wherein the microcontroller processes particle count data from signals received from the analog circuit; and at least one external communications interface communicatively coupled with the microcontroller that transfers particle count data to a mobile phone.
2. The portable particle counter apparatus of claim 1 wherein the analog circuitry further comprises at least one threshold comparator configured to process the amplified electrical pulses from the at least one amplifier and produce at least one output based on any pulse above a threshold pulse height that is a peak voltage of the amplified electrical pulse, the threshold associated with at least one particle size channel.
3. The portable particle counter apparatus of claim 1, further comprising: an integrated LCD display configured to display information related to the particle count data.
4. The portable particle counter apparatus of claim 3 wherein the integrated display is configured to display information related to air quality over time.
5. The portable particle counter apparatus of claim 3 wherein the integrated display is configured to display information related to a cumulative particulate mass.
6. The portable particle counter apparatus of claim 1 further comprising an integrated display is configured to display a current air quality status of the user's local environment.
7. The portable particle counter apparatus of claim 1 further comprising an integrated display wherein information related to detected airborne particulates is displayed in a graph or chart on the

integrated display.

8. The portable particle counter apparatus of claim 1 further comprising an integrated display that is configured to display information related to historic air quality logged to a memory.

9. The portable particle counter apparatus of claim 1 further comprising an integrated display that is configured to display particle counts associated with the plurality of different particle size channels, the apparatus further comprising an alarm to alert the user to a detected particle count level above a threshold or a cumulative particulate mass.

10. The portable particle counter apparatus of claim 1 wherein the device housing has a clip to attach the apparatus to clothing of a user.

11. The portable particle counter apparatus of claim 1 wherein the apparatus communicates with a mobile phone by wired or wireless interface.

12. The portable particle counter apparatus of claim 1 wherein the apparatus is configured to be worn by a user.

13. The portable particle counter apparatus of claim 1 wherein the light source comprises a light emitting diode.

14. The portable particle counter of claim 1 wherein the external connection interface comprises a wireless connection.

15. The portable particle counter of claim 14 wherein the wireless connection comprises at least one of a Bluetooth™ and a WiFi link.
