

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12407917
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Hyun; Daeyoung et al.

Electronic device and method for generating image by applying effect to subject and background

Abstract

At least one processor included in an electronic device may execute a camera, detect at least one object based on image data obtained through the camera in a first light source environment, analyze color properties of the detected at least one object, determine a first effect based on the analyzed color properties of the object, apply a second light source effect to the at least one object, the second light source effect being different from the first light source, and apply the first effect to a background except the at least one object. Various other embodiments identified through the specification are possible.

Inventors: Hyun; Daeyoung (Suwon-si, KR), Kim; Changhoon (Suwon-si, KR), Ahn; Byeongyong (Suwon-si, KR), Jang; Seulki (Suwon-si, KR)

Applicant: Samsung Electronics Co., Ltd. (Suwon-si, KR)

Family ID: 80117427

Assignee: SAMSUNG ELECTRONICS CO., LTD. (Gyeonggi-Do, KR)

Appl. No.: 18/105331

Filed: February 03, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230188831 A1	Jun. 15, 2023

Foreign Application Priority Data

KR	10-2020-0097491	Aug. 04, 2020
----	-----------------	---------------

Related U.S. Application Data

Publication Classification**Int. Cl.:** **H04N23/63** (20230101); **H04N23/611** (20230101); **H04N23/74** (20230101)**U.S. Cl.:****CPC** **H04N23/632** (20230101); **H04N23/611** (20230101); **H04N23/74** (20230101);**Field of Classification Search****CPC:** H04N (23/632); H04N (23/611); H04N (23/74); H04N (9/74); G06T (7/11); G06T (7/194); G06T (7/90); G06T (15/50); G06T (2207/10024)

References Cited**U.S. PATENT DOCUMENTS**

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
10171744	12/2018	Kitajima	N/A	N/A
10181210	12/2018	Lee et al.	N/A	N/A
10482346	12/2018	Kim et al.	N/A	N/A
10528243	12/2019	Manzari et al.	N/A	N/A
10740959	12/2019	Johnson et al.	N/A	N/A
11263469	12/2021	Kim et al.	N/A	N/A
12079974	12/2023	Li et al.	N/A	N/A
2006/0182367	12/2005	Moghaddam	N/A	N/A
2016/0112654	12/2015	Seo	348/333.12	G01J 3/463
2017/0228867	12/2016	Baruch	N/A	G06T 7/12
2017/0337693	12/2016	Baruch	N/A	G06T 7/12
2018/0349008	12/2017	Manzari	N/A	H04N 23/632
2019/0080508	12/2018	Johnson	N/A	H04N 23/631
2019/0364201	12/2018	Hirai et al.	N/A	N/A
2020/0204775	12/2019	Kitajima	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2013149219	12/2012	JP	N/A
2013171433	12/2012	JP	N/A
6287102	12/2017	JP	N/A
6700840	12/2019	JP	N/A
20140134844	12/2013	KR	N/A
20160016574	12/2015	KR	N/A
20160021607	12/2015	KR	N/A
20160144851	12/2015	KR	N/A
20190142397	12/2018	KR	N/A
20200043432	12/2019	KR	N/A
102140295	12/2019	KR	N/A
2018226264	12/2017	WO	N/A

OTHER PUBLICATIONS

International Search Report with Written Opinion for International Application No. PCT/KR2021/009727; International Filing Date Jul. 27, 2021; Date of Mailing Nov. 11, 2021; 57 pages. cited by applicant
Korean Office Action corresponding to Application No. KR10-2020-0097491; Issue Date Aug. 22, 2024. cited by applicant

Primary Examiner: Haskins; Twyler L

Assistant Examiner: Morehead, III; John H

Attorney, Agent or Firm: CANTOR COLBURN LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of International Application No. PCT/KR2021/009727 designating the United States, filed on Jul. 27, 2021, in the Korean Intellectual Property Receiving Office and claiming priority to Korean Patent Application No. 10-2020-0097491, filed on Aug. 4, 2020, in the Korean Intellectual Property Office, the disclosures of all of which are incorporated by reference herein in their entireties.

TECHNICAL FIELD

(1) Embodiments disclosed in this document relate to an electronic device and a method for applying light source effects or color effects to an image captured by a camera.

BACKGROUND ART

(2) Taking selfies using a front camera of a portable electronic device is on the rise, and a function of applying various image effects to a selfie image is required to satisfy various personalities of people taking a picture.

(3) As the demand for image effects increases as described above, manufacturers of portable electronic devices and application developers thereof are developing and applying various image effects. A method of applying image effects includes a method of applying effects stored in a portable electronic device to the entire preview image and a method of applying various effects to a captured and stored image through an editing function.

DISCLOSURE OF INVENTION**Technical Problem**

(4) In the past, desired image effects were simply applied through user input, and even when a light source effect is desired to be changed, the direction of a desired light source and the intensity of a light source are applied through user input.

(5) In addition, since virtual light source effects or color effects are simply applied to the foreground or one effect is applied to the entire image including a foreground and a background in the existing technology, there is a limit to applying the effects separately to the foreground and the background.

Solution to Problem

(6) Various embodiments of the disclosure may provide an electronic device that applies a virtual light source effect suitable for an object by analyzing the characteristics of a light source applied during photographing and applies a color effect different from the light source effect to a background, and a method for controlling the electronic device.

(7) An electronic device according to an embodiment disclosed in this document may include a camera and at least one processor electrically connected to the camera. The at least one processor may execute the camera, detect at least one object, based on image data obtained through the camera in a first light source environment, analyze color properties of the at least one detected object, determine a first effect, based on the analyzed color properties of the object, apply a second light source effect different from the first light source to the at least one object, and apply the first effect to a background, excluding the at least one object.

(8) In addition, a method of operating an electronic device according to an embodiment disclosed in this document may include executing a camera, detecting at least one object, based on image data obtained through the camera in a first light source environment, analyzing color properties of the at least one detected object, determining a first effect, based on the analyzed color properties of the object, applying a second light source effect different from the first light source to the at least one object, and applying the first effect to a background, excluding the at least one object.

(9) In addition, an electronic device according to an embodiment disclosed in this document may include a camera and at least one processor electrically connected to the camera. The at least one processor may execute the camera, detect at least one object, based on image data obtained through the camera in a first light source environment, analyze properties of the at least one detected object, determine at least one or more light source effects, based on the analyzed properties of the object, apply a second light source effect different from the first light source to the at least one object, and apply a third light source effect different from the second light source effect to a background, excluding the at least one object.

Advantageous Effects of Invention

(10) According to various embodiments disclosed in this document, effects may be applied separately to a foreground and a background of an image, thereby producing more diverse images.

(11) In addition, according to various embodiments, different effects may be applied to the foreground and the background of an image, respectively, thereby providing an unusual image.

(12) In addition, according to various embodiments, it is possible to apply optimized effects to the foreground and the background of an image, respectively.

(13) In addition, various effects identified directly or indirectly through this document may be provided.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) FIG. 1 illustrates an electronic device according to an embodiment.

(2) FIG. 2 illustrates a concept of controlling a function for applying an effect to an image in an electronic device according to an embodiment.

(3) FIG. 3 illustrates a process of separating an object from a background and applying different effects thereto in an electronic device according to an embodiment.

(4) FIG. 4 illustrates a process of separating an object from a background and applying different effects thereto in an electronic device according to an embodiment.

(5) FIG. 5 illustrates an image processing process in the case where an effect applied to an object is similar to an effect applied to a background in an electronic device according to an embodiment.

(6) FIG. 6 illustrates the state in which an image effect is applied to image data obtained by an electronic device according to an embodiment.

(7) FIG. 7 illustrates a process of obtaining a plurality of images through a function of an electronic device according to an embodiment.

(8) FIG. 8 illustrates an image in which a new light source effect is applied to an object detected in an electronic device according to an embodiment.

(9) FIG. 9 illustrates an image to which an effect is applied in an electronic device according to an embodiment.

(10) FIG. 10 is a block diagram of an electronic device in a network environment according to various embodiments.

(11) FIG. 11 is a block diagram illustrating a camera module according to various embodiments.
BEST MODE FOR CARRYING OUT THE INVENTION

(12) Hereinafter, various embodiments of this document will be described with reference to the accompanying drawings. However, this is not intended to limit the document to specific embodiments, and should be understood to include various modifications, equivalents, and/or alternatives of the embodiments of the disclosure.

(13) FIG. 1 illustrates an electronic device according to an embodiment.

(14) Referring to FIG. 1, a display **110** may be disposed on a front surface of an electronic device **100** according to an embodiment. According to an embodiment, the display **110** may occupy most of the front surface of the electronic device **100**. The display **110** and an area of a bezel **120** surrounding at least some edges of the display **110** may be disposed on the front surface of the electronic device **100**. In the example in FIG. 1, the display **110** may include a flat area **111** and a curved area **112** extending from the flat area **111** toward the side surface of the electronic device **100**. Although the curved area **112** is provided only on one side (e.g., the left side) in FIG. 1, it may be understood that the curved area may also be formed on the opposite side in the same manner. In addition, the electronic device **100** illustrated in FIG. 1 is only an example, and various embodiments may be possible. For example, the display **110** of the electronic device **100** may include only the flat area **111** without the curved area **112** or may be equipped with the curved area **112** only on one edge rather than both sides. In addition, according to an embodiment, the curved area may extend to the rear surface of the electronic device **100** so that the electronic device **100** may have an additional flat area. In still further embodiments, no curved areas may be provided on an electric device of the present disclosure. As such, the specific geometric shape and profile of the electronic device is not intended to be limiting to the scope of the present disclosure.

(15) According to an embodiment, a fingerprint sensor **141** for recognizing fingerprints of a user may be included in a first area **140** of the display **110**. Since the fingerprint sensor **141** is disposed on a lower layer of the display **110**, it may not be visible to the user or may be arranged to be difficult to view or visually observe. In addition, a sensor for user/biometric authentication may be further disposed in some areas of the display **110** in addition to the fingerprint sensor **141** (or alternatively thereto). In another embodiment, a sensor for user/biometric authentication may be disposed in one area of the bezel **120**. For example, an IR sensor for facial or iris authentication may be exposed through one area of the display **110** or exposed through one area of the bezel **120**.

(16) According to an embodiment, a front camera **131** may be disposed on the front surface of the electronic device **100**. Although the front camera **131** is shown as being exposed through one area of the display **110** in the embodiment in FIG. 1, the front camera **131** may be exposed through the bezel **120** in another embodiment or may be positioned at other location on the front surface of the electronic device **100**.

(17) According to an embodiment, the electronic device **100** may include one or more front cameras **131**. For example, the electronic device **100** may include two front cameras such as a first front camera and a second front camera. According to an embodiment, the first front camera and the second front camera may be the same type of camera having the same specifications (e.g., pixels). In other embodiments, the first front camera and the second front camera may be implemented as cameras having different specifications. In some embodiments, the two front cameras may share some similar specifications/properties, while other aspects specifications/properties of the two front cameras may be different to enable one or more functionalities. For example, the electronic device **100** may support functions related to a dual camera (e.g., 3D shooting, auto focus, etc.) through the two front cameras.

(18) According to an embodiment, a rear camera **132** may be disposed on the rear surface of the electronic device **100**. The rear camera **132** may be exposed through a camera area **130** of a rear cover **160**. According to an embodiment, the electronic device **100** may include a plurality of rear cameras disposed in the camera area **130**. For example, the electronic device **100** may include two or more rear cameras. For example, the electronic device **100** may include a first rear camera, a second rear camera, and a third rear camera. The first rear camera, the second rear camera, and the third rear camera may have different specifications from each other. For example, the first rear camera, the second rear camera, and/or the third rear camera may be different from one another in field of view (FOV), pixels, aperture, support or non-support of optical zoom/digital zoom, support or non-support of an image stabilization function, the type of lens set included in each camera, and arrangement thereof. For example, the first rear camera may be a normal camera, the second rear camera may be a camera for a wide photographing (e.g., wide FOV), and the third rear camera may be a camera for a telephoto photographing (e.g., narrow FOV, zoom capability, etc.). In this document, the description of the functions or characteristics of the front camera may be applied to the rear camera, and vice versa.

(19) According to an embodiment, various types of hardware or sensors assisting photographing, such as a flash **145**, may be disposed in the camera area **130**. For example, in some non-limiting embodiments, a distance sensor (e.g., a time-of-flight (TOF) sensor) for detecting a distance between a subject and the electronic device **100** may be included.

(20) According to an embodiment, at least one physical key, button, toggle, or the like may be disposed on the side surface of the electronic device **100**. For example, a first function key **151**, such as for turning on/off the display **110** or turning on/off the electronic device **100**, may be disposed on the right edge of the electronic device **100**, based on the front surface thereof. According to an embodiment, a second function key **152**, such as for controlling the volume or screen brightness of the electronic device **100**, may be disposed on the left edge of the electronic device **100**, with respect to the front surface thereof. In addition to this, additional buttons or keys may be disposed on the side(s) and/or on the front surface or the rear surface of the electronic device **100**. For example, a physical button or a touch button mapped to a specific function may be disposed on a lower area of the front bezel **120**.

(21) The electronic device **100** illustrated in FIG. **1** is only an example and is not intended to limit the form of the device to which the technical idea disclosed in this document is applied. The technical idea disclosed in this document may be applicable to various user devices equipped with a first camera module facing in a first direction and a second camera module facing in a direction different from the first direction. For example, the technical idea disclosed in this document may be applied to a foldable electronic device, a tablet, or a laptop capable of being folded in the horizontal or vertical direction by employing a flexible display **110** and a hinge structure. In addition, the technical idea may also be applied to the case in which a first camera module and a second camera module, which face in the same direction, may be disposed to face in different directions by rotation, folding, or deforming of the device.

(22) Hereinafter, for the convenience of description, various embodiments will be described based on the electronic device **100** shown in FIG. **1**.

(23) FIG. **2** illustrates a concept of controlling a function for applying an effect to an image in an electronic device according to an embodiment. In a description of FIG. **2**, configurations and/or functions described in FIG. **1** may be simply described or omitted.

(24) Referring to FIG. **2**, the electronic device **100** may use hardware and/or software modules to support functions for applying effects to images. For example, a processor **210** may execute instructions stored in the memory **230**, thereby operating an object detection module **201**, an image analyzing module **203**, a photographing effect application module **205**, and a photographing control module **207**. In various embodiments, software modules other than those shown in FIG. **2** may be implemented. For example, at least two modules may be integrated into a single module, or a single

module may be divided into two or more modules. In addition, hardware and software modules may share a single function, thereby improving work performance. For example, the electronic device **100** may include both an encoder implemented as hardware and an encoder implemented as software module, and some of data obtained through at least one camera module may be processed in the hardware encoder and the remaining data may be processed in the software encoder.

(25) According to an embodiment, the object detection module **201** may detect an object by analysis of image data obtained through a camera **220**. The object detection module **201** may perform detection of a face, detection of face-related parts (e.g., eyes, nose, mouth, ears, hair, etc.), detection of a body, detection of body-related parts (e.g., arms, legs, neck, torso, etc.), and detection of gestures. The object may also include animals as well as humans, and may also include things such as a doll or other humanoid shapes or objects.

(26) According to an embodiment, the object detection module **201** may detect at least one object through various detection methods. The object detection module **201** may detect an object using artificial intelligence such as machine learning. For example, a body may be detected through a segmentation technique (e.g., upper body segmentation). The various detection methods are not limited to a specific method and may include various methods previously disclosed. For example, various types of object detection algorithms and/or libraries may be implemented by the object detection module **201**, without departing from the scope of the present disclosure.

(27) According to an embodiment, if a specific gesture is detected, the object detection module **201** may transfer information about the specific gesture to the photographing control module **207**.

(28) According to an embodiment, the image analyzing module **203** may analyze color properties of an object and a background included in the image. The image analyzing module **203** may detect at least one of a number of detected objects, positions of the detected objects, sizes of the detected objects, shapes of the detected objects, colors of the detected objects, angles of the detected objects, and/or other properties and/or characteristics of the detected objects. The image analyzing module **203** may detect, for example and without limitation, photographing positions, complexity of a background, color saturation of an image, and contrast of an image. The image analyzing module **203** may estimate the properties of a light source by analyzing the image. The image analyzing module **203** may estimate the direction of a light source and the intensity of a light source by analyzing the image.

(29) According to an embodiment, the photographing effect application module **205** may apply various effects to the image. For example, the various effects may include, without limitation, virtual light source effects and virtual color effects. The photographing effect application module **205** may apply the effects to a preview image currently being displayed on the display **110** or apply the effects to the images stored in the memory **230**. The photographing effect application module **205** may automatically apply the effects to the image or apply, in response to a user input, an effect corresponding to the user input to the image.

(30) According to an embodiment, the photographing control module **207** may provide a user interface (UI)/graphical UI (GUI) related to the camera to the user through the display **110**. In addition, a photographing operation may be controlled in response to a user input provided through the UI/GUI output to the display **110**. For example, the photographing control module **207** may obtain a recording start/stop input from the user and transfer the obtained recording start/stop input to an encoder. The input obtained from the user may include an input obtained through a voice recognition function or include detection of a specific gesture. For example, if the processor **210** recognizes voices such as “shoot”, “photograph”, and “stop photographing”, the processor **210** may start/stop photographing in response thereto. Alternatively, if the processor **210** detects a gesture showing a palm, the processor **210** may start/stop photographing in response thereto.

(31) According to an embodiment, the display **110** may display an execution screen of an application executed by the processor **210** or content such as images and/or videos stored in the memory **230** on the display **110**. In addition, the processor **210** may display image data obtained

through the camera **220** on the display **110** in real time. The display **110** may output, as a preview image, a preview area cropped and/or resized to conform to resolution of the current preview image.

(32) According to an embodiment, the image signal processor **240** may perform a stabilization operation on the images obtained from the camera **220**. According to an embodiment, the stabilization operation may include at least one of auto exposure (AE), auto focus (AF), and auto white balance (AWB). In addition, the image signal processor **240** may improve the quality of an obtained image through an appropriate picture quality control/tuning operation, in addition to the auto exposure, the auto focus, and/or the auto white balance, or apply a desired effect thereto.

(33) In the embodiment in FIG. **2**, the functions performed by the object detection module **201**, the image analyzing module **203**, the photographing effect application module **205**, and the photographing control module **207** may be understood to be performed by the processor **210** executing instructions stored in the memory **230**. In addition, in various embodiments, the electronic device **100** may use one or more hardware processing circuits in order to perform various functions and operations disclosed in this document. For example, an application processor (AP) included in the mobile device, an image signaling processor (ISP) mounted to a camera module, a display driver integrated circuit (DDIC), a touch integrated circuit (IC), a communication processor (CP), a hardware encoder, and the like may be used to implement various embodiments disclosed in this document. In addition, the connection relationship between the hardware and software shown in FIG. **2** is intended for the convenience of description, and the flow/direction of data or commands are not limited thereto. The elements included in the electronic device **100** may have various electrical/operational connection relationships.

(34) FIG. **3** illustrates a process of separating an object from a background and applying different effects thereto in an electronic device according to an embodiment.

(35) In operation **310** according to an embodiment, the processor **210** may execute the camera **220**. For example, the processor **210** may execute the camera **220** in response to a user input. The user input may include at least one of a user input pressing a virtual photographing button displayed on the display **110**, a user input pressing a physical photographing button, a user input using a voice recognition function, and an instruction sent from a peripheral device (e.g., wearable electronic watch, connected alternative device (e.g., phone, tablet, computer)).

(36) According to an embodiment, the processor **210** may execute the camera **220** to obtain image data through an image sensor in the camera **220**. The image data may obtain various color values through a color filter array. The color filter array may include an RGB color filter array. The RGB color filter array is just one example, and the color filter array may include one or more, individually or in combination, of a color filter array of an RGBE (red, green, blue, and emerald) pattern, a CYYM (cyan, yellow, and magenta) pattern, a CYGM (cyan, yellow, green, and magenta) pattern, or an RGBW (red, green, blue, and white) pattern.

(37) In operation **320** according to an embodiment, the processor **210** may detect at least one object, based on image data obtained through the camera **220** in a first light source environment. The first light source environment may be understood as an external environment of the electronic device **100** during the photographing, instead of a light source environment produced by the electronic device **100**. For example, when photographing at least one person in the first light source environment, the processor **210** may detect at least one person and distinguish at least one part (e.g., a face or a body) of the person.

(38) According to an embodiment, the processor **210** may analyze at least one or more of the characteristics of the object, the characteristics of an image, and the characteristics of a light source detected based on the image data obtained through the camera **220** in the first light source environment. For example, the processor **210**, based on the obtained image data, may identify a photographing place, the complexity of a background, the number of detected objects (e.g., people and/or animals), the saturation of an image, and the contrast of an image. As another example, the

processor **210** may identify at least one of the position, the gender, the age, the facial expression, the angle of a face, the photographing pose, the facial size and shape, the skin, the hair, the clothes, the eyes, and the lip color of a detected person. As another example, the processor **210** may identify at least one of the direction and the intensity of a light source.

(39) In operation **330** according to an embodiment, the processor **210** may analyze color properties of at least one detected object. For example, an area related to the object may be distinguished, and a color value for the area related to the object may be analyzed. For example, a skin color may be obtained from the face of a person, a black color may be obtained from the hair of a person, and the color of clothes may be obtained from the clothes worn on a person, and information about the colors may be stored in the memory **230**.

(40) According to an embodiment, the processor **210** may determine an area having the largest proportion (e.g., area) among the areas related to the object. The processor **210** may obtain a color value of the area having the largest proportion of the object. For example, if the processor **210** detects a face of a person and an upper body of a person, and if the upper body has the largest proportion in the image, the color of the clothes corresponding to the upper body may be obtained.

(41) According to an embodiment, the processor **210** may obtain the color of a partial area (e.g., the clothes worn on the upper body) of the detected object (e.g., a person), regardless of the proportion. For example, if the color (e.g., purple) of the clothes worn on the detected person is identified, the processor **210** may obtain the color of the clothes and store information about the color in the memory **230**.

(42) In operation **340** according to an embodiment, the processor **210** may determine a first effect, based on the color properties of the analyzed object. For example, a purple color effect may be determined based on the color (e.g., purple) of the clothes that is a part of the analyzed object (e.g., a person). Operation **340** will be described in detail below with respect to operation **441**, operation **443**, and operation **446** in FIG. 4.

(43) In operation **350** according to an embodiment, the processor **210** may apply a second light source effect, which is different from the first light source, to at least one object detected in the image. The processor **210** may determine a second light source effect, based on the properties of the first light source, applied to the object. Alternatively, the processor **210** may randomly determine a second light source different from the first light source. The processor **210** may apply the second light source effect to at least one object. Operation **350** will be described in detail below with respect to operation **453** in FIG. 4.

(44) According to an embodiment, the processor **210** may remove the effect of the first light source from at least one object. The processor **210** may remove the effect of the first light source and apply the second light source effect to at least one object.

(45) In operation **360** according to an embodiment, the processor **210** may apply the first effect to a background, excluding the at least one object. The processor **210** may produce an image by applying the first effect to the background. The first effect may be a color effect in which a color value is adjusted or a light source effect in which a light source is adjusted. For example, if purple is determined as the first color effect, based on the color properties of the object, the processor **210** may apply purple as a background color.

(46) According to an embodiment, the processor **210** may remove the effect of the first light source from the background. The processor **210** may remove the effect of the first light source and apply the first effect to the background.

(47) FIG. 4 illustrates a process of separating an object from a background and applying different effects thereto in an electronic device according to an embodiment.

(48) In operation **410** according to an embodiment, the processor **210** may detect an object, based on image data obtained through the camera in a first light source environment. Since operation **410** corresponds to operation **320** in FIG. 3, a detailed description thereof will be omitted.

(49) In operation **420** according to this illustrative non-limiting embodiment, the processor **210**

may detect a face of the object and obtain information about the face. Although the present description is made with respect to a face of the object, it will be appreciated that other parts or aspects of the object may be the focus of the process of FIG. 4. The processor **210** may obtain information about the face in order to determine whether or not predetermined conditions are fulfilled. If the conditions are fulfilled, the processor **210** may apply an effect to an image. The processor **210** may determine whether or not the size of the face, the angle of the face, and the direction of the face fulfill predetermined conditions.

(50) For example, and without limitation, according to an embodiment, the processor **210** may determine a facial area corresponding to the face. The processor **210** may be configured to obtain information about the direction of the face, and determine the angle of the face between the direction of the face and a reference direction. If the determined facial area is greater than or equal to a predetermined area of the obtained image data and if the angle of the face is less than or equal to a predetermined angle, the processor **210** may determine that the conditions for applying an effect to an image is fulfilled. For example, the processor **210** may determine whether the determined facial area is $\frac{1}{3}$ of the obtained image data or more and whether the angle of the face falls within about -30° to about $+30^\circ$ in a yaw direction, within about -30° to about $+30^\circ$ in a roll direction, and within about -30° to about $+30^\circ$ in a pitch direction.

(51) In operation **430** according to an embodiment, the processor **210** may separate an object area and a background area. The processor **210** may separate an object area and a background area through a segmentation technique (e.g., upper body segmentation). The processor **210** may compare color values around the area corresponding to the edge of the detected object and separate the object area and the background area, based on differences between the color values.

(52) In operation **441** according to an embodiment, the processor **210** may analyze the color properties of the object. The processor **210** may obtain a color value of a partial area of the object by analyzing the color properties of the object. For example, the processor **210** may obtain a color value of the clothes worn on the upper body that is a partial area of the object (e.g., a person).

(53) In operation **443** according to an embodiment, the processor **210** may produce a pastel tone color, based on the analysis of the color properties of the object. For example, the processor **210** may determine the color properties (e.g., the color of the clothes worn on a person) of an object (e.g., a person) and calculate the color, thereby determining a pastel tone color to be applied to the background. For example, the processor **210** may convert the detected color of clothes into pastel tone using the following pastel tone conversion formula, thereby determining a pastel tone color to be applied to the background.

$$(54) \begin{matrix} R_i & R_o \\ G_i & G_o \\ B_i & B_o \end{matrix} + B = \begin{bmatrix} 0.060879 & -0.10606 & -0.17844 \\ 0.05503 & 0.40515 & -0.16873 \\ -0.10489 & -0.0145 & 0.41827 \end{bmatrix} \text{where } A = \begin{bmatrix} 0.060879 & -0.10606 & -0.17844 \\ 0.05503 & 0.40515 & -0.16873 \\ -0.10489 & -0.0145 & 0.41827 \end{bmatrix} \text{Math.}$$

$$B = \begin{bmatrix} 144.215 \\ 136.271 \\ 126.797 \end{bmatrix}$$

(55) In operation **445** according to an embodiment, the processor **210** may determine a gradation effect applied to the background, based on the direction of a light source. For example, if the direction of a light source is from the right to the left, the gradation effect may be darker on the right side and lighter on the left side. If the direction of a light source is from the top to the bottom, the gradation effect may be darker on the top and lighter on the bottom.

(56) In operation **447** according to an embodiment, the processor **210** may determine a frame effect applied to the background, based on the properties of the object. Operation **447** may be related to the third image **630** in FIG. 6, described herein. If the size of the area (e.g., face) related to the object is greater than a first size and if the position of the area (e.g., face) related to the object falls within one area of the image, the processor **210** may determine a frame effect. The frame effect

may be applied to the outer area of the image. The processor **210** may apply the frame effect by reducing the size of a background image to which a color effect and/or a gradation effect has been applied or apply the frame effect by applying a frame image to an image to which a color effect and/or a gradation effect has been applied.

(57) According to an embodiment, the processor **210** may adjust the frame size of the determined frame effect, based on the properties (e.g., size) of the area (e.g., face) related to the object. For example, the processor **210** may reduce the frame size if the size of the area (e.g., face) related to the object is greater than or equal to a second size, and increase the frame size if the size of the area (e.g., face) related to the object is less than the second size.

(58) According to an embodiment, the processor **210** may adjust the frame position of the determined frame effect, based on the properties (e.g., angle and/or direction) of the area (e.g., face) related to the object. For example, in the case where the face of a detected person is directed to the right, the processor **210** may determine that the right area of the frame is thicker than the left area. In the case where the face of a detected person is directed to the left, the processor **210** may determine that the left area of the frame is thicker than the right area. However, this is only an embodiment, and it may be understood by those skilled in the art that it may be applied in the opposite way.

(59) According to an embodiment, the processor **210** may control the frame color of the determined frame effect. The processor **210** may configure the basic color of the frame as white. The processor **210** may control the frame color in order to enhance the produced pastel tone color. For example, if a background color is purplish, the processor **210** may apply a white frame effect to the image. Alternatively, if the background color is yellowish, the processor **210** may apply a black frame, instead of a white frame, such that the frame and the background are easily distinguished in color.

(60) In operation **451** according to an embodiment, the processor **210** may analyze the properties of a first light source. The processor **210** may estimate at least one of a direction and an angle of the first light source by analyzing the properties of the first light source.

(61) In operation **453** according to an embodiment, the processor **210** may determine a second light source effect that is different from the first light source.

(62) According to an embodiment, the processor **210** may determine a second light source effect to be applied to the object, based on the properties of the first light source. The processor **210** may determine a second light source effect applied to the object, based on the intensity of the first light source. For example, the processor **210** may determine the contour light of a virtual front upper part that preserves the contour of the face to be the second light source effect in the case where the ISO is 800 or less and determine the light source that remains in the same direction as the first light source and increases the intensity to be the second light source effect in the case where the ISO 800 or more.

(63) According to an embodiment, the processor **210** may randomly determine a second light source that is different from the first light source. The second light source effect may be referred to as a virtual light source effect or relighting effect. The processor **210** may determine a second light source in a direction different from that of the first light source. For example, the processor **210** may determine at least one of a second light source effect in the front direction, a second light source effect in the right direction, a second light source effect in the left direction, and a second light source effect in the edge direction of the object. The processor **210** may determine a second light source having an intensity different from that of the first light source. For example, the processor **210** may determine a second light source having the same direction as the first light source and having an increased brightness value. The processor **210** may determine a second light source having a different direction and a different intensity from the first light source.

(64) In operation **460** according to an embodiment, the processor **210** may produce an image in which the effects are applied to the image data. The processor **210** may store the produced image in the memory **230**. The processor **210** may display the produced image on the display **110**.

(65) FIG. 5 illustrates an image processing process in the case where an effect applied to an object is similar to an effect applied to a background in an electronic device according to an embodiment. An operating entity of the flowchart illustrated in FIG. 5 may be understood as a processor (e.g., the processor **210** in FIG. 2) or an image signal processor (the image signal processor **240** in FIG. 2). The flowchart in FIG. 5 may be related to the operations and processes of FIGS. 3 and 4. For example, in applying a color or light source effect to an object and a background in FIGS. 3 and 4, FIG. 5 shows the process in the case where the effect applied to the object and the effect applied to the background are similar.

(66) In operation **510** according to an embodiment, the processor **210** may determine whether or not a first effect applied to the object and a second effect applied to the background are similar. The processor **210** may compare a color value of the first effect applied to the object with a color value of the second effect applied to the background, thereby determining whether or not they are similar.

(67) According to an embodiment, if a difference between the color value of the first effect and the color value of the second effect is within a predetermined value, the processor **210** may determine that they are similar. For example, in the case where a pixel have color values of 0 to 255 for red, 0 to 255 for green, and 0 to 255 for blue, if a difference between the color value of the first effect and the color value of the second effect is within 10% in red, within 10% in green, and within 10% in blue, the color value of the first effect and the color value of the second effect may be determined to be similar. However, the predetermined value is not limited to the above examples and may be variously configured according to at least a change in a program code or a user input.

(68) In operation **520** according to an embodiment, the processor **210** may change a brightness value of at least one of the first effect and the second effect. For example, the processor **210** may increase or reduce a brightness value of the first effect among the effects. The processor **210** may increase or reduce a color value of the second effect among the effects. The processor **210** may increase a brightness value of the first effect and reduce a brightness value of the second effect. The processor **210** may reduce a brightness value of the first effect and increase a brightness value of the second effect.

(69) According to an embodiment, the processor **210** may randomly change a color value of at least one of the first effect and the second effect. If it is determined that the effects are similar, the processor **210** may randomly change a color value of at least one of the effects. For example, the processor **210** may change a color value of the first effect among the effects. The processor **210** may change a color value of the second effect among the effects. The processor **210** may change a color value of the first effect and a color value of the second effect.

(70) According to an embodiment, the processor **210** may change a color value of at least one of the first effect and the second effect in response to a user input. The processor **210** may separate an object area from a background area and display the same on the display **110** such that at least one of the object area and the background area may be selected. In response to a user input for selecting the at least one area, the processor **210** may display a user interface in one area of the display **110** such that a color value of the selected area may be changed. In response to a user input for adjusting a color value of the selected area, the processor **210** may change the color value of the selected area.

(71) In operation **530** according to an embodiment, the processor **210** may produce an image to which the first effect and the second effect are applied. The processor **210** may store the produced image in the memory **230**. The processor **210** may display the produced image on the display **110**.

(72) FIG. 6 illustrates the state in which an image effect is applied to image data obtained by an electronic device according to an embodiment. An operating entity of the process illustrated in FIG. 6 may be understood as a processor (e.g., the processor **210** in FIG. 2 or the image signal processor **240** in FIG. 2). The images **610**, **620**, and **630** shown in FIG. 6 may be described as related to the description of FIG. 4.

(73) Referring to FIG. 6, a first image **610** may be understood as a preview image including a first

object **611** and a first background **613**, or an image photographed and stored in the memory **230**.

(74) According to an embodiment, a second image **620** may be understood as an image including a second object **621** obtained by applying a virtual light source effect to the first object **611** and a second background **623** obtained by applying a color effect the first background **613**. The virtual light source effect may be a light source that is different from the light source for photographing. The virtual light source effect may be determined based on the characteristics of the light source for photographing and the second object **621**. This is described, for example, in detail in operation **350** in FIG. **3** and/or operation **453** in FIG. **4**. The color effect may be determined based on color properties of the second object **621**. This is described, for example, in detail in operation **340** in FIG. **3**, operation **441** in FIG. **4**, operation **443** in FIG. **4**, and/or operation **445** in FIG. **4**.

(75) According to an embodiment, a third image **630** may be understood as an image including a third object **631**, a third background **633**, and a frame **635** obtained by applying a frame effect to the second image **620**. The frame **635** may be determined based on the characteristics of an area (e.g., face) related to the object **631**. This is described, for example, in detail in operation **447** in FIG. **4**.

(76) FIG. **7** illustrates a process of obtaining a plurality of images through a function of an electronic device according to an embodiment.

(77) Referring to FIG. **7**, the processor **210** may obtain a plurality of images through a function (e.g., a single take function) of the electronic device **100**.

(78) In step **710** according to an embodiment, the processor **210** may start recording in response to a user input received through a photographing start button **701**. The processor **210** may store images for every first period (e.g., about 1 second) during the recording. For example, in the case where the processor **210** performs recording for 3 seconds in response to a user input, the processor **210** may store a first image recorded at 1 second, a second image recorded at 2 seconds, and a third image recorded at 3 seconds in the memory **230**. The first period for storing the recorded images may vary according to the configuration of the user. It will be appreciated that other time intervals may be employed without departing from the scope of the present disclosure.

(79) In step **730** according to an embodiment, the processor **210** may end the recording in response to a user input received through a photographing end button **703**. In response to the user input, the processor **210** may terminate the recording and display the stored images on the display **110**, based on various user interfaces.

(80) According to an embodiment, the processor **210** may determine at least one image **713** from among a plurality of images **711** stored during the recording. The processor **210** may remove a color value of a background of the determined image.

(81) According to an embodiment, the processor **210** may produce a color effect **715** to be applied to a background. The processor **210** may determine a color effect for a background, based on the color properties (e.g., color of clothes) of an object included in the at least one determined image.

(82) According to an embodiment, the processor **210** may adjust the size of the background, thereby applying a frame effect to the image. The processor **210** may adjust the size of the frame, based on the size and/or position of an area (e.g., face) related to the object (e.g., a person). The processor **210** may apply a color effect and/or a frame effect for the determined background to the at least one determined image from which the color value of the background was removed.

(83) In step **750** according to an embodiment, the processor **210** may display at least one image stored during the recording in a first area **751** of the display **110** and display a plurality of images in a second area **753** thereof. Images stored during the recording, images obtained by applying color effects and/or frame effects to the stored images, and videos stored during the recording may be displayed in the second area **753**.

(84) FIG. **8** illustrates an image in which a new light source effect is applied to an object detected in an electronic device according to an embodiment.

(85) FIG. **8** shows the state in which a virtual light source effect is applied to an object included in

an image **800**. The virtual light source effect may be different from the light source environment for photographing. The processor **210** may increase the intensity of a light source for the object in the image **800** or change the direction of a light source, thereby producing images of various presentations. For example, the processor **210** may apply a light source effect in a first direction **801**, apply a light source effect in a second direction **803**, or apply a light source effect in a contour direction **805** of the object.

(86) FIG. **9** illustrates an image to which an effect is applied in an electronic device according to an embodiment. An operating entity in FIG. **9** may be understood as a processor (e.g., the processor **210** in FIG. **2**) or an image signal processor (e.g., the image signal processor **240** in FIG. **2**).

(87) Referring to FIG. **9**, a first image **910** may be understood as a preview image or an image including a first object **911** and a first background **913** to which no virtual light source effect and color effect are applied. The second image **920** may be an image obtained by adjusting a brightness value of the first image **910**. For example, the second image **920** may be an image including a second object **921** obtained by increasing the brightness value of the first object **911** and a second background **923** obtained by reducing the brightness value of the first background **913**.

(88) According to an embodiment, the processor **210** may detect a first object **911** in the first image **910**. The processor **210** may separate the first object **911** and the first background **913** through a segmentation technique (e.g., upper body segmentation).

(89) According to an embodiment, the processor **210** may increase a brightness value of a first object area corresponding to the first object **911**. The processor **210** may increase a color value corresponding to the first object area. For example, the processor **210** may increase the brightness value by increasing all the R, G, and B values of the pixels corresponding to the first object area.

(90) According to an embodiment, the processor **210** may reduce a brightness value of a first background area corresponding to the first background **913**. The processor **210** may reduce a color value corresponding to the first background area. For example, the processor **210** may reduce the brightness value by reducing all the R, G, and B values of the pixels corresponding to the first background area.

(91) According to an embodiment, the processor **210** may display, on the display **110**, a second image **920** in which the brightness values of the object and background have been adjusted separately.

(92) According to an embodiment, the processor **210** may apply a warm tone color to image data obtained through the camera **220**. The processor **210** may apply a highlight effect by increasing a brightness value of the edge portion of an object detected based on the image data. The effect of applying a warm tone color to the entire image and increasing the brightness value of the edge portion of the object may be referred to as a halation effect.

(93) According to an embodiment, the processor **210** may apply a black and white effect to image data obtained through the camera **220**. The processor **210** may apply a high-key mono black and white effect to the obtained image data. The processor **210** may apply a low-key mono black and white effect to the obtained image data.

(94) FIG. **10** is a block diagram illustrating an electronic device **1001** in a network environment **1000** according to various embodiments. Referring to FIG. **10**, the electronic device **1001** in the network environment **1000** may communicate with an electronic device **1002** via a first network **1098** (e.g., a short-range wireless communication network), or at least one of an electronic device **1004** or a server **1008** via a second network **1099** (e.g., a long-range wireless communication network). According to an embodiment, the electronic device **1001** may communicate with the electronic device **1004** via the server **1008**. According to an embodiment, the electronic device **1001** may include a processor **1020**, memory **1030**, an input module **1050**, a sound output module **1055**, a display module **1060**, an audio module **1070**, a sensor module **1076**, an interface **1077**, a connecting terminal **1078**, a haptic module **1079**, a camera module **1080**, a power management module **1088**, a battery **1089**, a communication module **1090**, a subscriber identification module

(SIM) **1096**, or an antenna module **1097**. In some embodiments, at least one of the components (e.g., the connecting terminal **1078**) may be omitted from the electronic device **1001**, or one or more other components may be added in the electronic device **1001**. In some embodiments, some of the components (e.g., the sensor module **1076**, the camera module **1080**, or the antenna module **1097**) may be implemented as a single component (e.g., the display module **1060**).

(95) The processor **1020** may execute, for example, software (e.g., a program **1040**) to control at least one other component (e.g., a hardware or software component) of the electronic device **1001** coupled with the processor **1020**, and may perform various data processing or computation. According to one embodiment, as at least part of the data processing or computation, the processor **1020** may store a command or data received from another component (e.g., the sensor module **1076** or the communication module **1090**) in volatile memory **1032**, process the command or the data stored in the volatile memory **1032**, and store resulting data in non-volatile memory **1034**.

According to an embodiment, the processor **1020** may include a main processor **1021** (e.g., a central processing unit (CPU) or an application processor (AP)), or an auxiliary processor **1023** (e.g., a graphics processing unit (GPU), a neural processing unit (NPU), an image signal processor (ISP), a sensor hub processor, or a communication processor (CP)) that is operable independently from, or in conjunction with, the main processor **1021**. For example, when the electronic device **1001** includes the main processor **1021** and the auxiliary processor **1023**, the auxiliary processor **1023** may be adapted to consume less power than the main processor **1021**, or to be specific to a specified function. The auxiliary processor **1023** may be implemented as separate from, or as part of the main processor **1021**.

(96) The auxiliary processor **1023** may control at least some of functions or states related to at least one component (e.g., the display module **1060**, the sensor module **1076**, or the communication module **1090**) among the components of the electronic device **1001**, instead of the main processor **1021** while the main processor **1021** is in an inactive (e.g., sleep) state, or together with the main processor **1021** while the main processor **1021** is in an active state (e.g., executing an application). According to an embodiment, the auxiliary processor **1023** (e.g., an image signal processor or a communication processor) may be implemented as part of another component (e.g., the camera module **1080** or the communication module **1090**) functionally related to the auxiliary processor **1023**. According to an embodiment, the auxiliary processor **1023** (e.g., the neural processing unit) may include a hardware structure specified for artificial intelligence model processing. An artificial intelligence model may be generated by machine learning. Such learning may be performed, e.g., by the electronic device **1001** where the artificial intelligence is performed or via a separate server (e.g., the server **1008**). Learning algorithms may include, but are not limited to, e.g., supervised learning, unsupervised learning, semi-supervised learning, or reinforcement learning. The artificial intelligence model may include a plurality of artificial neural network layers. The artificial neural network may be a deep neural network (DNN), a convolutional neural network (CNN), a recurrent neural network (RNN), a restricted boltzmann machine (RBM), a deep belief network (DBN), a bidirectional recurrent deep neural network (BRDNN), deep Q-network or a combination of two or more thereof but is not limited thereto. The artificial intelligence model may, additionally or alternatively, include a software structure other than the hardware structure.

(97) The memory **1030** may store various data used by at least one component (e.g., the processor **1020** or the sensor module **1076**) of the electronic device **1001**. The various data may include, for example, software (e.g., the program **1040**) and input data or output data for a command related thereto. The memory **1030** may include the volatile memory **1032** or the non-volatile memory **1034**.

(98) The program **1040** may be stored in the memory **1030** as software, and may include, for example, an operating system (OS) **1042**, middleware **1044**, or an application **1046**.

(99) The input module **1050** may receive a command or data to be used by another component (e.g., the processor **1020**) of the electronic device **1001**, from the outside (e.g., a user) of the

electronic device **1001**. The input module **1050** may include, for example, a microphone, a mouse, a keyboard, a key (e.g., a button), or a digital pen (e.g., a stylus pen).

(100) The sound output module **1055** may output sound signals to the outside of the electronic device **1001**. The sound output module **1055** may include, for example, a speaker or a receiver. The speaker may be used for general purposes, such as playing multimedia or playing record. The receiver may be used for receiving incoming calls. According to an embodiment, the receiver may be implemented as separate from, or as part of the speaker.

(101) The display module **1060** may visually provide information to the outside (e.g., a user) of the electronic device **1001**. The display module **1060** may include, for example, a display, a hologram device, or a projector and control circuitry to control a corresponding one of the display, hologram device, and projector. According to an embodiment, the display module **1060** may include a touch sensor adapted to detect a touch, or a pressure sensor adapted to measure the intensity of force incurred by the touch.

(102) The audio module **1070** may convert a sound into an electrical signal and vice versa. According to an embodiment, the audio module **1070** may obtain the sound via the input module **1050**, or output the sound via the sound output module **1055** or a headphone of an external electronic device (e.g., an electronic device **1002**) directly (e.g., wiredly) or wirelessly coupled with the electronic device **1001**.

(103) The sensor module **1076** may detect an operational state (e.g., power or temperature) of the electronic device **1001** or an environmental state (e.g., a state of a user) external to the electronic device **1001**, and then generate an electrical signal or data value corresponding to the detected state. According to an embodiment, the sensor module **1076** may include, for example, a gesture sensor, a gyro sensor, an atmospheric pressure sensor, a magnetic sensor, an acceleration sensor, a grip sensor, a proximity sensor, a color sensor, an infrared (IR) sensor, a biometric sensor, a temperature sensor, a humidity sensor, or an illuminance sensor.

(104) The interface **1077** may support one or more specified protocols to be used for the electronic device **1001** to be coupled with the external electronic device (e.g., the electronic device **1002**) directly (e.g., wiredly) or wirelessly. According to an embodiment, the interface **1077** may include, for example, a high definition multimedia interface (HDMI), a universal serial bus (USB) interface, a secure digital (SD) card interface, or an audio interface.

(105) A connecting terminal **1078** may include a connector via which the electronic device **1001** may be physically connected with the external electronic device (e.g., the electronic device **1002**). According to an embodiment, the connecting terminal **1078** may include, for example, a HDMI connector, a USB connector, a SD card connector, or an audio connector (e.g., a headphone connector).

(106) The haptic module **1079** may convert an electrical signal into a mechanical stimulus (e.g., a vibration or a movement) or electrical stimulus which may be recognized by a user via his tactile sensation or kinesthetic sensation. According to an embodiment, the haptic module **1079** may include, for example, a motor, a piezoelectric element, or an electric stimulator.

(107) The camera module **1080** may capture a still image or moving images. According to an embodiment, the camera module **1080** may include one or more lenses, image sensors, image signal processors, or flashes.

(108) The power management module **1088** may manage power supplied to the electronic device **1001**. According to one embodiment, the power management module **1088** may be implemented as at least part of, for example, a power management integrated circuit (PMIC).

(109) The battery **1089** may supply power to at least one component of the electronic device **1001**. According to an embodiment, the battery **1089** may include, for example, a primary cell which is not rechargeable, a secondary cell which is rechargeable, or a fuel cell.

(110) The communication module **1090** may support establishing a direct (e.g., wired) communication channel or a wireless communication channel between the electronic device **1001**

and the external electronic device (e.g., the electronic device **1002**, the electronic device **1004**, or the server **1008**) and performing communication via the established communication channel. The communication module **1090** may include one or more communication processors that are operable independently from the processor **1020** (e.g., the application processor (AP)) and supports a direct (e.g., wired) communication or a wireless communication. According to an embodiment, the communication module **1090** may include a wireless communication module **1092** (e.g., a cellular communication module, a short-range wireless communication module, or a global navigation satellite system (GNSS) communication module) or a wired communication module **1094** (e.g., a local area network (LAN) communication module or a power line communication (PLC) module). A corresponding one of these communication modules may communicate with the external electronic device via the first network **1098** (e.g., a short-range communication network, such as Bluetooth™, wireless-fidelity (Wi-Fi) direct, or infrared data association (IrDA)) or the second network **1099** (e.g., a long-range communication network, such as a legacy cellular network, a 5G network, a next-generation communication network, the Internet, or a computer network (e.g., LAN or wide area network (WAN))). These various types of communication modules may be implemented as a single component (e.g., a single chip), or may be implemented as multi components (e.g., multi chips) separate from each other. The wireless communication module **1092** may identify and authenticate the electronic device **1001** in a communication network, such as the first network **1098** or the second network **1099**, using subscriber information (e.g., international mobile subscriber identity (IMSI)) stored in the subscriber identification module **1096**.

(111) The wireless communication module **1092** may support a 5G network, after a 4G network, and next-generation communication technology, e.g., new radio (NR) access technology. The NR access technology may support enhanced mobile broadband (eMBB), massive machine type communications (mMTC), or ultra-reliable and low-latency communications (URLLC). The wireless communication module **1092** may support a high-frequency band (e.g., the mmWave band) to achieve, e.g., a high data transmission rate. The wireless communication module **1092** may support various technologies for securing performance on a high-frequency band, such as, e.g., beamforming, massive multiple-input and multiple-output (massive MIMO), full dimensional MIMO (FD-MIMO), array antenna, analog beam-forming, or large scale antenna. The wireless communication module **1092** may support various requirements specified in the electronic device **1001**, an external electronic device (e.g., the electronic device **1004**), or a network system (e.g., the second network **1099**). According to an embodiment, the wireless communication module **1092** may support a peak data rate (e.g., 20 Gbps or more) for implementing eMBB, loss coverage (e.g., 164 dB or less) for implementing mMTC, or U-plane latency (e.g., 0.5 ms or less for each of downlink (DL) and uplink (UL), or a round trip of 1 ms or less) for implementing URLLC.

(112) The antenna module **1097** may transmit or receive a signal or power to or from the outside (e.g., the external electronic device) of the electronic device **1001**. According to an embodiment, the antenna module **1097** may include an antenna including a radiating element composed of a conductive material or a conductive pattern formed in or on a substrate (e.g., a printed circuit board (PCB)). According to an embodiment, the antenna module **1097** may include a plurality of antennas (e.g., array antennas). In such a case, at least one antenna appropriate for a communication scheme used in the communication network, such as the first network **1098** or the second network **1099**, may be selected, for example, by the communication module **1090** (e.g., the wireless communication module **1092**) from the plurality of antennas. The signal or the power may then be transmitted or received between the communication module **1090** and the external electronic device via the selected at least one antenna. According to an embodiment, another component (e.g., a radio frequency integrated circuit (RFIC)) other than the radiating element may be additionally formed as part of the antenna module **1097**.

(113) According to various embodiments, the antenna module **1097** may form a mmWave antenna module. According to an embodiment, the mmWave antenna module may include a printed circuit

board, a RFIC disposed on a first surface (e.g., the bottom surface) of the printed circuit board, or adjacent to the first surface and capable of supporting a designated high-frequency band (e.g., the mmWave band), and a plurality of antennas (e.g., array antennas) disposed on a second surface (e.g., the top or a side surface) of the printed circuit board, or adjacent to the second surface and capable of transmitting or receiving signals of the designated high-frequency band.

(114) At least some of the above-described components may be coupled mutually and communicate signals (e.g., commands or data) therebetween via an inter-peripheral communication scheme (e.g., a bus, general purpose input and output (GPIO), serial peripheral interface (SPI), or mobile industry processor interface (MIPI)).

(115) According to an embodiment, commands or data may be transmitted or received between the electronic device **1001** and the external electronic device **1004** via the server **1008** coupled with the second network **1099**. Each of the electronic devices **1002** or **1004** may be a device of a same type as, or a different type, from the electronic device **1001**. According to an embodiment, all or some of operations to be executed at the electronic device **1001** may be executed at one or more of the external electronic devices **1002**, **1004**, or **1008**. For example, if the electronic device **1001** should perform a function or a service automatically, or in response to a request from a user or another device, the electronic device **1001**, instead of, or in addition to, executing the function or the service, may request the one or more external electronic devices to perform at least part of the function or the service. The one or more external electronic devices receiving the request may perform the at least part of the function or the service requested, or an additional function or an additional service related to the request, and transfer an outcome of the performing to the electronic device **1001**. The electronic device **1001** may provide the outcome, with or without further processing of the outcome, as at least part of a reply to the request. To that end, a cloud computing, distributed computing, mobile edge computing (MEC), or client-server computing technology may be used, for example. The electronic device **1001** may provide ultra low-latency services using, e.g., distributed computing or mobile edge computing. In another embodiment, the external electronic device **1004** may include an internet-of-things (IoT) device. The server **1008** may be an intelligent server using machine learning and/or a neural network. According to an embodiment, the external electronic device **1004** or the server **1008** may be included in the second network **1099**. The electronic device **1001** may be applied to intelligent services (e.g., smart home, smart city, smart car, or healthcare) based on 5G communication technology or IoT-related technology.

(116) The electronic device according to various embodiments may be one of various types of electronic devices. The electronic devices may include, for example, a portable communication device (e.g., a smartphone), a computer device, a portable multimedia device, a portable medical device, a camera, a wearable device, or a home appliance. According to an embodiment of the disclosure, the electronic devices are not limited to those described above.

(117) It should be appreciated that various embodiments of the present disclosure and the terms used therein are not intended to limit the technological features set forth herein to particular embodiments and include various changes, equivalents, or replacements for a corresponding embodiment. With regard to the description of the drawings, similar reference numerals may be used to refer to similar or related elements. It is to be understood that a singular form of a noun corresponding to an item may include one or more of the things, unless the relevant context clearly indicates otherwise. As used herein, each of such phrases as “A or B,” “at least one of A and B,” “at least one of A or B,” “A, B, or C,” “at least one of A, B, and C,” and “at least one of A, B, or C,” may include any one of, or all possible combinations of the items enumerated together in a corresponding one of the phrases. As used herein, such terms as “1st” and “2nd,” or “first” and “second” may be used to simply distinguish a corresponding component from another, and does not limit the components in other aspect (e.g., importance or order). It is to be understood that if an element (e.g., a first element) is referred to, with or without the term “operatively” or “communicatively”, as “coupled with,” “coupled to,” “connected with,” or “connected to” another

element (e.g., a second element), it means that the element may be coupled with the other element directly (e.g., wiredly), wirelessly, or via a third element.

(118) As used in connection with various embodiments of the disclosure, the term “module” may include a unit implemented in hardware, software, or firmware, and may interchangeably be used with other terms, for example, “logic,” “logic block,” “part,” or “circuitry”. A module may be a single integral component, or a minimum unit or part thereof, adapted to perform one or more functions. For example, according to an embodiment, the module may be implemented in a form of an application-specific integrated circuit (ASIC).

(119) Various embodiments as set forth herein may be implemented as software (e.g., the program **1040**) including one or more instructions that are stored in a storage medium (e.g., internal memory **1036** or external memory **1038**) that is readable by a machine (e.g., the electronic device **1001**). For example, a processor (e.g., the processor **1020**) of the machine (e.g., the electronic device **1001**) may invoke at least one of the one or more instructions stored in the storage medium, and execute it, with or without using one or more other components under the control of the processor. This allows the machine to be operated to perform at least one function according to the at least one instruction invoked. The one or more instructions may include a code generated by a compiler or a code executable by an interpreter. The machine-readable storage medium may be provided in the form of a non-transitory storage medium. Wherein, the term “non-transitory” simply means that the storage medium is a tangible device, and does not include a signal (e.g., an electromagnetic wave), but this term does not differentiate between where data is semi-permanently stored in the storage medium and where the data is temporarily stored in the storage medium.

(120) According to an embodiment, a method according to various embodiments of the disclosure may be included and provided in a computer program product. The computer program product may be traded as a product between a seller and a buyer. The computer program product may be distributed in the form of a machine-readable storage medium (e.g., compact disc read only memory (CD-ROM)), or be distributed (e.g., downloaded or uploaded) online via an application store (e.g., PlayStore™), or between two user devices (e.g., smart phones) directly. If distributed online, at least part of the computer program product may be temporarily generated or at least temporarily stored in the machine-readable storage medium, such as memory of the manufacturer's server, a server of the application store, or a relay server.

(121) According to various embodiments, each component (e.g., a module or a program) of the above-described components may include a single entity or multiple entities, and some of the multiple entities may be separately disposed in different components. According to various embodiments, one or more of the above-described components may be omitted, or one or more other components may be added.

(122) Alternatively or additionally, a plurality of components (e.g., modules or programs) may be integrated into a single component. In such a case, according to various embodiments, the integrated component may still perform one or more functions of each of the plurality of components in the same or similar manner as they are performed by a corresponding one of the plurality of components before the integration. According to various embodiments, operations performed by the module, the program, or another component may be carried out sequentially, in parallel, repeatedly, or heuristically, or one or more of the operations may be executed in a different order or omitted, or one or more other operations may be added.

(123) FIG. **11** is a block diagram **1100** illustrating the camera module **1080** according to various embodiments.

(124) Referring to FIG. **11**, the camera module **1080** may include a lens assembly **1110**, a flash **1120**, an image sensor **1130**, an image stabilizer **1140**, memory **1150** (e.g., buffer memory), or an image signal processor **1160**. The lens assembly **1110** may collect light emitted or reflected from an object whose image is to be taken. The lens assembly **1110** may include one or more lenses. According to an embodiment, the camera module **1080** may include a plurality of lens assemblies

1110. In such a case, the camera module **1080** may form, for example, a dual camera, a 360-degree camera, or a spherical camera. Some of the plurality of lens assemblies **1110** may have the same lens attribute (e.g., view angle, focal length, auto-focusing, f number, or optical zoom), or at least one lens assembly may have one or more lens attributes different from those of another lens assembly. The lens assembly **1110** may include, for example, a wide-angle lens or a telephoto lens.

(125) The flash **1120** may emit light that is used to reinforce light reflected from an object. According to an embodiment, the flash **1120** may include one or more light emitting diodes (LEDs) (e.g., a red-green-blue (RGB) LED, a white LED, an infrared (IR) LED, or an ultraviolet (UV) LED) or a xenon lamp. The image sensor **1130** may obtain an image corresponding to an object by converting light emitted or reflected from the object and transmitted via the lens assembly **1110** into an electrical signal. According to an embodiment, the image sensor **1130** may include one selected from image sensors having different attributes, such as a RGB sensor, a black-and-white (BW) sensor, an IR sensor, or a UV sensor, a plurality of image sensors having the same attribute, or a plurality of image sensors having different attributes. Each image sensor included in the image sensor **1130** may be implemented using, for example, a charged coupled device (CCD) sensor or a complementary metal oxide semiconductor (CMOS) sensor.

(126) The image stabilizer **1140** may move the image sensor **1130** or at least one lens included in the lens assembly **1110** in a particular direction, or control an operational attribute (e.g., adjust the read-out timing) of the image sensor **1130** in response to the movement of the camera module **1080** or the electronic device **1001** including the camera module **1080**. This allows compensating for at least part of a negative effect (e.g., image blurring) by the movement on an image being captured. According to an embodiment, the image stabilizer **1140** may sense such a movement by the camera module **1080** or the electronic device **1001** using a gyro sensor (not shown) or an acceleration sensor (not shown) disposed inside or outside the camera module **1080**. According to an embodiment, the image stabilizer **1140** may be implemented, for example, as an optical image stabilizer. The memory **1150** may store, at least temporarily, at least part of an image obtained via the image sensor **1130** for a subsequent image processing task. For example, if image capturing is delayed due to shutter lag or multiple images are quickly captured, a raw image obtained (e.g., a Bayer-patterned image, a high-resolution image) may be stored in the memory **1150**, and its corresponding copy image (e.g., a low-resolution image) may be previewed via the display module **1060**. Thereafter, if a specified condition is met (e.g., by a user's input or system command), at least part of the raw image stored in the memory **1150** may be obtained and processed, for example, by the image signal processor **1160**. According to an embodiment, the memory **1150** may be configured as at least part of the memory **1030** or as a separate memory that is operated independently from the memory **1030**.

(127) The image signal processor **1160** may perform one or more image processing with respect to an image obtained via the image sensor **1130** or an image stored in the memory **1150**. The one or more image processing may include, for example, depth map generation, three-dimensional (3D) modeling, panorama generation, feature point extraction, image synthesizing, or image compensation (e.g., noise reduction, resolution adjustment, brightness adjustment, blurring, sharpening, or softening). Additionally or alternatively, the image signal processor **1160** may perform control (e.g., exposure time control or read-out timing control) with respect to at least one (e.g., the image sensor **1130**) of the components included in the camera module **1080**. An image processed by the image signal processor **1160** may be stored back in the memory **1150** for further processing, or may be provided to an external component (e.g., the memory **1030**, the display module **1060**, the electronic device **1002**, the electronic device **1004**, or the server **1008**) outside the camera module **1080**.

(128) According to an embodiment, the image signal processor **1160** may be configured as at least part of the processor **1020**, or as a separate processor that is operated independently from the processor **1020**. If the image signal processor **1160** is configured as a separate processor from the

processor **1020**, at least one image processed by the image signal processor **1160** may be displayed, by the processor **1020**, via the display module **1060** as it is or after being further processed.

(129) According to an embodiment, the electronic device **1001** may include a plurality of camera modules **1080** having different attributes or functions. In such a case, at least one of the plurality of camera modules **1080** may form, for example, a wide-angle camera and at least another of the plurality of camera modules **1080** may form a telephoto camera. Similarly, at least one of the plurality of camera modules **1080** may form, for example, a front camera and at least another of the plurality of camera modules **1080** may form a rear camera.

(130) In various embodiments, an electronic device **100** may include a camera **220** and at least one processor (e.g., the processor **210** in FIG. 2) electrically connected to the camera **220**. The at least one processor may execute the camera **220**, detect at least one object, based on image data obtained through the camera in a first light source environment, analyze color properties of the at least one detected object, determine a first effect, based on the analyzed color properties of the object, apply a second light source effect different from the first light source to the at least one object, and apply the first effect to a background, excluding the at least one object.

(131) According to an embodiment, the at least one processor (e.g., the processor **210** in FIG. 2) may remove an effect of the first light source from the at least one object and apply the second light source effect different from the first light source thereto.

(132) According to an embodiment, the at least one processor (e.g., the processor **210** in FIG. 2) may apply the second light source effect to the object if a size of a face of the at least one object is greater than or equal to a first size and if an angle of the face of the object is less than or equal to a first angle in yaw, roll, and pitch directions.

(133) According to an embodiment, the at least one processor (e.g., the processor **210** in FIG. 2) may obtain a photographing input of a user, obtain at least a first image and a second image in response to the photographing input, apply a first light source effect to the first image, apply the second light source effect to the at least one object of the second image, apply the first effect to the background of the second image, and display the first image and the second image on a display.

(134) According to an embodiment, the at least one processor (e.g., the processor **210** in FIG. 2) may compare a second color value of the second light source effect with a first color value of the first effect. The at least one processor (e.g., the processor **210** in FIG. 2), based on the comparison, if a difference between the color values is equal to or less than a first value, may change a brightness value of at least one of the second light source effect and the first effect.

(135) According to an embodiment, the at least one processor (e.g., the processor **210** in FIG. 2) may apply a contour light effect, in response to detection of a brightness value of the image data, to the at least one object if the brightness value is less than a first brightness value and change and apply the brightness value as a light source effect if the brightness value is greater than or equal to the first brightness value.

(136) According to an embodiment, the at least one processor (e.g., the processor **210** in FIG. 2) may analyze the properties of the first light source by analyzing image data obtained through the camera **220**. The at least one processor (e.g., the processor **210** in FIG. 2) may determine a direction and an intensity of the first light source, based on the analysis, and determine the second light source effect, based on the direction and intensity of the first light source.

(137) According to an embodiment, the at least one processor (e.g., the processor **210** in FIG. 2) may further apply a gradation effect to the background, based on the direction of a light source.

(138) According to an embodiment, the at least one processor (e.g., the processor **210** in FIG. 2) may apply a frame effect to an outer portion of the image data, based on at least one of a size and a position of an area related to the at least one object.

(139) According to an embodiment, the at least one processor (e.g., the processor **210** in FIG. 2) may separate the object and the background through a segmentation technique (e.g., upper body segmentation).

- (140) In various embodiments, a method of operating an electronic device **100** may include executing a camera **220**, detecting at least one object, based on image data obtained through the camera **220** in a first light source environment, analyzing color properties of the at least one detected object, determining a first effect, based on the analyzed color properties of the object, applying a second light source effect different from the first light source to the at least one object, and applying the first effect to a background, excluding the at least one object.
- (141) According to an embodiment, the method of operating an electronic device **100** may include removing an effect of the first light source from the at least one object and applying the second light source effect different from the first light source thereto.
- (142) According to an embodiment, the method of operating an electronic device **100** may include applying the second light source effect to the object if a size of a face of the at least one object is greater than or equal to a first size and if an angle of the face of the object is less than or equal to a first angle in yaw, roll, and pitch directions.
- (143) According to an embodiment, the method of operating an electronic device **100** may include obtaining a photographing input of a user, obtaining at least a first image and a second image in response to the photographing input, applying a first light source effect to the first image, applying the second light source effect to the at least one object of the second image, applying the first effect to the background of the second image, and displaying the first image and the second image on a display.
- (144) According to an embodiment, the method of operating an electronic device **100** may include comparing a second color value of the second light source effect with a first color value of the first effect and, based on the comparison, if a difference between the color values is equal to or less than a first value, changing a brightness value of at least one of the second light source effect and the first effect.
- (145) In various embodiments, an electronic device **100** may include a camera **220** and at least one processor electrically connected to the camera **220**. The at least one processor (e.g., the processor **210** in FIG. 2) may execute the camera **220**, detect at least one object, based on image data obtained through the camera in a first light source environment, analyze properties of the at least one detected object, determine at least one or more light source effects, based on the analyzed properties of the object, apply a second light source effect different from the first light source to the at least one object, and apply a third light source effect different from the second light source effect to a background, excluding the at least one object.
- (146) According to an embodiment, the at least one processor (e.g., the processor **210** in FIG. 2) may separate the object and the background through a segmentation technique (e.g., upper body segmentation).
- (147) According to an embodiment, the at least one processor (e.g., the processor **210** in FIG. 2) may determine the third light source effect, based on at least one of the properties of the object and the second light source effect.
- (148) According to an embodiment, the second light source may be different from at least one of the intensity of the first light source and the direction of the first light source.
- (149) According to an embodiment, the at least one processor (e.g., the processor **210** in FIG. 2) may increase a brightness value of an area corresponding to the at least one object and reduce a brightness value of an area corresponding to the background.

Claims

1. An electronic device comprising: a camera; memory storing computer-executable instructions; and at least one processor electrically connected to the camera and comprising processing circuitry, wherein the instructions cause, when being executed by the at least one processor, the electronic device to: execute the camera; detect at least one object, based on image data obtained through the

camera in a first light source environment comprising a first light source; analyze color properties of the at least one detected object; determine a first effect, based on the analyzed color properties of the at least one detected object, wherein the first effect comprises a first light source effect corresponding to the first light source; apply a second light source effect comprising a relighting effect corresponding to a second light source different from the first light source to the at least one object, wherein the second light source comprises a virtual light source having properties different from the first light source; and apply the first effect to a background, excluding the at least one object.

2. The electronic device of claim 1, wherein the at least one processor is configured to remove an effect of the first light source from the at least one object and apply the second light source effect different from the first light source to the at least one object.

3. The electronic device of claim 1, wherein the at least one processor is configured to apply the second light source effect to the at least one object in response to a size of a face of the at least one object being greater than or equal to a first size and in response to an angle of the face of the object being less than or equal to a first angle in yaw, roll, and pitch directions.

4. The electronic device of claim 1, wherein the at least one processor is configured to: obtain a photographing input of a user; obtain at least a first image and a second image in response to the photographing input; apply the first light source effect to the first image; apply the second light source effect to the at least one object of the second image; apply the first effect to the background of the second image; and display the first image and the second image on a display.

5. The electronic device of claim 1, wherein the at least one processor is configured to compare a second color value of the second light source effect with a first color value of the first effect and, based on the comparison, in case that a difference between the second color value and the first color value is equal to or less than a first value, change a brightness value of at least one of the second light source effect and the first effect.

6. The electronic device of claim 1, wherein the at least one processor is configured to, in response to detection of a brightness value of the image data: apply a contour light effect to the at least one object in response to the brightness value being less than a first brightness value; and in response to the brightness value being greater than or equal to the first brightness value, change and apply the brightness value as a light source effect.

7. The electronic device of claim 1, wherein the at least one processor is configured to: analyze properties of the first light source by analyzing image data obtained through the camera; determine a direction and an intensity of the first light source, based on the analysis; and determine the second light source effect, based on the direction and intensity of the first light source.

8. The electronic device of claim 1, wherein the at least one processor is configured to apply a gradation effect to the background, based on a direction of at least one of the first light source and the second light source.

9. The electronic device of claim 8, wherein the at least one processor is configured to apply a frame effect to an outer portion of the image data, based on at least one of a size and a position of an area related to the at least one object.

10. The electronic device of claim 1, wherein the at least one processor is configured to separate the object and the background through upper body segmentation.

11. A method of operating an electronic device, the method comprising: executing a camera; detecting at least one object, based on image data obtained through the camera in a first light source environment; analyzing color properties of the at least one detected object; determining a first effect, based on the analyzed color properties of the at least one detected object, wherein the first effect comprises a first light source effect corresponding to the first light source; applying a second light source effect comprising a relighting effect corresponding to a second light source different from the first light source to the at least one object, wherein the second light source comprises a virtual light source having properties different from the first light source; and applying the first

effect to a background, excluding the at least one object.

12. The method of claim 11, further comprising: removing an effect of the first light source from the at least one object; and applying the second light source effect different from the first light source to the at least one object.

13. The method of claim 11, further comprising applying the second light source effect to the at least one object in response to a size of a face of the at least one object being greater than or equal to a first size and in response to an angle of the face of the object being less than or equal to a first angle in yaw, roll, and pitch directions.

14. The method of claim 11, further comprising: obtaining a photographing input of a user; obtaining at least a first image and a second image in response to the photographing input; applying the first light source effect to the first image; applying the second light source effect to the at least one object of the second image; applying the first effect to the background of the second image; and displaying the first image and the second image on a display.

15. The method of claim 11, further comprising: comparing a second color value of the second light source effect with a first color value of the first effect; and based on the comparison, in response to a difference between the second color value and the first color value being equal to or less than a first value, changing a brightness value of at least one of the second light source effect and the first effect.

16. An electronic device comprising: a camera; memory storing computer-executable instructions; and at least one processor electrically connected to the camera and comprising processing circuitry, wherein the instructions cause, when being executed by the at least one processor, the electronic device to: execute the camera, detect at least one object based on image data obtained through the camera in a first light source environment comprising a first light source, analyze properties of the at least one detected object, determine at least one light source effect based on the analyzed properties of the at least one detected object, apply, to the at least one detected object, a first light source effect corresponding to a second light source different from the first light source, wherein the second light source comprises a virtual light source having properties different from the first light source, apply, to a background excluding the at least one detected object, a second light source effect which is different from the first light source effect.

17. The electronic device of claim 16, wherein the at least one processor is configured to separate the at least one detected object and the background through upper body segmentation.

18. The electronic device of claim 16, wherein the at least one processor is configured to determine the second light source effect based on at least one of the properties of the at least one detected object or the first light source effect.

19. The electronic device of claim 16, wherein the second light source is different from the first light source in at least one of intensity or direction.

20. The electronic device of claim 16, wherein the at least one processor is configured to increase a brightness value of an area corresponding to the at least one detected object, and decrease a brightness value of an area corresponding to the background.
