

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12383181
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Mattila; Tomi et al.

Elastic wearable sensor

Abstract

In some embodiments, a system includes a first assembly, a second assembly, and a connecting member. The first assembly includes a first electrode and a first adhesive portion. The first assembly is configured to be coupled to a surface of a patient via the first adhesive portion. The second assembly includes a second electrode and a second adhesive portion. The second assembly is configured to be coupled to the surface of the patient via the second adhesive portion. The connecting member has a first end coupled to the first assembly and a second end coupled to the second assembly. The connecting member is configured to transition between a first configuration and a second configuration and may be configured to be coupled to the surface of the patient via a third adhesive portion in both the first configuration and the second configuration.

Inventors:	Mattila; Tomi (Espoo, FI), Jokelainen; Kimmo (Ii, FI), Yrjänä; Samuli (Oulu, FI), McCaffrey; Colm (Helsinki, FI), Behfar; Mohammadhossein (Espoo, FI), Kyynäräinen; Jukka (Espoo, FI), Rantala; Arto (Espoo, FI)
Applicant:	Otsuka Pharmaceutical Co., Ltd. (Tokyo, JP)
Family ID:	69528911
Assignee:	OTSUKA PHARMACEUTICAL CO, LTD. (Tokyo, JP)
Appl. No.:	17/424757
Filed (or PCT Filed):	January 24, 2020
PCT No.:	PCT/JP2020/002521
PCT Pub. No.:	WO2020/153479
PCT Pub. Date:	July 30, 2020

Prior Publication Data

Related U.S. Application Data

us-provisional-application US 62796435 20190124

Publication Classification

Int. Cl.: A61B5/257 (20210101)

U.S. Cl.:

CPC A61B5/257 (20210101);

Field of Classification Search

CPC: A61B (5/257); A61B (5/25); A61B (5/24); A61B (5/251)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4957109	12/1989	Groeger et al.	N/A	N/A
6129929	12/1999	Wick	N/A	N/A
6278036	12/2000	Anhauser et al.	N/A	N/A
6572636	12/2002	Hagen et al.	N/A	N/A
8688189	12/2013	Shennib	N/A	N/A
8897868	12/2013	Mazar et al.	N/A	N/A
11095821	12/2020	Katayama	N/A	N/A
2006/0030781	12/2005	Shennib	N/A	N/A
2006/0030782	12/2005	Shennib	N/A	N/A
2006/0224072	12/2005	Shennib	N/A	N/A
2007/0260133	12/2006	Meyer	N/A	N/A
2007/0299471	12/2006	Takahashi et al.	N/A	N/A
2008/0135408	12/2007	Sjolander	204/403.01	A61B 5/1468
2009/0076365	12/2008	Grassl	N/A	N/A
2009/0264792	12/2008	Mazar	N/A	N/A
2011/0009729	12/2010	Shin	600/391	A61B 5/6833
2011/0130640	12/2010	Dunagan	600/388	A61B 5/6804
2011/0160601	12/2010	Wang et al.	N/A	N/A
2015/0018643	12/2014	Cole et al.	N/A	N/A
2016/0135746	12/2015	Kumar et al.	N/A	N/A
2016/0166170	12/2015	Quintanar et al.	N/A	N/A
2016/0262649	12/2015	Hayes-Gill	N/A	A61B 5/339

2017/0265770	12/2016	Quinlan	N/A	N/A
2018/0014783	12/2017	Shi et al.	N/A	N/A
2019/0000341	12/2018	Xu et al.	N/A	N/A
2022/0117533	12/2021	Mattila et al.	N/A	N/A
2022/0117534	12/2021	Mattila et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
101385645	12/2008	CN	N/A
104144638	12/2013	CN	N/A
105050495	12/2014	CN	N/A
102112572	12/2016	CN	N/A
106923816	12/2016	CN	N/A
202013011290	12/2013	DE	A61B 5/282
0356614	12/1989	EP	N/A
0 509 689	12/1991	EP	N/A
0596604	12/1993	EP	N/A
0882460	12/1997	EP	N/A
1104325	12/2000	EP	N/A
2105089	12/2008	EP	N/A
2854937	12/2014	EP	N/A
3348490	12/2017	EP	N/A
2540955	12/2016	GB	N/A
4261699	12/2008	JP	N/A
5442112	12/2013	JP	N/A
5693874	12/2014	JP	N/A
201501692	12/2014	TW	N/A
201825045	12/2017	TW	N/A
WO-2010017276	12/2009	WO	N/A
WO-2013059600	12/2012	WO	N/A
WO-2013121415	12/2012	WO	N/A
2014/116816	12/2013	WO	N/A
2014/151925	12/2013	WO	N/A
WO-2015055289	12/2014	WO	N/A
2016/053731	12/2015	WO	N/A
WO-2016052818	12/2015	WO	N/A
WO-2017184596	12/2016	WO	N/A
2018/098417	12/2017	WO	N/A
WO-2020153479	12/2019	WO	N/A
WO-2020179922	12/2019	WO	N/A
WO-2020179924	12/2019	WO	N/A

OTHER PUBLICATIONS

Translation of DE-202013011290-U1, 2014 (Year: 2014). cited by examiner

Translation of DE 202013011290 (Year: 2013). cited by examiner

International Preliminary Report on Patentability for International Application No.

PCT/JP2020/002521, mailed Aug. 5, 2021, 16 pages. cited by applicant

International Search Report for International Application No. PCT/JP2020/002521, mailed Jul. 28, 2020, 6 pages. cited by applicant

AliveCor, Inc. "KardiaBand System Instructions for Use," (Nov. 2017), 2 pages. cited by applicant

AliveCor, Inc., “Kardia Mobile Instructions for Use,” (Nov. 2016), 2 pages. cited by applicant

Altini, M., “On Heart Rate Variability and the Apple Watch,” (Nov. 10, 2018), 15 pages. cited by applicant

Cardiac Insight, Inc., “Cardeo Solo Operator's Manual,” Model S300, (Dec. 2018), 65 pages. cited by applicant

CardioComm Solutions, Inc., Press Release, “CardioComm Solutions Introduces the HeartCheck™ ECG Sport—A Smartphone Connected, Wearable, Single & Multi-lead ECG Chest Patch,” [online], Retrieved from the Internet: https://www.cardiocommsolutions.com/news/2016/CCSnews_102016.html, (Oct. 20, 2016), 4 pages. cited by applicant

HeartCheck Handheld ECG Monitor Instruction Manual MD100B, Edition: VER1.0B1, Jul. 20, 2010, 35 pages. cited by applicant

International Preliminary Report on Patentability for International Application No. PCT/JP2020/009803 mailed Jun. 11, 2021, 7 pages. cited by applicant

International Preliminary Report on Patentability for International Application No. PCT/JP2020/009815 mailed Apr. 12, 2021, 10 pages. cited by applicant

International Search Report and Written Opinion of the International Searching Authority for International Application No. PCT/JP2020/009803 mailed May 28, 2020, 12 pages. cited by applicant

International Search Report and Written Opinion of the International Searching Authority for International Application No. PCT/JP2020/009815 mailed May 28, 2020, 14 pages. cited by applicant

IRhythm Technologies, Inc., ZioXT Patch Patient Experience Brochure, Feb. 2016, 12 pages. cited by applicant

Lindsey, D. P. et al., “A New Technique for Transmission of Signals from Implantable Transducers,” IEEE Transactions on Biomedical Engineering, vol. 45, No. 5, pp. 614-619 (May 1998). cited by applicant

“Maxim Integrated Launches a Movesense Based ECG Development Platform,” [online], Retrieved from the Internet: <https://www.movesense.com/news/2018/06/maxim-integrated-launches-a-movesense-based-ecg-development-platform/>, (Jun. 25, 2018), 4 pages. cited by applicant

MC10 BioStamp nPoint User Manual, Copyright 2016, 72 pages. cited by applicant

MC10, “Introducing BioStamp nPoint, Making Virtual Clinical Trials a Reality,” [online], Retrieved from the Internet: <https://web.archive.org/web/20181217224816/https://www.mc10inc.com/>, (Dec. 17, 2018), 8 pages. cited by applicant

Medqor, “Actiwave Cardio by CamNTEch,” [online], Retrieved from the Internet: <https://sleepreviewmag.com/sleep-diagnostics/in-lab-tests/polysomnography/actiwave-cardio-by-camntech/>, (Nov. 25, 2013), 3 pages. cited by applicant

Medtronic, SEEQ Mobile Cardiac Telemetry (MCT) System, Instructions for Use (Mar. 12, 2015), 26 pages. cited by applicant

Mega Electronics Ltd., “800778 eMotion Faros Series Manual 2.3.0,” (Apr. 10, 2017), 42 pages. cited by applicant

Vital Signum, “Beat2Phone User Guide,” Version 1.1, Android, [online], Retrieved from the Internet: www.manualslib.com, (Oct. 2017), 12 pages. cited by applicant

VitalConnect, “VitalPatch,” [Online], Retrieved from the Internet: <https://web.archive.org/web/20170830052411/https://vitalconnect.com/solutions/vitalpatch/>, (Aug. 30, 2017), 3 pages. cited by applicant

Wayback Machine, “HeartyPatch,” [online], Retrieved from the Internet: <https://web.archive.org/web/20180530180927/https://www.crowdsupply.com/protocentral/heartypatch>, (May 30, 2018), 16 pages. cited by applicant

Written Opinion of the International Preliminary Examining Authority for International Application No. PCT/JP2020/009803 dated Jan. 14, 2021, 7 pages. cited by applicant

Written Opinion of the International Preliminary Examining Authority for International Application

Primary Examiner: Minchella; Adam Z

Attorney, Agent or Firm: Pillsbury Winthrop Shaw Pittman LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a U.S. National Stage Application under 35 U.S.C. § 371 of International Application No. PCT/JP2020/002521, filed Jan. 24, 2020, entitled “ELASTIC WEARABLE SENSOR” which claims priority to and the benefit of U.S. Provisional Application No. 62/796,435, filed Jan. 24, 2019, entitled “Elastic Wearable Sensor,” the entire contents of each of which is hereby expressly incorporated by reference for all purposes.

TECHNICAL FIELD

(1) Some embodiments described herein relate generally to systems, methods, and apparatus for elastic wearable sensors that are able to accommodate skin deformation.

BACKGROUND ART

(2) The non-invasive measurement of electrical potential differences (e.g., biosignals) between locations on the skin of a human or animal may be used to diagnose and monitor a condition of the human or animal. For example, the measurement of electrical potential differences between locations on the skin may be used in performing an electrocardiogram (ECG), an electroencephalogram (EEG), and an electromyogram (EMG). The measurement of the electrical potential difference between locations on the skin may include coupling an electrode at each location, electrically coupling each electrode to an electronics module, and comparing the electric potential measured at the location of at least one of the electrodes to a reference electric potential (e.g., the electric potential measured at the location of another electrode).

(3) Furthermore, in in vivo telemetry applications, sensors on the skin of a human or animal may be configured to communicate with implanted or digested devices (e.g., digital medicines). For example, an implanted or digested device disposed within a patient may be able to communicate signals to a surface of the patient via body tissue. Using the body tissue as a conductive transmission medium, the signal may be detectable on the surface of the patient as an electrical potential difference.

(4) To detect events that may occur only occasionally, a sensor device may be attached to the surface of the patient for an extended period of time (e.g., hours or days). For example, for the detection of occasional cardiac arrhythmias, a Holter monitoring device may be attached to a patient for twenty-four hours or longer.

(5) Human skin, however, is highly elastic. For example, a typical range for the elastic constant of human skin is 0.1 to 2 MPa and may depend on factors including body location and age. Furthermore, natural movement of the patient may result in significant compressive and tensile skin strain, sometimes even in the range of 30-50% in the chest region, for example. Maintaining attachment between electrodes and human skin can present challenges, especially if the skin moves significantly due to patient movement and if the electrodes are intended to remain attached over an extended period of time (e.g., hours, days, weeks). Skin strain may cause stress on the interface between the adhesive and the skin of the patient, causing discomfort to the patient and weakening the adhesion. The use of strong adhesives used to attach the sensor device to the patient's skin may

be uncomfortable for the patient due to lack of breathability and/or causing skin irritation.

(6) Thus, there is a need for a sensor systems, methods, and apparatus that can accommodate movement-induced skin deformations while also improving adhesion durability, being breathable, and improving conformality with the skin surface.

SUMMARY OF INVENTION

(7) In some embodiments, a system includes a first assembly, a second assembly, and a connecting member. The first assembly includes a first electrode and a first adhesive portion. The first assembly is configured to be coupled to a surface of a patient via the first adhesive portion. The second assembly includes a second electrode and a second adhesive portion. The second assembly is configured to be coupled to the surface of the patient via the second adhesive portion. The connecting member has a first end, a second end, and a third adhesive portion. The first end is coupled to the first assembly and the second end is coupled to the second assembly. The connecting member is configured to transition between a first configuration and a second configuration. The distance between the first end and the second end of the connecting member in the first configuration is a first distance. The distance between the first end and the second end of the connecting member in the second configuration is a second distance. The second distance is different from the first distance. The connecting member may be configured to be coupled to the surface of the patient via the third adhesive portion in both the first configuration and the second configuration.

Description

BRIEF DESCRIPTION OF DRAWINGS

- (1) FIG. 1 is a schematic illustration of a sensor system, according to an embodiment.
- (2) FIG. 2A is an illustration of a top view of a sensor system, according to an embodiment.
- (3) FIG. 2B is an illustration of a side view of the sensor system of FIG. 2A prior to the sensor system being coupled to a surface of a skin of a patient.
- (4) FIG. 3A is an illustration of a side view of a sensor system in a first configuration, according to an embodiment.
- (5) FIG. 3B is an illustration of a side view of the sensor system of FIG. 3A in a second configuration.
- (6) FIG. 3C is an illustration of a side view of the sensor system of FIG. 3A in a third configuration.
- (7) FIG. 4A is an illustration of a side view of a sensor system in a first configuration, according to an embodiment.
- (8) FIG. 4B is an illustration of a side view of the sensor system of FIG. 4A in a second configuration.
- (9) FIG. 5A is an illustration of a bottom view of a sensor system, according to an embodiment.
- (10) FIG. 5B is an illustration of a bottom view of a sensor system, according to an embodiment.
- (11) FIG. 5C is an illustration of a bottom view of a sensor system, according to an embodiment.
- (12) FIG. 6 is a perspective view of a sensor system, according to an embodiment.
- (13) FIG. 7 is a perspective exploded view of a sensor system, according to an embodiment.
- (14) FIG. 8A is a schematic illustration of a cross section of a connecting member of a sensor system, according to an embodiment.
- (15) FIG. 8B is a schematic illustration of a cross section of a connecting member of a sensor system, according to an embodiment.
- (16) FIG. 8C is a schematic illustration of a cross section of a connecting member of a sensor system, according to an embodiment.
- (17) FIG. 8D is a schematic illustration of a cross section of a connecting member of a sensor

system, according to an embodiment.

(18) FIG. 9 is a top view of a sensor system, according to an embodiment.

(19) FIG. 10 is a schematic illustration of a sensor system, according to an embodiment.

(20) FIG. 11 is a schematic illustration of a sensor system, according to an embodiment.

(21) FIG. 12 is a schematic illustration of a sensor system, according to an embodiment.

(22) FIG. 13 is a schematic illustration of a sensor system, according to an embodiment.

(23) FIG. 14A is an illustration of a top view of a sensor system, according to an embodiment.

(24) FIG. 14B is an illustration of a side view of the sensor system of FIG. 14A.

(25) FIG. 15A is an illustration of a top view of a sensor system, according to an embodiment.

(26) FIG. 15B is an illustration of a side view of the sensor system of FIG. 15A.

DESCRIPTION OF EMBODIMENTS

(27) In some embodiments, a system includes a first assembly, a second assembly, and a connecting member. The first assembly includes a first electrode and a first adhesive portion. The first assembly is configured to be coupled to a surface of a patient via the first adhesive portion. The second assembly includes a second electrode and a second adhesive portion. The second assembly is configured to be coupled to the surface of the patient via the second adhesive portion. The connecting member has a first end, a second end, and a third adhesive portion. The first end is coupled to the first assembly and the second end is coupled to the second assembly. The connecting member is configured to transition between a first configuration and a second configuration. The distance between the first end and the second end of the connecting member in the first configuration is a first distance. The distance between the first end and the second end of the connecting member in the second configuration is a second distance. The second distance is different from the first distance. The connecting member may be configured to be coupled to the surface of the patient via the third adhesive portion in both the first configuration and the second configuration.

(28) In some embodiments, a system includes a first assembly, a second assembly, and a composite assembly. The first assembly includes a first electrode and a first housing. The first assembly is configured to be coupled to a surface of a patient's skin via a first adhesive portion. The second assembly includes a second electrode and a second housing. The second assembly is configured to be coupled to a surface of a patient's skin via a second adhesive portion. The composite assembly includes a processor and a composite board having a flexible portion. The flexible portion has a first end and a second end. The processor is disposed between the first electrode and the first housing. The composite assembly is configured to transition from a first configuration to a second configuration. A distance between the first end and the second end of the flexible portion in the first configuration is a first distance and a distance between the first end and the second end of the flexible portion in the second configuration is a second distance different from the first distance.

(29) In some embodiments, a system includes a first assembly, a second assembly, and a composite assembly. The first assembly includes a first electrode and a first adhesive portion. The first assembly is configured to be coupled to a surface of a patient via the first adhesive portion. The second assembly includes a second electrode and a second adhesive portion. The second assembly is configured to be coupled to a surface of a patient via the second adhesive portion. The composite assembly has a flexible portion. The flexible portion has a first end, a second end, and a plurality of layers. Each layer from the plurality of layers has a conductor extending between the first end and the second end. The first end is coupled to the first assembly and the second end is coupled to the second assembly. The composite assembly is configured to electrically couple the first assembly with the second assembly. The flexible portion is configured to transition from a first configuration to a second configuration. A distance between the first end and the second end of the flexible portion in the first configuration is a first distance. A distance between the first end and the second end of the flexible portion in the second configuration is a second distance different from the first distance. The flexible portion is configured to be coupled to a surface of a patient via a third

adhesive portion in both the first configuration and the second configuration.

(30) FIG. 1 is a schematic illustration of a sensor system **100**. The system **100** may be, for example, formed as a patch. As shown in FIG. 1, the system **100** includes a first assembly **110**, a second assembly **120**, and a connecting member **130**. The first assembly **110** includes a first electrode **112** and a first adhesive portion **114**. The first assembly **110** is configured to be coupled to a surface of a patient via the first adhesive portion **114**. The second assembly **120** includes a second electrode **122** and a second adhesive portion **124**. The second assembly **120** is configured to be coupled to the surface of the patient via the second adhesive portion **124**. The connecting member **130** has a first end **136** and a second end **138**. The first end **136** is coupled to the first assembly **110** and the second end **138** is coupled to the second assembly **120**. The first electrode **112** and the second electrode **122** may be galvanic or non-galvanic.

(31) The connecting member **130** is configured to transition between a first configuration and a second configuration. The distance between the first end **136** and the second end **138** of the connecting member **130** in the first configuration may be a first distance. The distance between the first end **136** and the second end **138** of the connecting member **130** in the second configuration may be a second distance. The second distance is different from the first distance. For example, the second difference may be greater than or less than the first distance.

(32) In some implementations, the connecting member **130** includes a third adhesive portion **134**. The connecting member **130** can be configured to be coupled to the surface of the patient via the third adhesive portion **134** in both the first configuration and the second configuration. In some implementations, the connecting member **130** can be configured to be coupled to the surface of the patient via the third adhesive portion **134** during a transition from the first configuration to the second configuration and/or during a transition from the second configuration to the first configuration. In some implementations, the connecting member **130** can include a skin-facing surface. The skin-facing surface can extend from the first end **136** to the second end **138** of the connecting member **130**. The third adhesive portion **134** may be disposed on all or a portion of the skin-facing surface.

(33) In some embodiments, the system **100** includes a composite assembly **140**. The composite assembly **140** can be included in and/or otherwise form an integrated circuit (IC), a printed circuit board (PCB) assembly including a printed circuit board, an application-specific integrated circuit (ASIC), or any other suitable electrical circuit structure. For example, the composite assembly **140** can include a composite board (e.g., a printed circuit board) and any suitable electronic components. The electronic components can be electrically coupled to the composite board. The electronic components can be coupled to conductors (e.g., conductive traces) of the composite board via, for example, soldering, spot welding, conductive adhesives, and/or via a tab contact. The conductive traces can be etched into the composite board. The electronic components can include, for example, a processor, an energy storage device, a memory, a transmitter, and/or a receiver. The electronic components can also include, for example, biosignal acquisition electronic components such as an analog front-end (e.g., a preamplifier) and/or an analog-to-digital converter. The energy storage device can include, for example, a battery or a capacitor. In some implementations, the energy storage device can include a coin cell battery. In some implementations, the transmitter and/or the receiver can include an antenna and can be able to communicate wirelessly via, for example, Bluetooth(trademark), near-field communication, and/or WiFi. In some implementations, the composite assembly **140**, the first electrode **112**, and the second electrode **122** can collectively be configured to perform any suitable type of monitoring such as ECG, EEG, EMG, and/or galvanic skin response (GSR) monitoring. In some implementations, the composite assembly **140** can include all of the electronic components necessary for the system **100** to be fully operational to perform a monitoring operation (e.g., ECG) and transmit the data gathered via the first electrode **112** and the second electrode **122** wirelessly to any suitable receiving device (e.g., an external computer or smart phone).

(34) In some implementations, the composite board of the composite assembly **140** can be a one-piece monolithic structure. In some implementations, the composite board can be formed of an insulator. The insulator may include, for example, polyimide. In some implementations, the composite board can be formed of any suitable material such as, for example, polyethylene terephthalate (PET) or polyethylene naphthalate (PEN). In some implementations, the composite assembly **140** can include any number of conductive layers that are physically and electrically separated by a corresponding number of insulating layers. The insulating layers can be formed from an insulating and/or dielectric material such as polyimide, fiberglass, cotton, silicone, and/or the like that can be bound by any suitable resin material (e.g., epoxy, polyimide, or the like). Thus, the insulating layers can be, for example, dielectric layers and/or core layers that can physically and electrically separate the conductive layers.

(35) In some implementations, the composite board can be a laminated composite board. For example, the conductive layers can be, for example, relatively thin conductive sheets that are disposed on at least one surface of an insulating layer (i.e., a core layer). For example, the conductive layer can be copper, silver, aluminum, gold, zinc, tin, tungsten, graphite, conductive polymer, and/or any other suitable conductive material. In this manner, the conductive sheet can be masked and the undesired portions of the conductive sheet can be etched away, thereby leaving a desired set of conductive traces. Moreover, the composite assembly **140** can include any number of alternately stacked insulating layers and conductive layers and can include a set of electrical interconnects (e.g., vias, pressed pins, bus bars, terminals, etc.) that can selectively place the conductive layers in electrical contact. Thus, the composite assembly **140** can be configured to carry a current (e.g., associated with power distribution, a signal carrying information and/or induced by a magnetic source) along a length of the conductive traces.

(36) In some implementations, the composite board can include conductors (e.g., conductive traces) printed on one or both sides of the composite board such that the composite assembly **140** can be configured to carry a current (e.g., associated with power distribution, a signal carrying information and/or induced by a magnetic source) along a length of each of the conductors. For example, the composite board can include a carrier film (e.g., a PET or PEN carrier film) onto which conductors can be printed via an additive manufacturing process. In some implementations, the conductors can be formed by printed silver and/or printed copper. In some implementations, the composite board may include any number of layers having conductors printed on one or both sides, and each of the layers having conductors can be physically and electrically separated from one another by a corresponding number of insulating layers (e.g., the layers having conductors and the insulating layers can be alternately stacked). In some implementations, the composite assembly **140** can include a two-layer conductor structure. The two-layer conductor structure can be formed via multi-layer printing. An insulator can be printed at the location of any conductor crossings. In some implementations, the two-layer conductor structure can be formed using a through-substrate-via approach.

(37) In some implementations, the composite assembly **140** can include a number of composite boards or board layers. Each of the composite boards can be monolithically formed. The composite boards or board layers can be arranged relative to one another in any suitable arrangement (e.g., stacked).

(38) In some implementations, the connecting member **130** (e.g., one or more composite boards of the composite assembly) can be sufficiently flexible such that the connecting member **130** can change in shape while remaining coupled to the first assembly **110** and the second assembly **120** when the first assembly **110** is moved relative to the second assembly **120** (e.g., due to movement of the skin locations to which the first assembly **110** and the second assembly **120** are coupled). Thus, the connecting member **130** can accommodate skin deformations by reducing stress at the skin-adhesive interface compared to a connecting member with an undeforming shape, causing better adhesion durability and better wear comfort for the user. In some implementations, the

connecting member **130** may include a number of portions (e.g., arranged in series) configured to move relative to one another when the first assembly **110** is moved relative to the second assembly **120** such that the connecting member **130** remains coupled to the first assembly **110** and the second assembly **120**.

(39) In some implementations, the connecting member **130** (e.g., one or more composite boards of the composite assembly) can be sufficiently flexible such that the connecting member **130** can deform from an initial configuration or shape when the first assembly **110** is moved relative to the second assembly **120** (e.g., due to movement of the skin locations to which the first assembly **110** and the second assembly **120** are coupled). In some implementations, the connecting member **130** (e.g., one or more composite boards of the composite assembly), can be sufficiently elastic such that the connecting member **130** can function as a spring arranged between the first assembly **110** and the second assembly **120**, allowing for expansion and contraction of the length of the connecting member **130** relative to an equilibrium or undeformed length.

(40) In some implementations, the connecting member **130** can have rigid or semi-rigid end portions and a flexible portion extending between the ends. For example, the end portions can be made of rigid or semi-rigid PCB material (e.g., FR4) and the flexible portion between the ends can be formed of polyimide. In some implementations, the portions of a composite board of the composite assembly **140** included in the first assembly **110** and/or the second assembly **120** can be rigid or semi-rigid (e.g., formed of FR4-type PCB), and a portion of the composite board included in the connecting member **130** can be flexible (e.g., formed of a flexible PCB including, for example, polyimide). In some implementations, the first end **136** and the second end **138** of the connecting member **130** can include or be coupled to a first end and a second end of a flexible portion of a composite board included in the composite assembly **140**. In some implementations, a composite board of the composite assembly **140** can be fully flexible such that a portion of the composite board included in the first assembly **110**, a portion of the composite board included in the second assembly **120**, and a portion of the composite board included in the connecting member **130** are all flexible. For example, the composite board may be formed as a monolithic flexible structure.

(41) As shown in FIG. 1, a portion of the composite assembly **140** can be included within or coupled to the first assembly **110**, the second assembly **120**, and/or the connecting member **130**. For example, a deformable portion of the composite board of the composite assembly can be included in the connecting member **130**, and each of the electronic components can be included in the first assembly **110** or the second assembly **120** and coupled to portions of the composite board included in the first assembly or the second assembly **120**. For example, the energy storage device can be included in the second assembly **120** and coupled to the composite board **140**, and other electronic components such as the processor, memory, transmitter, and/or receiver can be included in the first assembly **110** and coupled to the composite board **140**. The connecting member **130** can include only a portion (also referred to herein as a “flexible portion”) of the composite board. The flexible portion of the composite board may have a first end and a second end coupled to the first end **136** and the second end **138**, respectively. In some implementations, at least a portion of the composite board of the composite assembly **140** is flexible and/or elastic.

(42) In some implementations, the connecting member **130** or a portion of the connecting member **130** can be flexible. In some implementations, the connecting member **130** or a portion of the connecting member **130** can be inelastic and/or rigid. In some implementations, the connecting member **130** or a portion of the connecting member can be elastic. In some implementations, the first configuration of the connecting member **130** can be an undeformed configuration toward which the connecting member **130** is elastically biased. The second configuration of the connecting member **130** can be a deformed configuration different from the undeformed configuration. The connecting member **130** can be configured to be deformed from the first configuration to the second configuration when a force is applied to the first end **136** and/or the second end **138** of the

connecting member **130**. The connecting member **130** can be configured to transition from the second configuration to the first configuration when the force is removed.

(43) The connecting member **130** can have any suitable shape. The portion of the composite assembly **140** (e.g., a portion of the composite board of the composite assembly **140**) included within or forming the connecting member **130** (e.g., a flexible portion of the composite board of the composite assembly **140**) can have any suitable shape. The shape of the connecting member **130** can correspond to the shape of a portion of the composite board included in the connecting member **130**. In some implementations, at least a portion of the composite board of the composite assembly **140** is biased toward a first undeformed configuration such that the connecting member **130** is biased toward the first configuration.

(44) In some implementations, the connecting member **130** can have an arched or curved shape extending from the first end **136** to the second end **138**. In some implementations, the connecting member **130** can have a shape including a pattern with any suitable number of repeating portions. For example, the connecting member **130** can have a serpentine shape, a sinusoidal shape, a zig-zag shape, a repeating sawtooth shape, a repeating triangle shape, and/or any combination of shapes. In some implementations, the connecting member **130** can be shaped as a sinusoidal wave including two, three, four, five, or more periods. In some implementations, the connecting member **130** can be shaped as a sinusoidal wave having any suitable number of periods with any suitable wavelength and/or amplitude. For example, the connecting member **130** may be shaped to include one, two, three, four, five, or more periods of a sinusoidal wave at any suitable wavelength, amplitude, and/or frequency. In some implementations, the connecting member **130** can be shaped as a sinusoidal wave having multiple periods having varying wavelengths and/or amplitudes from the first end **136** to the second end **138** of the connecting member **130**. In some implementations, the connecting member **130** can have a first sinusoidal shape having a first frequency in the first configuration and a second sinusoidal shape having a second frequency in the second configuration, the second frequency different from (e.g., larger or smaller than) the first frequency.

(45) In some implementations, the connecting member **130** can include a number of inelastic segments coupled together by elastic portions. For example, the connecting member **130** can include a first segment, a second segment, and an elastic hinge coupling the first segment to the second segment. In some implementations, the elastic hinge can form a curved portion and the first segment and the second segment may each be curved or straight. In some implementations, the curved portion can include an arc segment. In some implementations, the elastic hinge can form an angled portion and the first segment and the second segment can each be straight portions. In some implementations, for example, the elastic hinge, first segment, and second segment can be arranged such that the first segment is arranged at an angle ranging from about 5° to about 120° relative to the second segment in the first, undeformed configuration. In some implementations, the connecting member **130** can have a number of elastic hinges coupling segments of the connecting member **130** to one another. For example, the connecting member **130** can include three segments, four segments, five segments, seven segments, or any other suitable number of segments, each segment being coupled to an adjacent segment by an elastic hinge.

(46) In some implementations, the connecting member **130** can have a length (e.g., a distance from the first end **136** to the second end **138**) and a width (e.g., a distance from an outermost edge of the connecting member **130** extending in a first direction extending perpendicularly relative to a line extending between the first assembly **110** and the second assembly **120** to an outermost edge of the connecting member **130** extending in a second direction opposite the first direction). The length of the connecting member **130** may be measured in an X-direction and the width may be measured in a Y-direction perpendicular to the X-direction. The connecting member **130** can have a first overall length and a first width in the first configuration and a second length and a second width in the second configuration. When the first assembly **110** and the second assembly **120** are closer to each other in the second configuration than in the first configuration, the second length may be smaller

than the first length and the second width may be greater than the first width. When the first assembly **110** and the second assembly **120** are farther from each other in the second configuration than in the first configuration, the second length may be greater than the first length and the second width may be smaller than the first width.

(47) In some implementations, the connecting member **130** can have the same overall shape (e.g., a zig-zag shape or a sinusoidal shape) in the first configuration and the second configuration, and the shape can be compressed or expanded in the second configuration compared to the first configuration. For example, an angle between two segments coupled via an elastic hinge of the connecting member **130** can be a first angle in the first configuration and a second angle in the second configuration. When the first assembly **110** and the second assembly **120** are closer to each other in the second configuration than in the first configuration, the second angle may be smaller than the first angle. When the first assembly **110** and the second assembly **120** are farther from each other in the second configuration than in the first configuration, the second angle may be greater than the first angle.

(48) The connecting member **130** can have any suitable thickness along the length of the connecting member **130** and/or height relative to a bottom surface of the connecting member **130**. In some implementations, the thickness of the connecting member **130** may vary along the length of the connecting member **130** (e.g., one or more portions of the connecting member **130** may be thicker compared to more narrow portions of the connecting member **130**). The height of the connecting member **130** can be a distance extending in a Z-direction which is perpendicular to both the X and Y-directions. The thickness can be a distance disposed in a plane including the X and Y-directions (as describe in more detail below). In some embodiments, the thickness of the connecting member **130** and/or the height of the connecting member **130** can be sufficiently small such that the connecting member **130** is sufficiently elastic (e.g., has a sufficiently small spring constant) to expand and contract based on movement (e.g., deformation such as flexing) of the skin to prevent discomfort and/or detachment of the system **100** from the skin. For example, the thickness of the connecting member **140** and/or the height of the connecting member **130** can be sufficiently small such that the connecting member **130** has enough elasticity from a first end **136** of the connecting member **130** to a second end **138** of the connecting member **130** to expand and contract based on movement of the skin locations to which the first assembly **110** and the second assembly **120** are attached (i.e., such that skin elasticity can be accommodated by the connecting member **130**). As an example, the surface of the skin to which the system **100** can be coupled may have an elasticity in the range of 0.1 to 2 MPa, and the connecting member **130** can have an elasticity equivalent to or less than the elasticity of the surface of the skin to which the system **100** is coupled such that the connecting member **130** can expand and contract in the X-direction with the deformation of the skin to which the first assembly **110** and the second assembly **120** is attached. In some implementations, the thickness of the connecting member **130** can be, for example, equal to or less than 100 μm . In some implementations, the height of the connecting member **130** can be, for example, equal to or less than 36 μm . In some implementations, the spring constant of the connecting member **130** (in the X-direction) can increase proportionally to a cube of the thickness of the connecting member **130** and linearly with respect to the height of the connecting member **130**.

(49) In some implementations, the first assembly **110** includes a first housing and the second assembly **120** includes a second housing. The connecting member **130** may optionally include a third housing. In some implementations, the first adhesive portion **114** can be disposed on a skin-facing surface of the first housing and the second adhesive portion **124** can be disposed on a skin-facing surface of the second housing. The third adhesive portion **134** can be disposed on a skin-facing surface of the third housing. The skin-facing surface of the first housing, the skin-facing surface of the second housing, and the skin-facing surface of the third housing can collectively form a continuous border along the outer edges of the system **100** configured to couple to a surface

of a patient (e.g., skin). The first adhesive portion **114** can partially or fully surround the first electrode **112** and the second adhesive portion **124** can partially or fully surround the second electrode. In some implementations, the third housing can have a shape corresponding to the connecting member **130**. The skin-facing surface of the third housing has sufficient surface area such that the third adhesive portion **134** can have a large enough surface area to maintain attachment between the connecting member **130** and the surface of the patient and to maintain conformality of the system **100** with the surface of the patient. By maintaining the attachment between the connecting member **130** and the surface of the patient, the third adhesive portion **134** can reduce motion artifacts (e.g., noise caused by movement of conductive traces in the connecting member **130**) in the signal recorded by the composite assembly **140**.

(50) In some implementations, the first housing, the second housing, and the third housing collectively form a cover layer and/or a bottom layer. The cover layer can be shaped and sized such that the cover can protect the composite assembly **140** when the system **100** is disposed on a surface of a patient. In some implementations, the bottom layer can be shaped and sized such that the composite assembly **140** can be disposed between the cover layer and the bottom layer and the bottom layer can be disposed between the composite assembly **140** and the surface of the patient when the system **100** is coupled to the surface of the patient. The bottom surface can be coupled to the surface of the patient via the first adhesive portion **114**, the second adhesive portion **124**, and, optionally, the third adhesive portion **134**. In some implementations, the bottom layer can define a first opening configured such that the first electrode **112** can contact the surface of the patient through the first opening and a second opening configured such that the second electrode **122** can contact the surface of the patient through the second opening. In some implementations, the cover layer may be monolithically or integrally formed. In some implementations, the bottom layer may be monolithically or integrally formed.

(51) In some implementations, the cover layer and the bottom layer can protect the system **100** from external effects (e.g., liquid (e.g., water or sweat) or mechanical impacts). In some implementations, the cover layer and the bottom layer can provide a sealed enclosure surrounding the composite assembly **140** such that the composite assembly **140** is protected from water during activities of the user such as, for example, showering or swimming. In some implementations, the bottom layer can include an adhesive on a side of the bottom layer facing the composite assembly **140** such that the bottom layer can be secured to the composite assembly **140**. In some implementations, the system **100** can be waterproof and/or breathable for skin comfort. In some implementations, the system **100** can include hydrogel disposed on a skin-contacting side of the first electrode **112** and on a skin-contacting side of the second electrode **124**. In some implementations, the hydrogel can include cut pads (e.g., cut from a hydrogel sheet). In some implementations, the hydrogel can be in the form of a dispensable gel. In some implementations, rather than including hydrogel, the first electrode **112** and the second electrode **124** can be dry electrodes configured to couple directly to a surface of the patient.

(52) The cover layer and the bottom layer can be formed of, for example, medical-grade materials (e.g., medical-grade materials manufactured by 3M and/or Adhesives Research). In some implementations, the cover layer and/or the bottom layer can be formed of a multi-layer material including adhesive layers. In some implementations, the adhesive includes synthetic rubber, acrylates, and/or silicones. In some implementations, the layers can include layers formed of polymers, PET, polyethylene (PE), polyurethane (PU), and/or polyamide (PA). The cover layer and the bottom layer can include film, non-woven materials, or a combination. In some implementations, the cover layer and/or the bottom layer can be formed of polyurethane materials combines with acrylic adhesives such that the cover layer and/or the bottom layer are waterproof, breathable, and minimize skin irritation of the user.

(53) In some implementations, the composite assembly **140** can include multiple electrical connections between electrical components disposed in the first assembly **110** and the second

assembly **120**. For example, the connecting member **130** can include multiple electrical connections extending from the first end **136** of the connecting member **130** to the second end **138** of the connecting member **130**. In some implementations, for example, the connecting member **130** can include a composite board and one or more traces can be etched into the composite board. In some implementations, the connecting member **130** can include a number of stacked composite boards with at least one conductive trace etched into each composite board. In some implementations, the composite assembly **140** can include a multi-layer composite board, an elastically deformable portion of the multi-layer composite board included in the connecting member **130**. For example, a first laminated composite layer having a first trace can be coupled to a second laminated composite layer having a second trace such that the first laminated composite layer and the first trace are vertically higher (e.g., in the Z-direction) than the second laminated composite layer and the second trace. A third laminated composite layer having a third trace can be coupled to the second laminated composite layer such that the second laminated composite layer and the second trace are vertically higher than the third laminated composite layer and the third trace. The traces of the laminated composite layers can be electrically isolated by insulative material forming the laminated composite layers. In some implementations, the traces of each of the layers of the multi-layer composite board can be electrically coupled via, for example, vias in any suitable arrangement. In some implementations, the multiple electrical connections may include electrical wiring.

(54) The third adhesive portion **134** can be coupled to any suitable portion of the connecting member **130**. For example, the third adhesive portion **134** can be disposed on a skin-facing surface of one or more of the flexible hinges such that the skin-facing surface of one or more of the flexible hinges may be coupled to a surface of a patient. Additionally or alternatively, the third adhesive portion **134** can be disposed on a skin-facing surface of a rigid segment coupled to a flexible hinge such that the rigid segment is coupled to a surface of a patient. In some implementations, the third adhesive portion **134** can be disposed in one location or more than one location on a skin-facing surface of the connecting member **130**. The third adhesive portion **134** can include discrete adhesive portions disposed in various locations (e.g., on flexible hinges and/or segments connecting flexible hinges to other segments or the first assembly **110** or second assembly **120**) on a skin-facing surface of the connecting member **130**.

(55) The first adhesive portion **114**, the second adhesive portion **124**, the third adhesive portion **134**, and any of the adhesives described herein can include any suitable type of adhesive. For example, the adhesive can be synthetic rubber, acrylates, and/or silicones. The adhesives can be applied in any suitable pattern.

(56) In some implementations, the system **100** can accommodate movement-induced skin deformations (e.g., due to skin flexing or tension) while continuing to operate to measure differences in electrical potential between discrete skin locations such that weaker adhesives or smaller adhesive interfaces may be utilized compared to a rigid system without an elastic connecting member. Furthermore, the system **100** can be more breathable than rigid systems due to the reduced skin surface area covered with adhesive. For example, the first assembly **110** can be coupled to a first location on a surface of a patient via the first adhesive portion **114** and the second assembly **120** can be coupled to a second location on the surface of the patient via the second adhesive portion **124** when the first location and the second location are in an initial configuration relative to each other. If the first location on the surface of the patient moves closer to the second location on the surface of the patient (e.g., due to patient movement), the first assembly **110** can move toward the second assembly **120**, decreasing the distance between the first end **136** of the connecting member **130** and the second end **138** of the connecting member **130**. The movement of the first assembly **110** toward the second assembly **120** can cause the connecting member **130** to be compressed. If the first location on the surface of the patient moves farther from the second location on the surface of the patient (e.g., due to patient movement), the first assembly **110** can

move farther from the second assembly **120**, increasing the distance between the first end **136** of the connecting member **130** and the second end **138** of the connecting member **130**. The movement of the first assembly **110** away from the second assembly **120** can cause the connecting member **130** to expand. In implementations in which the connecting member **130** is coupled to a third location on the surface of the patient via the third adhesive portion **134**, the portions of the connecting member **130** coupled to the third location can move relative to the first assembly **110** and the second assembly **120** based on the movement of the third location relative to the first location and the second location. If the first location and the second location return to the initial configuration, the connecting member **130** will return to the first undeformed configuration.

(57) FIG. 2A is a schematic illustration of a top view of a system **200**. The system **200** can be the same or similar in structure and/or function to the system **100** described above. For example, the system **200** can include a first assembly **210**, a second assembly **220**, and a connecting member **230**, which can be the same or similar to the first assembly **110**, the second assembly **120**, and the connecting member **130**, respectively. As shown in FIG. 2A, the connecting member **230** includes a first end **236** and a second end **238**. The connecting member **230** is coupled to the first assembly **210** via the first end **236** and to the second assembly **220** via the second end **238**. The connecting member **230** is configured to transition between a first configuration (shown in FIG. 2A) and a second configuration in which the first assembly **210** and the second assembly **220** are a different distance away from each other than in the first configuration. For example, when the system **200** is coupled to a patient's skin, a force (e.g., due to deformation due to skin flexing or tension) may be applied to the first assembly **210** and/or the second assembly **220** in either direction represented by the double-ended arrow A (e.g., in the X-direction) such that the length of the connecting member **230** from the first end **236** to the second end **238** is increased or decreased and the connecting member **230** is compressed or expanded. In some implementations, a force may be applied to the first assembly **210** and/or the second assembly **220** in any direction in the X-Y plane such that the length of the connecting member **230** from the first end **236** to the second end **238** is increased or decreased and the connecting member **230** is compressed or expanded.

(58) FIG. 2B is a schematic illustration of a side view of a system **200** prior to being applied to a patient's skin. As shown in FIG. 2B, the system **200** can be moved in the direction of arrows B (e.g., in the Z-direction) relative to a surface S of a skin K of a patient such that the first assembly **210**, the second assembly **220**, and the connecting member **230** are disposed in contact with the surface S of the skin K. As shown in FIG. 2B, the first assembly **210**, the second assembly **220**, and the connecting member **230** can each have a skin-facing surface that collectively forms a bottom or skin-facing surface of the system **200**. The first assembly **210** can include a first electrode (not shown) and the second assembly can include a second electrode (not shown), the first and second electrode forming a portion of the bottom surface of the system **200** and configured to contact the surface S of the skin K. The first assembly **210** can be coupled to a first location on the surface S via a first adhesive portion (not shown) and the second assembly **220** can be coupled to a second location on the surface S via a second adhesive portion (now shown). The first assembly **210**, the second assembly **220**, and the connecting member **230** can each include a portion of a composite assembly and be configured such that the system **200** can measure a potential difference between the first location and the second location via the first electrode and the second electrode.

(59) In some implementations, a connecting member may not include a third adhesive portion such that the connecting member is vertically movable relative to a surface of the patient. Furthermore, in some implementations, the connecting member may not have a shape allowing for expansion and contraction of the connecting member. Without a third adhesive portion and/or having an elastically deforming shape as described with respect to the connecting member **130** described above, however, the system including the connecting member may not maintain conformality with the surface of the patient's skin during patient movement. FIGS. 3A-3C are schematic illustrations of a side view of a system **300** coupled to a surface S of a skin K of a patient in a first

configuration, a second configuration, and a third configuration, respectively. The system **300** may be similar in structure and/or function to any of the systems described herein. For example, the system **300** can include a first assembly **310**, a second assembly **320**, and a connecting member **330**. The connecting member **330** has a first end **336** coupled to the first assembly **310** and a second end **338** coupled to the second assembly **320**.

(60) As shown in FIG. 3A, the first assembly **310** is coupled to the skin surface S at a first location and the second assembly **320** is coupled to the skin surface S at a second location. The skin K of the patient is under compression under a first force applied in the direction of arrow C and a second force opposite the first force applied in the direction of arrow D (i.e., opposing forces in the X-direction causing compressive skin strain). As a result of the compressive forces, the first location and the second location are pushed closer to each other, causing the first end **336** and the second end **338** of the connecting member **330** to move closer to each other. Because the connecting member **330** is not coupled to the surface S via adhesive and is not configured to be elastically deformed within a plane lying perpendicular to the surface S, the connecting member **330** may flex or bulge away from the surface S such that a gap G is defined between the connecting member **330** and the surface S. Furthermore, the compressive skin strain may also apply stress to the interface between the first assembly **310** and/or the second assembly **320** and the surface S of the skin K, potentially disrupting the interface (e.g., disrupting adhesion) and causing discomfort to the wearer of the system **300**.

(61) As shown in FIG. 3B, the first assembly **310** is coupled to the skin surface S at a first location and the second assembly **320** is coupled to the skin surface S at a second location. The skin K of the patient is deformed (e.g., under tension) under a first force applied in the direction of arrow E (i.e., in the Z-direction away from the system **300**) such that the curvature of the surface S changes from a flat configuration to a curved configuration. As a result of the deformation, the first location and the second location are pushed closer to each other. Since the connecting member **330** is not coupled to the surface S via adhesive, the surface S may flex away from the connecting member **330** such that a gap G is defined between the connecting member **330** and the surface S and the connecting member **330** bulges away from the surface S. Furthermore, if the connecting member **330** is rigid, the connecting member **330** may not be able to accommodate the change in curvature of the surface S and any strain on the skin K may apply strain along the length of the system **300**, inducing stresses at the interface (e.g., an adhesive interface) of the first assembly **310** and/or the second assembly **320** with the surface S of the skin K.

(62) As shown in FIG. 3C, the first assembly **310** is coupled to the skin surface S at a first location and the second assembly **320** is coupled to the skin surface S at a second location. The skin K of the patient is under tension under a first force applied in the direction of arrow O and a second force opposite the first force applied in the direction of arrow P (i.e., opposing forces in the X-direction causing tensile skin strain). As a result of the tensile forces, the first location and the second location are pulled away from each other (i.e., the surface S is deformed via lateral expansion), causing the first end **336** and the second end **338** of the connecting member **330** to move away from each other. Because the connecting member **330** is not coupled to the surface S via adhesive and/or is not configured to be elastically deformed within a plane lying perpendicular to the surface S, the system **300** may induce a force M and a force N at the interface of the first assembly **310** and the second assembly **320**, respectively, with the surface S of the skin K. The force M and the force N can disrupt the interface (e.g., disrupt adhesion via inducing a risk of adhesion loss) and can cause discomfort to the wearer of the system **300**.

(63) In some implementations, an elastic connecting member and/or a third adhesive portion coupling the elastic coupling member to the surface of a patient's skin may improve conformality between the connecting member and the surface, for example, to avoid unwanted snags of the connecting member due to the gap G and/or to avoid forces applied by the connecting member on the first or second assembly that may cause the first or second assembly to loosen from the surface.

FIGS. 4A and 4B are schematic illustrations of a side view of a system **400** coupled to a surface **S** of a skin **K** of a patient in a first configuration and a second configuration, respectively. The system **400** can be similar in structure and/or function to any of the systems described herein. For example, the system **400** can include a first assembly **410**, a second assembly **420**, and a connecting member **430**. The connecting member **430** has a first end **436** coupled to the first assembly **410** and a second end **438** coupled to the second assembly **420**. As shown in FIGS. 4A and 4B, the system **400** can be able to deform with the surface **S** of the skin **K** and remain conformal with the surface **S** of the skin **K**. Furthermore, although not shown, the connecting member **430** can be coupled to the surface **S** via a third adhesive portion to improve conformality during deformation of the surface **S**. (64) As shown in FIG. 4A, the first assembly **410** is coupled to the skin **S** at a first location and the second assembly **410** is coupled to the skin **S** at a second location. The skin **K** of the patient is under compression under a first force applied in the direction of arrow **C** and a second force opposite the first force applied in the direction of arrow **D** (i.e., opposing forces in the **X**-direction). As a result of the compressive forces, the first location and the second location have been pushed closer to each other, causing the first end **436** and the second end **438** of the connecting member **430** to move closer to each other. Since the connecting member **430** is coupled to the surface **S** via adhesive and is configured to be elastically deformed within a plane lying perpendicular to the surface **S**, the connecting member **430** can remain conformed to the surface **S** such that no gap is defined between the connecting member **430** and the surface **S**. Thus, the system **400** can accommodate compressive deformation such that the connecting member **430** remains conformal to the surface **S** of the skin **K** with reduced stress on the adhesive interfaces between each of the first assembly **410**, the second assembly **420**, and the connecting member **430** with the surface **S** compared to a system with a non-deformable coupling member.

(65) As shown in FIG. 4B, the first assembly **410** is coupled to the skin **S** at a first location and the second assembly **410** is coupled to the skin **S** at a second location. The skin **K** of the patient is under tension under a first force applied in the direction of arrow **E** (i.e., in the **Z**-direction away from the system **400**). As a result of the first force, the first location and the second location have been pushed closer to each other. Since the connecting member **430** is coupled to the surface **S** via adhesive, the connecting member **430** remains conformed to the surface **S** such that no gap is defined between the connecting member **430** and the surface **S**.

(66) As described above with respect to third adhesive portion **134**, a connecting member can be coupled to a surface of a patient via one or more adhesive portions. FIGS. 5A-5C show variations of a system with examples of adhesive portions in various locations. FIG. 5A is a schematic illustration of a bottom view of a system **500**. The system **500** can be the same or similar in structure and/or function to any of the systems described herein, such as the system **100** described with respect to FIG. 1. For example, the system **500** includes a first assembly **510**, a second assembly **520**, and a connecting member **530**, which can be the same or similar in structure and/or function to the first assembly **110**, the second assembly **120**, and the connecting member **130**, respectively. The connecting member **530** has a first end **536** coupled to the first assembly **510** and a second end **538** coupled to the second assembly **520**. The connecting member **530** can be shaped as one period of a sinusoidal wave. For example, the connecting member **530** includes a first segment **537A**, a second segment **537B**, and a third segment **537C**. The connecting member **530** also includes a first elastic hinge **539A** and a second elastic hinge **539B**. The first segment **537A** is coupled to the second segment **537B** via the first elastic hinge **539A**. The second segment **537B** is coupled to the third segment **537C** via the second elastic hinge **539B**. The first segment **537A**, the second segment **537B**, the third segment **537C**, the first elastic hinge **539A**, and the second elastic hinge **539B** can collectively form a continuous and monolithic connecting member **530**. The first assembly **510** and/or the second assembly **520** can be moved in one of the directions indicated by the double arrow **L** such that the connecting member **530** is stretched or compressed. The connecting member **530** includes an adhesive portion **534** distributed along the entire length of a

bottom or skin-facing surface of the connecting member **530**.

(67) FIG. 5B is a schematic illustration of a bottom view of a system **500'**. The system **500'** can be the same or similar in structure and/or function to the system **500** shown in FIG. 5A, except that the system **500'** includes a discrete adhesive portion **534'** covering only a portion of the length of the bottom or skin-facing surface of a connecting member **530'**. For example, the system **500'** includes a first assembly **510'**, a second assembly **520'**, and the connecting member **530'**, which can be the same or similar in structure and/or function to the first assembly **510**, the second assembly **520**, and the connecting member **530**, respectively. The connecting member **530'** has a first end **536'** coupled to the first assembly **510'** and a second end **538'** coupled to the second assembly **520'**. The connecting member **530'** includes a first segment **537A'**, a second segment **537B'**, and a third segment **537C'**. The connecting member **530'** also includes a first elastic hinge **539A'** and a second elastic hinge **539B'**. The first segment **537A'** is coupled to the second segment **537B'** via the first elastic hinge **539A'**. The second segment **537B'** is coupled to the third segment **537C'** via the second elastic hinge **539B'**. The connecting member **530'** includes an adhesive portion **534'** disposed on the second segment **537B'**. Thus, the second segment **537B'** can be coupled to a location on the surface of a patient via the adhesive portion **534'**, allowing for additional elasticity and reduced adhesive-skin contact area compared to if the connecting member **530** were coupled to the surface of the patient along the entire length of the connecting member **530**.

(68) FIG. 5C is a schematic illustration of a bottom view of a system **500''**. The system **500''** can be the same or similar in structure and/or function to the system **500** shown in FIG. 5A, except that the system **500''** includes a first adhesive portion **534A''** and a second adhesive portion **534B''**. For example, the system **500''** includes a first assembly **510''**, a second assembly **520''**, and a connecting member **530''**, which can be the same or similar in structure and/or function to the first assembly **510**, the second assembly **520**, and the connecting member **530**, respectively. The connecting member **530''** has a first end **536''** coupled to the first assembly **510''** and a second end **538''** coupled to the second assembly **520''**. The connecting member **530''** includes a first segment **537A''**, a second segment **537B''**, and a third segment **537C''**. The connecting member **530''** also includes a first elastic hinge **539A''** and a second elastic hinge **539B''**. The first segment **537A''** is coupled to the second segment **537B''** via the first elastic hinge **539A''**. The second segment **537B''** is coupled to the third segment **537C''** via the second elastic hinge **539B''**. The connecting member **530''** includes a first adhesive portion **534A''** disposed on the first elastic hinge **539A''** (e.g., at a first nodal point of the connecting member **530''**) and a second adhesive portion **534B''** disposed on the second elastic hinge **539B''** (e.g., at a second nodal point of the connecting member **530''**). Thus, the first elastic hinge **539A''** and the second elastic hinge **539B''** can each be coupled to a location on the surface of a patient via the first adhesive portion **534A''** and the second adhesive portion **534B''**, respectively, such that the skin deformation-induced stress is reduced at the skin adhesive-skin interface of each adhesive portion compared to if the connecting member **530''** were attached via only one adhesive portion.

(69) In some implementations, the first assembly and the second assembly can be coupled to each other via a non-elastic, flexible connecting member. For example, FIG. 6 is a perspective view of a system **600** disposed on the surface S of a patient. The system **600** can be the same or similar in structure and/or function to any of the systems described herein, such as the system **100**. For example, the system **600** includes a first assembly **610**, a second assembly **620**, and a connecting member **630**, which can be the same or similar in structure and/or function to the first assembly **110**, the second assembly **120**, and the connecting member **130**, respectively. The connecting member **630** has a first end **636** coupled to the first assembly **610** and a second end **638** coupled to the second assembly **620**. The connecting member **630** can be non-elastic and flexible. The connecting member **630** can, for example, include a flexible strap. In some implementations, the connecting member **630** can be coupled to a surface of a patient via an adhesive portion. The adhesive portion can be disposed on a portion or all of a skin-contacting surface of the connecting

member **630**. Since the connecting member **630** is non-elastic, however, the system **600** cannot accommodate deformation (e.g., stretching) of the surface **S**. Rather, the system **600** will experience strain over the length of the system **600** and will apply the strain to the surface **S**, causing the skin-adhesive interface between each of the first assembly **610** and the second assembly **620** and the surface **S** will experience greater stress compared to if the connecting member **630** were elastic. Thus, the skin-adhesive interface between the system **600** and the surface **S** can experience adhesion loss due to the system **600** applying stress to the surface **S** via deformation of the surface **S** by the system **600**.

(70) FIG. 7 is a perspective exploded view of a system **700**. The system **700** can be the same or similar in structure and/or function to any of the systems described herein, such as, for example, the system **100**. For example, the system **700** includes a first assembly **710**, a second assembly **720**, and a connecting member **730** that can be the same or similar in structure and/or function to the first assembly **110**, the second assembly **120**, and/or the connector **130**, respectively. The first assembly **710** includes a first upper housing **752**, a portion **746** of a composite assembly **740**, a first lower housing **762**, and a first adhesive portion (not shown). The portion **746** can include any suitable electronic components (e.g., a processor and a memory). The first lower housing **762** defines an opening **762A** such that an electrode **741** disposed on a bottom side of the portion **746** is accessible through the opening **762A**. The first assembly **710** also includes a hydrogel portion **772**.

(71) The second assembly **720** includes a second upper housing **754**, a portion **744** of the composite assembly **740**, a second lower housing **764**, and a second adhesive portion (not shown). The portion **744** can include any suitable electronic components (e.g., an energy storage device such as a coin cell battery). The second lower housing **764** defines an opening **764A** such that an electrode **743** disposed on a bottom side of the portion **744** is accessible through the opening **764A**. The second assembly **720** also includes a hydrogel portion **774**.

(72) In some implementations, the composite assembly **740** includes a tab contact **748**. The tab contact **748** can be integrally formed with the composite board of the composite assembly **740** and can be folded to contact the top of the energy storage device of the portion **744** as shown in FIG. 7. In some implementations, the energy storage device can be coupled to the composite board of the composite assembly **740** via a conductive adhesive. In some implementations, contacts of the energy storage device can be coupled to the composite board via spot welding.

(73) The connecting member **730** includes a third upper housing **756**, a portion **742** of the composite assembly **740**, a third lower housing **766**, and a third adhesive portion (not shown). The third lower housing **766** has a skin-facing surface **745** along the full length of the portion **742**. The portion **742** can include a composite board including an insulator and at least one conductive trace (e.g., a flexible printed circuit board). The insulator can include, for example, polyimide. The at least one conductive trace can include, for example, copper. In some implementations, the composite board can include a polyimide with double-sided copper conductors. In some implementations, the portion **742** can include multiple layers (e.g., two, three, or more layers), each layer including at least one conductive trace. In some implementations, the portion **742** can include multiple layers including at least one conductive trace, each layer including at least one conductive trace coupled to another layer including at least one conductive trace via an insulative layer. The third adhesive portion can cover the entire skin-facing surface **745** of the third lower housing **766**. In some implementations, the system **700** includes three conductive traces extending from the first assembly **710** to the second assembly **720**. For example, a first conductive trace can extend from a positive side of the energy storage device of the portion **744** to the portion **746**, a second conductive trace can extend from a negative side of the energy storage device of the portion **744** to the portion **746**, and the third conductive trace can extend from the electrode **743** to the portion **746**. Similarly as described above with reference to the connecting member **130**, in some implementations the connecting member **730** (and/or the portion **742**) may have a thickness equal to or less than 100 μm . In some implementations, the height of the connecting member **730** (and/or

the portion **742**) can be, for example, equal to or less than 36 μm . In some implementations, the spring constant of the connecting member **730** (and/or the portion **742**) (in the X-direction) can increase proportionally to a cube of the thickness of the connecting member **730** (and/or the portion **742**) and linearly with respect to the height of the connecting member **730** (and/or the portion **742**). (74) As shown in FIG. 7, the first upper housing **752**, the second upper housing **754**, and the third upper housing **756** can collectively form a cover layer **750**. The first lower housing **762**, the second lower housing **764**, and the third lower housing **766** can collectively form a bottom layer **760**. The bottom layer **760** can be coupleable to a surface of a skin via the first adhesive portion, the second adhesive portion, and/or the third adhesive portion such that the bottom layer **760** secures the composite assembly **740** to the surface of the skin. In some implementations, the cover layer **750** (including the first upper housing **752**, the second upper housing **754**, and the third upper housing **756**) can be monolithically or integrally formed. In some implementations, the bottom layer **760** (including the first lower housing **762**, the second lower housing **764**, and the third lower housing **766**) can be monolithically or integrally formed.

(75) FIGS. **8A-8D** illustrate various example arrangements of conductive traces within a connecting member. FIG. **8A** is a cross-sectional schematic illustration of a portion **842A** of a composite assembly, which can be the same or similar in structure and/or function to the composite assembly **740** described above with reference to FIG. 7. The portion **842A** includes an insulative portion **847'** and a first conductive trace **843A'**, a second conductive trace **843B'**, and a third conductive trace **843C'** disposed within the insulative portion **847'**. For example, the first conductive trace **843A'**, the second conductive trace **843B'**, and the third conductive trace **843C'** can be etched into or printed on the insulative portion **847'**. The portion **842A** has a skin-facing surface **845'**. The first conductive trace **843A'**, the second conductive trace **843B'**, and the third conductive trace **843C'** can be disposed at varying locations relative to the skin-facing surface **845'** such that at least one of the first conductive trace **843A'**, the second conductive trace **843B'**, and the third conductive trace **843C'** is disposed farther from the skin-facing surface **845'**. Thus, at least some of the conductive traces of the portion **842A** can be vertically-arranged relative to other conductive traces such that the portion **842A** can be narrower (i.e., have reduced thickness in an X-Y plane parallel to the surface of the patient) and more elastic than if the portion **842A** included only horizontally-distributed conductive traces. Although not shown, the portion **842A** can include any suitable number of vias electrically coupling a conductive trace to another conductive trace in any suitable arrangement.

(76) FIG. **8B** is a cross-sectional schematic illustration of a portion **842B** of a composite assembly, which can be the same or similar in structure and/or function to the composite assembly **740** described above with reference to FIG. 7. The portion **842B** is a multi-layer composite board, including a first layer **849A''** and a second layer **849B''**. The first layer **849A''** includes an insulative portion **847A''**, a first conductive trace **843A''**, and a second conductive trace **843B''**. The first conductive trace **843A''** and the second conductive trace **843B''** can be etched into or printed on the first layer **849A''**. The second layer **849B''** includes an insulative portion **847B''**, a third conductive trace **843C''**, and a fourth conductive trace **843D''**. The third conductive trace **843C''** and the fourth conductive trace **843D''** can be etched into or printed on the second layer **849B''**. The second layer **849B''** has a skin-facing surface **845''**. The portion **842B** can include an insulative layer **849C''** disposed between the first layer **849A''** and the second layer **849B''**. The first layer **849A''** can be stacked relative to the second layer **849B''** such that the first conductive trace **843A''** is disposed farther from the skin-facing surface **845''** than the second conductive trace **843B''**. Although each of the first layer **849A''** and the second layer **849B''** are shown as including two conductive traces, the first layer **849A''** and the second layer **849B''** can each include any suitable number of conductive traces (e.g., one, three, four, or more). Furthermore, although the portion **842B** is shown as having only two layers including conductive traces, the portion **842B** can have any suitable number of layers of conductive traces (e.g., three layers, four layer, or more). Each of the layers including

conductive traces can be separated by an insulative layer similar to insulative layer **849C''**. Thus, portion **842B** can include vertically-stacked layers each including at least one conductive trace such that the portion **842B** can be narrower and more elastic than if the portion **842B** included horizontally-distributed conductive traces.

(77) FIG. **8C** is a cross-sectional schematic illustration of a portion **842C** of a composite assembly, which can be the same or similar in structure and/or function to the composite assembly **740** described above with reference to FIG. **7**. The portion **842C** includes an insulative portion **847'''** and a first conductive trace **843A'''**, a second conductive trace **843B'''**, a third conductive trace **843C'''**, and a fourth conductive trace **843D'''** disposed within or coupled to the insulative portion **847'''**. For example, the first conductive trace **843A'''** and the third conductive trace **843C'''** can be etched into or printed on a first layer of the insulative portion **847'''** and the second conductive trace **843B'''** and the fourth conductive trace **843D'''** can be etched into or printed on a second layer of the insulative portion **847'''**. The portion **842C** has a skin-facing surface **845''**. The first layer is stacked on top of the second layer such that the first conductive trace **843A'''** and the third conductive trace **843C'''** are disposed farther from the skin-facing surface **845''** than the second conductive trace **843B'''** and the fourth conductive trace **843D'''**. By disposing at least some of the conductive traces (e.g., **843A'''** and **843C'''**) above others of the conductive traces (e.g., **843B'''** and **843D'''**), the portion **842C** can be narrower and more elastic compared to if the conductive traces were horizontally distributed.

(78) FIG. **8D** is a cross-sectional schematic illustration of a portion **842D** of a composite assembly, which can be the same or similar in structure and/or function to the composite assembly **740** described above with reference to FIG. **7**. The portion **842D** includes an insulative portion **847''''** and a first conductive trace **843A''''**, a second conductive trace **843B''''**, and a third conductive trace **843C''''** disposed within or coupled to the insulative portion **847''''**. For example, the first conductive trace **843A''''**, the second conductive trace **843B''''**, and the third conductive trace **843C''''** can be etched into or printed on the insulative portion **847''''**. The first conductive trace **843A''''**, the second conductive trace **843B''''**, and the third conductive trace **843C''''** are horizontally distributed (i.e., disposed in parallel to one another within a plane that is disposed parallel to a skin-facing surface **845'** of the portion **842D**). Although the first conductive trace **843A''''**, the second conductive trace **843B''''**, and the third conductive trace **843C''''** are shown as being disposed on the skin-facing surface **845''''** of the portion **842D**, the first conductive trace **843A''''**, the second conductive trace **843B''''**, and the third conductive trace **843C'** can be disposed on any suitable side or on any suitable layer of the portion **842D**.

(79) FIG. **9** is a top view of a system **900**. The system **900** can be the same or similar in structure and/or function to any of the systems described herein such as, for example, the system **100** or the system **700**. For example, the system **900** includes a first assembly **910**, a second assembly **920**, and a connecting member **930** that can be the same or similar in structure and/or function to the first assembly **710**, the second assembly **720**, and the connecting member **730**, respectively. The system **900** includes a cover layer **950** and an adhesive layer **960**. The cover layer **950** includes a first housing **952**, a second housing **954**, and a third housing **956**.

(80) In some embodiments, a system can include an additional assembly. For example, FIG. **10** is a schematic illustration of a system **1000**. The system **1000** includes a first assembly **1010**, a second assembly **1020**, and a third assembly **1080**. The first assembly **1010** can be coupled to the third assembly **1080** via a first connecting member **1030A** and the second assembly **1020** can be coupled to the third assembly **1080** via a second connecting member **1030B**. The system **1000** can be similar in structure and/or function to any of the systems described herein. For example, the first assembly **1010** and the second assembly **1020** can be the same or similar in structure and/or function to the first assembly **110** and/or the second assembly **120**. The first connecting member **1030A** and the second connecting member **1030B** can each be the same or similar to any of the connecting members described herein, such as, for example, the connecting member **130**.

(81) The third assembly **1080** can be the same or similar in structure and/or function to any of the assemblies described herein, such as, for example, the first assembly **110** and/or the second assembly **120**. The third assembly **1080** can include a portion of a composite assembly similar to the composite assembly **140**. For example, electronic components of the composite assembly (e.g., the processor and/or the battery) can be included in the third assembly **1080**. In some implementations, the third assembly **1080** includes a housing portion. In some implementations, the third assembly **1080** includes an adhesive portion (not shown) configured to couple the third assembly **1080** to a surface of a patient. In some implementations, the third assembly **1080** includes an electrode (not shown) configured to be coupled to the surface of the patient.

(82) In some implementations, the first assembly **1010** can include a first electrode and the second assembly **1020** can include a second electrode. The third assembly **1080** can include the processor and the battery. The first electrode and the second electrode can be separately optimized for electrode performance. For example, the first electrode and the second electrode can be made soft and compact in size since the first electrode and the second electrode are not within the same housing as the electronic components (e.g., the processor and/or the battery) of the third assembly **1080**. Thus, each of the first electrode and the second electrode can be conformal electrodes. For example, in some implementations, each of the first assembly **1010** and the second assembly **1020** can include a backing layer of thermoplastic polyurethane (TPU) on which silver/silver chloride (Ag/AgCl) can be printed. A skin adhesive layer can be disposed on a skin-facing surface of the backing and can define an opening surrounding a portion of the Ag/AgCl (e.g., an opening having a diameter of about 10 mm). The skin adhesive layer can include, for example, a soft, pliable polyurethane film having a thin acrylic absorbent adhesive (e.g., MED 5577A manufactured by Avery Dennison Corporation). A hydrogel pillow having a diameter smaller than the diameter of the opening of the skin adhesive layer (e.g., a diameter of about 6 mm) can be disposed within the opening defined by the skin adhesive in contact with the skin-facing surface of the backing and the printed Ag/AgCl electrode. The hydrogel pillow can be, for example, AG625 Sensing Gel manufactured by Axelgaard Manufacturing Co., Ltd.

(83) FIG. **11** is a schematic illustration of a system **1100**. The system **1100** includes a first assembly **1110**, a second assembly **1180**, and a third assembly **1190**. The first assembly **1110**, the second assembly **1180**, and/or the third assembly **1190** can be arranged in any suitable configuration on the surface of a patient. The first assembly **1110** can be coupled to the second assembly **1180** via a first connecting member **1130A**. The second assembly **1180** can be coupled to the third assembly **1190** via a second connecting member **1130B**. The first assembly **1110** can be coupled to the third assembly **1190** via a third connecting member **1130C**. The system **1100** can be similar in structure and/or function to any of the systems described herein. For example, the first assembly **1110**, the second assembly **1180**, and/or the third assembly **1190** can be the same or similar in structure and/or function to the first assembly **110** and/or the second assembly **120** described above with respect to the system **100**. The first connecting member **1130A**, the second connecting member **1130B**, and/or the third connecting member **1130C** can each be the same or similar to any of the connecting members described herein, such as, for example, the connecting member **130**. For example, the first connecting member **1130A** can be shaped as a sinusoidal wave including five periods. The second connecting member **1130B** can be shaped as a sinusoidal wave including two periods. The third connecting member **1130C** can be shaped as an arch.

(84) The second assembly **1180** and/or the third assembly **1190** can include a portion of a composite assembly similar to composite assembly **140**. For example, electronic components of the composite assembly can be included in the second assembly **1180** and/or the third assembly **1190**. In some implementations, the second assembly **1180** and/or the third assembly **1190** includes a housing portion. In some implementations, the second assembly **1180** and/or the third assembly **1190** includes an adhesive portion (not shown) configured to couple the second assembly **1180** and/or the third assembly **1190** to a surface of a patient. In some implementations, the second

assembly **1180** and/or the third assembly **1190** includes an electrode (not shown) configured to be coupled to the surface of the patient.

(85) FIG. **12** is a schematic illustration of a system **1200**. The system **1200** can be similar in structure and/or function to any of the systems described herein. The system **1200** includes a first electrode **1212**, a second electrode **1222**, an energy storage device **1282**, and an electronics module **1292**. The first electrode **1212** can be coupled to the energy storage device **1282** via a first connecting member **1230A**. The energy storage device **1282** can be coupled to the electronics module **1292** via a second connecting member **1230B**. The electronics module **1292** can be coupled to the second electrode **1222** via a third connecting member **1230C**. The first connecting member **1230A**, the second connecting member **1230B**, and/or the third connecting member **1230C** can each be the same or similar in structure and/or function to any of the connecting members described herein. In some implementations, the first electrode **1212**, the second electrode **1222**, the energy storage device **1282**, and the electronics module **1292** each include an adhesive portion (not shown) configured to couple the first electrode **1212**, the second electrode **1222**, the energy storage device **1282**, and the electronics module **1292** to a surface of a patient. The system **1200** can include a cover portion or a number of discrete cover portions (e.g., housings) shaped and sized to cover some or all of the first electrode **1212**, the second electrode **1222**, the energy storage device **1282**, the electronics module **1292**, the first connecting member **1230A**, the second connecting member **1230B**, and/or the third connecting member **1230C**. The first electrode **1212** and the second electrode **1222** can be the same or similar in structure and/or function to the first electrode and second electrode or first assembly **1010** and second assembly **1020** described with respect to the system **1000**.

(86) The first electrode **1212**, the second electrode **1222**, the energy storage device **1282**, and the electronics module **1292** can be arranged in any suitable configuration on the surface of the patient. The electronics module **1292** can include any of the electrical components of a composite assembly similar to the composite assembly **140** described above. Each of the first electrode **1212** and the second electrode **1222** can be separately optimized for electrode performance. For example, the first electrode **1212** and the second electrode **1222** can be made soft and compact in size since the first electrode **1212** and the second electrode **1222** are not directly coupled to and/or are in separate housings as the electronic components of the electronics module **1292** or the energy storage device **1282**. The electronics module **1292** can be separately optimized due to not being directly coupled to and/or not within the same housing as the first electrode **1212** and the second electrode **1222**. For example, the energy storage device **1282** and/or the electronics module **1292** can be increased in size while keeping the first electrode **1212** and the second electrode **1222** small.

(87) In some implementations, rather than including one electronics module, a system can include two or more separate electronics modules. For example, FIG. **13** is a schematic illustration of a system **1300**. The system **1300** can be similar in structure and/or function to any of the systems described herein. The system **1300** includes a first electrode **1312**, a second electrode **1322**, an energy storage device **1382**, a first electronics module **1392**, and a second electronics module **1394**. The first electrode **1312** can be coupled to the energy storage device **1382** via a first connecting member **1330A**. The energy storage device **1382** can be coupled to the first electronics module **1392** via a second connecting member **1330B**. The first electronics module **1392** can be coupled to the second electronics module **1394** via a third connecting member **1330C**. The second electronics module **1394** can be coupled to the second electrode **1322** via a fourth connecting member **1330D**. The first connecting member **1330A**, the second connecting member **1330B**, the third connecting member **1330C**, and/or the fourth connecting member **1330D** can each be the same or similar in structure and/or function to any of the connecting members described herein. In some implementations, the first electrode **1312**, the second electrode **1322**, the energy storage device **1382**, the first electronics module **1392** and the second electronics module **1394** each include an adhesive portion (not shown) configured to couple the first electrode **1312**, the second electrode

1322, the energy storage device **1382**, the first electronics module **1392**, and the second electronics module **1394** to a surface of a patient. The system **1300** can include a cover portion or a number of discrete cover portions (e.g., housings) shaped and sized to cover some or all of the first electrode **1312**, the second electrode **1322**, the energy storage device **1382**, the first electronics module **1392**, the second electronics module **1394**, the first connecting member **1330A**, the second connecting member **1330B**, the third connecting member **1330C**, and/or the fourth connecting member **1330D**. The first electrode **1312** and the second electrode **1322** can be the same or similar in structure and/or function to the first electrode and second electrode or first assembly **1010** and second assembly **1020** described with respect to the system **1000**.

(88) The first electrode **1312**, the second electrode **1322**, the energy storage device **1382**, the first electronics module **1392**, and the second electronics module **1394** can be arranged in any suitable configuration on the surface of the patient. The first electronics module **1392** and the second electronics module **1394** can include any of the electrical components of a composite assembly similar to the composite assembly **140** described above. Each of the first electrode **1312** and the second electrode **1322** can be separately optimized for electrode performance. For example, the first electrode **1312** and the second electrode **1322** can be made soft and compact in size since the first electrode **1312** and the second electrode **1322** are not directly coupled to and/or not within the same housing as the electronic components of the first electronics module **1392**, the second electronics module **1394**, or the energy storage device **1382**. The first electronics module **1392** and/or the second electronics module **1394** can be separately optimized due to not being directly coupled to and/or not within the same housing as each other or the first electrode **1312** and the second electrode **1322**. For example, the energy storage device **1382**, the first electronics module **1392**, and/or the second electronics module **1394** can have a size (e.g., perimeter) greater than the perimeter of the electrodes while the first electrode **1312** and the second electrode **1322** can have a smaller size (e.g., perimeter) than the energy storage device **1382**, the first electronics module **1392**, and/or the second electronics module **1394**. As shown in FIG. 13, the system **1300** can be arranged in a zig-zag pattern such that the system **1300** has elasticity.

(89) In some embodiments, a system can include connecting members that are configured to transition among various heights relative to the surface of the patient. For example, FIGS. 14A and 14B are schematic illustrations of a top view and a side view, respectively, of a system **1400**. The system **1400** includes a first assembly **1410**, a second assembly **1420**, and a third assembly **1480**. The first assembly **1410** can be coupled to the third assembly **1480** via a first connecting member **1430A** and the second assembly **1420** can be coupled to the third assembly **1480** via a second connecting member **1430B**. The system **1400** can be similar in structure and/or function to any of the systems described herein. For example, the first assembly **1410** and the second assembly **1420** can be the same or similar in structure and/or function to the first assembly **110** and/or the second assembly **120**. The first connecting member **1430A** and the second connecting member **1430B** can each be the same or similar to any of the connecting members described herein, such as, for example, the connecting member **130**.

(90) The third assembly **1480** can be the same or similar in structure and/or function to any of the assemblies described herein, such as, for example, the first assembly **110** and/or the second assembly **120**. The third assembly **1480** can include a portion of a composite assembly similar to the composite assembly **140**. For example, electronic components of the composite assembly (e.g., the processor and/or the battery) can be included in the third assembly **1480**. In some implementations, the third assembly **1480** includes a housing portion. In some implementations, the third assembly **1480** includes an adhesive portion (not shown) configured to couple the third assembly **1480** to a surface of a patient. In some implementations, the third assembly **1480** includes an electrode (not shown) configured to be coupled to the surface of the patient.

(91) The first connecting member **1430A** has a first end **1436A** coupled to the first assembly **1410** and a second end **1438A** coupled to the third assembly **1480**. The second connecting member

1430B has a first end **1436B** coupled to the second assembly **1420** and a second end **1438B** coupled to the third assembly **1480**. In some implementations, the first connecting member **1430A** and the second connecting member **1430B** can each be sufficiently flexible such that the first connecting member **1430A** and the second connecting member **1430B** can change in shape or deform from an initial configuration or shape while remaining coupled to the third assembly **1480** and the first assembly **1410** or the second assembly **1420**, respectively (e.g., due to movement of the skin locations to which the first assembly **1410**, the second assembly **1420**, and/or the third assembly **1480** are coupled). Thus, the first connecting member **1430A** and the second connecting member **1430B** can accommodate skin deformations by reducing stress at the skin-adhesive interface compared to a connecting member with an undeforming shape, causing better adhesion durability and better wear comfort for the user. In some implementations, each of the first connecting member **1430A** and the second connecting member **1430B** (e.g., one or more composite boards of the composite assembly) can be sufficiently elastic such that the first connecting member **1430A** and/or the second connecting member **1430B** can function as a spring arranged between the third assembly **1480** and the first assembly **110** or the third assembly **1480** and the second assembly **120**, respectively, allowing for expansion and contraction of the length of the first connecting member **1430A** and/or the second connecting member **1430B** relative to an equilibrium or undeformed length.

(92) The first connecting member **1430A** and the second connecting member **1430B** each have an overall length (e.g., a distance from the first end **1436A** to the second end **1438A** and a distance from the first end **1436B** to the second end **1438B**, respectively), an overall width (e.g., a distance from an outermost edge of each connecting member **1430A** and **1430B** extending in a first direction extending perpendicularly relative to a line extending between the first assembly **1410** and the third assembly **1480** or a line extending between the third assembly **1480** and the second assembly **1420**, respectively, to an outermost edge of each connecting member **1430A** and **1430B** extending in a second direction opposite the first direction), and an overall height (e.g., a vertical distance from a portion of each connecting member **1430A** and **1430B** closest to a surface of a patient to a portion farthest from the surface of the patient when the system **1400** is coupled to the surface). The length of each connecting member **1430A** and **1430B** may be measured in an X-direction, the width of each connecting member **1430A** and **1430B** may be measured in a Y-direction perpendicular to the X-direction, and the height of each connecting member **1430A** and **1430B** may be measured in a Z-direction perpendicular to the X-direction and the Y-direction. For example, as shown in FIGS. **14A** and **14B**, the first connecting member **1430A** has a length L, a width W, and a height H. Each connecting member **1430A** and **1430B** can have a first overall length, a first overall width, and a first overall height in the first configuration and a second overall length, a second overall width, and a second overall height in the second configuration. The first width and the second width can be equal. When the first assembly **1410** and the third assembly **1480** are closer to each other in the second configuration than the first configuration, the second length may be smaller than the first length and the second height may be greater than the first height. When the first assembly **1410** and the third assembly **1480** are farther from each other in the second configuration than in the first configuration, the second length may be greater than the first length and the second height may be smaller than the first height. Similarly, when the second assembly **1420** and the third assembly **1480** are closer to each other in the second configuration than the first configuration, the second length may be smaller than the first length and the second height may be greater than the first height. When the second assembly **1420** and the third assembly **1480** are farther from each other in the second configuration than in the first configuration, the second length may be greater than the first length and the second height may be smaller than the first height.

(93) As shown in FIG. **14B**, in some implementations, the first connecting member **1430A** and the second connecting member **1430B** can each include an arched or curved shape. For example, in

some implementations, the first connecting member **1430A** and the second connecting member **1430B** can each include an arched or curved shape in an initial or undeformed configuration. In some implementations, the first connecting member **1430A** and the second connecting member **1430B** can each be straight in an initial or undeformed configuration and can include an arched or curved shape in a contracted configuration. In some implementations, the more contracted the first connecting member **1430A** and the second connecting member **1430B** become, the smaller the frequency and/or the larger the amplitude of the arch or curve of each of the first connecting member **1430A** and the second connecting member **1430B**. In some implementations, the first connecting member **1430A** can include an arched or curved shape extending from the first end **1436A** to the second end **1438A** (e.g., closer to the second end **1438A** than the first end **1436A**) and the second connecting member **1430B** can include an arched or curved shape extending from the first end **1436B** to the second end **1438B** (e.g., closer to the second end **1438B** than the first end **1436B**). As shown in FIG. **14B**, each of the first connecting member **1430A** and the second connecting member **1430B** can be shaped and attached to the third assembly **1480** such that the arched or curved shape is outside of the third assembly **1480** (e.g., the second end **1438A** and the second end **1438B** are outside a housing of the third assembly **1480**).

(94) In some embodiments, a portion of each of a first connecting member and a second connecting member can be disposed within a housing of an assembly. For example, FIGS. **15A** and **15B** are schematic illustrations of a top view and a side view of a system **1500**. The system **1500** includes a first assembly **1510**, a second assembly **1520**, and a third assembly **1580**. The first assembly **1510** can be coupled to the third assembly **1580** via a first connecting member **1530A** and the second assembly **1520** can be coupled to the third assembly **1580** via a second connecting member **1530B**. The system **1500** can be similar in structure and/or function to any of the systems described herein. For example, the first assembly **1510** and the second assembly **1520** can be the same or similar in structure and/or function to any of the assemblies described herein, such as the first assembly **1410** and/or the second assembly **1420**. The third assembly **1580** can be the same or similar in structure and/or function to any of the assemblies described herein, such as the third assembly **1480**. The first connecting member **1530A** and the second connecting member **1530B** can each be the same or similar to any of the connecting members described herein, such as, for example, the first connecting member **1430A** and the second connecting member **1430B**.

(95) The first connecting member **1530A** has a first end **1536A** coupled to the first assembly **1510** and a second end **1538A** coupled to the third assembly **1580**. The second connecting member **1530B** has a first end **1536B** coupled to the second assembly **1520** and a second end **1538B** coupled to the third assembly **1580**. As shown in FIG. **15B**, the second end **1538A** and the second end **1538B** can be disposed within a housing of the third assembly **1580** such that a smaller portion of each of the first connecting member **1530A** and the second connecting member **1530B** is accessible from an exterior of the system **1500**. For example, the third assembly **1580** can include an opening configured to receive a portion of the first connecting member **1530A**, and the first connecting member **1530A** can move within the opening as the first connecting member **1530A** transitions between an initial configuration or shape and an expanded or contracted configuration or shape. Thus, an area or space bounded by a skin-facing surface of the first connecting member **1530A**, an outer surface of the third assembly **1580**, and a surface of the patient to which the system **1500** is coupled can be smaller than the space bounded by a skin-facing surface of the first connecting member **1430A** and a surface of the patient to which the system **1400** is coupled when the first connecting member **1530A** and the first connecting member **1430A** are otherwise in the same configuration.

(96) While shown in FIGS. **14B** and **15B** as having an arched or curved shape in the vertical direction (Y direction), in some embodiments the connecting members (**1430A**, **1430B**, **1530A** and **1530B**) can include, contract and/or deform into any suitable shape. For example, in some embodiments the connecting members can have a serpentine shape, a sinusoidal shape, a zig-zag

shape, a repeating sawtooth shape, a repeating triangle shape, and/or any combination of shapes lying in an X-Z plane (e.g., as viewed from a side view).

(97) In some implementations, a system, such as any of the systems described herein, can include one or more connecting members having a combination of the features described with respect to the connecting members described herein. For example, a connecting member can have an overall horizontal width and a vertical height relative to a surface of the patient to which a system including the connecting member is attached that are both configured to change (e.g., contract or expand) as the connecting member deforms in response to skin deformation. For example, in a default or contracted configuration, the connecting member can, for example, have a serpentine shape, a sinusoidal shape, a zig-zag shape, a repeating sawtooth shape, a repeating triangle shape, and/or any combination of shapes lying in an X-Y plane (e.g., as viewed in a top view), and can have an arched or curved shape lying in an X-Z plane (e.g., as viewed from a side view).

(98) In some implementations, the electrodes of any of the systems described herein (e.g., system **100**) may be configured to detect conductive or inductive signals generated by an ingestible event marker of an ingestible pill disposed within a patient or conductive or inductive signals generated by any other ingestible or implantable device.

(99) While various embodiments of the invention have been described above, it should be understood that they have been presented by way of example only, and not limitation. Where methods described above indicate certain events occurring in certain order, the ordering of certain events may be modified. Additionally, certain of the events may be performed concurrently in a parallel process when possible, as well as performed sequentially as described above.

(100) In some embodiments, the systems (or any of its components) described herein can include a non-transitory computer-readable medium (also can be referred to as a non-transitory processor-readable medium) having instructions or computer code thereon for performing various computer-implemented operations. The computer-readable medium (or processor-readable medium) is non-transitory in the sense that it does not include transitory propagating signals per se (e.g., a propagating electromagnetic wave carrying information on a transmission medium such as space or a cable). The media and computer code (also can be referred to as code) may be those designed and constructed for the specific purpose or purposes. Examples of non-transitory computer-readable media include, but are not limited to: magnetic storage media such as hard disks, floppy disks, and magnetic tape; optical storage media such as Compact Disc/Digital Video Discs (CD/DVDs), Compact Disc-Read Only Memories (CD-ROMs), and holographic devices; magneto-optical storage media such as optical disks; carrier wave signal processing modules; and hardware devices that are specially configured to store and execute program code, such as Application-Specific Integrated Circuits (ASICs), Programmable Logic Devices (PLDs), Read-Only Memory (ROM) and Random-Access Memory (RAM) devices.

(101) Although various embodiments have been described as having particular features and/or combinations of components, other embodiments are possible having a combination of any features and/or components from any of the embodiments where appropriate.

(102) In some embodiments, a system includes a first assembly, a second assembly, and a connecting member. The first assembly includes a first electrode and a first adhesive portion. The first assembly is configured to be coupled to a surface of a patient via the first adhesive portion. The second assembly includes a second electrode and a second adhesive portion. The second assembly is configured to be coupled to the surface of the patient via the second adhesive portion. The connecting member has a first end, a second end, and a third adhesive portion. The first end is coupled to the first assembly and the second end is coupled to the second assembly. The connecting member is configured to transition between a first configuration and a second configuration. A distance between the first end and the second end of the connecting member in the first configuration is a first distance. A distance between the first end and the second end of the connecting member in the second configuration is a second distance different from the first

distance. The connecting member is configured to be coupled to the surface of the patient via the third adhesive portion in both the first configuration and the second configuration.

(103) In some embodiments, the connecting member is configured to transition from the first configuration to the second configuration based at least in part on movement of the first assembly relative to the second assembly due to deformation of the surface of the patient.

(104) In some embodiments, the connecting member is biased toward the first configuration.

(105) In some embodiments, the connecting member is configured to be coupled to the surface of the patient via the third adhesive portion during the transition from the first configuration to the second configuration.

(106) In some embodiments, the connecting member includes a skin-facing surface, the third adhesive portion configured to cover a portion of the skin-facing surface.

(107) In some embodiments, the connecting member further includes a fourth adhesive portion. The third adhesive portion is disposed on a skin-facing surface of the connecting member at a first location. The fourth adhesive portion is disposed on a skin-facing surface of the connecting member at a second location.

(108) In some embodiments, the connecting member includes a first segment, a second segment, and a third segment. The first segment is coupled to the second segment via a first flexible hinge. The second segment is coupled to the third segment via a second flexible hinge.

(109) In some embodiments, the connecting member includes one or more conductive members configured to electrically couple the first assembly to the second assembly.

(110) In some embodiments, the connecting member has a first sinusoidal shape having a first frequency in the first configuration and a second sinusoidal shape having a second frequency in the second configuration, the second frequency different from the first frequency.

(111) In some embodiments, a system includes a first assembly, a second assembly, and a composite assembly. The first assembly includes a first electrode and a first housing. The first assembly is configured to be coupled to a surface of a patient's skin via a first adhesive portion. The second assembly includes a second electrode and a second housing. The second assembly is configured to be coupled to a surface of a patient's skin via a second adhesive portion. The composite assembly includes a processor and a composite board having a flexible portion. The flexible portion has a first end and a second end. The processor is disposed between the first electrode and the first housing. The composite assembly is configured to transition from a first configuration to a second configuration. A distance between the first end and the second end of the flexible portion in the first configuration being a first distance. A distance between the first end and the second end of the flexible portion in the second configuration being a second distance different from the first distance.

(112) In some embodiments, the system includes a connecting member having a third housing and the flexible portion of the composite assembly is disposed within the third housing. The third housing, the first housing, and the second housing collectively form a cover layer and a bottom layer. The flexible composite assembly is disposed between the cover layer and the bottom layer.

(113) In some embodiments, the composite assembly includes an energy storage device. The energy storage device is disposed within the second housing.

(114) In some embodiments, a system includes a first assembly, a second assembly, and a composite assembly. The first assembly includes a first electrode and a first adhesive portion. The first assembly is configured to be coupled to a surface of a patient via the first adhesive portion. The second assembly includes a second electrode and a second adhesive portion. The second assembly configured to be coupled to a surface of a patient via the second adhesive portion. The composite assembly having a flexible portion, the flexible portion having a first end, a second end, and a plurality of layers. Each layer from the plurality of layers having a conductor extending between the first end and the second end. The first end is coupled to the first assembly and the second end is coupled to the second assembly. The composite assembly is configured to electrically

couple the first assembly with the second assembly. The flexible portion is configured to transition from a first configuration to a second configuration. A distance between the first end and the second end of the flexible portion in the first configuration being a first distance. A distance between the first end and the second end of the flexible portion in the second configuration being a second distance different from the first distance. The flexible portion configured to be coupled to a surface of a patient via a third adhesive portion in both the first configuration and the second configuration.

(115) In some embodiments, a conductor of a first layer of the plurality of layers is disposed a first distance away from a bottom surface of the flexible portion and a conductor of a second layer of the plurality of layers is disposed a second distance away from the bottom surface of the flexible portion.

(116) In some embodiments, a first layer from the plurality of layers is stacked directly above a second layer from the plurality of layers.

(117) In some embodiments, the composite assembly includes a printed circuit board.

Claims

1. A system, comprising: a first assembly including a first electrode and a first adhesive portion, the first assembly configured to be coupled to a surface of a patient via the first adhesive portion; a second assembly including a second electrode and a second adhesive portion, the second assembly configured to be coupled to the surface of the patient via the second adhesive portion; and a connecting member having a first end, a second end, and a third adhesive portion, the first end coupled to the first assembly and the second end coupled to the second assembly, the connecting member configured to transition between a first configuration and a second configuration, a distance between the first end and the second end of the connecting member in the first configuration being a first distance, a distance between the first end and the second end of the connecting member in the second configuration being a second distance different from the first distance, the connecting member configured to be coupled to the surface of the patient via the third adhesive portion in both the first configuration and the second configuration, wherein the connecting member has a composite assembly portion, the composite assembly portion having an insulative portion and a plurality of conductive traces each exposed on an outer surface of an entire length of the composite assembly and electrically coupling the first and second assemblies, such that the insulative portion surrounds each of the conductive traces on all sides except for the outer surface; wherein the plurality of conductive traces has a first conductive trace and a second conductive trace, wherein the first conductive trace and the second conductive trace are disposed at varying locations relative to a skin-facing surface of the composite assembly portion, such that the first conductive trace is disposed farther from the skin-facing surface than the second conductive trace, wherein the first conductive trace is vertically arranged relative to the second conductive trace such that the composite assembly portion is narrower than if the first conductive trace were horizontally arranged relative to the second conductive trace, and wherein a remaining portion of the connecting member not including the composite assembly portion does not include any of the plurality of conductive traces.

2. The system of claim 1, wherein the connecting member is configured to transition from the first configuration to the second configuration based at least in part on movement of the first assembly relative to the second assembly due to deformation of the surface of the patient.

3. The system of claim 1, wherein the connecting member is biased toward the first configuration.

4. The system of claim 1, wherein the connecting member is configured to be coupled to the surface of the patient via the third adhesive portion during the transition from the first configuration to the second configuration.

5. The system of claim 1, wherein the connecting member includes the skin-facing surface, the

third adhesive portion configured to cover a portion of the skin-facing surface.

6. The system of claim 1, wherein the connecting member further includes a fourth adhesive portion, the third adhesive portion disposed on the skin-facing surface of the connecting member at a first location, the fourth adhesive portion disposed on the skin-facing surface of the connecting member at a second location.

7. The system of claim 1, wherein the connecting member includes a first segment, a second segment, and a third segment, the first segment coupled to the second segment via a first flexible hinge, the second segment coupled to the third segment via a second flexible hinge.

8. The system of claim 1, wherein the connecting member has a first sinusoidal shape having a first frequency in the first configuration and a second sinusoidal shape having a second frequency in the second configuration, the second frequency different from the first frequency.

9. The system of claim 1, wherein the plurality of conductive traces has a third conductive trace electrically coupling the first and second assemblies, the third conductive trace being disposed side by side with the second conductive trace.

10. The system of claim 1, wherein the plurality of conductive traces has a third conductive trace and a fourth conductive trace electrically coupling the first and second assemblies, the fourth conductive trace being disposed side by side with the second conductive trace while the third conductive trace being disposed farther from the skin-facing surface than the fourth conductive trace and side by side with the first conductive trace.

11. The system of claim 10, wherein the third conductive trace is vertically arranged relative to the fourth conductive trace such that the composite assembly portion can be narrower than if at least one of the first conductive trace or the third conductive trace were horizontally arranged relative to the second conductive trace and the fourth conductive trace.

12. The system of claim 1, wherein the plurality of conductive traces has a third conductive trace and a fourth conductive trace electrically coupling the first and second assemblies, the third conductive trace and the fourth conductive trace being vertically arranged relative to both the first conductive trace and the second conductive trace such that the composite assembly portion can be narrower than if at least one of the third conductive trace or the fourth conductive trace were horizontally arranged relative to the first conductive trace or the second conductive trace.

13. The system of claim 1, wherein the plurality of conductive traces has a third conductive trace electrically coupling the first and second assemblies, the third conductive trace being disposed side by side with the first conductive trace.

14. The system of claim 1, wherein the plurality of conductive traces are exposed on the outer surface by each being etched into or printed on the outer surface of the entire length of the composite assembly.
