

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12383397
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Yang; Yimin et al.

Prosthetic heart valve with suture loop preventing member

Abstract

A prosthetic heart valve system includes a prosthetic heart valve having an inflow side, and an outflow side. The heart valve further includes a base at the inflow side, a plurality of commissure posts and valve leaflets secured to the commissure posts to permit flow through the heart valve. An anti-loop member has a first portion on the inflow side of the heart valve and a second portion on the outflow side of the heart valve. The second portion of the anti-loop member is arranged along each commissure post at the tip of each commissure post, and arranged along at least one commissure post twice to form a loop around all of the commissure posts. The anti-loop member is made of a material sufficiently flexible to be removed from the commissure posts without damaging the heart valve yet rigid enough to retain its shape when coming in contact with sutures.

Inventors:	Yang; Yimin (Irvine, CA), Quach; Michael (Long Beach, CA)
Applicant:	Edwards Lifesciences Corporation (Irvine, CA)
Family ID:	69740676
Assignee:	EDWARDS LIFESCIENCES CORPORATION (Irvine, CA)
Appl. No.:	17/395341
Filed:	August 05, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20210361423 A1	Nov. 25, 2021

Related U.S. Application Data

continuation parent-doc WO PCT/US2020/015798 20200130 PENDING child-doc US 17395341
us-provisional-application US 62801598 20190205

Publication Classification

Int. Cl.: A61F2/24 (20060101)

U.S. Cl.:

CPC A61F2/2418 (20130101); A61F2210/0014 (20130101); A61F2220/0075 (20130101); A61F2230/0091 (20130101); A61F2250/0087 (20130101)

Field of Classification Search

CPC: A61F (2/2418); A61F (2210/0014); A61F (2220/0075); A61F (2230/0091); A61F (2250/0087)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3143742	12/1963	Cromie	N/A	N/A
3320972	12/1966	High et al.	N/A	N/A
3371352	12/1967	Siposs et al.	N/A	N/A
3546710	12/1969	Ivanovich et al.	N/A	N/A
3574865	12/1970	Hamaker	N/A	N/A
3755823	12/1972	Hancock	N/A	N/A
3839741	12/1973	Haller	N/A	N/A
3997923	12/1975	Possis	N/A	N/A
4035849	12/1976	Angell et al.	N/A	N/A
4079468	12/1977	Liotta et al.	N/A	N/A
4084268	12/1977	Ionescu et al.	N/A	N/A
4106129	12/1977	Carpentier et al.	N/A	N/A
4172295	12/1978	Batten	N/A	N/A
4217665	12/1979	Bex et al.	N/A	N/A
4218782	12/1979	Rygg	N/A	N/A
4259753	12/1980	Liotta et al.	N/A	N/A
RE30912	12/1981	Hancock	N/A	N/A
4340091	12/1981	Skelton et al.	N/A	N/A
4343048	12/1981	Ross et al.	N/A	N/A
4364126	12/1981	Rosen et al.	N/A	N/A
4388735	12/1982	Ionescu et al.	N/A	N/A
4441216	12/1983	Ionescu et al.	N/A	N/A
4451936	12/1983	Carpentier et al.	N/A	N/A
4470157	12/1983	Love	N/A	N/A
4490859	12/1984	Black et al.	N/A	N/A
4501030	12/1984	Lane	N/A	N/A
4506394	12/1984	Bedard	N/A	N/A
4535483	12/1984	Klawitter et al.	N/A	N/A
4566465	12/1985	Arhan et al.	N/A	N/A
4605407	12/1985	Black et al.	N/A	N/A
4626255	12/1985	Reichart et al.	N/A	N/A

4629459	12/1985	Ionescu et al.	N/A	N/A
4680031	12/1986	Alonso	N/A	N/A
4687483	12/1986	Fisher et al.	N/A	N/A
4705516	12/1986	Barone et al.	N/A	N/A
4725274	12/1987	Lane et al.	N/A	N/A
4731074	12/1987	Rousseau et al.	N/A	N/A
4778461	12/1987	Pietsch et al.	N/A	N/A
4790843	12/1987	Carpentier et al.	N/A	N/A
4851000	12/1988	Gupta	N/A	N/A
4888009	12/1988	Lederman et al.	N/A	N/A
4914097	12/1989	Oda et al.	N/A	N/A
4960424	12/1989	Grooters	N/A	N/A
4993428	12/1990	Arms	N/A	N/A
5010892	12/1990	Colvin et al.	N/A	N/A
5032128	12/1990	Alonso	N/A	N/A
5037434	12/1990	Lane	N/A	N/A
5147391	12/1991	Lane	N/A	N/A
5163955	12/1991	Love et al.	N/A	N/A
5258023	12/1992	Reger	N/A	N/A
5316016	12/1993	Adams et al.	N/A	N/A
5326370	12/1993	Love et al.	N/A	N/A
5326371	12/1993	Love et al.	N/A	N/A
5332402	12/1993	Teitelbaum	N/A	N/A
5360014	12/1993	Sauter et al.	N/A	N/A
5360444	12/1993	Kusuhara	N/A	N/A
5376112	12/1993	Duran	N/A	N/A
5396887	12/1994	Imran	N/A	N/A
5397351	12/1994	Pavcnik et al.	N/A	N/A
5423887	12/1994	Love et al.	N/A	N/A
5425741	12/1994	Lemp et al.	N/A	N/A
5431676	12/1994	Dubrul et al.	N/A	N/A
5449384	12/1994	Johnson	N/A	N/A
5449385	12/1994	Religa et al.	N/A	N/A
5469868	12/1994	Reger	N/A	N/A
5487760	12/1995	Villafana	N/A	N/A
5488789	12/1995	Religa et al.	N/A	N/A
5489296	12/1995	Love et al.	N/A	N/A
5489297	12/1995	Duran	N/A	N/A
5489298	12/1995	Love et al.	N/A	N/A
5500016	12/1995	Fisher	N/A	N/A
5533515	12/1995	Coller et al.	N/A	N/A
5549665	12/1995	Vesely et al.	N/A	N/A
5562729	12/1995	Purdy et al.	N/A	N/A
5571215	12/1995	Sterman et al.	N/A	N/A
5573007	12/1995	Bobo	N/A	N/A
5578076	12/1995	Krueger et al.	N/A	N/A
5584803	12/1995	Stevens et al.	N/A	N/A
5618307	12/1996	Donlon et al.	N/A	N/A
5626607	12/1996	Malecki et al.	N/A	N/A
5628789	12/1996	Vanney et al.	N/A	N/A

5693090	12/1996	Unsworth et al.	N/A	N/A
5695503	12/1996	Krueger et al.	N/A	N/A
5713952	12/1997	Vanney et al.	N/A	N/A
5716370	12/1997	Williamson et al.	N/A	N/A
5728064	12/1997	Burns et al.	N/A	N/A
5728151	12/1997	Garrison et al.	N/A	N/A
5735894	12/1997	Krueger et al.	N/A	N/A
5752522	12/1997	Murphy	N/A	N/A
5755782	12/1997	Love et al.	N/A	N/A
5766240	12/1997	Johnson	N/A	N/A
5800527	12/1997	Jansen et al.	N/A	N/A
5814097	12/1997	Sterman et al.	N/A	N/A
5814098	12/1997	Hinnenkamp et al.	N/A	N/A
5824064	12/1997	Taheri	N/A	N/A
5824068	12/1997	Bugge	N/A	N/A
5840081	12/1997	Andersen et al.	N/A	N/A
5848969	12/1997	Panescu et al.	N/A	N/A
5855563	12/1998	Kaplan et al.	N/A	N/A
5855601	12/1998	Bessler et al.	N/A	N/A
5855801	12/1998	Lin et al.	N/A	N/A
5891160	12/1998	Williamson et al.	N/A	N/A
5895420	12/1998	Mirsch et al.	N/A	N/A
5902308	12/1998	Murphy	N/A	N/A
5908450	12/1998	Gross et al.	N/A	N/A
5919147	12/1998	Jain	N/A	N/A
5921934	12/1998	Teo	N/A	N/A
5921935	12/1998	Hickey	N/A	N/A
5924984	12/1998	Rao	N/A	N/A
5957949	12/1998	Leonhardt et al.	N/A	N/A
5972004	12/1998	Williamson et al.	N/A	N/A
5984959	12/1998	Robertson et al.	N/A	N/A
5984973	12/1998	Girard et al.	N/A	N/A
6010531	12/1999	Donlon et al.	N/A	N/A
6042554	12/1999	Rosenman et al.	N/A	N/A
6042607	12/1999	Williamson et al.	N/A	N/A
6066160	12/1999	Colvin et al.	N/A	N/A
6074418	12/1999	Buchanan et al.	N/A	N/A
6081737	12/1999	Shah	N/A	N/A
6083179	12/1999	Oredsson	N/A	N/A
6099475	12/1999	Seward et al.	N/A	N/A
6106550	12/1999	Magovern et al.	N/A	N/A
6110200	12/1999	Hinnenkamp	N/A	N/A
6117091	12/1999	Young et al.	N/A	N/A
6126007	12/1999	Kari et al.	N/A	N/A
6162233	12/1999	Williamson et al.	N/A	N/A
6168614	12/2000	Andersen et al.	N/A	N/A
6176877	12/2000	Buchanan et al.	N/A	N/A
6197054	12/2000	Hamblin et al.	N/A	N/A
6217611	12/2000	Klostermeyer	N/A	N/A
6231561	12/2000	Frazier et al.	N/A	N/A

6241765	12/2000	Griffin et al.	N/A	N/A
6245102	12/2000	Jayaraman	N/A	N/A
6264611	12/2000	Ishikawa et al.	N/A	N/A
6283127	12/2000	Sterman et al.	N/A	N/A
6287339	12/2000	Vazquez et al.	N/A	N/A
6290674	12/2000	Roue et al.	N/A	N/A
6312447	12/2000	Grimes	N/A	N/A
6312465	12/2000	Griffin et al.	N/A	N/A
6328727	12/2000	Frazier et al.	N/A	N/A
6350282	12/2001	Eberhardt	N/A	N/A
6371983	12/2001	Lane	N/A	N/A
6375620	12/2001	Oser et al.	N/A	N/A
6402780	12/2001	Williamson et al.	N/A	N/A
6409674	12/2001	Brockway et al.	N/A	N/A
6425916	12/2001	Garrison et al.	N/A	N/A
6440164	12/2001	DiMatteo et al.	N/A	N/A
6442413	12/2001	Silver	N/A	N/A
6454799	12/2001	Schreck	N/A	N/A
6458153	12/2001	Bailey et al.	N/A	N/A
6468305	12/2001	Otte	N/A	N/A
6491624	12/2001	Lotfi	N/A	N/A
6582462	12/2002	Andersen et al.	N/A	N/A
6585766	12/2002	Huynh et al.	N/A	N/A
6645143	12/2002	VanTassel et al.	N/A	N/A
6652464	12/2002	Schwartz et al.	N/A	N/A
6652578	12/2002	Bailey et al.	N/A	N/A
6675049	12/2003	Thompson et al.	N/A	N/A
6682559	12/2003	Myers et al.	N/A	N/A
6685739	12/2003	DiMatteo et al.	N/A	N/A
6730118	12/2003	Spenser et al.	N/A	N/A
6733525	12/2003	Yang et al.	N/A	N/A
6741885	12/2003	Park et al.	N/A	N/A
6764508	12/2003	Roehe et al.	N/A	N/A
6767362	12/2003	Schreck	N/A	N/A
6773457	12/2003	Ivancev et al.	N/A	N/A
6786925	12/2003	Schoon et al.	N/A	N/A
6790229	12/2003	Berrekouw	N/A	N/A
6790230	12/2003	Beyersdorf et al.	N/A	N/A
6795732	12/2003	Stadler et al.	N/A	N/A
6805711	12/2003	Quijano et al.	N/A	N/A
6893459	12/2004	Macoviak	N/A	N/A
6893460	12/2004	Spenser et al.	N/A	N/A
6895265	12/2004	Silver	N/A	N/A
6908481	12/2004	Cribier	N/A	N/A
6939365	12/2004	Fogarty et al.	N/A	N/A
7011681	12/2005	Vesely	N/A	N/A
7025780	12/2005	Gabbay	N/A	N/A
7033322	12/2005	Silver	N/A	N/A
7052466	12/2005	Scheiner et al.	N/A	N/A
7070616	12/2005	Majercak et al.	N/A	N/A

7082330	12/2005	Stadler et al.	N/A	N/A
7097659	12/2005	Woolfson et al.	N/A	N/A
7101396	12/2005	Artof et al.	N/A	N/A
7147663	12/2005	Berg et al.	N/A	N/A
7153324	12/2005	Case et al.	N/A	N/A
7195641	12/2006	Palmaz et al.	N/A	N/A
7201771	12/2006	Lane	N/A	N/A
7201772	12/2006	Schwammenthal et al.	N/A	N/A
7238200	12/2006	Lee et al.	N/A	N/A
7252682	12/2006	Seguin	N/A	N/A
7261732	12/2006	Justino	N/A	N/A
RE40377	12/2007	Williamson, IV et al.	N/A	N/A
7416530	12/2007	Turner et al.	N/A	N/A
7422603	12/2007	Lane	N/A	N/A
7513909	12/2008	Lane et al.	N/A	N/A
7556647	12/2008	Drews et al.	N/A	N/A
7569072	12/2008	Berg et al.	N/A	N/A
7621878	12/2008	Ericson et al.	N/A	N/A
7916013	12/2010	Stevenson	N/A	N/A
7998151	12/2010	St. Goar et al.	N/A	N/A
8066650	12/2010	Lee et al.	N/A	N/A
8248232	12/2011	Stevenson et al.	N/A	N/A
8253555	12/2011	Stevenson et al.	N/A	N/A
8340750	12/2011	Prakash et al.	N/A	N/A
8401659	12/2012	Von Arx et al.	N/A	N/A
8529474	12/2012	Gupta et al.	N/A	N/A
8622936	12/2013	Schenberger et al.	N/A	N/A
9101264	12/2014	Acquista	N/A	N/A
9101281	12/2014	Reinert et al.	N/A	N/A
9693862	12/2016	Campbell et al.	N/A	N/A
2001/0039435	12/2000	Roue et al.	N/A	N/A
2001/0039436	12/2000	Frazier et al.	N/A	N/A
2001/0041914	12/2000	Frazier et al.	N/A	N/A
2001/0041915	12/2000	Roue et al.	N/A	N/A
2001/0049492	12/2000	Frazier et al.	N/A	N/A
2002/0020074	12/2001	Love et al.	N/A	N/A
2002/0026238	12/2001	Lane et al.	N/A	N/A
2002/0032481	12/2001	Gabbay	N/A	N/A
2002/0058995	12/2001	Stevens	N/A	N/A
2002/0082686	12/2001	Nguyen-Thien-Nhon	623/2.11	A61F 2/2427
2002/0123802	12/2001	Snyders	N/A	N/A
2002/0138138	12/2001	Yang	N/A	N/A
2002/0151961	12/2001	Lashinski	623/2.11	A61F 2/2451
2002/0151970	12/2001	Garrison et al.	N/A	N/A
2002/0188348	12/2001	DiMatteo et al.	N/A	N/A
2002/0198594	12/2001	Schreck	N/A	N/A
2003/0014104	12/2002	Cribier	N/A	N/A

2003/0023300	12/2002	Bailey et al.	N/A	N/A
2003/0023303	12/2002	Palmaz et al.	N/A	N/A
2003/0036795	12/2002	Andersen et al.	N/A	N/A
2003/0040792	12/2002	Gabbay	N/A	N/A
2003/0055495	12/2002	Pease et al.	N/A	N/A
2003/0105519	12/2002	Fasol et al.	N/A	N/A
2003/0109924	12/2002	Cribier	N/A	N/A
2003/0114913	12/2002	Spenser et al.	N/A	N/A
2003/0130729	12/2002	Paniagua et al.	N/A	N/A
2003/0149478	12/2002	Figulla et al.	N/A	N/A
2003/0167089	12/2002	Lane	N/A	N/A
2003/0236568	12/2002	Hojeibane et al.	N/A	N/A
2004/0010296	12/2003	Swanson et al.	N/A	N/A
2004/0019374	12/2003	Hojeibane et al.	N/A	N/A
2004/0027306	12/2003	Amundson et al.	N/A	N/A
2004/0034411	12/2003	Quijano et al.	N/A	N/A
2004/0044406	12/2003	Woolfson et al.	N/A	N/A
2004/0106976	12/2003	Bailey et al.	N/A	N/A
2004/0122514	12/2003	Fogarty et al.	N/A	N/A
2004/0122516	12/2003	Fogarty et al.	N/A	N/A
2004/0148017	12/2003	Stobie	623/2.11	A61F 2/2427
2004/0167573	12/2003	Williamson et al.	N/A	N/A
2004/0186563	12/2003	Lobbi	N/A	N/A
2004/0186565	12/2003	Schreck	N/A	N/A
2004/0193261	12/2003	Berreklouw	N/A	N/A
2004/0206363	12/2003	McCarthy et al.	N/A	N/A
2004/0210304	12/2003	Seguin et al.	N/A	N/A
2004/0210307	12/2003	Khairkhan	N/A	N/A
2004/0225355	12/2003	Stevens	N/A	N/A
2004/0236411	12/2003	Sarac et al.	N/A	N/A
2004/0260389	12/2003	Case et al.	N/A	N/A
2004/0260390	12/2003	Sarac et al.	N/A	N/A
2005/0010285	12/2004	Lambrecht et al.	N/A	N/A
2005/0027348	12/2004	Case et al.	N/A	N/A
2005/0033398	12/2004	Seguin	N/A	N/A
2005/0043760	12/2004	Fogarty et al.	N/A	N/A
2005/0043790	12/2004	Seguin	N/A	N/A
2005/0060029	12/2004	Le et al.	N/A	N/A
2005/0065594	12/2004	DiMatteo et al.	N/A	N/A
2005/0065614	12/2004	Stinson	N/A	N/A
2005/0075584	12/2004	Cali	N/A	N/A
2005/0075713	12/2004	Biancucci et al.	N/A	N/A
2005/0075717	12/2004	Nguyen et al.	N/A	N/A
2005/0075718	12/2004	Nguyen et al.	N/A	N/A
2005/0075719	12/2004	Bergheim	N/A	N/A
2005/0075720	12/2004	Nguyen et al.	N/A	N/A
2005/0075724	12/2004	Svanidze et al.	N/A	N/A
2005/0080454	12/2004	Drews et al.	N/A	N/A
2005/0096738	12/2004	Cali et al.	N/A	N/A

2005/0137682	12/2004	Justino	N/A	N/A
2005/0137686	12/2004	Salahieh et al.	N/A	N/A
2005/0137687	12/2004	Salahieh et al.	N/A	N/A
2005/0137688	12/2004	Salahieh et al.	N/A	N/A
2005/0137690	12/2004	Salahieh et al.	N/A	N/A
2005/0137692	12/2004	Haug et al.	N/A	N/A
2005/0137695	12/2004	Salahieh et al.	N/A	N/A
2005/0159811	12/2004	Lane	N/A	N/A
2005/0165479	12/2004	Drews et al.	N/A	N/A
2005/0182486	12/2004	Gabbay	N/A	N/A
2005/0192665	12/2004	Spenser et al.	N/A	N/A
2005/0203616	12/2004	Cribier	N/A	N/A
2005/0203617	12/2004	Forster et al.	N/A	N/A
2005/0203618	12/2004	Sharkawy et al.	N/A	N/A
2005/0216079	12/2004	MaCoviak	N/A	N/A
2005/0222674	12/2004	Paine	N/A	N/A
2005/0234546	12/2004	Nugent et al.	N/A	N/A
2005/0240263	12/2004	Fogarty et al.	N/A	N/A
2005/0251252	12/2004	Stobie	N/A	N/A
2005/0261765	12/2004	Liddicoat	N/A	N/A
2005/0283231	12/2004	Haug et al.	N/A	N/A
2006/0025857	12/2005	Bergheim et al.	N/A	N/A
2006/0052867	12/2005	Revuelta et al.	N/A	N/A
2006/0058871	12/2005	Zakay et al.	N/A	N/A
2006/0058872	12/2005	Salahieh et al.	N/A	N/A
2006/0074484	12/2005	Huber	N/A	N/A
2006/0085060	12/2005	Campbell	N/A	N/A
2006/0095125	12/2005	Chinn et al.	N/A	N/A
2006/0122634	12/2005	Ino et al.	N/A	N/A
2006/0149360	12/2005	Schwammenthal et al.	N/A	N/A
2006/0154230	12/2005	Cunanan et al.	N/A	N/A
2006/0167543	12/2005	Bailey et al.	N/A	N/A
2006/0195183	12/2005	Navia	623/2.11	A61F 2/2418
2006/0195184	12/2005	Lane et al.	N/A	N/A
2006/0195185	12/2005	Lane et al.	N/A	N/A
2006/0195186	12/2005	Drews et al.	N/A	N/A
2006/0207031	12/2005	Cunanan et al.	N/A	N/A
2006/0241745	12/2005	Solem	N/A	N/A
2006/0259136	12/2005	Nguyen et al.	N/A	N/A
2006/0271172	12/2005	Tehrani	N/A	N/A
2006/0271175	12/2005	Woolfson et al.	N/A	N/A
2006/0287717	12/2005	Rowe et al.	N/A	N/A
2006/0287719	12/2005	Rowe et al.	N/A	N/A
2007/0005129	12/2006	Damm et al.	N/A	N/A
2007/0010876	12/2006	Salahieh et al.	N/A	N/A
2007/0016285	12/2006	Lane et al.	N/A	N/A
2007/0016286	12/2006	Herrmann et al.	N/A	N/A
2007/0016288	12/2006	Gurskis et al.	N/A	N/A

2007/0043435	12/2006	Seguin et al.	N/A	N/A
2007/0078509	12/2006	Lotfy	N/A	N/A
2007/0078510	12/2006	Ryan	N/A	N/A
2007/0100440	12/2006	Figulla et al.	N/A	N/A
2007/0129794	12/2006	Realyvasquez	N/A	N/A
2007/0142906	12/2006	Figulla et al.	N/A	N/A
2007/0142907	12/2006	Moaddeb et al.	N/A	N/A
2007/0150053	12/2006	Gurskis et al.	N/A	N/A
2007/0156233	12/2006	Kapadia et al.	N/A	N/A
2007/0162103	12/2006	Case et al.	N/A	N/A
2007/0162107	12/2006	Haug et al.	N/A	N/A
2007/0162111	12/2006	Fukamachi et al.	N/A	N/A
2007/0179604	12/2006	Lane	N/A	N/A
2007/0185565	12/2006	Schwammenthal et al.	N/A	N/A
2007/0198097	12/2006	Zegdi	N/A	N/A
2007/0203575	12/2006	Forster et al.	N/A	N/A
2007/0203576	12/2006	Lee et al.	N/A	N/A
2007/0213813	12/2006	Von Segesser et al.	N/A	N/A
2007/0225801	12/2006	Drews et al.	N/A	N/A
2007/0233237	12/2006	Krivoruchko	N/A	N/A
2007/0239266	12/2006	Birdsall	N/A	N/A
2007/0239269	12/2006	Dolan et al.	N/A	N/A
2007/0239273	12/2006	Allen	N/A	N/A
2007/0255398	12/2006	Yang et al.	N/A	N/A
2007/0260305	12/2006	Drews et al.	N/A	N/A
2007/0265701	12/2006	Gurskis et al.	N/A	N/A
2007/0270944	12/2006	Bergheim et al.	N/A	N/A
2007/0282436	12/2006	Pinchuk	N/A	N/A
2007/0288089	12/2006	Gurskis et al.	N/A	N/A
2008/0033543	12/2007	Gurskis et al.	N/A	N/A
2008/0046040	12/2007	Denker et al.	N/A	N/A
2008/0119875	12/2007	Ino et al.	N/A	N/A
2008/0154356	12/2007	Obermiller et al.	N/A	N/A
2008/0319543	12/2007	Lane	N/A	N/A
2009/0036903	12/2008	Ino et al.	N/A	N/A
2009/0192591	12/2008	Ryan et al.	N/A	N/A
2009/0192599	12/2008	Lane et al.	N/A	N/A
2010/0049313	12/2009	Alon et al.	N/A	N/A
2010/0145438	12/2009	Barone	N/A	N/A
2010/0256723	12/2009	Murray	N/A	N/A
2012/0123284	12/2011	Kheradvar	N/A	N/A
2012/0296382	12/2011	Shuros et al.	N/A	N/A
2013/0144379	12/2012	Najafi et al.	N/A	N/A
2014/0039609	12/2013	Campbell	623/2.11	A61F 2/2412
2014/0128964	12/2013	Delaloye	N/A	N/A
2014/0188221	12/2013	Chung et al.	N/A	N/A
2014/0364707	12/2013	Kintz et al.	N/A	N/A
2015/0045635	12/2014	Tankiewicz et al.	N/A	N/A

2016/0045316	12/2015	Braido et al.	N/A	N/A
2016/0235525	12/2015	Rothstein	N/A	A61F 2/2418
2017/0224486	12/2016	Delaloye	N/A	A61F 2/966
2019/0224009	12/2018	Conklin	N/A	A61F 2/2427
2019/0321170	12/2018	Green et al.	N/A	N/A
2021/0113330	12/2020	Benichou	N/A	A61F 2/2418

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
0125393	12/1983	EP	N/A
0143246	12/1984	EP	N/A
1116573	12/1984	SU	N/A
1697790	12/1990	SU	N/A
1992013502	12/1991	WO	N/A
1997042871	12/1996	WO	N/A

OTHER PUBLICATIONS

Bapat, Vinayak et al. "A Guide to Fluoroscopic Identification and Design of Bioprosthetic Valves: A Reference for Valve-in-Valve Procedure", Wiley Periodicals, Inc., 2012. cited by applicant

Primary Examiner: Edwards; Jerrah

Assistant Examiner: Patel; Aren

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION (1) This application is a continuation of PCT Application PCT/US20/15798, filed Jan. 30, 2020, which claims the benefit of U.S. Application No. 62/801,598, filed Feb. 5, 2019, which is incorporated by reference in its entirety for all purposes.

FIELD

(1) The present disclosure generally concerns medical devices, deployment mechanisms, and methods for deploying such medical devices. More specifically, the disclosure relates to the surgical replacement of heart valves that have malformations and/or dysfunctions. Some embodiments relate to a prosthetic heart valve system having an anti-looping device to prevent suture looping during deployment of the prosthetic heart valve to the native heart valve site, for example for a mitral valve replacement procedure. Some embodiments also relate to methods of using the anti-looping device to facilitate implantation of prosthetic heart valves.

BACKGROUND

(2) Referring first to FIG. 1, the human heart is generally separated into four pumping chambers which pump blood through the body. Each chamber is provided with its own one-way exit valve. The left atrium receives oxygenated blood from the lungs and advances the oxygenated blood to the left ventricle through the mitral (or bicuspid) valve. The left ventricle collects the oxygenated blood from the left atrium and pushes it through the aortic valve to the aorta, where the oxygenated blood is then distributed to the rest of the body. Deoxygenated blood from the body is then

collected at the right atrium and advanced to the right ventricle through the tricuspid valve. The right ventricle then advances the deoxygenated blood through the pulmonary valve and the pulmonary arteries to the lungs to again supply the blood with oxygen.

(3) Each of the valves associated with the chambers of the heart are one-way valves that have leaflets to control the directional flow of the blood through the heart and to prevent backflow of the blood into other chambers or blood vessels that are upstream of the particular chamber. The valves are each supported by an annulus having a dense fibrous ring attached either directly or indirectly to the atrial or ventricular muscle fibers.

(4) When a valve becomes diseased or damaged, the efficiency and/or general functionality of the heart may be compromised. Diseased heart valves may be categorized as either stenotic, wherein the valve does not open sufficiently to allow adequate forward flow of blood through the valve, and/or incompetent, wherein the valve does not close completely, causing excessive backward flow of blood through the valve when the valve is closed. Valve disease can be severely debilitating and even fatal if left untreated.

(5) Various surgical techniques can be performed to replace a diseased or damaged valve. For example, the leaflets of a diseased or damaged native valve may be at least partially removed to prepare the valve annulus for receiving a prosthetic replacement valve. FIG. 2 shows an example of one type of popular prosthetic replacement valve **1** that is a tissue-type bioprosthetic valve generally constructed with natural-tissue valve leaflets **2**, made for example, from porcine tissue or bovine pericardium, or from synthetic or semisynthetic material, that are mounted on a surrounding valve stent structure or frame **3**. The shape and structure of the leaflets **2** are supported by a number of commissure posts **4** positioned circumferentially around the valve stent structure **3**. In these valves, a biocompatible cloth-covered suture or sewing ring **5** can also be provided on an inflow end of the stent structure **3** of the valve **1**, to facilitate easier attachment to the native valve annulus. Such prosthetic valves function much like natural human heart valves, where the leaflets coapt against one another to effect the one-way flow of blood.

(6) When implanting a tissue type prosthetic valve as described above at a native valve annulus, a number of sutures may be involved in the attachment process, many of which may be pre-installed for providing a track on which the valve is advanced, or “parachuted,” until it is properly positioned at the implant site. Additional sutures may also be tied and knotted between the prosthetic valve and the heart walls after proper placement, to securely attach or hold the valve implant in place.

(7) Depending on the direction of implantation, for example with some mitral valve replacement procedures, commissure posts of the stent or frame, or other portions of the prosthetic valve, may be pointed distally and advanced on a blind side of the valve, thereby obstructing visibility of the posts or other portions during advancement and implantation. Such procedures can also require a prosthetic valve and its holder to fit through an incision of approximately 15-20 mm in its narrowest direction or dimension. Meanwhile, in some cases, the prosthetic valves are implanted through small access channels using one of various minimally invasive surgical procedures, where visibility at the implant site may be impeded or obstructed.

(8) Each of the above factors may lead to tangling of the sutures with the valve prosthesis, most commonly with the commissure posts of the frame, since the commissure posts provide a protrusion on which the sutures can easily loop around and tangle. This type of entanglement of sutures with prosthetic valves is referred to as “suture looping,” which specifically refers to instances where a suture is inadvertently wrapped around one or more of the commissure post tips, where it can then migrate towards and damage the leaflets or interfere with proper leaflet coaptation or other valve operation when the sutures are tightened or secured, resulting in improper valve operation.

(9) An example of suture looping is shown in FIGS. 3A-3C. With reference to FIG. 3A, a prosthetic mitral valve **10** is shown as it is parachuted to a mitral valve opening **12** defined by a valve annulus

14 of the heart. One pre-installed suture **16** is shown that has been threaded through a sewing ring **18** of the valve **10**, down to the valve annulus **14** and back up through the sewing ring. Several sutures are used to parachute the valve and secure the valve to the annulus. Only one suture is shown in this example for clarity.

(10) With reference to FIG. 3B, an example of tangling is shown where a commissure post **20** passes between the left strand **22** and the right strand **24** of the suture **16**. As the heart valve **10** continues to move down the strands and into the valve opening **12**, the right strand **24** gets looped behind the commissure post **20** while the left strand **22** remains in front. To complete the procedure, the heart valve is pushed down until the sewing ring **18** contacts the valve annulus **14**. But this final action will cause the right strand **24** to slide along the inside of the commissure post **20** away from the tip and push on the flexible valve leaflets **26** (FIG. 3C), potentially causing damage or affecting blood flow through the valve. FIG. 3C is a view from the opposite side of the valve opening **12** showing the right strand **24** looped around the commissure post **20** and pushing down on the valve leaflets **26**. Such tangling may not be apparent to the surgical team at the time of implantation, and will only be revealed some time later when valve operation is observed to be improper or other complications arise in the patient, in which case it may be necessary to initiate another procedure to repair or replace the prosthetic valve.

(11) Attempts have been made to resolve the problem of suture looping, some of which revolve around the holders which hold the prosthetic valves when they are delivered to the native valve annulus. In one example, a holder has a mechanism that urges the commissure posts of the prosthetic valve radially inward during delivery, so that the ends of the commissure posts are pointed inwards, to reduce the possibility of sutures catching against or looping around them. After the valve prosthesis is delivered to the implant site, the holder is removed, releasing and expanding the commissure posts to their original positions. However, although the commissure posts are biased inwardly during delivery, since the ends of the commissure posts remain free, these holders have not been fully effective in eliminating instances of suture looping.

(12) Another valve holder system developed for use in mitral valve replacement procedures to protect the valve from suture looping during valve implantation is described in U.S. Pat. No. 6,964,682, the contents of which are incorporated by reference herein in their entirety. The system includes monofilament deflection sutures that attach to both the holder and pairs of commissures of the prosthetic valve, so that the sutures run across the outflow end of the valve between the ends of the commissures. When the holder is actuated, a central post extends distally through the prosthetic valve between the leaflets and pushes against the sutures in the middle of the valve between the commissures, pushing the sutures distally and causing an angled tent-like or umbrella shape of sutures. The pressure on the sutures deflects the commissures slightly inward, while also forming the angled umbrella shape of the sutures that slope outwardly and downwardly from the central post to the commissure posts. These angled surfaces deflect away from the prosthetic valve any other sutures, such as the pre-installed attachment sutures, mentioned above, that might otherwise engage and be looped around a commissure or valve leaflet.

(13) Other holders have also been developed in an attempt to further reduce instances of suture looping. However, some of these holders are very complex, for example, incorporating various rotary and advancement mechanisms in addition to the original hold and release mechanisms, such that a number of additional steps must be taken by the practitioner to operate the holders correctly. Many of these holders have proven to be too complicated and/or prone to user error, such as a failure to execute all deployment steps in the correct order. Consequently, when practitioners use these holders improperly, suture looping can still occur, while the implant process may also be further complicated by issues arising from user error.

(14) Accordingly, there is a need for an improved prosthetic heart valve assembly that is easier to use during valve implantation, is more effective to prevent suture looping, is simpler in design, and provides improved visibility for the surgical team when implanting the valve.

SUMMARY

(15) In a preferred embodiment, a prosthetic heart valve system includes a prosthetic heart valve having an inflow side and an outflow side, and a flow axis therethrough. The heart valve further includes a base at the inflow side, a plurality of commissure posts extending from the base away from the inflow side and circumferentially spaced around the flow axis, and valve leaflets secured to the commissure posts to permit flow through the heart valve. Each commissure post has a tip on the outflow side. An anti-loop member has a first portion on the inflow side of the heart valve and a second portion on the outflow side of the heart valve. The second portion of the anti-loop member is arranged along each commissure post at the tip of each commissure post, and arranged along at least one commissure post twice to form a loop around all of the plurality of commissure posts. The anti-loop member is preferably made of a material sufficiently flexible to be removed from the commissure posts without damaging the heart valve by pulling on the first end portion of the anti-loop member yet rigid enough to retain its shape when coming in contact with sutures used to secure the heart valve to a heart valve annulus.

(16) In a further embodiment, the second portion of the anti-loop member is attached to each commissure post at the tip of each commissure post and to the at least one commissure post twice, to form the loop around all of the plurality of commissure posts. In addition, the anti-loop member may be attached to a side of each commissure post facing away from the flow axis. Further, the anti-loop member may loop around the plurality of commissure posts twice. In an alternative embodiment, an outer loop of the anti-loop member is attached to a side of each commissure post facing away from the flow axis and an inner loop of the anti-loop member is inside the outer loop. In another embodiment, the anti-loop member is a superelastic nitinol. Furthermore, the anti-loop member may be shape set in a coiled form. In an alternative embodiment, a free end of the second portion of the anti-loop member may be located radially inside the periphery of the plurality of commissure posts.

(17) In another embodiment, a free end of the second portion of the anti-loop member is an enlarged portion shaped to prevent damage to surrounding tissue. The enlarged portion is in the shape of a ball.

(18) In a preferred embodiment, the base of the prosthetic heart valve has a sewing ring to engage a native valve annulus and the anti-loop member passes through the sewing ring. Preferably, the anti-loop member passes through the sewing ring adjacent an inner diameter of the sewing ring.

(19) Further, the anti-loop member may extend from a tip of one commissure post and through the sewing ring at a location closer to an adjacent commissure post than the one commissure post.

(20) In another embodiment, a prosthetic heart valve system, includes a prosthetic heart valve having an inflow side and an outflow side, and a flow axis therethrough. The heart valve further includes a base at the inflow side, a plurality of commissure posts extending from the base away from the inflow side and circumferentially spaced around the flow axis, and valve leaflets secured to the commissure posts to permit flow through the heart valve. Each commissure post has a tip on the outflow side. An anti-loop member has a first portion of the anti-loop member on the inflow side of the heart valve and a second portion on the outflow side of the heart valve. The second portion of the anti-loop member is arranged along each commissure post at the tip of each commissure post, and arranged along at least one commissure post twice to form a loop around all of the plurality of commissure posts. A valve holder is also removably secured to the prosthetic heart valve. The anti-loop member is preferably made of a material sufficiently flexible to be removed from the commissure posts without damaging the heart valve by pulling on the first end portion of the anti-loop member yet rigid enough to retain its shape when coming in contact with sutures used to secure the heart valve to a heart valve annulus.

(21) In a further embodiment, the first portion of the anti-loop member is secured to the valve holder such that removal of the valve holder from the heart valve also results in removal of the anti-loop member from the heart valve. In another embodiment, the first portion of the anti-loop

member has an indicator to alert a member of the surgical team to remove the anti-loop coil. The indicator is preferably a contrasting color to the environment.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) Further features and advantages will become apparent from the description of embodiments using the accompanying drawings. In the drawings:
- (2) FIG. 1 shows a schematic cross-sectional view of a human heart;
- (3) FIG. 2 shows a schematic perspective view of an example of a prosthetic valve that can be used with some embodiments;
- (4) FIG. 3A is a schematic view of a prosthetic heart valve as it is parachuted to a mitral valve opening;
- (5) FIG. 3B is a schematic view of the prosthetic heart valve of FIG. 3A just before entering the mitral valve opening;
- (6) FIG. 3C is a schematic view of the prosthetic heart valve of FIG. 3A after entering the mitral valve opening, as shown from the opposite side of the mitral valve opening;
- (7) FIG. 4 is a prosthetic heart valve with an anti-loop member according to an embodiment;
- (8) FIGS. 5A-5C are a sequence of views showing the prosthetic heart valve and anti-loop member of FIG. 4 as it is parachuted to a valve opening;
- (9) FIG. 5D is a view of the prosthetic heart valve and anti-loop member of FIG. 4 after entering the valve opening, as shown from the opposite side of the valve opening;
- (10) FIGS. 6A-6E are a sequence of views showing removal of the anti-loop member from the prosthetic heart valve of FIG. 4 as shown from the opposite side of the valve opening;
- (11) FIG. 7 is a perspective view of the heart valve and anti-loop member of FIG. 4 attached to a holder.

DETAILED DESCRIPTION

- (12) Disclosed herein are various embodiments of a prosthetic heart valve with anti-loop member for assisting in the delivery and implantation of a prosthetic heart valve at an implant site, and methods for preparing the prosthetic heart valve for such procedures. Embodiments of the prosthetic heart valve with anti-loop member herein are easy to use and simple in design.
- (13) The valve systems disclosed herein are particularly useful for avoiding suture looping during advancement of the prosthetic valve to the implant site as well as during final suturing of the valve at the native valve annulus. In procedures where commissure posts of the prosthetic valve point distally, for example in many mitral valve replacement procedures, the commissure posts point in the direction of valve advancement and may be more prone to suture looping or other entangling. In these cases, an anti-loop member according to embodiments disclosed herein deflects the pre-installed sutures away from the prosthetic valve. In some embodiments, the anti-loop member is pre-deployed without requiring any action by the surgeon or operating room staff and is ready for delivery to the native valve annulus upon removal of the packaging. Upon securement of the prosthetic heart valve to the native valve annulus, the anti-loop member can be easily removed from the heart valve without causing any damage to the valve or valve leaflets. In this fashion, ease of use can be maintained, while user error can be minimized. In addition, in some embodiments, the surgical team has improved visibility of the surgical site during the procedure.
- (14) With reference to FIG. 4, a prosthetic heart valve system **100** includes a prosthetic heart valve **102** and an anti-loop member **104**. The heart valve **102** has a base including an annular sewing ring **106** on an inflow side, and a plurality of commissure posts **108a**, **108b**, **108c** projecting generally axially in the outflow direction. The inflow side of the valve **102** is the proximal (e.g., accessible) side during implantation and the commissure posts **108** project distally toward the outflow side of

the valve **102**, defining the leading end of the valve during implantation.

(15) The heart valve **102** further includes a plurality of flexible leaflets **110** that are supported by and extend between the commissure posts **108**. The leaflets **110** provide the occluding surfaces of the valve **102**, and may be made of individual pieces of bovine pericardium, for example.

Alternatively, the leaflets **110** may be part of an entire xenograft, or homograft. In the former instance, natural porcine (pig) valves are particularly useful. Therefore it should be understood that the leaflets **110** may be formed of a variety of materials, none of which is limiting with respect to the present disclosure. In addition, there are preferably three such leaflets **110** corresponding to the three commissure posts **108**.

(16) Various constructions for the heart valve **102** are known, which may include metallic or plastic stent elements, a silicone or urethane insert for the sewing ring **106**, biocompatible fabric or cloth (e.g., polyester) covering around one or more of the elements. In a preferred embodiment, the heart valve **102** includes an internal metallic wireform (not shown) having an undulating shape with a plurality of arcuate cusps connected by the upstanding commissures. The wireform commissures provide internal structure for the commissure posts **108** of the valve, and are somewhat flexible so as to be able to flex or cantilever inward.

(17) The anti-loop member **104** is preferably a fine guide wire made of a flexible material such as a superelastic nitinol or other suitable material. Preferably, the guide wire is in the form of a coil and the material is such that the coil is not permanently bent or deformed after coiling. This permits the coil to be passed through the commissure tips during assembly without permanently deforming and permits easy removal from the commissure posts without pulling on the cloth and damaging the heart valve. In addition, the coil material is preferably rigid enough to retain its shape when coming in contact with sutures used to secure the heart valve to the heart valve annulus to prevent suture looping. In a preferred embodiment, the coil is shape set in a circular or otherwise coiled form before attaching it to the commissure tips so that the free end does not stick out of the coil at the outflow side.

(18) The anti-loop member **104** has a first end portion **116** and a second end portion **118**. The anti-loop member **104** is assembled to the prosthetic heart valve **102** by taking the free end **120** of the first end portion **116** and passing it through the covering or an attached loop (such as by a suture) at the tip of the first commissure post **108a**, then through the covering or loop at the tip of the second commissure post **108b** and through the covering or loop at the tip of the third commissure post **108c**. Preferably, the free end **120** continues to be fed to the first commissure post **108a** such that the anti-loop member **104** extends from the first commissure post **108** around the periphery of the heart valve to the second and third commissure posts **108b**, **108c** and back to the first commissure **108a**. If desired, the free end **120** of the first end portion **116** can continue to be passed through the commissures posts **108b**, **108c** consecutively. In the embodiment of FIG. 4, the anti-loop member passed through each commissure post twice before being passed through the sewing ring **106** to be engaged by a forceps (or other means) for removal after the heart valve has been placed or secured on the valve annulus. Preferably, the anti-loop member **104** passes through the sewing ring **106** at an inner diameter portion **107** of the sewing ring. This will permit easier removal of the anti-loop member after the heart valve is seated on the valve annulus.

(19) If the anti-loop member is coiled around the commissures twice, the inner coil may be attached on an inner side of the commissure posts while the outer coil may be on an outer side of the commissure posts. Alternatively, the coils may be adjacent each other, both on the outside, both on the inside, or other variations. It will be appreciated that the anti-loop member **104** can be assembled to the heart valve in the opposite direction also (e.g., through the sewing ring **6** first, then through the commissure posts).

(20) To prevent the free end of the second end portion **118** of the coil from scratching or damaging surrounding tissue, a small ball **130**, or other shape of protector, can be attached to it. The ball is small enough so that it does not impede pulling the coil through the commissures. A plastic ball can

be molded onto the free end of the coil. Alternatively, a metal ball may be formed by melting the free end of the coil so that nothing may fall off the free end. Other shapes may be used as long as the shape not only prevents the coil's free end from poking into the surrounding heart tissue but also does not impede pulling the coil through its attachment points on the commissures.

(21) With reference to FIGS. 5A-5D, the prosthetic heart valve **102** is shown in a sequence of views as it is parachuting to a valve opening **140** of the human heart. As is well known in the art, several sutures are passed through a valve annulus **142** and through the sewing ring **106**. Only one suture **144** is shown for clarity.

(22) As the heart valve **102** is parachuted to the valve annulus **142** (FIG. 5A), it is seen that the anti-loop member **104** is in position to deflect the suture **144** to a location outside the commissure posts **108** to prevent suture looping (FIG. 5B). Tilting of the heart valve **102** for easier entry into the valve opening can also be safely achieved without suture looping due to the location of the anti-loop member **104** (FIG. 5C). The suture **144** is deflected by the anti-loop member **104** to prevent it from looping inside the commissure post **108**. Once the heart valve **102** is fully seated against the valve annulus **142** (FIG. 5D, viewed from the opposite side of the valve opening), the surgeon is able to view the valve seating through the valve leaflets before and during tying of the suture knots. The presence of the anti-loop member **104** also prevents suture looping as the suture knots are being tied.

(23) Once the heart valve **102** is sufficiently secured to the valve annulus **142**, the anti-loop member **104** can be removed. In one embodiment (see FIG. 5C), the first end portion **116** of the anti-loop member **104** passes through the sewing ring **106** at a location next to a low point **148** of a cusp of one of the commissures **108**. Having the first end portion exit through the sewing ring at a distance away from the last commissure will reduce stress on the commissure during removal of the anti-loop member.

(24) With reference to FIGS. 6A-6E, a surgeon may grasp the first end portion **116** of the anti-loop member **104** with a forceps **150** at the inflow side of the valve annulus. Pulling on the anti-loop member will cause the second end portion **118** to unwind through the commissure posts **108** on the outflow side of the heart valve, and finally through the sewing ring **106**, releasing the anti-loop member from the heart valve. The first end portion of the anti-loop member can be provided with an indicator to alert the surgeon to grab the end of the coil. The indicator can be in vivid colors or other eye-catching device to contrast it from the environment to prevent it from being left behind after completion of valve implantation.

(25) In a further embodiment, the prosthetic heart valve system includes a valve holder and a handle. With reference to FIG. 7, the prosthetic heart valve **102** and anti-loop member **104** are secured to a valve holder **150** and a handle **152**. The holder includes a central disk portion **154** and three arms **156** equally spaced around and extending away from the disk portion **154**. Each arm **156** has a free end portion and a recess **160** provided in a top side of the free end portion. In the recess **160** is a pair of holes **162** through the arm to permit attachment of the holder to the heart valve **102** by a suture **164** passing through the holes. The recess also extends axially and has a deeper portion **166** to permit access for a cutting tool for cutting the suture.

(26) The holder also includes a central post **170** that protrudes axially in a proximal direction. The central post **170** has a threaded opening (not shown) to receive the handle **152**, which also has cooperative threading for attaching the handle to the valve holder. The first end portion **116** of the anti-loop member **104** is optionally connected to the holder, e.g., by tying down to an arm **156** of the holder **150**. Alternatively, the arm can be molded onto the free end of the coil, or other suitable means to secure the coil **104** to the holder **150**.

(27) As will be appreciated, the holder **150** can be removed from the heart valve by cutting the sutures **164**. The sutures are tied to the holder and will be removed with the holder. Similarly, in this embodiment, the anti-loop member **104** is connected to the holder and will be removed with the holder. Alternatively, the anti-loop member is not connected to the holder and can be removed

separately. After the heart valve is placed on the native valve annulus, the holder can be removed and the surgeon is provided a clear view to check on valve seating before and during tying of the suture knots, even when the anti-loop member is still present. The presence of the coil will prevent suture looping during the knot tying procedure. After all the suture knots are tied, the surgeon can easily pull the anti-loop member out by grabbing on the first end of the member.

(28) In other alternative embodiments, various different features from the different embodiments discussed above can also be combined in a single modified ring holder.

(29) For purposes of this description, certain aspects, advantages, and novel features of the embodiments of this disclosure are described herein. The disclosed methods, apparatus, and systems should not be construed as being limiting in any way. Instead, the present disclosure is directed toward all features and aspects of the various disclosed embodiments, alone and in various combinations and sub-combinations with one another. The methods, apparatus, and systems are not limited to any specific aspect or feature or combination thereof, nor do the disclosed embodiments require that any one or more specific advantages be present or problems be solved.

(30) Although the operations of some of the disclosed embodiments are described in a particular, sequential order for convenient presentation, it should be understood that this manner of description encompasses rearrangement, unless a particular ordering is required by specific language set forth below. For example, operations described sequentially can in some cases be rearranged or performed concurrently. Moreover, for the sake of simplicity, the attached figures may not show the various ways in which the disclosed methods can be used in conjunction with other methods. Additionally, the description sometimes uses terms like “provide” or “achieve” to describe the disclosed methods. These terms are high-level abstractions of the actual operations that are performed. The actual operations that correspond to these terms can vary depending on the particular implementation and are readily discernible by one of ordinary skill in the art.

(31) In view of the many possible embodiments to which the principles of the disclosure can be applied, it should be recognized that the illustrated embodiments are only preferred examples and should not be taken as limiting the scope of the disclosure. Rather, the scope of the disclosure is defined by the following claims.

Claims

1. A prosthetic heart valve system, comprising: a prosthetic heart valve having an inflow side and an outflow side, and a flow axis therethrough, the heart valve further comprising a base at the inflow side, a plurality of commissure posts extending from the base away from the inflow side and circumferentially spaced around the flow axis, and valve leaflets secured to the commissure posts to permit flow through the heart valve, each commissure post having a tip on the outflow side; and an anti-loop member having a first portion and a second portion, the first portion of the anti-loop member on the inflow side of the heart valve and the second portion of the anti-loop member on the outflow side of the heart valve; the second portion of the anti-loop member arranged to pass in a coiled form through a covering of fabric or cloth or an attached loop extending from the covering at the tip of each commissure post, and engaging at least one commissure post twice to form a coiled loop around all of the plurality of commissure posts, wherein the anti-loop member is a superelastic nitinol wire shape set in a coiled form, and wherein the second portion when assembled with the heart valve to prevent suture looping terminates in a free end located at the outflow side that is within and does not extend radially outward from the coiled loop, and wherein the coiled loop may be disengaged from the commissure post tips to release the anti-loop member from the heart valve by simply pulling on the first portion; wherein the anti-loop member comprises a material sufficiently flexible to be removed from the commissure posts without damaging the heart valve by pulling on the first end portion of the anti-loop member yet rigid enough to retain its shape when coming in contact with sutures used to secure the heart valve to a heart valve annulus.

2. The prosthetic heart valve system of claim 1, wherein the plurality of commissure posts is three or more commissure posts.
3. The prosthetic heart valve system of claim 1, wherein the anti-loop member is attached to a side of each commissure post facing away from the flow axis.
4. The prosthetic heart valve system of claim 1, wherein the anti-loop member loops around the plurality of commissure posts twice.
5. The prosthetic heart valve system of claim 4, wherein an outer loop of the anti-loop member is attached to a side of each commissure post facing away from the flow axis and an inner loop of the anti-loop member is inside the outer loop.
6. The prosthetic heart valve system of claim 1, further including a valve holder removably secured to the prosthetic heart valve wherein the first portion of the anti-loop member is secured to the valve holder such that removal of the valve holder from the heart valve also results in removal of the anti-loop member from the heart valve.
7. The prosthetic heart valve system of claim 6, wherein the valve holder has a central portion and three arms equally spaced around and extending away from the central portion, and the first portion of the anti-loop member is secured to one of the arms.
8. The prosthetic heart valve system of claim 1, wherein the free end of the second portion of the anti-loop member is located radially inside the periphery of the plurality of commissure posts.
9. The prosthetic heart valve system of claim 1, wherein the free end of the second portion of the anti-loop member is an enlarged portion shaped to prevent damage to surrounding tissue.
10. The prosthetic heart valve system of claim 9, wherein the enlarged portion is in the shape of a ball.
11. The prosthetic heart valve system of claim 1, wherein the base of the prosthetic heart valve comprises a sewing ring to engage a native valve annulus and the anti-loop member passes through the sewing ring.
12. The prosthetic heart valve system of claim 11, wherein the anti-loop member passes through the sewing ring adjacent an inner diameter of the sewing ring.
13. The prosthetic heart valve system of claim 12, wherein the anti-loop member extends from a tip of one commissure post and through the sewing ring at a location closer to an adjacent commissure post than the one commissure post.
14. A prosthetic heart valve system, comprising: a prosthetic heart valve having an inflow side and an outflow side, and a flow axis therethrough, the heart valve further comprising a base at the inflow side, a plurality of commissure posts extending from the base away from the inflow side and circumferentially spaced around the flow axis, and valve leaflets secured to the commissure posts to permit flow through the heart valve, each commissure post having a tip on the outflow side; an anti-loop member having a first portion and a second portion, the first portion of the anti-loop member on the inflow side of the heart valve and the second portion of the anti-loop member on the outflow side of the heart valve; the second portion of the anti-loop member arranged to pass in a coiled form through a covering of fabric or cloth or an attached loop extending from the covering at the tip of each commissure post, and engaging at least one commissure post twice to form a coiled loop around all of the plurality of commissure posts, wherein the anti-loop member is a superelastic nitinol wire shape set in a coiled form, and wherein the second portion when assembled with the heart valve to prevent suture looping terminates in a free end located at the outflow side that is within and does not extend radially outward from the coiled loop, and wherein the coiled loop may be disengaged from the commissure post tips to release the anti-loop member from the heart valve by simply pulling on the first portion; and a valve holder removably secured to the prosthetic heart valve; wherein the anti-loop member comprises a material sufficiently flexible to be removed from the commissure posts without damaging the heart valve by pulling on the first end portion of the anti-loop member yet rigid enough to retain its shape when coming in contact with sutures used to secure the heart valve to a heart valve annulus.

15. The prosthetic heart valve system of claim 14, wherein the first portion of the anti-loop member is secured to the valve holder such that removal of the valve holder from the heart valve also results in removal of the anti-loop member from the heart valve.
 16. The prosthetic heart valve system of claim 14, wherein the valve holder is secured to the prosthetic heart valve by sutures.
 17. The prosthetic heart valve system of claim 14, further comprising a handle removably attachable to the valve holder.
 18. The prosthetic heart valve system of claim 14, wherein the first portion of the anti-loop member comprises an indicator to alert a member of the surgical team to remove the anti-loop coil.
 19. The prosthetic heart valve system of claim 18, wherein the indicator is a contrasting color to a surrounding native environment when the heart valve is implanted.
 20. The prosthetic heart valve system of claim 14, wherein the free end of the second portion of the anti-loop member is an enlarged portion in the shape of a ball to prevent damage to surrounding tissue.
-