

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12385308
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Boundy; Tim J.

System and devices for adjustable door closure control

Abstract

Disclosed are systems and devices for controlling the closing of a door. A head unit is to be installed in a doorjamb, comprising a chamber filled at least in part with a shear thickening fluid. A piston is connected to a cap and configured to exert pressure against the shear thickening fluid in response to a force applied to the cap. The systems and devices provide an adjustable design that resists door slamming and aggressive closure, serving as a safety device as well as noise, damage and pet control around doors (preventing closure if desired). An install kit provides exact location, depth control and guide to place over the head unit to tap it into place with a hammer.

Inventors:	Boundy; Tim J. (Deer Park, IL)
Applicant:	Moshun, LLC (Oak Brook, IL)
Family ID:	69059888
Assignee:	Moshun, LLC (N/A, N/A)
Appl. No.:	17/555753
Filed:	December 20, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20220112756 A1	Apr. 14, 2022

Related U.S. Application Data

continuation parent-doc US 16502470 20190703 US 11866977 child-doc US 17555753
us-provisional-application US 62694762 20180706

Publication Classification

Int. Cl.: E05F3/04 (20060101); B23B47/28 (20060101); B23B49/00 (20060101); B23Q17/22 (20060101); E05F5/02 (20060101); F16F9/52 (20060101)

U.S. Cl.:

CPC E05F3/04 (20130101); B23B47/28 (20130101); B23B49/005 (20130101); B23Q17/2233 (20130101); E05F5/02 (20130101); F16F9/52 (20130101); E05Y2900/132 (20130101)

Field of Classification Search

CPC: E05F (3/04); E05F (5/02); B23B (47/28); B23B (49/005); B23Q (17/2233); F16F (9/52); E05Y (2900/132)

USPC: 16/82; 16/85; 188/130; 188/290-295; 267/64.11; 267/120

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
669762	12/1900	Peregrine	N/A	N/A
1041223	12/1911	Zuk	N/A	N/A
1700086	12/1928	Alonson	N/A	N/A
1704217	12/1928	Rosenthal	N/A	N/A
1730646	12/1928	Danner	N/A	N/A
1736175	12/1928	Rosenthal	N/A	N/A
1965806	12/1933	Riggins	N/A	N/A
2015989	12/1934	Bommer	N/A	N/A
2127327	12/1937	Millar	N/A	N/A
2695807	12/1953	Bissot	N/A	N/A
2740308	12/1955	Blanchard	N/A	N/A
2869913	12/1958	Schlaage	N/A	N/A
3284841	12/1965	Patriquin	N/A	N/A
3367454	12/1967	Scherer et al.	N/A	N/A
3400796	12/1967	Savins	N/A	N/A
3408683	12/1967	Zahn	N/A	N/A
3487494	12/1969	Baan	N/A	N/A
3537126	12/1969	Nakanshi	N/A	N/A
3548977	12/1969	Morgan	N/A	N/A
3952365	12/1975	Grisebach	N/A	N/A
3958673	12/1975	Alinquant et al.	N/A	N/A
3979790	12/1975	Chiarappa	N/A	N/A
4452437	12/1983	Lochner	N/A	N/A
4573238	12/1985	Phillips	N/A	N/A
4590639	12/1985	Fritsche	N/A	N/A
4658468	12/1986	Tillmann	N/A	N/A
4829628	12/1988	Vuksic	N/A	N/A
5078552	12/1991	Albel	N/A	N/A
5082317	12/1991	Delaney, Jr.	N/A	N/A
5152029	12/1991	Pai et al.	N/A	N/A
5172929	12/1991	Butsuen	N/A	N/A

5205015	12/1992	Huang	N/A	N/A
5222845	12/1992	Goldstein	N/A	N/A
5419013	12/1994	Hsiao	N/A	N/A
5507070	12/1995	Spyche, Jr. et al.	N/A	N/A
5529154	12/1995	Tanaka	N/A	N/A
5579874	12/1995	Jeffries et al.	N/A	N/A
5855040	12/1998	Lin	N/A	N/A
5924714	12/1998	Farris	N/A	N/A
6112368	12/1999	Luckett	N/A	N/A
6237959	12/2000	Hishon	N/A	N/A
6442795	12/2001	Chen	N/A	N/A
6634033	12/2002	Mizuno	N/A	N/A
6711856	12/2003	Hoffman	N/A	N/A
6799663	12/2003	Dubach	N/A	N/A
6824335	12/2003	Lynch	N/A	N/A
6854161	12/2004	Lee	N/A	N/A
6957807	12/2004	Zimmer	N/A	N/A
7234569	12/2006	Salice	267/209	E05F 5/006
7357231	12/2007	Kim et al.	N/A	N/A
7410154	12/2007	Lam et al.	N/A	N/A
7484914	12/2008	Weinstein	N/A	N/A
7584829	12/2008	Schmidt	N/A	N/A
7628257	12/2008	Lu	N/A	N/A
7825045	12/2009	Wagner	N/A	N/A
7845050	12/2009	Pyo	N/A	N/A
7861371	12/2010	Kim	16/85	E05F 5/10
7918167	12/2010	Tanielian	N/A	N/A
7975994	12/2010	Born	N/A	N/A
8104140	12/2011	Bassi	N/A	N/A
8123005	12/2011	Bantle	N/A	N/A
8127901	12/2011	Lu	N/A	N/A
8276497	12/2011	Hunn	N/A	N/A
8348028	12/2012	Zimmer et al.	N/A	N/A
8499908	12/2012	Barker	N/A	N/A
8657085	12/2013	Ogawa	N/A	N/A
8863356	12/2013	Bacchetti	N/A	N/A
8925695	12/2014	Rioja Calvo	N/A	N/A
8943652	12/2014	Bacchetti	N/A	N/A
8966712	12/2014	Yu	N/A	N/A
9127493	12/2014	Zimmer et al.	N/A	N/A
9152183	12/2014	Kurczewski	N/A	N/A
9217485	12/2014	Wu	N/A	N/A
9303709	12/2015	Manes	N/A	N/A
9360076	12/2015	Svara et al.	N/A	N/A
9410354	12/2015	Nakasone	N/A	N/A
9416570	12/2015	Colombo et al.	N/A	N/A
9453550	12/2015	Smith	N/A	N/A
9498690	12/2015	Lorentz, Ii	N/A	N/A
9534435	12/2016	Dora	N/A	N/A
9605462	12/2016	Bacchetti	N/A	N/A

9682605	12/2016	Ankney	N/A	N/A
9719285	12/2016	Nagl et al.	N/A	N/A
9777790	12/2016	Mizuno et al.	N/A	N/A
9890574	12/2017	Kruedener	N/A	N/A
9920563	12/2017	Löhken et al.	N/A	N/A
9970831	12/2017	Shih	N/A	N/A
10017082	12/2017	Zwaan	N/A	N/A
10041560	12/2017	Ankney	N/A	N/A
10047818	12/2017	Nakasone	N/A	N/A
10107352	12/2017	Grzesik et al.	N/A	N/A
10145162	12/2017	Liang et al.	N/A	N/A
10161173	12/2017	Kruedener	N/A	N/A
10221915	12/2018	Kull et al.	N/A	N/A
10246924	12/2018	Hopkins	N/A	N/A
10258146	12/2018	Hansen	N/A	N/A
10371097	12/2018	Sellinger	N/A	N/A
10428896	12/2018	Zimmer et al.	N/A	N/A
10443678	12/2018	Galindo Rosales	N/A	N/A
10462578	12/2018	Hoskins	N/A	N/A
10480281	12/2018	Al-Oayan	N/A	N/A
10480604	12/2018	Romano et al.	N/A	N/A
10557513	12/2019	Pecar et al.	N/A	N/A
10570935	12/2019	Koscielniak et al.	N/A	N/A
10580231	12/2019	Lin	N/A	N/A
10626651	12/2019	Chang	N/A	N/A
10633905	12/2019	Feng	N/A	N/A
10677309	12/2019	Ericksen et al.	N/A	N/A
10718144	12/2019	Wang et al.	N/A	N/A
10829975	12/2019	Wu	N/A	N/A
10837213	12/2019	Talpe	N/A	N/A
10858873	12/2019	Talpe	N/A	N/A
10865597	12/2019	Chen et al.	N/A	N/A
10920474	12/2020	Shinmura	N/A	N/A
10995813	12/2020	Yamashita et al.	N/A	N/A
11008794	12/2020	Chen	N/A	N/A
11041335	12/2020	Chen	N/A	N/A
11053722	12/2020	Teta et al.	N/A	N/A
11230869	12/2021	Weber	N/A	N/A
11261639	12/2021	Held	N/A	N/A
11268589	12/2021	Zimmer et al.	N/A	N/A
11274483	12/2021	Benedetti et al.	N/A	N/A
11344955	12/2021	Majer	N/A	N/A
11465218	12/2021	Degowske	N/A	N/A
11519476	12/2021	Gross et al.	N/A	N/A
11536344	12/2021	Kimishima et al.	N/A	N/A
11828100	12/2022	Benedetti et al.	N/A	N/A
11828308	12/2022	Lang et al.	N/A	N/A
11828309	12/2022	Lang et al.	N/A	N/A
11841065	12/2022	Boundy et al.	N/A	N/A

11866977	12/2023	Boundy	N/A	E05D 11/0009
12025206	12/2023	Boundy	N/A	N/A
2002/0010977	12/2001	Salice	N/A	N/A
2003/0155196	12/2002	Nishiyama	N/A	N/A
2003/0200623	12/2002	Hung	N/A	N/A
2003/0213663	12/2002	Salice	N/A	N/A
2004/0068833	12/2003	Sawa	N/A	N/A
2005/0034269	12/2004	Jinbo	N/A	N/A
2006/0207843	12/2005	Migli	N/A	N/A
2006/0278483	12/2005	Jiang	N/A	N/A
2007/0041800	12/2006	Santos	N/A	N/A
2007/0251052	12/2006	Pyo	N/A	N/A
2009/0028691	12/2008	Huang	N/A	N/A
2009/0119873	12/2008	Bassi	N/A	N/A
2009/0236783	12/2008	Doffing et al.	N/A	N/A
2009/0241287	12/2008	Reid	N/A	N/A
2009/0241289	12/2008	Choi et al.	N/A	N/A
2009/0272463	12/2008	Smith	N/A	N/A
2010/0066051	12/2009	Haugen	N/A	N/A
2010/0132161	12/2009	Vu	N/A	N/A
2010/0162521	12/2009	Pyo	N/A	N/A
2010/0170062	12/2009	Kim	N/A	N/A
2010/0287729	12/2009	Jin	N/A	N/A
2010/0319260	12/2009	Sawa	N/A	N/A
2011/0127706	12/2010	Sims et al.	N/A	N/A
2011/0253493	12/2010	Svara et al.	N/A	N/A
2011/0283478	12/2010	Berry	N/A	N/A
2012/0061194	12/2011	Yu	N/A	N/A
2012/0233810	12/2011	Salutzki	N/A	N/A
2013/0097805	12/2012	Bland	N/A	N/A
2014/0033476	12/2013	Bacchetti	N/A	N/A
2014/0319850	12/2013	Berger	N/A	N/A
2014/0352111	12/2013	Ng	N/A	N/A
2015/0040998	12/2014	Gilstad	N/A	N/A
2016/0177611	12/2015	Rissone	N/A	N/A
2016/0215552	12/2015	Löhken	N/A	F16F 9/483
2016/0238100	12/2015	Smith	N/A	N/A
2016/0305156	12/2015	Kamody	N/A	N/A
2017/0037669	12/2016	Kruedener	N/A	N/A
2017/0096850	12/2016	Hopkins	N/A	N/A
2017/0138433	12/2016	Wang et al.	N/A	N/A
2017/0210458	12/2016	Tothill	N/A	N/A
2017/0226682	12/2016	Duckworth	N/A	N/A
2017/0304057	12/2016	Bichler	N/A	N/A
2017/0350466	12/2016	Böhrer et al.	N/A	N/A
2018/0010614	12/2017	Sellinger	N/A	N/A
2018/0266512	12/2017	Zimmer	N/A	N/A
2018/0328445	12/2017	Gilbert	N/A	N/A
2018/0355945	12/2017	De Kock	N/A	N/A

2019/0024748	12/2018	Rioja Iribarren	N/A	N/A
2019/0040667	12/2018	Feng	N/A	N/A
2019/0128362	12/2018	Naserimojarad	N/A	N/A
2019/0330903	12/2018	Talpe	N/A	N/A
2019/0371090	12/2018	Lin	N/A	N/A
2019/0390496	12/2018	Bacchetti	N/A	N/A
2020/0238780	12/2019	Dhaens	N/A	N/A
2020/0240190	12/2019	Held	N/A	N/A
2020/0299995	12/2019	Eolckhoff	N/A	N/A
2020/0332581	12/2019	Balbo di Vinadio et al.	N/A	N/A
2020/0408019	12/2019	Vos	N/A	N/A
2021/0180381	12/2020	Wu	N/A	N/A
2022/0010592	12/2021	Kirk	N/A	N/A
2023/0039706	12/2022	Enders et al.	N/A	N/A
2023/0123139	12/2022	Talpe	N/A	N/A
2023/0146774	12/2022	Talpe	N/A	N/A
2023/0295968	12/2022	Lee	N/A	N/A
2023/0304342	12/2022	Boundy et al.	N/A	N/A
2023/0304346	12/2022	Boundy et al.	N/A	N/A
2023/0340823	12/2022	Buchalo et al.	N/A	N/A
2023/0373014	12/2022	Block	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
107083886	12/2016	CN	N/A
210087086	12/2019	CN	N/A
202006006422	12/2005	DE	N/A
202006011846	12/2006	DE	N/A
102008014329	12/2008	DE	N/A
2589152	12/2020	GB	N/A
1998088899	12/1997	JP	N/A
H10331516	12/1997	JP	N/A
2003-266222	12/2002	JP	N/A
2004036885	12/2003	JP	N/A
2004-353712	12/2003	JP	N/A
2009-531631	12/2008	JP	N/A
2014-118303	12/2013	JP	N/A
200165472	12/1999	KR	N/A
10-0337469	12/2001	KR	N/A
200357306	12/2003	KR	N/A
100534373	12/2004	KR	N/A
20-2004-0018600	12/2005	KR	N/A
20070014713	12/2006	KR	N/A
100777202	12/2006	KR	N/A
20170137390	12/2016	KR	N/A
102117780	12/2019	KR	N/A
20220043582	12/2021	KR	N/A
2007/116273	12/2006	WO	N/A

2015/132254	12/2014	WO	N/A
2020103458	12/2019	WO	N/A

OTHER PUBLICATIONS

Advisory Action, U.S. Appl. No. 17/570,504, dated Aug. 28, 2023 (3 pages). cited by applicant
United States Patent and Trademark, "Non-Final Office Action", issued in connection to U.S. Appl. No. 18/188,848, mailed Sep. 9, 2024, 10 pages. cited by applicant
United States Patent and Trademark, "Non-Final Office Action", issued in connection to U.S. Appl. No. 17/570,515, mailed Sep. 17, 2024, 7 pages. cited by applicant
United States Patent and Trademark, "Non-Final Office Action", issued in connection to U.S. Appl. No. 18/188,852, mailed Sep. 17, 2024, 13 pages. cited by applicant
Notification of Transmittal of the International Search Report and the Written Opinion of the International Searching Authority, or the Declaration, PCT/US2019/040533; Mailed on Jul. 4, 2022 (16 pages). cited by applicant
Non-Final Office Action, U.S. Appl. No. 17/570,504, dated Feb. 2, 2023 (8 pages). cited by applicant
Non-Final Office Action, U.S. Appl. No. 17/570,509, dated Jan. 5, 2023 (7 pages). cited by applicant
Non-Final Office Action, U.S. Appl. No. 18/188,853 dated Sep. 20, 2024 (56 pages). cited by applicant
Non-Final Office Action, U.S. Appl. No. 18/188,861 dated Sep. 20, 2024 (57 pages). cited by applicant
Non-Final Office Action, U.S. Appl. No. 18/188,859 dated Sep. 24, 2024 (58 pages). cited by applicant
Non-Final Office Action, U.S. Appl. No. 17/570,509 dated Jul. 18, 2023 (9 pages). cited by applicant
Non-Final Office Action, U.S. Appl. No. 17/555,738, dated Aug. 9, 2024 (69 pages). cited by applicant
Final Office Action, U.S. Appl. No. 17/570,504, dated Apr. 5, 2023 (13 pages). cited by applicant
Final Office Action, U.S. Appl. No. 17/570,509, dated Apr. 6, 2023 (11 pages). cited by applicant
Notification of Transmittal of the International Search Report and the Written Opinion of the International Searching Authority, or the Declaration, PCT/US23/16082; dated Aug. 24, 2023 (20 pagers). cited by applicant
Non-Final Office Action, U.S. Appl. No. 16/502,470, dated Aug. 23, 2023 (22 pages). cited by applicant
Notification of Transmittal of the International Search Report and the Written Opinion of the International Searching Authority, or the Declaration, PCT/US2019/040533, mailed Oct. 1, 2019 (11 pages). cited by applicant
United States Patent and Trademark Office, "Final Office Action", issued in connection with U.S. Appl. No. 17/555,738, dated Feb. 14, 2025, 38 pages. cited by applicant
United States Patent and Trademark Office, "Final Office Action", issue in connection with U.S. Appl. No. 18/188,848, dated Mar. 11, 2025, 25 pages. cited by applicant
United States Patent and Trademark Office, "Final Office Action", issue in connection with U.S. Appl. No. 18/188,859, dated Apr. 4, 2025, 26 pages. cited by applicant
United States Patent and Trademark Office, "Final Office Action", issue in connection with U.S. Appl. No. 18/188,861, dated Apr. 9, 2025, 31 pages. cited by applicant
United States Patent and Trademark Office, "Non-Final Office Action", issue in connection with U.S. Appl. No. 18/188,852, dated Apr. 10, 2025, 12 pages. cited by applicant

Background/Summary

RELATED APPLICATIONS (1) The present application is a continuation and claims the benefit of, and priority to, U.S. patent application Ser. No. 16/502,470, filed Jul. 3, 2019, and titled “Systems and Devices for Adjustable Door Closure Control,” which claims the benefit of, and priority to, U.S. Provisional Application Ser. No. 62/694,762, filed Jul. 6, 2018, and titled “Adjustable Door Jamb Side Damper/Slam Control/Closure Control Device.” The complete subject matter and contents of Application Ser. Nos. 62/694,762 and 16/502,470 are incorporated herein by reference in their entirety.

BACKGROUND

(1) The slamming of a door can cause many problems. For instance, there is the risk that the door could be slammed on a person's fingers—often the fingers of a child. Additionally, slamming a door may result in a person or a pet being locked in a room. Moreover, nobody enjoys the loud sound of a slammed door. Therefore, there is a need for a device that can solve these problems.

(2) Pressure at a doorjamb is extremely high. The ability to stop and/or control a forceful door closure with a device that allows normal closure when shut at gentle speeds, with the added benefit of being installed discretely in the jamb (i.e. in a small device barely visible when the door is closed) has not been accomplished before.

SUMMARY OF THE INVENTION

(3) Certain embodiments of the present technology include a device that discretely controls a door slam and the closure speed of a door as well as provide a lock out so that the door will not close. The device is designed to intelligently react (e.g., with the ability to respond to varying situations and/or inputs by adjusting its' state or action) to a slam and/or aggressive door closure, yet does not hinder door closure when the door is closed slowly and more normally. The device is small, easily installed and, through the use of engineered materials (e.g., a smart, shear thickening fluid that reacts to forces applied to it, such as engineered polymeric compositions), reacts accordingly to the speed and pressure of a door closure. Thus, the reaction from the engineered material effectively responds to the user input intelligently. Accordingly, higher pressure and/or speed of the door swing results in more resistance by the device to closure, while lighter pressure and/or slower speed results in a more normal door closing experience. Also, adjustability of the device allows for more resistance more quickly as well as full lock out capability, such that the door will not be able to close.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a cross-sectional side view of an example unit according to an embodiment of the present invention.

(2) FIG. 2 is a cross-sectional top view of an example head unit and strike installed in a doorjamb and door, respectively, according to an embodiment of the present invention.

(3) FIG. 3 is an isometric view of an example rebound shim with slots according to an embodiment of the present invention.

(4) FIGS. 4A-4C are isometric views of an example rebound guide plug according to an

embodiment of the present invention.

(5) FIG. 5 is an isometric view of an example shear thickening fluid piston head with slots according to an embodiment of the present invention.

(6) FIG. 6 is an isometric view of an example install guide according to an embodiment of the present invention.

(7) FIG. 7 shows a cutaway view of the install guide of FIG. 6 and a drill sleeve.

(8) FIG. 8 is a cross-sectional top view of the install guide of FIG. 6 in a doorjamb according to an embodiment of the present invention.

(9) The foregoing summary, as well as the following detailed description of certain embodiments of the present invention(s), will be better understood when read in conjunction with the appended drawings. For the purpose of illustrating the invention(s), there is shown in the drawings, certain embodiments. It should be understood, however, that the present invention(s) is not limited to the arrangements and instrumentality shown in the attached drawings.

DETAILED DESCRIPTION OF THE INVENTION

(10) In some examples of the disclosed system, a head unit **100** is defined as a generally cylindrical device as shown in FIG. 1, with adjustable valving filled to a specific volume within a channel **15** with a shear thickening fluid (or dilatant fluid), the device assembled to resist leakage or disassembly. In operation, the system has at least two parts—the head unit **100** (shown in FIG. 1) and a strike **14** (shown in FIG. 2).

(11) The head unit **100** is installed in, by way of example, a hole with a diameter of 15/16" and 3" deep that is drilled into the jamb side of the door above or below, for example, the middle hinge. This effectively leaves a blind 3" hole with enough framing support to carry the pressure of the door closure. The head unit **100** can be installed with an install kit including an install tool or guide **20**, disclosed with respect to FIGS. 6 through 8. As shown in FIG. 1, the strike **14** is installed into, by way of example, a hole with a diameter of 15/16" and 1/2" deep, which is drilled into the door edge (e.g., the jamb side) to provide a contact point for a plunger cap **3** of the head unit **100**, as shown in FIG. 2.

(12) As disclosed herein, shear thickening fluid, provides the "brains" that allow a slotted piston head **9** with an adjustable shim stack style valve to close onto the piston head **9** resulting in a controlled close. Shear thickening fluid (or dilatant material) is a Non-Newtonian fluid that stiffens when acted upon by pressure and/or speed. For example, the greater the speed and/or pressure, the stiffer the fluid becomes. When the speed and/or pressure is light, the fluid is flowable. When the speed and/or pressure is higher, it begins to act more like a solid. These phenomena combined with adjustable and accurate valving allows the desired reaction in preventing unwanted door slamming, preventing loud door closures and door vibrations upon closure (e.g., since the plunger cap **3** applies a slight back pressure to the door edge).

(13) Example components of an embodiment of the present technology are as follows: The Head Unit or Adjustable Assembly **100** (shown in FIG. 1) The components of the Head Unit **100** are as follows: Hydraulic Chamber (**1**) (shown in FIG. 1) Jamb Collar (**2**) (shown in FIGS. 1 and 5) Plunger Cap (**3**) (shown in FIG. 1) Plunger Bushing One Piece (**4**) (shown in FIG. 1) Shear Thickening Fluid Plunger (**5**) (shown in FIG. 1) Rebound Shim (**6**) with Slots (**18**) (shown in FIGS. 1 and 3) Rebound Guide Plug (**7**) (shown in FIGS. 1 and 4A-4C) Spring (**8**) (shown in FIG. 1) Shear Thickening Fluid Piston Head (**9**) with Slots (**19**) (shown in FIGS. 1 and 5) Hydraulic Chamber O-Ring (**10**) (shown in FIG. 1) Plunger Rod O-Ring (**11**) (shown in FIG. 1) Shear Thickening Fluid Piston Slots (Piston Head) O-Ring (**12**) (shown in FIG. 1) Retaining Ring (**13**) (shown in FIG. 1) The system also includes a Strike (**14**) (shown in FIG. 2) and Shear Thickening Fluid (**15**) (shown in FIG. 1).

Relationship Between the Components:

(14) As shown in FIG. 1, a plunger **5** is inserted, (non-flange end) through, by way of example, a 0.25" hole in a plunger bushing one piece **4**. A spring **8** is inserted into a larger diameter cavity in

the plunger bushing one piece **4**. The plunger cap **3** is inserted onto the non-flange end of the plunger **5** with the spring **8** settling into a cavity of the plunger cap **3**. The piston head **9** is placed on the flange side of the plunger **5**, and the rebound guide plug **7** is inserted into the drilled hole in the flange end of the plunger **5**. This whole sub-assembly is then pressed together and the rebound guide plug **7** and plunger **5**, and plunger **5** and plunger cap **3** engage at press-fit tolerance interfaces to become assembled. A retaining ring **13** is placed onto an upper groove of the plunger bushing one piece **4** closest to plunger cap **3**, a hydraulic chamber O-ring **10** is placed into a lower groove of the plunger bushing one piece **4** closest to the piston head **9**, and a piston slot O-ring **12** is placed onto a groove in piston head **9**. This resulting device is hereafter referred to as the Subassembly.

(15) The hydraulic chamber **1** is filled with shear thickening fluid **15**. By way of example only, approximately 7.5 grams of the shear thickening fluid **15** may be used. The volume that contains the shear thickening fluid **15** is hereinafter referred to as the Hydro Chamber.

(16) The Subassembly can then be inserted into the Hydro Chamber vertically. The retaining ring **13** is squeezed to allow it to enter the Hydro Chamber, and then the Subassembly is pressed in until retaining ring **13** snaps into place into a groove in the interior of the hydraulic chamber.

(17) The jamb collar **2** is then placed on the plunger bushing one piece **4** aligning the tabs on jamb collar **2** with the recesses on the hydraulic chamber **1** and pressed in place.

(18) The resulting device is the head unit **100** and it is a permanent assembly.

(19) Once assembled, the Head Unit **100** can be lightly hammered into a drilled hole in the jamb side of the door, such as by employing an install guide **20**, which is discussed further with respect to FIGS. **6** through **8**.

(20) The strike **14** (shown in FIG. **2**) can be lightly hammered into a drilled hole on the door edge side. Drilling of this hole is also done by use of the install guide **20**. However, in some examples, the plunger cap **3** can contact the door directly without the use of a strike while retaining the benefits of the systems and devices disclosed herein. Additionally or alternatively, a strike can be configured with a recessed cavity rather than a flat surface, such that the plunger cap **3** is inserted into the cavity before making contact with the strike. In some examples, a strike may be a plate on the surface of the door edge opposite the plunger cap **3**.

(21) The Operation of the Head Unit **100** and Strike **14**

(22) As shown in FIG. **2**, the head unit **100** is inserted into a hole drilled into the jamb side by tapping (lightly hammering) the head unit **100** into the cavity with the install kit. The strike **14** is inserted into the door edge by tapping (lightly hammering) the strike **14** into place in the drilled hole. When the door is closed, the plunger cap **3** of the head unit **100** contacts the edge of the door, such as at the strike **14**, which depresses the plunger cap **3** such that the plunger cap **3** pushes against the plunger **5** and spring **8** and such that plunger **5** is pushed through plunger bushing **4**. That action leads to piston head **9** and shim **6** on guide plug **7** moving with respect to fluid **15**. Fluid **15** reacts to the force and speed of that impact and stiffens up accordingly or remains flowable depending on the force applied.

(23) In some examples, shim **6** has one or more slots **18** that generally match one or more slots **19** through piston head **9** in one or both of size and/or shape. The ability of the fluid **15** to resist the force of the depressed plunger cap **3** (and thus control the speed and/or force of the door closure) depends on the alignment of the slots **18** of the shim **6** and the slots **19** of the piston head **9**. Piston head **9** has a stop built into it such that guide plug **7** contacts in both the left and right rotations to adjust the amount of fluid **15** compression. For example, if the slots **18** on shim **6** have been rotated to the left (e.g., by the user via a simple turn of plunger cap **3**), then the slots **18** on shim **6** will not align with the slots **19** in piston head **9** and, thus, the fluid **15** will resist the movement of the piston **5** and the plunger cap **3**, and the plunger cap **3** will not depress and the door will not close (i.e. partially, completely, and/or more slowly, depending on the resulting alignment).

(24) If, however, the slots **18** on the shim **6** have been rotated to the right, and are aligned with the slots **19** on the piston head **9**, then the fluid **15** flows more easily between the shim **6** and piston

head **9** and does not resist movement of the plunger **5** and cap **3** as much. Thus, the compression of the fluid **15** is at its lightest setting. The reactivity to force of fluid **15**, however, still lets the device control the speed of closure due to the stiffening effect of the material make-up (e.g., a polymeric material) of the fluid **15**. Fluid **15** also serves to control, in combination with the selection of the spring rate of spring **8**, the return force from cap **3** so that it does not push the door open or allow the door to aggressively bounce back at the user. In some examples, the force on the door from cap **3** can be adjusted to a desired level to provide for a controlled opening by gently pushing the door open, such as by unlatching the door (either remotely, electronically, manually or otherwise).

(25) The shim **6** is rotatable such as by a user (and thus the position of the slots **18** in the shim **6** with respect to the slots **19** in the piston head **9**) by rotating the plunger cap **3**. The plunger cap **3** is tightly fitted to the plunger **5**, which is tightly fitted to the guide plug **7**, which is tightly fitted to the shim **6**. Therefore, rotation of the plunger cap **3** causes the plunger **5** to rotate, which in turn causes the guide plug **7** to rotate, which in turn causes the shim **6** to rotate, allowing adjustment of the amount of compression (i.e. resistance) experienced during closure.

(26) As disclosed with respect to the figures, the slots **19** of piston head **9** are pitched with the wider part of the opening facing the fluid **15** and the narrower part on the backside of the piston head **9** such that the slots **19** are substantially “V” shaped. The shear thickening fluid **15** stack up (stiffen) as the piston **5** pushes through the fluid **15** upon the closing/slamming of a door closure. In some disclosed examples, the shear thickening fluid **15**, as engineered, has nanoparticles of a specific dimension that are mixed in a non-toxic carrier fluid or solvent. Force applied to the shear thickening fluid **15** results in these nanoparticles stacking up, thus stiffening and acting more like a solid than a flowable liquid. Examples of shear thickening fluid are disclosed in U.S. Pat. No. 7,825,045, which is incorporated herein in its entirety by reference.

(27) The particles of shear thickening fluid **15** may be, by way of example, oxides, calcium carbonate, synthetically occurring minerals, naturally occurring minerals, polymers, or a mixture thereof. The particles may also be, by way of example, SiO₂, polystyrene, or polymethylmethacrylate. The solvent may be, by way of example, water, which may contain salts, surfactants, and/or polymers. The solvent may also be, for example, ethylene glycol, polyethylene glycol, ethanol, silicon oils, phenyltrimethicone or a mixture thereof. In some examples, the particles may have an average diameter size that is less than 1 millimeter, and may have an average diameter size of less than 100 microns. By way of example, the shear thickening fluid **15** may be made of silica particles suspended in polyethylene glycol. By further way of example, silica particles may suspended in the polyethylene glycol at a volume fraction of approximately 0.57. The silica particles may have an average particle diameter of approximately 446 nm. The fluid may have a shear thickening transition at a shear rate of approximately 102-103 s⁻¹.

(28) Again, a simple rotation of the plunger cap **3** allows the user to control the valve sensitivity based on the feel they want when closing the door. Turning left to the stop locks out the device so that that door cannot be closed at all—even gently—because the shim **6** attached to the piston head **9** completely blocks the slots **19** of the piston head **9** from allowing any shear thickening fluid to pass through. Turning the plunger cap **3** to the right allows the device to let the door be closed normally (i.e., gently closed and not slammed) because the slots **18** on the shim **6** are generally aligned with the slots **19** on the piston head **9**, allowing the fluid to pass through. However, the fluid still reacts to speed and pressure. Therefore, the system still controls the door closing to resist a slam.

(29) The shim **6** is held in place by a cylindrical stainless steel rebound plug **7**, with a flat section (shown in FIGS. 4A-4C) that fits into a “D” shape in the shim **6** (shown in FIG. 3), keeping it in position for the user adjustment and alignment of its slots **18** with the piston head **9** slots **19**. The shim **6** floats on the rebound plug **7**, such that the shim **6** is not in a fixed position in the direction of the plunger **5**. Thus, during door closure, the shim **6** presses against the piston head **9** when the shear thickening fluid **15** is being compressed, and pulls away from the piston head **9** on rebound

of the door, allowing the piston head **9** slots **19** to be fully open. The piston head **9** is attached to the plunger **5** that is attached to the plunger cap **3** (the plunger cap **3** is the component that contacts the strike **14** on the door edge). The spring **8** returns the plunger **5** to its fully extended position with the combination of the selected spring rate and the engineered shear thickening fluid **15** controlling the rate of return, thus not allowing a spring-back effect. The plunger bushing one piece **4** serves as a guide for the plunger **5** and the plunger cap **3**, and as a stop for the spring **8**. The plunger bushing one piece **4** has one or more grooves for at least O-rings **10** and **11** used to seal the hydraulic chamber **1** as well as the plunger rod/bushing interface.

(30) With reference to FIG. **1**, the jamb collar **2** is slip fitted onto the outermost section of the one-piece plunger bushing **4** that protrudes from the hydraulic chamber **1**. The exterior or “face” of jamb collar **2** becomes flush with the jamb edge when the head unit **100** is inserted and tapped (lightly hammered) into the drilled hole in the doorjamb that receives the head unit **100**.

(31) This jamb collar **2** component function is three-fold. First, the jamb collar **2** holds the device securely in the doorjamb. Second, being slip fit on the bushing **4** gives the remainder of the device that is inside the doorjamb framing the ability to be disconnected from the doorjamb itself (because it is free to move slightly fore-aft inside the jamb collar), thus not pulling on the jamb millwork and stressing/flexing the jamb and hinges. And third, the jamb collar **2** is a finished face to the drilled hole where the head unit **100** is inserted.

(32) When the door closes, the plunger cap **3** (jamb side) contacts the strike **14** (door edge side) and functions as described above. The strike **14** may be manufactured from one or more engineered materials, such as polymers and/or thermoplastics with high stiffness and stability and low friction. In some examples, polyoxymethylene (such as Delrin or Acetyl), due to its hard, tough composition combined with a lubricity function, is a suitable material for a strike **14**. For example, the composition allows the plunger cap **3** to contact and slide against the strike **14**, yet without catching or sticking to the surface during door closure.

(33) Thus, as explained herein, the disclosed technology provides a way to control door slamming and closure. Advantageously, it can protect fingers from door slams (toddlers, young children), prevent unwanted aggressive door closures such as those done by teenagers or adults hastily closing doors, and prevent wind driven door slams. It can prevent a door from closing on pets, toddlers, or the elderly, who may have a tendency to accidentally close a door, locking themselves in a room.

(34) This can all be accomplished by the very small head unit and/or strike device, which are installed into the hinge side of the doorjamb and door edge, respectively.

(35) Below is a list of non-limiting examples of materials and/or manufacturing techniques from which certain components of the disclosed technology can be made. 1. Hydraulic Chamber—CNC machined from aluminum 2. Jamb Collar—Molded from Delrin (Acetyl) or CNC from aluminum 3. Plunger Cap—CNC from Stainless Steel 4. Plunger Bushing One Piece—Molded from Delrin (Acetyl) or CNC machined from Delrin (Acetyl) 5. Shear Thickening Fluid Plunger—CNC Machined from Stainless Steel 6. Rebound Shim—Stamped from Delrin (Acetyl) or Molded from Delrin (Acetyl) 7. Rebound Guide Plug—CNC Machined from Stainless Steel 9. Shear Thickening Fluid Piston Slots (Piston Head)—Molded from PEEK 14. Strike—Molded from Delrin (Acetyl)

The Structure and Operation of the Install Kit/Guide

(36) The disclosed technology also includes an installation kit, shown in FIGS. **6** through **8**, which can be used to install the head unit **100** and/or strike **14** into a jamb and door edge, respectively. The install tool assists in exactly locating the position of both the head unit **100** on the jamb and the strike **14** on the jamb side door edge, as well as controlling the depth of the drilled cavities into which the head unit **100** and strike **14** are installed.

(37) The install kit includes an install guide **20** (shown in FIGS. **6** through **8** and which can be molded from materials such as Delrin/Acetyl), a drill bit **30** (shown in FIGS. **7** and **8**) (alternative bits can also be employed), and the drill bit **30** bushing can be revised to fit alternative bits), a drill

bit bushing **40** (which can be molded or CNC machined from materials such as Delrin (Acetyl)), a drill sleeve **50** (which can be CNC machined from PVC Rod or Delrin Rod), and/or a locking collar **60** (shown in FIG. 8).

(38) Using the install guide **20**, a user can drill the two holes required for the head unit **100** and the strike **14** and then insert the head unit **100** into the jamb and insert the strike **14** into the jamb side of the door. A user can then adjust the head unit **100** as desired by turning plunger cap **3** left or right or in between as desired to control door closure and react to speed and pressure of closure. At lower speed and pressure, the closing door meets less resistance from the head unit **100** and the door closes easily, whereas at higher speed and pressure the head unit **100** stiffens up and controls the slam.

(39) In operation, the install kit is used as follows. To drill a hole for the head unit **100** in the doorjamb, a screw is removed from a hinge and placed into a screw slot in the guide **20** and tightened back up in the hinge screw hole with the tool/guide **20** held tightly to the edge of the doorjamb stop to stabilize the guide **20** on the jamb and locate the hole to be drilled for the head unit **100**. The bushing **40** is placed on the bit **30** and held in place by the collar **60**, which is tightened with a set screw on the collar **60**. The install kit can come with bushing **40** and collar **60** already installed on bit **30**. This is called the Drill Bit Assembly. Using a power drill with the Drill Bit Assembly installed, the user can drill into the jamb edge through, by way of example, an approximately 0.950 inch hole in the guide **20**. The assembly of the drill bit **30**, guide **20**, collar **60**, and bushing **40** is shown in FIG. 8. When the Drill Bit Assembly's drilling is stopped by the flange on the bushing **40** contacting the top of the guide **20**, the Head Unit hole drilling is complete. The drilling process for the doorjamb using the guide **20** is illustrated in FIG. 8. The guide **20** is then removed from the jamb by removing the screw holding it in place.

(40) In some examples, the screw from the matching location on the other half of the hinge on the door edge side is removed and the guide **20** is centered on the door edge and the screw is used to secure the guide **20** to the door edge. Drill sleeve **50** can then be put onto the drill (from the cutting side) and slid up until it contacts the flange on the bushing **40**. The process of drilling into the door edge is then similar to that described in drilling the jamb side for the head unit **100**, however the drill sleeve **50** will now contact the guide **20** when the drilling is complete, creating a, for example, 1/2" cavity in the door edge for the strike to be installed.

(41) The head unit **100** is now pushed into the hole in the jamb and the blind hole in the bottom of the guide **20** is placed over the plunger cap **3** of the head unit **100**. The head unit **100** is then lightly hammered into the jamb by tapping on the most raised portion of the guide **20**. When completed, the head unit jamb collar **2** is flush with the jamb and the head unit **100** is securely installed in the doorjamb. The strike is then lightly hammered into the cavity on the door edge side, securing it in place. This install guide **20** assists in aligning the drilled holes on the door edge and on the jamb with each other when the door is closed, such that the head unit **100** and the strike **14** line up with each other when installed. The install guide **20** also helps in making sure that the depth of the drilled holes is correct so that the head unit **100** is level and at the corrected depth when installed and that the strike **14** is level and at the correct depth when installed. In an alternate embodiment, the strike **14** can be installed in the jamb and the head unit **100** can be installed in the door edge.

(42) It is to be understood that the invention is not limited in its application to the details of construction and the arrangement of the components set forth in the description or illustrated in the drawings. The invention is capable of other embodiments and of being practiced or being carried out in various ways. Also, it is to be understood that the phraseology and terminology used herein are for the purpose of description and should not be regarded as limiting. The use of "including" and "comprising" and variations thereof is meant to encompass the items listed thereafter and equivalents thereof as well as additional items and equivalents thereof.

(43) While various spatial and directional terms, such as top, bottom, lower, mid, lateral, horizontal, vertical, front and the like may be used to describe embodiments of the present

invention, it is understood that such terms are merely used with respect to the orientations shown in the drawings. The orientations may be inverted, rotated, or otherwise changed, such that an upper portion is a lower portion, and vice versa, horizontal becomes vertical, and the like.

(44) Variations and modifications of the foregoing are within the scope of the present invention. It is understood that the invention disclosed and defined herein extends to all alternative combinations of two or more of the individual features mentioned or evident from the text and/or drawings. All of these different combinations constitute various alternative aspects of the present invention.

Claims

1. A device for controlling the motion of an object, comprising: a head unit that includes a chamber filled at least in part with a shear thickening fluid; a plunger in the head unit that is connected to a cap and a piston head, the piston head having at least one slot and being positioned in the chamber of the head unit; a shim that includes a D-shaped hole and at least one slot; and a plug having a D-shaped portion that is received in the D-shaped hole of the shim such that the shim does not rotate with respect to the plug and an end portion that is connected to the plunger; wherein the piston head and shim are configured to both move axially in the chamber with respect to the shear thickening fluid in response to a force applied to the cap by an object and wherein the shim is configured to be rotated with respect to the piston head.
2. The device of claim 1, wherein the at least one slot is located between the D-shaped hole and an outer edge of the shim.
3. The device of claim 1, wherein the piston head receives a portion of the plunger and engages a flange on the plunger.
4. The device of claim 1, wherein the plunger, plug, and shim are rotatable with respect to the piston head.
5. The device of claim 1, wherein the shim is axially movable along the D-shaped portion of the plug and with respect to the piston head and contacts the piston head when the piston head is caused to move axially in the chamber with respect to the shear thickening fluid in response to a force applied to the cap.
6. The device of claim 1, wherein the plug includes a base to which the D-shaped portion is connected, the based being configured to resistably engage the shim.
7. The device of claim 1, wherein a portion of the D-shaped portion of the plug is received in the piston head and is rotatable with respect to the piston head.
8. The device of claim 7, wherein the piston head has a first stop that prevents the D-shaped portion from being rotated beyond a first point in a first direction and a second stop that prevents the D-shaped portion from being rotated beyond a second point in a second direction.
9. The device of claim 1, wherein the at least one slot of the piston head is pitched such that a wider opening faces the shear thickening fluid and a narrower opening is on a backside of the piston head.
10. The device of claim 1, wherein the at least one slot of the shim has an opening shape and size approximately equal to an opening shape and size of the at least one slot of the of the piston head.
11. The device of claim 1, wherein rotation of the rebound shim to a first position with respect to the piston head substantially aligns the at least one slot of the rebound shim with the at least one slot of the piston head, and rotation of the rebound shim to a second position with respect to the piston head substantially misaligns the at least one slot of the rebound shim with the at least one slot of the of the piston head.
12. A device for controlling the motion of an object, comprising: a head unit that includes a chamber filled at least in part with a shear thickening fluid; a plunger in the head unit that is connected to a cap, a bushing and a spring in the head unit, wherein the spring is configured to provide mechanical resistance between the cap and the bushing in response to a force applied to the

cap; a piston head connected to the plunger and positioned in the chamber of the head unit, the piston head having at least one slot; a shim that includes a D-shaped hole and at least one slot; and a plug having a D-shaped portion that is received in the D-shaped hole of the shim such that the shim does not rotate with respect to the plug and an end portion that is connected to the plunger; wherein the piston head and shim are configured to both move axially in the chamber with respect to the shear thickening fluid in response to a force applied to the cap by an object and wherein the shim is configured to be rotated with respect to the piston head.

13. The device of claim 12, wherein the bushing comprises a cavity fluidly isolated from the chamber, and the cap is configured to move into the cavity in response to the force.

14. The device of claim 12, wherein the piston head receives a portion of the plunger and engages a flange on the plunger.

15. The device of claim 12, wherein the at least one slot is located between the D-shaped hole and an outer edge of the shim.

16. The device of claim 12, wherein a portion of the D-shaped portion of the plug is received in the piston head and is rotatable with respect to the piston head.

17. The device of claim 16, wherein the piston head has a first stop that prevents the D-shaped portion from being rotated beyond a first point in a first direction and a second stop that prevents the D-shaped portion from being rotated beyond a second point in a second direction.

18. A device for controlling the motion of an object, comprising: a head unit that includes a chamber filled at least in part with a shear thickening fluid; a plunger in the head unit that is connected to a cap, a bushing and a spring in the head unit, wherein the plunger extends through the bushing and spring, and the spring is configured to provide mechanical resistance between the cap and the bushing in response to a force applied to the cap; a piston head that receives a portion of the plunger, engages a flange on the plunger, and that is positioned in the chamber of the head unit, the piston head having at least one slot; a shim that includes a D-shaped hole and at least one slot; and a plug having a D-shaped portion that is received in the D-shaped hole of the shim such that the shim does not rotate with respect to the plug and an end portion that is received in the plunger; wherein the piston head and shim are configured to both move axially in the chamber with respect to the shear thickening fluid in response to a force applied to the cap by an object and wherein the shim is configured to be rotated with respect to the piston head.

19. The device of claim 18, wherein the bushing comprises a cavity fluidly isolated from the chamber and the cap is configured to move into the cavity in response to the force.

20. The device of claim 18, wherein a portion of the D-shaped portion of the plug is received in the piston head and is rotatable with respect to the piston head and wherein the piston head has a first stop that prevents the D-shaped portion from being rotated beyond a first point in a first direction and a second stop that prevents the D-shaped portion from being rotated beyond a second point in a second direction.
