

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250278025

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

BECKER; Moritz et al.

EUV OPTICS MODULE FOR AN EUV PROJECTION EXPOSURE APPARATUS

Abstract

An EUV optics module (35) for an EUV projection exposure apparatus (1) has at least one optical component (19, 21, 23, 7, M1 to M6, 13) having an optical surface guiding used EUV radiation (16) from an EUV source (3) along an illuminating and/or imaging beam path of the projection exposure apparatus (1). The optical component (19, 21, 23, 7, M1 to M6, 13) is accommodated in a reduced-pressure chamber (36). A gas source (37) is fluidically connected via at least one valve to the reduced-pressure chamber (36). The gas source (37) is configured to provide at least the following gas: hydrogen. This results in an EUV optics module having elevated operating time.

Inventors: BECKER; Moritz (Aalen, DE), DINGER; Udo (Oberkochen, DE), FENGLER; Stephanus (Aalen, DE)

Applicant: Carl Zeiss SMT GmbH (Oberkochen, DE)

Family ID: 88745897

Appl. No.: 19/210130

Filed: May 16, 2025

Foreign Application Priority Data

DE 10 2022 212 168.6

Nov. 16, 2022

Related U.S. Application Data

parent WO continuation PCT/EP2023/081090 20231108 PENDING child US 19210130

Publication Classification

Int. Cl.: G03F7/00 (20060101)

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS [0001] This is a Continuation of International Application PCT/EP2023/081090 which has an international filing date of Nov. 8, 2023, and the disclosure of which is incorporated in its entirety into the present Continuation by reference. This Continuation also claims foreign priority under 35 U.S.C. § 119(a)-(d) to and also incorporates by reference, in its entirety, German Patent Application DE 10 2022 212 168.6 filed on Nov. 16, 2022.

FIELD

[0002] The invention relates to an EUV optics module for an EUV projection exposure apparatus. The invention further relates to an optical system for an EUV projection exposure apparatus comprising such an EUV optics module, to a projection exposure apparatus comprising such an optical system, to a method of producing a micro- or nanostructured component with the aid of such a projection exposure apparatus, and to a micro- or nanostructured component produced by such a method.

BACKGROUND

[0003] An EUV optics module for an EUV projection exposure apparatus having an EUV source for generation of used extreme ultraviolet (EUV) radiation is known from U.S. Pat. No. 7,598,508 B2 for example. DE 10 2021 202 802 B3 discloses a projection exposure apparatus comprising a device for determining a concentration of atomic hydrogen. DE 10 2017 213 406 A1 discloses a reflective optical element for EUV lithography and a method of adjusting a geometry of a component. DE 10 2016 208 850 A1 discloses a projection exposure apparatus for semiconductor lithography having elements for plasma conditioning. DE 10 2020 202 179 A1 discloses an optical arrangement for EUV lithography and a method of determining a desired value for a target plasma parameter. US 2010/0071720 A1 discloses a method and a system for removal of contamination from a surface. US 2011/0143288 A1 discloses a radiation source, a lithography system and a component production method. US 2012/0086925 A1 discloses a method of avoiding contamination and an EUV lithography system. US 2007/0012889 A1 discloses gaseous spectral purity filters for EUV and an optical system comprising them.

SUMMARY

[0004] It is an object to develop an EUV optics module of the type specified in the Background section, above, such that an operating time of the EUV projection exposure apparatus is increased.

[0005] This and other objects are addressed, according to one formulation, by an EUV optics module having the features specified in the independent claims of the present application.

[0006] It has been recognized that hydrogen as the gas provided leads to creation of activated hydrogen species. This may be utilized in particular for generation of cleaning radicals with which the optical surface of the optical component is cleaned effectively. This increases the operating time of the EUV optics module. By definition of a partial hydrogen pressure, it is possible to achieve a desired generation of activated hydrogen species in the reduced-pressure chamber. The gas source can also be used to provide further gas species, for example oxygen or nitrogen or a mixture of two or more gas species. The gas source may have multiple gas source units, each of which is used to provide a particular gas. The gas source may have at least one gas vessel. The gas source may have two or more gas vessels containing different gases. Each of these gas vessels may then belong to a respective gas source unit. It is also possible to provide isotopes of the at least one gas provided. In

the case of hydrogen, these are D.sub.2HD, T.sub.2TD, HT (D: deuterium; T: tritium). By way of the addition of the hydrogen isotopes, it is possible to increase the effective cross section for dissociative generation of reactive hydrogen species proportionally by up to three orders of magnitude and hence to adjust the reactivity of the hydrogen in the environment of the gas injection. The reduced-pressure chamber may accommodate multiple optical components for which correspondingly activated hydrogen species and/or nitrogen/oxygen species are then generated via the gas provided, which accomplish effective cleaning and/or reaction of the optical surfaces of the optical components. Especially those optical components that are closest to the projection exposure apparatus in the beam path of the used EUV radiation in an EUV source can achieve a higher operating time in this way.

[0007] It is also possible to provide isotopes of these gases or vapors via the gas source, especially in a controlled concentration. In each case, open-loop control of the addition of gas is possible, or closed-loop control with respect to the partial pressure.

[0008] An isotope content in the concentration range according to an exemplary embodiment has been found to be particularly advantageous. Depending on the type of gas used, an advantageous increase in a cross section of dissociation may arise here, with especially uniform ionization cross section. The isotope content may be within an isotope concentration range between 0.1% and 10%.

[0009] The isotope concentration can be controlled by closed-loop control via the state of operation according to a further embodiment using states of operation that have already been described above in connection with the control valve design of the EUV optics module.

[0010] A control valve according to an exemplary embodiment enables provision under open-loop or even closed-loop control of the at least one gas via the gas source within the reduced-pressure chamber. It is possible to provide two or more control valves of this kind. In that case, it is possible in each case to assign at least one of the control valves to each of the gas source units or to each of the gas vessels of the gas source. The open-loop/closed-loop control device may be designed such that a respective partial pressure of the at least one gas provided is defined depending on a state of operation of the EUV optics module or of the projection exposure apparatus. This can be accomplished using a look-up table. States of operation may be defined via measurements of the gas composition, especially of H₂, N₂, NH₃, O₂, H₂O, and/or measurements of the concentration of activated species, especially H, N and O radicals or ions, and/or of the measured or calculated temperature of an optical element. In particular, a state of operation can also be defined via the measurement of a change in the reflective layer of an optical element.

[0011] The use of at least one pressure sensor according to a further embodiment allows definition of the partial pressure of the at least one gas provided under closed-loop control. The EUV optics module may have a plurality of such pressure sensors. In that case, at least one of these pressure sensors may be assigned to each gas species and/or to each gas source unit and/or to each gas vessel of the gas source. If nitrogen and hydrogen, for example, are provided via the gas source, one of the pressure sensors can specifically measure a partial nitrogen pressure and the other of the pressure sensors can specifically measure a partial hydrogen pressure. The respective pressure sensor may especially also be assigned to the respective optical component.

[0012] A design according to another exemplary embodiment optimizes the function of the EUV optics module in the environment of the optical surface of the optical component. In particular, the EUV optics module may then have a pressure sensor that assures measurement of pressure in the environment of the optical surface of the optical component. It is also possible for two or more pressure sensors of this kind assigned to exactly one optical surface or else assigned to more than one optical surfaces to be part of the EUV optics module.

[0013] A partial hydrogen pressure according to further embodiments has been found to be particularly suitable for assurance of a function of the EUV optics module.

[0014] Further gases provided via the gas source according to other embodiments have likewise been found to be particularly suitable for achievement of the function of the EUV optics module for

increasing the operating time of the at least one optical component.

[0015] It is also possible to use a noble gas.

[0016] The advantages of an optical system, a projection exposure apparatus, a production method and a microstructured or nanostructured component, all associated with the disclosed optics module correspond to those which have already been described above with reference to the EUV optics module.

[0017] The EUV light source of the projection exposure apparatus may be designed so as to result in a used wavelength of not more than 13.5 nm, of less than 13.5 nm, of less than 10 nm, of less than 8 nm, of less than 7 nm, and of 6.7 nm or 6.9 nm, for example. A used wavelength of less than 6.7 nm and, in particular, in the region of 6 nm is also possible.

[0018] In particular, the projection exposure apparatus can be used to produce a semiconductor component, for example a memory chip.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0019] At least one working example of the invention is described hereinafter with reference to the drawing. The drawing shows:

[0020] FIG. 1 a schematic in meridional cross section of a projection exposure apparatus for EUV projection lithography;

[0021] FIG. 2 a diagram of a dependence of an effective cross section σ , which is proportional to the absorption of light at particular wavelengths, of particular particle species on the partial pressure p thereof;

[0022] FIG. 3 results of a model calculation of a relative transmission T normalized to an in-band transmission for various particle species for a first, lowest partial pressure $p=0.001$ for various wavelength ranges;

[0023] FIGS. 4 to 6 each in a representation similar to FIG. 3, the relative transmissions of these particle species, each at a higher partial pressure p of these particle species, specifically in steps of one order of magnitude, i.e., $p=0.010$ Pa in FIG. 4, $p=0.100$ Pa in FIG. 5, and $p=1.000$ Pa in FIG. 6;

[0024] FIG. 7 the dependence of an effective effective cross section σ of nitrogen (N_2), adjacent to a mirror substrate surface, on a nitrogen gas pressure p adjustable via a nitrogen source, with observation of photoinduced ionization of a nitrogen molecule;

[0025] FIG. 8 the dependence of an effective effective cross section σ of nitrogen (N_2), adjacent to a mirror substrate surface, this time on partial pressures p firstly of various elemental vapors, with observation of the photoinduced splitting of a nitrogen molecule into two nitrogen atoms;

[0026] FIG. 9 the dependence of an effective effective cross section σ of nitrogen ($N_{\text{sub.2}}$), adjacent to a mirror substrate surface, on an isotope concentration c of deuterium $D_{\text{sub.2}}$ in hydrogen $H_{\text{sub.2}}$ within a reduced-pressure chamber of the projection exposure apparatus.

DETAILED DESCRIPTION

[0027] The primary components of a projection exposure apparatus 1 for microlithography are first described by way of example hereinafter with reference to FIG. 1. The description of the basic structure of the projection exposure apparatus 1 and its components should not be regarded as limiting here.

[0028] One design of an illumination system 2 of the projection exposure apparatus 1 has, in addition to a light or radiation source 3, an illumination optical unit 4 for illuminating an object field 5 in an object plane 6. In an alternative embodiment, the light source 3 may also be provided as a module separate from the rest of the illumination system. In this case, the illumination system does not comprise the light source 3.

[0029] A reticle 7 disposed in the object field 5 is exposed. The reticle 7 is held by a reticle holder

8. The reticle holder **8** is displaceable, in particular in a scanning direction, by way of a reticle displacement drive **9**.

[0030] FIG. **1** shows a Cartesian xyz coordinate system by way of facilitating the description. The x direction runs perpendicular to the plane of the drawing. The y direction runs horizontally, and the z direction runs vertically. The scanning direction runs in the y direction in FIG. **1**. The z direction runs perpendicular to the object plane **6**.

[0031] The projection exposure apparatus **1** further comprises a projection optical unit **10**. The projection optical unit **10** serves for imaging the object field **5** into an image field **11** in an image plane **12**. The image plane **12** extends parallel to the object plane **6**. Alternatively, an angle that differs from 0° between the object plane **6** and the image plane **12** is also possible.

[0032] A structure on the reticle **7** is imaged onto a light-sensitive layer of a wafer **13** arranged in the region of the image field **11** in the image plane **12**. The wafer **13** is held by a wafer holder **14**. The wafer holder **14** is displaceable, in particular in the y direction, by way of a wafer displacement drive **15**. The displacement firstly of the reticle **7** by way of the reticle displacement drive **9**, and secondly of the wafer **13** by way of the wafer displacement drive **15**, can be implemented so as to be mutually synchronized.

[0033] The radiation source **3** is an EUV radiation source or EUV source. The radiation source **3** emits, in particular, EUV radiation **16**, which is also referred to below as used radiation, illumination radiation or illumination light. In particular, the used radiation has a wavelength in the range between 5 nm and 30 nm. The radiation source **3** may be a plasma source, for example an LPP (laser produced plasma) source or a GDPP (gas discharge produced plasma) source. It may also be a synchrotron-based radiation source. The radiation source **3** may be a free electron laser (FEL).

[0034] The illumination radiation **16** emanating from the radiation source **3** is focused by a collector **17**. The collector **17** may be a collector with one or more ellipsoidal and/or hyperboloid reflection surfaces. The illumination radiation **16** may be incident on the at least one reflection surface of the collector **17** with grazing incidence (GI), i.e. at angles of incidence of greater than 45°, or with normal incidence (NI), i.e. at angles of incidence of less than 45°. The collector **17** may be structured and/or coated, firstly to optimize its reflectivity for the used radiation and secondly to suppress extraneous light.

[0035] Downstream of the collector **17**, the illumination radiation **16** propagates through an intermediate focus in an intermediate focal plane **18**. The intermediate focal plane **18** may represent a separation between a radiation source module, having the radiation source **3** and the collector **17**, and the illumination optical unit **4**.

[0036] The illumination optical unit **4** comprises a deflection mirror **19** and, downstream thereof in the beam path, a first facet mirror **20**. The deflection mirror **19** may be a planar deflection mirror or, alternatively, a mirror with a beam-influencing effect going beyond the pure deflection effect. As an alternative or in addition, the deflection mirror **19** may be designed as a spectral filter that separates a used light wavelength of the illumination radiation **16** from extraneous light of a wavelength deviating therefrom. If the first facet mirror **20** is arranged in a plane of the illumination optical unit **4** that is optically conjugate to the object plane **6** as a field plane, it is also referred to as a field facet mirror. The first facet mirror **20** comprises a multiplicity of individual first facets **21**, which are also referred to below as field facets. FIG. **1** depicts only some of these facets **21** by way of example.

[0037] The first facets **21** may be embodied as macroscopic facets, in particular as rectangular facets or as facets with an arcuate or part-circular edge contour. The first facets **21** may be in the form of plane facets or alternatively of facets with convex or concave curvature.

[0038] As is known for example from DE 10 2008 009 600 A1, the first facets **21** themselves may also each be composed of a multiplicity of individual mirrors, in particular a multiplicity of micromirrors. The first facet mirror **20** may in particular take the form of a microelectromechanical

system (MEMS system). For details, reference is made to DE 10 2020 212 351 A1, to U.S. Pat. No. 10,139,618, to U.S. Pat. No. 9,874,819, to U.S. Pat. No. 9,851,555 and to DE 10 2008 009 600 A1, and to the references cited therein.

[0039] The illumination radiation **16** travels horizontally, i.e. in the y direction, between the collector **17** and the deflection mirror **19**.

[0040] In the beam path of the illumination optical unit **4**, a second facet mirror **22** is arranged downstream of the first facet mirror **20**. If the second facet mirror **22** is arranged in a pupil plane of the illumination optical unit **4**, it is also referred to as a pupil facet mirror. The second facet mirror **22** can also be arranged at a distance from a pupil plane of the illumination optical unit **4**. In this case, the combination of the first facet mirror **20** and the second facet mirror **22** is also referred to as a specular reflector. Specular reflectors are known from US 2006/0132747 A1, EP 1 614 008 B1, and U.S. Pat. No. 6,573,978.

[0041] The second facet mirror **22** comprises a plurality of second facets **23**. In the case of a pupil facet mirror, the second facets **23** are also referred to as pupil facets.

[0042] The second facets **23** may likewise be macroscopic facets, which may for example have a round, rectangular or else hexagonal boundary, or may alternatively be facets composed of micromirrors. Reference is likewise made in this respect to DE 10 2008 009 600 A1 and to the references already mentioned above.

[0043] The second facets **23** may have plane reflection surfaces or alternatively reflection surfaces with convex or concave curvature.

[0044] The illumination optical unit **4** thus forms a double-faceted system. This basic principle is also referred to as a fly's eye integrator.

[0045] It may be advantageous to arrange the second facet mirror **22** not exactly in a plane that is optically conjugate to a pupil plane of the projection optical unit **10**. In particular, the pupil facet mirror **22** may be arranged so as to be tilted relative to a pupil plane of the projection optical unit **10**, as described, for example, in DE 10 2017 220 586 A1.

[0046] The individual first facets **21** are imaged into the object field **5** using the second facet mirror **22**. The second facet mirror **22** is the last beam-shaping mirror or else indeed the last mirror for the illumination radiation **16** in the beam path upstream of the object field **5**.

[0047] In a further embodiment (not illustrated) of the illumination optical unit **4**, a transfer optical unit may be arranged in the beam path between the second facet mirror **22** and the object field **5**, and contributes in particular to the imaging of the first facets **21** into the object field **5**. The transfer optical unit may comprise exactly one mirror or, alternatively, two or more mirrors, which are arranged in succession in the beam path of the illumination optical unit **4**. The transfer optical unit may in particular comprise one or two normal-incidence mirrors (NI mirrors) and/or one or two grazing-incidence mirrors (GI mirrors).

[0048] In the design shown in FIG. **1**, the illumination optical unit **4** has exactly three mirrors downstream of the collector **17**, specifically the deflection mirror **19**, the field facet mirror **20**, and the pupil facet mirror **22**.

[0049] The deflection mirror **19** may also be omitted in a further design of the illumination optical unit **4**, and so the illumination optical unit **4** may then have exactly two mirrors downstream of the collector **17**, specifically the first facet mirror **20** and the second facet mirror **22**.

[0050] The imaging of the first facets **21** into the object plane **6** with the second facets **23** or using the second facets **23** and a transfer optical unit is often only approximate imaging.

[0051] The projection optical unit **10** comprises a plurality of mirrors M_i , which are consecutively numbered in accordance with their arrangement in the beam path of the projection exposure apparatus **1**.

[0052] In the example illustrated in FIG. **1**, the projection optical unit **10** comprises six mirrors M_I to M_6 . Alternatives with four, eight, ten, twelve, or any other number of mirrors M_i are likewise possible. The projection optical unit **10** is a doubly obscured optical unit. The penultimate mirror

M5 and the last mirror M6 each have a through opening for the illumination radiation **16**. The projection optical unit **10** has an image-side numerical aperture that is greater than 0.5 and may also be greater than 0.6 and may be for example 0.7 or 0.75.

[0053] Reflection surfaces of the mirrors M_i may be designed as freeform surfaces without an axis of rotational symmetry. Alternatively, the reflection surfaces of the mirrors M_i may be designed as aspherical surfaces with exactly one axis of rotational symmetry of the reflection surface shape. Just like the mirrors of the illumination optical unit **4**, the mirrors M_i may have highly reflective coatings for the illumination radiation **16**. These coatings may be designed as multilayer coatings, in particular with alternating layers of molybdenum and silicon.

[0054] The projection optical unit **10** has a large object-image offset in the y direction between a y coordinate of a center of the object field **5** and a y coordinate of the center of the image field **11**. In the y direction, this object-image offset can be of approximately the same magnitude as a z distance between the object plane **6** and the image plane **12**.

[0055] The projection optical unit **10** may in particular have an anamorphic form. In particular, it has different imaging scales β_x , β_y in x and y directions. The two imaging scales β_x , β_y of the projection optical unit **10** are preferably at $(\beta_x, \beta_y) = (+/-0.25, +/-0.125)$. A positive imaging scale β means imaging without image inversion. A negative sign for the imaging scale β means imaging with image inversion.

[0056] The projection optical unit **10** consequently leads to a reduction in size with a ratio of 4:1 in x direction, i.e. in a direction perpendicular to the scanning direction.

[0057] The projection optical unit **10** leads to a reduction in size of 8:1 in y direction, i.e. in scanning direction.

[0058] Other imaging scales are likewise possible. Imaging scales with the same signs and the same absolute values in x direction and y direction are also possible, for example with absolute values of 0.125 or 0.25.

[0059] The number of intermediate image planes in the x direction and in the y direction in the beam path between the object field **5** and the image field **11** may be the same or may differ depending on the design of the projection optical unit **10**. Examples of projection optical units with different numbers of such intermediate images in x and y directions are known from US 2018/0074303 A1.

[0060] One of the pupil facets **23** in each case is assigned to exactly one of the field facets **21**, in each case to form an illumination channel for illuminating the object field **5**. This may in particular result in illumination according to the Köhler principle. The far field is deconstructed into a multiplicity of object fields **5** via the field facets **21**. The field facets **21** generate a plurality of images of the intermediate focus on the pupil facets **23** respectively assigned thereto.

[0061] The field facets **21** are imaged, each by way of an assigned pupil facet **23**, onto the reticle **7** in a manner such that they are mutually superposed for illumination of the object field **5**. The illumination of the object field **5** is in particular as homogeneous as possible. It preferably has a uniformity error of less than 2%. Field uniformity can be achieved by overlaying different illumination channels.

[0062] The illumination of the entrance pupil of the projection optical unit **10** may be geometrically defined by an arrangement of the pupil facets. It is possible to set the intensity distribution in the entrance pupil of the projection optical unit **10** by selecting the illumination channels, in particular the subset of pupil facets, which guide light. This intensity distribution is also referred to as illumination setting or illumination pupil filling.

[0063] A likewise preferred pupil uniformity in the region of sections of an illumination pupil of the illumination optical unit **4** which are illuminated in a defined manner may be achieved by a redistribution of the illumination channels.

[0064] Further aspects and details of the illumination of the object field **5** and in particular of the entrance pupil of the projection optical unit **10** are described hereinafter.

[0065] The projection optical unit **10** may in particular have a homocentric entrance pupil. The latter may be accessible. It may also be inaccessible.

[0066] The entrance pupil of the projection optical unit **10** generally cannot be illuminated exactly with the pupil facet mirror **22**. The aperture rays often do not intersect at a single point when imaging the projection optical unit **10** which telecentrically images the center of the pupil facet mirror **22** onto the wafer **13**. However, it is possible to find an area in which the spacing of the aperture rays that is determined in pairs becomes minimal. This area represents the entrance pupil or an area in real space that is conjugate thereto. In particular, this area has a finite curvature.

[0067] It may be the case that the projection optical unit **10** has different poses of the entrance pupil for the tangential beam path and for the sagittal beam path. In this case, an imaging element, in particular an optical component part of the transfer optical unit, should be provided between the second facet mirror **22** and the reticle **7**. With this optical element, the different pose of the tangential entrance pupil and the sagittal entrance pupil can be taken into account.

[0068] In the arrangement of the components of the illumination optical unit **4** illustrated in FIG. **1**, the pupil facet mirror **22** is arranged in an area conjugate to the entrance pupil of the projection optical unit **10**. The field facet mirror **20** is in a tilted arrangement with respect to the object plane **6**. The first facet mirror **20** is in a tilted arrangement with respect to an arrangement plane defined by the deflection mirror **19**.

[0069] The first facet mirror **20** is in a tilted arrangement with respect to an arrangement plane defined by the second facet mirror **22**.

[0070] In the source operation of the EUV source **3**, the used EUV radiation **16** is emitted by a source region **25**. This source region **25**, the collector **17** and also components of the EUV source **3** are accommodated in a reduced-pressure chamber **26** of an EUV source module **27** of the projection exposure apparatus **1**. Part of the EUV source module **27** is the EUV source **3**.

[0071] A gas source **29** of the EUV source module **27** is in fluid connection with the reduced-pressure chamber **26** via a valve group **28**. The gas source **29** has multiple gas source units. In the design shown, these are four gas source units **301**, **302**, **303** and **304**. The valve group **28** has an actuatable source valve **31i** assigned to each one of the respective gas source units **30i**, and a main valve **32**. The main valve **32** is in fluid connection with all source valves **31i** via fluid conduits. The main valve **32** is disposed between the source valves **31i** and the reduced-pressure chamber **26**. The respective gas source unit **30i** is in fluid connection with the reduced-pressure chamber **26** by the respective source valve **31i** and via the main valve **32** arranged in series therewith.

[0072] Each of the gas source units **30i** may have a corresponding gas vessel comprising the gas to be provided.

[0073] The gas source **29** is designed such that it provides, via the gas source units **30i**, at least one of the following gases: nitrogen, hydrogen, oxygen, water vapor, CH₄, NH₃, a metal vapor based, for example, on tin (Sn), zinc (Zn), ruthenium (Ru) or iron (Fe), a volatile metal hydride, for example SnH₄, ZnH₂ or PbH₄, or a volatile metal oxide, for example RuO₄, IrO₄, or a volatile metal fluoride, for example MoF₆, IrF₆, WF₆, ReF₆. It is also possible to use a noble gas. It is also possible to provide further gaseous species via the gas source **29** of the reduced-pressure chamber **26**. It is also possible to provide lead (Pb) and/or molybdenum as metal vapors. If a metal vapor is provided, this can be accomplished with an evaporator, for example using a spiral-wound filament.

[0074] It is also possible to provide isotopes that form the aforementioned gases, i.e., in the case of hydrogen (H₂), D₂, HD, T₂, TD, HT (D: deuterium; T: tritium).

[0075] The valves **31i** and **32** are each control valves having signal connection with a closed-loop control device **33** of the EUV source module **27**.

[0076] The closed-loop control device **33** may be designed so as to define, depending on a state of operation of the EUV source module **27** or of the projection exposure apparatus **1**, a particular partial pressure of the gas provided respectively via the gas source **29** or of two or more gases

provided by the gas source **29**. In this case, the closed-loop control device **33** may refer to a stored look-up table in which partial pressure values for the gas(es) that can be provided in each case by the gas source **29** are assigned as a function of the respective state of operation of the projection exposure apparatus **1**.

[0077] States of operation may be defined via measurements of the gas composition, especially of H₂, N₂, NH₃, O₂, H₂O, and/or measurements of the concentration of activated species, especially H, N and O radicals or ions, and/or of the measured or calculated temperature of an optical element. In particular, a state of operation can also be defined via the measurement of a change in the reflective layer of an optical element.

[0078] In one design of the EUV source module **27**, it has at least one pressure sensor **34** for measuring a partial pressure of the at least one gas provided by the gas source **29** in the reduced-pressure chamber **26**. In the design shown in FIG. **1**, there are two such pressure sensors **34.sub.1**, **34.sub.2**. These pressure sensors **34i** are disposed in the reduced-pressure chamber **26** close to the intermediate focus in the intermediate focal plane **18**, i.e. measure the partial pressure of the at least one gas provided close to this intermediate focus.

[0079] The pressure sensors **34i** can measure the partial pressure of each one of the gases which is provided via the gas source units **30i**.

[0080] In the design with the at least one pressure sensor **34**, the closed-loop control device **33** may be designed such that a target value is defined for the respective partial pressure of the at least one gas provided depending on the respective state of operation of the EUV source module **27** or of the projection exposure apparatus **1**, and the gas is then provided in the reduced-pressure chamber **26** in a controlled manner using the respective pressure sensor **34i** as the actual partial pressure value within the reduced-pressure chamber **26** via the gas source **29** by appropriate actuation firstly of the assigned source valve **31i** and secondly of the main valve **32**.

[0081] Alternatively, a corresponding pressure sensor **34** may also be disposed in the environment of the source region **25**, as likewise shown in FIG. **1**, where it may measure a corresponding partial pressure of the at least one gas provided.

[0082] The pressure sensor **34**, **34i** may in principle be designed as an optical sensor.

[0083] The partial pressure of the at least one gas provided can be kept within a defined pressure range with the open-loop/closed-loop pressure control system that has been explained above, for example in the source region **25**. This can be assured by monitoring by the pressure sensor **34** in the environment of the source region **25**.

[0084] Alternatively or additionally, it is also possible to keep a partial pressure of the at least one gas provided within a defined pressure range in the region of the intermediate focus in the intermediate focal plane **18** with the aid of the above-described open-loop/closed-loop control system. Compliance with the partial pressure can be monitored here by measuring the pressure via the pressure sensors **34.sub.1**, **34.sub.2** in the region of the intermediate focus in the intermediate focal plane **18**.

[0085] In one design (not shown) of the gas source **29**, this has injection nozzles for controlled injection of at least one of the gases provided into the reduced-pressure chamber **26** in the environment of the intermediate focus in the intermediate focal plane **18**. The amount of the gas injected respectively can then be monitored with the pressure sensors **34.sub.1**, **34.sub.2** in the environment of the intermediate focus in the intermediate focal plane **18**.

[0086] The respective gas can also be supplied to the reduced-pressure chamber **26** via at least one purge conduit.

[0087] If nitrogen is being provided, a partial nitrogen pressure in the reduced-pressure chamber **26** in the range between 10 Pa and 100 Pa can be maintained via the above-described open-loop/closed-loop control system. If hydrogen is being provided as gas in the reduced-pressure chamber **26**, a partial hydrogen pressure may typically be kept in the range between 30 Pa and 300 Pa.

[0088] FIG. 2 shows the dependence of an effective cross section σ of different particle species on the partial pressure p thereof. This effective cross section is proportional to the absorption of the respective particle species at particular wavelengths of light or radiation. Additionally shown in FIG. 2 as obliquely declining curves are a transmission of $1e-06$ (solid line) and a transmission of $1e-03$ (dotted line). Respectively shown in solid/dashed/dashed-and-dotted/dotted form are the effective cross section for H_2 , H_2O , N , N_2 , NH , NH^+ , NH_2 , NH_3 , O , O_2 , O_2^+ , O_3 , OH and OH^+ . Because of the comparatively large effective cross section of hydrogen and nitrogen, transmissions of $1e-06$ and $1e-03$ are found for comparatively low partial pressures in the region of 10^{-2} Pa. For the other particle species, these two $1e-03$ transmission values are found only at higher partial pressures, for example in the region of 100 Pa (H_2O) or even of even greater partial pressures (for example O_2).

[0089] In order that there is a significant interaction, for example, of hydrogen or nitrogen with the EUV radiation 16, for example in the source region 25 or in the intermediate focus in the intermediate focal plane 18, a partial pressure of at least $1e-03$ must be defined. For the other particle species, a correspondingly higher partial pressure p must be defined, as apparent from the diagram in FIG. 2.

[0090] NH_3 gas can especially bind nitrogen ions.

[0091] FIGS. 3 to 6 show wavelength dependences of a relative transmission T for particular particle species, shown for “in-band”, “VUV” and “DUV” wavebands.

[0092] “In-band” refers here to a used EUV wavelength of 13.5 nm.

[0093] “VUV” refers to the wavelength range between 70 nm and 130 nm.

[0094] “DUV” refers to the wavelength range between 130 nm and 400 nm.

[0095] FIG. 3 shows a wavelength dependence of a relative transmission for particular particle species, shown for various wavelength ranges and for a respective partial pressure of 0.001 Pa. The relative transmissions are shown for the particle species tin metal vapor, nitrogen, iron metal vapor and zinc metal vapor, which can be provided in the reduced-pressure chamber 26 by appropriate fitting of the gas source units 30; of the gas source 29, as explained above.

[0096] The relative transmission values according to FIG. 3 are normalized to transmission over an in-band wavelength range.

[0097] VUV transmission in this pressure range is slightly higher than in-band transmission and is about 1.1. DUV transmission for all these particle species is about 1.4 at the partial pressure of 0.001 Pa.

[0098] FIG. 4 shows the ratios at a partial particle species pressure of 0.01 Pa, ten times the value in FIG. 3. There is virtually no change by comparison with the relative transmission values according to FIG. 3. It can be concluded from this that the respective particle species still do not have any real influence on the relative transmission of the EUV radiation 16.

[0099] FIG. 5 shows the relative transmission values at a partial particle species pressure of 0.1 Pa, which is ten times greater again. The relative transmissions for the DUV wavelength range have slightly increased by comparison with FIGS. 3 and 4 for the particle species tin metal vapor and zinc metal vapor, and are about 1.5 for tin metal vapor and about 1.45 for zinc metal vapor at the partial pressure value of 0.1 Pa in FIG. 5.

[0100] FIG. 6 shows the relative transmission values for the same particle species at a partial pressure of 1.0 Pa, which is ten times higher again. By comparison with the lower partial pressure values, in particular, the relative transmissions for the DUV wavelength range have now increased for the particle species tin metal vapor, nitrogen and zinc metal vapor. For the partial pressure 1.0 Pa, the relative transmissions are now at a value of about 2.3 for tin metal vapor, at a value of about 1.75 for zinc metal vapor, and about 1.5 for nitrogen. The relative transmissions for the VUV wavelength range have also increased for tin metal vapor on the one hand and for zinc metal vapor, and are now about 1.2 for tin metal vapor and about 1.3 for zinc metal vapor.

[0101] Tin metal vapor and/or zinc metal vapor in particular can thus be utilized in a partial

pressure-dependent manner as effective wavelength filters for the DUV range and also for the VUV range.

[0102] This is used, for example, in the projection exposure apparatus in order to selectively filter out unwanted wavelengths or wavelength ranges from radiation components of different wavelengths included in the used EUV radiation **16** that cause unwanted photoreactions with particles present further down the beam path of the used EUV radiation **16**. Such unwanted reactions are especially those that lead to reaction products that impair or degrade optical surfaces of components of the projection exposure apparatuses **1** that guide the used EUV radiation **16**. Reactions that lead to products having unwanted absorption at the wavelength of the used EUV radiation **16** are also corresponding unwanted reactions.

[0103] Filtering via the gas provided can alternatively or additionally be utilized to avoid unwanted photocurrents that would otherwise be generated in the exposed optical component of the projection exposure apparatus **1** by exposure to the wavelengths or wavelength ranges that are now being filtered out. This in particular allows the performance of optical components to be enhanced, in that these overall or their individual components, for example in the form of single mirrors, are held in position with holding currents. It is then possible to avoid any unwanted influence on such components by photocurrents generated. One example of such components is a MEMS mirror system having a multitude of individual single mirrors that are held in a corresponding tilted position with holding currents.

[0104] The interaction of the at least one gas provided in the reduced-pressure chamber **26** via the gas source **29** gives rise, further down the beam path of the used EUV radiation **16**, to a wavelength distribution of the radiation included in the beam path with the used EUV radiation **16** that reduces or entirely avoids corresponding unwanted reactions and/or photocurrents. The result is attenuation of corresponding absorption lines of an overall radiation spectrum emitted by the source region **25**. Wavelength ranges of this overall radiation spectrum that are correspondingly attenuated by the gases provided in the reduced-pressure chamber **26** are then no longer available to cause unwanted degradation and/or also no longer available to cause an unwanted reduction in power as a result of photoinduced misadjustment of the optical components downstream in the beam path of the used EUV radiation **16**. In particular, it is possible to reduce or entirely avoid N.sub.2-induced and/or H.sub.2-induced degradation of optical coatings of optical surfaces of these optical components and/or unwanted photoinduced misadjustment of the optical components. N.sub.2/N ion/H.sub.2-induced coating degradation would otherwise be caused by radiation in these wavelength ranges by photoionization and/or photoinduced misadjustment would otherwise be caused by radiation in these wavelength ranges by photocurrents. The attenuation of these wavelength ranges then results in a reduction or complete avoidance of such photoionization. By definition, for example, of a corresponding partial H.sub.2 pressure, it is possible, for example, to avoid unwanted creation of hydrogen plasma further down the beam path of the used EUV radiation **16**.

[0105] In principle, there are two different ways of avoiding such unwanted reaction products in the at least one gas provided: [0106] Firstly, corresponding photoionization reactions can be induced within the reduced-pressure chamber **26** of the EUV source module **27** by addition of appropriate partial gas pressures, such that radiation wavelengths that are used in these disruptive photoionizing processes are no longer available further down the beam path of the used EUV radiation **16**. By inducing the disruptive reaction in the beam path before the intermediate focus in the intermediate focal plane **18**, the reaction in the beam path downstream of the intermediate focus in the intermediate focal plane **18** is then reduced or entirely avoided in a desirable manner. An example of this controlled inducement of reaction are photoionization processes on nitrogen particle species and/or hydrogen particle species. [0107] Secondly, a radiation wavelength at which an unwanted reaction, especially a photoionization, for creation of unwanted reaction products is known to take place, or unwanted photocurrents are known to be generated, can be attenuated with a filter used in a controlled manner, especially a bandpass filter which is formed by the at least one

gas provided, such that such disruptive photoionization/photocurrent wavelengths are no longer available for the creation of unwanted reaction products in the beam path of the used EUV radiation **16** downstream of the intermediate focus in the intermediate focal plane **18**. One example of such a bandpass filter is the metal vapors described above, for example in association with FIGS. **3** to **6**, based on tin, zinc or iron, or else nitrogen. Nitrogen and hydrogen gas species may act, for example, as line filters. With the aid of such a bandpass filter, it is especially possible to wholly or partly suppress a wavelength range between 40 nm and 170 nm, which has been found to be troublesome with regard to the creation of unwanted photocurrents.

[0108] FIG. **7** shows the dependence of an effective N₂ effective cross section σ close to an optical surface of an optical component downstream of the intermediate focus in the intermediate focal plane **18** on a partial nitrogen pressure p in the reduced-pressure chamber **26** in the environment of the source region **25** and/or in the environment of the intermediate focus in the intermediate focal plane **18**. Over and above a partial nitrogen pressure of 101 Pa, a distinct reduction in this effective N₂ dissociation effective cross section is found, which drops by more than one order of magnitude between 10 Pa and 100 Pa.

[0109] This effective effective cross section σ is reported in arbitrary units (a.u.).

[0110] The drop in the effective effective cross section σ in FIG. **7** for higher partial N₂ pressures leads, for example, to a corresponding reduction in disruptive photoionization of nitrogen to give a nitrogen ion N₂⁺ and an electron. If this photoionization reaction is reduced or entirely avoided in the environment of the optical surface of the optical component, N₂⁺ ions cannot contribute to degradation of the optical surface.

[0111] FIG. **8** shows a corresponding dependence of effective cross section on partial pressure for the photoinduced splitting, close to an optical surface, of a nitrogen molecule into two nitrogen atoms or into two nitrogen ions.

[0112] An effective effective cross section of the respectively considered element species is reported in FIG. **8** in the unit m².

[0113] Above a partial nitrogen pressure p in the reduced-pressure chamber **26** of 10⁻² Pa, there is a drop in the effective N₂ effective cross section σ by more than one order of magnitude for this photoinduced splitting.

[0114] Reduction in the effective N₂ effective cross section for this photoinduced splitting results in a corresponding reduction of disruptive nitrogen atoms or nitrogen ions in the region of the optical surfaces of the optical components in the beam path of the EUV radiation **16** downstream of the intermediate focus in the intermediate focal plane **18**.

[0115] The optical components, the degradation of which can be reduced or entirely avoided in this way or the performance of which can be increased, are firstly optical components of the illumination optical unit **4** and/or secondly the optical components of the projection optical unit **10**, i.e. the mirrors M_i.

[0116] FIG. **8** additionally shows the influence firstly of iron metal vapor (Fe) and secondly of zinc metal vapor (Zn) on the photoinduced splitting of a nitrogen molecule into two nitrogen atoms or nitrogen ions, again close to an optical surface of the optical component to be protected. Depending on the partial iron pressure, there is a drop in the effective N₂ effective cross section σ above a partial iron metal vapor pressure of 10° proceeding from a starting value of about 8×10⁻²⁴ m² to values of less than 4×10⁻²⁴ m², i.e. by more than a factor of 2.

Correspondingly, when such metal vapors with these partial pressures are used within the reduced-pressure chamber **26**, for example in the environment of the source region **25** or close to the intermediate focus in the intermediate focal plane **18**, the result is a desired reduction in this splitting reaction in the beam path of the used EUV radiation **16** downstream of the intermediate focus in the intermediate focal plane **18** and corresponding protection of the downstream optical components of the illumination optical unit **4** and the projection optical unit **10**.

[0117] When a zinc metal vapor is used, above a corresponding partial Zn metal vapor pressure of

100 Pa, there is an increase in the effective N₂ effective cross section for this splitting reaction. In the case of a partial Zn metal vapor pressure of 101 Pa, an N₂ effective cross section greater than 5×10^{-23} m² is achieved.

[0118] When a hydrogen vapor is used, no significant dependence of the N₂ effective cross section on the partial H₂ pressure is found.

[0119] Similar behavior is found when a tin metal vapor (Sn) is used. In that case, above a partial Sn metal vapor pressure of 100 Pa, an increase in the effective N₂ effective cross section is found, again proceeding from about 8×10^{-24} m² to more than 2×10^{-23} m².

[0120] The tin metal vapor efficiently suppresses the wavelength range between 80 nm and 160 nm in particular.

[0121] In a further design of the projection exposure apparatus **1**, which is used alternatively or additionally to that with the gas source **29** and/or the sensors **34** for the reduced-pressure chamber of the EUV source module **27**, an EUV optics module **35** is used, which is described hereinafter.

[0122] The EUV optics module **35** has a reduced-pressure chamber **36** that accommodates the illumination optical unit **4** and the projection optical unit **10**.

[0123] Reduced pressure is generated in the reduced-pressure chamber **26** and **36** by at least one reduced-pressure source, for example a vacuum pump, which is not shown in FIG. **1**.

[0124] The reduced-pressure chamber **36** includes all the optical components of the projection exposure apparatus **1** that guide the used EUV radiation **16** downstream of the intermediate focus in the intermediate focal plane **18**. In the beam path of the used EUV radiation **16** downstream of the intermediate focus in the intermediate focal plane **18**, these are the optical components **19**, **21**, **23**, the reticle **7**, M**1** to M**6**, and the wafer **13**.

[0125] These optical components each have an optical surface for guiding of the used EUV radiation **16** from the EUV source module **27** including the EUV source along the illumination and/or imaging beam path of the used EUV radiation **16** within the projection exposure apparatus **1**.

[0126] The optical components may be of temperature-controllable design.

[0127] The EUV optics module **35** in turn has a gas source **37** fluidically connected via at least one valve **32a** to the reduced-pressure chamber **36**. The construction of the gas source **37** with at least one gas source unit **30i** and with a valve group **28a** including the source valves **31i** each assigned to the gas source units **30i** and the main valve **32a** corresponds to the construction of the gas source **29** that has already been detailed above in connection with the EUV source module **27**.

[0128] The gas source **37** is designed such that it provides the reduced-pressure chamber **36** at least with hydrogen as gas. It is also possible to provide other gases, for example oxygen and/or nitrogen, especially also in the form of vapors, as already explained above in connection with the EUV source module **27**, via the gas source **37**.

[0129] The gas source **37** may have gas nozzles or injection nozzles that are directed onto the respective optical surfaces of the optical components **19**, **21**, **23**, **7**, M**1** to M**6**, **13**. This ensures that the activated hydrogen species are generated where they are used for cleaning of the optical surfaces of the respective optical component. It is also possible to provide a multitude of corresponding gas nozzles (not shown in FIG. **1**) for each optical surface of the optical component. The gas source **37** and especially the controllable valves thereof are in signal connection with the open-loop/closed-loop control device **33** of the projection exposure apparatus **1**.

[0130] The hydrogen gas provided by the gas source **37** leads, within the reduced-pressure chamber **36**, to generation of at least one activated hydrogen species which is used for reaction with an unwanted contamination component within the reduced-pressure chamber **36**, especially for cleaning of the optical surfaces of the optical components **19**, **21**, **23**, **7**, M**1** to M**6**, and **13**. In this way, the respective optical surface is effectively cleaned. The definition of the partial hydrogen pressure in the reduced-pressure chamber **36** achieves the desired generation of the activated hydrogen species therein.

[0131] The other gases that can be introduced into the reduced-pressure chamber **36** via the gas source **37** in addition to hydrogen, for example oxygen and/or nitrogen, may likewise serve for production, for example, of cleaning radicals for cleaning of the optical surfaces of the optical components of the illumination optical unit **4** and/or of the projection optical unit **10**, and/or may serve, analogously to what has been described above in association with the EUV source module **27**, to filter radiation included in the EUV light radiation **16**, which reduces or completely avoids generation of unwanted reaction components that could otherwise lead to degradation of the optical surfaces.

[0132] One option is to operate the EUV optics module **35** with control purely via the open-loop/closed-loop control device **33**, i.e. with the aid of a lookup table depending on states of operation of the EUV optics module **35** or of the overall projection exposure apparatus **1**, for example. Alternatively or additionally, the gas source **37** can also be operated under closed-loop control. For such closed-loop control operation, the EUV optics module **35** in turn has pressure sensors **38i** which, in FIG. **1**, are indicated as being assigned as pressure sensors **381** to **3811** to the optical surfaces of the optical component **19**, **21**, **23**, **7**, **M1** to **M6**, and **13**. The function of these pressure sensors **38i**, which are in turn in signal connection with the open-loop/closed-loop control device **33**, corresponds to that of the pressure sensors **34i** of the EUV source module **27**.

[0133] In particular, with the aid of the pressure sensors **38i**, it is possible to measure a partial hydrogen pressure.

[0134] The partial pressure measured via the respective pressure sensor **38**, as already described above in connection with the EUV source module **27**, can especially be kept in a defined pressure range with the open-loop/closed-loop control device **33**.

[0135] The partial hydrogen pressure within the reduced-pressure chamber **36** can be kept, for example, in the range between 0.2 Pa and 20 Pa.

[0136] It is possible to admit isotopes of the respective gases, especially hydrogen isotopes, into the reduced-pressure chamber **36** and optionally also into the reduced-pressure chamber **26** of the EUV source module **27** via the respective gas sources **37** or **29**.

[0137] FIG. **9** shows a dependence of an effective effective cross section σ for photoinduced splitting of molecular hydrogen species (H_2 and/or D_2) on an isotope concentration c of deuterium D_2 in hydrogen H_2 for a given proportion of D_2/H_2 in the reduced-pressure chamber **36** or **26**. The dependence shown in FIG. **9** is valid here especially for a partial D_2/H_2 pressure of 0.2-20 Pa within the reduced-pressure chamber **36** or **26**.

[0138] What is shown, in solid circles, is a dependence of this effective dissociation cross section σ on the concentration c (D_2/H_2), reported in relative units [r.u.], based on a dissociation cross section of exactly 1 for pure hydrogen (c (D_2/H_2)=0).

[0139] Additionally shown, in open circles, is the dependence of a relative effective cross section σ_I for a photoinduced ionization of molecular hydrogen species (H_2 and/or D_2). What is shown here is the ionization cross section σ_I in relation to a value of exactly 1 for a pure hydrogen content (c (D_2/H_2)=0).

[0140] The dissociation cross section σ , above a relative concentration c of 0.01, rises rapidly by several orders of magnitude, and at a concentration c (D_2/H_2) of 10% is more than 100. At this concentration, there has barely been any reduction in the ionization cross section σ_I , which is essentially constant for concentrations c in the range between 0.001% and 1%.

[0141] The dependences in FIG. **9** show that addition of, for example, 10% or 25% deuterium causes a rapid advantageous rise in the dissociation cross section, while there is no unwanted drop in the ionization cross section. This corresponding addition of deuterium thus allows, for example, an increase in the proportion of reactive hydrogen species in the reduced-pressure chamber **36** or **26**, which can achieve more effective cleaning and/or reaction of the optical surfaces of the optical components. Advantageous isotope concentration fractions c (D_2/H_2) are in the range between 0.02% and 25% and, for example, in the range between 0.1% and 10%.

[0142] In the design according to FIG. 1, the reduced-pressure chamber 36 encloses both the illumination optical unit 4 and the projection optical unit 10. Alternatively, the reduced-pressure chamber 36 may also be subdivided into a first subchamber which encloses exclusively the illumination optical unit 4, and a second subchamber which encloses exclusively the projection optical unit 10. Accordingly, the EUV optics module 35, if it is connected to one of these subchambers, may function as part of the illumination optical unit 4 and/or as part of the projection optical unit 10.

[0143] In order to produce a microstructured or nanostructured component, the projection exposure apparatus 1 is used as follows: First, the reflection mask 7 or the reticle and the substrate or the wafer 13 are provided. Subsequently, a structure on the reticle 7 is projected onto a light-sensitive layer of the wafer 13 with the aid of the projection exposure apparatus 1. Then a microstructure or nanostructure on the wafer 13, and hence the microstructured component, is produced by developing the light-sensitive layer.

Claims

1. An extreme ultraviolet (EUV) optics module for an EUV projection exposure apparatus, comprising: at least one optical component having an optical surface arranged to guide used EUV radiation along an illuminating and/or imaging beam path of the projection exposure apparatus, a reduced-pressure chamber configured to accommodate the optical component, a gas source fluidically connected via at least one valve to the reduced-pressure chamber, wherein the gas source is configured to provide hydrogen as an at least one gas, wherein the gas source is configured to add to the at least one gas provided at least one isotope of the gas in a controlled concentration.
2. The EUV optics module according to claim 1, wherein the gas source) is configured such that addition of hydrogen isotopes increases an effective cross section of the gas for dissociative generation of reactive hydrogen species proportionally by more than three orders of magnitude relative to an EUV optics module without an addition of isotopes.
3. The EUV optics module according to claim 2, wherein a proportion of an isotope corresponds to 0.02-25% of the at least one gas provided.
4. The EUV optics module according to claim 2, further comprising a closed loop control configured to adjust a concentration of the isotope in the gas provided in accordance with an operation state of the module.
5. The EUV optics module according to claim 1, wherein the valve is a control valve having a signal connection to an open-loop/closed-loop control device of the EUV optics module.
6. The EUV optics module according to claim 5, further comprising at least one pressure sensor arranged to measure a partial pressure of the at least one gas provided via the gas source in the reduced-pressure chamber, wherein the pressure sensor has signal connection to the control valve via the open-loop/closed-loop control device.
7. The EUV optics module according to claim 1, further comprising a control device configured to maintain a partial pressure of the at least one gas provided in a defined pressure range within an environment of the optical surface of the optical component.
8. The EUV optics module according to claim 1, further comprising a control device configured to maintain a partial hydrogen pressure in a range between 0.2 Pa and 20 Pa in the reduced-pressure chamber.
9. The EUV optics module according to claim 1, wherein the gas source is configured to provide at least one further gas selected from the group consisting of: oxygen and/or water vapor and/or nitrogen and/or CH₄ and/or NH₃ and/or CO and/or CO₂.
10. An optical system for an EUV projection exposure apparatus, comprising: an illumination optical unit configured to illuminate an object field, a support for an object disposed in the object field, and an imaging optical unit configured to image the object field in an image field, a support

for a wafer disposed in the image field, and an EUV optics module according to claim 1 and incorporated into the illumination optical unit.

11. An optical system for an EUV projection exposure apparatus, comprising: an illumination optical unit configured to illuminate an object field a support for an object disposed in the object field, and an imaging optical unit configured to image the object field in an image field, a support for a wafer disposed in the image field, and an EUV optics module according to claim 1 and incorporated into the imaging optical unit.

12. A projection exposure apparatus, comprising: an optical system according to claim **10**, and an EUV light source generating the EUV radiation.

13. A projection exposure apparatus, comprising: an optical system according to claim **11**, and an EUV light source generating the EUV radiation.

14. A method for producing a structured component, comprising: providing a reticle and a wafer, projecting a structure on the reticle onto a light-sensitive layer of the wafer with a projection exposure apparatus according to claim **12**, and producing a microstructure or nanostructure on the wafer.

15. A method for producing a structured component, comprising: providing a reticle and a wafer, projecting a structure on the reticle onto a light-sensitive layer of the wafer with a projection exposure apparatus according to claim **13**, and producing a microstructure or nanostructure on the wafer.
