

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250280340

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

GU; Xiaofei

INTERACTION METHOD AND RELATED DEVICE

Abstract

The present disclosure provides an interaction method and related device. The method includes: receiving first information sent in parallel by a plurality of first distributed unit entities (DUs) accessed by user equipment (UE); and sending, to each first DU, second information corresponding to the first DUs in parallel.

Inventors: GU; Xiaofei (Beijing, CN)

Applicant: DATANG MOBILE COMMUNICATIONS EQUIPMENT CO.,LTD.
(Beijing, CN)

Family ID: 88834560

Appl. No.: 18/859160

**Filed (or PCT
Filed):** May 10, 2023

PCT No.: PCT/CN2023/093309

Foreign Application Priority Data

CN 202210530972.6

May. 16, 2022

Publication Classification

Int. Cl.: H04W36/08 (20090101); H04W36/00 (20090101)

U.S. Cl.:

CPC H04W36/08 (20130101); H04W36/0033 (20130101); H04W36/0064 (20230501);

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This disclosure claims is a National Stage of International Application No. PCT/CN2023/093309, filed on May 10, 2023, which priority to Chinese Patent Application No. 202210530972.6, filed to China National Intellectual Property Administration on May 16, 2022 and entitled “INTERACTION METHOD AND RELATED DEVICE”. The two applications are hereby incorporated by reference in their entirety.

FIELD

[0002] The present disclosure relates to the field of interaction technologies and, in particular, to an interaction method and related devices.

BACKGROUND

[0003] In the 5.sup.th generation (5G) system, the structure of a base station evolves, and one base station includes one centralized unit (CU) entity and a plurality of distributed unit (DU) entities.

[0004] In interaction scenarios such as initial access of a user equipment (UE), access of the UE moving from a currently accessed DU entity to another DU entity, intra-handover of the DU entity, and the like, a plurality of DU entities need to interact with the CU entity.

[0005] In exemplary technologies, the way in which the plurality of DU entities interact with the CU entity is as follows: after the interaction between one DU entity and the CU entity is completed, the interaction between the next DU entity and the CU entity is to be completed. Assuming that an interaction time between the DU entity and the CU entity is T , an interaction time between one DU entity and the CU entity is $2T$, and if the number of the DU entities interacting with the CU entity is N , the interaction time between the plurality of DU entities and the CU entity is $2NT$.

[0006] It can be seen that the interaction time required in an interaction scenario involving the plurality of DU entities and the CU entity is too long, which results in a long time required for achieving the objective of the interaction scenario, and therefore the efficiency of achieving the objective of the interaction scenario is low.

SUMMARY

[0007] The present disclosure provides an interaction method and related devices, to solve the problem of relatively low efficiency of achieving the objective of an interaction scenario between a plurality of DU entities and a CU entity.

[0008] In one embodiment of the present disclosure provides an interaction method, applied to a centralized unit entity, and including: [0009] receiving first information sent in parallel by a plurality of first distributed unit DU entities accessed by a user equipment UE; and [0010] sending, to each first DU entity, second information corresponding to the first DU entity in parallel.

[0011] In one embodiment, before the sending, to each first DU entity, the second information corresponding to the first DU entity in parallel, the method further includes: [0012] determining a plurality pieces of first information to be sent to the first DU entities; and [0013] determining the second information of the first DU entity according to the plurality pieces of first information to be sent to the first DU entity.

[0014] In one embodiment, after the sending, to each first DU entity, the second information corresponding to the first DU entity in parallel, the method further includes: [0015] receiving a response message sent in parallel by each first DU entity.

[0016] In one embodiment, the second information is an RRC reconfiguration message, and after the sending, to each first DU entity, the second information corresponding to the first DU entity in parallel, the method further includes: receiving an RRC reconfiguration completion message sent in parallel by each first DU entity.

[0017] In one embodiment, the plurality of first DU entities are DU entities currently accessed by the UE, and after the sending, to each first DU entity, the second information corresponding to the first DU entity in parallel, the method further includes: [0018] receiving a context modification response message of the UE sent in parallel by each first DU entity; [0019] sending a context establishment request of the UE to a plurality of second DU entities in parallel, where the second DU entities are DU entities to be accessed by the UE; [0020] receiving a context establishment response message of the UE sent in parallel by each second DU entity; and [0021] sending a radio resource control RRC reconfiguration message to each first DU entity in parallel.

[0022] In one embodiment, after the sending the radio resource control RRC reconfiguration message to each first DU entity in parallel, the method further includes: [0023] receiving an RRC reconfiguration completion message sent in parallel by each second DU entity; [0024] sending a context release message to each first DU entity in parallel; and receiving a context release completion message sent in parallel by each first DU entity.

[0025] In one embodiment, after the receiving the RRC reconfiguration completion message sent in parallel by each second DU entity, the method further includes: [0026] receiving a plurality of interaction messages sent in parallel by the plurality of second DU entities; [0027] sending the plurality of interaction messages corresponding to the plurality of second DU entities to each second DU entity in parallel; and [0028] receiving a response message sent in parallel by each second DU entity.

[0029] In one embodiment, the method further includes: [0030] if the UE moves from a first cell to a second cell, allocating a first parameter corresponding to each first DU entity; [0031] sending in parallel, to each first DU entity, the first parameter corresponding to the first DU entity; and [0032] receiving a second parameter sent in parallel by each first DU entity, and re-establishing connection with each first DU entity; [0033] where the first parameter is used for the first DU entity to send data to the centralized unit entity having the re-established connection with the first DU entity, and the second parameter is used for the centralized unit entity to send data to the first DU entity having the re-established connection with the centralized unit entity.

[0034] In one embodiment, the method further includes: [0035] if the UE is handed over from the plurality of accessed first DU entities to a plurality of third DU entities, allocating a third parameter to each third DU entity, where each third DU entity and each first DU entity are located in the same cell; [0036] sending in parallel, to each third DU entity, the third parameter corresponding to the third DU entity; and [0037] receiving a fourth parameter sent in parallel by each third DU entity, and re-establishing connection with each first DU entity; [0038] where the third parameter is used for the first DU entity to send data to the centralized unit entity having the re-established connection with the first DU entity, and the fourth parameter is used for the centralized unit entity to send data to the first DU entity having the re-established connection with the centralized unit entity.

[0039] In another embodiment of the present disclosure further provides an interaction method, applied to a distributed unit entity, and including: [0040] receiving an indication message sent by a user equipment UE, where the indication message is used to instruct a plurality of distributed unit entities accessed by the UE to send information to a centralized unit CU entity in parallel; [0041] sending first information to the CU entity according to the indication message; and [0042] receiving second information sent by the CU entity.

[0043] In another embodiment of the present disclosure further provides an interaction method, applied to user equipment, and including: [0044] sending an indication message to a plurality of distributed unit DU entities accessed by a user equipment, where the indication message is used to instruct the plurality of DU entities to send information to a centralized unit CU entity in parallel.

[0045] In another embodiment of the present disclosure further provides a centralized unit entity, including: a memory, a transceiver and a processor; [0046] where the memory is configured to store a computer program; the transceiver is configured to receive and send data under a control of

the processor; and the processor is configured to read the computer program in the memory and perform the following operations: [0047] receiving first information sent in parallel by a plurality of first distributed unit DU entities accessed by a user equipment UE; and [0048] sending, to each first DU entity, second information corresponding to the first DU entity in parallel.

[0049] In another embodiment the present disclosure further provides a centralized unit entity, including: [0050] a first receiving unit, configured to receive first information sent in parallel by a plurality of first distributed unit DU entities accessed by a user equipment UE; and [0051] a first sending unit, configured to send, to each first DU entity, second information corresponding to the first DU entity in parallel.

[0052] In another embodiment of the present disclosure further provides a distributed unit entity, including: a memory, a transceiver and a processor; [0053] where the memory is configured to store a computer program; the transceiver is configured to receive and send data under a control of the processor; and the processor is configured to read the computer program in the memory and perform the following operations: [0054] receiving an indication message sent by a user equipment UE, where the indication message is used to instruct a plurality of distributed unit entities accessed by the UE to send information to a centralized unit CU entity in parallel; [0055] sending first information to the CU entity according to the indication message; and [0056] receiving second information sent by the CU entity.

[0057] In another embodiment of the present disclosure further provides a distributed unit entity, including:

[0058] a second receiving unit, configured to receive an indication message sent by a user equipment UE, where the indication message is used to instruct a plurality of distributed unit entities accessed by the UE to send information to a centralized unit CU entity in parallel; and [0059] a second sending unit, configured to send first information to the CU entity according to the indication message; [0060] the second receiving unit is further configured to receive second information sent by the CU entity.

[0061] In another embodiment of the present disclosure further provides a user equipment, including: a memory, a transceiver and a processor; [0062] where the memory is configured to store a computer program; the transceiver is configured to receive and send data under a control of the processor; and the processor is configured to read the computer program in the memory and perform the following operations: [0063] sending an indication message to a plurality of distributed unit DU entities accessed by a user equipment, where the indication message is used to instruct the plurality of DU entities to send information to a centralized unit CU entity in parallel.

[0064] In another embodiment of the present disclosure further provides a user equipment, including: [0065] a third sending unit, configured to send an indication message to a plurality of distributed unit DU entities accessed by a user equipment, where the indication message is used to instruct the plurality of DU entities to send information to a centralized unit CU entity in parallel.

[0066] In another embodiment of the present disclosure further provides a processor-readable storage medium, where the processor-readable storage medium stores a computer program, and the computer program is used to enable the processor to execute the above method.

[0067] The present disclosure provides an interaction method and related devices, after receiving the first information sent by the plurality of DU entities in parallel, the CU entity sends the second information to each DU entity, that is, the CU entity interacts with the plurality of DU entities in parallel, to save an interaction time between the plurality of DU entities and the CU entity, shortening a total interaction time of an interaction scenario between the plurality of DU entities and the CU entity, and further improving the efficiency of achieving the objective of the interaction scenario between the plurality of DU entities and the CU entity.

[0068] It should be understood that, the above-described content in the summary section is not intended to limit the critical or prominent features of embodiments of the present disclosure, nor is

it intended to limit the scope of the present disclosure. Other features of the present disclosure will be easily understood by the following description.

Description

BRIEF DESCRIPTION OF DRAWINGS

[0069] To describe technical solutions in the present disclosure more clearly, the following briefly introduces accompanying drawings required for describing the embodiments or the related art. Apparently, the accompanying drawings in the following description show some embodiments of the present disclosure.

[0070] FIG. 1 is a schematic diagram of an application scenario according to an embodiment of the present disclosure.

[0071] FIG. 2 is a schematic diagram of interaction between a DU entity and a CU entity involved in the present disclosure.

[0072] FIG. 3 is another schematic diagram of interaction between a DU entity and a CU entity involved in the present disclosure.

[0073] FIG. 4 is a schematic flowchart of a centralized unit entity according to an embodiment of the present disclosure.

[0074] FIG. 5 is a schematic flowchart of a centralized unit entity according to another embodiment of the present disclosure.

[0075] FIG. 6 is a schematic flowchart of a centralized unit entity according to yet another embodiment of the present disclosure.

[0076] FIG. 7 is a schematic flowchart of a centralized unit entity according to still another embodiment of the present disclosure.

[0077] FIG. 8 is a schematic flowchart of a centralized unit entity according to further still another embodiment of the present disclosure.

[0078] FIG. 9 is a schematic flowchart of a distributed unit entity according to an embodiment of the present disclosure.

[0079] FIG. 10 is a schematic flowchart of user equipment according to an embodiment of the present disclosure.

[0080] FIG. 11 is a hardware structural schematic diagram of a centralized unit entity according to the present disclosure.

[0081] FIG. 12 is a schematic diagram of functional modules of a centralized unit entity according to the present disclosure;

[0082] FIG. 13 is a hardware structural schematic diagram of a distributed unit entity according to the present disclosure.

[0083] FIG. 14 is a schematic diagram of functional modules of a distributed unit entity according to the present disclosure.

[0084] FIG. 15 is a hardware structural schematic diagram of user equipment according to the present disclosure.

[0085] FIG. 16 is a schematic diagram of functional modules of user equipment according to the present disclosure.

DESCRIPTION OF EMBODIMENTS

[0086] In the present disclosure, the term “and/or” describes an association relationship between associated objects, and indicates that three relationships may exist. For example, A and/or B may indicate three cases: A exists separately, A and B exist simultaneously, and B exists separately. The character ‘/’ generally indicates an ‘or’ relationship between the associated objects.

[0087] The term “a plurality of” in embodiments of the present disclosure means two or more than two, and other quantifiers are similar thereto.

[0088] The following clearly and completely describes the embodiments of the present disclosure with reference to the accompanying drawings in the embodiments of the present disclosure. Apparently, the described embodiments are merely a part rather than all of the embodiments of the present disclosure.

[0089] Embodiments of the present disclosure provide an interaction method and related devices, to solve the problem of relatively low efficiency of achieving the objective of an interaction scenario between a plurality of DU entities and a CU entity.

[0090] The method and the apparatus involved in the present disclosure are based on the same application concept, and since the principle of the method and the apparatus for solving the problem is similar, the implementation of the apparatus and the method can be referred to each other, and redundant description will be omitted.

[0091] The embodiments of the present disclosure may be applicable to various systems, especially, the 5G system. For example, the applicable system may be a global system of mobile communication (global system of mobile communication, GSM), a code division multiple access (code division multiple access, CDMA) system, and a wideband code division multiple access (wideband code division multiple access, WCDMA) general packet radio service (general packet radio service, GPRS) system, a long term evolution (long term evolution, LTE) system, an LTE frequency division duplex (frequency division duplex, FDD) system, an LTE time division duplex (time division duplex, TDD) system, a long term evolution advanced (long term evolution advanced, LTE-A) system, a universal mobile telecommunication system (universal mobile telecommunication system, UMTS), a worldwide interoperability for microwave access (worldwide interoperability for microwave access, WiMAX) system, a 5G new radio (New Radio NR) system, etc. All these systems include a terminal device and a network device. The systems can further include a core network part, such as an Evolved Packet System (Evolved Packet System, EPS), a 5G system (5GS), and the like.

[0092] The terminal device involved in the embodiments of the present disclosure may refer to a device providing voice and/or data connectivity for a user, a handheld device having a wireless connection function, or other processing devices connected to a wireless modem, etc. In different systems, the name of the terminal device may also be different, for example, in the 5G system, a terminal device may be referred to as user equipment (User Equipment, UE). A wireless terminal device may communicate with one or more core networks (core network, CN) via radio access network (radio access network, RAN). The wireless terminal device may be a mobile terminal device, such as a mobile phone (or referred to as a “cellular” phone) and a computer having the mobile terminal device, and may be, for example, portable, pocket-sized, handheld, computer built-in, or vehicle-mounted mobile apparatuses, which exchange language and/or data with the radio access network, for example, devices such as a personal communication service (Personal Communication Service, PCS) phone, a cordless phone, a session initiated protocol (Session Initiated Protocol, SIP) phone, a wireless local loop (Wireless Local Loop, WLL) station, and personal digital assistant (Personal Digital Assistant PDA), etc. The wireless terminal device may also be referred to as a system, a subscriber unit, a subscriber station, a mobile station, a mobile, a remote station, an access point, a remote terminal, an access terminal, a user terminal, a user agent, and a user device, which is not limited in the embodiments of the present disclosure.

[0093] The network device involved in the embodiments of the present disclosure may be a base station. The base station may include a plurality of cells providing services for a terminal. Depending on the specific application scenario, a base station may also be referred to as an access point, or a device that communicates with a wireless terminal device through one or more sectors over an air interface in access network, or other names. The network device can be used to exchange a received air frame with an internet protocol (Internet Protocol, IP) packet, and serves as a router between a wireless terminal device and the rest of the access network, where the rest of the access network may include Internet protocol (IP) communication network. The network device

may also coordinate management of attributes of the air interface. For example, the network device involved in the embodiments of the present disclosure may be a network device (Base Transceiver Station, BTS) in Global System for Mobile Communications (GSM) or Code Division Multiple Access (CDMA); may also be a network device (NodeB) in Wide-band Code Division Multiple Access (WCDMA); may also be an evolutionary network device (evolutional Node B, eNB or e-NodeB) in the long term evolution (LTE) system, a 5G base station (gNB) in a 5G network architecture (next generation system); may also be a home evolved base station (Home evolved Node B, HeNB), a relay node, a femto base station, a pico base station, etc., which are not limited in the embodiments of the present disclosure. In some network structures, a network device may include a centralized unit (CU) entity and a distributed unit (DU) entity. The centralized unit and the distributed unit may also be arranged in a geographically separated manner.

[0094] A network device and a terminal device may respectively use one or more antennas to perform multi-input multi-output (Multi Input Multi Output, MIMO) transmission, and the MIMO transmission may be single-user MIMO (Single User MIMO, SU-MIMO) or multi-user MIMO (Multiple User MIMO, MU-MIMO). According to the form and the quantity of the antenna combination, the MIMO transmission may be 2D-MIMO, 3D-MIMO, FD-MIMO or massive-MIMO, and may also be diversity transmission, precoding transmission or beam forming transmission, etc.

[0095] In order to better describe the embodiments of the present disclosure, the following explains nouns appearing in the embodiments of the present disclosure. [0096] UE: User Equipment; [0097] DU: Distributed Unit; [0098] gNB-DU: the next generation NodeB Distributed Unit, or a distributed unit of a 5G base station; [0099] CU: Centralized Unit; [0100] gNB-CU: the next generation NodeB Centralized Unit, or a centralized unit of a 5G base station; [0101] RRC: Radio Resource Control; [0102] F1AP: F1 application protocol; [0103] AMF: Access and Mobility Management; [0104] C-RNTI: a temporary identifier; [0105] gNB-DU ID: an identifier of a distributed unit entity of the 5G base station; [0106] RLC: Radio Link Control; [0107] UL GTP TEID: a field of the uplink GPRS tunneling protocol; [0108] GTP: GPRS Tunneling Protocol; [0109] GPRS: General packet radio service; [0110] UL: Uplink; [0111] PDCP: Packet Data Convergence Protocol; [0112] DL: Downlink; [0113] PDU: Protocol Data Unit; [0114] PDC: Primary Domain Controller; [0115] PPDU: Presentation Protocol Data Unit; [0116] NR: New Radio.

[0117] FIG. 1 is a schematic diagram of an application scenario according to an embodiment of the present disclosure. As shown in FIG. 1, the interaction method provided in this embodiment relates to UE, a plurality of gNB-DU entities and a gNB-CU entity. The plurality of gNB-DU entities are, for example, gNB-DU entity 1, gNB-DU entity 2, and gNB-DU entity 3. UE accesses each gNB-DU entity, and the CU entity can send a message to each accessed gNB-DU entity, where the message is used to instruct each gNB-DU entity to send a message to the gNB-CU entity in parallel or in series. The parallel sending of the message refers to that the plurality of gNB-DU entities send a message to the gNB-CU entity in the same time period. The serial sending of the message refers to that after one gNB-DU entity among the plurality of gNB-DU entities accessed by the UE completes information interaction with the gNB-CU entity, another gNB-DU entity accessed by the UE performs information interaction with the gNB-CU entity again. If the plurality of gNB-DU entities send a message to the gNB-CU entity in parallel, the gNB-CU entity may also send a message to the plurality of gNB-DU entities in parallel. The interaction scenarios between the plurality of DU entities and the CU entity involved in the present disclosure include initial access of the UE, inter-mobility of the gNB-DU entities, and intra-handover of the gNB-DU entity. The initial access of the UE refers to a scenario in which the UE accesses a plurality of gNB-DU entities. The inter-mobility of the gNB-DU entities refers to that the UE is handed over from a plurality of accessed gNB-DU entities to another plurality of gNB-DU entities. The intra-handover of the gNB-DU entity refers to that the UE moves from one cell to another cell, and the UE

switches after the UE accessing a gNB-DU entity of a cell before the UE moves to accessing a gNB-DU entity after the UE moves; or, the intra-handover of the gNB-DU entity refers to that the gNB-DU entity accessed by the UE in a cell is handed over to another gNB-DU entity in the cell.

[0118] The initial access of the UE and the inter-mobility of the gNB-DU entities involve many flows, and the flows of the two interaction scenarios will be described below.

[0119] Referring to FIG. 2, the flow of the initial access of UE is as follows.

[0120] 1. A UE sends an RRC establishment request to a DU entity (hereinafter gNB-DU entity is referred to as DU entity for short).

[0121] 2. The DU entity transmits initial uplink radio resource control information to a CU entity (hereinafter gNB-CU entity is referred to as for short).

[0122] 3. The CU entity transmits downlink radio resource control information to the DU entity.

[0123] 4. RRC Setup (RRC establishment) between the DU entity and the UE.

[0124] 5. The UE sends information about completion of radio resource control establishment to the DU entity.

[0125] 6. The DU entity transmits an uplink radio resource control information to the CU entity.

[0126] 7. The CU entity transmits an initial UE message to AMF.

[0127] 8. The AMF sends an initial context establishment request to the CU entity.

[0128] 9. The CU entity sends a context establishment request of the UE to the DU entity.

[0129] 10. The DU entity sends a security mode command to the UE.

[0130] 11. The DU entity sends a context establishment response of the UE to the CU entity.

[0131] 12. The UE sends security mode completion to the DU entity.

[0132] 13. The DU entity transmits an uplink radio resource control information to the CU entity.

[0133] 14. The CU entity transmits a downlink radio resource control information to the DU entity.

[0134] 15. The DU entity sends an RRC reconfiguration request to the UE.

[0135] 16. The UE sends RRC reconfiguration completion information to the DU entity.

[0136] 17. The DU entity transmits an uplink radio resource control information to the CU entity.

[0137] 18. The CU entity sends an initial context establishment response to the AMF.

[0138] Referring to FIG. 3, the flow of the inter-mobility of the gNB-DU entities is as follows.

[0139] After the UE accesses a Source gNB-DU entity (hereinafter referred to as a source DU entity for short), the CU entity sends downlink user data to the UE and the source DU entity accessed by the UE, and the UE sends downlink user data to the source DU entity and the CU entity.

[0140] 1. UE sends a measurement report to a source DU entity.

[0141] 2. The source DU entity transmits an uplink radio resource control information to the CU entity.

[0142] 2a. The CU entity sends a context modification request of the UE to the source DU entity.

[0143] 2b. The source DU entity sends a context modification response of the UE to the CU entity.

[0144] 3. The CU entity sends a context modification request of the UE to a Target gNB-DU entity (hereinafter referred to as a target DU entity for short) to be accessed by the UE.

[0145] 4. The target DU entity sends a context modification response of the UE to the CU entity.

[0146] 5. The CU entity sends a context modification request of the UE to the source DU entity, where the context modification request is RRC reconfiguration.

[0147] 6. The source DU entity sends an RRC reconfiguration request to the UE.

[0148] 7. The source DU entity sends a context establishment response of the UE to the CU entity in a downlink data transmission state.

[0149] 8. Random access process of the UE and the target DU entity, where in this process, the target DU entity transmits a message to the CU entity in a downlink data transmission state.

[0150] 9. The UE sends an RRC reconfiguration completion message to the target DU entity in a downlink data transmission state.

[0151] 10. The target DU entity transmits the RRC reconfiguration completion message to the CU

entity.

[0152] **11.** The CU entity sends a context release command of the UE to the source DU entity.

[0153] **12.** The source DU entity sends a context release completion message of the UE to the CU entity.

[0154] It should be noted that, in FIG. 2, an example in which a DU entity accessed by the UE interacts with the UE and the CU entity is illustrated, and a process in which other DU entities accessed by the UE interacts with the UE and the CU entity is the same as the process shown in FIG. 2. In FIG. 3, a source DU entity accessed by the UE and a target DU entity to be accessed are taken as an example for illustration, and the interaction between the UE and other accessed source DU entities and the interaction involved when the UE switches to other target DU entities are consistent with the flow shown in FIG. 3.

[0155] The present disclosure provides an interaction method.

[0156] Referring to FIG. 4, FIG. 4 is a schematic flowchart of an interaction method according to an embodiment of the present disclosure, which is applied to a centralized unit entity. The method includes the following steps.

[0157] Step **S101**: receive first information sent in parallel by a plurality of first distributed unit DU entities accessed by a user equipment UE.

[0158] In this embodiment, the centralized unit entity refers to an entity device of the CU entity, and a distributed unit entity refers to an entity device of the DU entity.

[0159] The UE selects a plurality of DU entities for access, and a DU entity accessed by the UE is defined as a first DU entity. After the UE accesses the plurality of DU entities, the plurality of DU entities interact with the CU entity. In an interaction scenario between the plurality of first DU entities and the CU entity, the plurality of first DU entities send information to the CU entity in parallel, where the information is defined as first information, i.e., the CU entity receives the first information sent in parallel by the plurality of first DU entities accessed by the UE.

[0160] After accessing the plurality of first DU entities, the UE may determine that the plurality of first DU entities send information to the CU entity in parallel or in series.

[0161] In an example, the UE sends indication information to a plurality of accessed first DU entities, and if the indication information indicates that the plurality of first DU entities send information to the CU entity in parallel, when the plurality of first DU entities need to interact with the CU entity, the plurality of first DU entities send the first information to the CU entity in parallel.

[0162] Step **S102**: send, to each first DU entity, second information corresponding to the first DU entity in parallel.

[0163] After receiving the first information sent by the plurality of first DU entities in parallel, the CU entity sends the second information to each first DU entity uniformly.

[0164] In an example, if the plurality of first DU entities interact with the CU entity in a scenario of initial access of the UE, the first information may be initial uplink radio resource control information transmitted to the CU entity by each first DU entity after the first DU entity receives an RRC establishment request, and the second information is downlink radio resource control information transmitted to each first DU entity by the CU entity. The initial uplink radio resource control information includes C-RNTI (temporary identifier) and gNB-DU identifier (ID) allocated to each first DU entity by the UE, that is, each first DU entity sends its own C-RNTI and gNB-DU ID to the CU entity through first information. After receiving the first information, the CU entity may generate the second information, where the second information includes gNB-CU UE F1AP ID allocated by the CU entity and an RRC message generated by the CU entity. The gNB-CU UE F1AP ID refers to an identifier of the F1 application protocol between the CU entity and the UE, and the RRC message is radio resource control establishment information. After receiving the second information, the plurality of first DU entities send the RRC message in the second information to the UE.

[0165] In another example, referring to steps **6**, **9**, **11**, **13**, **14** and **17** in FIG. 2, the interaction of the signaling between the UE and the AMF is involved, and the function of the plurality of first DU entities and the CU entity is to encapsulate the signaling, and then transparently transmit the encapsulated signaling to the AMF or the UE, and the interaction of the signaling between the CU entity and the plurality of first DU entities is not involved. When the first information is signaling sent by the UE to the CU entity via the plurality of first DU entities, the second information is signaling returned by the AMF to the plurality of first DU entities via the CU entity, and each first DU entity sends the received signaling sent by the AMF to the UE.

[0166] In yet another example, the initial access of the UE may involve RRC reconfiguration, that is, the second information is an RRC reconfiguration message sent by the CU entity to the plurality of first DU entities, and each first DU entity sends RRC reconfiguration to the CU entity. After completing the RRC reconfiguration, the UE sends an RRC reconfiguration completion message to each first DU entity. Each first DU entity sends the RRC reconfiguration completion message to the CU entity in parallel, that is, the CU entity receives an RRC reconfiguration completion message sent by each first DU entity in parallel.

[0167] In this embodiment, after receiving the first information sent by the plurality of DU entities in parallel, the CU entity sends the second information to each DU entity, that is, the CU entity interacts with the plurality of DU entities in parallel, to save an interaction time between the plurality of DU entities and the CU entity, shortening a total interaction time of an interaction scenario between the plurality of DU entities and the CU entity, and further improving the efficiency of achieving the objective of the interaction scenario between the plurality of DU entities and the CU entity.

[0168] Referring to FIG. 5, FIG. 5 is a schematic flowchart of an interaction method according to another embodiment of the present disclosure. Based on the embodiment shown in FIG. 5, before step **S102**, the method further includes the following steps.

[0169] Step **S201**, determine a plurality pieces of first information to be sent to the first DU entity.

[0170] In this embodiment, after the UE accesses the plurality of first DU entities, each first DU entity may interact with each other. Each first DU entity needs to interact with each other via the CU entity, that is, the first information includes a message to be sent by a first DU entity to other first DU entities, and the other first DU entities is a first DU entity other than the first DU entity sending the first information. The first information includes an identifier of the DU entity required to be interacted with, that is, the CU entity determines, according to the identifier of the DU entity in the first information, a plurality pieces of first information to be sent to the first DU entity. For example, a first DU entity accessed by the UE includes DU entity **1**, DU entity **2** and DU entity **3**, message a of the DU entity **1** carries identifiers **2** and **3**, where the message a is a message sent by the DU entity **1** to the DU entity **2** and the DU entity **3**. Message b of the DU entity **2** carries identifiers **1** and **3**, and then the message b of the DU entity **2** is a message sent to the DU entity **1** and the DU entity **3**. Message c of the DU entity **3** carries identifiers **1** and **2**, and the message c of the DU entity **3** is a message sent to the DU entity **2** and the DU entity **1**. Therefore, respective pieces of first information to be sent to the DU entity **1** are message b and message c, respective pieces first information to be sent to the DU entity **2** are message a and message c, and respective pieces first information to be sent to the DU entity **3** are message a and message b.

[0171] Step **S202**, determine the second information of the first DU entity according to the plurality pieces of first information to be sent to the first DU entity.

[0172] The CU entity integrates the plurality pieces of first information of the first DU entity into the second information of the first DU entity. For example, if respective pieces of first information to be sent to the DU entity **1** are message b and message c, the second information of the DU entity **1** includes the message b and the message c. If respective pieces of first information to be sent to the DU entity **2** are message a and message c, the second information of the DU entity **2** includes the message a and the message c. If respective pieces of first information to be sent to the DU

entity 3 are message a and message b, the second information of the DU entity 3 includes the message a and the message b.

[0173] The plurality of first DU entities perform interaction, which may be that a first DU entity sends the received parameter transmitted by the CU entity to other first DU entities, where the parameter is, for example, gNB-DU UE F1AP ID and gNB-DU ID, i.e., the second information includes gNB-DU UE F1AP ID and gNB-DU ID.

[0174] In addition, after receiving the second information including a parameter such as gNB-DU UE F1AP ID, gNB-DU ID or the like, each first DU entity sends in parallel to the CU entity a response indicating that the second information has been received. That is, after step S102, the method further includes: the CU entity receives a response message sent in parallel by each first DU entity, where the response message is used to prompt the first DU entity to respond to the second information. For example, the first DU entity stores gNB-DU UE F1AP ID and gNB-DU ID, and the first DU entity sends a response message to the CU entity, i.e., the response message is used to prompt that the first DU entity has stored gNB-DU UE F1AP ID and gNB-DU ID.

[0175] In this embodiment, if each first DU entity performs interaction, the CU entity integrates the respective pieces of first information to be sent to the first DU entity as the second information of the first DU entity, and then sends the second information of each first DU entity in parallel to the corresponding first DU entity, to complete interaction between the first DU entities in parallel, to save interaction time between the first DU entities.

[0176] Referring to FIG. 6, FIG. 6 is a schematic flowchart of an interaction method according to yet another embodiment of the present disclosure. Based on the embodiment shown in FIG. 4 or FIG. 5, after step S102, the method further includes the following steps.

[0177] Step S301, receive a context modification response message of the UE sent in parallel by each first DU entity.

[0178] In this embodiment, an interaction scenario between the plurality of DU entities and the CU entity is inter-mobility of gNB-DU entities, that is, the UE is switched from accessing the plurality of first DU entities to a plurality of second DU entities, where the second DU entities are DU entities to be accessed by the UE, and the plurality of first DU entities are DU entities CU entity accessed by the UE.

[0179] In this embodiment, the first information is an uplink RRC message, and the second information is a context modification request of the UE. After receiving the context modification request of the UE, each first DU entity sends a context modification response message of the UE to the CU entity in parallel, i.e., the CU entity receives a context modification response message of the UE sent by each first DU entity in parallel, i.e., each first DU entity notifies the CU entity that it has completed the context modification of the UE.

[0180] Step S302, send a context establishment request of the UE to a plurality of second DU entities in parallel, where the second DU entities are DU entities to be accessed by the UE.

[0181] Each second DU entity is a DU entity to be accessed by the UE. After receiving the context modification response message of the UE sent by each first DU entity, the CU entity sends the context establishment request of the UE to the plurality of second DU entities in parallel.

[0182] Step S303, receive a context establishment response message of the UE sent in parallel by each second DU entity.

[0183] After receiving the context establishment request of the UE, each second DU entity is connected to the UE through an identifier of the UE in the context establishment request of the UE, and the UE accesses the plurality of second DU entities, that is, each second DU entity completes context establishment of the UE. Context establishment of the UE refers to establishing connection between the plurality of second DU entities and the UE for information transmission, and context modification of the UE refers to modifying a DU entity accessed by the UE.

[0184] After establishing connection with the UE, each second DU entity sends a context establishment response message to the CU entity in parallel, that is, each second DU entity notifies

the CU entity that each second DU entity has been connected to the UE.

[0185] Step **S304**, send a radio resource control RRC reconfiguration message to each first DU entity in parallel.

[0186] After establishing connection with each second DU entity, the UE needs to perform RRC reconfiguration, that is, the CU entity sends the RRC reconfiguration message to each first DU entity. After receiving the RRC reconfiguration message, each first DU entity directly sends the RRC reconfiguration message to the UE without parsing same, i.e., the CU entity transparently transmits the RRC reconfiguration message to the UE via each first DU entity.

[0187] In an example, the UE may perform RRC reconfiguration, that is, establish radio resource control between the UE and each second DU entity. After completing the RRC reconfiguration, the UE sends an RRC reconfiguration completion message to each second DU entity. Each second DU entity sends an RRC reconfiguration completion message to the CU entity in parallel, that is, the CU entity receives the RRC reconfiguration completion message sent by each second DU entity in parallel. In this case, each first DU entity includes a context session with the UE. In order to free up the storage space of each first DU entity, the CU entity sends a context release message to each first DU entity in parallel, i.e., notifying each first DU entity to release the context session associated with the UE. After releasing the context session, each first DU entity sends a context release completion message to the CU entity in parallel, that is, the CU entity receives a context release completion message sent by each first DU entity in parallel.

[0188] After sending the RRC reconfiguration completion message to the CU entity in parallel, each second DU entity has established RRC connection. Each second DU entity can perform interaction with each other. Each second DU entity sends an interaction message to the CU entity in parallel, that is, the CU entity receives the interaction messages sent by the plurality of second DU entities, where the interaction message includes a message to be sent by the second DU entity to other second DU entities, and the other second DU entities is a second DU entity other than the second DU entity sending the interaction message. The interaction message includes an identifier of the DU entity required to be interacted with, that is, the CU entity determines, according to the identifier of the DU entity in the interaction message, a plurality of interaction messages to be sent to the second DU entity. For example, a second DU entity accessed by the UE includes DU entity **4**, DU entity **5** and DU entity **6**, message d of the DU entity **4** carries identifiers **5** and **6**, and message d is a message sent by DU entity **4** to DU entity **5** and DU entity **6**. Message e of DU entity **5** carries identifiers **4** and **6**, and then message e of DU entity **5** is a message sent to DU entity **4** and DU entity **6**. Message f of DU entity **6** carries identifiers **4** and **5**, and then message f of DU entity **6** is a message sent to DU entity **5** and DU entity **4**. Therefore, interaction messages to be sent to DU entity **4** are message e and message f, interaction messages to be sent to DU entity **5** are message d and message f, and interaction messages to be sent to DU entity **6** are message d and message e.

[0189] The CU entity sends a plurality of interaction messages corresponding to the second DU entity to each second DU entity, for example, respective interaction messages sent to DU entity **4** are message e and message f; respective interaction messages sent to DU entity **5** are message d and message f; and respective interaction messages sent to DU entity **6** are message d and message e.

[0190] The plurality of second DU entities perform interaction, which may be that a second DU entity sends the received parameter transmitted by the CU entity to other second DU entities, where the parameter is, for example, gNB-DU UE F1AP ID and gNB-DU ID, i.e., the second information includes gNB-DU UE F1AP ID and gNB-DU ID. In addition, after receiving the second information including a parameter such as gNB-DU UE F1AP ID, gNB-DU ID or the like, each second DU entity in parallel sends to the CU entity a response indicating that the second information has been received. That is, after step **S304**, the method further includes: the CU entity receives a response message sent in parallel by each second DU entity, where the response message

is used to prompt the second DU entities to respond to the second information. For example, the second DU entity stores gNB-DU UE F1AP ID and gNB-DU ID, and the second DU entity sends a response message to the CU entity, that is, the response message is used to prompt that the second DU entity has stored gNB-DU UE F1AP ID and gNB-DU ID.

[0191] In this embodiment, based on the context modification response message of the UE sent in parallel by each first DU entity, the CU entity sends the context establishment request of the UE to the plurality of second DU entities in parallel, and the UE is switched from accessing the first DU entities to accessing the second DU entities. Furthermore, the CU entity performs parallel information interaction with the plurality of first DU entities, and the CU entity performs parallel information interaction with the plurality of second DU entities, the time for the UE to switch from accessing the first DU entities to accessing the second DU entities is saved.

[0192] Referring to FIG. 7, FIG. 7 is a schematic flowchart of an interaction method according to still another embodiment of the present disclosure. Based on the embodiment shown in any one of FIG. 4 to FIG. 6, the interaction method further includes the following steps.

[0193] Step **S401**, if the UE moves from a first cell to a second cell, allocate a first parameter corresponding to each first DU entity.

[0194] Step **S402**, send in parallel, to each first DU entity, the first parameter corresponding to the first DU entity.

[0195] In this embodiment, the interaction scenario between the plurality of first DU entities and the CU entity is intra-handover of a gNB-DU entity. Specifically, the UE moves from one cell (a first cell) to a second cell, and each first DU entity accessed by the UE do not change, but the UE needs to change a parameter of the first cell to a parameter of the second cell. In other words, the cell where the UE is located changes, and each first DU entity needs to be re-established with the CU entity based on the cell to which the UE moves. The first cell and the second cell refer to communication cells.

[0196] When the UE interacts with the CU entity through the plurality of DU entities, the CU entity can position the UE to determine a position of the UE, or an interaction message from the UE to the CU entity includes the position of the UE.

[0197] The CU entity may determine whether the UE moves to an arbitrary second cell from the first cell in which the UE is CU entity located, based on the location of the UE. If it is detected that the UE moves from the first cell to the second cell, intra-handover of the gNB-DU entity needs to be performed, and in this case, the CU entity sends the first parameter to each first DU entity. The first parameter may be new UL GTP TEID of the first DU entities.

[0198] Step **S403**, receive a second parameter sent in parallel by each first DU entity, and re-establish connection with each first DU entity.

[0199] After receiving the first parameter, each first DU entity may send the second parameter to the CU entity in parallel. The second parameter may be new DL GTP TEID provided by each first DU entity.

[0200] Specifically, after receiving the first parameter, i.e., after receiving new UL GTP TEID, each first DU entity sends the UL PDC PDU to the CU entity by using the previous UL GTP TEID until RLC is re-established between the CU entity and the first DU entities. After the RLC is established between the first DU entities and the CU entity, the first DU entities send data to the CU entity by using the new UL GTP TEID.

[0201] After receiving the second parameter, i.e., after receiving the new UL GTP TEID provided by each first DU entity, the CU entity sends DL PDCP PDU to each first DU entity by using the previous DL GTP TEID provided by each first DU entity, until the CU entity performs PDCP re-establishment or PDCP data recovery, and then the CU entity sends data to the first DU entities by using the new DL GTP TEID of the first DU entities.

[0202] It can be seen from the above that, the first parameter is used for the first DU entity to send data to the CU entity having the re-established connection with the first DU entity, and the second

parameter is used for the CU entity to send data to the first DU entity having the re-established connection with the centralized unit entity.

[0203] It should be noted that, for ease of description, step **S401** to step **S403** shown in FIG. 7 are located after step **S102**, but step **S401** to step **S403** may be located at any position of step **S101** and step **S102**.

[0204] In this embodiment, if the UE moves from the first cell to the second cell, the CU entity allocates a first parameter corresponding to each first DU entity, and each first DU entity in the second cell sends data to the CU entity based on the first parameter, and each first DU entity also sends a second parameter to the CU entity in parallel, and the CU entity sends data to each first DU entity in the second cell based on the second parameter.

[0205] Referring to FIG. 8, FIG. 8 is a schematic flowchart of an interaction method according to further still another embodiment of the present disclosure. Based on the embodiment shown in any one of FIG. 4 to FIG. 6, the interaction method further includes the following steps.

[0206] Step **S501**, if the UE is handed over from the plurality of accessed first DU entities to a plurality of third DU entities, allocate a third parameter to each third DU entity.

[0207] Step **S502**, send in parallel, to each third DU entity, the third parameter corresponding to the third DU entity.

[0208] In this embodiment, the interaction scenario between the plurality of first DU entities and the CU entity is intra-handover of the gNB-DU entity, and the intra-handover of the gNB-DU entity means that the UE is handed over from the plurality of accessed first DU entities to the plurality of third DU entities when the NR is operating, where each first DU entity and each third DU entity are located in the same cell. The third DU entities are DU entities to be accessed by the UE in response to the operation of the NR. In this case, the CU entity may allocate the third parameter to each third DU entity. The third parameter may be UL GTP TEID that the CU entity allocates for each third DU entity.

[0209] Step **S503**, receive a fourth parameter sent in parallel by each third DU entity, and re-establish connection with each first DU entity.

[0210] After receiving the third parameter, each third DU entity sends the fourth parameter to the CU entity in parallel. The fourth parameter may be new DL GTP TEID provided by each third DU entity.

[0211] Specifically, after receiving the third parameter, i.e., after receiving new UL GTP TEID, each third DU entity sends the UL PDC PPDU to the CU entity by using the previous UL GTP TEID until the RLC is established between the CU entity and the third DU entities. After the RLC is established between the third DU entities and the CU entity, the third DU entities send data to the CU entity by using the new UL GTP TEID.

[0212] After receiving the fourth parameter, i.e., after receiving the new UL GTP TEID provided by each third DU entity, the CU entity sends DL PDCP PDU to each third DU entity by using the previous DL GTP TEID provided by each third DU entity, until the CU entity performs PDCP re-establishment or PDCP data recovery, and then the CU entity sends data to the third DU entities by using the new DL GTP TEID of the third DU entities.

[0213] It can be seen from the above that, the third parameter is used for the first DU entity to send data to the CU entity having the re-established connection with the first DU entity, and the fourth parameter is used for the CU entity to send data to the first DU entity having the re-established connection with the centralized unit entity.

[0214] It should be noted that, for ease of description, step **S501** to step **S503** shown in FIG. 8 are located after step **S102**, but step **S501** to step **S503** may be located at any position of step **S101** and step **S102**.

[0215] In this embodiment, if the UE is handed over from the first DU entities to the third DU entities, the CU entity allocates a corresponding third parameter to each third DU entity, and each third DU entity sends data to the CU entity based on the third parameter, and each third DU entity

also sends a fourth parameter to the CU entity in parallel, and the CU entity sends data to each third DU entity based on the fourth parameter.

[0216] Referring to FIG. 9, FIG. 9 is a schematic flowchart of an interaction method according to an embodiment of the present disclosure, which is applied to a distributed unit entity. The interaction method includes the following steps.

[0217] Step **S601**, receive an indication message sent by a user equipment UE, where the indication message is used to instruct a plurality of distributed unit entities accessed by the UE to send information to a centralized unit CU entity in parallel.

[0218] Step **S602**, send first information to the CU entity according to the indication message.

[0219] In this embodiment, the centralized unit entity refers to an entity device of the CU entity, and the distributed unit entity refers to an entity device of the DU entity.

[0220] After accessing a plurality of DU entities, the UE may determine that the plurality of DU entities send information to the CU entity in parallel or in series.

[0221] In an example, the UE sends indication information to a plurality of accessed DU entities, that is, the DU entities receive the indication information sent by the UE. If the indication information indicates that the plurality of DU entities send information to the CU entity in parallel, when the plurality of DU entities need to interact with the CU entity, the plurality of DU entities send the first information to the CU entity in parallel.

[0222] Step **S603**, receive second information sent by the CU entity.

[0223] After receiving the first information sent by the plurality of DU entities in parallel, the CU entity sends the second information to each DU entity uniformly.

[0224] In an example, if the plurality of first DU entities interact with the CU entity in a scenario of initial access of the UE, the first information may be initial uplink radio resource control information transmitted to the CU entity by each first DU entity after the first DU entity receives an RRC establishment request, and the second information is downlink radio resource control information transmitted to each first DU entity by the CU entity. The initial uplink radio resource control information includes C-RNTI (temporary identifier) and gNB-DU ID allocated to each first DU entity by the UE, that is, each first DU entity sends its own C-RNTI and gNB-DU ID to the CU entity through first information. After receiving the first information, the CU entity may generate the second information, where the second information includes gNB-CU UE F1AP ID allocated by the CU entity and an RRC message generated by the CU entity. The gNB-CU UE F1AP ID refers to an identifier of the F1application protocol between the CU entity and the UE, and the RRC message is radio resource control establishment information. After receiving the second information, the plurality of first DU entities send the RRC message in the second information to the UE.

[0225] In another example, referring to steps **6, 9, 11, 13, 14** and **17** in FIG. 2, the interaction of the signaling between the UE and the AMF is involved, and the function of the plurality of first DU entities and the CU entity is to encapsulate the signaling, and then transparently transmit the encapsulated signaling to the AMF or the UE, and the interaction of the signaling between the CU entity and the plurality of first DU entities is not involved. When the first information is signaling sent by the UE to the CU entity via the plurality of first DU entities, the second information is signaling returned by the AMF to the plurality of first DU entities via the CU entity, and each first DU entity sends the received signaling sent by the AMF to the UE.

[0226] In yet another example, the initial access of the UE may involve RRC reconfiguration, that is, the second information is an RRC reconfiguration message sent by the CU entity to the plurality of first DU entities, and each first DU entity sends RRC reconfiguration to the CU entity. After completing the RRC reconfiguration, the UE sends an RRC reconfiguration completion message to each first DU entity. Each first DU entity sends the RRC reconfiguration completion message to the CU entity in parallel, that is, the CU entity receives an RRC reconfiguration completion message sent by each first DU entity in parallel.

[0227] In addition, an interaction scenario between the plurality of DU entities and the CU entity further includes: the plurality of DU entities interacting via the CU entity, inter-mobility of gNB-DU entities and intra-handover of the gNB-DU entity. In these scenarios, the plurality of DU entities may send messages to the CU entity in parallel. After receiving respective messages, the CU entity may send a corresponding message to each DU entity in parallel. Regarding interaction scenarios of sending the message by each DU entity to the CU entity in parallel and sending the message by the CU entity to the plurality of DU entities in parallel, reference is made to the embodiments shown in FIG. 3 to FIG. 8 for details, which are not described herein again.

[0228] In this embodiment, the DU entity receives the indication message sent by the UE; based on the indication message, this DU entity and other DU entities accessed by the UE send the first information to the CU entity in parallel; and then the CU entity sends the second information to each DU entity accessed by the UE in parallel. In the interaction scenario between the plurality of DU entities and the CU entity, the CU entity interacts with the plurality of DU entities in parallel, to save an interaction time between the plurality of DU entities and the CU entity, shortening a total interaction time of an interaction scenario between the plurality of DU entities and the CU entity, and further improving the efficiency of achieving the objective of the interaction scenario between the plurality of DU entities and the CU entity.

[0229] Referring to FIG. 10, FIG. 10 is a schematic flowchart of an interaction method according to an embodiment of the present disclosure, which is applied to user equipment. The interaction method includes the following steps.

[0230] Step S701, send an indication message to a plurality of distributed unit DU entities accessed by a user equipment, where the indication message is used to instruct the plurality of DU entities to send information to a centralized unit CU entity in parallel.

[0231] In this embodiment, the centralized unit entity refers to an entity device of the CU entity, and the distributed unit entity refers to an entity device of the DU entity.

[0232] The UE selects a plurality of DU entities for access. In an example, the UE selects the quantity of DU entities based on a parameter such as transmission bandwidth, data transmission rate or the like required by the UE. If the UE requires a large transmission bandwidth and a high data transmission rate, the UE selects a large number of DU entities for access. If the UE requires a small transmission bandwidth and a low data transmission rate, the UE selects a smaller number of DU entities for access.

[0233] After the UE accesses the plurality of DU entities, an interaction scenario exists between the plurality of DU entities and the CU entity. In an example, data interaction between the UE and the CU entity needs to be performed through the DU entities, and the plurality of DU entities need to perform data interaction with the CU entity. In another example, if the UE needs to change an accessed DU entity, the DU entity currently accessed by the UE needs to perform data interaction with the CU entity, and a plurality of DU entities to be accessed by the UE also need to perform interaction with the CU entity. In addition, in intra-handover of the gNB-DU entity and the interaction between the respective DU entities, the plurality of DU entities are required to perform data interaction with the CU entity.

[0234] In a scenario where the plurality of DU entities perform data interaction with the CU entity, the UE sends indication information to each DU entity, and in an interaction process between the plurality of DU entities and the CU entity, the plurality of DU entities send messages to the CU entity in parallel, and the CU entity then feeds back corresponding messages to the plurality of CU entity in parallel. For the interaction process between the plurality of DU entities and the CU entity and related messages sent in parallel, reference may be made to the embodiments shown in FIG. 4 to FIG. 8, and details are not described herein again.

[0235] In this embodiment, the UE sends the indication message to the plurality of accessed DU entities, and the plurality of DU entities send information to the CU entity in parallel, and the CU entity sends a message to the plurality of DU entities in parallel. In the interaction scenario between

the plurality of DU entities and the CU entity, the CU entity interacts with the plurality of DU entities in parallel, to save an interaction time between the plurality of DU entities and the CU entity, shortening a total interaction time of an interaction scenario between the plurality of DU entities and the CU entity, and further improving the efficiency of achieving the objective of the interaction scenario between the plurality of DU entities and the CU entity.

[0236] An embodiment of the present disclosure provides a centralized unit entity. As shown in FIG. **11**, the centralized unit entity may include a transceiver **1101**, a processor **1102** and a memory **1103**.

[0237] The transceiver **1101** is configured to receive and send data under a control of the processor **1102**.

[0238] In FIG. **11**, the bus architecture may include any quantity of interconnecting buses and bridges, specifically link together various circuits including one or more memories represented by the processor(s) **1102** and a memory represented by the memory **1103**. The bus architecture may also link various other circuits together such as peripherals, voltage regulators, power management circuits or the like, which are well known in the art and, therefore, are not further described herein. A bus interface provides an interface. The transceiver **1101** may be a plurality of components, including a transmitter and a receiver, providing a unit for communicating with various other apparatuses over a transmission medium. The transmission medium includes transmission media such as wireless channels, wired channels, optical cables, etc. The processor **1102** is responsible for managing the bus architecture and general processing, and the memory **1103** can store data used by the processor **1102** when performing an operation.

[0239] The processor **1102** may be a central processing unit (Central Processing Unit, CPU), an application specific integrated circuit (Application Specific Integrated Circuit, ASIC), a field-programmable gate array (Field-Programmable Gate Array, FPGA), or a complex programmable logic device (Complex Programmable Logic Device, CPLD). The processor may also use a multi-core architecture.

[0240] The processor **1102** is configured to execute any method associated with the centralized unit entity provided by the embodiments of the present disclosure according to the obtained executable instructions by invoking the computer program stored in the memory **1103**. The processor and memory may also be physically separated.

[0241] Specifically, when executing the computer program stored in the memory **1103**, the processor **1102** implements the following operations: [0242] receiving first information sent in parallel by a plurality of first distributed unit DU entities accessed by a user equipment UE; and [0243] sending, to each first DU entity, second information corresponding to the first DU entity in parallel.

[0244] In one embodiment, the processor **1102** is further configured to perform the following operations: [0245] determining a plurality pieces of first information to be sent to the first DU entity; and [0246] determining the second information of the first DU entity according to the plurality pieces of first information to be sent to the first DU entity.

[0247] In one embodiment, the processor **1102** is further configured to perform the following operation: [0248] receiving a response message sent in parallel by each first DU entity.

[0249] In one embodiment, the second information is an RRC reconfiguration message, and the processor **1102** is further configured to perform the following operation: [0250] receiving an RRC reconfiguration completion message sent in parallel by each first DU entity.

[0251] In one embodiment, the plurality of first DU entities are DU entities currently accessed by the UE, and the processor **1102** is further configured to perform the following operations: [0252] receiving a context modification response message of the UE sent in parallel by each first DU entity; [0253] sending a context establishment request of the UE to a plurality of second DU entities in parallel, where the second DU entities are DU entities to be accessed by the UE; [0254] receiving a context establishment response message of the UE sent in parallel by each second DU

entity; and [0255] sending a radio resource control RRC reconfiguration message to each first DU entity in parallel.

[0256] In one embodiment, the processor **1102** is further configured to perform the following operations: [0257] receiving an RRC reconfiguration completion message sent in parallel by each second DU entity; [0258] sending a context release message to each first DU entity in parallel; and receiving a context release completion message sent in parallel by each first DU entity.

[0259] In one embodiment, the processor **1102** is further configured to perform the following operations: [0260] receiving a plurality of interaction messages sent in parallel by the plurality of second DU entities; [0261] sending the plurality of interaction messages corresponding to the plurality of second DU entities to each second DU entity in parallel; and [0262] receiving a response message sent in parallel by each second DU entity.

[0263] In one embodiment, the processor **1102** is further configured to perform the following operations: [0264] if the UE moves from a first cell to a second cell, allocating a first parameter corresponding to each first DU entity; [0265] sending in parallel, to each first DU entity, the first parameter corresponding to the first DU entity; and [0266] receiving a second parameter sent in parallel by each first DU entity, and re-establishing connection with each first DU entity; [0267] where the first parameter is used for the first DU entity to send data to the centralized unit entity having the re-established connection with the first DU entity, and the second parameter is used for the centralized unit entity to send data to the first DU entity having the re-established connection with the centralized unit entity.

[0268] In one embodiment, the processor **1102** is further configured to perform the following operations: [0269] if the UE is handed over from the plurality of accessed first DU entities to a plurality of third DU entities, allocating a third parameter to each third DU entity, where each third DU entity and each first DU entity are located in the same cell; [0270] sending in parallel, to each third DU entity, the third parameter corresponding to the third DU entity; and [0271] receiving a fourth parameter sent in parallel by each third DU entity, and re-establishing connection with each first DU entity; [0272] where the third parameter is used for the first DU entity to send data to the centralized unit entity having the re-established connection with the first DU entity, and the fourth parameter is used for the centralized unit entity to send data to the first DU entity having the re-established connection with the centralized unit entity.

[0273] It should be noted that, the foregoing centralized unit entity provided by the present disclosure can implement all method steps implemented by the foregoing embodiments of the interaction method, the same effects can be achieved, and details about the same parts and beneficial effects as the method embodiments are not described in this embodiment again.

[0274] An embodiment of the present disclosure provides a centralized unit entity. As shown in FIG. **12**, the centralized unit entity includes: [0275] a first receiving unit **1201**, configured to receive first information sent in parallel by a plurality of first distributed unit DU entities accessed by a user equipment UE; and [0276] a first sending unit **1202**, configured to send, to each first DU entity, second information corresponding to the first DU entity in parallel.

[0277] In one embodiment, the centralized unit entity further includes: [0278] a determining unit, configured to determine a plurality pieces of first information to be sent to the first DU entity; and [0279] a determining unit, configured to determine the second information of the first DU entity according to the plurality pieces of first information to be sent to the first DU entity.

[0280] In one embodiment, the centralized unit entity further includes: [0281] a first receiving unit **1201**, configured to receive a response message sent in parallel by each first DU entity.

[0282] In one embodiment, the second information is an RRC reconfiguration message, and the centralized unit entity further includes: [0283] a first receiving unit **1201**, configured to receive an RRC reconfiguration completion message sent in parallel by each first DU entity.

[0284] In one embodiment, the plurality of first DU entities are DU entities currently accessed by the UE, and the centralized unit entity further includes: [0285] a first receiving unit **1201**,

configured to receive a context modification response message of the UE sent in parallel by each first DU entity; [0286] a first sending unit **1202**, configured to send a context establishment request of the UE to a plurality of second DU entities in parallel, where the second DU entities are DU entities to be accessed by the UE; [0287] a first receiving unit **1201**, configured to receive a context establishment response message of the UE sent in parallel by each second DU entity; and [0288] a first sending unit **1202**, configured to send a radio resource control RRC reconfiguration message to each first DU entity in parallel.

[0289] In one embodiment, the centralized unit entity further includes: [0290] a first receiving unit **1201**, configured to receive an RRC reconfiguration completion message sent in parallel by each second DU entity; [0291] a first sending unit **1202**, configured to send a context release message to each first DU entity in parallel; and [0292] a first receiving unit **1201**, configured to receive a context release completion message sent in parallel by each first DU entity.

[0293] In one embodiment, the centralized unit entity further includes: a first receiving unit **1201**, configured to receive a plurality of interaction messages sent in parallel by the second DU entities; [0294] a first sending unit **1202**, configured to send the plurality of interaction messages corresponding to the second DU entities to each second DU entity in parallel; and [0295] a first receiving unit **1201**, configured to receive a response message sent in parallel by each second DU entity.

[0296] In one embodiment, the centralized unit entity further includes: [0297] an allocating unit, configured to, if the UE moves from a first cell to a second cell, allocate a first parameter corresponding to each first DU entity; [0298] a first sending unit **1202**, configured to send in parallel, to each first DU entity, the first parameter corresponding to the first DU entity; and [0299] a first receiving unit **1201**, configured to receive a second parameter sent in parallel by each first DU entity, and re-establishing connection with each first DU entity, where the first parameter is used for the first DU entity to send data to the centralized unit entity having the re-established connection with the first DU entity, and the second parameter is used for the centralized unit entity to send data to the first DU entity having the re-established connection with the centralized unit entity.

[0300] In one embodiment, the centralized unit entity further includes: [0301] an allocating unit, configured to, if the UE is handed over from the plurality of accessed first DU entities to a plurality of third DU entities, allocate a third parameter to each third DU entity; [0302] a first sending unit **1202**, configured to send in parallel, to each third DU entity, the third parameter corresponding to the third DU entity; and [0303] a first receiving unit **1201**, configured to receive a fourth parameter sent in parallel by each third DU entity, and re-establishing connection with each first DU entity, where the third parameter is used for the first DU entity to send data to the centralized unit entity having the re-established connection with the first DU entity, and the fourth parameter is used for the centralized unit entity to send data to the first DU entity having the re-established connection with the centralized unit entity.

[0304] It should be noted that, the foregoing centralized unit entity provided by the present disclosure can implement all method steps implemented by the foregoing embodiments of the interaction method, the same effects can be achieved, and details about the same parts and beneficial effects as the method embodiments are not described in this embodiment again.

[0305] An embodiment of the present disclosure provides a distributed unit entity. As shown in FIG. **13**, the distributed unit entity may include a transceiver **1301**, a processor **1302**, and a memory **1303**.

[0306] The transceiver **1301** is configured to receive and send data under a control of the processor **1302**.

[0307] In FIG. **13**, the bus architecture may include any quantity of interconnecting buses and bridges, specifically link together various circuits including one or more memories represented by the processor(s) **1302** and a memory represented by the memory **1303**. The bus architecture may

also link various other circuits together such as peripherals, voltage regulators, power management circuits or the like, which are well known in the art and, therefore, are not further described herein. A bus interface provides an interface. The transceiver **1301** may be a plurality of components, including a transmitter and a receiver, providing a unit for communicating with various other apparatuses over a transmission medium. The transmission medium includes transmission media such as wireless channels, wired channels, optical cables, etc. The processor **1302** is responsible for managing the bus architecture and general processing, and the memory **1303** can store data used by the processor **1302** when performing an operation.

[0308] The processor **1302** may be a central processing unit (Central Processing Unit, CPU), an application specific integrated circuit (Application Specific Integrated Circuit, ASIC), a field-programmable gate array (Field-Programmable Gate Array, FPGA), or a complex programmable logic device (Complex Programmable Logic Device, CPLD). The processor may also use a multi-core architecture.

[0309] The processor **1302** is configured to execute any method associated with the distributed unit entity provided by the embodiments of the present disclosure according to the obtained executable instructions by invoking a computer program stored in the memory **1303**. The processor and memory may also be physically separated.

[0310] Specifically, when executing the computer program stored in the memory **1303**, the processor **1302** implements the following operations: [0311] receiving an indication message sent by a user equipment UE, to instruct a plurality of distributed unit entities accessed by the UE to send information to a centralized unit CU entity in parallel; [0312] sending first information to the CU entity according to the indication message; and [0313] receiving second information sent by the CU entity.

[0314] It should be noted that, the foregoing distributed unit entity provided by the present disclosure can implement all method steps implemented by the foregoing embodiments of the interaction method, the same effects can be achieved, and details about the same parts and beneficial effects as the method embodiments are not described in this embodiment again.

[0315] An embodiment of the present disclosure provides a distributed unit entity. As shown in FIG. **14**, the distributed unit entity includes: [0316] a second receiving unit **1401**, configured to receive an indication message sent by a user equipment UE, where the indication message is used to instruct a plurality of distributed unit entities accessed by the UE to send information to a centralized unit CU entity in parallel; and [0317] a second sending unit **1402**, configured to send first information to the CU entity according to the indication message; [0318] the second receiving unit **1401** is further configured to receive second information sent by the CU entity.

[0319] It should be noted that, the distributed unit entity provided by the present disclosure can implement all method steps implemented by the foregoing embodiments of the interaction method, the same effects can be achieved, and details about the same parts and beneficial effects as the method embodiments are not described in this embodiment again.

[0320] An embodiment of the present disclosure provides a user equipment. As shown in FIG. **15**, the user equipment may include a transceiver **1501**, a processor **1502**, and a memory **1503**.

[0321] The transceiver **1501** is configured to receive and send data under a control of the processor **1502**.

[0322] In FIG. **15**, the bus architecture may include any quantity of interconnected buses and bridges, specifically link together various circuits including one or more memories represented by the processor(s) **1502** and a memory represented by the memory **1503**. The bus architecture may also link various other circuits together such as peripherals, voltage regulators, power management circuits or the like, which are well known in the art and, therefore, are not further described herein. A bus interface provides an interface. The Transceiver **1501** may be a plurality of components, including a transmitter and a receiver, providing a unit for communicating with various other apparatuses over a transmission medium. The transmission medium includes transmission media

such as wireless channels, wired channels, optical cables, etc. The processor **1502** is responsible for managing the bus architecture and general processing, and the memory **1503** can store data used by the processor **1502** when executing an operation.

[0323] The processor **1502** may be a central processing unit (Central Processing Unit, CPU), an application specific integrated circuit (Application Specific Integrated Circuit, ASIC), a field-programmable gate array (Field-Programmable Gate Array, FPGA), or a complex programmable logic device (Complex Programmable Logic Device, CPLD). The processor may also use a multi-core architecture.

[0324] The processor **1502** is configured to execute, according to the obtained executable instructions, any method associated with the user equipment provided by the embodiments of the present disclosure by invoking a computer program stored in the memory **1503**. The processor and memory may also be physically separated.

[0325] Specifically, when executing the computer program stored in the memory **1503**, the processor **1502** implements the following operations: [0326] sending an indication message to a plurality of distributed unit DU entities accessed by a user equipment, where the indication message is used to instruct the plurality of DU entities to send information to a centralized unit CU entity in parallel.

[0327] It should be noted that, the user equipment provided by the present disclosure can implement all method steps implemented by the foregoing embodiments of the interaction method, the same effects can be achieved, and details about the same parts and beneficial effects as the method embodiments are not described in this embodiment again.

[0328] An embodiment of the present disclosure provides a user equipment. As shown in FIG. **16**, the user equipment includes: [0329] a third sending unit **1601**, configured to send an indication message to a plurality of distributed unit DU entities accessed by a user equipment, where the indication message is used to instruct the plurality of DU entities to send information to a centralized unit CU entity in parallel.

[0330] It should be noted that, the user equipment provided by the present disclosure can implement all method steps implemented by the foregoing embodiments of the interaction method, the same effects can be achieved, and details about the same parts and beneficial effects as the method embodiments are not described in this embodiment again.

[0331] It should be noted that, the division of the units in the embodiments of the present disclosure is exemplary, and is merely a logical function division, and there may be other division manners in practical implementation. In addition, respective functional units in the embodiments of the present disclosure may be integrated into one processing unit, or each unit may exist alone physically, or two or more units are integrated into one unit. The integrated unit may be implemented in a form of hardware, and may also be implemented in a form of a software functional unit.

[0332] When being implemented in the form of a software functional unit and sold or used as an independent product, the integrated unit may be stored in a processor-readable storage medium. Based on such understanding, the solutions of the present disclosure essentially, or the part contributing to the prior art, or all or a part of the solutions may be implemented in a form of a software product. The computer software product is stored in a storage medium and includes several instructions for instructing a computer device (which may be a personal computer, a server, or a network device, etc.) or a processor to execute all or a part of the steps of the methods in the embodiments of the present disclosure. The foregoing storage medium includes: any medium that can store program codes, such as a USB flash disk, a removable hard disk, a read-only memory (Read-Only Memory, ROM), a random access memory (Random Access Memory, RAM), a magnetic disk, or an optical disk, etc.

[0333] An embodiment of the present disclosure provides a processor-readable storage medium. The processor-readable storage medium stores a computer program, where the computer program

is used to enable a processor to execute any method provided by the embodiments of the present disclosure associated with a centralized unit entity, a distributed unit entity or a user equipment. In this way, the processor can implement all method steps implemented by the centralized unit entity, the distributed unit entity, or the user equipment in the foregoing method embodiments, the same effects can be achieved, and details about the same parts and beneficial effects as the method embodiments are not described in this embodiment again.

[0334] The processor-readable storage medium may be any available medium or data storage device that can be accessed by the processor, including but not limited to a magnetic memory (such as a floppy disk, a hard disk, a magnetic tape, a magneto-optical disk (MO), etc.), an optical memory (such as a CD, a DVD, a BD, an HVD, etc.), and a semiconductor memory (such as a ROM, an EPROM, an EEPROM, a non-volatile memory (NAND FLASH), a solid state disk (SSD)), etc.

[0335] Embodiments of the present disclosure provide a computer program product including instructions that, when executed on a computer, cause the computer to execute all the method steps implemented by the centralized unit entity, the distributed unit entity or the user equipment in the above method embodiments, the same effect can be achieved, and the same parts and beneficial effects as the method embodiments are not described in this embodiment again.

[0336] The embodiments of the present disclosure can be provided as a method, a positioning management entity or a computer program product. Therefore, the present disclosure may take the form of an entirely hardware embodiment, an entirely software embodiment or an embodiment combining embodiments of software and hardware aspects. Furthermore, the present disclosure may take the form of a computer program product embodied on one or more computer-usable storage media (including, but not limited to, magnetic disk storage, optical storage, etc.) containing computer-usable program codes.

[0337] The present disclosure is described with reference to flowcharts and/or block diagrams of a method, a positioning management entity, and a computer program product according to embodiments of the present disclosure. It should be understood that, each flow and/or block in the flowcharts and/or block diagrams and combinations of flows and/or blocks in the flowcharts and/or block diagrams can be implemented by computer-executable instructions. The computer-executable instructions may be provided to a processor of a general purpose computer, a special purpose computer, an embedded processor or other programmable data processing devices to produce a machine, enabling instructions executed by a processor of a computer or other programmable data processing devices to generate an apparatus for implementing the functions specified in one or more processes in the flowcharts and/or one or more blocks in the block diagrams.

[0338] These processor-executable instructions may also be stored in a processor-readable memory that can guide a computer or other programmable data processing device to function in a particular manner, causing the instructions stored in the processor-readable memory to produce an article of manufacture including an instruction apparatus. The instruction apparatus implements functions specified in one or more processes in the flowcharts and/or one or more blocks in the block diagrams.

[0339] These processor-executable instructions may also be loaded onto a computer or other programmable data processing device, causing a series of operational steps to be performed on a computer or other programmable devices to produce a computer-implemented process. Thus, the instructions executed on the computer or other programmable devices provide steps for implementing the functions specified in one or more processes in the flowcharts and/or one or more blocks in the block diagrams.

[0340] Various modifications and variations to the present disclosure without departing from the spirit and scope of the present disclosure. As such, if these modifications and variations of the present disclosure belong to the scope of the claims of the present disclosure and the equivalents thereof, the present disclosure is intended to include these modifications and variations.

Claims

1. An interaction method, applied to a centralized unit entity, and comprising: receiving first information sent in parallel by a plurality of first distributed units (DU) entities accessed by a user equipment (UE); and sending, to each first DU entity, second information corresponding to the first DU entity in parallel.
2. The method according to claim 1, before the sending, to each first DU entity, the second information corresponding to the first DU entity in parallel, further comprising: determining a plurality pieces of first information to be sent to the first DU entity; and determining the second information of the first DU entity according to the plurality pieces of first information to be sent to the first DU entity.
3. The method according to claim 2, after the sending, to each first DU entity, the second information corresponding to the first DU entity in parallel, further comprising: receiving a response message sent in parallel by each first DU entity.
4. The method according to claim 1, wherein the second information is a radio resource control (RRC) reconfiguration message, and after the sending, to each first DU entity, the second information corresponding to the first DU entity in parallel, the method further comprises: receiving an RRC reconfiguration completion message sent in parallel by each first DU entity.
5. The method according to claim 1, wherein the plurality of first DU entities are DU entities currently accessed by the UE, and after the sending, to each first DU entity, the second information corresponding to the first DU entity in parallel, the method further comprises: receiving a context modification response message of the UE sent in parallel by each first DU entity; sending a context establishment request of the UE to a plurality of second DU entities in parallel, wherein the second DU entities are DU entities to be accessed by the UE; receiving a context establishment response message of the UE sent in parallel by each second DU entity; and sending an RRC reconfiguration message to each first DU entity in parallel.
6. The method according to claim 5, after the sending the RRC reconfiguration message to each first DU entity in parallel, further comprising: receiving an RRC reconfiguration completion message sent in parallel by each second DU entity; sending a context release message to each first DU entity in parallel; and receiving a context release completion message sent in parallel by each first DU entity.
7. The method according to claim 6, after the receiving the RRC reconfiguration completion message sent in parallel by each second DU entity, further comprising: receiving a plurality of interaction messages sent in parallel by the plurality of second DU entities; sending the plurality of interaction messages corresponding to the plurality of second DU entities to each second DU entity in parallel; and receiving a response message sent in parallel by each second DU entity.
8. The method according to claim 1, further comprising: in a condition that the UE moves from a first cell to a second cell, allocating a first parameter corresponding to each first DU entity; sending in parallel, to each first DU entity, the first parameter corresponding to the first DU entity; and receiving a second parameter sent in parallel by each first DU entity, and re-establishing connection with each first DU entity; wherein the first parameter is used for the first DU entity to send data to the centralized unit entity having the re-established connection with the first DU entity, and the second parameter is used for the centralized unit entity to send data to the first DU entity having the re-established connection with the centralized unit entity.
9. The method according to claim 1, further comprising: in a condition that the UE is handed over from the plurality of accessed first DU entities to a plurality of third DU entities, allocating a third parameter to each third DU entity, wherein each third DU entity and each first DU entity are located in the same cell; sending in parallel, to each third DU entity, the third parameter corresponding to the third DU entity; and receiving a fourth parameter sent in parallel by each third

DU entity, and re-establishing connection with each first DU entity; wherein the third parameter is used for the first DU entity to send data to the centralized unit entity having the re-established connection with the first DU entity, and the fourth parameter is used for the centralized unit entity to send data to the first DU entity having the re-established connection with the centralized unit entity.

10. (canceled)

11. An interaction method, applied to user equipment, and comprising: sending an indication message to a plurality of distributed unit (DU) entities accessed by a user equipment, wherein the indication message is used to instruct the plurality of DU entities to send information to a centralized unit (CU) entity in parallel.

12. A centralized unit entity, comprising: a memory, a transceiver and a processor, wherein the memory is configured to store a computer program; the transceiver is configured to receive and send data under a control of the processor; and the processor is configured to read the computer program in the memory and perform the method according to claim 1.

13-15. (canceled)

16. A user equipment, comprising: a memory, a transceiver and a processor, wherein the memory is configured to store a computer program; the transceiver is configured to receive and send data under a control of the processor; and the processor is configured to read the computer program in the memory and perform the following operations: sending an indication message to a plurality of distributed unit (DU) entities accessed by a user equipment, wherein the indication message is used to instruct the plurality of DU entities to send information to a centralized unit (CU) entity in parallel.

17-18. (canceled)

19. The centralized unit entity according to claim 12, wherein the processor is configured to perform the following operations: determining a plurality pieces of first information to be sent to the first DU entity; and determining the second information of the first DU entity according to the plurality pieces of first information to be sent to the first DU entity.

20. The centralized unit entity according to claim 19, wherein the processor is further configured to perform the following operation: receiving a response message sent in parallel by each first DU entity.

21. The centralized unit entity according to claim 12, wherein the second information is a radio resource control (RRC) reconfiguration message, and the processor is further configured to perform the following operation: receiving an RRC reconfiguration completion message sent in parallel by each first DU entity.

22. The centralized unit entity according to claim 12, wherein the plurality of first DU entities are DU entities currently accessed by the UE, and the processor is further configured to perform the following operations: receiving a context modification response message of the UE sent in parallel by each first DU entity; sending a context establishment request of the UE to a plurality of second DU entities in parallel, wherein the second DU entities are DU entities to be accessed by the UE; receiving a context establishment response message of the UE sent in parallel by each second DU entity; and sending an RRC reconfiguration message to each first DU entity in parallel.

23. The centralized unit entity according to claim 22, wherein the processor is further configured to perform the following operations: receiving an RRC reconfiguration completion message sent in parallel by each second DU entity; sending a context release message to each first DU entity in parallel; and receiving a context release completion message sent in parallel by each first DU entity.

24. The centralized unit entity according to claim 23, wherein the processor is further configured to perform the following operations: receiving a plurality of interaction messages sent in parallel by the plurality of second DU entities; sending the plurality of interaction messages corresponding to the plurality of second DU entities to each second DU entity in parallel; and receiving a response

message sent in parallel by each second DU entity.

25. The centralized unit entity according to claim 12, wherein the processor is further configured to perform the following operations: in a condition that the UE moves from a first cell to a second cell, allocating a first parameter corresponding to each first DU entity; sending in parallel, to each first DU entity, the first parameter corresponding to the first DU entity; and receiving a second parameter sent in parallel by each first DU entity, and re-establishing connection with each first DU entity; wherein the first parameter is used for the first DU entity to send data to the centralized unit entity having the re-established connection with the first DU entity, and the second parameter is used for the centralized unit entity to send data to the first DU entity having the re-established connection with the centralized unit entity.

26. The centralized unit entity according to claim 12, wherein the processor is further configured to perform the following operations: in a condition that the UE is handed over from the plurality of accessed first DU entities to a plurality of third DU entities, allocating a third parameter to each third DU entity, wherein each third DU entity and each first DU entity are located in the same cell; sending in parallel, to each third DU entity, the third parameter corresponding to the third DU entity; and receiving a fourth parameter sent in parallel by each third DU entity, and re-establishing connection with each first DU entity; wherein the third parameter is used for the first DU entity to send data to the centralized unit entity having the re-established connection with the first DU entity, and the fourth parameter is used for the centralized unit entity to send data to the first DU entity having the re-established connection with the centralized unit entity.
