

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250277673

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

Lu; Hongxiao

Display Method, Storage Medium, and Terminal Device

Abstract

A display method includes, after detecting that a user enables a tourist navigation function, the terminal device determines the current location coordinates. When detecting that the current location coordinates of the user are located on a tourist road, the terminal device separately displays a road interface for the tourist road, and displays, on the road interface, feature data corresponding to the tourist road. When detecting that the current location coordinates of the user are not located on any tourist road, the terminal device automatically queries a tourist road in a target range for the user, and returns a query result to the user.

Inventors: Lu; Hongxiao (Shenzhen, CN)

Applicant: Huawei Technologies Co., Ltd. (Shenzhen, CN)

Family ID: 91068862

Appl. No.: 19/210268

Filed: May 16, 2025

Foreign Application Priority Data

CN 202211447784.3

Nov. 18, 2022

Related U.S. Application Data

parent WO continuation PCT/CN2023/129123 20231101 PENDING child US 19210268

Publication Classification

Int. Cl.: G01C21/36 (20060101); G01C21/34 (20060101)

U.S. Cl.:

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This is a continuation of International Patent Application No. PCT/CN2023/129123, filed on Nov. 1, 2023, which claims priority to Chinese Patent Application No. 202211447784.3, filed on Nov. 18, 2022. The disclosures of the aforementioned applications are hereby incorporated by reference in their entireties.

TECHNICAL FIELD

[0002] This disclosure relates to the field of intelligent terminal technologies, and in particular, to a display method, a storage medium, and a terminal device.

BACKGROUND

[0003] A user can use a terminal device for map navigation. For example, after the user taps to start a map application on the terminal device, the map application can obtain a corresponding map interface based on location coordinates of the user, and display the map interface on a display of the terminal device for the user to view, so that the user can obtain the current location coordinates based on the map interface and follow map navigation instructions for direction navigation.

[0004] However information about a map interface presented by a map application is limited, and is usually limited to a basic road boundary, a bridge, a traffic condition, a text-based street name, a text-based building name, and the like. Content displayed on the map interface is simple, and content such as a related tourist attraction cannot be displayed on the map interface in real time based on location coordinates of the user. This is unfavorable to user experience.

SUMMARY

[0005] Embodiments of this disclosure provide a display method, a storage medium, and a terminal device. When detecting that current location coordinates of a user are located on a tourist road, the terminal device separately displays a road interface for the tourist road, and displays, on the road interface, feature data corresponding to the tourist road. In this way, the user can perform road navigation through the road interface displayed by the terminal device, and can also view, through the road interface, humanistic information of a tourist attraction related to the road. When detecting that the current location coordinates of the user are not located on any tourist road, the terminal device automatically queries a tourist road in a target range for the user, and returns a query result to the user. The user does not need to switch an interface for separate query, thereby improving user experience.

[0006] According to a first aspect, this disclosure provides a display method, applied to a terminal device. The method includes that the terminal device displays a navigation interface, where the navigation interface includes a first road, and the terminal device moves to a first location in a moving process, and displays, on the first road on the navigation interface, a first road feature corresponding to the first location.

[0007] In this embodiment, the navigation interface indicates a map interface of a map application presented on a display of the terminal device, for example, a map interface of an application **240** displayed on a display of a mobile phone **100**. The first road indicates a tourist road on which the terminal device is currently located. The first location indicates current location coordinates of the terminal device located on the tourist road. The first road feature indicates road attraction data. When a user uses a map application and enables tourist navigation, after the terminal device determines that the user is currently located on a tourist road, the terminal device displays a road interface for the tourist road, and displays, on the road interface, road attraction data corresponding to the tourist road. This enables the user to perform road navigation through the road interface

displayed by the terminal device, and also view, through the road interface, tourist attraction information related to the tourist road, thereby improving user experience.

[0008] In a possible implementation of the first aspect, the first road feature has a first feature location, and the method further includes a first display location of the corresponding first road feature on the first road on the navigation interface is determined based on the first feature location.

[0009] In this embodiment, the first feature location indicates attraction location coordinates of the road attraction data. The terminal device determines a display manner and a display location of a rendering element of each piece attraction data on a display layer of the tourist road based on the attraction location coordinates of the road attraction data on the tourist road and current location coordinates of the user.

[0010] In a possible implementation of the first aspect, the first display location of the first road feature on the first road on the navigation interface is determined in at least one of the following manners. The first display location of the corresponding first road feature on the first road on the navigation interface is determined based on a connection line intersection point between the first feature location and the first road, or the first display location of the corresponding first road feature on the first road on the navigation interface is determined based on a first distance between the first feature location and the first location.

[0011] In this embodiment, for example, rendering elements of tourist attractions are sequentially superimposed, based on corresponding attraction location coordinates and horizontal and vertical lines of the tourist road, at intersection points between the corresponding horizontal and vertical lines and the tourist road. Alternatively, for example, a rendering element of road attraction data located in front of the current location coordinates of the user is displayed. For another example, the terminal device may display, on the display layer, a rendering element of a tourist attraction within a vertical distance of 2 kilometers or 500 meters, and determine, based on a distance of each tourist attraction, a display size of a corresponding rendering element, and the like.

[0012] In a possible implementation of the first aspect, that the terminal device moves to a first location in a moving process, and displays, on the first road on the navigation interface, a first road feature corresponding to the first location, a first distance between the first location when the first feature location of the first road feature meets a first distance condition.

[0013] In this embodiment, the first distance condition indicates road attraction data located in a preset range in front of the current location coordinates of the user. This avoids displaying a rendering element of a far tourist attraction or rendering elements of too many tourist attractions on the display layer, and correspondingly reduces time for the user to move from the current location coordinates to a location corresponding to the rendering element, so that the user can see a tourist attraction corresponding to a rendering element displayed by the mobile phone **100** in a short time, thereby improving user experience.

[0014] In a possible implementation of the first aspect, the method further includes that the terminal device moves from the first location to a second location, and hides the first road feature displayed on the first road on the navigation interface.

[0015] In this embodiment, when the user drives a vehicle to pass through a rendering element of a piece of road attraction data, so that the rendering element is located behind the current location coordinates of the user, the rendering element disappears from the display layer. Correspondingly, display duration of the rendering element of the tourist attraction on the display layer is shortened, thereby preventing the rendering element of the tourist attraction from blocking road display, and the like.

[0016] In a possible implementation of the first aspect, the method further includes that the first location is located on the first road.

[0017] In this embodiment, the first location is located on the first road. A second location may be located on the first road, or a second location may not be located on the first road. For example, when the user drives a vehicle to pass through a rendering element of a piece of road attraction

data, so that the rendering element is located behind the current location coordinates of the user, the user may be located on a corresponding tourist road, or the user may drive through the tourist road to be located on another road.

[0018] In a possible implementation of the first aspect, the first road includes the first road feature and a second road feature, and the method further includes that the first road feature corresponding to the first location and the second road feature are displayed on the first road on the navigation interface.

[0019] In this embodiment, the second road feature indicates city feature data and road culture data. The terminal device may display the city feature data and the road culture data on the first road on the navigation interface. Alternatively, the terminal device may convert the road culture data into voice data, and play the voice data of the road culture data when displaying another first road feature and the second road feature.

[0020] In a possible implementation of the first aspect, the second road feature includes at least one of the following features, a city image feature, a city activity feature, a city tourism feature, a city historical feature, and a city humanistic feature.

[0021] In a possible implementation of the first aspect, the first road feature includes at least one of the following features, an architectural attraction feature and a natural landscape attraction feature.

[0022] In a possible implementation of the first aspect, the method further includes that the first road meets a first road condition, and the first road condition indicates that at least one first road feature is included.

[0023] In a possible implementation of the first aspect, the navigation interface includes a first road separately displayed on the navigation interface.

[0024] In this embodiment, when the terminal device detects that the user enables tourist navigation, or determines that a current location of the user is located on a tourist road, a display mode of a map interface on the terminal device is a road navigation display interface. In addition, when the terminal device determines that the current location of the user is located on a tourist road, a navigation road displayed on the road navigation display interface is the tourist road, so that a display layer of the tourist road can be enlarged. In this way, when corresponding feature data is subsequently superimposed on the display layer, viewing of the navigation road by the user is not affected, thereby improving road navigation safety.

[0025] In a possible implementation of the first aspect, before the navigation interface includes the first road, the method includes that a first road that meets the first road condition in a first range is queried based on a current location of the terminal device, and a query result is displayed on the navigation interface.

[0026] In this embodiment, the first range indicates a target range. The terminal device detects the current location coordinates of the user when the user uses the map application and enables tourist navigation. When detecting that the current location coordinates of the user are not located on any tourist road, the terminal device may obtain destination location coordinates of the user, actively query a tourist road in the target range for the user based on the current location coordinates and the destination location coordinates, and return a query result to the user, so that the user can choose whether to switch a navigation route. When the user performs map navigation, the terminal device can actively query the tourist road, and the user does not need to switch an interface for separate query, thereby improving user experience.

[0027] In a possible implementation of the first aspect, before the navigation interface includes the first road, the method includes that a first navigation route is displayed on the navigation interface, a second navigation route that meets a first query condition in a first range is queried based on the first navigation route, where the first query condition indicates that the second navigation route includes the first road, and a query result is displayed on the navigation interface.

[0028] In a possible implementation of the first aspect, that a query result is displayed on the navigation interface includes that the second navigation route and first navigation time of the

second navigation route are displayed on the navigation interface; or the second navigation route, first navigation time of the second navigation route, and the first navigation time of the second navigation route are displayed on the navigation interface; or the second navigation route, and a time difference between first navigation time of the second navigation route and the first navigation time of the second navigation route are displayed on the navigation interface.

[0029] In a possible implementation of the first aspect, the first range is determined in the following manner. The first range is determined based on an end location of the first navigation route and a current location of the terminal device.

[0030] In this embodiment, a direction in which the user drives a vehicle is determined based on the end location of the first navigation route and the current location of the terminal device, and a tourist road in the target range is queried based on the direction in which the user drives a vehicle. The target range may be a tourist road in a range such as a distance of 2 kilometers or 10 kilometers from the current location coordinates, or the target range may be a tourist road in a range such as driving time of 10 minutes or 20 minutes from the current location coordinates.

[0031] In a possible implementation of the first aspect, the first range is determined in the following manner. A second distance between an end location of the first navigation route and a current location of the terminal device is obtained; and the first range is determined based on a first threshold and the second distance.

[0032] In this embodiment, the target range is determined based on a dynamic threshold K and a distance L between the current location coordinates and the destination location coordinates. For example, the target range may be in a semi-circle range of 90 degrees to the left and right or may be in a sector range of 30 degrees to each of the left and right, which is in a direction of a connection line between the current location coordinates and a destination location and which is obtained by using a product of the distance L and the dynamic threshold K as a radius. The dynamic threshold K is any constant greater than 0 and less than or equal to 1. Long driving time for the user to switch a navigation route due to an excessively large target range can be avoided by limiting the dynamic threshold K . It may be understood that a queried target range is limited by using the dynamic threshold K , and driving time of a navigation route obtained through query is also limited by using the dynamic threshold K .

[0033] In a possible implementation of the first aspect, the first threshold is determined in the following manner. The first threshold is determined based on the second distance.

[0034] In this embodiment, a value of the dynamic threshold K may be determined based on a value of the distance L . For example, when the distance L ranges from 0 to 5 kilometers, the dynamic threshold K is 0.2; or when the distance L ranges from 5 to 10 kilometers, the dynamic threshold K is 0.5.

[0035] According to a second aspect, an embodiment of this disclosure provides a display apparatus. The display apparatus includes a first display module, configured to display a navigation interface of a terminal device, where the navigation interface includes a first road; and a second display module, configured to, when the terminal device moves to a first location in a moving process, display, on the first road on the navigation interface, a first road feature corresponding to the first location.

[0036] In this embodiment, the navigation interface indicates a map interface of a map application presented on a display of the terminal device, for example, a map interface of an application **240** displayed on a display of a mobile phone **100**. The first road indicates a tourist road on which the terminal device is currently located. The first location indicates current location coordinates of the terminal device located on the tourist road. The first road feature indicates road attraction data. When a user uses a map application and enables tourist navigation, after the terminal device determines that the user is currently located on a tourist road, the first display module displays a road interface for the tourist road, and displays, on the road interface through the second display module, road attraction data corresponding to the tourist road. This enables the user to perform

road navigation through the road interface displayed by the terminal device, and also view, through the road interface, tourist attraction information related to the tourist road, thereby improving user experience.

[0037] According to a third aspect, an embodiment provides a readable storage medium. The readable storage medium stores instructions. When the instructions are executed on a terminal device, the terminal device is enabled to implement any display method provided in the first aspect and the possible implementations of the first aspect.

[0038] According to a fourth aspect, an embodiment provides a terminal device. The terminal device includes a memory, configured to store instructions executed by one or more processors of the terminal device; and a processor, where the processor is one of the processors of the terminal device, and is configured to execute the instructions stored in the memory, to implement any display method provided in the first aspect and the possible implementations of the first aspect.

[0039] According to a fifth aspect, an embodiment provides a program product, where the program product includes instructions. When the instructions are executed by a terminal device, the terminal device may implement any display method provided in the first aspect and the possible implementations of the first aspect.

Description

BRIEF DESCRIPTION OF DRAWINGS

[0040] FIG. 1 is an example diagram of a communication system according to some embodiments;

[0041] FIG. 2A is an example diagram of a display interface for a road according to some embodiments;

[0042] FIG. 2B is an example diagram of another display interface for a road according to some embodiments;

[0043] FIG. 3A is a diagram of a structure of a terminal device according to some embodiments;

[0044] FIG. 3B is an example diagram of Global Positioning System (GPS) positioning according to some embodiments;

[0045] FIG. 3C is a diagram of another structure of a terminal device according to some embodiments;

[0046] FIG. 4A is a flowchart of steps of a display method according to some embodiments;

[0047] FIG. 4B is a flowchart of steps of displaying feature data according to some embodiments;

[0048] FIG. 5A is an example diagram of a display layer according to some embodiments;

[0049] FIG. 5B is an example diagram of a rendering element according to some embodiments;

[0050] FIG. 5C is an example diagram of a rendering element according to some embodiments;

[0051] FIG. 5D is an example diagram of a rendering element according to some embodiments;

[0052] FIG. 6A is an example diagram of a target sector range according to some embodiments;

[0053] FIG. 6B is an example diagram of a navigation route according to some embodiments;

[0054] FIG. 6C is an example diagram of a navigation route according to some embodiments;

[0055] FIG. 7A is a flowchart of steps of a navigation display method according to some embodiments;

[0056] FIG. 7B is a flowchart of steps of another navigation display method according to some embodiments; and

[0057] FIG. 8 is a diagram of a structure of a mobile phone according to some embodiments.

DESCRIPTION OF EMBODIMENTS

[0058] Illustrative embodiments of this disclosure include but are not limited to a display method, a storage medium, and a terminal device.

[0059] The following describes some embodiments by using examples with reference to the accompanying drawings.

[0060] FIG. 1 is an example diagram of a communication system **10** according to some embodiments.

[0061] As shown in FIG. 1, the communication system **10** includes a terminal device **11**, an access device **12**, and a network device **13**. The terminal device **11** may establish a communication connection to the network device **13** by using the access device **12**. A user may initiate a task request to the network device **13** by using the terminal device **11**. For example, when the user performs a map navigation operation by using the terminal device **11**, in response to the map navigation operation, the terminal device **11** obtains current location coordinates of the user, and initiates, to the network device **13**, a task request related to map data query. The network device **13** may query corresponding map data based on the received current location coordinates of the user, and return the corresponding map data to the terminal device **11**. In this way, the terminal device **11** may display, on a display, a map interface of the map data for the user to view, and the terminal device **11** may alternatively convert the map data into voice data that is played for the user to listen, or the like.

[0062] In some embodiments, the communication system **10** may include a plurality of terminal devices **11**. For example, the terminal devices **11** shown in FIG. 1 may include a mobile phone and a vehicle-mounted device in a vehicle. The plurality of terminal devices **11** may establish communication connections between the plurality of terminal devices **11** by using the access device **12**, or may establish communication connections between the plurality of terminal devices **11** in a wired connection manner. For example, the mobile phone may establish a wireless communication connection to the vehicle-mounted device by using the access device **12**, the mobile phone may establish a wired communication connection to the vehicle-mounted device in a data line connection manner, or the like.

[0063] It may be understood that in a driving process, the user may directly perform map navigation by using the mobile phone, or may perform map navigation by using the vehicle-mounted device after the communication connection is established between the mobile phone and the vehicle-mounted device. This is not specifically limited.

[0064] Further, the access device **12** may be any device that supports a wireless transceiver function, including but not limited to an evolved base station, a base station in a 5G communication system, a base station in a future communication system, an access node in a wireless fidelity (Wireless Fidelity, Wi-Fi) system, a wireless relay node, a wireless backhaul node, and the like. The network device **13** may be any single server having storage space, or may be a server cluster including a plurality of servers. The network device **13** stores map data corresponding to different location coordinates, including but not limited to a 2D map, a 3D map, a heat map, a satellite map, a topographic map, an indoor map, a bus map, a high-definition map, a lane-level road map, and the like.

[0065] In some embodiments, the terminal device **11** may determine display modes of interfaces of the foregoing maps based on different state modes. For example, when detecting that the user selects a driving state mode to perform a navigation operation, the terminal device **11** may switch a full map display interface to a driving road navigation display interface. When detecting that the user selects a riding/walking state mode to perform a navigation operation, the terminal device **11** may switch a full map display interface to a riding/walking road navigation display interface, or the like.

[0066] For example, as shown in FIG. 2A and FIG. 2B, when the user uses the terminal device **11** to perform map navigation, the terminal device **11** may display a full map display interface shown in FIG. 2A. When subsequently detecting that the user selects the driving state mode to perform a navigation operation, the terminal device **11** may switch from the full map display interface shown in FIG. 2A to a driving road navigation display interface shown in FIG. 2B.

[0067] It may be understood that regardless of the full map display interface shown in FIG. 2A or the driving road navigation display interface shown in FIG. 2B, information displayed on the map

interface by the terminal device **11** is limited. For example, FIG. 2A is limited only to display of a basic road boundary, a bridge, a traffic condition, a text-based street name, a text-based building name, and the like, or FIG. 2B is limited only to display of a driving road, a driving direction, and the like. Therefore, display content on the display interface is simple, and user experience is poor. [0068] In some other embodiments, the network device **13** further stores feature data corresponding to different location coordinates, and the feature data may include city feature data and road feature data. For example, the corresponding location coordinates are a road A of a city A, and the city feature data may include a tourism image based on a city in which the location coordinates are located. For example, a tourism image based on the city A may include a cartoon image, an activity image, and the like of the city A.

[0069] Further, the road feature data may include road culture data and road attraction data. The corresponding location coordinates are the road A of the city A, and the road attraction data may include a tourist attraction around a road on which the location coordinates are located. For example, tourist attractions based on the road A may include an attraction A1, an attraction A2, an attraction A3, and the like. The road culture data may include historical humanistic information of the road on which the location coordinates are located. For example, the historical humanistic information based on the road A may include cultural information of the attraction A1, historical information of the attraction A2, and the like. In some other embodiments, the road attraction data may be an architectural attraction, such as a temple or an ancient city tower, or may be a natural landscape attraction, such as a lake, a flowing river, a mountain, or a tree. This is not specifically limited.

[0070] In some embodiments, a road corresponding to location coordinates including road feature data is used as a tourist road. For example, if the road A includes road feature data of tourist attractions such as the attraction A1, the attractions A2, and the attraction A3, the road A may be used as a tourist road. The tourist road includes but is not limited to a lane, a riding lane, a sidewalk, and the like.

[0071] In some embodiments, the user may query, by using the terminal device **11**, the network device **13** for content related to the tourist road. For example, when the user performs a tourism information query operation on a tourist road by using the terminal device **11**, in response to the tourism information query operation, the terminal device **11** obtains the current location coordinates of the user, and initiates, to the network device **13**, a task request related to the tourism information query. The network device **13** may determine, based on the received location coordinates, a tourist road on which the user is located, query corresponding feature data based on the tourist road, and return the feature data to the terminal device **11**. In this way, the terminal device **11** may display, on the display, the feature data for the user to view, and the terminal device **11** may alternatively convert the feature data into voice data that is played for the user to listen, or the like.

[0072] It may be understood that in a process of performing map navigation by using the terminal device **11**, if the user wants to query related tourism consultation of a tourist road on which the user is currently located, the user needs to exit the map navigation interface or the map application, and then perform query by using another search application, which affects user experience.

[0073] To resolve the foregoing technical problem, the disclosed display method, applied to a terminal device, and the terminal device has a tourist navigation function. After detecting that a user enables a tourist navigation function, the terminal device obtains current location coordinates of the user, and determines the current location coordinates. When a determining result is that the current location coordinates are located on a tourist road, feature data (for example, the city feature data, the road culture data, and the road attraction data mentioned above) of the tourist road is obtained. In addition, a road interface for the tourist road is separately displayed, and the feature data is displayed on the road interface. In this way, the user can perform road navigation through the road interface displayed by the terminal device, and can also view, through the road interface,

humanistic information of a tourist attraction related to the road, thereby improving user experience.

[0074] The terminal device may obtain road location coordinates of the tourist road from the network device in advance, and store a correspondence between the road location coordinates and the corresponding tourist road. After obtaining the current location coordinates of the user, the terminal device may determine, from the prestored correspondence, whether the current location coordinates are located on a tourist road.

[0075] In some embodiments, when a determining result is that the current location coordinates of the user are not located on any tourist road, the terminal device obtains destination location coordinates of the user, query a tourist road in a target range for the user based on the current location coordinates and the destination location coordinates, and returns a query result to the user, so that the user can choose whether to switch a navigation route. When the user performs map navigation, the terminal device can actively query the tourist road, and the user does not need to switch an interface for separate query, thereby improving user experience.

[0076] The following describes some embodiments by using examples with reference to the driving scenario shown in FIG. 2A or FIG. 2B.

[0077] FIG. 3A is a diagram of a structure of the terminal device **11** according to some embodiments. As shown in FIG. 3A, the terminal device **11** includes a communication module **21**, a positioning module **22**, a display module **23**, and an application module **24**.

[0078] In some embodiments, the communication module **21** is configured to enable the terminal device **11** to establish a communication connection to the network device **13** or another terminal device **11** in the foregoing wireless connection manner. The network device **13** stores at least the foregoing map data and the feature data that correspond to different location coordinates, and the foregoing road location coordinates of the corresponding tourist road.

[0079] In some embodiments, the positioning module **22** may obtain current location coordinates of the terminal device **11** by using a GPS, a BeiDou navigation satellite system (BDS), or any other positioning system. For example, as shown in FIG. 3B, the positioning module **22** may obtain broad-spectrum GPS satellite signals **11B** from at least three satellites **11A** by using the GPS, to obtain two-dimensional geographic coordinates of the terminal device **11**. Alternatively, the positioning module **22** may obtain broad-spectrum GPS satellite signals **11B** from at least four satellites **11A** by using the GPS, to obtain three-dimensional geographic coordinates of the terminal device **11**. This is not specifically limited.

[0080] In some embodiments, the display module **23** is configured to display a display interface of the terminal device **11**, and is configured to display an application interface of any application in the application module **24**. The application module **24** includes at least an application **240** having a specific map navigation function, including but not limited to a map application, a browser application, another application having a map applet, and the like. This is not specifically limited.

[0081] In some embodiments, the application **240** includes a detection unit **241**, an obtaining unit **242**, a processing unit **243**, a rendering unit **244**, and a playback unit **245**.

[0082] The detection unit **241** is configured to detect that the user enables or disables the tourist navigation function. The obtaining unit **242** is configured to obtain the current location coordinates of the terminal device **11** received by the positioning module **22**, and query corresponding map data and feature data from the network device **13** based on the current location coordinates. The processing unit **243** is configured to perform data processing on the feature data, for example, convert city feature data and road attraction data into data in a text or picture format, and convert road culture data into data in a voice format. The rendering unit **244** is configured to obtain a display layer of a tourist road, and superimpose the feature data in a text or picture format on the display layer. The playback unit **245** is configured to play the feature data in a voice format.

[0083] It may be understood that the terminal device **11** may be any device that supports a positioning and navigation function, including but not limited to a mobile phone, a tablet computer,

a wearable device, a vehicle-mounted device, an augmented reality (AR)/virtual reality (VR) device, a notebook computer, an ultra-mobile personal computer (UMPC), a netbook, a personal digital assistant (PDA), a dedicated camera (for example, a single-lens reflex camera or a card camera), and the like.

[0084] In some embodiments, as shown in FIG. 3C, the terminal device **11** may include a mobile phone, a vehicle-mounted tablet, a tablet computer, a smartwatch, and the like. The application module **24** may include a map application, a map applet, a browser application, and the like. The display module **23** may include a two-dimensional (2D) map interface, a three-dimensional (3D) map interface, a navigation map interface, and the like.

[0085] It can be understood that the structure illustrated in this embodiment does not constitute a specific limitation on the terminal device **11**. In some other embodiments, the terminal device **11** may include more or fewer components than those shown in the figure, or combine some components, or split some components, or have different component arrangements. The components shown in the figure may be implemented by hardware, software, or a combination of software and hardware.

[0086] With reference to the structure shown in FIG. 3A, an example in which a mobile phone **100** is used as the terminal device **11** is used to describe some embodiments.

[0087] FIG. 4A is a flowchart of steps of a display method according to some embodiments. As shown in FIG. 4A, the method specifically includes the following steps.

[0088] **S401**: The mobile phone **100** detects that the user enables tourist navigation.

[0089] In some embodiments, the user may enable map navigation by using the application **240** that has a map navigation function and that is in the mobile phone **100**. When detecting, by using the detection unit **241**, that the user taps to start the application **240**, the application **240** may obtain current location coordinates of the user from the positioning module **22** in the mobile phone **100** by using the obtaining unit **242**, obtain corresponding map data from the network device **13** based on the current location coordinates of the user, and display a map interface (as shown in FIG. 2B) of the map data on a display of the mobile phone **100** by using the display module **23** in the mobile phone **100** for the user to view, so that the user selects a route and performs query.

[0090] Further, after the user taps to start the application **240**, the user may choose whether to enable tourist navigation. When the detection unit **241** detects that the user enables tourist navigation, step **S402** is performed.

[0091] **S402**: The mobile phone **100** obtains the current location coordinates of the user, and determines whether the current location coordinates are located on a tourist road.

[0092] In some embodiments, the application **240** may obtain road location coordinates of the tourist road from the network device **13** in advance by using the communication module **21** in the mobile phone **100**, and store a correspondence between the road location coordinates and the corresponding tourist road. Therefore, when obtaining the current location coordinates of the user and determining the current location coordinates, the obtaining unit **242** may perform query and determining from the prestored correspondence.

[0093] For example, when obtaining, through query, the current location coordinates from the stored road location coordinates, the obtaining unit **242** may determine that the current location coordinates are located on the tourist road corresponding to the road location coordinates. Alternatively, for example, when not obtaining, through query, the current location coordinates from the stored road location coordinates, the obtaining unit **242** determines that the current location coordinates are not located on any tourist road.

[0094] In some embodiments, when obtaining, through query, the current location coordinates from the stored road location coordinates, the obtaining unit **242** may determine that the current location coordinates of the user are located on the tourist road corresponding to the road location coordinates. In this case, step **S411** is performed.

[0095] **S411**: The mobile phone **100** obtains feature data of the tourist road.

[0096] In some embodiments, when obtaining, through query, the current location coordinates from the stored road location coordinates, the obtaining unit **242** may determine that the current location coordinates are located on the tourist road corresponding to the road location coordinates. Then, the obtaining unit **242** may query, based on the tourist road on which the current location coordinates are located, the network device **13** for the feature data corresponding to the tourist road.

[0097] In some other embodiments, the application **240** may alternatively obtain the feature data of the tourist road from the network device **13** in advance by using the communication module **21** in the mobile phone **100**, and store a correspondence between each piece of feature data and a corresponding tourist road. Then, when determining that the current location coordinates are located on a tourist road, the obtaining unit **242** may obtain corresponding feature data from the correspondence.

[0098] In some embodiments, the feature data includes city feature data, road culture data, and road attraction data. For example, a tourist road corresponding to the current location coordinates is a road A of a city A, and the city feature data may include a tourism image based on the city A such as a cartoon image and an activity image of the city A. The road attraction data may include tourist attractions based on the road A such as an attraction A1, an attraction A2, and an attraction A3. The road culture data may include historical humanistic information based on the road A such as cultural information of the attraction A1 and historical information of the attraction A2.

[0099] **S412**: The mobile phone **100** separately displays a road interface for the tourist road, and superimposes the feature data on the road interface.

[0100] In some embodiments, before detecting that the user enables tourist navigation, if detecting that a map interface displayed by the display module **23** is the full map display interface shown in FIG. 2A, after detecting that the user enables tourist navigation, the detection unit **241** may switch the full map display interface shown in FIG. 2A displayed by the display module **23** to the driving road navigation display interface shown in FIG. 2B.

[0101] In some other embodiments, after the obtaining unit **242** determines that the current location coordinates are located on the tourist road, the detection unit **241** may also switch the full map display interface shown in FIG. 2A displayed by the display module **23** to the driving road navigation display interface shown in FIG. 2B.

[0102] It may be understood that when the mobile phone **100** detects that the user enables tourist navigation, or determines that a current location of the user is located on a tourist road, a display mode of a map interface on the mobile phone **100** is a road navigation display interface (as shown in FIG. 2B). The road navigation display interface may be a road on which the user is currently located after the mobile phone **100** detects that the user enables tourist navigation, or may be a tourist road after the mobile phone **100** determines that the current location of the user is located on the tourist road.

[0103] FIG. 4B is a flowchart of steps of displaying the feature data according to some embodiments. As shown in FIG. 4B, the method specifically includes the following steps.

[0104] **S412A**: The mobile phone **100** obtains feature data of a corresponding tourist road from the network device **13**.

[0105] In some embodiments, after determining that the current location coordinates are located on the tourist road, the mobile phone **100** queries the network device **13** for the feature data corresponding to the tourist road. When querying the network device **13** to obtain the feature data, the mobile phone **100** may synchronously obtain attraction location coordinates corresponding to each tourist attraction in the road attraction data in the feature data.

[0106] **S412B**: The mobile phone **100** performs data processing on the feature data to obtain voice data and a rendering element.

[0107] In some embodiments, the mobile phone **100** converts, by using the processing unit **243**, the city feature data and the road attraction data in the feature data into a rendering element in a text or picture format, and converts the road culture data into voice data in an MP3 format.

[0108] **S412C**: The mobile phone **100** obtains a display layer of the tourist road.

[0109] In some embodiments, the mobile phone **100** obtains the display layer **40** of the tourist road from the display interface of the display module **23** by using the rendering unit **244**.

[0110] **S412D**: The mobile phone **100** superimposes the rendering element on the display layer.

[0111] In some embodiments, steps **S412D** and **S412E** are described by using an example in which the road A of the city A is used as a tourist road on which the current location coordinates of the user are located. It may be understood that a tourist road corresponding to the current location coordinates is the road A of the city A, and the city feature data may include a snowflake tourism image based on the city A. The road attraction data may include a tourist attraction based on the road A such as a zoo, a botanical garden, and a museum. The road culture data may include historical humanistic information based on the road A such as historical zoo information and of museum culture information.

[0112] In some embodiments, the mobile phone **100** superimposes, on the display layer **40** by using the rendering unit **244**, the city feature data of the tourism image of the city A and rendering elements of the road attraction data of the attraction A1, the attraction A2, and the attraction A3 on the road A.

[0113] First, as shown in FIG. 5A, after obtaining the display layer **40** of the road A from the display interface of the display module **23**, the rendering unit **24** separately displays the display layer **40** of the road A by using the display module **23**, for example, the display layer of the road A.

[0114] Second, as shown in FIG. 5B, after the display module **23** separately displays the display layer **40** of the road A, the rendering unit **24** tiles a rendering element **54** of a tourism image picture on the display layer **40** or on a current driving lane of the user on the display layer **40**. For example, a snowflake picture is tiled on the display layer **40** or on a current driving lane of the user on the display layer **40**.

[0115] Further, based on the attraction location coordinates of tourist attractions in the feature data obtained by the mobile phone **100**, the rendering unit **24** may sequentially superimpose, based on corresponding attraction location coordinates and horizontal and vertical lines of the tourist road, rendering elements of the tourist attractions at intersection points between the corresponding horizontal and vertical lines and the tourist road.

[0116] As shown in FIG. 5C, based on the current location coordinates of the user, location coordinates of the attraction A1 and location coordinates of the attraction A2 are respectively located at a point-A location and a point-B location on the left and right sides of the road A, location coordinates of the attraction A3 are on the same side as the location coordinates of the attraction A2, and the location coordinates of the attraction A3 are located at a point-C location. In this way, a rendering element **52** of the attraction A2 and a rendering element **53** of the attraction A3 are respectively superimposed at intersection points between horizontal and vertical lines of the road A, and the point-B location and the point-C location, and are located on the right side of the road A. A rendering element **51** of the attraction A1 is superimposed at an intersection point between the point-A location and the horizontal and vertical lines of the road A, and are located on the left side of the road A.

[0117] It may be understood that when driving a vehicle to the location of the rendering element **52**, the user may turn to the right to see the attraction A2, and turn to the left to see the attraction A1. When driving a vehicle to the location of the rendering element **53**, the user may turn to the right to see the attraction A3, and the like. For example, the attraction A1 is a botanical garden, the attraction A2 is a zoo, and the attraction A3 is a museum. When driving a vehicle to the location of the rendering element **52**, the user may turn to the right to see the zoo, and turn to the left to see the botanical garden. When driving a vehicle to the location of the rendering element **53**, the user may turn to the right to see the museum, and the like.

[0118] Finally, as shown in FIG. 5D, after superimposing the road attraction data, the rendering unit **24** superimposes a rendering element **55** of text of the “city A” on the front side of the driving

vehicle on the display interface.

[0119] **S412E**: The mobile phone **100** plays the voice data.

[0120] In some embodiments, the mobile phone **100** plays voice data of the historical humanistic information such as cultural information of the attraction A1 and historical information of the attraction A2 by using the playback unit **245**. For example, voice data of historical humanistic information such as zoo historical information and museum cultural information is played.

[0121] In some embodiments, after the user drives a vehicle to pass through the location of the rendering element **51/52**, the rendering unit **24** may clear the rendering elements **51** and **52** from the display layer **40** based on the current location coordinates of the user, to prevent too many rendering elements on the display layer **40** from blocking road display.

[0122] It may be understood that the rendering element of the road tourist attraction displayed on the display layer **40** is located in front of the current location coordinates of the user. When the user drives a vehicle to pass through a rendering element, so that the rendering element is located behind the current location coordinates of the user, the rendering element disappears from the display layer **40**, so that each rendering element on the display layer **40** can be updated in real time based on the current location coordinates of the user, thereby improving user experience.

[0123] In some embodiments, the mobile phone **100** may determine, based on a vertical distance between a horizontal line of the attraction location coordinates of each tourist attraction and a horizontal line of the current location coordinates of the user, a display manner and a display location of the rendering element of each tourist attraction on the display layer **40**.

[0124] For example, the mobile phone **100** may display, on the display layer **40**, a rendering element of a tourist attraction within a vertical distance of 2 kilometers or 500 meters, and determine, based on a distance of each tourist attraction, a display size of a corresponding rendering element. This avoids displaying a rendering element of a far tourist attraction or rendering elements of too many tourist attractions on the display layer **40**, and correspondingly reduces time for the user to move from the current location coordinates to a location corresponding to the rendering element, so that the user can see a tourist attraction corresponding to a rendering element displayed by the mobile phone **100** in a short time, thereby improving user experience. In addition, correspondingly, display duration of the rendering element of the tourist attraction on the display layer **40** is shortened, thereby preventing the rendering element of the tourist attraction from blocking road display, and the like.

[0125] In some embodiments, when the mobile phone **100** detects that the user enables tourist navigation, or determines that a current location of the user is located on a tourist road, a display mode of a map interface on the mobile phone **100** is a road navigation display interface. In addition, when the mobile phone **100** determines that the current location of the user is located on a tourist road, a navigation road displayed on the road navigation display interface is the tourist road, so that a display layer of the tourist road can be enlarged. In this way, when corresponding feature data is subsequently superimposed on the display layer, viewing of the navigation road by the user is not affected, thereby improving road navigation safety.

[0126] It may be understood that the mobile phone **100** detects the current location coordinates of the user when the user uses the map application and enables tourist navigation. When detecting that the current location coordinates of the user match road location coordinates of a tourist road, the mobile phone **100** may determine that the user is currently located on the tourist road, and then automatically obtain feature data of the tourist road. Further, the mobile phone **100** separately displays a road interface for the tourist road on the display, and superimposes the feature data on the road interface. In this way, the user can perform road navigation through the road interface displayed by the mobile phone **100**, and can also view, through the road interface, tourist attraction information related to the tourist road. In addition, the mobile phone **100** may further perform voice playback on historical humanistic information related to the tourist road, to improve user experience.

[0127] In some other embodiments, when not obtaining, through query, the current location coordinates from the stored road location coordinates, the obtaining unit **242** may determine that the current location coordinates of the user are not located on any tourist road. In this case, step **S421** is performed.

[0128] **S421**: The mobile phone **100** obtains destination location coordinates of the user.

[0129] In some embodiments, when not obtaining, through query, the current location coordinates from the stored road location coordinates, the obtaining unit **242** may determine that the user currently does not drive on any tourist road.

[0130] It may be understood that although the obtaining unit **242** determines that the user currently does not drive on any tourist road, because the user enables tourist navigation, it may indicate that the user has a requirement for a tourist road, and a navigation route that includes a tourist road in a target range may be queried based on the current location coordinates of the user and the destination location coordinates of the user, so that the user switches and selects a route.

[0131] **S422**: The mobile phone **100** queries, based on the current location coordinates and the destination location coordinates, a navigation route that meets a target condition in the target range, where the target condition indicates that a driving road in the navigation route includes a tourist road.

[0132] In some embodiments, the target range is determined based on a dynamic threshold K and a distance L between the current location coordinates and destination location coordinates.

[0133] For example, the target range may be in a semi-circle range of 90 degrees to the left and right or may be in a sector range of 30 degrees to each of the left and right, which is in a direction of a connection line between the current location coordinates and a destination location and is obtained by using a product of the distance L and the dynamic threshold K as a radius. This is not specifically limited.

[0134] In some embodiments, the dynamic threshold K is any constant greater than 0 and less than or equal to 1. Long driving time for the user to switch a navigation route due to an excessively large target range can be avoided by limiting the dynamic threshold K . It may be understood that a queried target range is limited by using the dynamic threshold K , and driving time of a navigation route obtained through query is also limited by using the dynamic threshold K .

[0135] For example, as shown in FIG. 6A, the target range may be a sector **61** about 30 degrees to the left and right, which is in the direction of the connection line between the current location coordinates and the destination location coordinates and which is obtained by using the product of a distance L between the current location coordinates and a destination location and the dynamic threshold K as a radius.

[0136] In some embodiments, a value of the dynamic threshold K may be determined based on a value of the distance L . For example, when the distance L ranges from 0 to 5 kilometers, the dynamic threshold K is 0.2; or when the distance L ranges from 5 to 10 kilometers, the dynamic threshold K is 0.5. This is not specifically limited.

[0137] In some other embodiments, when the obtaining unit **242** does not obtain, through query, the destination location coordinates, that is, the user uses the map application to view only a navigation direction, but does not enter the destination location coordinates to perform route navigation, the obtaining unit **242** queries a tourist road in the target range based on a direction in which the user drives a vehicle. The target range may be a tourist road in a range such as a distance of 2 kilometers or 10 kilometers from the current location coordinates, or the target range may be a tourist road in a range such as driving time of 10 minutes or 20 minutes from the current location coordinates. This is not specifically limited.

[0138] **S423**: The mobile phone **100** returns a query result to the user, and detects a route switching operation of the user.

[0139] In some embodiments, as shown in FIG. 6B, a navigation route **62** including a tourist road is obtained through query based on the sector **61**, and an original navigation route **63** and the

navigation route **62** newly obtained through query are displayed on the display interface. In addition, the mobile phone **100** calculates, by using the processing unit **243**, driving time increased by the navigation route **62** relative to the navigation route **63**, and prompts the user on the display interface of the mobile phone **100**.

[0140] In some other embodiments, the mobile phone **100** may alternatively respectively calculate driving time of the navigation route **63** and that of the navigation route **62** by using the processing unit **243**, and prompt the user of the driving time of the navigation route **63** and that of the navigation route **62** on the display interface of the mobile phone **100**.

[0141] **S424**: The mobile phone **100** detects the route switching operation of the user, and detects that the current location coordinates of the user are located on the tourist road.

[0142] In some embodiments, as shown in FIG. **6C**, when the user chooses to switch from the navigation route **63** to the navigation route **62** for driving, the navigation route **62** is separately displayed on the display interface.

[0143] In some embodiments, after the user switches to the navigation route **62**, the mobile phone **100** detects the current location coordinates of the user. When obtaining the current location coordinates by querying stored road location coordinates of the tourist road included in the navigation route **62**, the mobile phone **100** may determine that the current location coordinates of the user are on the tourist road corresponding to the navigation route **62**. In this case, step **S411** is performed.

[0144] It may be understood that after step **S411** is performed, the mobile phone **100** may obtain feature data of the tourist road, to separately display a road interface for the tourist road, and may superimpose the feature data on the road interface. In this way, the user can perform road navigation through the road interface displayed by the mobile phone **100**, and can also view, through the road interface, tourist attraction information related to the tourist road.

[0145] It may be understood that the mobile phone **100** detects the current location coordinates of the user when the user uses the map application and enables tourist navigation. When detecting that the current location coordinates of the user are not located on any tourist road, the mobile phone **100** may obtain destination location coordinates of the user, actively query a tourist road in the target range for the user based on the current location coordinates and the destination location coordinates, and return a query result to the user, so that the user can choose whether to switch a navigation route. When the user performs map navigation, the mobile phone **100** can actively query the tourist road, and the user does not need to switch an interface for separate query, thereby improving user experience.

[0146] With reference to the flowchart shown in FIG. **4A**, the following separately explains and describes a scenario in which the current location coordinates of the user are located on the tourist road and a scenario in which the current location coordinates of the user are not located on the tourist road.

[0147] FIG. **7A** is a flowchart of steps of navigation display according to some embodiments. As shown in FIG. **7A**, the method specifically includes the following steps.

[0148] **S711**: The mobile phone **100** detects that the user starts the application **240**.

[0149] In some embodiments, after the mobile phone **100** detects that the user starts the map application **240**, an application interface of the map application **240** may be displayed through the display module **23** of the mobile phone **100**. In addition, when detecting, by using the detection unit **241**, that the user taps to start the application **240**, the application **240** may obtain current location coordinates of the user from the positioning module **22** in the mobile phone **100** by using the obtaining unit **242**, obtain corresponding map data from the network device **13** based on the current location coordinates of the user, and display a map interface (as shown in FIG. **2B**) of the map data on a display of the mobile phone **100** by using the display module **23** in the mobile phone **100** for the user to view, so that the user selects a route and performs query.

[0150] **S712**: The mobile phone **100** detects a user operation.

[0151] In some embodiments, after the user taps to start the application **240**, the user may tap an enabling button of tourist navigation to enable tourist navigation, or the user may enable tourist navigation in a voice conversation manner.

[0152] **S713**: The mobile phone **100** determines whether the user operation is enabling tourist navigation.

[0153] In some embodiments, when the mobile phone **100** detects, by using the detection unit **241**, that the user operation is not the operation of enabling tourist navigation, or no user operation is detected, step **S712** is performed. In some other embodiments, when the detection unit **241** detects that the user operation is the operation of enabling tourist navigation, step **S714** is performed.

[0154] **S714**: The mobile phone **100** obtains feature data of a corresponding tourist road from the network device **13**.

[0155] In some embodiments, the application **240** may obtain road location coordinates of the tourist road from the network device **13** in advance by using the communication module **21** in the mobile phone **100**, and store a correspondence between the road location coordinates and the corresponding tourist road. Therefore, when obtaining the current location coordinates of the user and determining the current location coordinates, the obtaining unit **242** may perform query and determining from the prestored correspondence.

[0156] In some embodiments, when obtaining, through query, the current location coordinates from the stored road location coordinates, the obtaining unit **242** may determine that the current location coordinates of the user are located on the tourist road corresponding to the road location coordinates. In this case, step **S715** is performed.

[0157] **S715**: The mobile phone **100** performs data processing on the feature data to obtain voice data and a rendering element.

[0158] In some embodiments, the mobile phone **100** converts, by using the processing unit **243**, the city feature data and the road attraction data in the feature data into a rendering element in a text or picture format, and converts the road culture data into voice data in an MP3 format.

[0159] **S715A**: The mobile phone **100** superimposes the rendering element on the display layer of the tourist road.

[0160] In some embodiments, the mobile phone **100** obtains the display layer of the tourist road from the display interface of the display module **23** by using the rendering unit **244**, and superimposes rendering elements of the city feature data and the road scenic spot data on the display layer. For a specific superimposition process, refer to related descriptions of the step flowchart in FIG. **4B** and the diagrams in FIG. **5A** to FIG. **5D**. Details are not described herein again.

[0161] **S715B**: The mobile phone **100** plays the voice data.

[0162] In some embodiments, the mobile phone **100** plays the voice data of the road culture data by using the playback unit **245**.

[0163] It may be understood that the mobile phone **100** detects the current location coordinates of the user when the user uses the map application and enables tourist navigation. When detecting that the current location coordinates of the user match road location coordinates of a tourist road, the mobile phone **100** may determine that the user is currently located on the tourist road, and then automatically obtain feature data of the tourist road. Further, the mobile phone **100** separately displays a road interface for the tourist road on the display, and superimposes the feature data on the road interface. In this way, the user can perform road navigation through the road interface displayed by the mobile phone **100**, and can also view, through the road interface, tourist attraction information related to the tourist road. In addition, the mobile phone **100** may further perform voice playback on historical humanistic information related to the tourist road, to improve user experience.

[0164] FIG. **7B** is a flowchart of steps of another navigation display according to some embodiments. As shown in FIG. **7B**, the method specifically includes the following steps.

[0165] S721: The mobile phone **100** detects that the user starts the application **240**.

[0166] In some embodiments, after the mobile phone **100** detects that the user starts the map application **240**, an application interface of the map application **240** may be displayed through the display module **23** of the mobile phone **100**. In addition, when detecting, by using the detection unit **241**, that the user taps to start the application **240**, the application **240** may obtain current location coordinates of the user from the positioning module **22** in the mobile phone **100** by using the obtaining unit **242**, obtain corresponding map data from the network device **13** based on the current location coordinates of the user, and display a map interface (as shown in FIG. 2B) of the map data on a display of the mobile phone **100** by using the display module **23** in the mobile phone **100** for the user to view, so that the user selects a route and performs query.

[0167] S722: The mobile phone **100** detects a user operation.

[0168] In some embodiments, after the user taps to start the application **240**, the user may tap an enabling button of tourist navigation to enable tourist navigation, or the user may enable tourist navigation in a voice conversation manner.

[0169] S723: The mobile phone **100** determines whether the user operation is enabling tourist navigation.

[0170] In some embodiments, when the mobile phone **100** detects, by using the detection unit **241**, that the user operation is not the operation of enabling tourist navigation, or no user operation is detected, step S722 is performed. In some other embodiments, when the detection unit **241** detects that the user operation is the operation of enabling tourist navigation, step S724 is performed.

[0171] S724: The mobile phone **100** obtains the current location coordinates and the destination location coordinates of the user, and obtains, through query based on the current location coordinates and the destination location coordinates, a navigation route that meets a target condition in the target range.

[0172] In some embodiments, the target condition indicates that a driving road of the navigation route includes a tourist road. As shown in FIG. 6A, the target range may be a sector **61** about 30 degrees to each of the left and right, which is in the direction of the connection line between the current location coordinates and the destination location coordinates and which is obtained by using the product of a distance L between the current location coordinates and a destination location and the dynamic threshold K as a radius.

[0173] S725: The mobile phone **100** calculates a driving time difference for switching a route.

[0174] In some embodiments, as shown in FIG. 6B, a navigation route **62** including a tourist road is obtained through query based on the sector **61**, and an original navigation route **63** and the navigation route **62** newly obtained through query are displayed on the display interface. In addition, the mobile phone **100** calculates, by using the processing unit **243**, driving time increased by the navigation route **62** relative to the navigation route **63**, and prompts the user on the display interface of the mobile phone **100**. For a specific process of querying the navigation route, refer to related descriptions of the foregoing steps S421 to S423 and the diagrams of FIG. 6A to FIG. 6C. Details are not described herein again.

[0175] S726: After detecting that the user switches a navigation route, the mobile phone **100** provides a voice prompt.

[0176] In some embodiments, as shown in FIG. 6C, when the user chooses to switch from the navigation route **63** to the navigation route **62** for driving, the navigation route **62** is displayed on the display interface, and the mobile phone **100** provides, by using the playback unit **245**, a voice prompt indicating that the navigation route is successfully switched.

[0177] It may be understood that the mobile phone **100** detects the current location coordinates of the user when the user uses the map application and enables tourist navigation. When detecting that the current location coordinates of the user are not located on any tourist road, the mobile phone **100** may obtain destination location coordinates of the user, actively query a tourist road in the target range for the user based on the current location coordinates and the destination location

coordinates, and return a query result to the user, so that the user can choose whether to switch a navigation route. When the user performs map navigation, the mobile phone **100** can actively query the tourist road, and the user does not need to switch an interface for separate query, thereby improving user experience.

[0178] In some embodiments, the mobile phone **100** determines that the current location coordinates of the user are located on a tourist road corresponding to the road location coordinates, separately displays a road interface for the tourist road on the display, and superimposes feature data on the road interface. The mobile phone **100** may further continue to obtain the destination location coordinates of the user, and query, based on the current location coordinates and the destination location coordinates, a navigation route that meets the target condition in the target range. Alternatively, when not obtaining the destination location coordinates of the user, the mobile phone **100** may query, based on the current location coordinates, a navigation route that meets the target condition in the target range, and return a navigation route obtained through query to the user for selection among a plurality of routes.

[0179] It may be understood that when the mobile phone **100** queries, based on the current location coordinates and/or the destination location coordinates, the navigation route that meets the target condition in the target range, the current location coordinates of the user may be located on a tourist road, or may be located on any road of another non-tourist road. That is, when the current location coordinates of the user are located on the tourist road A, the mobile phone **100** may actively query another tourist road for the user, for example, a tourist road B, and return a query result to the user, so that the user selects between the tourist road A and the tourist road B, to provide diversified tourist road recommendations for the user, thereby improving user experience.

[0180] FIG. **8** is a diagram of a structure of a mobile phone **100** according to some embodiments.

[0181] It may be understood that the structure shown in this embodiment does not constitute a specific limitation on the mobile phone **100**. In some other embodiments, the mobile phone **100** may include more or fewer components than those shown in the figure, combine some components, split some components, or have different component arrangements. The components shown in the figure may be implemented by hardware, software, or a combination of software and hardware.

[0182] As shown in FIG. **8**, the mobile phone **100** may include a processor **110**, an external memory interface **120**, an internal memory **121**, a universal serial bus (USB) interface **130**, a charging management module **140**, a power management module **141**, a battery **142**, an antenna **1**, an antenna **2**, a mobile communication module **150**, a wireless communication module **160**, an audio module **170**, a speaker **170A**, a receiver **170B**, a microphone **170C**, a headset jack **170D**, a sensor module **180**, a button **190**, a motor **191**, an indicator **192**, a camera **193**, a display **194**, a subscriber identity module (SIM) card interface **195**, and the like. The sensor module **180** may include a pressure sensor **180A**, a gyroscope sensor **180B**, a barometric pressure sensor **180C**, a magnetic sensor **180D**, an acceleration sensor **180E**, a distance sensor **180F**, an optical proximity sensor **180G**, a fingerprint sensor **180H**, a temperature sensor **180J**, a touch sensor **180K**, an ambient light sensor **180L**, a bone conduction sensor **180M**, and the like.

[0183] The processor **110** may include one or more processing units. For example, the processor **110** may include an application processor (AP), a modem processor, a graphics processing unit (GPU), an image signal processor (ISP), a controller, a video codec, a digital signal processor (DSP), a baseband processor, a neural-network processing unit (NPU), and/or the like. Different processing units may be independent components, or may be integrated into one or more processors. The controller may generate an operation control signal based on an instruction operation code and a time sequence signal, to complete control of instruction reading and instruction execution. In some embodiments, the processor **110** may execute an instruction corresponding to the display method provided in the foregoing embodiments.

[0184] A memory may be further disposed in the processor **110**, and is configured to store instructions and data. In some embodiments, the memory in the processor **110** is a cache. The

memory may store instructions or data that has been used or cyclically used by the processor **110**. If the processor **110** needs to use the instructions or the data again, the processor **110** may directly invoke the instructions or the data from the foregoing memory. This avoids repeated access, reduces waiting time of the processor **110**, and improves processing efficiency.

[0185] In some embodiments, the processor **110** may include one or more interfaces. The interface may include an inter-integrated circuit (I2C) interface, an inter-integrated circuit sound (I2S) interface, a pulse-code modulation (PCM) interface, a universal asynchronous receiver/transmitter (UART) interface, a mobile industry processor interface (MIPI), a general-purpose input/output (GPIO) interface, a SIM interface, a USB interface, and/or the like.

[0186] The USB interface **130** is an interface conforming to a USB standard specification, and may be specifically a mini USB interface, a micro USB interface, a USB Type-C interface, or the like. The USB interface **130** may be configured to connect to a charger to charge the mobile phone **100**, or may be configured to transmit data between the mobile phone **100** and a peripheral device, or may be configured to connect to a headset for playing audio by using the headset. The interface may be further configured to connect to another terminal device, for example, an AR device.

[0187] It may be understood that an interface connection relationship between the modules shown in this embodiment is merely an example for description, and does not constitute a limitation on the structure of the mobile phone **100**. In some other embodiments, the mobile phone **100** may alternatively use an interface connection manner different from that in the foregoing embodiment, or use a combination of a plurality of interface connection manners.

[0188] The charging management module **140** is configured to receive a charging input from a charger. The charger may be a wireless charger or a wired charger. In some embodiments of wired charging, the charging management module **140** may receive a charging input of the wired charger through the USB interface **130**. In some embodiments of wireless charging, the charging management module **140** may receive a wireless charging input through a wireless charging coil of the mobile phone **100**. The charging management module **140** may further supply power to the mobile phone **100** by using the power management module **141** while charging the battery **142**.

[0189] The power management module **141** is configured to connect to the battery **142**, the charging management module **140**, and the processor **110**. The power management module **141** receives an input from the battery **142** and/or the charging management module **140**, and supplies power to the processor **110**, the internal memory **121**, the display **194**, the camera **193**, the wireless communication module **160**, and the like. The power management module **141** may be further configured to monitor parameters such as a battery capacity, a battery cycle count, and a battery health status (electric leakage or impedance). In some other embodiments, the power management module **141** may alternatively be disposed in the processor **110**. In some other embodiments, the power management module **141** and the charging management module **140** may alternatively be disposed in a same device.

[0190] A wireless communication function of the mobile phone **100** may be implemented through the antenna **1**, the antenna **2**, the mobile communication module **150**, the wireless communication module **160**, the modem processor, the baseband processor, and the like. The antenna **1** and the antenna **2** are configured to transmit and receive an electromagnetic wave signal. Each antenna in the mobile phone **100** may be configured to cover one or more communication bands. Different antennas may be further multiplexed, to improve antenna utilization. For example, the antenna **1** may be multiplexed as a diversity antenna of a wireless local area network. In some other embodiments, the antenna may be used in combination with a tuning switch.

[0191] The mobile communication module **150** may provide a wireless communication solution that is applied to the mobile phone **100** and that includes second generation/third generation/fourth generation/fifth generation/sixth generation (2G/3G/4G/5G/6G), or the like. The mobile communication module **150** may include at least one filter, a switch, a power amplifier, a low-noise amplifier (LNA), and the like. The mobile communication module **150** may receive an

electromagnetic wave through the antenna **1**, perform processing such as filtering or amplification on the received electromagnetic wave, and transmit the electromagnetic wave to the modem processor for demodulation. The mobile communication module **150** may further amplify a signal modulated by the modem processor, and convert the signal into an electromagnetic wave for radiation through the antenna **1**. In some embodiments, at least some functional modules in the mobile communication module **150** may be disposed in the processor **110**. In some embodiments, at least some functional modules of the mobile communication module **150** may be disposed in a same device as at least some modules of the processor **110**.

[0192] The modem processor may include a modulator and a demodulator. The modulator is configured to modulate a to-be-sent low-frequency baseband signal into a medium-high frequency signal. The demodulator is configured to demodulate a received electromagnetic wave signal into a low-frequency baseband signal. Then, the demodulator transmits the low-frequency baseband signal obtained through demodulation to the baseband processor for processing. The low-frequency baseband signal is processed by the baseband processor and then is transferred to the application processor. The application processor outputs a sound signal through an audio device (which is not limited to the speaker **170A**, the receiver **170B**, or the like), or displays an image or a video through the display **194**. In some embodiments, the modem processor may be an independent device. In some other embodiments, the modem processor may be independent of the processor **110**, and is disposed in a same device as the mobile communication module **150** or another functional module.

[0193] The wireless communication module **160** may provide a wireless communication solution that is applied to the mobile phone **100** and that includes a wireless local area network (WLAN) (for example, a Wi-Fi network), BLUETOOTH (BT), a global navigation satellite system (GNSS), frequency modulation (FM), a near-field communication (NFC) technology, an infrared (IR) technology, or the like. The wireless communication module **160** may be one or more devices integrating at least one communication processing module. The wireless communication module **160** receives an electromagnetic wave by the antenna **2**, performs frequency modulation and filtering processing on an electromagnetic wave signal, and sends a processed signal to the processor **110**. The wireless communication module **160** may further receive a to-be-sent signal from the processor **110**, perform frequency modulation and amplification on the signal, and convert the signal into an electromagnetic wave for radiation through the antenna **2**.

[0194] In some embodiments, in the mobile phone **100**, the antenna **1** and the mobile communication module **150** are coupled, and the antenna **2** and the wireless communication module **160** are coupled, so that the mobile phone **100** can communicate with a network and another device by using a wireless communication technology. The wireless communication technology may include a Global System for Mobile Communications (GSM), a general packet radio service (GPRS), code-division multiple access (CDMA), wideband code division multiple access (WCDMA), time-division code division multiple access (TD-SCDMA), Long-Term Evolution (LTE), 5G and subsequent evolution standards, BT, a GNSS, a WLAN, NFC, FM, an IR technology, and/or the like. The GNSS may include a GPS, a global navigation satellite system (GLONASS), a BDS, a quasi-zenith satellite system (QZSS), and/or a satellite-based augmentation system (SBAS).

[0195] The mobile phone **100** implements a display function by using the GPU, the display **194**, the application processor, and the like. The GPU is a microprocessor for image processing, and is connected to the display **194** and the application processor. The GPU is configured to perform mathematical and geometric computation; and render an image. The processor **110** may include one or more GPUs that execute program instructions to generate or change display information.

[0196] The display **194** is configured to display an image, a video, and the like. The display **194** includes a display panel. In some embodiments, the mobile phone **100** may include one or N displays **194**, where N is a positive integer greater than 1.

[0197] The mobile phone **100** can implement a photographing function by using the ISP, the camera **193**, the video codec, the GPU, the display **194**, the application processor, and the like. The ISP is configured to process data fed back by the camera **193**. For example, during photographing, a shutter is pressed, and light is transferred to a photosensitive element of the camera through a lens. An optical signal is converted into an electrical signal, and the photosensitive element of the camera transfers the electrical signal to the ISP for processing, to convert the electrical signal into a visible image. The ISP may further perform algorithm optimization on noise, brightness, and complexion of the image. The ISP may further optimize parameters such as exposure and a color temperature of a photographing scenario. In some embodiments, the ISP may be disposed in the camera **193**.

[0198] The camera **193** is configured to capture a static image or a video. An optical image of an object is generated through a lens, and is projected onto a photosensitive element. The photosensitive element may be a charge-coupled device (CCD) or a complementary metal-oxide-semiconductor (CMOS) phototransistor. The photosensitive element converts an optical signal into an electrical signal, and then transfers the electrical signal to the ISP to convert the electrical signal into a digital image signal. The ISP outputs the digital image signal to the DSP for processing. The DSP converts the digital image signal into an image signal in a standard format such as red-green-blue RGB or chroma-red projection-blue projection (YUV). In some embodiments, the mobile phone **100** may include one or N cameras **193**, where N is a positive integer greater than 1.

[0199] The digital signal processor is configured to process a digital signal, and may process another digital signal in addition to the digital image signal. For example, when the mobile phone **100** selects a frequency, the digital signal processor is configured to perform Fourier transform on frequency energy.

[0200] The video codec is configured to compress or decompress a digital video. The mobile phone **100** may support one or more video codecs. In this way, the mobile phone **100** can play or record videos in a plurality of coding formats, for example, moving picture experts group (MPEG)-1, MPEG-2, MPEG-3, and MPEG-4.

[0201] The NPU is a neural-network (NN) computing processor, and quickly processes input information by emulating a biological neural network structure, for example, by emulating a mode of transfer between human-brain neurons, and may further perform self-learning constantly. The NPU can implement applications such as intelligent cognition of the mobile phone **100**, for example, image recognition, facial recognition, speech recognition, and text understanding.

[0202] The external memory interface **120** may be configured to connect to an external storage card, for example, a microSD card, to extend a storage capability of the terminal device **100**. The external memory card communicates with the processor **110** through the external memory interface **120**, to implement a data storage function. For example, files such as music and a video are stored in the external storage card.

[0203] The internal memory **121** may be configured to store computer-executable program code. The executable program code includes instructions. The internal memory **121** may include a program storage area and a data storage area. The program storage area may store an operating system, an application required for at least one function (such as a sound playing function and an image display function), and the like. The data storage area may store data (such as audio data and an address book) and the like created during use of the mobile phone **100**. In addition, the internal memory **121** may include a high-speed random access memory, or may include a nonvolatile memory, for example, at least one magnetic disk storage device, a flash memory, or a universal flash storage (UFS). The processor **110** runs instructions stored in the internal memory **121** and/or instructions stored in a memory disposed in the processor, to perform various function applications of the mobile phone **100** and data processing. For example, in some embodiments, the internal memory **121** may be configured to temporarily store an instruction of the display method provided in the foregoing embodiments.

[0204] The mobile phone **100** may implement an audio function such as music playing and recording by using the audio module **170**, the speaker **170A**, the receiver **170B**, the microphone **170C**, the headset jack **170D**, the application processor, and the like.

[0205] The SIM card interface **195** is configured to connect to a SIM card. The SIM card may be inserted into the SIM card interface **195** or pulled out of the SIM card interface **195**, to implement contact with or separation from the mobile phone **100**. The mobile phone **100** may support one or N SIM card interfaces, where N is a positive integer greater than 1. The SIM card interface **195** can support a nano-SIM card, a micro-SIM card, a SIM card, and the like. A plurality of cards may be inserted into a same SIM card interface **195** at the same time. The plurality of cards may be of a same type or different types. The SIM card interface **195** may also be compatible with different types of SIM cards. The SIM card interface **195** may also be compatible with an external storage card. The mobile phone **100** interacts with a network by using the SIM card, to implement functions such as calling and data communication. In some embodiments, the mobile phone **100** uses an eSIM, that is, an embedded SIM card. The eSIM card may be embedded in the mobile phone **100**, and cannot be separated from the mobile phone **100**.

[0206] In the accompanying drawings, some structural or method features may be shown in a particular arrangement and/or order. However, it should be understood that such a particular arrangement and/or order may not be needed. In some embodiments, these features may be arranged in a manner and/or order different from those that shown in the descriptive accompanying drawings. In addition, inclusion of the structural or method features in a particular figure does not imply that such features are needed in all embodiments, and in some embodiments, these features may not be included or may be combined with other features.

[0207] It should be noted that all units/modules mentioned in the device embodiments of this disclosure are logical units/modules. Physically, one logical unit/module may be one physical unit/module, may be a part of one physical unit/module, or may be implemented by using a combination of a plurality of physical units/modules. Physical implementations of these logical units/modules are not the most important, and a combination of functions implemented by these logical units/modules is a key to resolving technical issues proposed in this disclosure. In addition, a unit/module that is not closely related to resolving the technical problem is not described in the foregoing device embodiments. This does not mean that there are no other units/modules in the foregoing device embodiments.

[0208] It should be noted that in the examples and the specification of this patent, relational terms such as first and second are merely used to distinguish one entity or operation from another, and do not necessarily require or imply any such actual relationship or order between these entities or operations. Moreover, terms “include”, “comprise”, or any other variants thereof are intended to cover a non-exclusive inclusion, so that a process, a method, an article, or a device that includes a list of elements includes those elements, and also includes other elements which are not expressly listed, or further includes elements inherent to this process, method, article, or device. Without more limitations, an element limited by “include a/an” does not exclude other same elements existing in the process, the method, the article, or the device which includes the element.

[0209] Although this disclosure has been illustrated and described with reference to some embodiments, a person of ordinary skill in the art should understand that various changes may be made in form and detail without departing from the scope of this disclosure.

Claims

1. A method comprising: displaying a navigation interface; displaying a first road on the navigation interface; moving to a first location; and displaying, on the first road on the navigation interface, a first road feature corresponding to the first location.
2. The method of claim 1, wherein the first road feature comprises a first feature location, and

wherein the method further comprises determining, based on the first feature location, a first display location of the first road feature.

3. The method of claim 2, further comprising further determining the first display location based on a connection line intersection point between the first feature location and the first road or based on a first distance between the first feature location and the first location.

4. The method of claim 3, wherein the first distance meets a first distance condition.

5. The method of claim 1, further comprising: moving from the first location to a second location; and hiding the first road feature.

6. The method of claim 1, further comprising: wherein the first location on the first road.

7. The method of claim 1, further comprising displaying, on the first road on the navigation interface, a second road feature.

8. The method of claim 7, wherein displaying the second road feature comprises displaying at least one of, a city image feature, a city activity feature, a city tourism feature, a city historical feature, or a city humanistic feature.

9. The method of claim 1, wherein before displaying the first road on the navigation interface, the method further comprises: displaying a first navigation route on the navigation interface; querying, based on the first navigation route, a second navigation route that comprises the first road to obtain a query result; and displaying the query result on the navigation interface.

10. The method of claim 9, wherein displaying the query result comprises: displaying the first navigation route and a first navigation time of the first navigation route; displaying the first navigation route, the first navigation time and a second navigation time of the second navigation route; or displaying the second navigation route and a time difference between first navigation time and the second navigation time.

11. A terminal device, comprising: a memory configured to store instructions; and one or more processors configured to execute the instructions to cause the terminal device to: display a navigation interface; display a first road on the navigation interface; detect moving, by the terminal device, to a first location; and display, on the first road on the navigation interface, a first road feature corresponding to the first location.

12. The terminal device of claim 11, wherein the first road feature comprises a first feature location, and wherein the one or more processors are further configured to execute the instructions to cause the terminal device to determine, based on the first feature location, a first display location of the first road feature.

13. The terminal device of claim 12, wherein the one or more processors are further configured to execute the instructions to cause the terminal device to further determine the first display location based on a connection line intersection point between the first feature location and the first road or based on a first distance between the first feature location and the first location.

14. The terminal device of claim 13, wherein the first distance meets a first distance condition.

15. The terminal device of claim 11, wherein the one or more processors are configured to execute the instructions to further cause the terminal device to: detect movement of the terminal device from the first location to a second location; and hide the first road feature.

16. The terminal device of claim 11, wherein the first location is on the first road.

17. The terminal device of claim 11, wherein the one or more processors are further configured to execute the instructions to cause the terminal device to display a second road feature.

18. The terminal device of claim 17, wherein displaying the second road feature comprises displaying at least one of, a city image feature, a city activity feature, a city tourism feature, a city historical feature, and a city humanistic feature.

19. The terminal device of claim 11, wherein before displaying the first road on the navigation interface, the one or more processors are further configured to execute the instructions to cause the terminal device to: display a first navigation route on the navigation interface; query, based on the first navigation route, a second navigation route that comprises the first road to obtain a query

result; and display the query result on the navigation interface.

20. The terminal device of claim 19, wherein the terminal device is further enabled to: display the first navigation route and a first navigation time of the first navigation route; or display the first navigation route, the first navigation time, and a second navigation time of the second navigation route; or display the second navigation route and a time difference between first navigation time and the second navigation time.
