

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250279363

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

HUANG; TSE-YAO

SEMICONDUCTOR DEVICE STRUCTURE WITH ENERGY REMOVABLE STRUCTURE AND METHOD FOR PREPARING THE SAME

Abstract

A semiconductor device structure includes a first dielectric layer over a semiconductor substrate, and a first energy removable structure in the first dielectric layer. The semiconductor device structure also includes a second dielectric layer over the first dielectric layer, and an N.sup.th dielectric layer over the second dielectric layer. The N is an integer greater than 2. The semiconductor device structure further includes a first conductor in the N.sup.th dielectric layer, and an (N+1).sup.th dielectric layer over the N.sup.th dielectric layer. A top surface of the first conductor is exposed by a first opening, and a top surface of the first energy removable structure is exposed by a second opening.

Inventors: HUANG; TSE-YAO (TAIPEI CITY, TW)

Applicant: NANYA TECHNOLOGY CORPORATION (NEW TAIPEI CITY, TW)

Family ID: 91280122

Appl. No.: 19/206351

Filed: May 13, 2025

Related U.S. Application Data

parent US continuation 18075666 20221206 PENDING child US 19206351

Publication Classification

Int. Cl.: H01L23/528 (20060101); H01L21/311 (20060101); H01L21/768 (20060101);
H01L23/522 (20060101)

U.S. Cl.:

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION [0001] This application is a continuation application of U.S. Non-Provisional application Ser. No. 18/075,666 filed Dec. 6, 2022, which is incorporated herein by reference in its entirety.

TECHNICAL FIELD

[0002] The present disclosure relates to a semiconductor device structure and a method for preparing the same, and more particularly, to a semiconductor device structure with an energy removable structure and a method for preparing the same.

DISCUSSION OF THE BACKGROUND

[0003] Semiconductor devices are essential for many modern applications. With the advancement of electronic technology, semiconductor devices are becoming smaller in size while providing greater functionality and including greater amounts of integrated circuitry. Due to the miniaturized scale of semiconductor devices, various types and dimensions of semiconductor devices providing different functionalities are integrated and packaged into a single module. Furthermore, numerous manufacturing operations are implemented for integration of various types of semiconductor devices.

[0004] However, the manufacturing and integration of semiconductor devices involve many complicated steps and operations. Integration in semiconductor devices becomes increasingly complicated. An increase in complexity of manufacturing and integration of the semiconductor device may cause deficiencies. Accordingly, there is a continuous need to improve the manufacturing process of semiconductor devices so that the problems can be addressed.

[0005] This Discussion of the Background section is provided for background information only. The statements in this Discussion of the Background are not an admission that the subject matter disclosed in this section constitutes prior art to the present disclosure, and no part of this Discussion of the Background section may be used as an admission that any part of this application, including this Discussion of the Background section, constitutes prior art to the present disclosure.

SUMMARY

[0006] In one embodiment of the present disclosure, a semiconductor device structure is provided. The semiconductor device structure includes a first dielectric layer disposed over a semiconductor substrate, and a first energy removable structure disposed in the first dielectric layer. The semiconductor device structure also includes a second dielectric layer disposed over the first dielectric layer, and an N^{th} dielectric layer disposed over the second dielectric layer. The N is an integer greater than 2. The semiconductor device structure further includes a first conductor disposed in the N^{th} dielectric layer, and an $(N+1)^{\text{th}}$ dielectric layer disposed over the N^{th} dielectric layer. A top surface of the first conductor is exposed by a first opening, and a top surface of the first energy removable structure is exposed by a second opening.

[0007] In an embodiment, the first energy removable structure penetrates through the first dielectric layer. In an embodiment, a bottom surface of the first conductor is higher than a bottom surface of the N^{th} dielectric layer. In an embodiment, the first conductor is in direct contact with the $(N+1)^{\text{th}}$ dielectric layer. In an embodiment, the semiconductor device structure further includes a second conductor disposed in the $(N+1)^{\text{th}}$ dielectric layer. In an embodiment, the semiconductor device structure further includes an $(N+2)^{\text{th}}$ dielectric layer disposed over the $(N+1)^{\text{th}}$ dielectric layer, wherein a top surface of the second conductor is exposed by a third opening. In an embodiment, a bottom surface of the second conductor is higher than a bottom

surface of the (N+1).sup.th dielectric layer.

[0008] In another embodiment of the present disclosure, a semiconductor device structure is provided. The semiconductor device structure includes a first dielectric layer disposed over a semiconductor substrate, and a first energy removable structure disposed in the first dielectric layer. The semiconductor device structure also includes a second dielectric layer disposed over the first dielectric layer, and a second energy removable structure disposed in the second dielectric layer. The semiconductor device structure further includes an N.sup.th dielectric layer disposed over the second dielectric layer. The N is an integer greater than 2. In addition, the semiconductor device structure includes a first conductor disposed in the N.sup.th dielectric layer, and an (N+1).sup.th dielectric layer disposed over the N.sup.th dielectric layer. A top surface of the first conductor is exposed by a first opening, and a top surface of the second energy removable structure is exposed by a second opening.

[0009] In an embodiment, the second energy removable structure is directly over the first energy removable structure. In an embodiment, the second energy removable structure penetrates through the second dielectric layer to directly contact the first energy removable structure. In an embodiment, the first energy removable structure penetrates through the first dielectric layer. In an embodiment, a bottom surface of the first conductor is higher than the top surface of the second energy removable structure. In an embodiment, the top surface of the first conductor is substantially coplanar with a bottom surface of the (N+1).sup.th dielectric layer. In an embodiment, the semiconductor device structure further includes a second conductor disposed in the (N+1).sup.th dielectric layer, and a bottom surface of the second conductor is higher than the top surface of the first conductor. In an embodiment, the semiconductor device structure further includes an (N+2).sup.th dielectric layer disposed over the (N+1).sup.th dielectric layer, wherein a top surface of the second conductor is exposed by a third opening.

[0010] In yet another embodiment of the present disclosure, a method for preparing a semiconductor device structure is provided. The method includes forming a first dielectric layer over a semiconductor substrate, and forming a first energy removable structure in the first dielectric layer. The method also includes forming a second dielectric layer over the first dielectric layer and covering the first energy removable structure, and forming an N.sup.th dielectric layer over the second dielectric layer. The N is an integer greater than 2. The method further includes forming a first conductor in the N.sup.th dielectric layer, and forming an (N+1).sup.th dielectric layer over the N.sup.th dielectric layer and covering the first conductor. In addition, the method includes performing an etching process to form a first opening exposing the first conductor and a second opening directly over the first energy removable structure. A bottom surface of the first opening is higher than a bottom surface of the second opening.

[0011] In an embodiment, a top surface of the first conductor is exposed by the first opening. In an embodiment, the method further includes forming a second conductor in the (N+1).sup.th dielectric layer, forming an (N+2).sup.th dielectric layer over the (N+1).sup.th dielectric layer and covering the second conductor, and performing the etching process to form a third opening exposing the second conductor. In an embodiment, a bottom surface of the third opening is higher than the bottom surface of the first opening. In an embodiment, a top surface of the second conductor is exposed by the third opening. In an embodiment, a bottom surface of the second conductor is higher than the bottom surface of the first opening.

[0012] In an embodiment, a top surface of the first energy removable structure is exposed by the second opening, and the first energy removable structure is removed after the etching process is performed. In an embodiment, the forming the first energy removable structure includes forming a fourth opening penetrating through the first dielectric layer, and filling the fourth opening with the first energy removable structure. In an embodiment, the method further includes forming a second energy removable structure in the second dielectric layer before the N.sup.th dielectric layer is formed, wherein a top surface of the second energy removable structure is exposed by the second

opening. In an embodiment, the forming the second energy removable structure includes forming a fifth opening penetrating through the second dielectric layer to expose a top surface of the first energy removable structure, and filling the fifth opening with the second energy removable structure. In an embodiment, the first energy removable structure and the second energy removable structure are removed after the etching process is performed.

[0013] Embodiments of a semiconductor device structure and method for preparing the same are provided in the disclosure. In some embodiments, the semiconductor device structure includes multiple stacked dielectric layers, and a conductor and an energy removable structure disposed in different levels of the dielectric layers. In some embodiments, the energy removable structure is exposed by an opening deeper than the one exposing the conductor, and the two openings are formed simultaneously by etching. Since the energy removable structure is used as an etch stop for the etching of the opening with a high aspect ratio, and the energy removable structure can be easily removed after the etching process, the aspect ratio difference between the two openings can be reduced (compared to the case where the energy removable structure is not formed). As a result, the performance, reliability and yield of the semiconductor device structure can be improved.

[0014] The foregoing has outlined rather broadly the features and technical advantages of the present disclosure in order that the detailed description of the disclosure that follows may be better understood. Additional features and advantages of the disclosure will be described hereinafter, and form the subject of the claims of the disclosure. It should be appreciated by those skilled in the art that the conception and specific embodiment disclosed may be readily utilized as a basis for modifying or designing other structures or processes for carrying out the same purposes of the present disclosure. It should also be realized by those skilled in the art that such equivalent constructions do not depart from the spirit and scope of the disclosure as set forth in the appended claims.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0015] Aspects of the present disclosure are best understood from the following detailed description when read with the accompanying figures. It should be noted that, in accordance with the standard practice in the industry, various features are not drawn to scale. In fact, the dimensions of the various features may be arbitrarily increased or reduced for clarity of discussion.

[0016] FIG. 1 is a cross-sectional view illustrating a semiconductor device structure, in accordance with some embodiments.

[0017] FIG. 2 is a cross-sectional view illustrating a semiconductor device structure, in accordance with some other embodiments.

[0018] FIG. 3 is a cross-sectional view illustrating the semiconductor device structure after removing the energy removable structure(s), in accordance with some embodiments.

[0019] FIG. 4 is a flow diagram illustrating a method for preparing a semiconductor device structure, in accordance with some embodiments.

[0020] FIG. 5 is a flow diagram illustrating a method for preparing a semiconductor device structure, in accordance with some other embodiments.

[0021] FIG. 6 is a cross-sectional view illustrating an intermediate stage of forming a first dielectric layer over a semiconductor substrate during the formation of the semiconductor device structure, in accordance with some embodiments.

[0022] FIG. 7 is a cross-sectional view illustrating an intermediate stage of forming an opening in the first dielectric layer during the formation of the semiconductor device structure, in accordance with some embodiments.

[0023] FIG. 8 is a cross-sectional view illustrating an intermediate stage of filling the opening in

the first dielectric layer with a first energy removable structure during the formation of the semiconductor device structure, in accordance with some embodiments.

[0024] FIG. **9** is a cross-sectional view illustrating an intermediate stage of sequentially forming a plurality of dielectric layers over the first dielectric layer during the formation of the semiconductor device structure, the plurality of dielectric layers includes a second dielectric layer and an N^{sup}.th dielectric layer over the second dielectric layer, and the N is an integer greater than 2, in accordance with some embodiments.

[0025] FIG. **10** is a cross-sectional view illustrating an intermediate stage of forming a patterned mask over the N^{sup}.th dielectric layer during the formation of the semiconductor device structure, in accordance with some embodiments.

[0026] FIG. **11** is a cross-sectional view illustrating an intermediate stage of forming a recess in the N^{sup}.th dielectric layer using the patterned mask as a mask during the formation of the semiconductor device structure, in accordance with some embodiments.

[0027] FIG. **12** is a cross-sectional view illustrating an intermediate stage of filling the recess in the N^{sup}.th dielectric layer with a first conductor, and removing the patterned mask during the formation of the semiconductor device structure, in accordance with some embodiments.

[0028] FIG. **13** is a cross-sectional view illustrating an intermediate stage of forming an (N+1)^{sup}.th dielectric layer over the N^{sup}.th dielectric layer and covering the first conductor during the formation of the semiconductor device structure, in accordance with some embodiments.

[0029] FIG. **14** is a cross-sectional view illustrating an intermediate stage of forming a recess in the (N+1)^{sup}.th dielectric layer during the formation of the semiconductor device structure, in accordance with some embodiments.

[0030] FIG. **15** is a cross-sectional view illustrating an intermediate stage of filling the recess in the (N+1)^{sup}.th dielectric layer with a second conductor during the formation of the semiconductor device structure, in accordance with some embodiments.

[0031] FIG. **16** is a cross-sectional view illustrating an intermediate stage of forming an (N+2)^{sup}.th dielectric layer over the (N+1)^{sup}.th dielectric layer and covering the second conductor during the formation of the semiconductor device structure, in accordance with some embodiments.

[0032] FIG. **17** is a cross-sectional view illustrating an intermediate stage of performing an etching process to form a plurality of openings respectively exposing top surfaces of the first conductor, the second conductor, and the first energy removable structure during the formation of the semiconductor device structure, in accordance with some embodiments.

[0033] FIG. **18** is a cross-sectional view illustrating an intermediate stage of forming a second dielectric layer over the first dielectric layer and covering the first energy removable structure during the formation of the semiconductor device structure, in accordance with some embodiments.

[0034] FIG. **19** is a cross-sectional view illustrating an intermediate stage of forming an opening in the second dielectric layer to expose a top surface of the first energy removable structure during the formation of the semiconductor device structure, in accordance with some embodiments.

[0035] FIG. **20** is a cross-sectional view illustrating an intermediate stage of filling the opening in the second dielectric layer with a second energy removable structure during the formation of the semiconductor device structure, in accordance with some embodiments.

[0036] FIG. **21** is a cross-sectional view illustrating an intermediate stage of forming a plurality of dielectric layers over the second dielectric layer and forming a first conductor and a second conductor in different levels of the plurality of dielectric layers during the formation of the semiconductor device structure, in accordance with some embodiments.

[0037] FIG. **22** is a cross-sectional view illustrating an intermediate stage of performing an etching process to form a plurality of openings respectively exposing top surfaces of the first conductor, the second conductor, and the second energy removable structure during the formation of the semiconductor device structure, in accordance with some embodiments.

DETAILED DESCRIPTION

[0038] The following disclosure provides many different embodiments, or examples, for implementing different features of the provided subject matter. Specific examples of components and arrangements are described below to simplify the present disclosure. These are, of course, merely examples and are not intended to be limiting. For example, the formation of a first feature over or on a second feature in the description that follows may include embodiments in which the first and second features are formed in direct contact, and may also include embodiments in which additional features may be formed between the first and second features, such that the first and second features may not be in direct contact. In addition, the present disclosure may repeat reference numerals and/or letters in the various examples. This repetition is for the purpose of simplicity and clarity and does not in itself dictate a relationship between the various embodiments and/or configurations discussed.

[0039] Further, spatially relative terms, such as “beneath,” “below,” “lower,” “above,” “upper” and the like, may be used herein for ease of description to describe one element or feature's relationship to another element(s) or feature(s) as illustrated in the figures. The spatially relative terms are intended to encompass different orientations of the device in use or operation in addition to the orientation depicted in the figures. The apparatus may be otherwise oriented (rotated 90 degrees or at other orientations) and the spatially relative descriptors used herein may likewise be interpreted accordingly.

[0040] FIG. 1 is a cross-sectional view illustrating a semiconductor device structure **100a**, in accordance with some embodiments. As shown in FIG. 1, the semiconductor device structure **100a** includes a semiconductor substrate **101**, and a plurality of dielectric layers disposed over the semiconductor substrate **101**, in accordance with some embodiments. In some embodiments, the plurality of the dielectric layers number from 1 to N+2, with the first dielectric layer **103** being the nearest dielectric layer to the semiconductor substrate **101**, and the (N+2).sup.th dielectric layer **179** being the furthest dielectric layer from the semiconductor substrate **101**. In some embodiments, the N is an integer greater than 2.

[0041] For example, as shown in FIG. 1, the semiconductor device structure **100a** includes a first dielectric layer **103** disposed over the semiconductor substrate **101**, a second dielectric layer **117** disposed over the first dielectric layer **103**, an N.sup.th dielectric layer **151** disposed over the second dielectric layer, an (N+1).sup.th dielectric layer **165** disposed over the N.sup.th dielectric layer **151**, and an (N+2).sup.th dielectric layer **179** disposed over the (N+1).sup.th dielectric layer **165**, and the N is an integer greater than 2, in accordance with some embodiments.

[0042] If N is equal to 3, the N.sup.th dielectric layer **151** will be the third dielectric layer **151**, and the third dielectric layer **151** is in direct contact with the second dielectric layer **117** (i.e., no dielectric layer disposed between the second dielectric layer **117** and the third dielectric layer **151**). If N is equal to 4, the N.sup.th dielectric layer **151** will be the fourth dielectric layer **151**. Although not shown, a third dielectric layer may be sandwiched between the second dielectric layer **117** and the fourth dielectric layer **151**, in accordance with some embodiments. If N is a number greater than 4, there will be more dielectric layers present, and so on.

[0043] In some embodiments, the semiconductor device structure **100a** includes a first energy removable structure **115** disposed in the first dielectric layer **103**. In some embodiments, the first energy removable structure **115** penetrates through the first dielectric layer **103**. In some embodiments, the first energy removable structure **115** is in direct contact with the semiconductor substrate **101**. In some embodiments, the first energy removable structure **115** is surrounded by and in direct contact with the first dielectric layer **103**.

[0044] Moreover, in some embodiments, the semiconductor device structure **100a** includes a first conductor **163** disposed in the N.sup.th dielectric layer **151**, and a second conductor **177** disposed in the (N+1).sup.th dielectric layer **165**. In some embodiments, the bottom surface BS1 of the second conductor **177** is higher than the bottom surface BS3 of the (N+1).sup.th dielectric layer

165, and the bottom surface **BS2** of the first conductor **163** is higher than the bottom surface **BS4** of the **N.sup.th** dielectric layer **151**. In other words, the second conductor **177** does not penetrate through the **(N+1).sup.th** dielectric layer **165**, and the first conductor **163** does not penetrate through the **N.sup.th** dielectric layer **151**, in accordance with some embodiments.

[0045] In some embodiments, the first energy removable structure **115**, the first conductor **163**, and the second conductor **177** are respectively exposed by openings **194**, **192**, and **190**. In some embodiments, the top surface **S3** of the first energy removable structure **115** is exposed by the opening **194**, the top surface **S2** of the first conductor **163** is exposed by the opening **192**, and the top surface **S1** of the second conductor **177** is exposed by the opening **190**.

[0046] The top surface **S1** of the second conductor **177** is also referred to as the bottom surface of the opening **190**, the top surface **S2** of the first conductor **163** is also referred to as the bottom surface of the opening **192**, and the top surface **S3** of the first energy removable structure **115** is also referred to as the bottom surface of the opening **194**. In some embodiments, the bottom surface **S1** of the opening **190** is higher than the bottom surface **S2** of the opening **192**, and the bottom surface **S2** of the opening **192** is higher than the bottom surface **S3** of the opening **194**. Still referring to FIG. **1**, the opening **190** penetrates through the **(N+2).sup.th** dielectric layer **179**, the opening **192** penetrates through the **(N+2).sup.th** dielectric layer **179** and the **(N+1).sup.th** dielectric layer **165**, and the opening **194** penetrates through the **(N+2).sup.th** dielectric layer **179**, the **(N+1).sup.th** dielectric layer **165**, the **N.sup.th** dielectric layer **151**, the second dielectric layer **117**, and the dielectric layer(s) between the **N.sup.th** dielectric layer **151** and the second dielectric layer **117**, if any.

[0047] In some embodiments, the openings **190**, **192**, and **194** are formed by an etching process, the opening **194** has an aspect ratio higher than that of the openings **190** and **192**, and the first energy removable structure **115**, the first conductor **163**, and the second conductor **177** are used as etch stops for the etching process. After the etching process is performed, the first energy removable structure **115** can be easily removed.

[0048] By using the first energy removable structure **115** as an etch stop for forming the opening **194** (i.e., the opening with a higher aspect ratio), the aspect ratio differences between the opening **194** and the openings **190** and **192** can be reduced (compared to the case where the first energy removable structure **115** is not formed). As a result, the etching process for forming the openings **190**, **192**, and **194** can be performed easily, and the performance, reliability and yield of the semiconductor device structure **100a** can be improved.

[0049] FIG. **2** is a cross-sectional view illustrating a semiconductor device structure **100b**, in accordance with some other embodiments. The semiconductor device structure **100b** is similar to the semiconductor device structure **100a**. However, in the semiconductor device structure **100b**, a second energy removable structure **129** is disposed in the second dielectric layer **117** and over the first energy removable structure **115**, and the second energy removable structure **129** is exposed by an opening **196** rather than the opening **194** described in FIG. **1**, in accordance with some embodiments.

[0050] In some embodiments, the second energy removable structure **129** is directly over and substantially aligned with the first energy removable structure **115**. Within the context of this disclosure, the word “substantially” means preferably at least 90%, more preferably 95%, even more preferably 98%, and most preferably 99%. In some embodiments, the second energy removable structure **129** penetrates through the second dielectric layer **117** to directly contact the first energy removable structure **115**. In some embodiments, the second energy removable structure **129** is surrounded by and in direct contact with the second dielectric layer **117**.

[0051] In some embodiments, the top surface **S4** of the second energy removable structure **129** is exposed by the opening **196**. The top surface **S4** of the second energy removable structure **129** is also referred to as the bottom surface of the opening **196**. In some embodiments, the bottom surface **S1** of the opening **190** is higher than the bottom surface **S2** of the opening **192**, and the bottom

surface **S2** of the opening **192** is higher than the bottom surface **S4** of the opening **196**. In some embodiments, the opening **196** penetrates through the (N+2).sup.th dielectric layer **179**, the (N+1).sup.th dielectric layer **165**, the N.sup.th dielectric layer **151**, and the dielectric layer(s) between the N.sup.th dielectric layer **151** and the second dielectric layer **117**, if any.

[0052] In some embodiments, the openings **190**, **192**, and **196** are formed by an etching process, the opening **196** has an aspect ratio higher than that of the openings **190** and **192**, and the second energy removable structure **129**, the first conductor **163**, and the second conductor **177** are used as etch stops for the etching process. After the etching process is performed, the second energy removable structure **129** and the first energy removable structure **115** can be easily removed. The formation of the first energy removable structure **115** and the second energy removable structure **129** can help to reduce the aspect ratio differences between the opening **196** and the openings **190** and **192** (compared to the case where the first energy removable structure **115** and the second energy removable structure **129** are not formed). As a result, the etching process can be performed easily, and the performance, reliability and yield of the semiconductor device structure **100b** can be improved.

[0053] FIG. **3** is a cross-sectional view illustrating the semiconductor device structure **100a** or the semiconductor device structure **100b** after removing the energy removable structure(s), in accordance with some embodiments. As mentioned above, a removal process may be performed on the first energy removable structure **115** after the semiconductor device structure **100a** is obtained. For example, the removal process includes a heat treatment process, and the temperature used in the heat treatment process is high enough to efficiently burn-out the first energy removable structure **115**, thereby deepening the opening **194**, referred to as an opening **198** shown in FIG. **3**.

[0054] The removal process for the first energy removable structure **115** is not limited to the heat treatment process. In some embodiments, the removal process includes a light treatment process, an e-beam treatment process, a combination thereof, or another suitable energy treatment process. After the first energy removable structure **115** is removed, additional cleaning process may be used to ensure no undesired residue remains in the openings **190**, **192**, and **198**.

[0055] Similar to the semiconductor device structure **100a**, a removal process may be performed on the second energy removable structure **129** and first energy removable structure **115** after the semiconductor device structure **100b** is obtained. For example, the removal process includes a heat treatment process, and the temperature used in the heat treatment process is high enough to efficiently burn-out the second energy removable structure **129** and the first energy removable structure **115**, thereby deepening the opening **196**, referred to as an opening **198** shown in FIG. **3**. The removal process for the second energy removable structure **129** and the first energy removable structure **115** is not limited to the heat treatment process. In some embodiments, the removal process includes a light treatment process, an e-beam treatment process, a combination thereof, or another suitable energy treatment process. After the first energy removable structure **115** and the second energy removable structure **129** are removed, additional cleaning process may be used to ensure no undesired residue remains in the opening **190**, **192**, and **198**.

[0056] FIG. **4** is a flow diagram illustrating a method **10** for preparing the semiconductor device structure **100a**, and the method **10** includes steps **S11**, **S13**, **S15**, **S17**, **S19**, **S21**, **S23**, **S25**, **S27** and **S29**, in accordance with some embodiments. The steps **S11** to **S29** of FIG. **4** are elaborated in connection with the following figures, such as FIGS. **6-17**.

[0057] FIG. **5** is a flow diagram illustrating a method **30** for preparing the semiconductor device structure **100b**, and the method **30** includes steps **S31**, **S33**, **S35**, **S37**, **S39**, **S41**, **S43**, **S45**, **S47**, **S49** and **S51**, in accordance with some embodiments. The steps **S31** to **S51** of FIG. **5** are elaborated in connection with the following figures, such as FIGS. **18-22**.

[0058] FIGS. **6-17** are cross-sectional views illustrating intermediate stages of forming the semiconductor device structure **100a**, in accordance with some embodiments. As shown in FIG. **6**, a semiconductor substrate **101** is provided. The semiconductor substrate **101** may be a

semiconductor wafer such as a silicon wafer.

[0059] Alternatively or additionally, the semiconductor substrate **101** may include elementary semiconductor materials, compound semiconductor materials, and/or alloy semiconductor materials. Examples of the elementary semiconductor materials may include, but are not limited to, crystal silicon, polycrystalline silicon, amorphous silicon, germanium, and/or diamond. Examples of the compound semiconductor materials may include, but are not limited to, silicon carbide, gallium arsenic, gallium phosphide, indium phosphide, indium arsenide, and/or indium antimonide. Examples of the alloy semiconductor materials may include, but are not limited to, SiGe, GaAsP, AlInAs, AlGaAs, GaInAs, GaInP, and/or GaInAsP.

[0060] In some embodiments, the semiconductor substrate **101** includes an epitaxial layer. For example, the semiconductor substrate **101** has an epitaxial layer overlying a bulk semiconductor. In some embodiments, the semiconductor substrate **101** is a semiconductor-on-insulator substrate which may include a substrate, a buried oxide layer over the substrate, and a semiconductor layer over the buried oxide layer, such as a silicon-on-insulator (SOI) substrate, a silicon germanium-on-insulator (SGOI) substrate, or a germanium-on-insulator (GOI) substrate. Semiconductor-on-insulator substrates can be fabricated using separation by implantation of oxygen (SIMOX), wafer bonding, and/or other suitable methods.

[0061] A first dielectric layer **103** is formed over the semiconductor substrate **101**, as shown in FIG. **6** in accordance with some embodiments. The respective step is illustrated as the step **S11** in the method **10** shown in FIG. **4**. In some embodiments, the first dielectric layer **103** is made of silicon oxide, silicon nitride, silicon oxynitride, a low-k dielectric material or another suitable material. The first dielectric layer **103** may be formed by a deposition process, such as a chemical vapor deposition (CVD) process, a physical vapor deposition (PVD) process, an atomic layer deposition (ALD) process, a spin-on coating process, or another suitable method.

[0062] Then, still referring to FIG. **6**, a patterned mask **105** with an opening **108** is formed over the first dielectric layer **103**. In some embodiments, the first dielectric layer **103** is partially exposed by the opening **108**. In some embodiments, the first dielectric layer **103** and the patterned mask **105** include different materials so that the etching selectivities may be different in the subsequent etching process.

[0063] Next, an etching process is performed on the first dielectric layer **103** using the patterned mask **105** as a mask, such that an opening **110** is formed in the first dielectric layer **103**, as shown in FIG. **7** in accordance with some embodiments. In some embodiments, the opening **110** penetrates through the first dielectric layer **103**, such that the semiconductor substrate **101** is partially exposed. The etching process may be a wet etching process, a dry etching process, or a combination thereof.

[0064] Subsequently, the opening **110** in the first dielectric layer **103** is filled by a first energy removable structure **115**, as shown in FIG. **8** in accordance with some embodiments. The respective step is illustrated as the step **S13** in the method **10** shown in FIG. **4**. In some embodiments, the formation of the first energy removable structure **115** includes conformally depositing an energy removable material (not shown) in the opening **110** and over the first dielectric layer **103**, and planarizing the energy removable material to expose the first dielectric layer **103**. The patterned mask **105** may be removed before the energy removable material is deposited, or after the energy removable material is deposited (i.e., remove the patterned mask **105** with the excess energy removable material outside the opening **110** by the planarization process).

[0065] In some embodiments, the energy removable material for forming the first energy removable structure **115** includes a thermal decomposable material. In some other embodiments, the energy removable material includes a photonic decomposable material, an e-beam decomposable material, or another suitable energy decomposable material. In some embodiments, the energy removable material includes a base material and a decomposable porogen material that is substantially removed once being exposed to an energy source (e.g., heat). In this case, the base

material may include hydrogen silsesquioxane (HSQ), methylsilsesquioxane (MSQ), porous polyarylether (PAE), porous SiLK, or porous silicon oxide (SiO₂), and the decomposable porogen material may include a porogen organic compound, which can provide porosity to the space originally occupied by the first energy removable structure **115** in the subsequent processes. [0066] In addition, the depositing of the energy removable material may include a CVD process, a PVD process, an ALD process, a spin-on coating process, or another suitable process, and the planarization process for forming the first energy removable structure **115** may include a chemical mechanical polishing (CMP) process, an etch-back process, or another suitable process. After the planarization process is performed, the first dielectric layer **103** is exposed, and the top surface of the first energy removable structure **115** is substantially coplanar with the top surface of the first dielectric layer **103**, in accordance with some embodiments.

[0067] Then, a plurality of dielectric layers including a second dielectric layer **117** to an N^{sup}.th dielectric layer **151** are formed over the first dielectric layer **103** and covering the first energy removable structure **115**, as shown in FIG. **9** in accordance with some embodiments. In some embodiments, the N is an integer greater than 2. The respective step is illustrated as the steps **S15** and **S17** in the method **10** shown in FIG. **4**. Some materials and processes used to form the second dielectric layer **117** to the N^{sup}.th dielectric layer **151** are similar to, or the same as, those used to form the first dielectric layer **103**, and details thereof are not repeated herein.

[0068] Next, a patterned mask **153** with an opening **156** is formed over the N^{sup}.th dielectric layer **151**, as shown in FIG. **10** in accordance with some embodiments. In some embodiments, the N^{sup}.th dielectric layer **151** is partially exposed by the opening **156**. In some embodiments, the opening **156** and the first energy removable structure **115** are not overlapped from the top view. In some embodiments, the N^{sup}.th dielectric layer **151** and the patterned mask **153** include different materials so that the etching selectivities may be different in the subsequent etching process.

[0069] Subsequently, an etching process is performed on the N^{sup}.th dielectric layer **151** using the patterned mask **153** as a mask, such that a recess **158** is formed in the N^{sup}.th dielectric layer **151**, as shown in FIG. **11** in accordance with some embodiments. In some embodiments, the recess **158** does not penetrate through the N^{sup}.th dielectric layer **151**. The etching process may be a wet etching process, a dry etching process, or a combination thereof.

[0070] Then, the recess **158** in the N^{sup}.th dielectric layer **151** is filled by a first conductor **163**, as shown in FIG. **12** in accordance with some embodiments. The respective step is illustrated as the step **S19** in the method **10** shown in FIG. **4**. In some embodiments, the formation of the first conductor **163** includes conformally depositing a conductive material (not shown) in the recess **158** and over the N^{sup}.th dielectric layer **151**, and planarizing the conductive material to expose the N^{sup}.th dielectric layer **151**. The patterned mask **153** may be removed before the conductive material is deposited, or after the conductive material is deposited (i.e., remove the patterned mask **153** with the excess conductive material outside the recess **158** by the planarization process).

[0071] In some embodiments, the conductive material for forming the first conductor **163** includes copper (Cu), aluminum (Al), tungsten (W), titanium (Ti), tantalum (Ta), gold (Au), silver (Ag), a combination thereof, or another suitable conductive material. Moreover, the conductive material for forming the first conductor **163** may be deposited by a CVD process, a PVD process, an ALD process, a metal organic chemical vapor deposition (MOCVD) process, a sputtering process, a plating process, or another suitable process, and the planarization process for forming the first conductor **163** may include a CMP process, an etch-back process, or another suitable process. After the planarization process is performed, the N^{sup}.th dielectric layer **151** is exposed, and the top surface of the first conductor **163** is substantially coplanar with the top surface of the N^{sup}.th dielectric layer **151**, in accordance with some embodiments.

[0072] Next, an (N+1)^{sup}.th dielectric layer **165** is formed over the N^{sup}.th dielectric layer **151** and covering the first conductor **163**, as shown in FIG. **13** in accordance with some embodiments. The respective step is illustrated as the step **S21** in the method **10** shown in FIG. **4**. Some materials

and processes used to form the (N+1).sup.th dielectric layer **165** are similar to, or the same as, those used to form the first dielectric layer **103**, and details thereof are not repeated herein. [0073] Moreover, a patterned mask **167** with an opening **170** is formed over the (N+1).sup.th dielectric layer **165**, in accordance with some embodiments. In some embodiments, the (N+1).sup.th dielectric layer **165** is partially exposed by the opening **170**. In some embodiments, the opening **170** and the first energy removable structure **115** are not overlapped from the top view. In some embodiments, the (N+1).sup.th dielectric layer **165** and the patterned mask **167** include different materials so that the etching selectivities may be different in the subsequent etching process.

[0074] Subsequently, an etching process is performed on the (N+1).sup.th dielectric layer **165** using the patterned mask **167** as a mask, such that a recess **172** is formed in the (N+1).sup.th dielectric layer **165**, as shown in FIG. **14** in accordance with some embodiments. In some embodiments, the recess **172** does not penetrate through the (N+1).sup.th dielectric layer **165**. The etching process may be a wet etching process, a dry etching process, or a combination thereof.

[0075] Then, the recess **172** in the (N+1).sup.th dielectric layer **165** is filled by a second conductor **177**, as shown in FIG. **15** in accordance with some embodiments. The respective step is illustrated as the step S23 in the method **10** shown in FIG. **4**. In some embodiments, the formation of the second conductor **177** includes conformally depositing a conductive material (not shown) in the recess **172** and over the (N+1).sup.th dielectric layer **165**, and planarizing the conductive material to expose the (N+1).sup.th dielectric layer **165**. The patterned mask **167** may be removed before the conductive material is deposited, or after the conductive material is deposited (i.e., remove the patterned mask **167** with the excess conductive material outside the recess **172** by the planarization process).

[0076] Some materials and processes used to form the second conductor **177** are similar to, or the same as, those used to form the first conductor **163**, and details thereof are not repeated herein. After the second conductor **177** is formed, the top surface of the second conductor **177** is substantially coplanar with the top surface of the (N+1).sup.th dielectric layer **165**, in accordance with some embodiments.

[0077] Next, an (N+2).sup.th dielectric layer **179** is formed over the (N+1).sup.th dielectric layer **165** and covering the second conductor **177**, as shown in FIG. **16** in accordance with some embodiments. The respective step is illustrated as the step S25 in the method **10** shown in FIG. **4**. Some materials and processes used to form the (N+2).sup.th dielectric layer **179** are similar to, or the same as, those used to form the first dielectric layer **103**, and details thereof are not repeated herein.

[0078] Moreover, a patterned mask **181** with openings **184**, **186**, and **188** is formed over the (N+2).sup.th dielectric layer **179**, in accordance with some embodiments. In some embodiments, the (N+2).sup.th dielectric layer **179** is partially exposed by the openings **184**, **186**, and **188**. In some embodiments, the opening **184** and the second conductor **177** are overlapped from the top view, the opening **186** and the first conductor **163** are overlapped from the top view, and the opening **188** and the first energy removable structure **115** are overlapped from the top view. In some embodiments, the (N+2).sup.th dielectric layer **179** and the patterned mask **181** include different materials so that the etching selectivities may be different in the subsequent etching process.

[0079] Subsequently, an etching process is performed on the structure using the patterned mask **181** as a mask, such that openings **190**, **192**, and **194** are formed, as shown in FIG. **17** in accordance with some embodiments. In some embodiments, the first energy removable structure **115**, the first conductor **163**, and the second conductor **177** are used as etch stops for the etching process, such that the first energy removable structure **115** is exposed by the opening **194**, the first conductor **163** is exposed by the opening **192**, and the second conductor **177** is exposed by the opening **190**. The respective step is illustrated as the step S27 in the method **10** shown in FIG. **4**. The etching process

may be a wet etching process, a dry etching process, or a combination thereof.

[0080] In some embodiments, the top surface S3 of the first energy removable structure **115** is exposed by the opening **194**, the top surface S2 of the first conductor **163** is exposed by the opening **192**, and the top surface S1 of the second conductor **177** is exposed by the opening **190**. The top surface S1 of the second conductor **177** is also referred to as the bottom surface of the opening **190**, the top surface S2 of the first conductor **163** is also referred to as the bottom surface of the opening **192**, and the top surface S3 of the first energy removable structure **115** is also referred to as the bottom surface of the opening **194**. In some embodiments, the bottom surface S1 of the opening **190** is higher than the bottom surface S2 of the opening **192**, and the bottom surface S2 of the opening **192** is higher than the bottom surface S3 of the opening **194**. It should be noted that the openings **190**, **192**, and **194** are formed by the same etching process.

[0081] After the etching process for forming the openings **190**, **192**, and **194** are performed, the patterned mask **181** is removed, as shown in FIG. 1 in accordance with some embodiments. In some embodiments, the patterned mask **181** is removed by a stripping process, an ashing process, an etching process, or another suitable process. Then, as mentioned above, the first energy removable structure **115** is removed, as shown in FIG. 3 in accordance with some embodiments. The respective step is illustrated as the step S29 in the method **10** shown in FIG. 4. Details regarding the removal of the first energy removable structure **115** are the same as those previously described, and the details are not repeated herein.

[0082] FIGS. **18-22** are cross-sectional views illustrating intermediate stages of forming the semiconductor device structure **100b**, in accordance with some embodiments. It should be pointed out that operations for forming the semiconductor device structure **100b** before the structure shown in FIG. **18** are substantially the same as the operations for forming the semiconductor device structure **100a** shown in FIGS. **6-8** (The steps S31 and S33 in the method **30** shown in FIG. 5 is the same as the steps S11 and S13 in the method **10** shown in FIG. 4), and the related detailed descriptions may refer to the foregoing paragraphs and are not discussed again herein.

[0083] After the first energy removable structure **115** is formed in the first dielectric layer **103**, a second dielectric layer **117** is formed over the first dielectric layer **103** and covering the first energy removable structure **115**, as shown in FIG. **18** in accordance with some embodiments. The respective step is illustrated as the step S35 in the method **30** shown in FIG. 5. The details for forming second dielectric layer **117** may be similar to, or the same as, those for forming second dielectric layer **117** shown in FIG. 9 and are not repeated herein.

[0084] Moreover, a patterned mask **119** with an opening **122** is formed over the second dielectric layer **117**, in accordance with some embodiments. In some embodiments, the second dielectric layer **117** is partially exposed by the opening **122**. In some embodiments, the opening **122** and the first energy removable structure **115** are overlapped from the top view. In some embodiments, the opening **122** is substantially aligned with the first energy removable structure **115**. In some embodiments, the second dielectric layer **117** and the patterned mask **119** include different materials so that the etching selectivities may be different in the subsequent etching process.

[0085] Then, an etching process is performed on the second dielectric layer **117** using the patterned mask **119** as a mask, such that an opening **124** is formed in the second dielectric layer **117**, as shown in FIG. **19** in accordance with some embodiments. In some embodiments, the opening **124** penetrates through the second dielectric layer **117**, such that the top surface S3 of the first energy removable structure **115** is exposed. The etching process may be a wet etching process, a dry etching process, or a combination thereof.

[0086] Next, the opening **124** in the second dielectric layer **117** is filled by a second energy removable structure **129**, as shown in FIG. **20** in accordance with some embodiments. The respective step is illustrated as the step S37 in the method **30** shown in FIG. 5. In some embodiments, the formation of the second energy removable structure **129** includes conformally depositing an energy removable material (not shown) in the opening **124** and over the second

dielectric layer **117**, and planarizing the energy removable material to expose the second dielectric layer **117**. The patterned mask **119** may be removed before the energy removable material is deposited, or after the energy removable material is deposited (i.e., remove the patterned mask **119** with the excess energy removable material outside the opening **124** by the planarization process). [0087] Some materials and processes used to form the second energy removable structure **129** are similar to, or the same as, those used to form the first energy removable structure **115**, and details thereof are not repeated herein. After the planarization process is performed, the second dielectric layer **117** is exposed, and the top surface of the second energy removable structure **129** is substantially coplanar with the top surface of the second dielectric layer **117**, in accordance with some embodiments.

[0088] Subsequently, a plurality of dielectric layers including an N.sup.th dielectric layer **151**, an (N+1).sup.th dielectric layer **165**, and an (N+2).sup.th dielectric layer **179** are formed over the second dielectric layer **117** and covering the second energy removable structure **129**, a first conductor **163** is formed in the N.sup.th dielectric layer **151**, and a second conductor **177** is formed in the (N+1).sup.th dielectric layer **165**, as shown in FIG. **21** in accordance with some embodiments. In some embodiments, the N is an integer greater than 2. The respective steps are illustrated as the steps **S39** to **S47** in the method **30** shown in FIG. **5**. After the (N+2).sup.th dielectric layer **179** is formed, a patterned mask **181** with openings **184**, **186**, and **188** is formed to partially expose the (N+2).sup.th dielectric layer **179**, in accordance with some embodiments.

[0089] The details for forming N.sup.th dielectric layer **151**, (N+1).sup.th dielectric layer **165**, (N+2).sup.th dielectric layer **179**, first conductor **163**, second conductor **177**, and patterned mask **181** may be similar to, or the same as, those for forming N.sup.th dielectric layer **151**, (N+1).sup.th dielectric layer **165**, (N+2).sup.th dielectric layer **179**, first conductor **163**, second conductor **177**, and patterned mask **181** shown in FIGS. **9-16** and are not repeated herein.

[0090] Then, an etching process is performed on the structure using the patterned mask **181** as a mask, such that openings **190**, **192**, and **196** are formed, as shown in FIG. **22** in accordance with some embodiments. In some embodiments, the second energy removable structure **129**, the first conductor **163**, and the second conductor **177** are used as etch stops for the etching process, such that the second energy removable structure **129** is exposed by the opening **196**, the first conductor **163** is exposed by the opening **192**, and the second conductor **177** is exposed by the opening **190**. The respective step is illustrated as the step **S49** in the method **30** shown in FIG. **5**. The etching process may be a wet etching process, a dry etching process, or a combination thereof.

[0091] In some embodiments, the top surface **S4** of the second energy removable structure **129** is exposed by the opening **196**, the top surface **S2** of the first conductor **163** is exposed by the opening **192**, and the top surface **S1** of the second conductor **177** is exposed by the opening **190**. The top surface **S1** of the second conductor **177** is also referred to as the bottom surface of the opening **190**, the top surface **S2** of the first conductor **163** is also referred to as the bottom surface of the opening **192**, and the top surface **S4** of the second energy removable structure **129** is also referred to as the bottom surface of the opening **196**. In some embodiments, the bottom surface **S1** of the opening **190** is higher than the bottom surface **S2** of the opening **192**, and the bottom surface **S2** of the opening **192** is higher than the bottom surface **S4** of the opening **196**. It should be noted that the openings **190**, **192**, and **196** are formed by the same etching process.

[0092] After the etching process for forming the openings **190**, **192**, and **196** are performed, the patterned mask **181** is removed, as shown in FIG. **2** in accordance with some embodiments. In some embodiments, the patterned mask **181** is removed by a stripping process, an ashing process, an etching process, or another suitable process. Then, as mentioned above, the first energy removable structure **115** and the second energy removable structure **129** are removed, as shown in FIG. **3** in accordance with some embodiments. The respective step is illustrated as the step **S51** in the method **30** shown in FIG. **5**. Details regarding the removal of the first energy removable structure **115** and the second energy removable structure **129** are the same as those previously

described, and the details are not repeated herein.

[0093] Embodiments of the semiconductor device structure and method for preparing the same are provided in the disclosure. In some embodiments, the semiconductor device structure includes multiple stacked dielectric layers, that is, from the first dielectric layer **103**, the second dielectric layer **117** to the N.sup.th dielectric layer **151**, the (N+1).sup.th dielectric layer **165**, and the (N+2).sup.th dielectric layer **179**. In some embodiments, the semiconductor device structure also includes a conductor (e.g., the first conductor **163**) and an energy removable structure (e.g., the first energy removable structure **115**) disposed in different levels of the dielectric layers.

[0094] An etching process is performed to form an opening exposing the conductor (e.g., the opening **192**) and another opening exposing the energy removable structure (e.g., the opening **194**), the opening exposing the energy removable structure has an aspect ratio higher than that of the opening exposing the conductor, and both of the conductor and the energy removable structure are used as etch stops for the etching process. After the etching process is performed, the energy removable structure can be easily removed. By using the energy removable structure as an etch stop for forming the opening with a higher aspect ratio, the aspect ratio difference between the openings can be reduced (compared to the case where the energy removable structure is not formed). As a result, the etching process for forming the openings with different aspect ratios can be performed easily, and the performance, reliability and yield of the semiconductor device structure can be improved.

[0095] In one embodiment of the present disclosure, a semiconductor device structure is provided. The semiconductor device structure includes a first dielectric layer disposed over a semiconductor substrate, and a first energy removable structure disposed in the first dielectric layer. The semiconductor device structure also includes a second dielectric layer disposed over the first dielectric layer, and an N.sup.th dielectric layer disposed over the second dielectric layer. The N is an integer greater than 2. The semiconductor device structure further includes a first conductor disposed in the N.sup.th dielectric layer, and an (N+1).sup.th dielectric layer disposed over the N.sup.th dielectric layer. A top surface of the first conductor is exposed by a first opening, and a top surface of the first energy removable structure is exposed by a second opening.

[0096] In another embodiment of the present disclosure, a semiconductor device structure is provided. The semiconductor device structure includes a first dielectric layer disposed over a semiconductor substrate, and a first energy removable structure disposed in the first dielectric layer. The semiconductor device structure also includes a second dielectric layer disposed over the first dielectric layer, and a second energy removable structure disposed in the second dielectric layer. The semiconductor device structure further includes an N.sup.th dielectric layer disposed over the second dielectric layer. The N is an integer greater than 2. In addition, the semiconductor device structure includes a first conductor disposed in the N.sup.th dielectric layer, and an (N+1).sup.th dielectric layer disposed over the N.sup.th dielectric layer. A top surface of the first conductor is exposed by a first opening, and a top surface of the second energy removable structure is exposed by a second opening.

[0097] In yet another embodiment of the present disclosure, a method for preparing a semiconductor device structure is provided. The method includes forming a first dielectric layer over a semiconductor substrate, and forming a first energy removable structure in the first dielectric layer. The method also includes forming a second dielectric layer over the first dielectric layer and covering the first energy removable structure, and forming an N.sup.th dielectric layer over the second dielectric layer. The N is an integer greater than 2. The method further includes forming a first conductor in the N.sup.th dielectric layer, and forming an (N+1).sup.th dielectric layer over the N.sup.th dielectric layer and covering the first conductor. In addition, the method includes performing an etching process to form a first opening exposing the first conductor and a second opening directly over the first energy removable structure. A bottom surface of the first opening is higher than a bottom surface of the second opening.

[0098] The embodiments of the present disclosure have some advantageous features. In some embodiment, the semiconductor device structure includes multiple stacked dielectric layers, and a conductor and an energy removable structure disposed in different levels of the dielectric layers. An etching process is performed to form a low-aspect-ratio opening exposing the conductor and a high-aspect ratio opening exposing the energy removable structure, and both of the conductor and the energy removable structure are used as etch stops for the etching process. Since the energy removable structure can be easily removed after the etching process, the aspect ratio difference between the two openings can be reduced (compared to the case where the energy removable structure is not formed). As a result, the etching process for forming the openings with different aspect ratios can be performed easily, and the performance, reliability and yield of the semiconductor device structure can be improved.

[0099] Although the present disclosure and its advantages have been described in detail, it should be understood that various changes, substitutions and alterations can be made herein without departing from the spirit and scope of the disclosure as defined by the appended claims. For example, many of the processes discussed above can be implemented in different methodologies and replaced by other processes, or a combination thereof.

[0100] Moreover, the scope of the present application is not intended to be limited to the particular embodiments of the process, machine, manufacture, composition of matter, means, methods and steps described in the specification. As one of ordinary skill in the art will readily appreciate from the disclosure of the present invention, processes, machines, manufacture, compositions of matter, means, methods, or steps, presently existing or later to be developed, that perform substantially the same function or achieve substantially the same result as the corresponding embodiments described herein may be utilized according to the present disclosure. Accordingly, the appended claims are intended to include within their scope such processes, machines, manufacture, compositions of matter, means, methods, and steps.

Claims

1. A method for preparing a semiconductor device structure, comprising: forming a first dielectric layer over a semiconductor substrate; forming a first energy removable structure in the first dielectric layer; forming a second dielectric layer over the first dielectric layer; forming an N^{th} dielectric layer over the second dielectric layer, wherein the N is an integer greater than 2; forming a first conductor in the N^{th} dielectric layer; and forming an $(N+1)^{\text{th}}$ dielectric layer over the N^{th} dielectric layer, wherein a top surface of the first conductor is exposed by a first opening, and a top surface of the first energy removable structure is exposed by a second opening.
2. The method of claim 1, wherein the first energy removable structure penetrates through the first dielectric layer.
3. The method of claim 1, wherein a bottom surface of the first conductor is higher than a bottom surface of the N^{th} dielectric layer.
4. The method of claim 1, wherein the first conductor is in direct contact with the $(N+1)^{\text{th}}$ dielectric layer.
5. The method of claim 1, further comprising: forming a second conductor in the $(N+1)^{\text{th}}$ dielectric layer.
6. The method of claim 5, further comprising: forming an $(N+2)^{\text{th}}$ dielectric layer over the $(N+1)^{\text{th}}$ dielectric layer, wherein a top surface of the second conductor is exposed by a third opening.
7. The method of claim 5, wherein a bottom surface of the second conductor is higher than a bottom surface of the $(N+1)^{\text{th}}$ dielectric layer.
8. A method for preparing a semiconductor device structure, comprising: forming a first dielectric layer over a semiconductor substrate; forming a first energy removable structure in the first

dielectric layer; forming a second dielectric layer over the first dielectric layer; forming a second energy removable structure in the second dielectric layer; forming an N^{th} dielectric layer over the second dielectric layer, wherein the N is an integer greater than 2; forming a first conductor in the N^{th} dielectric layer; and forming an $(N+1)^{\text{th}}$ dielectric layer over the N^{th} dielectric layer, wherein a top surface of the first conductor is exposed by a first opening, and a top surface of the second energy removable structure is exposed by a second opening.

9. The method of claim 8, wherein the second energy removable structure is directly over the first energy removable structure.

10. The method of claim 8, wherein the second energy removable structure penetrates through the second dielectric layer to directly contact the first energy removable structure.

11. The method of claim 10, wherein the first energy removable structure penetrates through the first dielectric layer.

12. The method of claim 8, wherein a bottom surface of the first conductor is higher than the top surface of the second energy removable structure.

13. The method of claim 8, wherein the top surface of the first conductor is substantially coplanar with a bottom surface of the $(N+1)^{\text{th}}$ dielectric layer.

14. The method of claim 8, further comprising: forming a second conductor in the $(N+1)^{\text{th}}$ dielectric layer, and a bottom surface of the second conductor is higher than the top surface of the first conductor.

15. The method of claim 14, further comprising: forming an $(N+2)^{\text{th}}$ dielectric layer over the $(N+1)^{\text{th}}$ dielectric layer, wherein a top surface of the second conductor is exposed by a third opening.

16. A method for preparing a semiconductor device structure, comprising: forming a first dielectric layer over a semiconductor substrate; forming a first energy removable structure in the first dielectric layer; forming a second dielectric layer over the first dielectric layer and covering the first energy removable structure; forming an N^{th} dielectric layer over the second dielectric layer, wherein the N is an integer greater than 2; forming a first conductor in the N^{th} dielectric layer; forming an $(N+1)^{\text{th}}$ dielectric layer over the N^{th} dielectric layer and covering the first conductor; and performing an etching process to form a first opening exposing the first conductor and a second opening directly over the first energy removable structure, wherein a bottom surface of the first opening is higher than a bottom surface of the second opening.
