

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250281788

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

WANG; Lopin

Kettlebell

Abstract

A kettlebell comprises a main weight block and several weight blocks, a teeth meshing plate is disposed on a top surface of the main weight block; a rotating shaft having an upper engaging rod and a lower engaging rod, the lower engaging rod optionally engages on the teeth meshing plate; a large teeth plate can move elastically, the large teeth plate is provided with first engaging teeth on a periphery of a through hole annularly; a connecting plate annularly provided with second engaging teeth movably meshing with the first engaging teeth, a lower end surface of the connecting plate is annularly provided with connecting teeth connected with the upper engaging rod. Positions of the connecting plate can be changed through the upper engaging rod, the main weight block can be fixed on the lower engaging rod, so that actions of the kettlebell can be switched reliably, and the rotating shaft can rotate freely without weight.

Inventors: WANG; Lopin (Taipei City, TW)

Applicant: MAGNATE HEALTH TECH. CO., LTD. (Taipei City, TW)

Family ID: 1000007740294

Appl. No.: 18/601872

Filed: March 11, 2024

Publication Classification

Int. Cl.: A63B21/075 (20060101); A63B21/00 (20060101); A63B21/072 (20060101)

U.S. Cl.:

CPC A63B21/075 (20130101); A63B21/0728 (20130101); A63B21/4035 (20151001);

Background/Summary

FIELD OF THE INVENTION

[0001] The invention relates to a kettlebell, and more particularly to a kettlebell that can be conveniently adjusted.

DESCRIPTION OF THE RELATED ART

[0002] Conventional kettlebells can be used to perform various types of exercise training. A variety of exercises can be performed through kettlebells of different weights. Users often need many kettlebells with different weights to perform daily exercises. In order to achieve choosing kettlebells of different weights, for example, Taiwan Patent No. 1810242 discloses a weight-selectable kettlebell, a main body of the kettlebell is provided with a rotating shaft, by changing a rotational position of the rotating shaft, it can be combined with different weight blocks to achieve an adjustment effect.

[0003] However, the rotating shaft cannot produce a matching effect of the weight block during use. That is, the user needs to observe and adjust to determine whether the weight block is reliably combined with the rotating shaft, which is relatively inconvenient in use. In addition, the rotating shaft is fixed and cannot rotate except in an adjustment state, making it impossible to perform fine adjustments or other rotations.

SUMMARY OF THE INVENTION

[0004] One object of the invention is to provide a kettlebell that can be easily adjusted.

[0005] One object of the invention is to provide a kettlebell with clear rotational positioning.

[0006] One object of the invention is to provide a kettlebell with a rotating shaft capable of rotating freely in an unloaded state.

[0007] The invention provides a kettlebell comprising: [0008] a main weight block stacked on a top of a plurality of weight blocks, each of the weight blocks is provided with an axle hole; a teeth meshing plate is provided on a top surface of the main weight block, the teeth meshing plate is annularly provided with a plurality of connecting grooves thereon; [0009] a rotating shaft pivotally disposed on a main body and having a fixed shaft and a sliding shaft; the fixed shaft is radially provided with a plurality of pins capable of optionally connecting with all of the weight blocks, a through groove is formed in a center of the fixed shaft, a slot is axially provided on the fixed shaft at an upper position; the sliding shaft is inserted into the through groove, a pushed block is provided at a bottom of the sliding shaft and capable of being pushed by a pushing member to cause axial position changes; the sliding shaft is radially provided with an upper engaging rod and a lower engaging rod thereon, the upper engaging rod and the lower engaging rod pass through the slot, the lower engaging rod is capable of optionally engaging with the connecting grooves of the main weight block; [0010] a large teeth plate elastically disposed on a top end of the main body and being able to move elastically in the main body; a through hole is provided in a center of the large teeth plate for the rotating shaft to pass through; a bottom of the large teeth plate is provided with first engaging teeth on a periphery of the through hole annularly; and [0011] a connecting plate provided with a perforation in a middle for the rotating shaft to pass through, an upper end surface of the connecting plate is annularly provided with second engaging teeth movably meshing with the first engaging teeth, a lower end surface of the connecting plate is annularly provided with connecting teeth, and the connecting teeth are connected with the upper engaging rod of the rotating shaft.

[0012] Preferably, the sliding shaft is provided with a chute thereon, the upper engaging rod is disposed in the chute to enable the upper engaging rod to displace axially relative to the sliding shaft, when the upper engaging rod moves upward, the connecting plate is capable of butting against the large teeth plate upward to form fixation; when the upper engaging rod moves downward, the connecting plate is capable of rotating relative to the large teeth plate, and the second engaging teeth are capable of elastically disengaging from the first engaging teeth.

[0013] Preferably, further comprising a handle, the handle comprises a driving block and an

eccentric grip, one end of the driving block is inserted with the upper engaging rod, another end thereof is pivotally provided on an eccentric block of the eccentric grip, the eccentric block is capable of eccentrically driving the driving block to displace to enable the driving block to drive the upper engaging rod to displace.

[0014] In the kettlebell provided by the invention, the upper engaging rod on the rotating shaft is capable of driving the connecting plate to elastically mesh with the large teeth plate, so that when the rotating shaft rotates, the connecting plate can be elastically positioned on the large teeth plate. Each rotation only switches one position, so that a weight adjustment position of the weight blocks is clear. In addition, the lower engaging rod is capable of engaging on the main weight block to form an embedded fixation, which can increase a fixation effect when the weight blocks are combined on the main body, and the rotating shaft is capable of rotating freely without engaging with the weight block.

Description

BRIEF DESCRIPTION OF DRAWINGS

[0015] The objects, features, and achieved efficacies of the invention can be understood from the description and drawings of the following preferred embodiment, in which:

[0016] FIG. 1 is an exploded perspective view of a main body of a kettlebell according to a preferred embodiment of the invention.

[0017] FIG. 2 is an exploded perspective view of the kettlebell according to a preferred embodiment of the invention.

[0018] FIG. 3 is a cross-sectional view of the main body separated from a base of the kettlebell according to a preferred embodiment of the invention with the main body not combined with a main weight block or a weight block.

[0019] FIG. 4 is a cross-sectional view of combination of the main body and the base of the kettlebell according to a preferred embodiment of the invention with a rotating shaft in a state without combination of the weight block and with an eccentric grip being lifted up.

[0020] FIG. 4A is a partially enlarged cross-sectional view of FIG. 4.

[0021] FIG. 4B is a partially enlarged cross-sectional view perpendicular to FIG. 4.

[0022] FIG. 5 is a cross-sectional view of combination of the main body and the base of the kettlebell according to a preferred embodiment of the invention with the rotating shaft in a state without combination of the weight block and with the eccentric grip being pressed down.

[0023] FIG. 5A is a partially enlarged cross-sectional view of FIG. 5.

[0024] FIG. 5B is a partially enlarged cross-sectional view perpendicular to FIG. 5.

[0025] FIG. 6 is a cross-sectional view of the main body of the kettlebell being lifted up and combined with the main weight block according to a preferred embodiment of the invention.

[0026] FIG. 6A is a partially enlarged cross-sectional view of FIG. 6.

DETAILED DESCRIPTION OF THE INVENTION

[0027] Please refer to FIGS. 1 to 4 for a preferred embodiment of a kettlebell provided by the invention, mainly comprising a base **10**, a plurality of weight blocks **20**, a main weight block **30**, a rotating shaft **40**, a main body **50**, a large teeth plate **60**, a connecting plate **70**, and a handle **80**.

[0028] The base **10** has a supporting groove **11** on a top surface. The supporting groove **11** is oval in shape. A pushing member **12** is provided at a central position of the supporting groove **11**. A height of the pushing member **12** is higher than a bottom surface of the supporting groove **11**.

[0029] Please refer to FIG. 2. The weight blocks **20**, **30** are stacked up and down on the supporting groove **11** of the base **10**, and are disposed in an oval shape. A center of each of the weight blocks **20**, **30** has an axle hole **21**, **31**, each of the axle hole passes through a top and a bottom faces of each of the weight blocks. Each of the weight blocks **20**, **30** is provided with a through hole **22**, **33**

by the axle hole **21**, **31**. The sizes of the through holes **22**, **33** of the weight blocks **20**, **30** are different, the lower the weight block **20**, the larger the through hole **22**.

[0030] Please refer to FIG. 2. The main weight block **30** is stacked on a top of the weight blocks **20** and is the topmost weight block. The axle hole **31** is provided in a center of the main weight block **30** to coincide with the axle holes **21** of the weight blocks **20**. A teeth meshing plate **32** is disposed on a top surface of the main weight block **30**, close to a circumference of the axle hole **31**. The teeth meshing plate **32** is annularly provided with a plurality of connecting grooves **321** thereon. The main weight block **30** is provided with the through hole **33**, the through hole **33** is disposed by connecting to the teeth meshing plate **32**. A quantity of the connecting grooves **321** is twice a quantity of all of the weight blocks **20**, **30**.

[0031] Please refer to FIG. 2. The rotating shaft **40** is pivotally disposed on the main body **50**. The rotating shaft **40** is inserted into the axle holes **21**, **31** of the weight blocks **20**, **30**. The rotating shaft **40** has a fixed shaft **41** and a sliding shaft **42**. The fixed shaft **41** is radially provided with a plurality of pins **411** capable of optionally connecting with the weight blocks **20**, **30**. When the pins **411** are rotated positionally to locate at the through holes **22**, **33** of the weight blocks **20**, **30**, the rotating shaft **40** will not connect with the weight blocks **20**, **30**. When the pins **411** are located at positions not provided with the through holes **22**, **33** of the weight blocks **20**, **30**, the pins **411** are capable of connecting with the weight blocks **20**, **30**. A through groove **412** is formed in a center of the fixed shaft **41**, and a slot **413** is axially provided on the fixed shaft **41** at an upper position. The sliding shaft **42** is inserted into the through groove **412**, a pushed block **421** is provided at a bottom of the sliding shaft **42** and capable of being pushed by the pushing member **12** of the base **10** to cause axial position changes of the sliding shaft **42**.

[0032] The sliding shaft **42** is radially provided with an upper engaging rod **422** and a lower engaging rod **423**. The upper engaging rod **422** and the lower engaging rod **423** pass through the slot **413** of the fixed shaft **41**. The upper engaging rod **422** and the fixed shaft **41** actuate synchronously, and the lower engaging rod **423** is capable of optionally engaging with the connecting grooves **321** of the teeth meshing plate **32** of the main weight block **30**. When the main body **50** is placed on the base **10**, the pushing member **12** contacts the rotating shaft **40** and pushes the pushed block **421** upward. The lower engaging rod **423** upwardly disengages from the connecting grooves **321** of the teeth meshing plate **32** so that the rotating shaft **40** is not limited by the main weight block **30**, and the rotating shaft **40** is capable of performing weight adjustment operations. When the main body **50** is separated from the base **10**, the pushing member **12** cannot push the pushed block **421**, the sliding shaft **42** will move downward, and the lower engaging rod **423** will also move downward. When the main weight block **30** is assembled in the main body **50**, the lower engaging rod **423** is engaged in one of the connecting grooves **321**, so that the lower engaging rod **423** and the main weight block **30** are engaged with each other, and the rotating shaft **40** cannot rotate. When the main weight block **30** is not assembled in the main body **50**, the lower engaging rod **423** will not be limited, so that the rotating shaft **40** is capable of rotating freely. The sliding shaft **42** is provided with a chute **424** thereon, the upper engaging rod **422** is slidably disposed in the chute **424** to enable the upper engaging rod **422** to move upward and downward. An elastic member **43** is provided between a top end of the fixed shaft **41** and the sliding shaft **42** of the rotating shaft **40**. The elastic member **43** is capable of generating an elastic pushing force for the sliding shaft **42**. When the sliding shaft **42** is pushed upward by the pushing member **12**, the elastic member **43** will also be compressed, causing the elastic member **43** to generate an elastic pushing force. After the pushing member **12** is separated from the sliding shaft **42**, the elastic member **43** will generate an elastic force to push the sliding shaft **42** downward.

[0033] Please refer to FIG. 3. The main body **50** can be detachably placed on the base **10**, and an accommodating chamber **51** is provided at a bottom of the main body **50** for accommodating the weight blocks **20**, **30**. A top surface of the main body **50** is provided with a weight display part **52**. The weight display part **52** is annularly provided with a plurality of weight values, which

correspond to different weight value changes of the weight blocks **20** and the main weight block **30**.

[0034] Please refer to FIG. 2. The large teeth plate **60** is axially slidably disposed in a top end of the accommodating chamber **51** of the main body **50**. A through hole **61** is provided in a center of the large teeth plate **60** for the rotating shaft **40** to pass through. A bottom of the large teeth plate **60** is provided with first engaging teeth **62** on a periphery of the through hole **61** annularly. A top surface of the large teeth plate **60** is provided with four elastic elements **63** so that the large teeth plate **60** can be elastically disposed on the top end of the accommodating chamber **51** of the main body **50** and is movable elastically relative to the main body **50**.

[0035] Please refer to FIG. 2. The connecting plate **70** has a perforation **71** in a middle for the rotating shaft **40** to pass through. An upper end surface of the connecting plate **70** is annularly provided with second engaging teeth **72** movably meshing with the first engaging teeth **62**. A lower end surface of the connecting plate **70** is annularly provided with connecting teeth **73**, and the connecting teeth **73** are connected with the upper engaging rod **422** of the rotating shaft **40**. A quantity of the second engaging teeth **72** is the same as a quantity of the connecting teeth **73**, and are symmetrically disposed.

[0036] The handle **80** comprises a driving block **81** and an eccentric grip **82**. One end of the driving block **81** is inserted with the upper engaging rod **422** of the rotating shaft **40**, and another end thereof is pivotally disposed on an eccentric block **821** of the eccentric grip **82**. When the eccentric block **821** rotates, an eccentricity is generated to drive the driving block **81** to displace. When the eccentric grip **82** is pulled upward, the driving block **81** moves with the upper engaging rod **422**, and the driving block **81** moves downward relatively. When the eccentric grip **82** is pressed downward, the driving block **81** rises relatively. When the driving block **81** moves upward, that is, the eccentric grip **82** is pressed downward, the upper engaging rod **422** is driven to move upward. When the driving block **81** displaces downward, that is, the eccentric grip **82** is pulled upward, the upper engaging rod **422** moves downward. When the main body **50** is located on the base **10**, the sliding shaft **42** is pushed upward. When the eccentric grip **82** is maintained in a downwardly pressed state, a position of the upper engaging rod **422** is driven upward, and the upper engaging rod **422** causes the connecting plate **70** to butt against the large teeth plate **60** upwardly, the large teeth plate **60** is fixed close to the top end of the main body **50**, and the connecting plate **70** cannot be separated from the large teeth plate **60**. When the main body **50** is located on the base **10**, the sliding shaft **42** is pushed upward. At this time, the eccentric grip **82** is pulled upward, the upper engaging rod **422** is driven downward by the driving block **81**, and the connecting plate **70** moves downward along with the upper engaging rod **422**. An elastic force of the elastic elements **63** pushes the large teeth plate **60** away from the main body **50**. A gap is provided between the large teeth plate **60** and the main body **50** so that the connecting plate **70** is capable of rotating relative to the large teeth plate **60**. When the connecting plate **70** rotates, the second engaging teeth **72** push the first engaging teeth **62** upward, and one of the second engaging teeth **72** elastically disengages from one of the first engaging teeth **62** and rotates in a direction toward one of the other first engaging teeth **62**, and an elastic force of the elastic elements **63** of the large teeth plate **60** pushes the first engaging teeth **62** to mesh with the second engaging teeth **72** to form a switching action. A single switching is a weight selection switch of the weight blocks **20**, **30**. The handle **80** is provided with a display window **83** relative to the weight display part **52** of the main body **50** to enable a user to observe a currently adjusted weight value from a position of the display window **83**.

[0037] Please refer to FIGS. 3 to 6. When in use, when the main body **50** is not disposed on the base **10**, and the weight blocks **20**, **30** are not assembled in the main body **50**, all of the weight blocks **20**, **30** are disposed on the base **10**. The main body **50** and the rotating shaft **40** are not combined with all of the weight block **20**, **30**. The main body **50** only has its weight, that is, a lightest weight. At this time, the lower engaging rod **423** on the rotating shaft **40** is not limited positionally, the pushed block **421** is not pushed, and the upper engaging rod **422** is not meshed

with the connecting plate **70**. Therefore, the rotating shaft **40** and the handle **80** are capable of rotating freely, when the upper engaging rod **422** rotates, the connecting plate **70** is not driven to rotate. An elastic force of the elastic elements **63** of the large teeth plate **60** pushes the large teeth plate **60** to combine with the connecting plate **70**, so that the large teeth plate **60** and the connecting plate **70** are maintained at fixed positions. The rotating shaft **40** and the handle **80** are in a freely rotatable state, enabling the user to adjust a position of the rotating shaft **40**. At this time, regardless of whether the driving block **81** of the handle **80** ascends or descends, because the pushed block **421** of the sliding shaft **42** has not been pushed upward, the upper engaging rod **422** is not meshed with the connecting plate **70**. That is, the upper engaging rod **422** cannot drive the connecting plate **70** to rotate. In this way, a position of the rotating shaft **40** can be freely adjusted in the main body **50**, so that before the rotating shaft **40** engages with any of the weight blocks **20**, **30**, positions of the pins **411** can be adjusted to initial positions. In addition, if different weight blocks are combined, the axle holes have different positions, the rotating shaft **40** can be adjusted accordingly to suit dispositions at different positions.

[0038] Please refer to FIGS. **4**, **4A**, **4B** and **5**, **5A**, **5B**. When adjusting a weight of the kettlebell, the main body **50** is disposed on the base **10**. At this time, the rotating shaft **40** passes through the axle holes **21**, **31** of the weight blocks **20**, **30**, and the pins **411** on the rotating shaft **40** pass through the through hole **33** of the main weight block **30** and the through holes **22** of the weight blocks **20**. After the main body **50** is fixed on the base **10**, the pushed block **421** of the sliding shaft **42** of the rotating shaft **40** is pushed by the pushing member **12**, causing the lower engaging rod **423** to move upward to maintain a distance from the teeth meshing plate **32** of the main weight block **30**. At the same time, the elastic member **43** is pressed to generate an elastic pushing force.

[0039] Then, please refer to FIGS. **5**, **5A** and **5B**. When the main body **50** is disposed on the base **10**, the pushing member **12** pushes the sliding shaft **42** to move upward. When the eccentric grip **82** is pressed down, the upper engaging rod **422** is lifted up by the driving block **81**, enabling the upper engaging rod **422** to drive the connecting teeth **73** to move upward, causing the connecting plate **70** to move upward, and the connecting plate **70** is moved toward the large teeth plate **60**. As a result, the large teeth plate **60** is pressed and moves toward the top end of the accommodating chamber **51** of the main body **50**, the second engaging teeth **72** and the first engaging teeth **62** are fixed with one another, and the connecting plate **70** cannot be adjusted.

[0040] Please refer to FIGS. **4**, **4A** and **4B**. When the main body **50** is disposed on the base **10** and a position of the rotating shaft **40** is to be adjusted, that is, weight adjustment. The eccentric grip **82** is pulled upward to lower a position of the eccentric block **821**, the driving block **81** descends accordingly, thereby causing the upper engaging rod **422** to descend. At this time, an elastic force of the elastic elements **63** of the large teeth plate **60** pushes the large teeth plate **60** and the connecting plate **70** downward, and the connecting teeth **73** of the connecting plate **70** are engaged with the upper engaging rod **422**. Then, the handle **80** is rotated, so that the upper engaging rod **422** drives the connecting teeth **73** to rotate, and the second engaging teeth **72** also rotate along with the connecting teeth **73**. The first engaging teeth **62** are actuated by the second engaging teeth **72** to produce a teeth displacement action that moves upward, causing the large teeth plate **60** to move upward. At the same time, the elastic elements **63** generate an elastic restoring force, when one of the second engaging teeth **72** rotates to mesh with one of the other first engaging teeth **62**, an elastic force of the elastic elements **63** pushes the large teeth plate **60** to restore, so that the first engaging teeth **62** mesh with the second engaging teeth **72** again. At this time, the pins **411** of the rotating shaft **40** rotate at a predetermined angle, which is an angle at which a weight of the weight blocks **20**, **30** is adjusted. For example, the invention discloses that the five weight blocks **20** and the weight block **30** are provided, so the connecting teeth **73** will have seven angle switches, that is, seven different configurations of weight blocks **20**, **30** can be provided (no weight block, the main weight block **30**, the main weight block **30** and one to five of the weight blocks **20**). The user will feel a switching action between the second engaging teeth **72** and the first engaging teeth **62** in

every switching, and can also determine a reversing angle and completion of adjustment of the weight blocks **20**, **30**, and weight values of the weight blocks **20**, **30** displayed by the weight display part **52** can be observed from the display window **83** of the handle **80**. After adjustment is completed, the eccentric grip **82** is pressed down to move the driving block **81** upward, so that the upper engaging rod **422** pushes the connecting teeth **73** upward, the connecting plate **70** drives the large teeth plate **60** to push upward, and the second engaging teeth **72** cannot move on the first engaging teeth **62**.

[0041] Please refer to FIG. 6 and FIG. 6A. When in use, the main body **50** is lifted, and the pins **411** of the rotating shaft **40** assemble the selected through holes **22**, **33** of the weight blocks **20**, **30** on the rotating shaft **40**. In this embodiment, the pins **411** of the rotating shaft **40** are combined with the main weight block **30**, and the weight blocks **20** are not combined. When the main body **50** is lifted, the pushed block **421** is not pushed by the pushing member **12**, an elastic pushing force of the elastic member **43** pushes the sliding shaft **42** and the pushed block **421** downward, causing the lower engaging rod **423** to be engaged downwardly in the connecting grooves **321** of the teeth meshing plate **32** of the main weight block **30** to form fixation. Therefore, when the rotating shaft **40** is combined with at least the main weight block **30**, the lower engaging rod **423** limits rotation of the rotating shaft **40**, thereby preventing accidental touching by the user when the main body **50** is assembled with the weight blocks.

[0042] In the kettlebell provided by the invention, fixation is formed through the lower engaging rod and the teeth meshing plate of the main weight block. Compared with the conventional kettlebell with the main shaft being fixed to the main body, the rotating shaft of the invention is capable of rotating freely without being combined with the main weight block and when the main body is not disposed on the base, enabling the user to adjust a position of the rotating shaft. In addition, through the upper engaging rod driving the connecting plate to form a meshing structure between the connecting plate and the large teeth plate, rotation position of the rotating shaft can be made clear and reliability of adjustment and positioning of the weight blocks can be ensured.

[0043] Although the invention has been disclosed as above with the embodiment, it is not intended to limit the invention. A person having ordinary skill in the art to which the invention pertains can make various changes and modifications without departing from the spirit and scope of the invention. Therefore, scope of protection of the invention shall be subject to what is defined in the pending claims.

Claims

1. A kettlebell comprising: a base having a pushing member; a plurality of weight blocks stacked on the base, each of the weight blocks having an axle hole; a main weight block stacked on a top of the weight blocks, the main weight block being provided with an axle hole; a teeth meshing plate being provided on a top surface of the main weight block, the teeth meshing plate being annularly provided with a plurality of connecting grooves thereon; a main body detachably placed on the base, an accommodating chamber being provided at a bottom of the main body for accommodating all of the weight blocks; a rotating shaft pivotally disposed on a main body and having a fixed shaft and a sliding shaft; the fixed shaft being radially provided with a plurality of pins capable of optionally connecting with all of the weight blocks, a through groove being formed in a center of the fixed shaft, a slot being axially provided on the fixed shaft at an upper position; the sliding shaft being inserted into the through groove, a pushed block being provided at a bottom of the sliding shaft and capable of being pushed by the pushing member to cause axial position changes; the sliding shaft being radially provided with an upper engaging rod and a lower engaging rod thereon, the upper engaging rod and the lower engaging rod passing through the slot, the lower engaging rod being capable of optionally engaging with the connecting grooves of the main weight block; a large teeth plate elastically disposed on a top end of the accommodating chamber of the main body

and being movable elastically in the main body; a through hole being provided in a center of the large teeth plate for the rotating shaft to pass through; a bottom of the large teeth plate being provided with first engaging teeth on a periphery of the through hole annularly; and a connecting plate provided with a perforation in a middle for the rotating shaft to pass through, an upper end surface of the connecting plate being annularly provided with second engaging teeth movably meshing with the first engaging teeth, a lower end surface of the connecting plate being annularly provided with connecting teeth, and the connecting teeth being connected with the upper engaging rod of the rotating shaft.

2. The kettlebell as claimed in claim 1, wherein the sliding shaft is provided with a chute thereon, the upper engaging rod is disposed in the chute to enable the upper engaging rod to displace axially relative to the sliding shaft, when the upper engaging rod moves upward, the connecting plate is capable of butting against the large teeth plate upward to form fixation; when the upper engaging rod moves downward, the connecting plate is capable of rotating relative to the large teeth plate, and the second engaging teeth are capable of elastically disengaging from the first engaging teeth.

3. The kettlebell as claimed in claim 2, further comprising a handle having a driving block and an eccentric grip, one end of the driving block being inserted with the upper engaging rod, another end thereof being pivotally provided on an eccentric block of the eccentric grip, the eccentric block being capable of eccentrically driving the driving block to displace to enable the driving block to drive the upper engaging rod to displace.

4. The kettlebell as claimed in claim 3, wherein the main body is provided with a weight display part thereon, the handle is provided with a display window thereon, the display window is capable of displaying the corresponding weight display part.

5. The kettlebell as claimed in claim 1, wherein a plurality of elastic elements are provided between the large teeth plate and the main body.

6. The kettlebell as claimed in claim 1, wherein each of the weight blocks is provided with a through hole by the axle hole for the pins to pass through, and the sizes of the through holes of the different weight blocks are different.

7. The kettlebell as claimed in claim 1, wherein the main weight block is provided with a through hole by the axle hole of the main weight block, the through hole is adjacent to the teeth meshing plate.

8. The kettlebell as claimed in claim 1, wherein a quantity of the connecting grooves of the teeth meshing plate on the main weight block is twice a quantity of all of the weight blocks.

9. The kettlebell as claimed in claim 7, wherein a quantity of the connecting grooves of the teeth meshing plate on the main weight block is twice a quantity of all of the weight blocks.

10. The kettlebell as claimed in claim 1, wherein the base has a supporting groove on a top surface, the pushing member is provided in the supporting groove, a height of the pushing member is higher than a bottom surface of the supporting groove, and the weight blocks are provided in the supporting groove.

11. The kettlebell as claimed in claim 1, wherein a quantity of the second engaging teeth of the connecting plate is the same as a quantity of the connecting teeth, and are symmetrically disposed.

12. The kettlebell as claimed in claim 1, wherein an elastic member is provided between a top end of the fixed shaft and the sliding shaft of the rotating shaft, the elastic member is capable of generating an elastic pushing force for the sliding shaft.
