

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12384168
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Somano; Toshiaki et al.

Printing apparatus and printing method

Abstract

Provided is a technique that enables proper sorting of discharged print media by suppressing curling of each of the print media sufficiently. A determining unit determines a curling suppressing operation to be executed such that in a case where sorting operation is executed, the suppressing operation having a higher effect of suppressing curling is executed than in a case where the sorting operation is executed. Then, a print control unit controls a print head to perform printing on print media while executing the suppressing operation determined by the determining unit.

Inventors: Somano; Toshiaki (Tokyo, JP), Yamamoto; Kosuke (Yokohama, JP), Sakurai; Norio (Tokyo, JP), Emoto; Yuki (Tokyo, JP), Muro; Kentaro (Tokyo, JP)

Applicant: CANON KABUSHIKI KAISHA (Tokyo, JP)

Family ID: 68695182

Assignee: Canon Kabushiki Kaisha (Tokyo, JP)

Appl. No.: 18/504606

Filed: November 08, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240100862 A1	Mar. 28, 2024

Foreign Application Priority Data

JP	2018-104789	May. 31, 2018
----	-------------	---------------

Related U.S. Application Data

Publication Classification

Int. Cl.: **B41J11/00** (20060101); **B41J13/00** (20060101); **B41J13/02** (20060101); **B41J13/10** (20060101); **B41J29/38** (20060101); **B65H33/08** (20060101)

U.S. Cl.:

CPC **B41J11/0005** (20130101); **B41J13/0036** (20130101); **B41J13/009** (20130101); **B41J13/02** (20130101); **B41J13/106** (20130101); **B41J29/38** (20130101); **B65H33/08** (20130101); B65H2301/51256 (20130101); B65H2405/351 (20130101); B65H2511/15 (20130101)

Field of Classification Search

CPC: B65H (43/08); B65H (2553/612); B65H (43/06); B65H (2511/20); B65H (2511/414); B65H (43/00); B65H (29/68); B65H (2515/81); B65H (2513/53); B65H (2513/108); B65H (2513/512); B65H (2513/10); B65H (2801/06); B65H (29/00); B41J (2/16535); B41J (2/16588); B41J (2/16508); B41J (2/195)

USPC: 347/104

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
7452043	12/2007	Ono et al.	N/A	N/A
11020988	12/2020	Somano et al.	N/A	N/A
2009/0073211	12/2008	Imoto	N/A	N/A
2013/0257964	12/2012	Itogawa	N/A	N/A
2015/0239702	12/2014	Sugiyama et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2006-137610	12/2005	JP	N/A
2007-307763	12/2006	JP	N/A
2009-286513	12/2008	JP	N/A
2013-208809	12/2012	JP	N/A
2015-160695	12/2014	JP	N/A
2016-190394	12/2015	JP	N/A

OTHER PUBLICATIONS

U.S. Appl. No. 16/423,354, filed May 28, 2019 (First Named Inventor: Norio Sakurai). cited by applicant

U.S. Appl. No. 16/423,361, filed May 28, 2019 (First Named Inventor: Yuki Emoto). cited by applicant

U.S. Appl. No. 16/420,393, filed May 23, 2019 (First Named Inventor: Yuki Emoto). cited by applicant

Primary Examiner: Uhlenhake; Jason S

Assistant Examiner: Shenderov; Alexander D

Attorney, Agent or Firm: Venable LLP

Background/Summary

(1) This is a continuation of U.S. patent application Ser. No. 17/243,703, filed Apr. 29, 2021, which is a continuation of U.S. patent application Ser. No. 16/416,483, filed May 20, 2019, now U.S. Pat. No. 11,020,988.

BACKGROUND OF THE INVENTION

Field of the Invention

(1) The present invention relates to printing apparatuses and printing methods in which print media after printing are sorted and stacked when discharged.

Description of the Related Art

(2) Japanese Patent Laid-Open No. 2007-307763 discloses a technique for performing an operation of suppressing curling of a print medium caused by printing according to the type of print medium, the size of the printed area of the print medium, the ratio of the margin, and the humidity. Also, Japanese Patent Laid-Open No. 2006-137610 discloses a technique for sorting print media into stacks each having a specified number of sheets by moving a stacking unit (delivery tray), on which print media are stacked, to shift the discharged print media in the direction intersecting the discharging direction.

(3) In a case where a print medium has a large curl, the print medium tends to come into contact with a member disposed fixedly or the like. In this state, in a case where sorting operation is performed using a movable tray as in the technique disclosed in Japanese Patent Laid-Open No. 2006-137610, the print medium may move on the tray along with the movement of the tray, and this may make it impossible to sort discharged print media properly.

SUMMARY OF THE INVENTION

(4) The present invention provides a technique capable of suppressing curling of the print medium to sort the discharged print medium properly even in a case of using a tray to sort print media after printing.

(5) In the first aspect of the present invention, there is provided a printing apparatus comprising: a print head configured to apply ink to a print medium to perform printing; a conveying unit configured to convey a print medium; an obtaining unit configured to obtain information on whether a stacking unit is to execute sorting operation, the stacking unit including a stacking surface on which a print medium printed by the print head and discharged by the conveying unit is stacked, the stacking unit being capable of executing the sorting operation for a stacked print medium by moving a movable portion that is movable part of the stacking surface, in a direction along the stacking surface; and a determining unit configured to determine, based on the information, execution of suppressing operation that suppresses curling of a print medium to be discharged on the stacking unit, wherein the determining unit determines execution of the suppressing operation that suppresses curling of a print medium to a higher extent in a case where the sorting operation is executed than an extent to which curling of a print medium is suppressed in a case where the sorting operation is not executed.

(6) In the second aspect of the present invention, there is provided a printing apparatus comprising: a print head configured to apply ink to a print medium to perform printing; a conveying unit configured to convey a print medium; an obtaining unit configured to obtain information on whether a stacking unit is to execute sorting operation, the stacking unit including a stacking surface on which a print medium printed by the print head and conveyed by the conveying unit is stacked, the stacking unit being capable of executing the sorting operation for a stacked print medium by moving a movable portion that is movable part of the stacking surface, in a direction along the stacking surface; and a control unit configured to control the conveying unit based on the information, wherein the control unit causes the conveying unit to convey a print medium such that a retention period for which the print medium is retained within a conveying path through which the print medium is conveyed is longer in a case where the sorting operation is executed than in a case where the sorting operation is not executed.

(7) In the third aspect of the present invention, there is provided a printing method comprising: printing by applying ink to a print medium; conveying a print medium; and stacking a print medium printed, conveyed, and discharged onto a stacking unit including a stacking surface, wherein in a case of executing sorting operation of sorting a stacked print medium by moving a movable portion that is movable part of the stacking surface, in a direction along the stacking surface, curling of a print medium being conveyed to the stacking unit is suppressed to a higher extent than in a case where the sorting operation is not executed.

(8) The present invention makes it possible to suppress curling of the print medium to sort the discharged print medium properly even in a case of using a tray to sort print media after printing.

(9) Further features of the present invention will become apparent from the following description of exemplary embodiments with reference to the attached drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a view of a printing apparatus in a standby state;
- (2) FIG. 2 is a diagram of a control configuration of the printing apparatus;
- (3) FIG. 3 is a view of the printing apparatus in a print state;
- (4) FIG. 4A, FIG. 4B, and FIG. 4C are views of a conveying path of a print medium fed from a first cassette;
- (5) FIG. 5A, FIG. 5B, and FIG. 5C are views of a conveying path of a print medium fed from a second cassette;
- (6) FIG. 6A, FIG. 6B, FIG. 6C, and FIG. 6D are views of views of a conveying path used in a case of performing a print operation on the back surface of a print medium;
- (7) FIG. 7 is a view of the printing apparatus in a maintenance state;
- (8) FIG. 8 is a diagram illustrating the correspondence relationship between drive rollers and motors;
- (9) FIGS. 9A and 9B are diagrams illustrating a schematic configuration of a discharging tray and a movement mechanism of a movable tray;
- (10) FIGS. 10A and 10B are diagrams illustrating states where an arm is at a detecting position and at an evacuation position;
- (11) FIG. 11 is a diagram illustrating the structure near the arm;
- (12) FIGS. 12A, 12B, 12C, 12D, and 12E are diagrams showing detection results of sensors and the states for the detection results;
- (13) FIGS. 13A, 13B, and 13C are diagrams for explaining the occurrence of curling and the problem in the curling;
- (14) FIGS. 14A and 14B are diagrams for explaining correction values based on the ink injection

amount;

(15) FIGS. **15A** and **15B** are diagrams for explaining correction values based on the type of print medium and the temperature and humidity environment;

(16) FIGS. **16A**, **16B**, and **16C** are diagrams for explaining correction values based on a stack amount and whether to execute the sorting operation; and

(17) FIG. **17** is a flowchart illustrating a detailed process routine of a determination process.

DESCRIPTION OF THE EMBODIMENTS

(18) Hereinafter, embodiments of the present invention will be described with reference to the drawings.

(19) FIG. **1** is an internal configuration diagram of an inkjet printing apparatus **1** (hereinafter “printing apparatus **1**”) used in the present embodiment. In the drawings, an x-direction is a horizontal direction, a y-direction (a direction perpendicular to paper) is a direction in which ejection openings are arrayed in a print head **8** described later, and a z-direction is a vertical direction.

(20) The printing apparatus **1** is a multifunction printer comprising a print unit **2** and a scanner unit **3**. The printing apparatus **1** can use the print unit **2** and the scanner unit **3** separately or in synchronization to perform various processes related to print operation and scan operation. The scanner unit **3** comprises an automatic document feeder (ADF) and a flatbed scanner (FBS) and is capable of scanning a document automatically fed by the ADF as well as scanning a document placed by a user on a document plate of the FBS. The present embodiment is directed to the multifunction printer comprising both the print unit **2** and the scanner unit **3**, but the scanner unit **3** may be omitted. FIG. **1** shows the printing apparatus **1** in a standby state in which neither print operation nor scan operation is performed.

(21) In the print unit **2**, a first cassette **5A** and a second cassette **5B** for housing printing medium (cut sheets) **S** are detachably provided at the bottom of a casing **4** in the vertical direction.

Relatively small printing medium of up to A4 size are stacked and housed in the first cassette **5A** and relatively large printing medium of up to A3 size are stacked and housed in the second cassette **5B**. A first feeding unit **6A** for feeding housed printing medium one by one is provided near the first cassette **5A**. Similarly, a second feeding unit **6B** is provided near the second cassette **5B**. In print operation, a print medium **S** is selectively fed from either one of the cassettes.

(22) Conveying rollers **7**, a discharging roller **12**, pinch rollers **7a**, spurs **7b**, a guide **18**, an inner guide **19**, and a flapper **11** are conveying mechanisms for guiding a print medium **S** in a predetermined direction. The conveying rollers **7** are drive rollers located upstream and downstream of the print head **8** and driven by a conveying motor (not shown). The pinch rollers **7a** are follower rollers that are turned while nipping a print medium **S** together with the conveying rollers **7**. The discharging roller **12** is a drive roller located downstream of the conveying rollers **7** and driven by the conveying motor (not shown). The spurs **7b** nip and convey a print medium **S** together with the conveying rollers **7** and discharging roller **12** located downstream of the print head **8**.

(23) The printing apparatus **1** has multiple motors for driving the above drive rollers, and each drive roller is connected to one of the motors. The relationship between the motors and the drive roller will be described later in detail.

(24) The guide **18** is provided in a conveying path of a print medium **S** to guide the print medium **S** in a predetermined direction. The inner guide **19** is a member extending in the y-direction. The inner guide **19** has a curved side surface and guides a print medium **S** along the side surface. The flapper **11** is a member for changing a direction in which a print medium **S** is conveyed in duplex print operation. A discharging tray **13** (stacking unit) is a tray for stacking and housing printing medium **S** that were subjected to print operation and discharged by the discharging roller **12**.

(25) The print head **8** of the present embodiment is a full line type color inkjet print head. In the print head **8**, a plurality of ejection openings configured to eject ink based on print data are arrayed

in the y-direction in FIG. 1 so as to correspond to the width of a print medium S. That is, the print head **8** is configured to eject inks of a plurality of colors. When the print head **8** is in a standby position, an ejection opening surface **8a** of the print head **8** is oriented vertically downward and capped with a cap unit **10** as shown in FIG. 1. In print operation, the orientation of the print head **8** is changed by a print controller **202** described later such that the ejection opening surface **8a** faces a platen **9**. The platen **9** includes a flat plate extending in the y-direction and supports a print medium S being subjected to print operation by the print head **8** from the back side. The movement of the print head **8** from the standby position to a printing position will be described later in detail.

(26) An ink tank unit **14** separately stores ink of four colors to be supplied to the print head **8**. An ink supply unit **15** is provided in the midstream of a flow path connecting the ink tank unit **14** to the print head **8** to adjust the pressure and flow rate of ink in the print head **8** within a suitable range. The present embodiment adopts a circulation type ink supply system, where the ink supply unit **15** adjusts the pressure of ink supplied to the print head **8** and the flow rate of ink collected from the print head **8** within a suitable range.

(27) A maintenance unit **16** comprises the cap unit **10** and a wiping unit **17** and activates them at predetermined timings to perform maintenance operation for the print head **8**. The maintenance operation will be described later in detail.

(28) FIG. 2 is a block diagram showing a control configuration in the printing apparatus **1**. The control configuration mainly includes a print engine unit **200** that exercises control over the print unit **2**, a scanner engine unit **300** that exercises control over the scanner unit **3**, and a controller unit **100** that exercises control over the entire printing apparatus **1**. A print controller **202** controls various mechanisms of the print engine unit **200** under instructions from a main controller **101** of the controller unit **100**. Various mechanisms of the scanner engine unit **300** are controlled by the main controller **101** of the controller unit **100**. The control configuration will be described below in detail.

(29) In the controller unit **100**, the main controller **101** including a CPU controls the entire printing apparatus **1** using a RAM **106** as a work area in accordance with various parameters and programs stored in a ROM **107**. For example, when a print job is input from a host apparatus **400** via a host I/F **102** or a wireless I/F **103**, an image processing unit **108** executes predetermined image processing for received image data under instructions from the main controller **101**. The main controller **101** transmits the image data subjected to the image processing to the print engine unit **200** via a print engine I/F **105**.

(30) The printing apparatus **1** may acquire image data from the host apparatus **400** via a wireless or wired communication or acquire image data from an external storage unit (such as a USB memory) connected to the printing apparatus **1**. A communication system used for the wireless or wired communication is not limited. For example, as a communication system for the wireless communication, Wi-Fi (Wireless Fidelity; registered trademark) and Bluetooth (registered trademark) can be used. As a communication system for the wired communication, a USB (Universal Serial Bus) and the like can be used. For example, when a scan command is input from the host apparatus **400**, the main controller **101** transmits the command to the scanner unit **3** via a scanner engine OF **109**.

(31) An operating panel **104** is a mechanism for the user to give and receive input and output to and from the printing apparatus **1**. Via the operating panel **104**, the user can give instructions for operations, such as copying and scanning, set the print mode, and receive information from the printing apparatus **1**. The user can set via the operating panel **104** whether to execute a sorting operation for discharging sheets with the sheets sorted into stacks each having a specified number of sheets in copying. Note that for printing based on a print job inputted from the host apparatus **400**, setting for sorting operation is made at the host apparatus **400**. In the present embodiment, copying operation on print media S performed by the print unit **2** based on information that the scanner unit **3** scans and printing operation on print media S performed by the print unit **2** based on

information inputted from the host apparatus **400** are simply called “printing” as appropriate.

(32) For example, in a case where copying operation is selected on the operating panel **104** (input panel), a button for setting the sorting operation appears along with buttons for setting the magnification and other settings, and whether to execute the sorting operation is set according to the selection of the button. The host apparatus **400** opens a window of printer properties with which detailed setting related to printing can be made. Whether to execute the sorting operation is set by checking the checkbox displayed in this window. In other words, in the present embodiment, the host apparatus **400** serves as an external apparatus to which setting of the sorting operation can be inputted.

(33) In the print engine unit **200**, the print controller **202** including a CPU controls various mechanisms of the print unit **2** using a RAM **204** as a work area in accordance with various parameters and programs stored in a ROM **203**. When various commands and image data are received via a controller OF **201**, the print controller **202** temporarily stores them in the RAM **204**. The print controller **202** allows an image processing controller **205** to convert the stored image data into print data such that the print head **8** can use it for print operation. After the generation of the print data, the print controller **202** allows the print head **8** to perform print operation based on the print data via a head OF **206**. At this time, the print controller **202** conveys a print medium **S** by driving the feeding units **6A** and **6B**, conveying rollers **7**, discharging roller **12**, and flapper **11** shown in FIG. **1** via a conveyance control unit **207**. The print head **8** performs print operation in synchronization with the conveyance operation of the print medium **S** under instructions from the print controller **202**, thereby performing printing.

(34) The conveyance control unit **207**, connected to the detection unit **212** for detecting the conveyance state of the printing medium **S** and the drive unit **211** for driving the drive rollers, controls the conveyance of the printing medium **S** using the drive unit **211**, based on detection results obtained from the detection unit **212**. The detection unit **212** has the detection members **20** for detecting the printing medium **S** and the encoders **21** for detecting the amount of rotation of the drive rollers.

(35) Printing is performed in the course of the conveyance of the printing medium **S** by the conveyance control unit **207**, by the print head **8** performing print operation under instructions from the print controller **202**.

(36) A head carriage control unit **208** changes the orientation and position of the print head **8** in accordance with an operating state of the printing apparatus **1** such as a maintenance state or a printing state. An ink supply control unit **209** controls the ink supply unit **15** such that the pressure of ink supplied to the print head **8** is within a suitable range. A maintenance control unit **210** controls the operation of the cap unit **10** and wiping unit **17** in the maintenance unit **16** when performing maintenance operation for the print head **8**.

(37) An arm control unit **213** drives a flapper **91** (described later) to control the rotation of an arm **90** (described later) and thus moves the arm **90** to an evacuation position or a detecting position. The arm control unit **213** is connected to a stack-amount detection unit **214** for detecting a stack amount of print media **S** on the discharging tray **13** based on the displacement (rotation) of the arm **90**. A sorting control unit **217** controls the movement of a movable tray **13b** (described later), which is part of the discharging tray **13**, via a drive unit **218** to sort print media **S** being discharged. A temperature detection unit **219** (temperature detection unit) detects the temperature of the environment where the printing apparatus **1** is disposed. A humidity detection unit **220** (humidity detection unit) detects the humidity of the environment where the printing apparatus **1** is disposed. Note that the temperature detection unit **219** and the humidity detection unit **220** may detect the temperature and humidity inside the printing apparatus **1**.

(38) In the scanner engine unit **300**, the main controller **101** controls hardware resources of the scanner controller **302** using the RAM **106** as a work area in accordance with various parameters and programs stored in the ROM **107**, thereby controlling various mechanisms of the scanner unit

3. For example, the main controller **101** controls hardware resources in the scanner controller **302** via a controller OF **301** to cause a conveyance control unit **304** to convey a document placed by a user on the ADF and cause a sensor **305** to scan the document. The scanner controller **302** stores scanned image data in a RAM **303**. The print controller **202** can convert the image data acquired as described above into print data to enable the print head **8** to perform print operation based on the image data scanned by the scanner controller **302**.

(39) FIG. **3** shows the printing apparatus **1** in a printing state. As compared with the standby state shown in FIG. **1**, the cap unit **10** is separated from the ejection opening surface **8a** of the print head **8** and the ejection opening surface **8a** faces the platen **9**. In the present embodiment, the plane of the platen **9** is inclined about 45° with respect to the horizontal plane. The ejection opening surface **8a** of the print head **8** in a printing position is also inclined about 45° with respect to the horizontal plane so as to keep a constant distance from the platen **9**.

(40) In the case of moving the print head **8** from the standby position shown in FIG. **1** to the printing position shown in FIG. **3**, the print controller **202** uses the maintenance control unit **210** to move the cap unit **10** down to an evacuation position shown in FIG. **3**, thereby separating the cap member **10a** from the ejection opening surface **8a** of the print head **8**. The print controller **202** then uses the head carriage control unit **208** to turn the print head **8** 45° while adjusting the vertical height of the print head **8** such that the ejection opening surface **8a** faces the platen **9**. After the completion of print operation, the print controller **202** reverses the above procedure to move the print head **8** from the printing position to the standby position.

(41) Next, a conveying path of a print medium S in the print unit **2** will be described. When a print command is input, the print controller **202** first uses the maintenance control unit **210** and the head carriage control unit **208** to move the print head **8** to the printing position shown in FIG. **3**. The print controller **202** then uses the conveyance control unit **207** to drive either the first feeding unit **6A** or the second feeding unit **6B** in accordance with the print command and feed a print medium S.

(42) FIGS. **4A** to **4C** are diagrams showing a conveying path in the case of feeding an A4 size print medium S from the first cassette **5A**. A print medium S at the top of a stack of printing medium in the first cassette **5A** is separated from the rest of the stack by the first feeding unit **6A** and conveyed toward a print area P between the platen **9** and the print head **8** while being nipped between the conveying rollers **7** and the pinch rollers **7a**. FIG. **4A** shows a conveying state where the leading edge of the print medium S is about to reach the print area P. The direction of movement of the print medium S is changed from the horizontal direction (x-direction) to a direction inclined about 45° with respect to the horizontal direction while being fed by the first feeding unit **6A** to reach the print area P.

(43) In the print area P, a plurality of ejection openings provided in the print head **8** eject ink toward the print medium S. In an area where ink is applied to the print medium S, the back side of the print medium S is supported by the platen **9** so as to keep a constant distance between the ejection opening surface **8a** and the print medium S. After ink is applied to the print medium S, the conveying rollers **7** and the spurs **7b** guide the print medium S such that the print medium S passes on the left of the flapper **11** with its tip inclined to the right and is conveyed along the guide **18** in the vertically upward direction of the printing apparatus **1**. FIG. **4B** shows a state where the leading edge of the print medium S has passed through the print area P and the print medium S is being conveyed vertically upward. The conveying rollers **7** and the spurs **7b** change the direction of movement of the print medium S from the direction inclined about 45° with respect to the horizontal direction in the print area P to the vertically upward direction.

(44) After being conveyed vertically upward, the print medium S is discharged into the discharging tray **13** by the discharging roller **12** and the spurs **7b**. FIG. **4C** shows a state where the leading edge of the print medium S has passed through the discharging roller **12** and the print medium S is being discharged into the discharging tray **13**. The discharged print medium S is held in the discharging tray **13** with the side on which an image was printed by the print head **8** down.

(45) FIGS. 5A to 5C are diagrams showing a conveying path in the case of feeding an A3 size print medium S from the second cassette 5B. A print medium S at the top of a stack of printing medium in the second cassette 5B is separated from the rest of the stack by the second feeding unit 6B and conveyed toward the print area P between the platen 9 and the print head 8 while being nipped between the conveying rollers 7 and the pinch rollers 7a.

(46) FIG. 5A shows a conveying state where the leading edge of the print medium S is about to reach the print area P. In a part of the conveying path, through which the print medium S is fed by the second feeding unit 6B toward the print area P, the plurality of conveying rollers 7, the plurality of pinch rollers 7a, and the inner guide 19 are provided such that the print medium S is conveyed to the platen 9 while being bent into an S-shape.

(47) The rest of the conveying path is the same as that in the case of the A4 size print medium S shown in FIGS. 4B and 4C. FIG. 5B shows a state where the leading edge of the print medium S has passed through the print area P and the print medium S is being conveyed vertically upward. FIG. 5C shows a state where the leading edge of the print medium S has passed through the discharging roller 12 and the print medium S is being discharged into the discharging tray 13.

(48) FIGS. 6A to 6D show a conveying path in the case of performing print operation (duplex printing) for the back side (second side) of an A4 size print medium S. In the case of duplex printing, print operation is first performed for the first side (front side) and then performed for the second side (back side). A conveying procedure during print operation for the first side is the same as that shown in FIGS. 4A to 4C and therefore description will be omitted. A conveying procedure subsequent to FIG. 4C will be described below.

(49) After the print head 8 finishes print operation for the first side and the trailing edge of the print medium S passes by the flapper 11, the print controller 202 turns the conveying rollers 7 backward to convey the print medium S into the printing apparatus 1. At this time, since the flapper 11 is controlled by an actuator (not shown) such that the tip of the flapper 11 is inclined to the left, the leading edge of the print medium S (corresponding to the trailing edge during the print operation for the first side) passes on the right of the flapper 11 and is conveyed vertically downward. FIG. 6A shows a state where the leading edge of the print medium S (corresponding to the trailing edge during the print operation for the first side) is passing on the right of the flapper 11.

(50) Then, the print medium S is conveyed along the curved outer surface of the inner guide 19 and then conveyed again to the print area P between the print head 8 and the platen 9. At this time, the second side of the print medium S faces the ejection opening surface 8a of the print head 8. FIG. 6B shows a conveying state where the leading edge of the print medium S is about to reach the print area P for print operation for the second side.

(51) The rest of the conveying path is the same as that in the case of the print operation for the first side shown in FIGS. 4B and 4C. FIG. 6C shows a state where the leading edge of the print medium S has passed through the print area P and the print medium S is being conveyed vertically upward. At this time, the flapper 11 is controlled by the actuator (not shown) such that the tip of the flapper 11 is inclined to the right. FIG. 6D shows a state where the leading edge of the print medium S has passed through the discharging roller 12 and the print medium S is being discharged into the discharging tray 13.

(52) Next, maintenance operation for the print head 8 will be described. As described with reference to FIG. 1, the maintenance unit 16 of the present embodiment comprises the cap unit 10 and the wiping unit 17 and activates them at predetermined timings to perform maintenance operation.

(53) FIG. 7 is a diagram showing the printing apparatus 1 in a maintenance state. In the case of moving the print head 8 from the standby position shown in FIG. 1 to a maintenance position shown in FIG. 7, the print controller 202 moves the print head 8 vertically upward and moves the cap unit 10 vertically downward. The print controller 202 then moves the wiping unit 17 from the evacuation position to the right in FIG. 7. After that, the print controller 202 moves the print head 8

vertically downward to the maintenance position where maintenance operation can be performed.

(54) On the other hand, in the case of moving the print head **8** from the printing position shown in FIG. **3** to the maintenance position shown in FIG. **7**, the print controller **202** moves the print head **8** vertically upward while turning it 45°. The print controller **202** then moves the wiping unit **17** from the evacuation position to the right. Following that, the print controller **202** moves the print head **8** vertically downward to the maintenance position where maintenance operation can be performed.

(55) FIG. **8** is a diagram illustrating the correspondence relationship between the multiple motors and drive rollers in the printing apparatus **1**. A first feeding motor **22** drives the first feeding unit **6A** for feeding print media **S** from the first cassette **5A**. A second feeding motor **23** drives the second feeding unit **6B** for feeding print media **S** from the second cassette **5B**. A first conveying motor **24** drives a first intermediate roller **71A** which conveys first a print medium **S** fed by the first feeding unit **6A**. A second conveying motor **25** drives a second intermediate roller **71B** which conveys first a print medium **S** fed by the second feeding unit **6B**.

(56) A main conveying motor **26** drives a main conveying roller **70** which is disposed upstream of the platen **9** and conveys mainly the print medium **S** being printed. The main conveying motor **26** also drives two conveying rollers **7** that are disposed downstream of the platen **9** and convey further downstream the print medium **S** conveyed by the main conveying roller **70**.

(57) A third conveying motor **27** drives two conveying rollers **7** that convey downward the print medium **S** on the first side of which printing has been performed. The third conveying motor **27** also drives two conveying rollers **7** that are disposed along the inner guide **19** and convey toward the print head **8** the print medium fed from the second cassette **5B** and conveyed by the second intermediate roller **71B** or the print medium on the first side of which printing has been performed and which was reversed.

(58) A fourth conveying motor **28** drives two conveying rollers **7** that convey upward or downward the print medium **S** on which print operation has been performed. A discharging motor **29** drives the discharging roller **12** which discharges the print medium **S** on which printing has been performed to the discharging tray **13**. In this way, each of the two feeding motors **22** and **23**, five conveying motors **24** to **28**, and discharging motor **29** is associated with one or more drive rollers.

(59) Meanwhile, at eight places along the conveying path are disposed the detection members **20** for detecting the presence of the print medium **S**. Each detection member **20** includes a sensor and a mirror disposed on both sides of the conveying path. The sensor having a light emitting portion and a light receiving portion is disposed on one side of the conveying path; the mirror is disposed at a position on the other side of the conveying path and facing the sensor. The light emitted from the light emitting portion of the sensor is reflected by the mirror, and the presence of a print medium **S**, in other words, whether the leading edge or the trailing edge has passed is determined based on whether the light receiving portion detects the reflected light.

(60) The conveyance control unit **207** drives the feeding motors **22** and **23**, the conveying motors **24** to **28**, and the discharging motor **29** separately to control the conveyance as the entire apparatus, based on the detection results from the multiple detection members **20** and the output values of the encoders each of which detects the amount of rotation of the corresponding drive roller.

(61) Next, the configuration of the discharging tray **13** will be described. FIG. **9A** is a schematic configuration perspective diagram of the discharging tray **13** in the printing apparatus **1**. FIG. **9B** is a schematic configuration diagram illustrating the movement mechanism of the movable tray **13b** of the discharging tray **13**.

(62) The discharging tray **13** (stacking unit) has a slanted surface which is slanted relative to the print medium **S** being discharged, and the print media **S** are stacked on this slanted surface. The discharging tray **13** includes fixed trays **13a** fixed to frames which are frameworks of the printing apparatus **1** and the movable tray **13b** movable in the y-direction (the direction orthogonal to the direction in which the print medium **S** is discharged) on the fixed tray **13a**, as illustrated in FIG. **9A**. The fixed trays **13a** are located at both edges of the discharging tray **13** in the y-direction, and

the movable tray **13b** is located at the center portion in the y-direction. With this structure, the print media **S** discharged onto the discharging tray **13** are mainly stacked on the movable tray **13b**. For example, based on an instruction inputted by the user, when a specified number of print media **S** are discharged, the movable tray **13b** moves in the forward direction or backward direction of the y-direction on the discharging tray **13** so that print media **S** are sorted into stacks each being the specified number of print media.

(63) The movable tray **13b** (movable portion) is movable via a movement mechanism relative to the fixed tray **13a** in the forward direction and backward direction of the y-direction as illustrated in FIG. **9B**. The fixed tray **13a** has a base member **401** extending in the y-direction, on the back surface thereof (the surface opposed to the surface on which the print media **S** are stacked). On the base member **401** is disposed the drive unit **218** including a motor driven under the control of the sorting control unit **217**. Also, on the base member **401** are disposed a pulley **402** that rotates by being driven by the drive unit **218** and an idler pulley **404** between which and the pulley **402** an endless belt **403** is stretched. The belt **403** stretched between the pulley **402** and the idler pulley **404** extends in the y-direction. Fixed to the belt **403** is a driving force transmission unit **405**. The driving force transmission unit **405** is provided with a connecting portion **405a** that is connected to a connecting portion **13ba** disposed on the back surface of the movable tray **13b**.

(64) With this structure, the rotation of the belt **403** by the drive unit **218** moves the driving force transmission unit **405** in the forward direction and backward direction of the y-direction. This movement of the driving force transmission unit **405** moves in the y-direction the movable tray **13b** connected to the driving force transmission unit **405** via the connecting portions **405a** and **13ba**. In other words, the driving force of the drive unit **218** is transmitted to the movable tray **13b** via the belt **403** and other parts, and the transmitted driving force moves the movable tray **13b** in the forward direction and backward direction of the y-direction.

(65) Next, description will be provided for the structure for detecting a stack amount of print media **S** on the discharging tray **13**. FIG. **10A** is a cross-sectional view of a discharge opening **95** and its periphery in a case where the arm **90** is at the detecting position where the arm **90** can detect the stack amount of print media **S**. FIG. **10B** is a cross-sectional view of the discharge opening **95** and its periphery in a case where the arm **90** is at the evacuation position where the arm **90** is not in contact with the print medium **S**. FIG. **11** is a schematic configuration perspective diagram illustrating the arm **90** and its periphery.

(66) The printing apparatus **1** includes the arm **90** to detect the stack amount of print media **S** on the discharging tray **13** and the flapper **91** that rotates the arm **90** and is also capable of restraining curling of the discharged print medium **S**, near the discharge opening **95** through which the print medium **S** is discharged by the discharging roller **12**. The arm **90** is rotatable, and its rotation center is above the discharge opening **95**. The flapper **91** is rotatable, and its rotation center is between the rotation center of the arm **90** and the discharge opening **95** in the z-direction.

(67) The rotation of the flapper **91** is controlled by a drive unit (not illustrated) driven by the arm control unit **213**. The arm **90** and the flapper **91** are separate members, so that the arm **90** and the flapper **91** can operate separately. Note that the arm **90** can come into contact with and move away from the flapper **91** via a cam portion **92** provided on the arm **90**. With this structure, the arm **90** rotates by being driven by the flapper **91** and is movable between the detecting position where the distal end of the arm **90** can come into contact with the print media **S** stacked on the discharging tray **13** by its rotating and the evacuation position where the arm **90** does not come into contact with the print medium **S** being discharged from the discharge opening **95**.

(68) The evacuation position should preferably be, for example, a position where the arm **90** does not come into contact with the print medium **S** being discharged from the discharge opening **95** and the print media **S** stacked on the discharging tray **13**. In addition, the evacuation position should preferably be a position where the arm **90** is less likely to interfere with the print media **S** or the user's hand in a case where the user removes the stacked print media **S** from the discharging tray

13. The arm **90** is positioned at the detecting position in a case where it detects the stack amount of print media **S** on the discharging tray **13** (see FIG. **10A**). The arm **90** is positioned at the evacuation position at maintenance, removal of the print medium **S**, a specified timing in a full-stack detection process described later, and the like (see FIG. **10B**).

(69) The flapper **91** has a guide groove **97** formed at an approximate center thereof, and the cam portion **92** provided on the arm **90** is slidably in contact with this guide groove **97**. Here, the arm **90** is rotatable around a supporting shaft **96** extending in the y-direction. The supporting shaft **96** rotates circumferentially according to the displacement of the arm **90**. Thus, in a case where the flapper **91** rotates in the arrow A direction (see FIG. **10A**), the arm **90** is moved up from the detecting position by means of the cam portion **92** and rotates in the arrow B direction (see FIG. **10A**) to the evacuation position. In a case where the flapper **91** rotates in the arrow C direction (see FIG. **10B**), the arm **90** moves from the evacuation position following the rotation of the flapper **91** by its own weight and rotates in the arrow D direction (see FIG. **10B**) to the detecting position.

(70) The supporting shaft **96** has a first flag **96a** and a second flag **96b** fixed thereto at different positions in the circumferential direction (rotation direction) of the supporting shaft **96**. In other words, the first flag **96a** and the second flag **96b** have the same rotation center as the arm **90**, so that the rotation of the arm **90** causes the first flag **96a** and the second flag **96b** to rotate integrally with the arm **90**. In addition, sensors **215** (a first sensor **215a** and a second sensor **215b**) are provided to detect the rotation of the first flag **96a** and the second flag **96b**. The first sensor **215a** detects the first flag **96a**, and the second sensor **215b** detects the second flag **96b**. The sensors **215** are, for example, photo interrupters, and the on and off of the first sensor **215a** or the second sensor **215b** is determined based on whether the first flag **96a** or the second flag **96b** blocks light. This allows the sensors **215** to detect the rotation state of the arm **90**. Thus, based on the detection results by the sensors **215**, it is possible to estimate the stack amount of print media **S** on the discharging tray **13**.

(71) In the present embodiment, the first flag **96a** and second flag **96b** and the first sensor **215a** and second sensor **215b** are included in the stack-amount detection unit **214**. The detection results by the first sensor **215a** and the second sensor **215b**, for example, are outputted from the stack-amount detection unit **214** to the print controller **202**, which estimates the stack amount. In other words, in the present embodiment, the arm **90**, the stack-amount detection unit **214**, and the print controller **202** function as a detection unit configured to detect the stack amount of print media **S** on the discharging tray **13**.

(72) Specifically, the stack amount is determined by combinations of detection results of the first sensor **215a** and the second sensor **215b**. FIG. **12A** is a table showing the relationship between the detection results of the first sensor **215a** and the second sensor **215b** and the stack amount. In the first sensor **215a** and the second sensor **215b**, “ON” indicates that the light is blocked, and “OFF” indicates that the light is passing through. The stack amount is defined by the vertical length from the surface of the discharging tray **13** on which print media **S** are stacked. FIG. **12B** is a diagram illustrating the state where the stack amount is less than 14 mm. In this state, both the first sensor **215a** and the second sensor **215b**, light toward which is not blocked, are “OFF”. FIG. **12C** is a diagram illustrating the state where the stack amount is more than or equal to 14 mm and less than 33 mm (what is called “nearly full stack”). In this state, the first sensor **215a**, light toward which is blocked by the first flag **96a**, is “ON”, and the second sensor **215b**, light toward which is not blocked by the second flag **96b**, is “OFF”. FIG. **12D** is a diagram illustrating the state where the stack amount is more than or equal to 33 mm (what is called “full stack”). In this state, both the first sensor **215a** and the second sensor **215b**, light toward which is blocked, are “ON”. FIG. **12E** is a diagram illustrating the state where the arm **90** is at the evacuation position. In this state, the first sensor **215a**, light toward which is not blocked by the first flag **96a**, is “OFF”, and the second sensor **215b**, light toward which is blocked by the second flag **96b**, is “ON”.

(73) Here, curling of a print medium **S** caused by printing will be described. In a case where the

print medium is print paper, curling caused by ink ejected from the print head **8** is different depending on the paper grain direction of the print paper. FIG. **13A** is a diagram illustrating the state of curling in a case where a print paper sheet (long grain paper) the entire print surface of which ink has been applied to uniformly by the printing apparatus **1** is discharged on the discharging tray **13** without its curling being suppressed. FIG. **13B** is a diagram illustrating the print medium **S** discharged on the discharging tray **13** in FIG. **13A** when viewed from the downstream side toward the upstream side in the discharging direction. FIG. **13C** is a cross-sectional perspective view of the discharge opening **95** and its periphery. Note that in the printing apparatus **1**, the print medium **S** is discharged with the printed surface facing down, which operation is called the face-down discharging.

(74) In a case of long grain paper, the paper grain direction of which agree with the longitudinal direction (discharging direction), application of ink causes curling at both edges in the width direction (y-direction) which intersects (is orthogonal to) the discharging direction of the print medium **S**, causing both the edge portions to curl up from the discharging tray **13** (movable tray **13b**), as illustrated in FIG. **13A**. Note that although not illustrated, in a case of short grain paper the paper grain direction of which is the lateral direction (width direction), curling occurs at both edges of the print medium **S** in the discharging direction, and both the edge portions curl up from the discharging tray **13** (movable tray **13b**).

(75) Thus, in a case where the sheet is long grain paper, and curling occurs as illustrated in FIG. **13B**, the contact area between the print medium **S** and the movable tray **13b** is smaller in the width direction than in the case of no curling. In other words, this print medium **S** is unstable on the movable tray **13b** with respect to force in the width direction. In a case where the movable tray **13b** moves in the width direction (y-direction) in this state, the print medium **S** on the movable tray **13b** moves in the width direction. As a result, there is a possibility that the print media **S** discharged cannot be sorted by means of the movable tray **13b** properly.

(76) In addition, in a case where the edge portions of the print medium **S** in the width direction are curled, the edge portions in the width direction may come into contact with a member fixedly disposed around the discharge opening **95**, for example, a spur base **94** (see FIG. **13C**), on the discharging tray **13**. In a case where the movable tray **13b** moves in a state where the edge portions curled up by curling is in contact with a member disposed fixedly, the print medium **S** turns about the position of the print medium **S** that is in contact with the member. This decreases an orderly stacking property of the discharged print medium **S** and prevents the print medium **S** from being sorted properly. Note that the spur base **94** protrudes downstream in the discharging direction above a standing surface **13bb** of the movable tray **13b**, and the protruded portion is located downstream of the standing surface **13bb**.

(77) In the present embodiment, in printing operation for performing printing on the print media **S**, a curling suppressing operation (suppressing operation) is determined according to whether sorting operation is to be executed, along with various conditions. Specifically, a curling suppressing operation (including the necessity of curling suppressing operation) is determined according to a monitor value calculated based on four conditions. The four conditions are the ink injection amount, the type of print medium **S**, the temperature and humidity environment, and the stack amount and sorting information. A correction value is obtained for each condition, and the obtained correction values are added up to obtain the monitor value. The obtained monitor value is compared with thresholds corresponding to respective curling suppressing operations, a curling suppressing operation is determined based on the comparison result.

(78) Hereinafter, description will be provided for how to obtain the correction values based on the conditions and how to obtain the monitor value. Note that in the present embodiment, description is provided for a case where the print medium **S** is print paper (long grain paper). Obtaining the correction values and obtaining the monitor value based on the correction values are executed by the print controller **202**. In other words, in the present embodiment, the print controller **202**

functions as an obtaining unit configured to obtain the correction values and the monitor value.

(79) <Obtaining Correction Values Based on Ink Injection Amount>

(80) FIG. 14A is a diagram illustrating specified areas **S0** for calculating the ink injection amount; FIG. 14B is a table showing weighting coefficients set for respective areas in the specified area **S0**.

(81) For the print medium **S** such as print paper, even if the amount of applied ink is the same, the degree of curling (the amount of curling, in other words, the amount of curling up from the movable tray **13b** in the present embodiment) is different depending on the printing position of the ink. Specifically, the closer to an edge of the print medium **S** the area of printing is, the more noticeable curling occurs. Thus, in the present invention, the ink injection amount (the amount of applied ink, the ratio of ink) in the specified area **S0** at each of the four corners of the print medium **S** is calculated, and a correction value is obtained based on the calculation result for the specified area **S0** having the largest ink injection amount among the four specified areas **S0**. Note that calculation of the ink injection amounts at the four specified areas **S0** is executed by the print controller **202**. In other words, in the present embodiment, the print controller **202** functions as a calculation unit configured to calculate the ink injection amount.

(82) The size (area) of the specified area **S0** may be changed according to various conditions such as the type of print medium **S** that can be used and the type of ink to be used. For the position of the specified area **S0**, the specified area **S0** may be away by a specified distance from the nearest short side or long side of the print medium **S**, or the specified area **S0** may abut on it. The distance from the short side and the distance from the long side may be different.

(83) Each of the four specified areas **S0** is divided into four sub-areas in the width direction of the print medium **S** (the moving direction of the movable tray **13b**). Specifically, the sub-area **S1**, sub-area **S2**, sub-area **S3**, and sub-area **S4** are set in this order from the edge toward the center of the print medium **S** in the width direction. The ink injection amount in each specified area **S0** is calculated as a sum of products of the ink injection amounts in the respective sub-areas **S1**, **S2**, **S3**, and **S4** multiplied by the corresponding weighting coefficients.

(84) Specifically, to calculate the ink injection amount of the specified area **S0**, the ink injection amount in each of the sub-areas **S1**, **S2**, **S3**, and **S4** is calculated based on input image data. For each of the sub-areas **S1**, **S2**, **S3**, and **S4**, the corresponding weighting coefficient is set in advance (see FIG. 14B). The ink injection amount calculated for an area is multiplied by the weighting coefficient set for the area. Specifically, the ink injection amount in the sub-area **S1** is multiplied by the weighting coefficient “4”. The ink injection amount in the sub-area **S2** is multiplied by the weighting coefficient “3”. The ink injection amount in the sub-area **S3** is multiplied by the weighting coefficient “2”. The ink injection amount in the sub-area **S4** is multiplied by the weighting coefficient “1”. Note that the closer to the edge in the width direction an area is, the larger the weighting coefficient of the area is. After that, the calculated values are added up, and the resultant value is the ink injection amount of the specified area **S0**.

(85) The ink injection amount is calculated for each of the four specified areas **S0** as described above, and a correction value is obtained based on the ink injection amount of the specified area **S0** for which the calculated value is largest. For the correction value, for example, a table in which correction values based on the ink injection amount are set in advance is stored in the ROM **203** or the like, and a correction value is obtained based on the table. Alternatively, a formula having the ink injection amount as a variable may be stored in the ROM **203** or the like, and the correction value may be obtained based on the formula.

(86) <Obtaining Correction Value Based on Type of Print Media **S**, and Obtaining Correction Value Based on Temperature and Humidity Environment>

(87) FIG. 15A is a table showing correction values set according to the type of print medium **S**; FIG. 15B is a table showing correction values set according to combinations of temperatures and humidities.

(88) The table in which correction values are set according to the type of print medium **S** (see FIG.

15A) is stored, for example, in the ROM 203 or the like. A correction value based on the type of print medium S is obtained from the stored table using inputted information on the type of print medium S.

(89) Also, the table in which correction values are set according to combinations of temperatures and humidities (see FIG. 15B) is stored, for example, in the ROM 203 or the like. A correction value based on the temperature and humidity environment is obtained from the stored table based on the detection result detected by the temperature detection unit 219 and the detection result detected by the humidity detection unit 220.

(90) Note that for the correction values set in the tables of FIGS. 15A and 15B, the larger curling is caused by ink application in a condition, the larger value is set for the condition. The correction values are not limited to the values indicated in FIGS. 15A and 15B. Specifically, the correction value may be changed depending on the type of ink to be used. In addition, although the correction value based on temperature and humidity environment is obtained using a table as shown in FIG. 15B, the present invention is not limited to this method. Specifically, a formula having information on temperature and humidity as variables may be stored in the ROM 203 or the like, the correction value may be calculated based on the formula.

(91) <Obtaining Correction Value Based on Stack Amount and Sorting Information>

(92) FIG. 16A is a diagram illustrating the discharge opening 95 and its periphery in a case where the stack amount of print media S on the discharging tray 13 is less than a specified amount; FIG. 16B is a diagram illustrating the discharge opening 95 and its periphery in a case where the stack amount is more than or equal to the specified amount. FIG. 16C is a table showing correction values set according to the combinations of the stack amount and whether to execute the sorting operation.

(93) In a case where the sorting information indicates that the sorting operation is not to be executed, the possibility that the movement of the movable tray 13b in the width direction may cause a curled print medium S to be caught at the spur base 94, does not have to be taken into account, but only an opening for discharging, specifically, the discharge path from the discharge opening 95 needs to be provided for the print medium. In other words, the operation only needs to be such that the print medium S being discharged does not hit the trailing edge (the upstream edge portion in the discharging direction) of a curled portion of stacked print media S. Thus, in the vertical direction (z-direction), the curled print medium S is made to be within the distance L1 from the trailing edge (the upstream edge portion in the discharging direction) of the stacked print media to the discharge opening 95. In other words, in a case where a curled print medium S is stacked onto the print media S on the discharging tray 13, the trailing edge of the curled print medium S is made to be positioned below the discharge opening 95.

(94) On the other hand, in a case where the sorting information indicates that the sorting operation is to be executed, the possibility of the print media S being caught at the spur base 94 needs to be taken into account in order to sort stacked print media S properly. Thus, in the vertical direction (z-direction), the curled print medium S is made to be within the distance L2 from the trailing edge of the stacked print media S to the spur base 94. In other words, in a case where a curled print medium S is stacked onto the print media S on the discharging tray 13, the trailing edge of the curled print medium S is made to be positioned below the spur base 94.

(95) Distance L2 is shorter than distance L1. Accordingly, the amount of allowable curling is smaller in a case of executing the sorting operation than in a case of no sorting operation, and thus the amount of curling that the curling suppressing operation has to suppress is higher. Hence, the correction value is set larger in a case of executing the sorting operation than in a case of no sorting operation.

(96) Meanwhile, the distances L1 and L2 from the print media S stacked on the discharging tray 13 to the discharge opening 95 and the spur base 94, respectively, are shorter in a case where the stack amount of print media S on the discharging tray 13 is more than or equal to a specified amount (see

FIG. 16B) than in a case where it is less than the specified amount (see FIG. 16A). Thus, the amount of allowable curling is lower in a case where the stack amount of print media S on the discharging tray **13** is more than or equal to the specified amount than in a case where it is less than the specified amount, thus the amount of curling that the curling suppressing operation has to suppress is higher. Hence, the correction value is larger in a case where the stack amount of print media S on the discharging tray **13** is more than or equal to the specified amount than in a case where it is less than the specified amount. Note that in the present embodiment, the specified amount for the stack amount is set to 14 mm. The specified amount for the stack amount is not limited to 14 mm, but it may be changed depending on the apparatus configuration and other factors.

(97) Based on these viewpoints, a table in which correction values are set according to the combinations of the stack amount and whether to execute the sorting operation (see FIG. 16C), is created and stored in the ROM **203**. A correction value based on the stack amount and whether to execute the sorting operation is obtained from the stored table based on the information on the stack amount obtained by the stack-amount detection unit **214** and the setting information on whether to execute the sorting operation.

(98) Note that for the correction values set in the table of FIG. 16C, the correction value is larger in a case where the stack amount is more than or equal to the specified amount than in a case where it is less than the specified amount. The correction value is also larger in a case of executing the sorting operation than in a case of no sorting operation. Although correction values in two steps are set—in a case where the stack amount is more than or equal to the specified amount as the threshold and in a case where it is less than the specified amount—the present invention is not limited to this setting. The correction values in three or more steps may be set for the stack amount. In this case, increasing the number of sensors and flags as appropriate enables the stack-amount detection unit **214** to detect the stack amount in three or more steps.

(99) <Obtaining Monitor Value>

(100) The correction value based on the ink injection amount, the correction value based on the type of print medium S, the correction value based on the temperature and humidity environment, and the correction value based on the stack amount and the sorting information are added up to obtain the monitor value. For example, in a case where the ink injection amount in the specified area **S0** is 260, the type of print medium S is plain paper, the temperature is 30° C., the humidity is 60%, the stack amount is 5 mm, and the sorting operation is to be executed, the correction values are as follows. The correction value based on the ink injection amount is “260”, the correction value based on the type of print medium S is “30”, the correction value based on the temperature and humidity environment is “-80”, and the correction value based on the stack amount and the sorting information is “20”. Thus, the monitor value is $260+30+(-80)+20=230$. By comparing the monitor value thus obtained with thresholds described later, a curling suppressing operation is selected and executed.

(101) Selection of a curling suppressing operation based on the monitor value is made based on the thresholds set for the curling suppressing operations. In the present embodiment, the printing apparatus **1** is capable of executing a first curling suppressing operation and a second curling suppressing operation in printing operation for performing printing on the print media S. In the first curling suppressing operation, the conveyance speed is reduced to retain the print medium S after printing within the conveying path for a first period. In the second curling suppressing operation, to retain the print medium after printing within the conveying path for a second period which is longer the first period, the conveyance speed is reduced, and in addition, the print medium is stopped for a certain period within the conveying path after printing. Specifically, the retention period of the print medium within the conveying path is set longer in the second curling suppressing operation than in the first curling suppressing operation, increasing the ink drying time, and this makes it possible to discharge the print medium in a state where curls of the print medium are sufficiently suppressed.

(102) For the first curling suppressing operation and the second curling suppressing operation, different thresholds are set. For example, for the first curling suppressing operation, a first threshold “220” is set, and for the second curling suppressing operation a second threshold “250” is set, which is larger than the first threshold. In a case where the obtained monitor value is less than 220, no curling suppressing operation is executed; 220 or more and less than 250, the first curling suppressing operation is executed; and 250 or more, the second curling suppressing operation is executed. Note that the determination of the curling suppressing operation to be executed is executed by the print controller **202**. In other words, in the present embodiment, the print controller **202** is capable of determining whether to execute a curling suppressing operation by comparing the monitor value and the thresholds, and also functions as a determining unit capable of determining the curling suppressing operation to be executed.

(103) With the above configuration, in a case where the user gives an instruction to start printing with an input of information necessary for performing printing on the print media S, a determination process for determining a curling suppressing operation is executed, and after that, printing operation is executed based on the determined curling suppressing operation. FIG. **17** is a flowchart illustrating the process details of the determination process. A series of processes illustrated in the flowchart of FIG. **17** is executed by the print controller **202** loading program codes stored in the ROM **203** to the RAM **204**. Alternatively, part or all of the functions in the steps in FIG. **17** may be implemented by using hardware, such as an ASIC or an electronic circuit.

(104) When the determination process starts, first the print controller **202** obtains the correction values (**S1702**). Specifically, at **S1702**, the print controller **202** obtains the correction value based on the ink injection amount, the correction value based on the type of print medium S, the correction value based on the temperature and humidity environment, and the correction value based on the stack amount and the sorting information.

(105) Next, the monitor value is obtained based on the obtained correction values (**S1704**), and it is determined whether the obtained monitor value is larger than or equal to the first threshold (**S1706**). In a case where it is determined at **S1706** that the monitor value is not larger than or equal to the first threshold, it is determined that the curling suppressing operation is not to be executed (**S1708**), and this determination process ends. In a case where it is determined at **S1706** that the monitor value is larger than or equal to the first threshold, it is determined whether the monitor value is larger than or equal to the second threshold (**S1710**).

(106) In a case where it is determined at **S1710** that the monitor value is not larger than or equal to the second threshold, it is determined that the first curling suppressing operation is to be executed (**S1712**), and this determining process ends. In other words, it is determined at **S1712** that the first curling suppressing operation, in which the conveyance speed of the print medium S is reduced, is to be executed in printing operation. In a case where it is determined at **S1710** that the monitor value is larger than or equal to the second threshold, it is determined that the second curling suppressing operation is to be executed (**S1714**), and this determining process ends. In other words, it is determined at **S1714** that the second curling suppressing operation, in which the conveyance speed of the print medium S is reduced and the print medium S after printing is stopped for a certain period, is to be executed in printing operation.

(107) After that, printing operation is performed on the print media S based on the curling control process determined by the determining unit and various kinds of information included in the print job. Specifically, in printing operation with the first curling suppressing operation, print operation is executed on the print media S with the conveyance speed of the print medium S reduced from the speed set in advance to the speed set for the first curling suppressing operation. In printing operation with the second curling suppressing operation, print operation is executed on the print media S with the conveyance speed of the print medium S reduced from the speed set in advance to the speed set for the second curling suppressing operation. In addition, the print medium S after printing is stopped within the conveying path for a certain period, and then discharged onto the

discharging tray **13**.

(108) Note that the print operation with the curling suppressing operation is executed by the print controller **202** controlling the conveyance control unit **207** and the print head **8**. In other words, in the present embodiment, the print controller **202** functions as a print control unit configured to perform printing on the print media **S** while executing the curling suppressing operation.

(109) As has been described above, the printing apparatus **1** includes the discharging tray **13** configured such that the movable tray **13b** is movable on the fixed tray **13a** in a direction orthogonal to the discharging direction of the print medium **S** being discharged (in the width direction of the print medium **S**). In addition, before executing printing operation, not only the correction values based on the ink injection amount, the type of print medium **S**, and the temperature and humidity environment, but also the correction value based on the stack amount and whether to execute the sorting operation is obtained, and a curling control process is determined according to the monitor value based on the obtained correction values. Note that the monitor value is set larger in a case of performing the sorting operation than in a case of no sorting operation, and thus the larger the monitor value is, the more likely the curling suppressing operation having a higher effect to suppress curling is executed.

(110) This configuration allows the printing apparatus **1** to execute the operation that suppresses curling of the print medium **S** after printing more positively in a case of executing the sorting operation than in a case of no sorting operation. With this operation, the printing apparatus **1** can suppress curling of the print medium **S** so that the print media **S** discharged can be properly sorted.

OTHER EMBODIMENTS

(111) Note that the above embodiment may be modified as described in the following (1) to (6).

(112) (1) Although in the above embodiment, in a case where the print medium **S** is long grain paper, the print medium **S** discharged is sorted by shift in the width direction, the present invention is not limited to this operation. Specifically, in a case where the print medium **S** is short grain paper, the print medium **S** discharged may be sorted by shift in the conveyance direction. In this case, the specified area **S0** is divided into four sub-areas in the discharging direction. In the four sub-areas, the weighting coefficients are set such that the values decrease from the edge to the center in the discharging direction. Although in the above embodiment, the specified area **S0** for calculating the ink injection amount is divided into four sub-areas, the present invention is not limited to this number. Specifically, the specified area **S0** may be divided into two or three sub-areas, or it may be divided into five or more sub-areas.

(113) (2) Although in the above embodiment, the printing apparatus **1** is capable of executing the first curling suppressing operation, in which the conveyance speed is reduced, and the second curling suppressing operation, in which the conveyance speed is reduced and the print medium **S** after printing is stopped for a certain period, the present invention is not limited to this operation. Specifically, the printing apparatus **1** may be capable of only one of the curling suppressing operations. Although in the above embodiment, as the curling suppressing operation, the retention period of the print medium **S** is changed to dry the print medium **S** after printing within the conveying path and thus to suppress curling of the print medium **S**, the present invention is not limited to this operation. Specifically, the printing apparatus **1** may have a mechanism for correcting curls, and in the curling suppressing operation, curling may be suppressed by means of the mechanism.

(114) (3) Although in the present embodiment, one curling suppressing operation is selected out of the two curling suppressing operations, the present invention is not limited to this operation. Specifically, one curling suppressing operation may be selected out of three or more curling suppressing operations. In this case, for example, three or more kinds of curling suppressing operations would be set, each having a different retention period for which the print medium **S** is retained within the conveying path. The number of curling suppressing operations may be one, and only whether the curling suppressing operation is to be executed may be determined according to

the monitor value. Further, preparing two curling suppressing operations, only one of the curling suppressing operations may be determined according to the monitor value.

(115) (4) Although not described in the above embodiment, even in a case of no sorting operation, for example, the stacked print media **S** may be moved by means of the movable tray **13b** to a position where the user can take them out easily, for the user taking out print media **S**. Although in the above embodiment, the arm **90** is displaced by rotation, the present invention is not limited to this configuration. Specifically, the arm **90** may be displaced by any kind of movement as long as the arm **90** does not obstruct the movement of the print medium **S** being discharged, and the arm **90** is capable of detecting the stack amount at the position where the arm **90** is displaced.

(116) (5) Although in the above embodiment, the printing apparatus **1** is an inkjet printing apparatus of a full line type, the present invention is not limited to this type. Specifically, the printing apparatus **1** may be an inkjet printing apparatus of a serial type. In addition, although the printing apparatus **1** performs printing by an inkjet method, the present invention is not limited to this method. Various known techniques can be used for the printing method.

(117) (6) Although in the above embodiment, a curling suppressing operation is determined based on the monitor value obtained from the correction values based on the ink injection amount, the type of print medium, the temperature and humidity environment, and the stack amount and sorting information, the present invention is not limited to this operation. Specifically, the monitor value may be obtained based on at least whether to execute the sorting operation. In other words, the monitor value may be obtained only from the information on whether to execute the sorting operation, or the monitor value may be obtained based on the sorting information and at least one of the conditions of the ink injection amount, the type of print medium, the temperature, the humidity, and the stack amount.

(118) While the present invention has been described with reference to exemplary embodiments, it is to be understood that the invention is not limited to the disclosed exemplary embodiments. The scope of the following claims is to be accorded the broadest interpretation so as to encompass all such modifications and equivalent structures and functions.

(119) This application claims the benefit of Japanese Patent Application No. 2018-104789 filed May 31, 2018, which is hereby incorporated by reference herein in its entirety.

Claims

1. A printing apparatus comprising: a print head configured to apply liquid to a print medium to perform printing; and a conveying unit configured to convey a print medium to a stacking unit, wherein the conveying unit conveys the print medium in a conveying path at a first conveyance speed in a case where a sorting operation is not executed, and wherein the conveying unit conveys the print medium in the conveying path at a second conveyance speed which is lower than the first conveyance speed in a case where the sorting operation is executed.
2. The printing apparatus according to claim 1, further comprising a detection unit configured to detect a stack amount of print media on the stacking unit, wherein the conveying unit conveys the print medium in such a way that a period for which the print medium to be conveyed on the stacking unit is retained within the conveying path is longer than a period for which the print medium is conveyed at the second conveyance speed in a case where (1) the sorting operation is executed and (2) the stack amount detected by the detection unit is more than or equal to a specified amount, and wherein the conveying unit conveys the print medium to be conveyed on the stacking unit in the conveying path at the second conveyance speed in a case where (1) the sorting operation is executed and (2) the stack amount detected by the detection unit is less than the specified amount.
3. The printing apparatus according to claim 1, wherein the conveying unit conveys the print medium in such a way that a period for which the print medium is retained within the conveying

path before the print medium is conveyed on the stacking unit is longer than a period for which the print medium is conveyed at the second conveyance speed in a case where (1) the sorting operation is executed and (2) a liquid application amount which is an amount of liquid to be applied to a print medium by the print head is more than or equal to a specified amount, and wherein the conveying unit conveys the print medium in the conveying path at the second conveyance speed before the print medium is conveyed on the stacking unit in a case where (1) the sorting operation is executed and (2) the liquid application amount is less than the specified amount.

4. The printing apparatus according to claim 3, wherein the liquid application is a liquid application amount which is an amount of liquid to be applied by the print head in a specified area set at each of four corners of a print medium.

5. The printing apparatus according to claim 1, further comprising: a temperature detection unit configured to detect temperature; and a humidity detection unit configured to detect humidity, wherein the conveying unit conveys the print medium in such a way that a retention period is based on a detection result by the temperature detection unit and a detection result by the humidity detection unit.

6. The printing apparatus according to claim 1, wherein the conveying unit conveys the print medium at the second conveyance speed while the print medium is conveyed on the stacking unit after printing performed by the print head ends in the conveying path in a case where the sorting operation is executed.

7. The printing apparatus according to claim 1, wherein the conveying path is a path through which the print medium in the printing apparatus is conveyed.

8. The printing apparatus according to claim 1, further comprising an input panel to which information on whether to execute the sorting operation is inputted.

9. The printing apparatus according to claim 1, further comprising a connecting unit connectable to an external apparatus that allows input of information on whether to execute the sorting operation.

10. The printing apparatus according to claim 1, wherein a movable member moves in a width direction intersecting a direction in which a print medium is discharged.

11. The printing apparatus according to claim 1, wherein a print medium is discharged onto the stacking unit with a print surface of the print medium facing down.

12. The printing apparatus according to claim 1, further comprising the stacking unit.

13. A printing apparatus comprising: a print head configured to apply liquid to a print medium to perform printing; and a conveying unit configured to convey a print medium to a stacking unit, wherein the conveying unit do not stop the print medium at a position before the print medium is conveyed on the stacking unit after printing performed by the print head ends in a conveying path in a case where a sorting operation is not executed, and wherein the conveying unit stops, for a specified period, the print medium at the position before the print medium is conveyed on the stacking unit after printing performed by the print head ends in the conveying path in a case where the sorting operation is executed.

14. The printing apparatus according to claim 13, further comprising a detection unit configured to detect a stack amount of print media on the stacking unit, wherein the conveying unit stops, for a period longer than the specified period, the print medium at the position before the print medium is conveyed on the stacking unit after printing performed by the print head ends in the conveying path in a case where (1) the sorting operation is executed and (2) the stack amount detected by the detection unit is more than or equal to the specified amount, and wherein the conveying unit stops the print medium at the position before the print medium is conveyed on the stacking unit after printing performed by the printing head ends in the conveying path for the specified period in a case where (1) the sorting operation is executed and (2) the stack amount detected by the detection unit is less than the specified amount.

15. The printing apparatus according to claim 13, wherein the conveying unit stops, for a period longer than the specified period, the print medium at the position before the print medium is

conveyed on the stacking unit after printing performed by the print head ends in the conveying path in a case where (1) the sorting operation is executed and (2) a liquid application amount which is an amount of liquid to be applied to a print medium by the print head is more than or equal to a specified amount, wherein the conveying unit stops, for the specified period, the print medium at the position before the print medium is conveyed on the stacking unit after printing performed by the print head ends in the conveying path in a case where (1) the sorting operation is executed and (2) the liquid application amount is less than the specified amount.

16. The printing apparatus according to claim 15, wherein the liquid application amount is a liquid application amount which is an amount of liquid to be applied by the print head in a specified area set at each of four corners of a print medium.

17. The printing apparatus according to claim 13, further comprising: a temperature detection unit configured to detect temperature; and a humidity detection unit configured to detect humidity, wherein the conveying unit stops the print media in such a way that a retention period is based on a detection result by the temperature detection unit and a detection result by the humidity detection unit.

18. The printing apparatus according to claim 13, further comprising an input panel to which information on whether to execute the sorting operation is inputted.

19. The printing apparatus according to claim 13, further comprising a connecting unit connectable to an external apparatus that allows input of information on whether to execute the sorting operation.

20. The printing apparatus according to claim 13, wherein a movable member moves in a width direction intersecting a direction in which a print medium is discharged.

21. The printing apparatus according to claim 13, wherein a print medium is discharged onto the stacking unit with a print surface of the print medium facing down.

22. The printing apparatus according to claim 13, further comprising the stacking unit.
