

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12386480
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Yost; David Arthur

Computer system with a plurality of work environments where each work environment affords one or more workspaces

Abstract

A computer system provides at least one workspace as a user interface corresponding to a user-generated topic. A home topic is provided to the user as an initially selected topic. The home topic provides a workspace to the user as a user interface. User selection of a first topic within the home topic causes designation of the first topic as the current topic. A first workspace is associated with the first topic, and a first topic data structure associated with the first topic is generated and the first topic data structure is associated only with application windows, files and application related data used by the user while the first topic is designated as the current topic. The user is provided, within the first workspace, only application windows, files and application related data used by the user while the first topic is designated as the current topic.

Inventors:	Yost; David Arthur (Los Altos, CA)
Applicant:	Yost; David Arthur (Los Altos, CA)
Family ID:	68385197
Appl. No.:	18/648391
Filed:	April 28, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240353971 A1	Oct. 24, 2024

Related U.S. Application Data

continuation parent-doc US 18201141 20230523 US 11972089 child-doc US 18648391
continuation parent-doc US 17404583 20210817 US 11698711 20230711 child-doc US 18201141
continuation parent-doc US 16807041 20200302 US 11137877 20211005 child-doc US 17404583
continuation parent-doc US 16213643 20181207 US 10606446 20200331 child-doc US 16807041

Publication Classification

Int. Cl.: **G06F15/16** (20060101); **G06F3/04817** (20220101); **G06F3/0482** (20130101); **G06F9/445** (20180101); **G06F9/455** (20180101); **G06F9/50** (20060101); **G06F12/00** (20060101); **G06F16/185** (20190101); **G06F16/248** (20190101); **G06F21/53** (20130101); **H04L29/06** (20060101)

U.S. Cl.:

CPC **G06F3/04817** (20130101); **G06F3/0482** (20130101); **G06F9/5016** (20130101); **G06F16/185** (20190101); **G06F21/53** (20130101);

Field of Classification Search

CPC: G06F (3/04817); G06F (16/185); G06F (3/0482); G06F (9/5016); G06F (21/53); G06F (9/44505); G06F (8/656); G06F (9/45558); G06F (9/45533); G06F (8/63); G06Q (10/1095); G06Q (30/015); G06Q (10/02); G16H (40/20)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
8332470	12/2011	Arun	709/204	G06Q 10/10
8396891	12/2012	Tsao	707/781	B66C 1/442
8738904	12/2013	Ting	713/164	H04L 9/12
8762326	12/2013	Zhou et al.	N/A	N/A
9158820	12/2014	Bauchot et al.	N/A	N/A
9275001	12/2015	Liebold et al.	N/A	N/A
9317468	12/2015	Liebold et al.	N/A	N/A
9424359	12/2015	Hamadani et al.	N/A	N/A
10592927	12/2019	Cheng et al.	N/A	N/A
2010/0269158	12/2009	Ehler et al.	N/A	N/A
2011/0126132	12/2010	Anderson et al.	N/A	N/A
2011/0225232	12/2010	Casalaina et al.	N/A	N/A
2011/0270830	12/2010	Stefik et al.	N/A	N/A
2012/0216122	12/2011	Wong et al.	N/A	N/A
2012/0296974	12/2011	Tabe	N/A	N/A
2013/0073970	12/2012	Piantino et al.	N/A	N/A
2014/0236953	12/2013	Rapaport et al.	N/A	N/A
2014/0298201	12/2013	Tsui et al.	N/A	N/A
2015/0104003	12/2014	Holman et al.	N/A	N/A
2015/0382147	12/2014	Clark et al.	N/A	N/A
2016/0085388	12/2015	Fang et al.	N/A	N/A
2016/0283085	12/2015	Beausoleil et al.	N/A	N/A
2016/0366088	12/2015	Mahmoud et al.	N/A	N/A
2018/0183748	12/2017	Zhang et al.	N/A	N/A

OTHER PUBLICATIONS

Chen et al., People Opinion Topic Model: Opinion based User Clustering in Social Networks, 7 pages (Year: 2017). cited by applicant

Deng et al., The Prediction of User Topic Interest Based on Tags and Interaction of Users, 7 pages (Year: 2016). cited by applicant

How to Use Linux Style Virtual Workspaces in Windows 10, lifewire.com, updated Nov. 7, 2018. cited by applicant

How to use Linux's virtual desktops and workspaces, PCWorld, Chris Hoffman, Mar. 9, 2015. cited by applicant

Kim et al., TopicSifter: Interactive Search Space Reduction through Targeted Topic Modeling, 11 pages (2019). cited by applicant

Leopard Sneak Peak, Internet Archive, on the Wayback Machine, <http://www.apple.com/macosx/leopard/features/spaces.html>, Jul. 10, 2007. cited by applicant

Multiple desktop support in Windows, Microsoft Developer, Jul. 5, 2006. cited by applicant

Road to Mac Os X Leopard: Spaces, Prince McLean, Appleinsider.com, Oct. 11, 2007. cited by applicant

Rooms: the use of multiple virtual workspaces to reduce space contention in a window-based graphical user interface, Henderson, D. A.; Card, S. K. ACM Transactions on Graphics. Jul. 1986; 5 (3): 211-243. cited by applicant

Spaces: A look at Apple's take on virtual desktops Macworld on the Wayback Machine, <http://web.archive.org>, Oct. 22, 2007. cited by applicant

Spaces: Apple's take on virtual desktops in Leopard, Computerworld, Ryan Fass, Nov. 22, 2006. cited by applicant

International Search Report, International Application No. PCT/US 19/30817, Oct. 2, 2019. cited by applicant

PCT/US/19/30817: Written Opinion of the International Searching Authority, Oct. 2, 2019. cited by applicant

Primary Examiner: Dao; Thuy

Attorney, Agent or Firm: Appleton Luff

Background/Summary

RELATED APPLICATIONS (1) This application is a continuation of U.S. patent application Ser. No. 18/201,141, filed on May 23, 2023, which application is a continuation of U.S. patent application Ser. No. 17/404,583, filed on Aug. 17, 2021, which application is a continuation of U.S. patent application Ser. No. 16/807,041 filed on Mar. 2, 2020 and issued as U.S. Pat. No. 11,137,877, which application is a continuation of U.S. patent application Ser. No. 16/213,643 filed on Dec. 7, 2018 and issued as U.S. Pat. No. 10,606,446, which application claims priority to provisional patent application 62/666,702 filed on May 4, 2018 and provisional patent application 62/768,909 filed on Nov. 17, 2018.

FIELD OF THE DISCLOSURE

(1) This disclosure relates generally to computerized information systems and more particularly to facilitating usage of such systems.

BACKGROUND

(2) Users are increasingly using computer systems for a greater number of tasks. It is not uncommon for a user to have open on their computer at one time several applications when working on a single project. For example, the user may be using (i) a browser to perform World Wide Web (WWW) searches and access web-based applications; (ii) a word processor to generate documents comprising text, graphs, images and video; (iii) a spreadsheet to manipulate data; (iv) an email system to exchange email messages with others; and (v) a Short-Message-System (SMS) application to exchange SMS messages with others. In addition to the above, many users are required to work on multiple projects. When working on a second project, some users prefer to close or hide any document windows and applications associated with the first project to avoid confusion and unwanted data exchange with the second project. While this approach maintains separation between projects it requires discipline and time and may not be practical for many users who must switch quickly between projects during a workday. Other users may leave open the document windows and applications associated with the first project. This is likely the more common scenario for many users and results in clutter, which can lead to confusion, additional work and possible intermingling of information between projects. A user may have open a web browser with tabs or windows containing search results and applications for multiple projects, a word processor with documents for multiple projects, an email program with emails for multiple projects, etc.

(3) A partial solution to the increasing amount of information consumed by computer users, as described above, has been to use larger computer monitors to permit a larger amount of information to be displayed at one time. Another related solution has been to employ multiple monitors.

(4) Other solutions, include virtual monitors, sometimes referred to as workspaces, such as the Spaces feature of macOS® by Apple Inc or the Virtual Desktops feature of Windows® by Microsoft Corporation, which derive from a 1986 paper from Xerox Palo Alto Research Center, Intelligent Systems Laboratory (Henderson, D. A.; Card, S. K. Rooms: the use of multiple virtual workspaces to reduce space contention in a window-based graphical user interface ACM Transactions on Graphics. 1986 July; 5 (3): 211-243). These solutions attempt to achieve with virtual monitor software the increased screen space achieved by larger or multiple monitors, by permitting the user to move easily between what appear to be different monitors showing different sets of windows within the same user login session. For example, a user may create and use a workspace for office work, enabling a work-related application (such as a word processor or spreadsheet window) to occupy the full monitor, and then may switch to a different workspace created for browsing the Internet or exchanging email messages.

(5) While the aforementioned hardware and software-based solutions facilitate increased consumption of information and computing resources, there remains a need for improved computer systems that support and facilitate the increased needs of computer users for better control over and isolation between their work on multiple projects.

SUMMARY

(6) The embodiments disclosed herein simplify usage of computer systems by providing one or more topics to a user. Generally speaking, to summarize, a topic, which is specifically defined below, may take the form of a work environment that is a user interface comprising only the window(s), file(s) and application related data that are associated with a current topic. So, for a particular current topic selected by the user, the user sees only the application windows, and in certain embodiments, desktop icons, associated with the current topic. In addition, the application related data associated with the topic, such as browser history, application settings, and data managed implicitly by the applications (as opposed to managed explicitly by the user), such as email, or pictures, is also associated with the topic and made available while the topic is selected. Moreover, in certain embodiments, searches for data from within a topic may provide only data associated with that topic. The embodiments disclosed herein allow the user to create and switch between multiple topics providing isolation that is in many cases better suited to users' needs than

the isolation provided by conventional workspaces. In other embodiments, topics span multiple devices so that a topic selected and used on one device, such as a laptop computer, may also be seen and used on another device such as a mobile phone. To aid in the use of multiple topics, the embodiments disclosed herein include features to facilitate working with data from more than one topic at once and for sharing selectively the preferences appropriate to different topics.

(7) Additional aspects related to the invention will be set forth in part in the description that follows, and in part will be apparent to those skilled in the art from the description or may be learned by practice of the invention. Aspects of the invention may be realized and attained by means of the elements and combinations of various elements and aspects particularly pointed out in the following detailed description and the appended claims.

(8) It is to be understood that both the foregoing and the following descriptions are exemplary and explanatory only and are not intended to limit the claimed invention or application thereof in any manner whatsoever.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The accompanying drawings, which are incorporated in and constitute a part of this specification exemplify the embodiments of the present invention and, together with the description, serve to explain and illustrate principles of the inventive techniques. Elements designated with reference numbers ending in a suffix such as .1, .2, .3 are referred to collectively by employing the main reference number without the suffix. For example, **100** refers to topics **100.1**, **100.2**, **100.3** generally and collectively.

(2) FIG. 1A provides high level overview to explain the operation of a computer system employing topics.

(3) FIG. 1B is a chart showing relationships between the terms introduced in connection with FIG. 1A and described further herein.

(4) FIGS. 2, 3, 4 and 6, are screenshots illustrating usage of an embodiment of a computer system implementing topics.

(5) FIG. 5 is a flow diagram illustrating creation of a new topic.

(6) FIGS. 7A, 7B, 7C, 7D and 7E are additional screenshots illustrating usage of an embodiment of a system implementing topics.

(7) FIGS. 8A, 8B, 8C, 8D, and 8E illustrate preference inheritance.

(8) FIGS. 9A, 9B, 9C and 9D illustrate topic inclusion.

(9) FIG. 10 illustrates topics in connection with a web browser.

(10) FIG. 11 illustrates an example of operation of topics across two separate computer systems.

(11) FIGS. 12A and 12B provide a user-interface-level overview of topic inclusion.

(12) FIG. 13 provides a user-interface-level overview of nested topic folders.

(13) FIGS. 14A and 14B provide a user-interface-level overview of topic inclusion with email and the effect of private topic designation on topic inclusion.

(14) FIGS. 15A, 15B and 15C provide a user-interface-level overview of topic inclusion scope control in connection with email.

(15) FIG. 16 is a flow diagram illustrating an overview of operation of an embodiment of a computer system implementing topics.

(16) FIG. 17 is a block diagram of computer hardware that may be employed in certain embodiments of computer systems described herein.

DETAILED DESCRIPTION

(17) In the following detailed description, reference will be made to the accompanying drawing(s), in which identical functional elements are designated with like numerals. The aforementioned

accompanying drawings show by way of illustration, and not by way of limitation, specific embodiments and implementations consistent with principles of the present invention. These implementations are described in sufficient detail to enable those skilled in the art to practice the invention and it is to be understood that other implementations may be utilized and that structural changes and/or substitutions of various elements may be made without departing from the scope and spirit of present invention. The following detailed description is, therefore, not to be construed in a limited sense.

(18) Disclosed herein are various embodiments of a computer system that provides beyond a default, system-generated home topic, additional user-generated topics. Applications, files and application related data are stored in a data storage associated with the computer system. In certain embodiments, a processor is configured to execute instructions that when executed cause the processor to provide to the user, who is logged in, and thereby identified to the system, a home topic that corresponds to a first user account. The home topic provides a user interface while the user is logged into the first user account. Certain computer systems provide for explicit user account(s), where each user account provides to a user a home topic comprising certain capabilities. Systems that do not provide explicit user accounts provide an implicit single user account for any user. The term “user account” as used herein refers to the aforementioned explicit and implicit user accounts. In some embodiments a system requires a user to take authentication steps before the system will allow the user to access the system.

(19) At all times one of the user's topics is the current topic. The system may operate to designate the home topic by default as a current topic provided to the user. The system responds to user selection of a first topic other than the home topic, by designating the first topic as the current topic provided to the user. The system also generates for persistent storage in the data storage, a first topic data structure associated with the first topic. The system stores with the first topic data structure, troves containing trove data relating to application windows, files and application related data used by the user while the first topic is designated as the current topic. As will be appreciated by those skilled in the art in view of the present disclosure, an application window is an instance of a window generated by an application. The system provides to the user within the isolated first topic, as the user interface, only application windows, files and application related data used by the user while the first topic is designated as the current topic. The system responds to subsequent user selection of the first topic by designating the first topic as the current topic provided to the user and restoring the first topic by retrieving one or more portions of the first topic data structure from the data storage. The system also provides to the user, in response to one or more user inputs, the isolated first topic as the user interface in which only application windows, files and application related data used by the application windows while the first topic is designated as the current topic, are displayed to the user. In certain embodiments, the user may via various interfaces, which may be partially or fully automated, designate application windows, files and application related data to be associated with a particular topic. In certain embodiments, a topic can comprise multiple workspaces, and all workspaces within a particular topic have a shared set of desktop icons in the background, and by default, share the same background graphic.

(20) For simplicity of explanation, the following description provides an explanation of various embodiments in the context of a single example operating system, specifically the macOS® operating system available from Apple Inc. Those skilled in the art will appreciate that the disclosed embodiments may be implemented within the context of other operating systems such as the Windows® operating system available from Microsoft Corp., Chrome OS™ available from Google LLC, or UNIX/XWindow-derivative operating systems such as Linux®. The disclosed embodiments may also be implemented in the context of operating systems directed specifically to mobile devices such as the iOS® operating system from Apple Inc. or the Android® operating system from Google LLC, among others.

(21) The terms set forth below, as used in capitalized or uncapitalized forms, should be interpreted

to have the following meanings:

- (22) Topic—a work environment that includes a user interface comprising one or more workspaces, relationships to other topics in a topic tree (described below), and associated storage for troves. A topic may be open or closed. A topic contains one current workspace and may contain other workspaces. An example of a topic may be seen at reference number **100** in the drawings.
- (23) Workspace—an object representing the collection of application (or application program, or app) windows and system windows and background that are displayed when the workspace is active on an output medium. When an app renders a graphical command for the user, the target of the command is a window in a workspace. A workspace may be open or closed. If a workspace is open it may be visible on a physical monitor, it may be visible in a window of a virtual display app, or it may be invisible. If a workspace is closed its contents are not visible to the user. Data used in managing a workspace, its windows, and other images such as the desktop and icons on the desktop, are stored in a trove. When a workspace is visible, the workspace and its topic are open. An example of a workspace may be seen at reference number **104** in the drawings.
- (24) Output medium—a physical display monitor (one or more), or one or more virtual emulation(s) of a display monitor. An example of a virtual emulation of a display monitor is a window provided by a virtual machine desktop application such as VMware Desktop or a remote desktop screen sharing application compatible with Virtual Network Computing (VNC), an industry standard for controlling computers remotely on a network using TCP/IP.
- (25) Full-workspace mode—a state of an application window in which the window covers an entire workspace. Another common term of art for full-workspace mode is full-screen mode.
- (26) Trove—a storage container used by an app or by the system for data that the app or the system stores implicitly for use while the trove's owning topic is the current topic, as for example data and metadata for workspaces, window positions, user preferences, browser bookmarks or history, notes, photos, and emails. Trove data is distinguished from document data that is placed somewhere explicitly by a user via a user interface (UI) save dialog. An example of a trove may be seen at reference number **102** in the drawings, with a special case being seen at **109**.
- (27) Trove data—data that is stored in a trove.
- (28) Trove storage—a collection of troves owned by a topic. Trove storage may be in a folder contained by a topic folder or may be stored somewhere else. An example of trove storage may be seen at reference number **103** in the drawings.
- (29) Trove window—a window whose primary purpose is to display trove data.
- (30) Document window—a window that displays data from a document file.
- (31) Topic folder—a folder whose subsumed hierarchy of files and folders can be used to store data pertaining to a topic, such as files and troves. Example: In an embodiment employing macOS®, a topic folder would contain subfolders such as the Library folder, which if modified in accordance with embodiments disclosed herein would contain troves.
- (32) Home folder—a folder that is designated as the root of a folder hierarchy to be used for a user login session. Typically, a home folder is the topic folder owned by a home topic.
- (33) Home topic—the topic at the root of a topic tree. In some embodiments, a home topic is associated with a home folder.
- (34) Nonhome topic—a topic that is not the home topic.
- (35) Topic tree—a hierarchy of topics. Starting from the home topic, which is the root of a topic tree, each topic is a parent topic to zero or more subtopics, also referred to as child topics. Each nonhome topic has a parent topic, of which the nonhome topic is a subtopic. Following normal terminology for hierarchies, all ancestors of a topic are reached recursively via parent topic lineal relationships, and all descendants of a topic are reached recursively via subtopic lineal relationships. An example of a topic tree may be seen at reference number **106** in the drawings. An embodiment may provide a more general structure than a tree, for example a directed graph, where the term subtopic refers to a topic in a subordinate relationship.

(36) Desktop folder—a folder contained within the topic folder hierarchy whose contents are displayed in the background layer of a workspace.

(37) Current topic—a topic selected by a user, the current workspace of which is displayed on an output medium. At all times one of the user's topics is the current topic for the output medium. When a first topic is the current topic, we sometimes say that the user “is in” the first topic.

(38) Topics panel—a graphical object that shows representations, such as thumbnails or names, of topics. An example of a topics panel may be seen at reference number **602** in the drawings. In embodiments disclosed herein, a topics panel **602** allows the user to open topics, to close topics, to select a topic to be the current topic, to create workspaces for a topic, and to select the current workspace for a topic.

(39) FIG. **1A** provides a high-level overview to explain the operation of a computer system **10.1** employing topics as further disclosed herein. Hardware and software portions of the computer system **10.1**, and methods performed by the computer system **10.1**, are described in further detail herein, and the computer system **10.1** may be configured, via hardware and software to perform the functions and to implement the features described herein to improve operation of the computer system **10.1** by facilitating user interaction with and operation of the computer system **10.1**. Computer system **10.1** includes a processor, storage, output media and associated hardware and software, which are explained in further detail in connection with FIG. **17**.

(40) In FIG. **1A** a plurality of topics **100** are seen, with each topic **100** having a corresponding set of workspaces **104**. Topic **100.1** labeled ‘TpH’ is a home topic, i.e. it corresponds to a top-level folder. In the context of the macOS® environment, the home topic **100.1** may correspond to the folder in macOS® typically known as the ‘Home’ folder. In such an embodiment, topic **100.1** is associated with the folder labeled Home. The topic hierarchy relationship is seen at **106**, which also illustrates the relationship of topic folders associated with the topics. The Home topic has associated with it subtopics A and B, which have a subordinate relationship to the Home topic. Topics C and D are subtopics of topic A. Topics Home, A and C are represented at right as TpH (**100.1**), TpA (**100.2**) and TpC (**100.3**). Topics associated with topics B and D are not shown in FIG. **1A**, for simplicity of illustration. Each topic **100** is associated with one or more workspaces **104**. In certain embodiments, the folders and the workspaces **104** may both take a standard form such as provided by macOS® by way of its folders and Spaces® features.

(41) The workspaces **104**, as implemented in macOS®, such as in Apple's 10.14 macOS® operating system, and known there as ‘Spaces’, provide a form of a virtual desktop in which multiple workspaces may be created by a user **105** with each workspace typically containing one or more windows in addition to a desktop background (not shown). For example, user **105** may use one workspace for a word processing program that consumes the entire workspace, the user may use another workspace for a spreadsheet window and a Finder window with each application consuming approximately half of the workspace, and the user may assign a third workspace to show the user's desktop not obscured by any windows. Workspace **104.2** is an example of an application in full-workspace mode. The Spaces® feature permits easier organization of a user's workflow. Application windows may be parceled out into workspaces instead of being crammed into a single workspace where they are layered on top of one another and continually minimized or obscured and then called back into action.

(42) In some embodiments, each topic **100** has associated with it a set of standard folders (Desktop, Library, etc.) (not shown). Each workspace **104** is owned by either the home folder or with some other topic folder. In FIG. **1A**, the arrows show two workspaces WS1 (**104.1**) and WS4 (**104.2**) associated with the home topic. Each workspace **104** has associated with it one or more windows (W). For example, workspace WS1 (**104.1**) is configured to display two windows, W1 and W2 when selected by the user **105**. Workspace WS4 (**104.2**) is configured to display a single window W3 in the full-workspace mode. Workspace WS2 (**104.3**) is configured to display two windows, W4 and W5. Workspace WS3 (**104.4**) is configured to display a single window W6 in a portion of

the workspace **104.4**, and workspace **WS5 (104.5)** is similarly configured to display a single window **W7** in a portion of the workspace **104.5**. In a typical configuration, a workspace **104** will consume an entire output medium used by the user **105**. In other configurations, the computer system **10.1** may employ multiple output media and a workspace **104** may consume all of the output media or a subset of the output media, as designated by the user **105**. In certain embodiments, the user may arrange computer system **10.1** to cause a workspace **104** to consume a portion of an output medium.

(43) In general, the user **105** is identified to the computer system **10.1**, such as by logging into an account provided by the computer system **10.1**. This permits the computer system **10.1** to retrieve topics **100** from persistent storage associated with user **105** to provide the user **105** with topics and associated workspaces and windows from one or more prior interactions by the user **105** with the computer system **10.1**. The computer system **10.1** may support multiple users by providing an account to each user and in such an event each user **105** upon logging in will be provided with the topics and associated workspaces and windows from a prior interaction by that user with the system. In certain embodiments, the computer system **10.1** may not support login, or more than one account, in which case usage of the computer system **10.1** may be assumed to be by a single user, or by multiple users that are effectively treated by the computer system **10.1** as a single user.

(44) Each window is managed by and is under control of a particular application. As shown in FIG. **1A**, application **A1** manages window **W3**, application **A2** manages window **W2**, application **A3** manages windows **W1**, **W4** and **W6**. Application **A4** manages windows **W5** and **W7**.

(45) As generally indicated in FIG. **1A**, the configuration and usage of the workspaces and applications within a workspace are managed by the user **105**. In a topic **100** in which the user **105** has designated more than one workspace, such as **TpH (100.1)** and **TpC (100.3)** user **105** may switch between the multiple workspaces, as indicated by arrows **108.1** and **108.3**. For example, while **TpH** is selected or designated as the current topic, the user **105** may switch between **WS1** (to use windows **W1** and **W2**, managed by applications **A3** and **A2**, respectively), and **WS4** (to use window **W3**, managed by application **A1**). Similarly, the user **105**, while **TpC** is selected as the current topic, may switch between **WS3** (to use window **W6**, managed by application **A3**) and **WS5** (to use window **W7**, managed by application **A4**). For simplicity of illustration, FIG. **1A** shows a single workspace **104** or two workspaces **104** generated for each topic, but the computer system **10.1** may be configured to permit more than two workspaces **104** per topic **100**.

(46) If two or more output media are simultaneously available to the user **105**, the system can allow the user **105** to choose to simultaneously display on different output media two or more workspaces **104** from the same or from different topics **100**, or to allow the user **105** to choose to display any workspace **104** on two or more output media, or a combination of the above configurations.

(47) Each topic has associated with it a trove storage **103**. A trove storage **103**, which may be seen at **TrH.1**, **TrA.1** and **TrC.1**, contains a plurality of troves **102** and/or **109**. To simplify illustration, additional troves are shown by the shaded oval-shaped elements (denoted as **102** and **109** in the legend at the lower left of FIG. **1A**) in the trove storage **103** in FIG. **1A**. An example of a trove **102** is a trove that contains trove data for window metadata **109**. Trove windows **W1**, **W4** and **W6** retrieve data from and store data to troves **TrH.1**, **TrA.1** and **TrC.1** respectively, as indicated by bidirectional solid arrows. The windows **W2**, **W3**, **W5**, and **W7** are ordinary windows, which can be document windows or can serve some other purpose. Document windows retrieve data from and store data to a document file, such as used for word processing documents, spreadsheets and presentations, where the documents are typically stored within a conventional file system hierarchy. All windows employ, for their window metadata, data stored in trove storage **103** as indicated by bidirectional dotted arrows extending into trove storage **103.1**, **103.2** and **103.3** and pointing to trove data for window metadata **109**.

(48) A topic **100** can exist anywhere in a topic tree **106**. As seen at **106**, the Home topic includes topic **A (TpA) 100.2** and topic **B** (not shown at right) as subtopics. Topic **B** has no subtopics, and

topic A has two subtopics, C and D. Here, the term parent topic refers to a topic **100**'s parent in the tree, which can be the Home topic or a nonhome topic. The Home topic (TpH) **100.1** is the parent topic of topics A (TpA) **100.2** and B (not shown at right). Topic A is the parent topic of topics C (TpC) **100.3** and topic D (not shown at right).

(49) There can be a group of workspaces **104** associated with any topic **100**, not just the Home topic, as shown by the containment of workspace WS2 (**104.3**) within the box for TpA, and workspaces WS4 (**104.4**) and WS5 (**104.5**) within the box for TpC. Arrows **107.1** and **107.2**, represent that topics A and C display the same relationship to each other and to the home topic as the relationships seen in the topic tree **106**, which also represents the relationship of topic folders corresponding to those topics in the folder hierarchy maintained by the computer system **10.1**. In certain embodiments, all workspaces **104** in a topic may share the same set of desktop icons **204** (shown in FIG. 2). Workspaces **104** in different topics would not necessarily have the same desktop icons **204**.

(50) Preferably, each topic **100** is represented by a data structure that is persistently stored and that has associated with it a topic folder. Each topic folder has associated therewith containers for document data and trove data (such as TrH.1, TrA.1, TrC.1 in FIG. 1A) and one or more workspaces **104**. In certain embodiments, the data associated with a topic folder may include data that has been explicitly designated by the user to be associated with the topic folder, or data that is automatically assigned to the topic by virtue of the topic being the current topic. The trove storage **103** associated with a topic folder will comprise storage that is managed by an app or the computer system **10.1** that is used in some way while the topic associated with topic folder is the current topic. In certain embodiments, trove data associated with a topic may include data that has been explicitly designated by an app in use by the user to be associated with the current topic, or that is implicitly designated by system software employed by computer system **10.1** to be associated with the current topic. By way of example, document data includes documents such as word processing documents, spreadsheet documents, and presentation documents, which a user typically uses from within a certain current topic **100** but can use from within any other topic. By contrast, trove data, which is associated exclusively with a certain topic, includes meta-data associated with any applications used within the current topic, such as preference data, and also files or objects that are managed by applications and presented to the user while the topic is the current topic, such as for example, photographs that are managed by a photo display/editing application, and email messages that are managed by an email application. An example of trove data stored by the system software is window position trove data stored by the system window manager.

(51) Documents may be stored in a conventional file hierarchy. A user **105** can open any document stored in any folder, regardless of which topic is current at the time for the user **105**. If the user **105** opens a document, the metadata for the window in which the document is displayed is stored into a trove associated with the current topic, because window metadata is trove data, which is topic-specific.

(52) In certain embodiments, a feature referred to herein as topic inclusion is employed so that for example, when a user uses a picture management application, for example in the Home topic, the user will see all of the photos from the Photo Libraries of all descendant topics of the Home topic, merged in with the photos from the Home topic Photos Library. When the current topic is a subtopic of the Home topic and the user opens the Photos app, the current topic is at a deeper level of the topic tree, so the user will see all the photos from the subtopic Photos library but will not see any photos from the Home topic Photos library or Photos libraries of any of the Home topic's other subtopics. As usual, thanks to topic inclusion, the user will see all photos from all topics that are nested under the current topic, which in this case is a subtopic of the Home topic.

(53) Through topic inclusion, a trove window such as W1 in FIG. 1A shows data belonging to the current topic and to all of its subtopics, recursively. In the example shown in FIG. 1A: TrH.1 is a trove in Home topic (TpH **100.1**), containing photos, for example. TrA.1 is a trove in topic A (TpA

100.2), which is topic-included by TrH.1. TrC.1 is a trove in topic C (TpC **100.3**), which is topic-included by TrA.1.

There may be multiple subtopics within a topic. For example, a topic TrD.2 (not shown) may also be a trove in topic D, which is topic-included by TrA.1.

(54) Reviewing the relationship among the elements shown in FIG. 1A: WS1 and WS4 are workspaces **104** of Home topic (TpH **100.1**). WS2 is a workspace **104** of topic A (TpA **100.2**). WS3 and WS5 are workspaces **104** of topic C (TpC **100.3**). W1, a trove window in WS1, is associated with TrH.1 and is open in application A3. W2 in WS1 is associated with WS1 and is open in application A2. W3 in WS4 is associated with a document and is open in application A1, in full-workspace mode. W4, a trove window in WS2, is associated with TrA.1 and is open in application A3. W5 in WS2 is associated with a document and is open in application A4. W6, a trove window in WS3, is associated with TrC.1 and is open in application A3. W7 in WS5 is associated with a document and is open in application A4. TrH.1, TrA.1, and TrC.1 are all in use by application A3, which is an app that allows user **105** to view and manipulate the kind of trove data stored in these troves. In certain embodiments, if the user moves W1 to WS3 in topic C, W1 will automatically be associated with topic C instead of topic H and the contents of the trove window W1 will automatically change to show to the user **105** the contents of TrC.1, the trove containing the type of trove data that W1 displays. In certain embodiments, the system allows the user to designate that a window should be associated with a topic other than the current topic, and the application will display trove data from the application's trove in the other topic. Shaded oval-shaped elements representing window metadata **109** illustrate that every window has a trove for its associated metadata, including data for window position and size.

(55) The relationship among the terms employed in FIG. 1A and elsewhere herein may be seen in FIG. 1B. In FIG. 1B the term “own” refers to an exclusive relationship where the owned entity has that relationship only with the owning entity. In other words, if A owns B, then B has no other owner with respect to the relationship. As shown in FIG. 1B, a user account has a relationship with a home folder where the user account “owns” the home folder. So, no other user account owns that home folder. The user account also “owns” the home topic. So, no other user account owns that home topic. The home folder has an “is a” relationship with a topic folder which means that the home folder functions as a topic folder. A topic folder “owns” a desktop folder. A topic may “own” one or more workspace(s). A topic also “owns” trove storage, which in turn “owns” one or more trove(s). Trove data is “stored in” a trove. A workspace “owns one or more” trove window(s). A workspace also “renders drawing commands to” an output medium. A trove window “sends drawing commands to” a workspace. An app “owns” a trove window, and “owns” trove data, which is “displayed in” a trove window. As further seen in FIG. 1B, a current topic is “one of” a home topic or a nonhome topic. A home topic or nonhome topic can be “the parent of” a nonhome topic and “owns zero or more” nonhome topics as subtopics. A nonhome topic “has as parent” and “is a subtopic of” a nonhome topic or a home topic.

(56) FIGS. 2, 3, 4, 6, 7A, 7B, 7C, 7D, and 7E are screenshots illustrating, within the context of the macOS® operating system user interface, usage of an embodiment of a system implementing topics **100**. FIG. 2 shows a desktop **202** with some desktop icons **204**. The user has the finder application as provided by the macOS® as the active application, as seen at **206**, with the “Documents” folder **208** opened in a Finder window **210**, which is also more specifically the Documents folder window **208**. In the Documents folder window **208**, there can be seen a folder **212** for a company called CoDesign. In that folder **212**, there are multiple folders for the company's clients (Smith **216**, Thomas **218**) and a BlueSky folder **214** for a special project. Placing cursor **215** with, for example, a mouse or trackpad, over the BlueSky folder and invoking a Finder contextual menu **302** for the BlueSky folder **214** (such as by right-clicking on the BlueSky folder **214**) causes display of the image shown in FIG. 3 where the result is that a Finder contextual menu **302** pops up, and it has a menu item for Open As Topic **304**, to permit user **105** to create a new topic from,

and that is associated with, an existing folder. Movement of the cursor **215** to and Clicking on the Open As Topic **304** results in the image shown in FIG. **4**. The result is that the entire macOS® screen **110** is now dedicated to the new BlueSky topic and an alias file referencing the BlueSky topic folder **214** is shown in the upper right at **402**. In some embodiments, a name or icon for the current topic could be displayed on a menu bar, on a window title bar or status bar, in a front most graphics layer, or as part of a desktop background.

(57) Because this was the first time the Open As Topic was clicked on the BlueSky folder **214**, the computer system **10.1** responded by performing the actions shown in the flow diagram of FIG. **5** to create a topic and associate it with an existing folder as the topic's topic folder. The flow diagram of FIG. **5** is for illustrative purposes and the steps shown do not need to be performed in the sequence shown. As will be appreciated by those skilled in the art in view of the present disclosure, the ordering of the steps in FIG. **5** may be changed and certain steps may be performed concurrently. At **501**, the system **10.1** allocates trove storage **103.1** and associates it with topic **100.1**. At **502**, the system **10.1** designates a folder as the topic folder associated with topic **100.1**. At **503**, a first workspace **104.1** is created, the workspace **104.1** is associated with the topic **100.1**, and the workspace **104.1** is designated as the current workspace of topic **100.1**. Typically, the new workspace **104.1** will take over the output medium. Preferably the computer system **10.1** changes a visual aspect of the BlueSky folder **214** when it becomes a topic folder associated with a topic **100.4** to indicate to the user **105** that the folder is a topic folder. A Desktop folder is created at **504** and associated with the topic **100.1**. An alias file referencing the topic folder is created at **505** and placed in the Desktop folder. The topic **100.1** is then designated at **506** as the current topic.

(58) Optionally, in certain embodiments, moving the cursor **215** briefly to the upper left corner of the screen exposes the topics panel **602**, resulting in the image shown in FIG. **6**. As seen, the result is that the topics panel **602** appears at the upper left of the screen. The topics panel **602** shows thumbnails of open topics, labeled with their names, Home **604** and the BlueSky **606**. Preferably the current topic is highlighted in some manner, such as by providing a border as seen at **608** to provide a visual indication to the user. In certain embodiments, topic names appear while the user has moved the cursor over the topics panel **602**. Clicking on a topic thumbnail switches to that topic. While the user has moved the cursor over a topic thumbnail, a close button appears, which the user can use to close the topic and remove it from the topics panel **602** until the user reopens the topic later. In certain embodiments a topics panel may cover a large portion, possibly the entire output medium, as for example the “home screen” on a touch screen computer running Apple's iOS® operating system, and topic icons or thumbnails can be arranged ad hoc or in tree structures or other arrangements. In other arrangements, a panel may contain topic icons intermingled with app icons, perhaps as a default home screen, such as on a mobile device.

(59) For every Home folder, a conventional embodiment of macOS® provides a set of standard Folders: Desktop, Library, Pictures, Downloads, Documents, and so on. The Library folder, which is hidden by default in a conventional embodiment of macOS®, in embodiments disclosed herein contains trove storage for trove data such as preferences and other user state, such as the size and position of windows, bookmarks, etc. Another example, in disclosed embodiments of trove data is that of the Mail application available from Apple, which stores emails as trove data under the Library folder. Another example is the Apple Notes app, which stores notes as under the Library folder. Preferably, for every one of the many topics a user **105** can have, the computer system **10.1** creates a topic folder with its own separate set of standard folders, which are used by applications while the user has selected a topic as the current topic.

(60) FIGS. **7A** and **7B** show further details of workspaces **104** as associated with a topic **100**. The user can manually create a new workspace **104**. In certain embodiments, whenever the user puts a window into full-workspace mode the computer system **10.1** will create a new workspace **104** in the current topic **100** for the window. When the window leaves full-workspace mode that workspace **104** in certain embodiments will cease to exist. In FIG. **7A**, the BlueSky topic **606** has

only one workspace **104.6**. In FIG. 7B, the BlueSky topic **606** has three workspaces **104**: the current workspace **104.6** for the topic is at left, displayed as a thumbnail in the topics panel **602** itself, and thumbnails for the two additional, currently-hidden workspaces **104.7** and **104.8** are to the right, displayed in a workspaces subpanel **704**. These additional workspaces **104** are displayed while the user **105** moved the cursor over the thumbnail for the topic that owns them. The workspace **104.8** shows iMovie® in full-workspace mode. As seen by the border **608**, in FIGS. 7A and 7B, the home topic is selected as the current topic.

(61) Continuing with the example, in FIG. 7B, with a single click the user **105** switches to another workspace **104** and to another topic **100**. The user **105** moves the cursor **215** over workspace **104.7**, resulting in the image shown in FIG. 7C. The result is that the user is no longer hovering over the BlueSky topic thumbnail, so the close button **702** in FIG. 7B on the BlueSky topic disappears. Turning to FIG. 7C, the user **105** clicks the workspace **104.7** thumbnail to select the workspace **104.7**. The result, seen in FIG. 7D, is that the lower thumbnail in the topics panel **602** shows that the workspace **104.7** is now the current workspace **104** within the BlueSky topic, and the border **608** around the BlueSky topic thumbnail shows that the user **105** has switched to the BlueSky topic. The workspace **104.7**'s workspaces subpanel **704** and the topic names disappear because the cursor **215** is no longer over the topics panel **602**. In FIG. 7D, movement of the cursor **215** by the user **105** over the BlueSky topic thumbnail results in the image shown in FIG. 7E. The result is that the workspace **104.7**'s workspaces subpanel **704** at right appears again, and the user **105** can see now that the upper workspace **104** in the workspace **104.7**'s workspaces subpanel **704** has been exchanged with the current workspace **104.8** of the BlueSky topic. Also, the close button and the topic names are revealed again for the lower thumbnail because the cursor **215** is hovering over the lower topic thumbnail.

(62) FIGS. 8A, 8B, 8C, 8D, and 8E illustrate that in certain embodiments, application preferences **803** in force for the current topic **100.2** are either stored in a trove of the current topic **100.2** or are inherited by the current topic **100.2** from an ancestor topic or from default preference storage **811**, and that modifications of preference values **804** in preference storage **808** occur in copy-on-write fashion. Preference panel **802** permits the user **105** to view and customize individual application preferences **803**. This preference inheritance system allows the user to specify particular preference values **804** that should be in force for the current topic, while sharing, by default, preference values **804** from ancestor topics. This per-topic preference value feature has profound uses, beyond simple convenience preferences such as font size. For example, the user **105** can set an identity to be used for outgoing communication, such as their email “From” address, or their outgoing phone number; or the user **105** can set an account to be used in accessing shared or external services, such as a database or an external online account. In some embodiments, an external event, such as an incoming phone call, can cause the system to offer to the user **105** the opportunity to switch from a current topic to a topic selected from a set of topics relevant to the external event. The relevance of an external event to a topic might be determined by the applicability of data received in conjunction with the event to certain trove data, for example, topic-specific preferences. The system responds to an external event to generate for display to the user, one or more topics, to permit the user to select a new topic as the current topic. The generation of the one or more topics may be determined as a function of trove data and data pertaining to the external event. An example of this would be matching the called phone number of an incoming call to an outgoing phone number preference value for a topic or topics in a topic subtree. Solid square boxes in preference panel **802** and in the diagram for preference storage **808** illustrate preference values **804**. A solid square box in preference storage **808** illustrates where a preference value **804** is stored; a dashed square box in preference storage **808** illustrates where a preference value **804** could be stored but is not stored. The square boxes are shown with two possible values: with an X for “ON”, or without an X for “OFF”. For example, in FIG. 8A, the system is displaying preference **803.1** “Enable Color”, whose preference value **804.1** is “ON”. Inheritance of preference values within preference storage **808** is

illustrated by vertical dashed arrows between individual possible storage locations for preference values **804**, each of which is stored in default preference storage **811** and may be stored in one or more troves **102**. For example, in FIG. **8A**, topic trove **102.3** of topic **100.3** inherits preferences by default from the trove **102.2** of its parent topic **100.2**, which inherits preferences by default from the trove **102.1** of its parent topic, the Home topic **100.1**, which inherits preferences by default from default preference storage **811**.

In certain embodiments, An application used by a user in a current topic **100.2** (which corresponds to preference panel **802.2**) will attempt to access storage for a particular preference value **804** in the application's trove **102.2** for the topic **100.2**. For a particular preference **803.1**, storage for the preference is found in the trove **102.2** for topic **100.2**, so the application uses that storage for the preference value **804.1**. For a particular preference **803.2**, storage for the preference is not found in the trove **102.2**, so the preference value is inherited, and therefore the application looks to the trove **102.1** for the parent topic **100.1**, where it does find storage for the preference and uses that storage. Preference inheritance spans multiple levels of parent topics, if present. For a particular preference **803.3**, storage for the preference is not found in the trove **102.2** for topic **100.2**, so the preference value is inherited, and therefore the application looks to the trove **102.1** for the parent topic **100.1**; upon finding no storage there and noting that there is no parent topic for Home topic **100.1**, the application uses the default preference storage **811** for the preference value **804.3**. There are no preference values **804** in preference storage **808** in the trove **102.3** for the “C” topic **100.3**, so storage for all preferences used by the topic **100.3** when it is the current topic will be found variously in a parent topic trove **102.2** or in an ancestor topic trove **102.1** or in default preference storage **811**. The preference value **804.1**, which was changed for topic **100.2** and the preference value **804.2**, which was changed for topic **100.1** and the default value for preference value **804.3** are all inherited by default for topic **100.3** and its descendants.

(63) In FIGS. **8A**, **8B**, **8C**, **8D**, and **8E** preference panel **802** permits the user **105** to view and customize individual application preferences **803**, by clicking on controls to change individual preference values **804**. In the example preference panel **802**, the preference values shown are ON/OFF values, but they can be numbers, text, or other value types. For example, in FIG. **8A**, the system is displaying preference **803.1** “Enable Color” as a preference whose preference value **804.1** is “ON”. In FIGS. **8B**, **8C**, **8D**, and **8E**, the system, in response to user input, is indicating, by highlighting **807**, that preferences **803** are individually changeable and that their preference values **804** are subject to inheritance either from an ancestor topic trove **102** or from default preference storage **811**. In FIGS. **8D** and **8E**, the system, in response to user input, is showing a discard button **805.1**, which indicates that preference **803.1** has been changed. In FIGS. **8D** and **8E**, the system, in response to user input, is showing a preview of the inherited preference value **804.1**, to which the changed preference **803.1** will revert if the user discards the change to the preference value **804.1**. In FIGS. **8B** and **8E**, in some embodiments, a mouse over gesture on the preference **803.1** elicits the highlighting **807.1**. In FIG. **8C**, in some embodiments, a mouse over gesture on the preference **803.2** elicits the highlighting **807.2** and the information display **809.2**, which indicates the inherited source of the preference value **804.2**. In FIG. **8D**, in some embodiments, a user input mouse over gesture on the Discard Changes button **806** elicits (a) the highlighting **807**, (b) the display of a discard button **805.1**, and (c) a preview of the inherited preference value **804.1**, to which the changed preference **803.1** will revert if the user discards the change to the preference value **804.1**. In FIG. **8D**, if the user clicks the Discard Changes button **806** then the system reverts all changed preferences in preference panel **802** to their respective inherited preference value **804**. In FIG. **8E**, in some embodiments, a user input mouse over gesture in the rightmost portion of the highlighting **807.1** of preference **803.1** elicits (a) the highlighting **807.1**, (b) the display of a discard button **805.1**, and (c) the preference value **804.1**, to which the changed preference **803.1** will revert if the user discards the change to the preference **803.1**. The relevance of the cursor position for the display of the discard button **805.1** can be most clearly seen by comparing FIG. **8B** with FIG. **8E**.

In FIG. 8E, if the user clicks the discard button **807.1**, then preference **803.1** reverts to the preference value inherited from the parent topic or if none, the default preference storage **811**. It should be noted that the foregoing features relating to responding to user input, displaying preference values **804**, displaying inherited preference values, discarding changed preferences, preference highlighting **807**, information display **809**, and displaying and responding to activation of discard buttons **805** and **806**, work similarly even if the Home topic is the only topic.

(64) FIGS. **9A**, **9B**, **9C** and **9D** illustrate topic inclusion, a feature of the system that allows an application to display its trove data that is associated with a first topic, intermingled with trove data associated with descendant topics of the first topic, where the first topic is typically the current topic. In certain embodiments, a default topic inclusion may be employed such as seen in FIG. **9A**. Turning back to FIG. **1A**, as seen at topic tree **106**, the Home topic has two subtopics, A and B. Topic A has two subtopics, C and D, which are descendent topics of the Home topic. Topics A, C, and D are all descendant topics of the Home topic. Topic B has no subtopics. With the default topic inclusion shown in FIG. **9A**, an application displays, in addition to trove data associated with the first topic, trove data associated with the first topic's descendant topics; the application does not display trove data associated with topics that have any other relationship to the first topic, such as ancestor topics or sibling topics. In FIGS. **9A**, **9B**, **9C** and **9D**, topics are denoted as Home or in upper case letters (A, B, C, D), and trove data associated with these topics are denoted in corresponding lower-case letters (h, a, b, c, d).

(65) As seen at the table in FIG. **9A**, when the current topic is the Home topic, the application displays trove data associated with the Home topic intermingled with trove data associated with the Home topic's descendant topics A, B, C, D (trove data: h a b c d). When the current topic is topic A, the application displays trove data associated with topic A intermingled with trove data associated with topic A's descendant topics C and D (trove data: a c d). The application does not display trove data associated with topic B while the user's current topic is topic A because topic B is not a descendant of topic A. Topics B, C and D have no subtopics and therefore while one of them is the current topic, the application displays only trove data associated with that topic (trove data: b or c or d).

(66) FIGS. **9B** and **9C** illustrate another embodiment of topic inclusion, in the form of topic inclusion scope control, which permits the user to cause the application to depart from the default topic inclusion view, such as seen in FIG. **9A**, to display a view of trove data from topics other than from the current topic and its descendant topics. Such other views typically allow the user to see a view as if the user's current topic were some other selected topic that is an ancestor topic of the current topic. Two modes are shown, an inclusive mode and an exclusive mode. In some embodiments the system provides a Topic bar **1404** and allows the user to select topics via scope buttons **1505**, as seen in FIGS. **15A**, **15B**, and **15C**.

(67) The table in FIG. **9B** illustrates a topic inclusion scope control feature that allows the user to select a topic other than the current topic for the purpose of seeing the trove data that the application would display if the selected topic were the current topic C. FIG. **9B** shows an embodiment in which the user may select the current topic C or an ancestor of topic C. In inclusive mode, the application displays trove data associated with the selected topic and its descendant topics. Each row of the table shows all possible permutations of user selection as underlined text, like Home, or A or C. For example, rows **1**, **2**, and **3** of FIG. **9B** show inclusive mode: At row **1**, the user has selected the Home topic. The application displays trove data associated with the Home topic and its descendant topics, A, B, C, D (trove data: h a b c d). At row **2**, the user has selected topic A. The application displays trove data associated with topic A and its descendant topics, C and D (trove data: a c d). At row **3** the user has chosen topic C. The application displays only the trove data associated with topic C, which has no descendant topics (trove data: c).

Rows **4-11** in FIG. **9B** show exclusive mode, in which the application displays only the trove data for the selected topic(s) and does not display trove data for topics that are not selected.

(68) FIG. 9C shows another example of topic inclusion scope control. The trove data in the table in FIG. 9C illustrates the trove data associated with topic(s) that the user can see when the current topic is topic A. Because the Home topic is the only ancestor of topic A, in inclusive mode (rows 1 and 2), the user 105 is presented with two choices for Topic bar selections: Home or A. In exclusive mode (rows 3-10), the user 105 is also presented with a third option, which permits selection of trove data in subtopics to the current topic and their descendants (of which there are none here), in this case, topics C and D. At rows 1 and 2, the trove data the user sees is the same as in rows 1 and 2 of FIG. 9B. At row 3, the Home, A and subtopics are selected, permitting the user to see trove data associated with topics Home, A, C, D (trove data: h a c d). At row 4, the Home and A topics are selected, without selection of subtopics of A, permitting the user to see only trove data associated with topics Home and A (trove data: h a). At row 5, Home and subtopics of A are selected but topic A is not selected, permitting the user to see trove data associated with topics Home, C and D but not topic A (trove data: h c d). At row 6, only the Home topic is selected, permitting the user to see only trove data associated with the Home topic (trove data: h). At row 7, the A topic and subtopics are selected but the Home topic is not selected, permitting the user to see trove data associated with topics A, C and D but not the Home topic (trove data: a c d). At row 8, only topic A is selected, permitting the user to see only trove data associated with topic A (trove data: a). At row 9 only subtopics are selected, permitting the user to see only trove data associated with subtopics C and D (trove data: c d). At row 10 no topics are selected and hence the user sees no trove data.

As seen, the computer system 10.1, via the inclusive and exclusive modes of selection and the “sub” selection of descendant topics, provides the user flexibility and ease of selection in the trove data that may be seen from the vantage point of a given current topic.

(69) FIG. 9D illustrates the effect of a private topic on the topic inclusion feature. A user may designate a topic as a private topic so that the system will allow the user, for example, to avoid inadvertently disclosing the existence of a first topic A or its contents to a coworker who can see the user's screen but who is not cleared for topic A. An application may display, through topic inclusion, the existence of, or the trove data associated with, a private first topic A or its descendant topics only if the current topic is the first topic A or a descendant of topic A. In the example shown in FIG. 9D, topic A is designated by user 105 as private. In row 1, the current topic is the Home topic, which is neither topic A nor one of its descendants; therefore, the application does not display the existence of or trove data associated with topic A or any of its descendants. The system does display the existence of, and trove data associated, with private topic A when (a) private topic A is the current topic, or (b) any of topic A's descendant topics is the current topic as for example, if the current topic is topic C, and the user uses the topic inclusion scope control feature to widen the topic scope to topic A or to the Home topic.

(70) FIG. 10 illustrates an embodiment of topics in connection with usage of a web browser. In FIG. 10, the user has selected the BlueSky topic, which by way of example, corresponds to topic A of FIG. 1A. The user opens a browser 1002. Because the user has not used the browser 1002 to perform browsing while the BlueSky topic is the current topic, there is no browsing history associated with the BlueSky topic. Browsing by the user while the BlueSky topic is the current topic generates browsing history and metadata 1004 associated with the BlueSky topic. The browsing history includes URLs visited by the user while using the browser 1002 when the BlueSky topic is selected as the current topic. The metadata includes other data associated with the browser 1002 while the BlueSky topic is selected as the current topic, such as the browser windows and tabs that are open, the window sizes and placement, font size selection, etc. The user may then close the BlueSky topic by bringing up the topics panel 602 and closing the BlueSky topic by clicking its close button 702 in the panel. This causes the Home topic to become the current topic, where some further browsing via the browser 1002 may be performed. This causes browsing history and metadata while the Home topic is the current topic to be stored to browsing history

1006 associated with the Home topic. The user may then reopen the BlueSky topic. To reopen the BlueSky topic, the user brings up the topics panel **602** again and clicks the + button. This brings up a menu of topics, and the user selects BlueSky. The current topic is now again the BlueSky topic with everything still exactly as before when the user left the BlueSky topic. The same browser windows are open, with the same tabs and the same forward-and-back history for each tab, and the browser history menu is exactly as the user left it, even though while the user was using the Home topic the user did some browsing there.

(71) Many applications retain information (metadata) pertaining to prior or current documents opened by the application. This information can often be found in the selections available in menus such as “Open Recent” and “Window”. Applications that are compatible with the computer system **10.1** provide only the information associated with the current topic. In some embodiments, information associated with a topic can be shown in callouts for the topics as in the Window menu example. The user selects the BlueSky topic and opens a word processing document and creates a document named “Ideas” on the Desktop, and then closes the document. Later, when the BlueSky topic is the current topic, the user seeks to reopen the Ideas document. This can be accomplished by using the Open Recent submenu selection. The word processor displays the document title as a recently opened document. Moreover, the Open Recent submenu isn't cluttered with other documents has been working on in other topics. There are no other items in the Open Recent menu because the current topic is the topic **100** created for BlueSky, and the state of the Open Recent menu is stored in a trove within the current topic, isolated from troves in other topics **100** and in the user's Home folder. The Window menu for the word processor also shows only the Ideas document, even though other word processor documents are open in the Home topic. The system presents to the user a workspace **104** that makes provides an experience to the user similar to that of working on a computer dedicated to the selected topic.

(72) FIG. **11** illustrates an example of operation of topics across two devices. In FIG. **11**, computer system **10.1** is in communication with a mobile device **10.2**. As seen in FIG. **11**, the computer system **10.1** takes the form of a laptop computer executing instructions to implement the features and functions described herein. It should be understood that the laptop in FIG. **11** is merely illustrative and other computing devices, such as desktop computers and tablets may be used in implementing computer system **10.1**. Computer system **10.2** takes the form of a mobile device for purposes of illustration of the usage of topics across multiple devices, by user **105** who may at different times use computer system **10.1** and computer system **10.2** to work on one or more topics. For example, the user may need to take some photos to incorporate into a document titled “Ideas.” The user ensures that a file sharing capability is enabled on the systems **10.1** and **10.2**. The file sharing capability may take the form of the iCloud Photo Library as provided by Apple Inc. The user **105** brings up a topics panel **602** on the mobile device **10.2** to see the user's list of topics. Two topics are shown, Home and BlueSky. User **105** selects BlueSky as the current topic and takes some photos with the mobile device. The user **105** then opens a photos app on the mobile device that the user uses to manage photographs. The app shows only the photos the user **105** has just taken because the BlueSky topic is new, and these are the first photos the user has taken while the BlueSky topic is the current topic. Later the user **105** uses the computer system **10.1** and selects BlueSky as the current topic. The user **105** opens a photos app on the computer system **10.1**, and sees the photos taken earlier on the computer system **10.2** while the BlueSky topic was chosen as the current topic, because the BlueSky topic is the current topic on the computer system **10.1**. The photos apps on the computer system **10.1** and the computer system **10.2** employ the file sharing facility selected by the user **105** to synchronize the photos among the devices and implement topics compatibility to keep the photos organized by topic.

(73) Complete isolation of topics **100** is not beneficial in every instance as it can require unnecessary duplication of work by the user. For example, many user preferences are likely to be applicable to multiple topics. The user should not need to start from scratch setting their

preferences for every new topic. But customization of certain preferences by topic is desirable. Preferably, existing user preferences in a first topic are inherited by a new second topic child of the first topic. The user can override a preference and even discard the override, so the preference reverts to the inherited preference. In addition, it is sometimes useful to use data in one topic that is associated with another topic. In the disclosed embodiments, for data that is stored in document files, the Finder and the Open File and Save File dialogs (as used in the macOS® environment, or similar functionality in other environments) preferably let the user access files anywhere, no matter what topic they are in. In the disclosed embodiments, for data that is stored in troves, the topic inclusion feature lets the user access trove data in a topic-focused manner, as is explained in further detail in connection with FIGS. **12A** and **12B**. An exception to such open access is explained in connection with FIG. **9D**, where private topics are off limits except from inside the private topic itself or one of its subtopics. In the case of trove data, compatible apps implement the topic inclusion feature to permit display of data outside the current topic.

(74) Complete isolation of topics **100** would restrict the ability of a user **105** to see trove data outside of the current topic **100**. In certain embodiments a topic inclusion feature lets the user **105** see trove data outside the current topic. The user may set the private topic option on a topic **100** so that the topic inclusion will not show the topic or its data unless the current topic is the topic itself or in one of the topic's subtopics. In the following example, none of the topics **100** have their private topic option set. The user goes to the topics panel **602** and switches to the Home topic. The user opens a photos management app, and here sees all of the user's photos, including the ones added while the BlueSky topic is the current topic. If the user had any other topics **100**, the user would also see the other topics' photos, mixed in, perhaps all sorted by date, as usual. There are various ways the user can control topic inclusion, which will be explained in more detail. The user can arrange to see: everything, only photos that are in specified topics **100**, or only photos that are not in specified topics **100**. Also, the user can arrange to see tags showing the topics that photos belong to. One benefit of topic inclusion is that it makes it easy to move items around between topics. In the Photos app, the user can select a BlueSky photo and reassign it from BlueSky to Home, or vice versa. Or the user can reassign a photo from one topic to another or copy it to another topic. Topic inclusion makes it a lot easier to manage the trove content of topics **100** than if topics were isolated islands. Preferably, topic inclusion applies to any trove data where it is appropriate, for example in notes and mail apps, in addition to photos.

(75) FIGS. **12A** and **12B** provide examples of topic inclusion at the platform user-interface-level. As with the photos example of topic inclusion, the topic inclusion feature preferably is available for items in an app's Window menu (in the macOS® system). FIG. **12A** shows an example where the current topic is the Home topic and shows a Window menu for a word processing app. The Window menu shows that the Travel Checklist document, seen at **1202**, is open in the Home topic (which is selected by the user as the current topic), and it shows that the Ideas document, seen at **1204**, is open in the BlueSky topic, seen at **1206**. The user clicks on Ideas **1204** in the Window menu. The result is shown in FIG. **12B** where the user's click has caused the current topic to be automatically switched to the BlueSky topic, with the Window menu of the word processing app showing that only the Ideas document is open, with the BlueSky topic as the current topic. Subsequent actions the user may take in the same app or in other apps would be performed with the BlueSky topic selected as the current topic. This feature permits easy switching between topics. The user does not need to manually switch between topics with a separate input. Instead the computer system **10.1** automatically switches the current topic to the topic of a document window selected by user **105**. In certain embodiments, other menu items that permit opening of files, such as the Open Recent menu, a menu item that shows recently used documents, work similarly. In some embodiments, when the user selects an item from another topic, the system **10** may permit the user **105** to choose whether to switch to the other topic before opening a window to display the item or instead to take some other action, such as remaining in the current topic while opening the

item in a window designated as belonging to the other topic.

(76) FIG. 13 provides a user-interface-level overview of topic folders for nested topics. The topic inclusion feature takes advantage of a topic tree folder structure, anchored by the Home topic. In the embodiment shown in FIG. 13, the folders 212, 214, 216, and 218 each correspond to a topic and serve as the storage location for the associated topic. The BlueSky topic folder 214 is automatically nested inside the Home folder by virtue of being contained within the Home folder tree. In FIG. 13, the user makes the CoDesign 212, Smith 216, and Thomas 218 folders into topic folders. Preferably they turn a different color to reflect the change. As a result, the BlueSky, Smith, and Thomas topics are nested under the CoDesign topic, and the CoDesign topic is nested under the Home topic.

(77) FIG. 14A provides a user-interface-level overview of topic inclusion with email. Email is one of the biggest problem areas in the complexity of modern life. One way that topics help is that in certain embodiments, each topic has its own set of standard mailboxes: Inbox, Sent, Drafts, Trash, and so on. If the user 105 creates a mailbox, then subtopics have their own mailboxes of the same name. Preferably, assigning emails to topics should be as automatic as possible because there is a constant stream of new emails. Assignment of outgoing emails to topics is relatively straightforward. The mail app may automatically assign outgoing emails to the currently selected topic when the emails are created. The timing of incoming emails cannot be controller by the user 105 and assignment to topics is hence more challenging. Certain mail apps have rule systems that may be employed to assign incoming emails to topics in one of three ways: (i) assigned with certainty—for example, an email that's in a chain of replies to an email already assigned to a topic or an email from an address associated with only one topic; (ii) assigned as a suggestion—for example, a phrase was found in the message; (iii) unassigned—there are no matching rules. To help with topic assignment, emails whose topic assignments are only suggestions are preferably highlighted as such, so the user can review them and manually finalize assignments. For example, such highlighting could be a color such as grey. Along the way, the mail app may preferably sometimes suggest new or improved rules based on what the user does.

(78) While the user is manually assigning incoming emails to topics, the user needs to see all of the incoming emails. The topic inclusion feature plays an important role here. As a practical matter, it may take time to transition to a new system of organization. Preferably, a compatible mail app lets the user make the transition at their own pace. Until the user adds rules for assigning topics, the mail app in certain embodiments will not assign any incoming emails to topics.

(79) FIG. 14A shows what an embodiment of a mail viewer window 1401 may look like at each level of a topic tree. Mail apps that are compatible with topics preferably provide a topic column 1402 to indicate the topic assigned to each email message that is displayed. As seen in FIG. 14, the mail app's viewer window 1401 displays only messages relevant to the topic, be it the Home topic or some other topic. In the Mail in Home topic example at mail viewer window 1401.1, we see messages from all topics, including two messages near the bottom that are not assigned to any topic because they belong to the Home folder by default. In the Mail in CoDesign topic example at mail viewer window 1401.2 we see only emails assigned to the CoDesign topic and to topics that it contains (BlueSky, Smith, Thomas). In the Mail in BlueSky topic example at mail viewer window 1401.3 we see only emails assigned to the BlueSky topic. Topic bars 1404.1, 1404.2 and 1404.3 show the current topic.

(80) Turning to FIG. 14B, it can be seen by comparison against FIG. 14A that messages in a private topic are visible to a user only when the user's current topic is the private topic itself or when the current topic is a subtopic of the private topic. In FIG. 14B, for example, the user's BlueSky topic is private. The BlueSky topic's emails are visible when the private BlueSky topic is the current topic, as seen at 1402.3, but they are not visible in either the Home or the CoDesign topic when they are the current topic, as seen at 1402.1 and 1402.2 because those topics are neither the BlueSky topic nor subtopics of the BlueSky topic. In certain embodiments, the computer system 10.1 never hides

a private topic from the user if the private topic is the user's current topic or is an ancestor topic of the user's current topic, and this holds true even if the user uses topic inclusion scope control to widen the topic scope; for example, if the BlueSky topic were marked private it would nevertheless be visible in FIGS. **15B** and **15C** (explained below), where the user is using topic inclusion scope control to widen the topic scope toward ancestors of the private topic while it is the current topic. (81) FIGS. **15A**, **15B**, **15C** provide a user-interface-level overview of scope adjustment of topics in connection with email. The system responds to user input to select a set of topics from which to provide data to an application, whereby the application provides to the user a union of the trove data corresponding to the set of topics. It's useful to be able to have a quick look outside the scope of the current topic without having to switch the current topic to a different topic. For example, the user's current topic may be the BlueSky topic, and he may want to see all recent emails. The Topic bar **1404** permits quick access beyond the current topic. In the mail windows shown in FIGS. **15A**, **15B**, **15C**, just below toolbar **1502**, is Topic bar **1404**, which contains the identifier "Topic:" to the left and provides scope buttons. Turning to FIG. **15A**, the current topic where this mail window is viewed is the BlueSky topic, which is shown selected at the BlueSky topic scope button **1505.3**. A single message is seen in the inbox, and its topic is the BlueSky topic as seen in the Topic column **1402.1**. The user can click on Home or CoDesign in the Topic bar to widen the scope of the topics the user sees. If the user clicks on the topic scope button **1505.2** for the CoDesign topic, which as seen in FIG. **13** is the parent topic of the BlueSky topic, which is the current topic, the result, as seen in FIG. **15B** is that the user has widened the scope of the messages displayed. The window shows all messages in the CoDesign topic plus a topics column **1402.2** calling out the topics of messages from all topics that CoDesign contains, such as the Smith, Thomas and BlueSky topics as would be shown if the user's current topic were the CoDesign topic. Next, the user clicks on the topic scope button **1505.1** for the Home topic in the Topic bar **1404**. Recall from the description accompanying FIG. **13** that Home is the parent topic of the CoDesign topic. The result as shown in FIG. **15C**, where the Home topic scope button **1505.1** is selected. This effect is that the user has further widened the scope of the messages displayed. The window shows all messages, as if the current topic were the Home topic.

(82) Preferably, compatible apps show a Topic bar in any window that displays a collection of items belonging to topics. The items might be photos in a photos app or emails in a mail app viewer window or URLs in a browser history window. The user can sort items by topic and can select items and assign or copy them to the topic of the user's choice. If the user creates a new mail message while in a topic, the new email message will belong to the current topic, no matter what the Topic bar setting is. The Topic bar is just for setting the scope of topics the user can see.

(83) In certain embodiments, the computer system **10** can allow for encrypting private topic data. In such embodiments, a topic folder is either encrypted and not in use or is decrypted and used within a distinct processing environment provided for the private topic. The computer system **10** responds to user input by encrypting data associated with a first topic, such as for example, topic A, to create encrypted first topic data for storage to the data storage. The computer system **10** responds to further user input by decrypting the encrypted first topic data to create a temporary unencrypted data set while the first topic is open. The computer system **10**, while the first topic is open, creates a protected processing environment associated with the first topic, and provides restricted access to the temporary unencrypted data set for use by the protected processing environment associated with the first topic. As will be appreciated by those skilled in the art in view of the present disclosure, the protected processing environment may take the form of a process tree such as employed in derivatives of the Unix operating system or unused, temporary user ID and group ID, or folder storage in a separate volume not reachable by other processes.

(84) Returning to the overall system, it can be seen that a computer system provides at least one isolated workspace as a user interface corresponding to a user-generated topic. Data storage stores application windows, files and application related data. A processor is coupled to the data storage

and is configured to execute instructions that when executed cause the processor to provide a home topic to the user as a default topic corresponding to a first user account. The home topic provides a workspace to the user as a user interface, while the user is logged into the first user account. The home topic is designated by default as a current topic provided to the user. The processor further responds to user selection of a first topic other than the home topic, by, designating the first topic as the current topic provided to the user, associating a first isolated workspace with the first topic, generating for storage in the data storage, a first topic data structure associated with the first topic, associating with the first topic data structure, only application windows, files and application related data used by the user while the first topic is designated as the current topic. This provides to the user within the isolated first workspace, as the user interface, only application windows, files and application related data used by the user while the first topic is designated as the current topic.

(85) An embodiment of the computer system disclosed herein provides a user interface that permits interaction with preferences corresponding to software executed by the computer system. A default preferences data structure comprising a plurality of default user preferences regarding certain of the software executed by the computer system is stored in data storage. Also stored in data storage is a user override preferences data structure comprising a plurality of user override preferences that differ from corresponding default user preferences. A processor is coupled to the data storage and is configured to execute instructions that cause the processor to accept a first user input to accept a user override preference to replace a default preference. The processor stores the user override preference to the user override preferences data structure and responds to user input to reveal the default user preference corresponding to the user override preference. The processor accepts a second user input to discard the user override preference by removing the user override preference from the user override preferences data structure. The processor may further execute instructions that cause the processor to respond to user input to reveal default user preferences that correspond to any user override preferences and accept one or more user inputs to discard any user override preferences by removing the user override preferences from the user override preferences data structure. The instruction that causes the processor to respond to user input to reveal the default user preference corresponding to the user override preference may further highlight the default user preference.

(86) FIG. 16 is a flow diagram illustrating an overview of operation of an embodiment of a computer system implementing topics. Computer system 10 provides to user 105, a user interface that permits interaction with a first topic, generated by the user 105. The topic includes trove data and at least one associated workspace. Troves 102 are stored in data storage which is operatively coupled to a processor, which is configured to execute instructions that cause the processor to execute the operations shown in FIG. 16. The user, which the system associates with a first user account, is provided at 1601 with a home topic, initially selected as a current topic, and which corresponds to the first user account. The home topic associates a first home topic workspace to the user 105 as a user interface. The system 10 responds at 1602 to user selection of the first topic, different from the home topic, by designating the first topic as the current topic provided to the user 105. The system 10 also at 1603 associates a first workspace with the first topic. The system 10 further, at 1604, allocates trove storage for the first topic for applications used by the user 105 while the first topic is selected as the current topic. The system 10 provides to the user 105, at 1605, as the user interface of a workspace, only trove data associated with the current topic.

(87) The embodiments herein can be implemented in the general context of computer-executable instructions, such as those included in program modules, being executed in a computing system on a target real or virtual processor. Generally, program modules include routines, programs, libraries, objects, classes, components, data structures, etc. that perform particular tasks or implement particular abstract data types. The functionality of the program modules may be combined or split between program modules as desired in various embodiments. Computer-executable instructions for program modules may be executed within a local or distributed computing system. The

computer-executable instructions, which may include data, instructions, and configuration parameters, may be provided via an article of manufacture including a computer readable medium, which provides content that represents instructions that can be executed. A computer readable medium may also include a storage or database from which content can be downloaded. A computer readable medium may also include a device or product having content stored thereon at a time of sale or delivery. Thus, delivering a device with stored content, or offering content for download over a communication medium may be understood as providing an article of manufacture with such content described herein.

(88) The terms “computer system” and “computing device” are used interchangeably herein. Unless the context clearly indicates otherwise, neither term implies any limitation on a type of computing system or computing device. In general, a computing system or computing device can be local or distributed and can include any combination of special-purpose hardware and/or general-purpose hardware with software implementing the functionality described herein.

(89) FIG. 17 depicts a generalized example of a suitable general-purpose computing system **10**, such as computer system **10.1** and/or computer system **10.2** in which the described innovations may be implemented in order to improve the processing speed and efficiency with which the computing system **10** operates to perform the functions disclosed herein. With reference to FIG. 17 the computing system **10** includes one or more processing units **1702**, **1704** and memory **1706**, **1708**. The processing units **1702**, **1704** execute computer-executable instructions. A processing unit can be a general-purpose central processing unit (CPU), processor in an application-specific integrated circuit (ASIC) or any other type of processor. The tangible memory **1706**, **1708** may be volatile memory (e.g., registers, cache, RAM), non-volatile memory (e.g., ROM, EEPROM, flash memory, etc.), or some combination of the two, accessible by the processing unit(s). The hardware components in FIG. 17 may be standard hardware components, or alternatively, some embodiments may employ specialized hardware components to further increase the operating efficiency and speed with which the computer system **10.1** operates. The various components of computer system **10** may be rearranged in various embodiments, and some embodiments may not require nor include all of the above components, while other embodiments may include additional components, such as specialized processors and additional memory.

(90) Computing system **10** may have additional features such as for example, storage **1710**, one or more input devices **1714**, one or more output devices **1712**, and one or more communication connections **1716**. An interconnection mechanism (not shown) such as a bus, controller, or network interconnects the components of the computing system **10**. Typically, operating system software (not shown) provides an operating system for other software executing in the computing system **10**, and coordinates activities of the components of the computing system **10**.

(91) The tangible storage **1710** may be removable or non-removable, and includes flash memory, magnetic disks, magnetic tapes or cassettes, CD-ROMs, DVDs, nonvolatile random-access memory, or any other medium that can be used to store information in a non-transitory way and that can be accessed within the computing system **10**. The storage **1710** stores instructions for the software implementing one or more innovations described herein.

(92) The input device(s) **1714** may be a touch input device such as a keyboard, mouse, pen, or trackball, a voice input device, a scanning device, or another device that provides input to the computing system **10**. For video encoding, the input device(s) **1714** may be a camera, video card, TV tuner card, or similar device that accepts video input in analog or digital form, or a CD-ROM or CD-RW that reads video samples into the computing system **10**. The output device(s) **1712** may be a monitor, printer, speaker, CD-writer, or another device that provides output from the computing system **10**.

(93) The communication connection(s) **1716** enable communication over a communication medium to another computing entity (such as between computer system **10.1** and computer system **10.2**). The communication medium conveys information such as computer-executable instructions, audio

or video input or output, or other data in a modulated data signal. A modulated data signal is a signal that has one or more of its characteristics set or changed in such a manner as to encode information in the signal. By way of example, and not limitation, communication media can use an electrical, optical, RF, or other carrier.

(94) It should be understood that functions/operations shown in this disclosure are provided for purposes of explanation of operations of certain embodiments. The implementation of the functions/operations performed by any particular module may be distributed across one or more systems and computer programs and are not necessarily contained within a particular computer program and/or computer system.

(95) In the foregoing specification, the invention has been described with reference to specific embodiments thereof. It will, however, be evident that various modifications and changes may be made thereto without departing from the broader spirit and scope of the invention. The specification and drawings are, accordingly, to be regarded in an illustrative rather than a restrictive sense.

Claims

1. A computer system with an operating system that provides user access through a user account, each user account configurable by an associated user to provide a plurality of user work environments, and the plurality of user work environments comprising at least a first user work environment and a second user work environment, each user work environment providing trove storage associated with user activity while the user work environment is selected as the user's current user work environment, the computer system providing a user interface that permits interaction with the second user work environment, generated by a user, that includes at least one associated workspace, the system comprising: data storage, operatively coupled to a processor, for storing trove data, the trove data associated with an application executing while the user has selected the second user work environment as the current user work environment; the processor configured to execute instructions that cause the processor to: provide to the user of a first user account, the first user work environment, initially selected as a current user work environment corresponding to the first user account, wherein the first user work environment associates a first user work environment current workspace to the user as a user interface; respond to user selection of the second user work environment, different from the first user work environment, by, designating the second user work environment as the current user work environment provided to the user; associating a second user work environment current workspace with the second user work environment; and allocating a trove per application used by the user while the second user work environment is selected as the current user work environment.

2. The computer system of claim 1 wherein the instructions that cause the processor to respond to user selection of the second user work environment, comprise instructions that cause the processor to create the second user work environment in response to the user designating for use as a user work environment folder for the second user work environment, a folder in a file system that is stored at least in part in the data storage.

3. The computer system of claim 1 wherein the processor is further configured to execute instructions that cause the processor to: respond to subsequent user re-selection of the second user work environment or the first user work environment as a selected user work environment by designating the selected user work environment as the current user work environment provided to the user; retrieving one or more portions of the selected user work environment from trove storage allocated for the selected user work environment; and providing to the user, in response to one or more user inputs, a workspace corresponding to the selected user work environment as the user interface.

4. The computer system of claim 1 further comprising instructions that cause the processor to

respond to closing by the user of the first user work environment by ensuring that the trove data corresponding to the first user work environment has been persistently stored.

5. The computer system of claim 1 wherein the second user work environment may comprise one or more workspaces, one of the workspaces being a current workspace, and wherein the processor is further configured to respond to user selection of a second workspace for the second user work environment, by designating the second workspace as the current workspace for the second user work environment.

6. The computer system of claim 1 wherein the processor is configured to execute instructions that cause the processor to: associate the second user work environment as a sub-user work environment of the first user work environment in a hierarchy; associate a third user work environment as a sub-user work environment of the first user work environment in the hierarchy; and associate additional user work environments as sub-user work environments in the hierarchy.

7. The computer system of claim 6 wherein the processor is configured to execute instructions that cause the processor to: associate a third user work environment as a sub-user work environment of the second user work environment in a hierarchy; wherein the hierarchy may have multiple levels.

8. The computer system of claim 6 wherein the first user work environment is a home user work environment, having associated therewith a home user work environment preferences data structure comprising a plurality of home user work environment user preferences regarding applications executed by the computer system and wherein the processor is further configured to execute instructions that cause the processor, when the home user work environment is the current user work environment, to: reference the home user work environment user preferences as inherited default preferences for the second user work environment; accept a user modification of an inherited default preference; create a second user work environment data structure; and store the user modification of the inherited default preference to the second user work environment data structure thereby overriding the inherited default preference.

9. The computer system of claim 6 wherein the second user work environment has associated therewith a second user work environment preferences data structure comprising a plurality of second user work environment user preferences regarding applications executed by the computer system and wherein the processor is further configured to execute instructions that cause the processor, when the third user work environment is the current user work environment, to: reference the second user work environment user preferences as inherited default preferences for the third user work environment; accept a user modification of an inherited default preference; create a third user work environment data structure; and store the user modification of the inherited default preference to the third user work environment data structure thereby overriding the inherited default preference.

10. The computer system of claim 1 wherein a second computer system maintains a data collection corresponding to the first user work environment, and wherein the processor is further configured to execute instructions that cause the processor to: receive from the second computer system, data from the data collection; and associate the data from the data collection received from the second computer system with the first user work environment.

11. The computer system of claim 1 wherein the first user work environment is a home user work environment, having an associated trove corresponding to the home user work environment, and wherein, the data storage includes a default preferences data structure comprising a plurality of default user preferences, and wherein the trove storage corresponding to the home user work environment includes a user override preferences data structure comprising a plurality of user override preferences that differ from corresponding default user preferences; and wherein the processor is further configured to execute instructions that cause the processor, when the home user work environment is the current user work environment provided to the user, to: accept a first user input to accept a user override preference to replace a default preference; store the user override preference to the user override preferences data structure; respond to user input to reveal the

overridden user preference corresponding to the user override preference; and accept a second user input to discard the user override preference by removing the user override preference from the user override preferences data structure.

12. The computer system of claim 11 wherein the processor is further configured to execute instructions that cause the processor to: respond to user input to reveal default user preferences that correspond to any user override preferences and accept one or more user inputs to discard any user override preferences by removing the user override preferences from the user override preferences data structure.

13. The computer system of claim 12 wherein the instruction that causes the processor to respond to user input to reveal default user preferences that correspond to any user override preferences and accept one or more user inputs to discard any user override preferences by removing the user override preferences from the user override preferences data structure also highlights the default user preferences.

14. The computer system of claim 11 wherein the instruction that causes the processor to respond to user input to reveal the default user preference corresponding to the user override preference also highlights the default user preference.

15. The computer system of claim 1 wherein the processor is further configured to execute instructions that cause the processor to: retrieve from a trove associated with the current user work environment, an identity to be used in accessing services requiring an identity.

16. The computer system of claim 1 wherein the processor is further configured to execute instructions that cause the processor to: respond to an external event to offer to the user an option to provide user input to switch to a different user work environment from the current user work environment in order to respond to the external event from the different user work environment.

17. The computer system of claim 1 wherein the processor is further configured to execute instructions that cause the processor to: respond to user input by encrypting data associated with the first user work environment to create encrypted first user work environment data for storage to the data storage; respond to user input by decrypting the encrypted first user work environment data to create a temporary unencrypted data set for use while the first user work environment is open.

18. The computer system of claim 17 wherein the processor is configured to execute instructions that cause the processor to, while the first user work environment is open: create a protected processing environment; and provide access to the temporary unencrypted data set for use only within the protected processing environment.

19. A method, implemented by a computer system, of facilitating interaction with a user of the computer system, wherein the computer system has executing thereupon an operating system that provides user access through a user account, each user account configurable by an associated user to provide a plurality of user work environments, the plurality of user work environments comprising at least a first user work environment and a second user work environment, each user work environment providing trove storage associated with user activity while the user work environment is selected as the user's current user work environment, the computer system providing a user interface that permits interaction with a second user work environment, generated by a user, that includes at least one associated workspace, the method comprising: providing to the user of a first user account, a first user work environment, initially selected as a current user work environment corresponding to the first user account, wherein the first user work environment associates a first user work environment current workspace to the user as a user interface; responding to user selection of the second user work environment, different from the first user work environment, by, designating the second user work environment as the current user work environment provided to the user; associating a second user work environment current workspace with the second user work environment; and allocating a trove per application used by the user while the second user work environment is selected as the current user work environment, wherein

each trove is associated with an application executing while the user has selected the second user work environment as the current user work environment.

20. A computer program product for facilitating interaction with a user of a computer system, the computer program product stored on a non-transitory computer readable storage medium and including instructions for causing the computer system to execute a method for facilitating interaction with a user of the computer system, wherein the computer system has executing thereupon an operating system that provides user access through a user account, each user account configurable by an associated user to provide a plurality of user work environments, the plurality of user work environments comprising at least a first user work environment and a second user work environment, each user work environment providing trove storage associated with user activity while the user work environment is selected as the user's current user work environment, the computer system providing a user interface that permits interaction with a second user work environment, generated by a user, that includes at least one associated workspace, the method comprising the actions of: providing to the user of a first user account, a first user work environment, initially selected as a current user work environment corresponding to the first user account, wherein the first user work environment associates a first user work environment current workspace to the user as a user interface; responding to user selection of the second user work environment, different from the first user work environment, by, designating the second user work environment as the current user work environment provided to the user; associating a second user work environment current workspace with the second user work environment; and allocating a trove used by the user while the second user work environment is selected as the current user work environment, wherein the trove is associated with an application executing while the user has selected the second user work environment as the current user work environment.
