

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12389761
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Lim; SangHyun et al.

Display device

Abstract

Discussed is a display device including an organic light emitting device in a display area on a substrate, a thin film transistor connected with the organic light emitting device, a planarization layer on the thin film transistor, a protecting portion on a buffer area on the substrate, the protecting portion surrounding at least a portion of a camera area on the substrate, the buffer area disposed between the display area and the camera area, a dam structure on the buffer area, the dam structure apart from the protecting portion, an encapsulation layer including a first encapsulation layer, a second encapsulation layer on the first encapsulation layer, and a third encapsulation layer on the second encapsulation layer, and a hole in the camera area, the hole provided inside the display area. The first encapsulation layer and the third encapsulation layer are disposed on a side surface of the planarization layer.

Inventors: Lim; SangHyun (Paju-si, KR), Kang; MinJi (Paju-si, KR), Na; SeHwan (Paju-si, KR)

Applicant: LG Display Co., Ltd. (Seoul, KR)

Family ID: 68917552

Assignee: LG DISPLAY CO., LTD. (Seoul, KR)

Appl. No.: 18/626111

Filed: April 03, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240251589 A1	Jul. 25, 2024

Foreign Application Priority Data

KR	10-2018-0170527	Dec. 27, 2018
----	-----------------	---------------

Related U.S. Application Data

continuation parent-doc US 18138530 20230424 US 11980051 child-doc US 18626111
continuation parent-doc US 17710426 20220331 US 11672142 20230606 child-doc US 18138530
continuation parent-doc US 16716817 20191217 US 11329255 20220510 child-doc US 17710426

Publication Classification

Int. Cl.: **H10K50/844** (20230101); **H04N23/54** (20230101); **H10K59/00** (20230101);
H10K59/122 (20230101); **H10K59/124** (20230101); **H10K59/131** (20230101);
H10K59/65 (20230101); **H10K59/80** (20230101); **H10K77/10** (20230101)

U.S. Cl.:

CPC **H10K59/124** (20230201); **H04N23/54** (20230101); **H10K50/844** (20230201);
H10K59/00 (20230201); **H10K59/122** (20230201); **H10K59/131** (20230201);
H10K77/10 (20230201); H10K59/65 (20230201); H10K59/8731 (20230201)

Field of Classification Search

CPC: H10K (59/13); H10K (59/60-771); H10K (59/87-8731); H04M (1/0264); H04N (5/2253)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
9632487	12/2016	Kim et al.	N/A	N/A
11355728	12/2021	Kim	N/A	H10K 50/844
11672142	12/2022	Lim et al.	N/A	N/A
2012/0013900	12/2011	Lee et al.	N/A	N/A
2014/0097430	12/2013	Park et al.	N/A	N/A
2014/0098005	12/2013	Kim et al.	N/A	N/A
2015/0041772	12/2014	Han	N/A	N/A
2017/0031323	12/2016	Kim	N/A	H10K 59/124
2017/0148856	12/2016	Choi et al.	N/A	N/A
2017/0288004	12/2016	Kim et al.	N/A	N/A
2018/0151834	12/2017	Kanaya	N/A	N/A
2018/0183015	12/2017	Yun et al.	N/A	N/A
2018/0254431	12/2017	Kim	N/A	N/A
2019/0148672	12/2018	Seo et al.	N/A	N/A
2020/0006700	12/2019	Kim et al.	N/A	N/A
2020/0238267	12/2019	Baniecki et al.	N/A	N/A
2020/0273927	12/2019	Oh et al.	N/A	N/A
2020/0343481	12/2019	Lee et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
106158881	12/2015	CN	N/A
107275335	12/2016	CN	N/A

107275363	12/2016	CN	N/A
107919293	12/2017	CN	N/A
108039418	12/2017	CN	N/A
108172593	12/2017	CN	N/A
108666347	12/2017	CN	N/A
109994657	12/2018	CN	N/A
110224077	12/2018	CN	N/A
110429118	12/2018	CN	N/A
3486962	12/2018	EP	N/A
3588574	12/2019	EP	N/A
3 633 751	12/2019	EP	N/A
2019-91039	12/2018	JP	N/A
10-2017-0080311	12/2016	KR	N/A
10-2020-0003328	12/2019	KR	N/A
10-2020-0113957	12/2019	KR	N/A

Primary Examiner: Santiago; Mariceli

Attorney, Agent or Firm: Birch, Stewart, Kolasch & Birch, LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a Continuation of U.S. patent application Ser. No. 18/138,530, filed on Apr. 24, 2023, which is a Continuation of U.S. patent application Ser. No. 17/710,426, filed on Mar. 31, 2022 (now U.S. Pat. No. 11,672,142, issued on Jun. 6, 2023), which is a Continuation of U.S. patent application Ser. No. 16/716,817, filed on Dec. 17, 2019 (now U.S. Pat. No. 11,329,255, issued on May 10, 2022), which claims the priority benefit of Korean Patent Application No. 10-2018-0170527 filed on Dec. 27, 2018, the entire contents of all these applications being hereby expressly incorporated by reference into the present application.

BACKGROUND

Field

(1) The present disclosure relates to a display device, and more particularly, to a display device with a camera provided therein.

Discussion of the Related Art

(2) A display apparatus includes various display devices such as a liquid crystal display device or an organic light emitting device in a display area. In these display devices, a method for applying various applications by the use of camera provided inside the display device and configured to interwork with the display area has been studied.

(3) In order to provide the camera inside the display device, a camera hole for placing the camera in the display device has to be provided. Generally, the camera hole is obtained by a process of removing some areas from the display device through a laser-beam irradiation.

(4) However, damages such as cracks may be generated in the process of removing some areas from the display device through the laser-beam irradiation. Furthermore, the cracks may extend to the display area so that it may cause problems such as degradation of picture quality and deterioration of the display device.

SUMMARY OF THE DISCLOSURE

(5) The present disclosure has been made in view of the above problems and limitations associated

with the related art, and it is an object of the present disclosure to provide a display device which is capable of preventing damages such as cracks, which might be generated when a camera hole is formed, from extending to a display area.

(6) In accordance with an aspect of the present disclosure, the above and other objects can be accomplished by the provision of a display device comprising a hole area on a substrate, a buffer area configured to surround the hole area, and a display area configured to surround the buffer area, wherein the display area includes a thin film transistor including a gate electrode, a source electrode, and a drain electrode on the substrate, the buffer area is provided with a damage preventing portion configured to control damages generated in a process of forming the hole area from extending to the display area, and the damage preventing portion is formed of a same material as a material of the source and drain electrodes.

(7) In accordance with another aspect of the present disclosure, there is provided a display device comprising a substrate, and a circuit device layer on the substrate, wherein the display device includes a hole area configured to penetrate through the substrate and the circuit device layer, and a buffer area configured to surround the hole area, a damage preventing portion is provided in the buffer area, and one lateral surface of the damage preventing portion confronting the hole area is formed in a groove structure toward a direction being farther away from the camera area.

(8) According to one embodiment of the present disclosure, the buffer area is provided to surround the hole area, and the damage preventing portion is provided in the buffer area so that it is possible to prevent damages, which might be generated when the hole area is formed, from extending to the display area. Especially, according to one embodiment of the present disclosure, the damage preventing portion is formed of the same material as that of the source and drain electrodes in the display area, and is manufactured by the same patterning process as that of the source and drain electrodes in the display area, whereby it is unnecessary to carry out an additional process for forming the damage preventing portion, thereby realizing simplified manufacturing process and minimizing the increase of manufacturing cost.

(9) Also, according to one embodiment of the present disclosure, the camera area and the buffer area are surrounded by the display area, whereby the size of the display area can be increased in comparison to the case where the camera area and the buffer area are surrounded by the non-display area positioned in the periphery of the display area.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The above and other objects, features and other advantages of the present disclosure will be more clearly understood from the following detailed description taken in conjunction with the accompanying drawings, in which:
- (2) FIG. 1 is a rough plane view illustrating a display device according to one embodiment of the present disclosure;
- (3) FIG. 2 is a rough cross-sectional view illustrating the display device according to one embodiment of the present disclosure, which corresponds to a cross section along line A-B of FIG. 1;
- (4) FIG. 3 is a rough cross-sectional view illustrating a buffer area and a camera area in the display device according to one embodiment of the present disclosure;
- (5) FIG. 4 is a rough cross-sectional view illustrating a buffer area and a camera area in a display device according to another embodiment of the present disclosure;
- (6) FIG. 5 is a rough cross-sectional view illustrating a display device according to another embodiment of the present disclosure, wherein a camera hole is formed by applying a laser cutting process to the display device of FIG. 2, and a camera is placed in the camera hole;

- (7) FIG. 6 is a rough cross-sectional view illustrating a buffer area and a camera area in a display device according to another embodiment of the present disclosure;
- (8) FIG. 7 is a rough cross-sectional view illustrating a buffer area and a camera area in a display device according to another embodiment of the present disclosure;
- (9) FIG. 8 is a rough cross-sectional view illustrating a buffer area and a camera area in a display device according to another embodiment of the present disclosure;
- (10) FIG. 9 is a rough cross-sectional view illustrating a buffer area and a camera area in a display device according to another embodiment of the present disclosure;
- (11) FIG. 10 is a rough cross-sectional view illustrating a display device according to another embodiment of the present disclosure;
- (12) FIGS. 11 to 13 are rough plane views illustrating display devices according to various embodiments of the present disclosure; and
- (13) FIGS. 14 and 15 are rough plane views illustrating display devices according to various embodiments of the present disclosure.

DETAILED DESCRIPTION OF THE DISCLOSURE

(14) Advantages and features of the present disclosure, and implementation methods thereof will be clarified through following embodiments described with reference to the accompanying drawings. The present disclosure may, however, be embodied in different forms and should not be construed as limited to the embodiments set forth herein. Rather, these embodiments are provided so that this disclosure will be thorough and complete, and will fully convey the scope of the present disclosure to those skilled in the art. Further, the present disclosure is only defined by scopes of claims.

(15) A shape, a size, a ratio, an angle, and a number disclosed in the drawings for describing embodiments of the present disclosure are merely an example, and thus, the present disclosure is not limited to the illustrated details. Like reference numerals refer to like elements throughout the specification. In the following description, when the detailed description of the relevant known function or configuration is determined to unnecessarily obscure the important point of the present disclosure, the detailed description will be omitted.

(16) In a case where ‘comprise’, ‘have’, and ‘include’ described in the present specification are used, another part can be added unless ‘only-’ is used. The terms of a singular form can include plural forms unless referred to the contrary.

(17) In construing an element, the element is construed as including an error range although there is no explicit description.

(18) In describing a position relationship, for example, when the position relationship is described as ‘upon-’, ‘above-’, ‘below-’, and ‘next to-’, one or more portions can be arranged between two other portions unless ‘just’ or ‘direct’ is used.

(19) In describing a time relationship, for example, when the temporal order is described as ‘after-’, ‘subsequent-’, ‘next-’, and ‘before-’, a case which is not continuous can be included unless ‘just’ or ‘direct’ is used.

(20) It will be understood that, although the terms “first”, “second”, etc. can be used herein to describe various elements, these elements should not be limited by these terms. These terms are only used to distinguish one element from another. For example, a first element could be termed a second element, and, similarly, a second element could be termed a first element, without departing from the scope of the present disclosure.

(21) It should be understood that the term “at least one” includes all combinations related with any one item. For example, “at least one among a first element, a second element and a third element” can include all combinations of two or more elements selected from the first, second and third elements as well as each element of the first, second and third elements.

(22) Features of various embodiments of the present disclosure can be partially or overall coupled to or combined with each other, and can be variously inter-operated with each other and driven technically as those skilled in the art can sufficiently understand. The embodiments of the present

disclosure can be carried out independently from each other, or can be carried out together in co-dependent relationship.

(23) Hereinafter, the preferred embodiments of the present disclosure will be described in detail with reference to the accompanying drawings.

(24) FIG. 1 is a rough plane view illustrating a display device according to one embodiment of the present disclosure. All the components of the display device according to all embodiments of the present disclosure are operatively coupled and configured. Further, the display device in all embodiments of the present disclosure can be any one of various displays used in a wide range of applications, such as smart phones, TVs, navigation devices, computers, security devices, remote devices, augmented reality devices, artificial intelligent-based devices, etc.

(25) As shown in FIG. 1, the display device according to one embodiment of the present disclosure includes a display area (DA), a non-display area (NDA), a hole area (CA), and a buffer area (BA).

(26) The display area (DA) is provided in a central portion of the display device, and an image is displayed on the display area (DA). In the display area (DA), various display devices which are generally known to those in the art, for example, an organic light emitting device or a liquid crystal display device can be provided therein. This image display device includes a plurality of pixels, wherein the plurality of pixels include a plurality of signal lines and a plurality of thin film transistors.

(27) The non-display area (NDA) is provided in the periphery of the display area (DA). In the non-display area (NDA), there are a driver configured to supply various signals to the plurality of signal lines in the display area (DA), and a link portion configured to connect the driver with the plurality of signal lines. The driver includes a gate driver configured to supply a gate signal to a gate line, and a data driver configured to supply a data signal to a data line.

(28) The hole area (CA) is provided inside the display area (DA). The hole area (CA) corresponds to the area where a camera is to be positioned, and an image is not displayed on the hole area (CA). The hole area (CA) can be formed in a circular shape.

(29) The buffer area (BA) is provided between the hole area (CA) and the display area (DA). Especially, the buffer area (BA) is provided to surround the peripheral area of the hole area (CA) so that the buffer area (BA) can be formed in a shape corresponding to a shape of the hole area (CA). For example, the hole area (CA) is formed in a circle shape, the buffer area (BA) can be formed in a circular doughnut or tube shape.

(30) As the buffer area (BA) separates the hole area (CA) and the display area (DA) from each other, it is possible to prevent the hole area (CA) from being influenced by the display area (DA), and also to prevent the display area (DA) from being influenced by the hole area (CA). In detail, the buffer area (BA) prevents an organic encapsulation layer formed in the display area (DA) from being permeated into the hole area (CA), and also prevents damages such as cracks which might be generated during a process of forming the hole area (CA) from being transferred to the display area (DA).

(31) On the plane view, the hole area (CA) and the buffer area (BA) can be positioned in the center with respect to a first axis (for example, X-axis) of the display area (DA), or can be positioned between the center and one end (for example, upper end or lower end) with respect to a second axis (for example, Y-axis) of the display area, wherein the second axis is perpendicular to the first axis, especially, can be positioned adjacent to one end, but not necessarily.

(32) The buffer area (BA) and the hole area (CA) can be provided inside the display area (DA) while being apart from the non-display area (NDA). That is, the buffer area (BA) is surrounded by the display area (DA), and the hole area (CA) is surrounded by the display area (DA) while the buffer area (BA) is interposed in-between.

(33) When the hole area (CA) and the buffer area (BA) are provided in the non-display area (NDA), a size of the non-display area (NDA) is increased in the Y-axis direction, whereby a size of the display area (DA) is decreased by the increased size of the non-display area (NDA).

(34) Meanwhile, according to one embodiment of the present disclosure, the hole area (CA) and the buffer area (BA) are surrounded by the display area (DA) so that a size of the display area (DA) is not decreased in the Y-axis direction.

(35) In this disclosure, the hole area (CA) corresponds to the area where a hole for a camera to be placed therein is formed. Hereinafter, it will be explained on assumption that the hole area (CA) is a camera area (CA) where a camera is placed therein. In all embodiments, one or more cameras or camera components can be provided in the CA.

(36) Hereinafter, the display device according to one embodiment of the present disclosure will be described in detail with reference to the cross-sectional structure.

(37) FIG. 2 is a rough cross-sectional view illustrating a display device according to one embodiment of the present disclosure, which corresponds to the cross-sectional view along line A-B of FIG. 1. FIG. 2 illustrates the display device including an organic light emitting device. Also, FIG. 2 shows the state before a camera hole is formed by a laser cutting process.

(38) As shown in FIG. 2, the display device according to one embodiment of the present disclosure includes a display area (DA), a buffer area (BA), and a camera area (CA).

(39) First, the display area (DA) will be described. On the display area (DA) of a substrate **100**, there are a circuit device layer **200**, a first electrode **300**, a bank **400**, an emission layer **500**, a second electrode **600**, and encapsulation layers **710**, **720** and **730**.

(40) The substrate **100** can be formed of transparent glass or plastic, but is not limited to these materials. If the display device according to one embodiment of the present disclosure includes a top emission type organic light emitting device, the substrate **100** can be formed of an opaque material.

(41) The circuit device layer **200** is provided on the substrate **100**. In the circuit device layer **200**, a circuit device including various signal lines, a thin film transistor, and a capacitor is provided for each pixel. The plurality of signal lines can include a gate line, a data line, a power line, and a reference line. The plurality of thin film transistors can include a switching thin film transistor, a driving thin film transistor, and a sensing thin film transistor. In FIG. 2, only the driving thin film transistor is shown in the circuit device layer **200**.

(42) The circuit device layer **200** includes an active layer **210**, a gate insulating layer **220**, a gate electrode **230**, an insulating interlayer **240**, a source electrode **251**, a drain electrode **252**, a passivation layer **260**, and a planarization layer **270**.

(43) The active layer **210** is patterned on the substrate **100**. The gate insulating layer **220** is formed between the active layer **210** and the gate electrode **230**. The gate electrode **230** is overlapped with the active layer **210** while being formed on the gate insulating layer **220**. The insulating interlayer **240** is provided between the gate electrode **230** and the source electrode **251**, and also provided between the gate electrode **230** and the drain electrode **252**. The source electrode **251** and the drain electrode **252** confront each other on the insulating interlayer **240**. Also, the source electrode **251** and the drain electrode **252** are respectively connected with the active layer **210** through a contact hole provided in the insulating interlayer **240** and the gate insulating layer **220**. The passivation layer **260** is formed on the source electrode **251** and the drain electrode **252**, and the planarization layer **270** is formed on the passivation layer **260**. Each of the gate insulating layer **220**, the insulating interlayer **240**, and the passivation layer **260** is formed of an inorganic insulating layer having a relatively small thickness, and the planarization layer **270** is formed of an organic insulating layer having a relatively large thickness. This structure of the driving thin film transistor can be changed in various types generally known to those in the art.

(44) The first electrode **300** is patterned for each pixel while being provided on the circuit device layer **200**. The first electrode **300** can function as an anode electrode of the organic light emitting device. The first electrode **300** is connected with the source electrode **251** of the driving thin film transistor through a contact hole provided in the passivation layer **260** and the planarization layer **270**. If needed, the first electrode **300** can be connected with the drain electrode **252** of the driving

thin film transistor through a contact hole provided in the passivation layer **260** and the planarization layer **270**.

(45) The bank **400** is formed in the boundaries between each of the pixels while being provided on the circuit device layer **200** and being configured to cover the edges of the first electrode **300**. An exposed portion of the first electrode **300**, which is exposed without being covered by the bank **400**, forms an emission area.

(46) The emission layer **500** is formed on the first electrode **300**. The emission layer **500** can be provided to emit white light. To this end, the emission layer **500** can comprise a plurality of stacks for emitting different-colored light. For example, the emission layer **500** can include a first stack for emitting blue colored light, a second stack for emitting yellow-green colored light, and a charge generation layer provided between the first stack and the second stack. The emission layers **500** for emitting white light can be connected with each other in the plurality of pixels. Meanwhile, the emission layer **500** can include a blue emission layer, a green emission layer, and a red emission layer which are patterned while being separated from each other in the plurality of pixels.

(47) The second electrode **600** is provided on the emission layer **500**. The second electrode **600** can function as a cathode of the organic light emitting device. The second electrodes **600** can be connected with each other in the plurality of pixels.

(48) The encapsulation layer **710**, **720** and **730** is provided on the second electrode **600**. The encapsulation layer **710**, **720** and **730** can include the first encapsulation layer **710**, the second encapsulation layer **720**, and the third encapsulation layer **730**. The first encapsulation layer **710** is provided on the second electrode **600**, the second encapsulation layer **720** is provided on the first encapsulation layer **710**, and the third encapsulation layer **730** is provided on the second encapsulation layer **720**. The first encapsulation layer **710** and the third encapsulation layer **730** are formed of inorganic insulating layers, and prevent external moisture from being permeated into the emission layer **500**. The second encapsulation layer **720** is formed of an organic insulating layer, and absorbs externally-permeated moisture so as to prevent moisture permeation into the emission layer **500**. Also, the second encapsulation layer **720** covers an external particle and also absorbs an external shock.

(49) The buffer area (BA) will be described as follows. On the buffer area (BA) of the substrate **100**, there are the gate insulating layer **220**, the insulating interlayer **240**, the passivation layer **260**, the planarization layer **270**, a dam structure **450**, the second electrode **600**, the encapsulation layer **710**, **720** and **730**, and a damage preventing portion **800**.

(50) In the buffer area (BA), inorganic insulating layers or organic insulating layers such as the gate insulating layer **220**, the insulating interlayer **240**, the passivation layer **260**, and the planarization layer **270** constituting the circuit device layer **200** can be formed, and the aforementioned thin film transistor is not formed. And, other circuit devices may not be provided in the buffer area (BA).

(51) The gate insulating layer **220** and the insulating interlayer **240** can be provided in the entire buffer area (BA). However, the passivation layer **260** and the planarization layer **270** can be provided in only some areas of the buffer area (BA), but may not be provided in the remaining areas of the buffer area (BA). Accordingly, a first upper surface **240a** of the insulating interlayer **240** in the buffer area (BA) is covered by the passivation layer **260** and the planarization layer **270**, and a second upper surface **240b** of the insulating interlayer **240** in the buffer area (BA) is exposed without being covered by the passivation layer **260** and the planarization layer **270**.

(52) The dam structure **450** is provided on the planarization layer **270**. For example, the dam structure **450** is overlapped with the first upper surface **240a** of the insulating interlayer **240**. The dam structure **450** prevents the second encapsulation layer **720** of the organic material from flowing into the camera area (CA). The second encapsulation layer **720** of a liquid type can be coated onto the first encapsulation layer **710**. In this case, if the second encapsulation layer **720** of the liquid type flows to the camera area (CA), a laser cutting process to be performed later in the camera area (CA) might be difficult.

(53) Thus, according to one embodiment of the present disclosure, the dam structure **450** is formed in the buffer area (BA) so that it is possible to prevent the second encapsulation layer **720** from flowing into the camera area (CA). Eventually, since the second encapsulation layer **720** is not provided in the corresponding areas from the area overlapped with the dam structure **450** to the area overlapped with the damage preventing portion **800**, a lower surface of the third encapsulation layer **730** is brought into contact with an upper surface of the first encapsulation layer **710** in the corresponding areas where the second encapsulation layer **720** is not provided.

(54) The dam structure **450** can include a first dam structure **451** and a second dam structure **452**. The first dam structure **451** and the bank **400** can be formed of the same material, and can be patterned at the same height. The second dam structure **452** is provided on the first dam structure **451** so that it is possible to increase an entire height of the dam structure **450**. A width in a lower surface of the second dam structure **452** can be smaller than a width in an upper surface of the first dam structure **451**, but is not limited to this structure.

(55) The second electrode **600** can be formed in the entire buffer area (BA). In detail, the second electrode **600** can extend from the area above the upper surface of the planarization layer **270** to the area above the second upper surface **240b** of the insulating interlayer **240** and the upper surface of the damage preventing portion **800** along the upper surface of the dam structure **450** and the lateral surface of the planarization layer **270**.

(56) Among the encapsulation layers **710**, **720** and **730**, the second encapsulation layer **720** is blocked by the dam structure **450**, whereby the second encapsulation layer **720** can extend only to the front of the dam structure **450**, and more particularly, to the front of the dam structure **450** corresponding to an opposite area of the camera area (CA). Meanwhile, the first encapsulation layer **710** and the third encapsulation layers **730** can be provided in the entire buffer area (BA). Accordingly, the first encapsulation layer **710** extends along the upper surface of the second electrode **600** on the upper surface of the second electrode **600**, and the third encapsulation layer **730** extends along the upper surface of the first encapsulation layer **710** on the upper surface of the first encapsulation layer **710**. Thus, each of the first encapsulation layer **710** and the third encapsulation layer **730** can be overlapped with the planarization layer **270**, the dam structure **450**, the second upper surface **240b** of the insulating interlayer **240**, and the damage preventing portion **800**.

(57) The damage preventing portion **800** is provided while being in contact with the second upper surface **240b** of the insulating interlayer **240**. Thus, the damage preventing portion **800** is not overlapped with the planarization layer **270** of the organic insulating layer having the large thickness.

(58) In the same manner as the above source electrode **251** and drain electrode **252** of the display area (DA), the damage preventing portion **800** is provided on the insulating interlayer **240**. Thus, the damage preventing portion **800** can be formed of the same material as that of the source electrode **251** and the drain electrode **252**, and can be patterned by the same process as that of the source electrode **251** and the drain electrode **252**. According to one embodiment of the present disclosure, the damage preventing portion **800** is formed of the same material as that of the source electrode **251** and the drain electrode **252**, and patterned by the same process as that of the source electrode **251** and the drain electrode **252**, whereby it is unnecessary to carry out an additional process for forming the damage preventing portion **800**, thereby realizing a simplified manufacturing process and minimizing the increase of manufacturing cost.

(59) The damage preventing portion **800** is formed to be in contact with the boundaries between the buffer area (BA) and the camera area (CA). Owing to the damage preventing portion **800**, it is possible to prevent damages such as cracks which might be generated in the camera area (CA) from extending to the display area (DA) through the buffer area (BA). In more detail, when the camera hole is formed in the camera area (CA) by the laser cutting process, damages such as cracks might be generated in at least one among the second electrode **600**, the first encapsulation layer **710**, and

the third encapsulation layer **730** formed in the camera area (CA) during the laser cutting process, and the damages such as cracks might extend to the display area (DA) through the buffer area (BA). If the cracks formed in the second electrode **600** extend to the display area (DA), the emission is not smoothly generated in the emission layer **500**. Furthermore, if the cracks formed in the first encapsulation layer **710** and the third encapsulation layer **730** extend to the display area (DA), external moisture can be permeated through the generated cracks, whereby it accelerates deterioration of the emission layer **500**. Thus, according to one embodiment of the present disclosure, the damage preventing portion **800** is formed in the buffer area (BA) so that it is possible to prevent the cracks, which might occur in the camera area (CA) during the laser cutting process, from extending to the display area (DA).

(60) The damage preventing portion **800** is configured to disconnect (or separate) the second electrode **600**, the first encapsulation layer **710**, and the third encapsulation layer **730** formed thereon in the buffer area (BA) from the second electrode **600**, the first encapsulation layer **710**, and the third encapsulation layer **730** formed thereon in the camera area (CA). For instance, the second electrode **600**, the first encapsulation layer **710**, and the third encapsulation layer **730** formed in the buffer area (BA) are disconnected from the second electrode **600**, the first encapsulation layer **710**, and the third encapsulation layer **730** formed in the camera area (CA) by the use of damage preventing portion **800**. Even though the damages such as cracks may occur in at least one among the second electrode **600**, the first encapsulation layer **710**, and the third encapsulation layer formed in the camera area (CA), the damages can hardly extend to the buffer area (BA).

(61) Hereinafter, a structure of the damage preventing portion **800** configured to disconnect the second electrode **600**, the first encapsulation layer **710**, and the third encapsulation layer **730** formed in the buffer area (BA) from the second electrode **600**, the first encapsulation layer **710**, and the third encapsulation layer **730** formed in the camera area (CA) according to various embodiments of the present disclosure will be described with reference to FIGS. **3** and **4**.

(62) The camera area (CA) will be described as follows. On the camera area (CA) of the substrate **100**, there are the gate insulating layer **220**, the insulating interlayer **240**, the second electrode **600**, the first encapsulation layer **710**, and the third encapsulation layer **730**.

(63) In the camera area (CA), the passivation layer **260** and the planarization layer **270** are not formed so that it facilitates to form the camera hole by the laser cutting process to be performed later. The gate insulating layer **220** and the insulating interlayer **240** formed in the camera area (CA) are respectively connected with the gate insulating layer **220** and the insulating interlayer **240** formed in the buffer area (BA) and the display area (DA). However, the second electrode **600**, the first encapsulation layer **710**, and the third encapsulation layer **730** formed in the camera area (CA) are not connected with the second electrode **600**, the first encapsulation layer **710**, and the third encapsulation layer **730** formed in the buffer area (BA) and the display area (DA).

(64) FIG. **3** is a rough cross-sectional view illustrating the buffer area (BA) and the camera area (CA) in the display device according to one embodiment of the present disclosure, which shows the cross-sectional structure of the damage preventing portion **800** according to one embodiment of the present disclosure. FIG. **3** shows the state before the camera hole is formed by the laser cutting process.

(65) As shown in FIG. **3**, according to one embodiment of the present disclosure, the damage preventing portion **800** can include a first layer **810**, a second layer **820**, and a third layer **830**. The second layer **820** is provided on the first layer **810**, and the third layer **830** is provided on the second layer **820**.

(66) The damage preventing portion **800** can be formed of the same material as that of the source electrode **251** and drain electrode **252** of the aforementioned display area (DA), and can be provided in the same layer as that of the source electrode **251** and drain electrode **252** of the aforementioned display area (DA), whereby each of the source electrode **251** and the drain

electrode **252** can have a three-layered structure in the same manner as the damage preventing portion **800**. If the damage preventing portion **800** is formed of the same material as that of the source electrode **251** and drain electrode **252**, the first layer **810**, the second layer **820**, and the third layer **830** can be formed of a conductive material. In this case, the first layer **810** and the third layer **830** respectively cover lower and upper surfaces of the second layer **820** so that it is possible to prevent corrosion of the second layer **820**. To this end, the first layer **810** and the third layer **830** can be formed of a material with relatively-low oxidation degree and relatively-high corrosion resistance in comparison to the second layer **820**. Also, the second layer **820** can be formed of a material with relatively-low resistance in comparison to the first layer **810** and the third layer **830**. In order to lower the total resistance in the three-layered structure, a thickness of the second layer **820** is relatively larger than a thickness of each of the first layer **810** and the third layer **830**.

(67) Owing to the damage preventing portion **800**, the second electrode **600**, the first encapsulation layer **710**, and the third encapsulation layer **730** provided in the buffer area (BA) are disconnected from the second electrode **600**, the first encapsulation layer **710**, and the third encapsulation layer **730** provided in the camera area (CA). In detail, the second electrode **600**, the first encapsulation layer **710**, and the third encapsulation layer **730** provided on the damage preventing portion **800** in the buffer area (BA) are disconnected from the second electrode **600**, the first encapsulation layer **710**, and the third encapsulation layer **730** provided on the damage preventing portion **800** in the camera area (CA).

(68) To this end, a first lateral surface **820a** of the second layer **820** confronting the camera area (CA) is provided in a groove structure toward an inner direction, and more particularly, toward the direction being gradually farther-away from the camera area (CA). Especially, the groove structure is provided with a curved-line structure having a predetermined inclination in the first lateral surface **820a** of the second layer **820**.

(69) If the first lateral surface **820a** of the second layer **820** is provided in the groove structure, the second electrode **600**, the first encapsulation layer **710**, and the third encapsulation layer **730** are not sequentially deposited on the groove structure of the first lateral surface **820a** of the second layer **820**, and can be provided in the disconnected structure.

(70) Meanwhile, a width (W) of the second layer **820**, and more particularly, a width (W) between the first lateral surface **820a** of the second layer **820** confronting the camera area (CA) and a second lateral surface **820b** opposite to the first lateral surface **820a** is gradually decreased as it goes from its upper portion to its central portion, and is then gradually increased as it goes from its central portion to its lower portion, whereby it is possible to realize a stable deposition structure in the first layer **810** and the third layer **830** respectively provided below and above the second layer **820**.

(71) FIG. **4** is a rough cross-sectional view illustrating a buffer area (BA) and a camera area (CA) in a display device according to another embodiment of the present disclosure, which shows a cross-sectional structure of a damage preventing portion **800** according to another embodiment of the present disclosure. FIG. **4** shows the state before a camera hole is formed by a laser cutting process.

(72) In case of the damage preventing portion **800** of FIG. **4**, both a first lateral surface **820a** and a second lateral surface **820b** in a second layer **820** are formed in groove structures. In this respect, the damage preventing portion of FIG. **4** is different from the damage preventing portion of FIG. **3**.

(73) Referring to FIG. **4**, the first lateral surface **820a** of the second layer **820** confronting a camera area (CA) is provided in the groove structure toward an inner direction, and more particularly, the direction being gradually farther-away from the camera area (CA). Also, the second lateral surface **820b** of the second layer **820**, which corresponds to the opposite lateral surface to the first lateral surface **820a**, is provided in the groove structure toward the inner direction, and more particularly, the direction being gradually close to the camera area (CA). Especially, the groove structure is provided with a curved-line structure having a predetermined inclination in both the first lateral

surface **820a** and the second lateral surface **820b** of the second layer **820**.

(74) Thus, according to another embodiment of the present disclosure, the second lateral surface **820b** of the second layer **820** is formed in the groove structure, whereby a second electrode **600**, a first encapsulation layer **710**, and a third encapsulation layer **730** provided on an upper surface of the damage preventing portion **800** are disconnected from a second electrode **600**, a first encapsulation layer **710**, and a third encapsulation layer **730** provided on some areas of the buffer area (BA) being not overlapped with the damage preventing portion **800**, and more particularly, provided on a second upper surface **240b** of an insulating interlayer **240** in the buffer area (BA). Thus, it is possible to prevent damages such as cracks, which might be generated in the camera area (CA), from extending to the display area (DA) via the buffer area (BA).

(75) Meanwhile, in the structures of FIG. 3 and FIG. 4, the damage preventing portion **800** can be formed in a single-layered structure having only the second layer **820** without the first layer **810** and the third layer **830**.

(76) FIG. 5 is a rough cross-sectional view illustrating a display device according to another embodiment of the present disclosure, wherein a camera hole is formed by applying a laser cutting process to the display device of FIG. 2, and a camera is placed in the camera hole. Accordingly, the same reference numbers will be used throughout the drawings to refer to the same or like parts, and only different structures will be described in detail.

(77) As shown in FIG. 5, a display area (DA) and a buffer area (BA) on a substrate **100** are the same as those of FIG. 2. However, a camera area (CA) on the substrate **100** is different from that of FIG. 2. In detail, the substrate **100**, a gate insulating layer **220**, an insulating interlayer **240**, a second electrode **600**, a first encapsulation layer **710**, and a third encapsulation layer **730** provided in the camera area (CA) are removed by a laser cutting process.

(78) Accordingly, the camera area (CA) is provided with a camera hole (CH) penetrating through the area from the substrate **100** to the third encapsulation layer **730**, and a camera **910** is placed in the camera hole (CH). Thus, the camera **910** is provided while being confronted with the substrate **100** on the same plane as that of the substrate **100** in the buffer area (BA).

(79) Also, a supporting portion **900** for supporting the camera **910** is provided below the substrate **100**. The supporting portion **900** can be provided in the entire areas of the display area (DA), the buffer area (BA), and the camera area (CA). The supporting portion **900** can function as an external case.

(80) FIG. 6 is a rough cross-sectional view illustrating a buffer area and a camera area in a display device according to another embodiment of the present disclosure, which shows one case where a camera hole (CH) is formed by applying a laser cutting process to the display device with the damage preventing portion **800** of FIG. 3, and a camera **910** is placed in the camera hole.

(81) FIG. 7 is a rough cross-sectional view illustrating a buffer area and a camera area in a display device according to another embodiment of the present disclosure, which shows another case where a camera hole (CH) is formed by applying a laser cutting process to the display device with the damage preventing portion **800** of FIG. 3, and a camera **910** is placed in the camera hole.

(82) In case of FIG. 6, in the above display device with the damage preventing portion **800** of FIG. 3, a camera hole (CH) is configured to penetrate through the entire areas including a substrate **100**, a gate insulating layer **220**, an insulating interlayer **240**, a second electrode **600**, a first encapsulation layer **710**, and a third encapsulation layer **730** in a camera area (CA).

(83) Thus, referring to FIG. 6, the camera hole (CH) is formed in the entire camera area (CA), a camera **910** is placed in the camera hole (CH), and a supporting portion **900** for supporting the camera **910** is provided below the substrate **100**. Accordingly, the damage preventing portion **800** provided in a buffer area (BA) is brought into contact with the camera hole (CH). Also, the camera **910** confronts the substrate **100** of the buffer area (BA).

(84) Meanwhile, referring to FIG. 7, in the display device with the damage preventing portion **800** of FIG. 3, a camera hole (CH) is configured to penetrate through some areas of a substrate **100**, a

gate insulating layer **220**, an insulating interlayer **240**, a second electrode **600**, a first encapsulation layer **710**, and a third encapsulation layer **730** provided in a camera area (CA).

(85) Thus, in case of FIG. 7, each of the substrate **100**, the gate insulating layer **220**, the insulating interlayer **240**, the second electrode **600**, the first encapsulation layer **710**, and the third encapsulation layer **730** provided in the buffer area (BA) extends to the camera area (CA). That is, the above substrate **100**, the gate insulating layer **220**, the insulating interlayer **240**, the second electrode **600**, the first encapsulation layer **710**, and the third encapsulation layer **730** extended to the camera area (CA) remain without being removed by a laser cutting process.

(86) Referring to FIG. 7, the camera hole (CH) is provided in some areas of the camera area (CA), a camera **910** is placed in the camera hole (CH), and a supporting portion **900** for supporting the camera **910** is provided below the substrate **100**. Accordingly, the damage preventing portion **800** provided in a buffer area (BA) is not in contact with the camera hole (CH), and the substrate **100**, the gate insulating layer **220**, the insulating interlayer **240**, the second electrode **600**, the first encapsulation layer **710**, and the third encapsulation layer **730** are provided between the damage preventing portion **800** and the camera hole (CH). Also, the camera **910** confronts the substrate **100** extended to the camera area (CA).

(87) As described above in FIG. 6, if a processing error is generated under the condition that the camera hole (CH) is formed in the entire camera area (CA), the camera hole (CH) can invade the buffer area (BA). Thus, in case of FIG. 7, the camera area (CA) is designed to be larger than the camera hole (CH) in consideration of processing margin so that it is possible to prevent the invasion of the camera hole (CH) to the buffer area (BA).

(88) FIG. 8 is a rough cross-sectional view illustrating a buffer area and a camera area in a display device according to another embodiment of the present disclosure, which shows one case where a camera hole (CH) is formed by applying a laser cutting process to the display device with the damage preventing portion **800** of FIG. 4, and a camera **910** is placed in the camera hole.

(89) FIG. 9 is a rough cross-sectional view illustrating a buffer area and a camera area in a display device according to another embodiment of the present disclosure, which shows another case where a camera hole (CH) is formed by applying a laser cutting process to the display device with the damage preventing portion **800** of FIG. 4, and a camera **910** is placed in the camera hole.

(90) In case of FIG. 8, in the above display device with the damage preventing portion **800** of FIG. 4, a camera hole (CH) is configured to penetrate through entire areas of a substrate **100**, a gate insulating layer **220**, an insulating interlayer **240**, a second electrode **600**, a first encapsulation layer **710**, and a third encapsulation layer **730** provided in a camera area (CA).

(91) Thus, referring to FIG. 8, the camera hole (CH) is formed in the entire camera area (CA), a camera **910** is placed in the camera hole (CH), and a supporting portion **900** for supporting the camera **910** is provided below the substrate **100**. Accordingly, the damage preventing portion **800** provided in a buffer area (BA) is brought into contact with the camera hole (CH). Also, the camera **910** confronts the substrate **100** of the buffer area (BA).

(92) Meanwhile, referring to FIG. 9, in the display device with the damage preventing portion **800** of FIG. 4, a camera hole (CH) is configured to penetrate through some areas of a substrate **100**, a gate insulating layer **220**, an insulating interlayer **240**, a second electrode **600**, a first encapsulation layer **710**, and a third encapsulation layer **730** provided in a camera area (CA).

(93) Thus, in case of FIG. 9, each of the substrate **100**, the gate insulating layer **220**, the insulating interlayer **240**, the second electrode **600**, the first encapsulation layer **710**, and the third encapsulation layer **730** provided in the buffer area (BA) extends to the camera area (CA). That is, the above substrate **100**, the gate insulating layer **220**, the insulating interlayer **240**, the second electrode **600**, the first encapsulation layer **710**, and the third encapsulation layer **730** extended to the camera area (CA) remain without being removed by a laser cutting process.

(94) Referring to FIG. 9, the camera hole (CH) is provided in some areas of the camera area (CA), a camera **910** is placed in the camera hole (CH), and a supporting portion **900** for supporting the

camera **910** is provided below the substrate **100**. Accordingly, the damage preventing portion **800** provided in a buffer area (BA) is not in contact with the camera hole (CH), and the substrate **100**, the gate insulating layer **220**, the insulating interlayer **240**, the second electrode **600**, the first encapsulation layer **710**, and the third encapsulation layer **730** are provided between the damage preventing portion **800** and the camera hole (CH). Also, the camera **910** confronts the substrate **100** extended to the camera area (CA).

(95) As described above in FIG. **8**, if a processing error is generated under the condition that the camera hole (CH) is formed in the entire camera area (CA), the camera hole (CH) can invade the buffer area (BA). Thus, in case of FIG. **9**, the camera area (CA) is designed to be larger than the camera hole (CH) in consideration of processing margin so that it is possible to prevent the invasion of the camera hole (CH) to the buffer area (BA).

(96) FIG. **10** is a rough cross-sectional view illustrating a display device according to another embodiment of the present disclosure. Except a position of a damage preventing portion **800**, the display device of FIG. **10** is identical in structure to the display device of FIG. **5**. Accordingly, the same reference numbers will be used throughout the drawings to refer to the same or like parts, and only different structures will be described in detail.

(97) Referring to above FIG. **5**, the damage preventing portion **800** is brought into contact with the second upper surface **240b** of the insulating interlayer **240**. Meanwhile, in case of FIG. **10**, the damage preventing portion **800** is brought into contact with a second upper surface **100b** of a substrate **100**.

(98) That is, referring to FIG. **10**, a gate insulating layer **220**, an insulating interlayer **240**, a passivation layer **260**, and a planarization layer **270** are provided in some areas of a buffer area (BA), and not provided in the remaining areas of the buffer area (BA). Thus, a first upper surface **100a** of the substrate **100** in the buffer area (BA) is covered by the gate insulating layer **220**, the insulating interlayer **240**, the passivation layer **260**, and the planarization layer **270**, however, the second upper surface **100b** of the substrate **100** in the buffer area (BA) is exposed without being covered by the gate insulating layer **220**, the insulating interlayer **240**, the passivation layer **260**, and the planarization layer **270**. Accordingly, the damage preventing portion **800** is formed on the second upper surface **100b** of the substrate **100**.

(99) In the structure of FIG. **10**, the gate insulating layer **220** and the insulating interlayer **240** are not provided in the camera area (CA) before a laser cutting process so that it is possible to smoothly perform the laser cutting process with easiness.

(100) The structures of the buffer area (BA) and the camera area (CA) shown in FIGS. **6** to **8** can be identically applied to the structure of FIG. **10**.

(101) FIGS. **11** to **13** are rough plane views illustrating display devices according to various embodiments of the present disclosure. A structure of a camera area (CA) and a buffer area (BA) on the plane shown in FIGS. **11** to **13** is different from that of FIG. **1**.

(102) Referring to above FIG. **1**, the camera area (CA) is formed in the circle shape, the buffer area (BA) is formed in the circular doughnut or tube shape to surround the camera area (CA).

(103) Meanwhile, in case of FIG. **11**, the camera area (CA) is formed in a rectangular shape, and the buffer area (BA) is formed in a rectangular doughnut or tube shape to surround the camera area (CA). Also, in case of FIG. **12**, the camera area (CA) is formed in an oval shape, and the buffer area (BA) is formed in an oval-type doughnut or tube shape to surround the camera area (CA). Also, in case of FIG. **13**, the camera area (CA) is formed in a triangular shape, and the buffer area (BA) is formed in a triangular doughnut or tube shape to surround the camera area (CA). The camera area (CA) is formed in a pentagonal or polygonal shape, and the buffer area (BA) is formed in a pentagonal or polygonal doughnut or tube shape to surround the camera area (CA).

(104) FIGS. **14** and **15** are rough plane views illustrating display devices according to various embodiments of the present disclosure. A position of a camera area (CA) and a buffer area (BA) on the plane shown in FIGS. **11** to **13** is different from that of FIG. **1**.

(105) In case of FIG. 14, the camera area (CA) and the buffer area (BA) are positioned between the center of the display area (DA) and the left end of the display area (DA) with respect to the X-axis of the display area (DA) on the plane, and more particularly, are positioned to be close to the left end of the display area (DA). In this respect, the position of the camera area (CA) and the buffer area (BA) shown in FIG. 14 is different from that of FIG. 1.

(106) In case of FIG. 15, the camera area (CA) and the buffer area (BA) are positioned between the center of the display area (DA) and the right end of the display area (DA) with respect to the X-axis of the display area (DA) on the plane, and more particularly, are positioned to be close to the right end of the display area (DA). In this respect, the position of the camera area (CA) and the buffer area (BA) shown in FIG. 15 is different from that of FIG. 1.

(107) In addition to the above cases of FIGS. 14 and 15, the position of the camera area (CA) and the buffer area (BA) can be changed in various methods while being surrounded by the display area (DA).

(108) Meanwhile, according as the camera area (CA) and the buffer area (BA) surrounding the camera area (CA) are prepared inside the display area (DA), the buffer area (BA) and the camera area (CA) are surrounded by the display area (DA), but are not limited to this structure. For example, the camera area (CA) and the buffer area (BA) surrounding the camera area (CA) can be prepared inside the non-display area (NDA), whereby the buffer area (BA) and the camera area (CA) can be surrounded by the non-display area (NDA).

(109) Even though the buffer area (BA) and the camera area (CA) are surrounded by the non-display area (NDA), the structure in each of the buffer area (BA) and the camera area (CA) can be the same as that of the aforementioned embodiments.

(110) In addition to the effects of the present disclosure as mentioned above, additional advantages and features of the present disclosure will be clearly understood by those skilled in the art from the above description of the present disclosure. It will be apparent to those skilled in the art that the present disclosure described above is not limited by the above-described embodiments and the accompanying drawings and that various substitutions, modifications, and variations can be made in the present disclosure without departing from the spirit or scope of the disclosures. Consequently, the scope of the present disclosure is defined by the accompanying claims, and it is intended that all variations or modifications derived from the meaning, scope, and equivalent concept of the claims fall within the scope of the present disclosure.

Claims

1. A display device comprising: an organic light emitting device in a display area on a substrate; a thin film transistor being connected with the organic light emitting device; a planarization layer on the thin film transistor; a protecting portion on a buffer area on the substrate, the protecting portion surrounding at least a portion of a camera area on the substrate, the buffer area being disposed between the display area and the camera area; a dam structure on the buffer area, the dam structure apart from the protecting portion; an encapsulation layer including a first encapsulation layer, a second encapsulation layer on the first encapsulation layer, and a third encapsulation layer on the second encapsulation layer; and a hole in the camera area, the hole provided inside the display area, wherein the first encapsulation layer and the third encapsulation layer are disposed on a side surface of the planarization layer, wherein the dam structure includes a first dam structure and a second dam structure on the first dam structure, and wherein the first dam structure is formed of a same material as that of a bank provided in the display area.
2. The display device according to claim 1, wherein the first dam structure is provided at a same height as that of the bank.
3. The display device according to claim 1, wherein the protection portion is overlapped with the first encapsulation layer and the third encapsulation layer.

4. The display device according to claim 1, wherein the protection portion is not overlapped with the planarization layer.
5. The display device according to claim 1, wherein the first encapsulation layer and the third encapsulation layer contact each other between the dam structure and the protecting portion.
6. The display device according to claim 1, further comprising an insulating layer under the planarization layer, wherein the first encapsulation layer contacts the insulating layer.
7. The display device according to claim 6, wherein the first encapsulation layer contacts the insulating layer between the dam structure and the protecting portion.
8. The display device according to claim 6, wherein the first encapsulation layer contacts the insulating layer between the planarization layer and the protecting portion.
9. The display device according to claim 8, wherein the first encapsulation layer further contacts a side of the planarization layer.
10. The display device according to claim 1, wherein the protecting portion includes a plurality of portions.
11. The display device according to claim 1, wherein a lower surface of the third encapsulation layer is brought into contact with an upper surface of the first encapsulation layer in an overlap area between the encapsulation layer and the dam structure.
12. The display device according to claim 1, wherein the hole is configured to penetrate through the substrate.
13. The display device according to claim 1, wherein the camera area is formed in a circular shape, an oval shape, or a polygonal shape in plan view.
14. A display device comprising: an organic light emitting device in a display area on a substrate; a thin film transistor being connected with the organic light emitting device; a planarization layer on the thin film transistor; a protecting portion on a buffer area on the substrate, the protecting portion surrounding at least a portion of a camera area on the substrate, the buffer area being disposed between the display area and the camera area; a dam structure on the buffer area, the dam structure apart from the protecting portion; an encapsulation layer including a first encapsulation layer, a second encapsulation layer on the first encapsulation layer, and a third encapsulation layer on the second encapsulation layer; and a hole in the camera area, the hole provided inside the display area, wherein the first encapsulation layer and the third encapsulation layer are disposed on a side surface of the planarization layer, and wherein a first lateral surface of the protecting portion confronting the camera area is formed in a groove structure toward a direction being farther away from the camera area.
15. The display device according to claim 14, wherein a second lateral surface of the protecting portion corresponding to an opposite lateral surface to the first lateral surface is formed in a groove structure toward a direction being closer to the camera area.
16. A display device comprising: an organic light emitting device in a display area on a substrate; a thin film transistor being connected with the organic light emitting device; a planarization layer on the thin film transistor; a protecting portion on a buffer area on the substrate, the protecting portion surrounding at least a portion of a camera area on the substrate, the buffer area being disposed between the display area and the camera area; a dam structure on the buffer area, the dam structure apart from the protecting portion; an encapsulation layer including a first encapsulation layer, a second encapsulation layer on the first encapsulation layer, and a third encapsulation layer on the second encapsulation layer; and a hole in the camera area, the hole provided inside the display area, wherein the first encapsulation layer and the third encapsulation layer are disposed on a side surface of the planarization layer, and wherein the buffer area includes an inorganic insulating layer on the substrate, an organic insulating layer on the inorganic insulating layer, an electrode on the organic insulating layer, and the encapsulation layer on the electrode.
17. The display device according to claim 16, wherein the electrode and the encapsulation layer are provided on the protecting portion.

18. The display device according to claim 16, wherein the protecting portion is not overlapped with the organic insulating layer.
